Locally private online change point detection

Abstract

We study online change point detection problems under the constraint of local differential privacy (LDP) where, in particular, the statistician does not have access to the raw data. As a concrete problem, we study a multivariate nonparametric regression problem. At each time point t, the raw data are assumed to be of the form (X_t, Y_t), where X_t is a d-dimensional feature vector and Y_t is a response variable. Our primary aim is to detect changes in the regression function $m_t(x) = \mathbb{E}(Y_t | X_t = x)$ as soon as the change occurs. We provide algorithms which respect the LDP constraint, which control the false alarm probability, and which detect changes with a minimal (minimax rate-optimal) delay. To quantify the cost of privacy, we also present the optimal rate in the benchmark, non-private setting. These non-private results are also new to the literature and thus are interesting *per se*. In addition, we study the univariate mean online change point detection problem, under privacy constraints. This serves as the blueprint of studying more complicated private change point detection problems.

1 Introduction

Online change point detection has been an active statistical research area for decades, originated from the demand of a reliable quality control mechanism under time and resources constraints [e.g. 30]. In recent years, due to the advance of technology, the applications of online change point detection are well beyond quality control and include climatology, speech recognition, imaging processing, among many others. While collecting the data as they are generated, one wishes to detect the underlying distributional changes as soon as the changes occur.

As the ability of collecting and storing data improves exponentially, protecting users' privacy has become one of the central concerns of data science. In practice, many of the systems that we monitor contain sensitive information. For instance, change point algorithms are used in cyber security to detect attacks, with the ultimate aim often being to protect private information [21, 27, 1]. Other common application areas include public health [19, 16] and finance [17], in which many of the data involved are highly personal. Given the prevalence of such problems, we address two questions in this paper:

- whether we can detect changes without the need for direct access to the sensitive raw data;

- and what the cost of protecting privacy is in terms of the detection delay and accuracy.

Traditional anonymisation of data has been shown to be an outdated method of privacy protection, particularly in multivariate settings [25, 23]. Even when direct identifiers such as names and locations are removed, data sets often contain enough information for researchers to identify individual subjects, and hence there is a need to quantify and control the release of privileged information. Formal privacy constraints provide us with a rigorous framework in which we may tackle such problems and explore the fundamental limits of private methods. Constraints of this type have been imposed in analyses

carried out by Apple [26], Google [15] and Microsoft [10], and provides organisations with a way of demonstrating the General Data Protection Regulation compliance [7].

The most popular privacy constraint is that of differential privacy [14], which assumes the existence of a third party who can be trusted to handle all of the raw data. In situations where this assumption cannot be made, which are the focus in our work, we strengthen this constraint and require our algorithms to satisfy local differential privacy [e.g. 18, 12], which, in particular, insists that the raw data are not accessed by anyone except its original holder. Solutions to a wide range of statistical problems have been given, and much underlying theory has been developed [e.g. 31, 12, 13, 24, 3].

In this paper, we are concerned with a multivariate nonparametric regression online change point detection problem, with privatised data. To be specific, we assume that the original data are $\{(X_i, Y_i)\}_{i \in \mathbb{N}^*} \subset \mathbb{R}^d \times \mathbb{R}$, where the regression functions

$$m_i(x) = \mathbb{E}(Y_i | X_i = x), \quad x \in \mathbb{R}^d, \quad i \in \mathbb{N}^*, \tag{1}$$

satisfy that $m_{i+1} \neq m_i$ if and only if $i = \Delta \in \mathbb{N}^*$. The goal is to find a stopping time $\widehat{t}$, which minimises the detection delay $(\widehat{t} - \Delta)_+$, while controlling the false alarm probability $\mathbb{P}(\widehat{t} < \Delta)$.

With the concern of maintaining privacy, we do not directly have access to the original data $\{(X_i, Y_i)\}_{i \in \mathbb{N}^*}$, but a privatised version. Specifically, the original data are transmitted through an α-locally differentially private (α-LDP) channel for some fixed $\alpha > 0$. The privatised data are denoted by $\{(W_i, Z_i)\}_{i \in \mathbb{N}^*} \subset \mathbb{R}^d \times \mathbb{R}$. In our upper bounds we restrict attention to non-interactive mechanisms [see, for example, 12], and so a privacy mechanism is given by a sequence $\{Q_i\}_{i \in \mathbb{N}^*}$ of conditional distributions, with the interpretation that

$$(W_i, Z_i) | (X_i, Y_i) = (x_i, y_i) \sim Q_i(\cdot | (x_i, y_i)).$$

For $\{Q_i\}_{i \in \mathbb{N}^*}$ to satisfy the α-LDP constraint we require that

$$\sup_{i \in \mathbb{N}^*} \sup_{A} \sup_{(x,y),(x',y') \in \mathbb{R}^d \times \mathbb{R}} \frac{Q_i(A | (x,y))}{Q_i(A | (x',y'))} \leq e^\alpha. \tag{2}$$

In our lower bounds, however, we allow mechanisms to be sequentially interactive [e.g. 12], so that a privacy mechanism is given by $\{Q_i\}_{i \in \mathbb{N}^*}$, with the interpretation that

$$(W_i, Z_i) | \{(X_i, Y_i, W_{i-1}, Z_{i-1}, \ldots, W_1, Z_1) = (x_i, y_i, w_{i-1}, z_{i-1}, \ldots, w_1, z_1)$$
$$\sim Q_i(\cdot | (x_i, y_i, w_{i-1}, z_{i-1}, \ldots, w_1, z_1)).$$

Here the α-LDP constraint requires that

$$\sup_{i \in \mathbb{N}^*} \sup_{A} \sup_{(x,y),(x',y') \in \mathbb{R}^d \times \mathbb{R}} \sup_{w_1, z_1, \ldots, w_{i-1}, z_{i-1}} \frac{Q_i(A | (x, y, w_{i-1}, z_{i-1}, \ldots, w_1, z_1))}{Q_i(A | (x', y', w_{i-1}, z_{i-1}, \ldots, w_1, z_1))} \leq e^\alpha.$$

Since our upper and lower bounds match, up to a logarithmic factor, we may conclude that simpler non-interactive procedures result in optimal performance for this problem.

We will assume throughout that $\alpha \leq 1$, though this can be relaxed to $\alpha \leq C$ for any $C > 0$. This restricts attention to the strongest constraints, and is often the regime of primary interest [e.g. 12].

1.1 Summary of contributions and related literature

To the best of our knowledge, this is the first work on a few fronts.

Firstly, this is the first paper to consider change point detection under local privacy constraints. Previous work has focused on the central model of differential privacy, where there exists a third party trusted to have access to all of the data. [9] use established tools from the central model of differential privacy to detect changes in both the offline and online settings. The pre- and post-change distributions are assumed to be known, and a private version of the likelihood ratio statistic is analysed. Further development of these ideas, in particular the extension to detection of multiple changes in the online setting, is given in [35]. [6] give differentially private tests of simple hypotheses, shown to be optimal up to constants, which are then applied to the change point detection problem with known pre- and post-change distributions. In a setting in which the distributions are unknown, [8] develop

private versions of the Mann–Whitney test to detect a change in location. The problem has also been studied under different notions of central privacy [20].

Secondly, this is the first paper to study the fundamental limits in multivariate nonparametric regression change point detection problems. We have derived the minimax rate of the detection delay, allowing the jump size $\|m_\Delta - m_{\Delta+1}\|_\infty$, the variance of the additive noise σ^2 and the privacy constraint α to vary with the location of the change point Δ. There has been a vast body of literature discussing the detection boundary and optimal estimation in the offline change point analysis [e.g. 29, 32]. Their counterparts in online change point analysis are relatively scarce and existing work includes univariate mean change [e.g. 33] and dynamic networks [e.g. 34]. On a separate note, multivariate nonparametric regression estimation, under privacy constraints, is studied in [4], and classification is studied in [2]

In addition, we have also provided the analysis and results based on the univariate mean online change point detection problem, with privatised data. This is, arguably, the simplest privatised, online change point detection problem. The analysis and results we shown in this paper enrich statisticians' toolboxes and serve as a benchmark for more complex problems.

2 Methodology

In this section, we describe our private change point detection algorithm, which takes the privatised data as input. The whole algorithm consists of two key ingredients: (1) the privacy mechanism and (2) the change point detection method.

The privacy mechanism. Throughout this paper, a binned estimator is the core of the analysis. Recall that the raw data at time point i include a d-dimensional feature vector X_i, which we assume is supported within some bounded set $\mathcal{X} \subset \mathbb{R}^d$, and a univariate response variable Y_i. We denote $\{A_{h,j}\}_{j=1,\ldots,N_h}$ as a set of cubes of volume h^d, such that $\{\mathcal{X} \cap A_{h,j}\}_{j=1,\ldots,N_h}$ is a partition of $\mathcal{X}$, and write $x_{h,j}$ for the centre of $A_{h,j}$. The data point (X_i, Y_i) is then randomised by taking

$$W_{i,j} = \mathbb{1}_{\{X_i \in A_{h,j}\}} + \frac{4}{\alpha}\epsilon_{i,j} \quad \text{and} \quad Z_{i,j} = [Y_i]^M_{-M}\mathbb{1}_{\{X_i \in A_{h,j}\}} + \frac{4M}{\alpha}\zeta_{i,j},$$

where $\{\epsilon_{i,j}, \zeta_{i,j}\}$ are independent and identically distributed standard Laplace random variables, and where $[Y]^M_{-M} = \min(M, \max(Y, -M))$ with $M > 0$ a truncation parameter. It is shown in Proposition 1 in [4] [see also 2] that this non-interactive mechanism is an α-LDP channel.

The change point detection method. Given data $\{(W_{i,j}, Z_{i,j})\}$, as for online change point detection, we propose Algorithm 1, with the CUSUM estimator defined in Definition 1 and the nonparametric estimators involved defined in Definition 2.

Algorithm 1 Online change point detection via CUSUM statistics

---

INPUT: $\{(W_{u,j}, Z_{u,j})\}_{u,j=1,2,\ldots} \subset \mathbb{R}^d \times \mathbb{R}$, $\{b_{s,t}, 1 \le s < t < \infty, \ldots\} \subset \mathbb{R}$.
   $t \leftarrow 1$;
   FLAG $\leftarrow 0$;
   while FLAG $= 0$ **do**
      $t \leftarrow t + 1$;
      FLAG $= 1 - \prod_{s=1}^{t-1} \mathbb{1}\left\{\widehat{D}_{s,t} \le b_{s,t}\right\}$;
   end while
OUTPUT: t.

Definition 1. *Given a sequence $\{(W_{t,j}, Z_{t,j})\}$ and a pair of integers $1 \le s < t$, we define the CUSUM statistic*

$$\widehat{D}_{s,t} = \max_{j=1}^{N_h} \sqrt{\frac{s(t-s)}{t}} \left|\widehat{m}_{1:s}(x_{h,j}) - \widehat{m}_{(s+1):t}(x_{h,j})\right|,$$

where $\widehat{m}_{\cdot:\cdot}(\cdot)$ is defined in Definition 2.

Definition 2. *Given a sequence $\{(W_{t,j}, Z_{t,j})\}$ and a pair of integers $1 \le s < t$, with $h > 0$ being our bandwidth parameter, we define the regression function estimator as*

$$\widehat{m}_{s:t}(x) = \frac{\widehat{\nu}_{s:t}(A_{h,j})}{\widehat{\mu}_{s:t}(A_{h,j})}\mathbb{1}_{\{\widehat{\mu}_{s:t}(A_{h,j}) \ge \frac{\log(t-s+2)}{t-s+1}\}}, \quad \text{if } x \in A_{h,j},$$

where

$$\widehat{\nu}_{s:t}(A_{h,j}) = \frac{1}{t-s+1} \sum_{s \leq i \leq t} Z_{i,j} \quad and \quad \widehat{\mu}_{s:t}(A_{h,j}) = \frac{1}{t-s+1} \sum_{s \leq i \leq t} W_{i,j}.$$

Algorithm 1 is a standard online change point detection procedure. Whenever a new data point stamped at t is collected, one checks if a change point has occurred by checking if any of $(\widehat{D}_{s,t})_{s=1,\ldots,t-1}$ have exceeded pre-specified thresholds. Apparently, both the storage and computation costs of this procedure are high. As pointed out in [33], without knowing the pre- and/or post-change point distributions, there is no existing algorithm which can have a constant computational cost $O(1)$ when a new data point is collected. Of course, one can also be smarter: instead of scanning through $s \in \{1, \ldots, t-1\}$, one can just scan through a dyadic grid as described in [34].

The CUSUM statistic $\widehat{D}_{s,t}$, defined in Definition 1, is a normalised difference between two estimated functions, before and after time point s, evaluated at each cell in the partition. It is used to examine, given all the data up to t, if s is a possible change point. It can be viewed as a sample version of the quantity

$$\max_{s=1}^{t-1} \sqrt{\frac{s(t-s)}{t}} \left\| s^{-1} \sum_{i=1}^{s} m_i - (t-s)^{-1} \sum_{i=s+1}^{t} m_i \right\|_{\infty},$$

where $\| \cdot \|_\infty$ is the sup-norm of a function. In [22], a similar CUSUM was proposed in studying the nonparametric density change point detection problem. In our setting, we are interested in change points in the regression functions. The construction of estimators is detailed in Definition 2. This estimator has previously studied in the one sample estimation scenario in [4], where it was shown to be a universally strongly consistent estimator of the true regression function.

3   Theory

In this section, we present our core results. All the assumptions are collected in Section 3.1. The theoretical guarantees of Algorithm 1 are presented in Section 3.2, which also includes a minimax lower bound result showing our proposed method is optimal, off by at most a logarithmic factor. To quantify the cost of maintaining α-LDP, we also provide a benchmark result of the same data generating mechanism but without privacy in Section 3.3.

3.1   Assumptions

Assumption 1 (Setup). *Assume that $\{(X_i, Y_i)\}_{i \in \mathbb{N}^*}$ is a sequence of independent random objects, taking values in $\mathcal{X} \times \mathbb{R}$, such that $\{X_i\}_{i \in \mathbb{N}^*}$ are independent each with distribution μ on $\mathcal{X}$. We assume that there exists an absolute constant $c_{\min} > 0$ such that $\mu(A_{h,j}) \geq c_{\min} h^d$ for all $A_{h,j}$ in the partition of $\mathcal{X}$. Assume that the regression functions $m_i(\cdot)$, given by (1), are well defined for μ-almost all x and $i \in \mathbb{N}^*$, such that there exists an absolute constant $C_{\mathrm{Lip}} > 0$ with*

$$\sup_{i \in \mathbb{N}^*} |m_i(x_1) - m_i(x_2)| \leq C_{\mathrm{Lip}} \|x_1 - x_2\|, \quad \forall x_1, x_2 \in \mathcal{X}.$$

We also assume that there exists $\sigma > 0$ such that for all $\lambda \in \mathbb{R}$ we have

$$\sup_{i \in \mathbb{N}^*} \sup_{x \in \mathbb{R}^d} \mathbb{E}\left(e^{\lambda\{Y_i - m_i(x)\}} \,\middle|\, X_i = x \right) \leq e^{\frac{\lambda^2 \sigma^2}{2}}$$

and that $\sup_{i \in \mathbb{N}^*} \sup_{x \in \mathbb{R}^d} |m_i(x)| \leq M_0$ for some $M_0 > 0$.

Assumption 1 is the main model assumption. It is a general feature of the local differential privacy constraint that it is not possible to work with unbounded parameter spaces [see, for example, 11, Appendix G]. Thus, we assume that the feature vectors are supported in a bounded set $\mathcal{X}$, and we moreover assume that the regression functions m_i are bounded, though these bounds are allowed to vary with the pre-change sample size Δ. In addition, we also assume that the regression functions are Lipschitz with a constant C_{Lip}. The Lipschitz condition can be easily relaxed to other type of continuity conditions, e.g. Hölder continuity. We assume the additive noise is sub-Gaussian with parameter σ, which is allowed to vary with the pre-change sample size.

149 **Assumption 2** (No change point). *Assume that $m_1 = m_2 = \cdots$.*

150 **Assumption 3** (One change point). *Assume that there exists a positive integer $\Delta \geq 1$ such that*

$$m_1 = \cdots = m_\Delta \neq m_{\Delta+1} = m_{\Delta+2} = \cdots .$$

151 *In addition, let $\kappa = \|m_\Delta - m_{\Delta+1}\|_\infty$.*

152 **Assumption 4** (Signal-to-noise ratio). *There exists a sufficiently large absolute constant $C_{\mathrm{SNR}} > 0$*
153 *such that*

$$\frac{\kappa^2 h^{2d}\alpha^2\Delta}{\max\{\sigma^2,\, M_0^2\}} \geq C_{\mathrm{SNR}} \log\left(\frac{\Delta}{c_{\min}h^{2d}\gamma}\right),$$

154 *where $\gamma \in (0,1)$ is the desired bound on false alarm probability and h is the bin-width used in*
155 *constructing the estimators.*

156 Assumptions 2, 3 and 4 describe different scenarios and aspects of the change point assumptions.
157 Assumption 2 is a formal assumption describing when there is no change point and Assumption 3
158 depicts the scenario when there is one change point. Recall that in Definition 1 we proposed
159 the CUSUM statistic which is a sample version of a normalised sup-norm difference between
160 two functions. This is to be consistent with κ, the characterisation of the jump, introduced in
161 Assumption 3.

162 Assumption 4 is the signal-to-noise ratio condition. Recall that κ is the jump size, σ is the fluctuation
163 size, M_0 is the upper bound of the mean function m_i, α is the privacy constraint and Δ is the size of
164 the pre-change point sample size. Assumption 4 requires that $\kappa^2 h^{2d}\alpha^2\Delta \min\{M_0^{-2}, \sigma^{-2}\}$ is larger
165 than a logarithmic factor. This in fact allows κ, σ, M_0 and α to vary as Δ diverges. It may appear to
166 be unnatural to involve tuning parameters in the signal-to-noise ratio condition. We remark that the
167 involvement of h in Assumption 4 is to provide more flexibility in the tuning parameter selection. We
168 will elaborate this point in Section 3.2.

169 ### 3.2 Optimal online change point detection with privatised data

170 Theorem 1 below is the main result, which shows that for any $\gamma \in (0,1)$, with properly chosen tuning
171 parameters, with probability at least of $1 - \gamma$, Algorithm 1 does not have false alarms and has a
172 detection delay upper bounded by ϵ in (12).

173 **Theorem 1.** *Consider the settings described in Assumption 1. Let $\gamma \in (0,1)$ and $\widehat{t}$ be the stopping*
174 *time returned by Algorithm 1 with inputs $\{(W_{tj}, Z_{tj})\}_{t,j=1,2,\ldots}$ and $\{b_{s,t}\}_{t=2,3,\ldots;s=1,\ldots,t}$, where*

$$b_{s,t} = \begin{cases} 2\sqrt{\dfrac{s(t-s)}{t}}\Big\{2(M - M_0)e^{-\frac{(M-M_0)^2}{2\sigma^2}} \\ \quad + C_{\mathrm{Lip}}\sqrt{d}h\Big\} + \dfrac{M}{c_{\min}h^d\alpha}\sqrt{\log\left(\dfrac{72t^3}{\gamma c_{\min}h^d}\right)}, & \text{if } \dfrac{s(t-s)}{t}c_{\min}^2 h^{2d}\alpha^2 \geq 64\log\left(\dfrac{72t^3}{\gamma c_{\min}h^d}\right); \\ \\ \infty, & \textit{otherwise.} \end{cases}$$
(3)

175 *Assume that the truncation parameter satisfies*

$$M \geq M_1 = M_0 + \sigma\sqrt{2\log(2 + \sigma/h) + \log\log(2 + \sigma/h)}.$$
(4)

176 *and the bandwidth satisfies $h \leq C\kappa$, where $C > 0$ is an absolute constant.*

177 *If Assumption 2 holds, then*

$$\mathbb{P}_\infty\left\{\widehat{t} < \infty\right\} < \gamma.$$
(5)

178 *Under Assumption 3, we have*

$$\mathbb{P}_\Delta\left\{\widehat{t} \leq \Delta\right\} < \gamma,$$
(6)

179 *for any $\Delta \geq 1$. If Assumptions 3 and 4 both hold, then*

$$\mathbb{P}_\Delta\left\{\Delta < \widehat{t} \leq \Delta + \epsilon\right\} \geq 1 - \gamma, \quad \text{where} \quad \epsilon = C_\varepsilon \frac{M^2}{\kappa^2 h^{2d}\alpha^2}\log\left(\frac{\Delta}{h^{2d}c_{\min}\gamma}\right)$$
(7)

180 *and $C_\varepsilon > 0$ is an absolute constant.*

To better understand Theorem 1, we first inspect the sources of the error in the procedure. The estimators of the regression functions m_i are defined in Definition 2, which is a binned estimator averaging over cubes of volume h^d. This is a typical nonparametric estimator, which brings in both bias and variance. On top of this, due to the constraints of privacy, we truncate the responses by M in the privacy channel. The truncation level M should be an upper bound on M_1 – a large-probability upper bound on the response, consisting of the upper bound on the regression function and the additive noise – so that the truncation bias is no larger than the bias due to smoothing. On the other hand, larger values of M result in larger variance, due to the need to add more noise in the privacy mechanism. If $M < M_1$ then the change point may be undetectable, as the bias could be larger than the signal. The same phenomenon occurs in nonparametric testing and change point detection problems, that the smoothing parameter should not be too large to mask the signal.

Algorithm 1 declares the existence of a change point t, if there exists an integer pair (s, t) such that $\widehat{D}_{s,t} > b_{s,t}$. The threshold sequence is detailed in (3). It is separated into two cases: (i) when $s(t - s)/t$ is large enough for both $\widehat{m}_{1:s}$ and $\widehat{m}_{(s+1):t}$ to be estimated accurately, and (ii) otherwise. In view of the sources of errors, we can see that in case (i), with probability at least $1 - \gamma$, the threshold $b_{s,t}$ is set to be the sum of an upper bound of all sources of errors. In case (ii), the threshold is set to be infinity, so that we never declare a change.

When there is no change point, or when there is a change point but $t \leq \Delta$, the thresholds, with probability at least $1 - \gamma$, are upper bounds on the estimators. When there is a change point and $t > \Delta$, due to Assumption 4, one can always let $s = \Delta$ such that there are enough samples to provide a good estimator of m_Δ, the pre-change regression function. If $t - \Delta$ is not large enough such that case (i) holds, then we cannot provide a good estimator of $m_{\Delta+1}$. Once enough data is collected after the change point, Algorithm 1 is able to tell the difference and thus declare a change point, with delay upper bounded by ϵ in (12). Note that the conditions of case (i) will be satisfied before time $\Delta + \epsilon$.

We require the bandwidth $h \leq C\kappa$ to ensure that the binning will not smooth out the jump, and this condition is necessary. In practice, the bin-width can be chosen in a data-driven way [e.g. 34]. In view of Assumption 4, the smaller h is, the larger $\kappa^2\alpha^2\Delta/\max\{\sigma^2, M_0^2\}$ needs to be. In the best case that $h \asymp \kappa$, Assumption 4 and ϵ in (12) read as

$$\frac{\kappa^{2+2d}\alpha^2\Delta}{\max\{\sigma^2, M_0^2\}} \gtrsim \log\left(\frac{\Delta}{c_{\min}\kappa^{2d}\gamma}\right) \quad \text{and} \quad \epsilon = C_\varepsilon \frac{M^2}{\kappa^{2+2d}\alpha^2} \log\left(\frac{\Delta}{\kappa^{2d}c_{\min}\gamma}\right). \tag{8}$$

We remark that the detection delay in (12) is of order

$$\epsilon \asymp \frac{M^2}{\kappa^2 h^{2d}\alpha^2} \log(\Delta/(h^{2d}\gamma)) \asymp \frac{(M - M_0)^2 + M_0^2 + \sigma^2}{\kappa^2 h^{2d}\alpha^2} \log(\Delta/(h^{2d}\gamma)),$$

which again reflects all three sources of errors. Now the question is whether this rate can be improved. To answer the question, we consider a simplified scenario, where we assume that $M_0 \leq \sigma$.

Theorem 2 (Lower bound). *Denote by $\mathcal{P}_{\kappa,\sigma,\Delta}$ the class of distributions satisfying Assumptions 1 and 3, and assume $M_0 \leq \sigma$. Given $\alpha > 0$ let $\mathcal{Q}_\alpha$ be the collection of all sequentially interactive α-locally differentially private mechanisms. Given $\gamma > 0$ consider the class of change point estimators*

$$\mathcal{D}(\gamma) = \left\{T : T \text{ is a stopping time wrt. the natural filtration and satisfies } \mathbb{P}_\infty(T < \infty) \leq \gamma\right\}.$$

Then for a sufficiently small γ, it holds that

$$\inf_{Q \in \mathcal{Q}_\alpha} \inf_{\widehat{t} \in \mathcal{D}(\gamma)} \sup_{P \in \mathcal{P}_{\kappa,\sigma,\Delta}} \frac{2\kappa^{2+2d}\alpha^2}{\sigma^2} \mathbb{E}_P\left\{(\widehat{t} - \Delta)_+\right\} \geq \log(1/\gamma).$$

Theorem 2 studies the private minimax rate of the detection delay in the framework proposed in [12]. Compared with standard minimax theory, new tools are required in order to deal with an arbitrary privacy mechanism in $\mathcal{Q}_\alpha$. We use Lemma 1 in [12, Supplementary material], which provides a uniform bound on the log-likelihood ratio of two distributions seen through a private channel. To the best of our knowledge, this is the first time that these tools have been applied to change point problems. Although, in our upper bounds, we only had to consider non-interactive mechanisms, this lower bound also applies to general sequentially interactive mechanisms. In particular, this shows that the use of interactive mechanisms is unnecessary in our problem.

Since in the minimax sense the lower bound is taken to be the infimum over all possible estimators, to make the results comparable in Assumption 4 and Theorem 1, we let $h \asymp \kappa$ and compare Theorem 2 with (8). Theorem 2 shows that the lower bound on the detection delay is of order $\sigma^2/(\kappa^{2+2d}\alpha^2)\log(1/\gamma)$, which compared to (8) is off by a logarithmic factor and therefore shows that Algorithm 1 is nearly minimax rate optimal.

3.3 Optimal online change point detection with non-private data

As a benchmark, we provide the non-private counterpart of Theorem 1 and 2 in this subsection. For completeness, we also detail the counterparts of Definitions 1, 2 and Algorithm 1 in Definitions 3, 4 and Algorithm 2, respectively. We will conclude this subsection with comparisons of results in the private and non-private cases, quantifying the cost of maintaining privacy.

Definition 3. *Given a sequence $\{(X_t, Y_t)\}_{t\in\mathbb{N}^*}$ and a pair of integers $1 \leq s < t$, we define the CUSUM statistic*

$$\widetilde{D}_{s,t} = \max_{i=1}^{t} \sqrt{\frac{s(t-s)}{t}} \left| \widetilde{m}_{1:s}(X_i) - \widetilde{m}_{(s+1):t}(X_i) \right|,$$

where $\widetilde{m}_{.:.}(\cdot)$ is defined in Definition 4.

Definition 4. *Given a sequence $\{(X_t, Y_t)\}_{t\in\mathbb{N}^*}$, a pair of integers $1 \leq s < t$ and a tuning parameter $h > 0$, we define the regression function estimator as*

$$\widetilde{m}_{s:t}(x) = \frac{\nu_{s:t}(A_{h,j})}{\mu_{s:t}(A_{h,j})}, \quad \text{if } x \in A_{h,j},$$

where

$$\nu_{s:t}(A_{h,j}) = \frac{1}{t-s+1} \sum_{s\leq i\leq t} Y_i \mathbb{1}_{\{X_i \in A_{h,j}\}} \quad \text{and} \quad \mu_{s:t}(A_{h,j}) = \frac{1}{t-s+1} \sum_{s\leq i\leq t} \mathbb{1}_{\{X_i \in A_{h,j}\}}.$$

Algorithm 2 Online change point detection via CUSUM statistics

---

INPUT: $\{(X_u, Y_u)\}_{u=1,2,\dots} \subset \mathbb{R}^p \times \mathbb{R}$, $\{\tilde{b}_{u,t}, t = 2, 3, \dots; u = 1, \dots, t\} \subset \mathbb{R}$.
   $t \leftarrow 1$;
   FLAG $\leftarrow 0$;
   while FLAG $= 0$ **do**
      $t \leftarrow t + 1$;
      FLAG $= 1 - \prod_{s=1}^{t-1} \mathbb{1}\left\{ \widetilde{D}_{s,t} \leq \tilde{b}_{s,t} \right\}$;
   end while
OUTPUT: t.

Assumption 5 (Non-private signal-to-noise ratio). *There exists a sufficiently large absolute constant $C_{\mathrm{SNR}} > 0$ such that*

$$\kappa^2 h^d \Delta \sigma^{-2} \geq C_{\mathrm{SNR}} \log(\Delta/(\gamma h^d)).$$

The following two theorems are the non-private version counterparts of Theorems 1 and 2. Theorem 4 shows that the detection delay rate we obtain in Theorem 3 is optimal off by a logarithmic factor.

Theorem 3. *Consider the settings described in Assumption 1. Let $\gamma \in (0,1)$ and $\widetilde{t}$ be the stopping time returned by Algorithm 2 with inputs $\{(X_t, Y_t)\}_{t=1,2,\dots}$ and $\{\tilde{b}_{s,t}\}_{t=2,3,\dots;s=1,\dots,t}$, where*

$$\tilde{b}_{s,t} = 2\sqrt{\frac{s(t-s)}{t}} C_{\mathrm{Lip}}\sqrt{d}h + \frac{4\sigma}{\sqrt{c_{\min}h^d}}\sqrt{5\log(t) + \log(32/\gamma)} \tag{9}$$

Assume that the bandwidth satisfies $h \leq C\kappa$.

If Assumption 2 holds, then

$$\mathbb{P}_\infty\left\{\widetilde{t} < \infty\right\} < \gamma. \tag{10}$$

Under Assumption 3 we have

$$\mathbb{P}_\Delta\left\{\widetilde{t} \leq \Delta\right\} < \gamma, \tag{11}$$

for any $\Delta \geq 1$. If Assumptions 3 and 5 both hold, then

$$\mathbb{P}_\Delta \left\{ \Delta < \widetilde{t} \leq \Delta + \epsilon \right\} \geq 1 - \gamma - (c_{\min}h^d)^{-1}\exp(-\Delta c_{\min}h^d), \tag{12}$$

where

$$\epsilon = C_\varepsilon \frac{\sigma^2}{\kappa^2 h^d}\log(\Delta/\gamma),$$

with $C_\varepsilon > 0$ being an absolute constant.

Theorem 4. *Denote by $\mathcal{P}_{\kappa,\sigma,\Delta}$ the class of distributions satisfying Assumptions 1 and 3 For any $\gamma \in (0,1)$, consider the class of change point estimators*

$$\mathcal{D}(\gamma) = \left\{ T : T \text{ is a stopping time wrt. the natural filtration and satisfies } \mathbb{P}_\infty(T < \infty) \leq \gamma \right\}.$$

Then for any sufficiently small γ, it holds that

$$\inf_{\widehat{t}\in\mathcal{D}(\gamma)} \sup_{P\in\mathcal{P}_{\kappa,\sigma,\Delta}} \frac{2\kappa^{2+d}}{\sigma^2}\mathbb{E}_P\left\{(\widehat{t}-\Delta)_+\right\} \geq \log(1/\gamma).$$

We are now ready to quantify the cost of maintaining the privacy in the multivariate nonparametric regression online change point detection scenario.

- As we have pointed out, in order to maintain the privacy, we require $\mathcal{X}$ to be a bounded set, the regression function to be upper bounded by M_0 and an extra tuning parameter M is introduced in truncation. All these are not needed in the non-private case.

- A more prominent difference roots in the detection delay rate. In the non-private case, the denominator is κ^{2+d}, which roots in the optimal nonparametric estimation [e.g. 28]. In the private case, the corresponding rate is κ^{2+2d}. This is in line with the literature in local differential privacy, where the curse of dimensionality is typically worse in nonparametric and high-dimensional problems than in their non-private counterparts [12, 2, 5, 3].

- Another difference is in terms of the privacy parameter α, which only shows up in the private case. Recalling that we restrict ourselves to the most interesting regime $\alpha \in (0,1]$, the effect of α is twofold: (1) Comparing Assumptions 4 and 5, we see that the private case requires a larger signal by a factor of α^{-2}; and (2) comparing the detection delay rates in Theorem 1 and 3, we see that the rate in the private case is also inflated by a factor of α^{-2}.

4 Conclusions

In this paper, we studied a multivariate, nonparametric regression, online, privatised change point detection problem. The method we proposed is shown to be minimax rate-optimal in terms of its detection delay, with a theory-guided tuning parameter. As a benchmark result, we have also provided its counterpart for non-private data. The comparisons enable us to understand the cost of maintaining privacy.

In addition to the main results in the paper, in Section S.1 in the supplementary material, we investigate an online univariate mean change point detection problem with privatised data. Section S.1 is self-contained. It includes a minimax lower bound on the detection delay and a polynomial-time algorithm which provides a matching upper bound, saving for a logarithmic factor. The framework we set up in Section S.1 serves as a blueprint to study private online change detection with more complex data types.

Comparing the results in Section S.1 to those in the non-private setting [e.g. 33] and comparing these differences with those we examined at the end of Section 3.3, one can see that we pay different costs for privacy in different data types. This leads to our future work, studying private change point detection in high-dimensional, functional or other nonparametric data, and understanding the tradeoff between accuracy and privacy in these more challenging situations.

Regarding the setup we have in this paper, it can be easily adjusted to allow for multiple change points. This is because, with large probability, our algorithm will not declare false alarms and will correctly detect a change point with a delay ϵ being a small fraction of Δ. Therefore, provided that two consecutive change points are at least Δ apart, refreshing the algorithm whenever a change point is declared can enable us to detect multiple change points accurately.

Another interesting but challenge future work direction is to allow temporal dependence, say weakly dependent time series. It is not even clear how to define valid privacy mechanisms in this setting: if the time points were strongly dependent then our mechanisms would give more information as time progressed. In fact, this is even an open problem without the presence of change points. We would also need to adjust the concentration inequalities we are currently using to those which are suitable for weakly dependent data.

Supplementary material

The supplementary material contains a self-contained analysis of locally private univariate mean change point detection problems and all the technical details of this paper.

References

[1] Ibrahim Ethem Bagci, Utz Roedig, Ivan Martinovic, Matthias Schulz, and Matthias Hollick. Using channel state information for tamper detection in the internet of things. In *Proceedings of the 31st Annual Computer Security Applications Conference*, pages 131–140, 2015.

[2] Thomas Berrett and Cristina Butucea. Classification under local differential privacy. *Annales de l'ISUP*, 63 – 80 ans de Denis Bosq, 2019.

[3] Thomas B Berrett and Cristina Butucea. Locally private non-asymptotic testing of discrete distributions is faster using interactive mechanisms. *Advances in Neural Information Processing Systems 34*, 2020.

[4] Thomas B. Berrett, László Györfi, and Harro Walk. Strongly universally consistent nonparametric regression and classification with privatised data. *Electron. J. Statist.*, 15(1):2430–2453, 2021.

[5] Cristina Butucea, Amandine Dubois, Martin Kroll, and Adrien Saumard. Local differential privacy: Elbow effect in optimal density estimation and adaptation over besov ellipsoids. *Bernoulli*, 26(3):1727–1764, 2020.

[6] Clément L Canonne, Gautam Kamath, Audra McMillan, Adam Smith, and Jonathan Ullman. The structure of optimal private tests for simple hypotheses. In *Proceedings of the 51st Annual ACM SIGACT Symposium on Theory of Computing*, pages 310–321, 2019.

[7] Aloni Cohen and Kobbi Nissim. Towards formalizing the gdpr's notion of singling out. *Proceedings of the National Academy of Sciences*, 117(15):8344–8352, 2020.

[8] Rachel Cummings, Sara Krehbiel, Yuliia Lut, and Wanrong Zhang. Privately detecting changes in unknown distributions. In *Proceedings of the 37th International Conference on Machine Learning*, volume 119, pages 2227–2237, 2020.

[9] Rachel Cummings, Sara Krehbiel, Yajun Mei, Rui Tuo, and Wanrong Zhang. Differentially private change-point detection. In *Advances in Neural Information Processing Systems*, volume 31, 2018.

[10] Bolin Ding, Janardhan Kulkarni, and Sergey Yekhanin. Collecting telemetry data privately. In *Advances in Neural Information Processing Systems*, pages 3571–3580, 2017.

[11] John C Duchi, Michael I Jordan, and Martin J Wainwright. Local privacy, data processing inequalities, and minimax rates. *arXiv preprint arXiv:1302.3203*, 2013.

[12] John C Duchi, Michael I Jordan, and Martin J Wainwright. Minimax optimal procedures for locally private estimation. *Journal of the American Statistical Association*, 113(521):182–201, 2018.

[13] John C Duchi and Feng Ruan. The right complexity measure in locally private estimation: It is not the Fisher information. *arXiv preprint arXiv:1806.05756*, 2018.

[14] Cynthia Dwork, Frank McSherry, Kobbi Nissim, and Adam Smith. Calibrating noise to sensitivity in private data analysis. In *Theory of Cryptography Conference*, pages 265–284. Springer, 2006.

[15] Úlfar Erlingsson, Vasyl Pihur, and Aleksandra Korolova. Rappor: Randomized aggregatable privacy-preserving ordinal response. In *Proceedings of the 2014 ACM SIGSAC conference on computer and communications security*, pages 1054–1067, 2014.

[16] Dario Gregori, Danila Azzolina, Corrado Lanera, Ilaria Prosepe, Nicolas Destro, Giulia Lorenzoni, and Paola Berchialla. A first estimation of the impact of public health actions against covid-19 in veneto (italy). *J Epidemiol Community Health*, 74(10):858–860, 2020.

[17] David J Hand and Gordon Blunt. Prospecting for gems in credit card data. *IMA Journal of management Mathematics*, 12(2):173–200, 2001.

[18] Peter Kairouz, Sewoong Oh, and Pramod Viswanath. Extremal mechanisms for local differential privacy. In *Advances in Neural Information Processing Systems*, volume 27, pages 2879–2887, 2014.

[19] Taha A Kass-Hout, Zhiheng Xu, Paul McMurray, Soyoun Park, David L Buckeridge, John S Brownstein, Lyn Finelli, and Samuel L Groseclose. Application of change point analysis to daily influenza-like illness emergency department visits. *Journal of the American Medical Informatics Association*, 19(6):1075–1081, 2012.

[20] T. S. Lau and W. Peng Tay. Privacy-aware quickest change detection. In *ICASSP 2020 - 2020 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 5999–6003, 2020.

[21] Céline Lévy-Leduc and François Roueff. Detection and localization of change-points in high-dimensional network traffic data. *Annals of Applied Statistics*, 3(2):637–662, 2009.

[22] Oscar Hernan Madrid Padilla, Yi Yu, Daren Wang, and Alessandro Rinaldo. Optimal nonparametric multivariate change point detection and localization. *arXiv preprint arXiv:1910.13289*, 2019.

[23] Luc Rocher, Julien M Hendrickx, and Yves-Alexandre De Montjoye. Estimating the success of re-identifications in incomplete datasets using generative models. *Nature Communications*, 10(1):1–9, 2019.

[24] Angelika Rohde and Lukas Steinberger. Geometrizing rates of convergence under local differential privacy constraints. *Annals of Statistics*, 48(5):2646–2670, 2020.

[25] Latanya Sweeney. k-anonymity: A model for protecting privacy. *International Journal of Uncertainty, Fuzziness and Knowledge-Based Systems*, 10(05):557–570, 2002.

[26] Jun Tang, Aleksandra Korolova, Xiaolong Bai, Xueqiang Wang, and Xiaofeng Wang. Privacy loss in Apple's implementation of differential privacy on MacOS 10.12. *arXiv preprint arXiv:1709.02753*, 2017.

[27] Alexander G Tartakovsky. Rapid detection of attacks in computer networks by quickest changepoint detection methods. In *Data Analysis for Network Cyber-Security*, pages 33–70. World Scientific, 2014.

[28] Alexandre B Tsybakov. *Introduction to nonparametric estimation*. Springer Science & Business Media, 2008.

[29] Nicolas Verzelen, Magalie Fromont, Matthieu Lerasle, and Patricia Reynaud-Bouret. Optimal change-point detection and localization. *arXiv preprint arXiv:2010.11470*, 2020.

[30] W Allen Wallis. The statistical research group, 1942–1945. *Journal of the American Statistical Association*, 75(370):320–330, 1980.

[31] Di Wang, Marco Gaboardi, and Jinhui Xu. Empirical risk minimization in non-interactive local differential privacy revisited. In *Advances in Neural Information Processing Systems*, pages 965–974, 2018.

[32] Yi Yu. A review on minimax rates in change point detection and localisation. *arXiv preprint arXiv:2011.01857*, 2020.

[33] Yi Yu, Oscar Hernan Madrid Padilla, Daren Wang, and Alessandro Rinaldo. A note on online change point detection. *arXiv preprint arXiv:2006.03283*, 2020.

[34] Yi Yu, Oscar Hernan Madrid Padilla, Daren Wang, and Alessandro Rinaldo. Optimal network online change point localisation. *arXiv preprint arXiv:2101.05477*, 2021.

[35] Wanrong Zhang, Sara Krehbiel, Rui Tuo, Yajun Mei, and Rachel Cummings. Single and multiple change-point detection with differential privacy. *Journal of Machine Learning Research*, 22(29):1–36, 2021.