Contrastive Intrinsic Control for Unsupervised Reinforcement Learning

Abstract

We introduce Contrastive Intrinsic Control (CIC), an unsupervised reinforcement learning (RL) algorithm that maximizes the mutual information between state-transitions and latent skill vectors. CIC utilizes contrastive learning between state-transitions and skills vectors to learn behaviour embeddings and maximizes the entropy of these embeddings as an intrinsic reward to encourage behavioural diversity. We evaluate our algorithm on the Unsupervised RL Benchmark (URLB) in the asymptotic state-based setting, which consists of a long reward-free pre-training phase followed by a short adaptation phase to downstream tasks with extrinsic rewards. We find that CIC improves over prior exploration algorithms in terms of adaptation efficiency to downstream tasks on state-based URLB. [1]

Deep RL is a powerful approach toward solving complex control tasks in the presence of extrinsic rewards. Successful applications include playing video games from pixels [1], mastering the game of Go [2, 3], robotic locomotion [4, 5, 6] and dexterous manipulation [7, 8, 9] policies. While effective, the above advances produced agents that are unable to generalize to new downstream tasks beyond the one they were trained to solve. Humans and animals on the other hand are able to acquire skills with minimal supervision and apply them to solve a variety of downstream tasks. In this work, we seek to train agents that acquire skills without supervision with generalization capabilities by efficiently adapting these skills to downstream tasks.

Over the last few years, unsupervised RL has emerged as a promising framework for developing RL agents that can generalize to new tasks. In the unsupervised RL setting, agents are first pre-trained with self-supervised intrinsic rewards and then finetuned to downstream tasks with extrinsic rewards. Unsupervised RL algorithms broadly fall into three categories - knowledge-based, data-based, and competence-based methods[2]. Knowledge-based methods maximize the error or uncertainty of a predictive model [12, 13, 14]. Data-based methods maximize the entropy of the agent's visitation [15, 16]. Competence-based methods learn skills that generate diverse behaviors [17, 18]. This work falls into the latter category of competence-based exploration methods.

Unlike knowledge-based and data-based algorithms, competence-based algorithms simultaneously address both the exploration challenge as well as distilling the generated experience in the form of reusable skills. This makes them particularly appealing, since the resulting skill-based policies (or skills themselves) can be finetuned to efficiently solve downstream tasks. While there are many self-supervised objectives that can be utilized, our work falls into a family of methods that learns skills by maximizing the mutual information between visited states and latent skill vectors. Many earlier works have investigated optimizing such objectives [17, 18, 19, 20]. However, competence-based methods have been empirically challenging to train and have under-performed when compared to knowledge and data-based methods [21].

---

[1] Project website and code: `https://sites.google.com/view/cicneurips2022/`

[2] These categories for exploration algorithms were introduced by [10] and inspired by [11].

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

Figure 1: Qualitative visualizations of unsupervised skills discovered in Walker, Quadruped, and Jaco arm environments. The Walker learns to balance and move, the Quadruped learns to flip upright and walk, and the 6 DOF robotic arm learns how to move without locking. Unlike prior competence-based methods for continuous control which evaluate on OpenAI Gym (e.g. [17]), which reset the environment when the agent loses balance, CIC is able to learn skills in fixed episode length environments which are much harder to explore (see Appendix J).

In this work, we take a closer look at the challenges of pre-training agents with competence-based algorithms. We introduce Contrastive Intrinsic Control (CIC) – an exploration algorithm that uses a new estimator for the mutual information objective. CIC combines particle estimation for state entropy [22, 15] and noise contrastive estimation [23] for the conditional entropy which enables it to both generate diverse behaviors *(explore)* and discriminate high-dimensional continuous skills *(exploit)*. To the best of our knowledge, CIC is the first exploration algorithm to utilize noise contrastive estimation to discriminate between state transitions and latent skill vectors. Empirically, we show that CIC adapts to downstream tasks more efficiently than prior exploration approaches on the state-based Unsupervised Reinforcement Learning Benchmark (URLB). CIC achieves 79% higher returns on downstream tasks than prior competence-based algorithms and 18% higher returns than the next-best exploration algorithm overall.

1 Background and Notation

Markov Decision Process: We operate under the assumption that our system is described by a Markov Decision Process (MDP) [24]. An MDP consis of the tuple $(\mathcal{S}, \mathcal{A}, \mathcal{P}, r, \gamma)$ which has states $s \in \mathcal{S}$, actions $a \in \mathcal{A}$, transition dynamics $p(s'|s,a) \sim \mathcal{P}$, a reward function r, and a discount factor γ. In an MDP, at each timestep t, an agent observes the current state s, selects an action from a policy $a \sim \pi(\cdot|s)$, and then observes the reward and next state once it acts in the environment: $r, s' \sim \text{env.step}(a)$. Note that usually r refers to an extrinsic reward. However, in this work we will first be pre-training an agent with intrinsic rewards r^{int} and finetuning on extrinsic rewards r^{ext}.

For convenience we also introduce the variable $\tau(s)$ which refers to any function of the states s. For instance τ can be a single state, a pair of states, or a sequence depending on the algorithm. Our method uses $\tau = (s, s')$ to encourage diverse state transitions while other methods have different specifications for τ. Importantly, τ does not denote a state-action trajectory, but is rather shorthand for any function of the states encountered by the agent. In addition to the standard MDP notation, we will also be learning skills $z \in \mathcal{Z}$ and our policy will be skill-conditioned $a \sim \pi(\cdot|s,z)$.

Unsupervised Skill Discovery through Mutual Information Maximization: Most competence-based approaches to exploration maximize the mutual information between states and skills. Our work and a large body of prior research [17, 20, 18, 25, 26, 27] aims to maximize a mutual information objective with the following general form:

$$I(\tau; z) = \mathcal{H}(z) - \mathcal{H}(z|\tau) = \mathcal{H}(\tau) - \mathcal{H}(\tau|z) \tag{1}$$

Competence-based algorithms use different choices for τ and can condition on additional information such as actions or starting states. For a full summary of competence-based algorithms and their objectives see Table 2 in Appendix D.

Lower Bound Estimates of Mutual Information: The mutual information $I(s; z)$ is intractable to compute directly. Since we wish to maximize $I(s; z)$, we can approximate this objective by instead

Figure 2: Architecture illustrating the practical implementation of CIC . During a gradient update step, random $\tau = (s, s')$ tuples are sampled from the replay buffer, then a particle estimator is used to compute the entropy and a noise contrastive loss to compute the conditional entropy. The contrastive loss is backpropagated through the entire architecture. The entropy and contrastive terms are then scaled and added to form the intrinsic reward. The RL agent is optimized with a DDPG [29].

maximizing a lower bound estimate. Most known mutual information maximization algorithms use the variational lower bound introduced in [28]:

$$I(\tau; z) = \mathcal{H}(\tau) - \mathcal{H}(\tau|z) \geq \mathcal{H}(\tau) + \mathbb{E}[\log q(\tau|z)] \tag{2}$$

The variational lower bound can be applied to both decompositions of the mutual information. The design decisions of a competence-based algorithm therefore come down to (i) which decomposition of $I(\tau; z)$ to use, (ii) whether to use discrete or continuous skills, (iii) how to estimate $H(z)$ or $H(\tau)$, and finally (iv) how to estimate $H(z|\tau)$ or $H(\tau|z)$.

2   Motivation

Results from the recent Unsupervised Reinforcement Learning Benchmark (URLB) [21] show that competence-based approaches underperform relative to knowledge-based and data-based baselines on DeepMind Control (DMC). We argue that the underlying issue with current competence-based algorithms when deployed on harder exploration environments like DMC has to do with the currently used estimators for $I(\tau; z)$ rather than the objective itself. To produce structured skills that lead to diverse behaviors, $I(\tau; z)$ estimators must (i) explicitly encourage diverse behaviors and (ii) have the capacity to discriminate between high-dimensional continuous skills. Current approaches do not satisfy both criteria.

Competence-base algorithms do not ensure diverse behaviors: Most of the best known competence-based approaches [17, 18, 25, 26], optimize the first decomposition of the mutual information $\mathcal{H}(z) - \mathcal{H}(z|\tau)$. The issue with this decomposition is that while it ensures diversity of skill vectors it does not ensure diverse behavior from the policy, meaning $\max \mathcal{H}(z)$ does not imply $\max \mathcal{H}(\tau)$. Of course, if $H(z) - \mathcal{H}(z|\tau)$ is maximized and the skill dimension is sufficiently large, then $\mathcal{H}(\tau)$ will also be maximized implicitly. Yet in practice, to learn an accurate discriminator $q(z|\tau)$, the above methods assume skill spaces that are much smaller than the state space (see Table 2), and thus behavioral diversity may not be guaranteed. In contrast, the decomposition $I(\tau; z) = \mathcal{H}(\tau) - \mathcal{H}(\tau|z)$ ensures diverse behaviors through the entropy term $\mathcal{H}(\tau)$. Methods that utilize this decomposition include [27, 20].

Why it is important to utilize high-dimensional skills: Once a policy is capable of generating diverse behaviors, it is important that the discriminator can distill these behaviors into distinct skills. If the set of behaviors outnumbers the set of skills, this will result in degenerate skills – when one skill maps to multiple different behaviors. It is therefore important that the discriminator can accommodate continuous skills of sufficiently high dimension. Empirically, the discriminators used in prior work utilize only low-dimensional continuous skill vectors. DIAYN [17] utilized 16 dimensional skills, DADS [20] utilizes continuous skills of dimension $2 - 5$, while APS [27], an algorithm that utilizes successor features [30, 31] for the discriminator, is only capable of learning continuous skills with dimension 10. We show how small skill spaces can lead to ineffective exploration in a simple gridworld setting in Appendix H and evidence that skill dimension affects performance in Fig. 5.

Figure 3: To empirically demonstrate issues inherent to competence-based exploration methods, we run DIAYN [17] and compare it to ICM [12] and a *Fixed* baseline where the agent receives an intrinsic reward of 1.0 for each timestep and no extrinsic reward on both OpenAI Gym *(episode resets when agent loses balance)* and DeepMind Control (DMC) *(episode is fixed for 1k steps)* Hopper environments. Since Gym and DMC rewards are on different scales, we normalize rewards based on the maximum reward achieved by any algorithm (1k for Gym, 3 for DMC). While DIAYN is able to achieve higher extrinsic rewards than ICM on Gym, the Fixed intrinsic reward baseline performs best. However, on DMC the Fixed and DIAYN agents achieve near-zero reward while ICM does not. This is consistent with findings of prior work that DIAYN is able to learn diverse behaviors in Gym [17] as well as the observation that DIAYN performs poorly on DMC environments [21]

On the importance of benchmarks for evaluation: While prior competence-based approaches such as DIAYN [17] were evaluated on OpenAI Gym [32], Gym environment episodes terminate when the agent loses balance thereby leaking some aspects of extrinsic signal to the exploration agent. On the other hand, DMC episodes have fixed length. We show in Fig 3 that this small difference in environments results in large performance differences. Specifically, we find that DIAYN is able to learn diverse skills in Gym but not in DMC, which is consistent with both observations from DIAYN and URLB papers. Due to fixed episode lengths, DMC tasks are harder for reward-free exploration since agents must learn to balance without supervision.

3 Method

3.1 Contrastive Intrinsic Control

From Section 2 we are motivated to find a lower bound for $I(\tau; z)$ with a discriminator that is capable of supporting high-dimensional continuous skills[3]. Additionally, we wish to increase the diversity of behaviors so that the discriminator can continue learning new skills throughout training. We choose the forward decomposition of MI $I(\tau; z) = \mathcal{H}(\tau) - \mathcal{H}(\tau|z)$ similar to [27] and estimate the lower bound with Eq. 2. The entropy is estimated $\mathcal{H}(\tau)$ with a particle-based estimator similar to [15]. As such, the primary technical contribution of this work is a novel estimator for the discriminator.

To improve the discriminator, we propose to utilize noise contrastive estimation (NCE) [23] between state-transitions and latent skills as a lower bound for $I(\tau; z)$.[4] It has been shown previously that such estimators provide a valid lower bound for mutual information [33]. However, to the best of our knowledge, this is the first work to investigate contrastive representation learning for intrinsic control.

Representation Learning: Specifically, we propose to learn embeddings by parameterizing the discriminator with a contrastive density estimator. This is a novel choice that differs from prior works which utilize a classifier [17] or non-contrastive density estimation [20].

$$\log q(\tau|z) \coloneqq f(\tau, z) - \log \frac{1}{N} \sum_{j=1}^{N} \exp(f(\tau_j, z)). \tag{3}$$

where $f(\tau, z)$ is any real valued function.

For our practical algorithm, we parameterize this function as $f(\tau, z) = g_{\psi_1}(\tau)^\top g_{\psi_2}(z)/\|g_{\psi_1}(\tau)\|\|g_{\psi_2}(z)\|T$ where $\tau = (s, s')$ is a transition tuple, g_{ψ_k} are neural

---

[3]In high-dimensional state-action spaces the number of distinct behaviors can be quite large.

[4]Note that τ is not a trajectory but some function of states.

Figure 4: We report the aggregate statistics using stratified bootstrap intervals [35] for 12 downstream tasks on URLB with 10 seeds, so each statistic for each algorithm has 120 seeds in total. We find that overall, CIC achieves leading performance on URLB in terms of the IQM, mean, and OG statistics. As recommended by [35], we use the IQM as our primary performance measure. In terms of IQM, CIC improves upon the next best skill discovery algorithm (APS) by 79% and the next best algorithm overall (ProtoRL) by 18%.

encoders, and T is a temperature parameter. This inner product is similar to the one used in SimCLR [34].

The representation learning loss backpropagates gradients from the NCE loss which maximizes similarity between state-transitions and corresponding skills.

$$F_{CIC}(\tau) = \frac{g_{\psi_1}(\tau_i)^\top g_{\psi_2}(z_i)}{\|g_{\psi_1}(\tau_i)\|\|g_{\psi_2}(z_i)\|T} - \log \frac{1}{N} \sum_{j=1}^{N} \exp\left(\frac{g_{\psi_1}(\tau_j)^\top g_{\psi_2}(z_i)}{\|g_{\psi_1}(\tau_j)\|\|g_{\psi_2}(z_i)\|T} \right)$$

We provide pseudocode for the CIC representation learning loss:

```
"""
PyTorch-like pseudocode for the CIC loss
"""

def cic_loss(s, s_next, z, temp):
    """
    states: s, s_next (B, D), skills: z (B, D)
    """

    tau = concat(s, s_next, dim=1)

    query = query_net(z)
    key = key_net(tau)

    query = normalize(query, dim=1)
    key = normalize(key, dim=1)

    logits = matmul(query, key.T) / temp
    labels = arange(logits.shape[0]) # positives are on diagonal

    loss = cross_entropy(logits, labels) # negatives are off diagonal

    return loss
```

Listing 1: Pseudocode for the CIC loss

Intrinsic reward: Although we have a representation learning objective, we still need to specify the intrinsic reward for the algorithm for which there can be multiple choices. Prior works consider specifying an intrinsic reward that is proportional to state-transition entropy [15], the discriminator [17], a similarity score between states and skills [36], and the uncertainty of the discriminator [37]. We investigate each of these choices in Section 6 and find that an intrinsic reward that maximizes state-transition entropy coupled with representation learning via the CPC loss defined in Sec. 3.1 is the simplest variant that also performs well (see Table 1).

(a) Skill projection   **(b)** Skill dimension   **(c)** Skill adaptation   **(d)** Skill grid sweep

Figure 5: Design choices for pre-training and adapting with skills have significant impact on performance. In (a) and (b) the agent's zero-shot performance is evaluated while sampling skills randomly while in (c) and (d) the agent's performance is evaluated after finetuning the skills vector. *(a)* we show empirically that the projecting skill vectors after sampling them from noise significantly improves the agent's performance. *(b)* The skill dimension is a crucial hyperparameter and, unlike prior methods, CIC scales to large skill vectors achieving optimal performance at 64 dimensional skills. *(c)* We test several adapation strategies and find that a simple grid search performs best given the small 4k step adaptation budget, *(d)* Choosing the right skill vector has substantial impact on performance and grid sweeping allows the agent to select the appropriate skill.

For the intrinsic reward, we use a particle estimate [22, 38] as in [15] of the state-transition entropy. Similar to [15, 16] we estimate the entropy up to a proportionality constant, because we want the agent to maximize entropy rather than estimate its exact value.

The APT particle entropy estimate is proportional to the distance between the current visited state transition and previously seen neighboring points.

$$\mathcal{H}_{particle}(\tau) \propto \frac{1}{N_k} \sum_{h_i^\star \in N_k}^{N_k} \log \|h_i - h_i^\star\| \tag{4}$$

where h_i is an embedding of τ_i shown in Fig. 2, h_i^* is a kNN embedding, N_k is the number of kNNs, and $N-1$ is the number of negatives. The total number of elements in the summation is N because it includes one positive.

Explore and Exploit: With these design choices the two components of the CIC algorithm can be interpreted as *exploration* with intrinsic rewards and *exploitation* using representation learning to distill behaviors into skills. The marginal entropy maximizes the diversity of state-transition embeddings while the contrastive discriminator $\log q(\tau|z)$ encourages exploitation by ensuring that skills z lead to predictable states τ. Together the two terms incentivize the discovery of diverse yet predictable behaviors from the RL agent. While CIC shares a similar intrinsic reward structure to APT [15], we show that the new representation learning loss from the CIC estimator results in substantial performance gains in Sec 6.

4   Practical Implementation

Our practical implementation consists of two main components: the RL optimization algorithm and the CIC architecture. For fairness and clarity of comparison, we use the same RL optimization algorithm for our method and all baselines in this work. Since the baselines implemented in URLB [21] use a DDPG[5] [29] as their backbone, we opt for the same DDPG architecture to optimize our method as well (see Appendix B).

CIC Architecture: We use a particle estimator as in [15] to estimate $\mathcal{H}(\tau)$. To compute the variational density $q(\tau|z)$, we first sample skills from uniform noise $z \sim p(z)$ where $p(z)$ is the uniform distribution over the $[0, 1]$ interval. We then use two MLP encoders to embed $g_{\psi_1}(\tau)$ and $g_{\psi_2}(z)$, and optimize the parameters ψ_1, ψ_2 with the CPC loss similar to SimCLR [34] since $f(\tau, z) =$

---

[5]It was recently was shown that a DDPG achieves state-of-the-art performance [39] on DeepMind Control [40] and is more stable than SAC [41] on this benchmark.

$g_{\psi_1}(\tau)^T g_{\psi_2}(z)$. We fix the hyperparameters across all domains and downstream tasks. We refer the reader to the Appendices E and F for the full algorithm and a full list of hyperparameters.

Adapting to downstream tasks: To adapt to downstream tasks we follow the same procedure for competence-based method adaptation as in URLB [21]. During the first 4k environment interactions we populate the DDPG replay buffer with samples and use the extrinsic rewards collected during this period to finetune the skill vector z. While it's common to finetune skills with Cross Entropy Adaptation (CMA), given our limited budget of 4k samples (only 4 episodes) we find that a simple grid sweep of skills over the interval $[0, 1]$ produces the best results (see Fig. 5). After this, we fix the skill z and finetune the DDPG actor-critic parameters against the extrinsic reward for the remaining 96k steps. Note that competence-based methods in URLB also finetune their skills during the first 4k finetuning steps ensuring a fair comparison between the methods. The full adaptation procedure is detailed in Appendix E.

5 Experimental Setup

Environments We evaluate our approach on tasks from URLB, which consists of twelve downstream tasks across three challenging continuous control domains for exploration algorithms – walker, quadruped, and Jaco arm. Walker requires a biped constrained to a 2D vertical plane to perform locomotion tasks while balancing. Quadruped is more challenging due to a higher-dimensional state-action space and requires a quadruped to in a 3D environment to learn locomotion skills. Jaco arm is a 6-DOF robotic arm with a three-finger gripper to move and manipulate objects without locking. All three environments are challenging in the absence of an extrinsic reward.

Baselines: We implemented CIC using the URLB [21] codebase [6] and compare CIC to baselines included in URLB across all three exploration categories. Knowledge-based basedlines include ICM [12], Disagreement [13], and RND [14]. Data-based baselines incude APT [15] and Pro-toRL [16]. Competence-based baselines include DIAYN [17], SMM [26], and APS [27]. The closest baselines to CIC are APT, which is similar to CIC but without state-skill CPC representation learning (no discriminator), and APS which uses the same decomposition of mutual information as CIC and also uses a particle entropy estimate for $\mathcal{H}(\tau)$. The main difference between APS and CIC is that APS uses successor features while CIC uses a contrastive estimator for the discriminator. For further details regarding baselines we refer the reader to Appendix C.

Evaluation: We follow an identical evaluation to the 2M pre-training setup in URLB. First, we pre-train each RL agent with the intrinsic rewards for 2M steps. Then, we finetune each agent to the downstream task with extrinsic rewards for 100k steps. All baselines were run for 10 seeds per downstream task for each algorithm using the code and hyperparameters provided by URLB [21]. Built on top of URLB, CIC is also run for 10 seeds per task. A total of $1080 = 9$ algorithms $\times$ 12 tasks $\times$ 10 seeds experiments were run for the main results. Importantly, all baselines and CIC use a DDPG agent as their backbone.

To ensure that our evaluation statistics are unbiased we use stratified bootstrap confidence intervals to report aggregate statistics across M runs with N seeds as described in *Rliable* [35] to report statistics for our main results in Fig. 4. Our primary success metric is the interquartile mean (IQM) and the Optimality Gap (OG). IQM discards the top and bottom 25% of runs and then computes the mean. It is less susceptible to outliers than the mean and was shown to be the most reliable statistic for reporting results for RL experiments in [35]. OG measures how far a policy is from optimal (expert) performance. To define expert performance we use the convention in URLB, which is the score achieved by a randomly initialized DDPG after 2M steps of finetuning (20x more steps than our finetuning budget).

6 Results

We investigate empirical answers to the following research questions: (Q1) How does CIC adaptation efficiency compare to prior competence-based algorithms and exploration algorithms more broadly? (Q2) Which intrinsic reward instantiation of CIC performs best? (Q3) How do the two terms in the

---

[6]URLB is open-sourced under an MIT license https://github.com/rll-research/url_benchmark/blob/main/LICENSE.

CIC objective affect algorithm performance? (Q4) How does skill selection affect the quality of the pre-trained policy? (Q5) Which architecture details matter most?

Adaptation efficiency of CIC and exploration baslines: Expert normalized scores of CIC and exploration algorithms from URLB are shown in Fig. 4. We find that CIC substantially outperforms prior competence-based algorithms (DIAYN, SMM, APS) achieving a 79% higher IQM than the next best competence-based method (APS) and, more broadly, achieving a 18% higher IQM than the next best overall baseline (ProtoRL). In further ablations, we find that the contributing factors to CIC's performance are its ability to accommodate substantially larger continuous skill spaces than prior competence-based methods.

Intrinsic reward specification: The intrinsic reward for competence-based algorithms can be instantiated in many different ways. Here, we analyze intrinsic reward for CIC with the form $r_{int} = H(\tau) + D(\tau, z)$, where D is some function of (τ, z). Prior works, select D to be (i) the discriminator [27], (ii) a cosine similarity between embeddings [36], (iii) uncertainty of the discriminator [37], and (iv) just the entropy $D(\tau, z) = 0$ [15]. We run CIC with each of these variants on the walker and quadruped tasks and measure the final mean performance across the downstream tasks (see Tab. 1). The results show that the entropy-only intrinsic reward performs best followed by an uncertainty-based intrinsic reward. We hypothesize that the reason why a simple entropy-only intrinsic reward works well is that state-skill CPC representation learning clusters similar behaviors together. Since similar behaviors are clustered, maximizing the entropy of state-transition embeddings produces increasingly diverse behaviors.

	disc.	similarity	uncertainty	entropy
walker	0.79 ± 0.04	0.79 ± 0.03	0.76 ± 0.04	0.82 ± 0.02
quad.	0.45 ± 0.07	0.60 ± 0.05	0.70 ± 0.03	0.76 ± 0.03
mean	0.62	0.70	0.73	0.80

Table 1: Comparing different potential intrinsic rewards for CIC, we find that entropy-based intrinsic reward performs best, suggesting that the CIC discriminator is primarily useful for representation learning. These are normalized scores averaged over 5 seeds across 8 downstream tasks.

The importance of representation learning: To what extent does representation learning with the state-skill CIC loss affect the agent's exploration capability? To answer this question we train the CIC agent with the entropy intrinsic reward with and without the representation learning auxiliary loss for 2M steps. The zero-shot reward plotted in Fig. 6 indicates that without representation learning the policy collapses. With representation learning, the agent is able to discover diverse skills evidenced by the non-zero reward. This result suggests that state-skill CPC representation learning is a critical part of CIC.

Qualitative analysis of CIC behaviors: Qualitatively, we find that CIC is able to learn locomotion behaviors in DMC without extrinsic information such as early termination as in OpenAI Gym. While most skills are higher entropy and thus more chaotic, we show in Fig 1 that structured behaviors can be isolated by fixing a particular skill vector. For example, in the walker and quadruped domains - balancing, walking, and flipping skills can be isolated. For more qualitative investigations we refer the reader to Appendix I.

Skill architecture and adaptation ablations: We find that projecting the skill to a latent space before inputting it as the key for the contrastive loss is an important design decision (see Fig. 5a), most likely because this reduces the diversity of the skill vector making the discriminator task simpler.

We also find empirically that the skill dimension is an important hyperparameter and that larger skills results in better zero-shot performance (see Fig. 5b), which empirically supports the hypothesis posed in Section 2 and Appendix H that larger skill spaces are important for internalizing diverse behaviors. Interestingly, CIC zero-shot performance is poor in lower skill dimensions (e.g. $\dim(z) < 10$), suggesting that when $\dim(z)$ is small CIC performs no better than prior competence-based methods such as DIAYN, and that scaling to larger skills enables CIC to pre-train effectively.

To measure the effect of skill finetuning described in Section 4, we sweep mean skill values along the interval of the uniform prior $[0, 1]$ with a budget of 4k total environment interactions and read out

Figure 6: Mean zero-shot extrinsic rewards for Quadruped stand over 3 seeds with and without state-skill representation learning. Without representation learning, the algorithm collapses. Similarly, with CIC representation learning but no entropy term (in which case we use the discriminator as the intrinsic reward) the policy also collapses. Note that there is no finetuning happening here. We're showing the task-specific extrinsic reward during reward-free pre-training as a way to sense-check exploration policy.

the performance on the downstream task. By sweeping, we mean simply iterating over the interval $[0, 1]$ with fixed step size (e.g. $v = 0, 0.1, \ldots, 0.9, 1$) and setting $z_i = v$ for all i. This is not an optimal skill sampling strategy but works well due to the extremely limited number of samples for skill selection. We evaluate this ablation on the Quadruped Stand and Run downstream tasks. The results shown in Fig. 5 indicate that skill selection can substantially affect zero-shot downstream task performance.

7 Limitations and Impact

While CIC achieves leading results on state-based URLB, we would also like to address its limitations. First, in this paper we only consider MDPs (and not partially observed MDPs) where the full state is observable. We focus on MDPs because generating diverse behaviors in environments with large state spaces has been the primary bottleneck for competence-based exploration. Combining CIC with visual representation learning to scale this method to pixel-based inputs is a promising future direction for research not considered in this work.

One issue with unsupervised RL algorithms (and hence CIC) in terms of potentially negative societal impact is that self-supervised exploration can be dangerous. Since self-supervised agents maximize intrinsic rewards, this can lead to destructive behavior. For example, when deploying CIC on a Walker or Quadruped robot it learns chaotic exploration behaviors [7] that would most likely break the robot in real-world settings. Alignment of exploration agents to prevent them from learning dangerous policies is a promising direction for future work.

8 Conclusion

We have introduced a new competence-based algorithm – Contrastive Intrinsic Control (CIC) – which enables more effective exploration than prior unsupervised skill discovery algorithms by explicitly encouraging diverse behavior while distilling predictable behaviors into skills with a contrastive discriminator. We showed that CIC is the first competence-based approach to achieve leading performance on URLB. We hope that this encourages further research in developing RL agents capable of generalization.

References

[1] Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Bellemare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, et al. Human-level control through deep reinforcement learning. *Nature*, 518(7540):529, 2015.

---

[7]See https://sites.google.com/view/cicneurips2022/home

[2] David Silver, Julian Schrittwieser, Karen Simonyan, Ioannis Antonoglou, Aja Huang, Arthur Guez, Thomas Hubert, Lucas Baker, Matthew Lai, Adrian Bolton, et al. Mastering the game of go without human knowledge. *Nature*, 550(7676):354, 2017.

[3] David Silver, Thomas Hubert, Julian Schrittwieser, Ioannis Antonoglou, Matthew Lai, Artfhur Guez, Marc Lanctot, Laurent Sifre, Dharshan Kumaran, Thore Graepel, et al. A general reinforcement learning algorithm that masters chess, shogi, and go through self-play. *Science*, 362(6419):1140–1144, 2018.

[4] John Schulman, Philipp Moritz, Sergey Levine, Michael Jordan, and Pieter Abbeel. High-dimensional continuous control using generalized advantage estimation. In *International Conference on Learning Representations*, 2016.

[5] John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

[6] Xue Bin Peng, P. Abbeel, Sergey Levine, and Michiel van de Panne. Deepmimic: Example-guided deep reinforcement learning of physics-based character skills. *ACM Trans. Graph.*, 37:143:1–143:14, 2018.

[7] Aravind Rajeswaran, Vikash Kumar, Abhishek Gupta, Giulia Vezzani, John Schulman, Emanuel Todorov, and Sergey Levine. Learning complex dexterous manipulation with deep reinforcement learning and demonstrations. In *Proceedings of Robotics: Science and Systems (RSS)*, 2018.

[8] OpenAI. Learning dexterous in-hand manipulation. *CoRR*, abs/1808.00177, 2018.

[9] OpenAI. Solving rubik's cube with a robot hand. *ArXiv*, abs/1910.07113, 2019.

[10] Aravind Srinivas and Pieter Abbeel. Unsupervised learning for reinforcement learning, 2021.

[11] Pierre-Yves Oudeyer, Frdric Kaplan, and Verena V Hafner. Intrinsic motivation systems for autonomous mental development. *IEEE transactions on evolutionary computation*, 11(2):265–286, 2007.

[12] Deepak Pathak, Pulkit Agrawal, Alexei A Efros, and Trevor Darrell. Curiosity-driven exploration by self-supervised prediction. In *International Conference on Machine Learning*, 2017.

[13] Deepak Pathak, Dhiraj Gandhi, and Abhinav Gupta. Self-supervised exploration via disagreement. In *International Conference on Machine Learning*, 2019.

[14] Yuri Burda, Harrison Edwards, Amos Storkey, and Oleg Klimov. Exploration by random network distillation. In *International Conference on Learning Representations*, 2019.

[15] Hao Liu and Pieter Abbeel. Behavior from the void: Unsupervised active pre-training. *arXiv preprint arXiv:2103.04551*, 2021.

[16] Denis Yarats, Rob Fergus, Alessandro Lazaric, and Lerrel Pinto. Reinforcement learning with prototypical representations. In *International Conference on Machine Learning*, 2021.

[17] Benjamin Eysenbach, Abhishek Gupta, Julian Ibarz, and Sergey Levine. Diversity is all you need: Learning skills without a reward function. In *International Conference on Learning Representations*, 2019.

[18] Karol Gregor, Danilo Jimenez Rezende, and Daan Wierstra. Variational intrinsic control. In *International Conference on Learning Representations*, 2017.

[19] Taehwan Kwon. Variational intrinsic control revisited. In *International Conference on Learning Representations*, 2021.

[20] Archit Sharma, Shixiang Gu, Sergey Levine, Vikash Kumar, and Karol Hausman. Dynamics-aware unsupervised discovery of skills. In *International Conference on Learning Representations*, 2020.

[21] Michael Laskin, Denis Yarats, Hao Liu, Kimin Lee, Albert Zhan, Kevin Lu, Catherine Cang, Lerrel Pinto, and Pieter Abbeel. Urlb: Unsupervised reinforcement learning benchmark, 2021.

[22] Harshinder Singh, Neeraj Misra, Vladimir Hnizdo, Adam Fedorowicz, and Eugene Demchuk. Nearest neighbor estimates of entropy. *American Journal of Mathematical and Management Sciences*, 23(3-4):301–321, 2003.

[23] Michael Gutmann and Aapo Hyvärinen. Noise-contrastive estimation: A new estimation principle for unnormalized statistical models. In Yee Whye Teh and Mike Titterington, editors, *Proceedings of the Thirteenth International Conference on Artificial Intelligence and Statistics*, volume 9 of *Proceedings of Machine Learning Research*, pages 297–304, Chia Laguna Resort, Sardinia, Italy, 13–15 May 2010. PMLR.

[24] Richard S Sutton and Andrew G Barto. *Reinforcement learning: An introduction*. MIT Press, 2018.

[25] Joshua Achiam, Harrison Edwards, Dario Amodei, and Pieter Abbeel. Variational option discovery algorithms. *arXiv preprint arXiv:1807.10299*, 2018.

[26] Lisa Lee, Benjamin Eysenbach, Emilio Parisotto, Eric P. Xing, Sergey Levine, and Ruslan Salakhutdinov. Efficient exploration via state marginal matching. *CoRR*, abs/1906.05274, 2019.

[27] Hao Liu and Pieter Abbeel. APS: active pretraining with successor features. In *International Conference on Machine Learning*, 2021.

[28] David Barber and Felix V. Agakov. The im algorithm: A variational approach to information maximization. In *Advances in neural information processing systems*, 2003.

[29] Timothy P. Lillicrap, Jonathan J. Hunt, Alexander Pritzel, Nicolas Heess, Tom Erez, Yuval Tassa, David Silver, and Daan Wierstra. Continuous control with deep reinforcement learning. In *International Conference on Learning Representations*, 2016.

[30] André Barreto, Will Dabney, Rémi Munos, Jonathan J Hunt, Tom Schaul, Hado Van Hasselt, and David Silver. Successor features for transfer in reinforcement learning. *arXiv preprint arXiv:1606.05312*, 2016.

[31] Steven Hansen, Will Dabney, André Barreto, David Warde-Farley, Tom Van de Wiele, and Volodymyr Mnih. Fast task inference with variational intrinsic successor features. In *International Conference on Learning Representations*, 2020.

[32] Greg Brockman, Vicki Cheung, Ludwig Pettersson, Jonas Schneider, John Schulman, Jie Tang, and Wojciech Zaremba. Openai gym. *arXiv preprint arXiv:1606.01540*, 2016.

[33] Aaron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*, 2018.

[34] Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey E. Hinton. A simple framework for contrastive learning of visual representations. In *International conference on machine learning*, 2020.

[35] Rishabh Agarwal, Max Schwarzer, Pablo Samuel Castro, Aaron Courville, and Marc G. Bellemare. Deep reinforcement learning at the edge of the statistical precipice, 2021.

[36] David Warde-Farley, Tom Van de Wiele, Tejas Kulkarni, Catalin Ionescu, Steven Hansen, and Volodymyr Mnih. Unsupervised control through non-parametric discriminative rewards, 2018.

[37] DJ Strouse, Kate Baumli, David Warde-Farley, Vlad Mnih, and Steven Hansen. Learning more skills through optimistic exploration. *CoRR*, abs/2107.14226, 2021.

[38] J Beirlant. Nonparametric entropy estimation: An overview. *International Journal of the Mathematical Statistics Sciences*, 6:17–39, 1997.

[39] Denis Yarats, Rob Fergus, Alessandro Lazaric, and Lerrel Pinto. Mastering visual continuous control: Improved data-augmented reinforcement learning, 2021.

[40] Yuval Tassa, Yotam Doron, Alistair Muldal, Tom Erez, Yazhe Li, Diego de Las Casas, David Budden, Abbas Abdolmaleki, Josh Merel, Andrew Lefrancq, et al. Deepmind control suite. *arXiv preprint arXiv:1801.00690*, 2018.

[41] Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *International Conference on Machine Learning*, 2018.

[42] Carlos Florensa, Yan Duan, and Pieter Abbeel. Stochastic neural networks for hierarchical reinforcement learning. In *International Conference on Learning Representations*, 2018.

[43] Mathilde Caron, Ishan Misra, Julien Mairal, Priya Goyal, Piotr Bojanowski, and Armand Joulin. Unsupervised learning of visual features by contrasting cluster assignments. In *Advances in Neural Information Processing Systems*, 2020.

[44] Tom Zahavy, Andre Barreto, Daniel J Mankowitz, Shaobo Hou, Brendan O'Donoghue, Iurii Kemaev, and Satinder Baveja Singh. Discovering a set of policies for the worst case reward, 2021.

[45] Michael Laskin, Aravind Srinivas, and Pieter Abbeel. Curl: Contrastive unsupervised representations for reinforcement learning. In *International Conference on Machine Learning*, 2020.

[46] Ben Poole, Sherjil Ozair, Aäron van den Oord, Alex Alemi, and George Tucker. On variational bounds of mutual information. In Kamalika Chaudhuri and Ruslan Salakhutdinov, editors, *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*, volume 97 of *Proceedings of Machine Learning Research*, pages 5171–5180. PMLR, 2019.

[47] Michael Tschannen, Josip Djolonga, Paul K. Rubenstein, Sylvain Gelly, and Mario Lucic. On mutual information maximization for representation learning. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020.