Adaptive Retrieval-Augmented Generation for Conversational Systems

Abstract

With the success of integrating large language models into the development of conversational systems, many studies have shown the effectiveness of retrieving and augmenting external knowledge for informative responses. While many existing studies agree on the necessity of Retrieval Augmented Generation (RAG), further investigation about the necessity and value of applying RAG to every turn of the conversation is needed. In this study, we propose to investigate the need for each turn of system response to be augmented with external knowledge. In particular, by leveraging human judgements on the binary choice of adaptive augmentation, we develop *RAGate*, a gating model, which models conversation context and relevant inputs to predict if a conversational system requires RAG for improved responses. We conduct extensive experiments on devising and applying *RAGate* to conversational models, joined with well-rounded analyses on various conversational scenarios. Our experimental results and analysis indicate the effective application of *RAGate* in RAG-based conversational systems in identifying if system responses require RAG for generating high-quality responses with high confidence. This study also identifies and shows the correlation between the generation's confidence level and the relevance of the augmented knowledge.

1 Introduction

Recently, the advancement of Large Language Models (LLMs) has significantly improved conversational systems, enabling the generation of natural and high-quality responses (Ni et al., 2023). Despite these advancements, recent studies have identified several limitations on the simple use of LLMs to address conversational tasks (Onoe et al., 2022; Huang et al., 2021; Ren et al., 2018). These limitations include the lack of up-to-date knowledge (Onoe et al., 2022), the generation of

Figure 1: Example conversation when generating a response with or without a knowledge snippet using a language model (GPT-4 in this example).

non-factual or hallucinated content (Huang et al., 2021), and restricted domain adaptability (Ren et al., 2018). These issues can hinder the development of conversational agents with satisfactory user experience. To address these identified challenges, a common approach is to retrieve and augment LLMs with external knowledge to enhance the conversational response, making them more accurate, reliable, and adaptable to different domains (Zhao et al., 2020; Lian et al., 2019; Ye et al., 2024). For example, Shuster et al. (2021) demonstrated that using a dense retrieval model (DPR) (Karpukhin et al., 2020) to retrieve relevant knowledge for augmentation can significantly reduce the hallucination rate, according to a corresponding human evaluation. Similarly, Yang et al. (2020) showed that leveraging a graph-structured knowledge base can boost the reasoning ability and domain generalisability of task-oriented conversational agents. These achievements of knowledge-augmented techniques high-

light a promising direction for enhancing conversational agents and address the current limitations.

However, while implementing retrieval augmentation to a conversational system for improved response generation, we question the necessity of knowledge augmentation for every turn of system responses. To develop effective human-computer conversations, it is essential to provide factual and relevant responses, offer *appropriate* amount of information, and not unnaturally drive and shift the conversation to non-relevant topics (Kasirzadeh and Gabriel, 2023; Miehling et al., 2024). We argue that overusing external knowledge could result in system responses against these core criteria. Figure 1 presents a conversation example that shows how the system response to a generic user utterance about suggesting activities can vary with and without augmented knowledge. The knowledge-augmented system response is being information conditioned with limited diversity and assuming specific user preferences. In contrast, without the addition of external knowledge, the system response is more diverse and natural in this early stage of a conversation. This indicates that misusing external knowledge can lead to system responses with unnecessary or misleading specificness and a negative user experience.

To address this, we investigate an adaptive retrieval-augmented generation solution for effective conversational systems. In particular, motivated by the gate function in Long-Short Term Memory (LSTM) models (Graves and Graves, 2012), which explicitly controls the use of input and memory, we propose a binary knowledge gate mechanism, called *RAGate*, to manipulate the use of external knowledge for a conversational system. To model the conversation context and accurately estimate the need for augmentation, we leverage the human labels as ground truth and develop RAGate by exploring the use of recent advanced language models or constructing attention neural gate models. To validate the effectiveness of RAGate, we conduct extensive experiments on an annotated Task-Oriented Dialogue (TOD) system dataset, KETOD, that builds upon the SGD dataset with TOD-spanning 16 domains, such as Restaurant and Weather. The experimental results show that RAGate enables conversational systems to efficiently use external knowledge at appropriate conversation turns, producing high-quality system responses. In particular, by modelling the uncertainty and confidence level of the system – which correlates with the likelihood of hallucinated output (Varshney et al., 2023) – we show that augmenting external knowledge to every turn of conversation can significantly increase generation uncertainty and the risk of hallucination. After applying RAGate, we can effectively control the conversation system to make confident and informative responses. In addition, by varying the use of knowledge snippets in different relevance levels, we also observe the positive correlation between the calculated confidence score and the relevance of augmented knowledge, which can be valuable for many future studies.

2 Related Work

In the pipeline of knowledge-augmented generation for a conversation system, two main components are identified: the knowledge retriever and the response generator. Existing studies have improved conversational responses to different extents by improving one or both components (Li et al., 2022; Komeili et al., 2022; Wang et al., 2024).

Knowledge Retrieval: Several studies have explored the use of dense passage retrieval techniques (Lewis et al., 2020; Karpukhin et al., 2020) and public search service for effective retrievers (Li et al., 2022). For example, Li et al. (2022) retrieved Wikipedia passages through a database interface and then ranked them according to statistical relevance, calculated by TF-IDF, or semantic relevance as per cosine similarity. Similarly, Komeili et al. used a search engine API to retrieve relevant knowledge but first transformed the dialogue context into a natural search query using an encoder-decoder model before searching.

Joint Optimisation of Retriever and Generator: On the other hand, another thread of research studies has explored joint optimisation approaches. For instance, Shi et al. (2023) introduced a retriever-generator architecture that aims to improve the performance of Task-Oriented Dialogue (TOD) systems by using a dual-feedback mechanism. The retriever identifies relevant knowledge from a database, while the generator uses this information to create appropriate system responses. The feedback from the generator is further used as pseudo-labels to train the retriever to select pertinent information. Shen et al. (2023) introduced a training method based on maximal marginal likelihood. This method jointly optimise a perceptive retriever and the response generation in a feed-

Figure 2: *RAGate* variants for implementing the gating function. The three variants are the prediction with pre-trained language models after prompting (1), after parameter-efficient fine-tuning (2), and with a multi-head attention encoder (3).

back loop. The proposed approach incorporates meta-knowledge, which guides the generator to improve the utilisation of knowledge and, consequently, the quality of the generated responses. Kang et al. (2023) further advance the retriever by proposing SUbgraph Retrieval-augmented GEneration (SURGE), which employed a graph neural network (GNN)-based context-relevant subgraph retriever. SURGE incorporates contrastive learning to optimise the latent representation space, ensuring that generated texts closely resemble the retrieved subgraphs.

Despite the richness of existing retrieval-augmented generation techniques for conversational systems, they commonly hypothesise that every conversation turn needs external knowledge. However, the necessity of augmenting every turn of the conversation with external knowledge remains questionable. A relevant thread of work that aims to answer this question is the introduction of the knowledge-seeking turn detection task using the DSTC-9 dataset (Kim et al., 2020), and the follow-up studies, such as (Hong et al., 2023; Jin et al., 2021). However, this task is to identify the turns in conversations injected by human workers about knowledge enquiry instead of identifying the system responses that require knowledge augmentation for improvements. This research gap highlights the value and novelty of this study, which investigates the adaptive use of retrieval-augmented generation for advanced conversational systems.

3 Methodology

3.1 Problem Formulation

This study addresses the challenge of effectively identifying conversation turns that require augmentation of external knowledge. In particular, we aim to develop a gate mechanism that dynamically determines when to search for external knowledge to ensure natural, relevant and contextually appropriate responses. First, we define the task of user-system conversation. Let $D = \{d_1, d_2, ..., d_{|D|}\}$ be a set of user-system dialogues, and each dialogue d comprises a sequence of interactions between users and systems (i.e., $d = \{u_0, s_0, u_1, s_1, ..., u_T, s_T\}$) with varying lengths. Here, u_t and s_t denote the user utterance and system response at the t-th turn, respectively. The conversational context up to turn t can be formulated by aggregating the previous user-system interactions, i.e., $c_t = u_0, s_0, .., u_t$. With this context information c_t, the conversation system can augment it with a list of retrieved external knowledge, $e_{t,k}$, where k represents the ranking cutoff for the retrieved knowledge. Hence, the binary gate mechanism proposed in this study, deciding the knowledge augmentation, can be formulated as $f(c_t) = \{0, 1\}$ or $f(c_t, e_{t,k}) = \{0, 1\}$ if the external knowledge $e_{t,k}$ is considered. Then, the follow-up response generation function $g(\cdot)$ can be formulated as follows:

$$g(\cdot) = \begin{cases} g(c_t, e_{t,k}) & \text{if } f(c_t) \text{ or } f(c_t, e_{t,k}) \\ g(c_t) & \text{otherwise.} \end{cases} \quad (1)$$

Hence, by evaluating and estimating the necessity of augmenting with external knowledge, we dynamically update the conversational response generation accordingly.

3.2 RAGate Gate Mechanism

To effectively estimate the need to use external knowledge and implement adaptive retrieval augmented generation for a conversation system, we introduce our proposed gate mechanism, RAGate,

that uses the conversational context and, optionally, the retrieved external knowledge to predict the binary choice of using external knowledge. In particular, we explore three RAGate variants that are implemented by the use of Large Language Models (LLMs) with devised prompts, with parameter efficient fine-tuning (e.g., QLoRA (Dettmers et al., 2024)) and the construction of an end-to-end multi-head attention encoder. This exploration is motivated by the recent advancement of transformer-structured neural models in natural language processing. In Figure 2, we illustrate the application of RAGate and its three variants. We describe each of these three variants to clarify the use of RAGate:

RAGate-Prompt: As denoted by Arora et al. (2022), a language model can effectively adapt to new tasks by using a natural language prompt that explains the process to address the tasks without extra training. Hence, we can formulate a gate function $f(\cdot)$ as $f(y|c_t) = f(y|\Theta, c_t, p)$, where Θ denotes the used language model with its pre-trained weights and p is the devised natural language prompt. Alternatively, if the retrieved knowledge is also involved in prediction, we have $f(y|c_t) = f(y|\Theta, c_t, e_{t,k}, p)$. Specifically, we explore two types of prompts: zero-shot and in-context learning. Zero-shot prompts describe the task that uses the conversational context and, optionally, the retrieved knowledge to generate a response with binary feedback. As for the in-context learning prompts, we augment the zero-shot prompts with illustrative examples. We show the set of prompts in Appendix A.

RAGate-PEFT: Despite the high adaptability of the language model with devised prompts, we further explored the use of instruction tuning on language models with a parameter-efficient fine-tuning method (i.e., QLoRA (Dettmers et al., 2024)) to meet the goal of an effective gate function. QLoRA is built upon the known Low-rank Adapter (LoRA) (Hu et al., 2021), which keeps the pre-trained weight matrix W_0 frozen and addresses the gradient updates of the weight matrix ΔW through low-rank approximation (i.e., $\Delta W = BA$, where B and A are the result of lower-rank decomposition on ΔW). Hence, the forward pass during the model training can be updated from $h = W_0 x + \Delta W x$ to $h = W_0 x + BAx$. QLoRA (Dettmers et al., 2024), which is used in this study, further quantises the language model into a 4-bit NormalFloat data type and leverages the page-to-page transfer between the CPU and GPU to fur-

ther avoid memory spikes. To implement RAGate-PEFT, we format the train data with devised instructions, joined with paired inputs and outputs for developing parameter-efficient fine-tuned large language models. In particular, we provide a set of instruction-input-output triples for model training. The input can vary with the provision of a set of available features. Apart from the use of the conversational context (contx), we also include the system response (resp), synthetic responses generated by the language model (syn-resp) due to the missing responses as input in the practical scenario, the name entities within the incoming responses (ner), retrieved knowledge (know) and the description of the knowledge source, e.g., the WikiHow website (source). By using various combinations of inputs and customising the corresponding instructions, we explore the effectiveness of the resulting learned language models that implement the RAGate-PEFT.

RAGate-MHA: Apart from the use of pre-trained language models and further fine-tuned language models, we also explore the introduction of a multi-head attention neural encoder to model the context as input and estimate the augmentation necessity (i.e., RAGate-MHA). Here, we describe the model structure of RAGate-MHA. At first, as denoted by (Vaswani et al., 2017), the attention mechanism is formulated as the interaction between three objects, queries Q, keys K, and values V: $Attention(Q, K, V) = \text{softmax}(\frac{QK^T}{\sqrt{d_k}})V$. To estimate the necessity of augmentation, we fit the context and the retrieved knowledge into the roles of these three objects. Specifically, we include the setups of (1) using context only (*contx*) or (2) using the concatenated context and retrieved knowledge (*contx* $\oplus$ *know*) as queries, keys, and values, and (3) using the context as queries and interact with the retrieved knowledge as keys and values (*contx* $\times$ *know*). Next, following (Vaswani et al., 2017) in the encoder construction of a transformer model, we encode the inputs via an input embedding layer into latent vectors and a position encoding layer to encode the order of tokens in the sequence. After that, we leverage the multi-head attention to learn attention weights on the inputs and then followed by a feed-forward network:

$$FFN(x) = \max(0, xW_1 + b_1)W_2 + b_2 \quad (2)$$

where W_1 and W_2 are two learned parameter matrics with two bias terms (b_1 and b_2). Both multi-head attention and feed-forward neural modules are

Retrieval Models	Recall@1	Recall@3
TF-IDF	0.0227	0.0871
BERT-Ranker	0.2475	0.4714

Table 1: Retrieval Performance Evaluation when using context as the query.

followed by residual connection (He et al., 2016) and layer normalisation (Ba et al., 2016). Unlike the introduction of another decoder module that addresses the sequence-to-sequence generation in (Vaswani et al., 2017), we followed the encoder output with a linear projection module and a softmax function for our binary classification task.

4   Model Training and Evaluation Setups

We evaluate the performance of introducing RAGate according to its binary classification performance and the effectiveness of the resulting response generation. Specifically, we use the KETOD dataset (Chen et al., 2022), which has fully annotated 5,324 dialogues and 52,063 turns of conversations. In particular, it is associated with 33,761 knowledge snippets to be retrieved and augmented. In addition, KETOD was developed with human labels on turns of conversations (around 12.1% of turns) about the need for augmenting with retrieved knowledge snippets for a natural and informative system response. Hence, we use these human labels as natural ground truths when evaluating RAGate. It is worth indicating that many current knowledge-augmented conversational datasets often ground their conversations on the knowledge snippet, such as Wizard of Wikipedia (Dinan et al., 2018) and CMU_DoG (Zhou et al., 2018), which makes them not a natural fit to be investigated in this study.

Due to the limited computational resource availability, we explore the use of Llama-v2-7B and Llama-v2-13B to implement RAGate-prompt and fine-tune Llama-v2-7B for RAGate-PEFT. We implement QLoRA using the PEFT library (Mangrulkar et al., 2022) and set the lower rank to 16. As discussed in Section 3, we have various input features to be combined for performance optimisation. We begin with the use of context only, then concatenate the context with the real response (contx-resp), with the synthetic response and recognised entities (contx-syn-resp-ner) and further extend with the use of retrieved knowledge (contx-syn-resp-ner-know) or the source of knowledge (contx-syn-resp-ner-source). Specifically, we retrieve the relevant knowledge by exploring the use of TF-IDF and

a learned BERT ranker. We evaluate their performance with the classic Recall@1 and Recall@3 on the test collection. We use a shallow cutoff because we only use top-relevant knowledge snippets for augmentation. Table 1 shows their retrieval performance. According to the leading performance of BERT-Ranker, we augment knowledge with its retrieved top 3 relevant knowledge snippets (i.e., $k = 3$). Regarding the development of RAGate-MHA, we explore the combinations of 2 to 8 layers, 2 or 4 heads and the embedding size in [64, 128, 256] for the best classification accuracy. We report the precision, recall, F1, Area Under Curve (AUC) and the False Discovery Rate (FDR) as the main measures to show the classification effectiveness.

Next, we further deploy the best-performing RAGate gate function to update the KETOD dialogue system (Chen et al., 2022), which uses GPT-2 (Radford et al., 2019) as the backbone model. To highlight the effect of various augmentation setups, we use the context with the gold action without extra prediction as input to KETOD. Then, we compare the resulting performance to the KETOD model without knowledge augmentation and augmenting every system response as baselines. To report the response generation effectiveness, we report how close the response is to the ground truth via BLEU, ROUGE-1/2/L and BERTScores and the confidence score calculated by the minimum probabilities of individual tokens that compose the response. As argued by Varshney et al. (2023), this calculated confidence score can highly correlate with a language model's likelihood of generating hallucinated responses. We trained our models and conducted the evaluations on one machine with one NVIDIA 4090 GPU.

5   Results and Analysis

5.1   Augmentation Need Classification

First, we evaluate the classification accuracy of our developed RAGate gate methods for addressing the adaptive RAG to system responses. Table 2 presents the classification performance of RAGate baselines while evaluated on the test collection of the KETOD dataset, which includes rich human labels on the use of RAG for response generation. As discussed in Section 3, we explore the development of RAGate with three variants: the use of LLM prompting (RAGate-Prompt), parameter-efficient fine-tuned LLMs (RAGate-PEFT), and a neural classifier with Multi-Head Attention struc-

Model Variants	Precision	Recall	F1
RAGate-Prompt: LLMs – Zero Shot			
Llama-2-7B	0.1323	0.0278	0.0460
Llama-2-13B	0.1422	0.1083	0.1230
RAGate-Prompt: LLMs – In-Context Learning			
Llama-2-7B	0.1417	0.0294	0.0487
Llama-2-13B	0.0989	0.0851	0.0915
RAGate-PEFT: Parameter Efficient Fine-tuned LLMs (Llama2-7B)			
[contx⊕resp]	0.4926	0.3095	0.3802
contx-only	0.5203	0.3359	**0.4082**
contx-(syn-resp)-ner	**0.6818**	0.2321	0.3464
contx-(syn-resp)-ner-know	0.4698	0.0603	0.1069
contx-(syn-resp)-ner-source	0.4000	0.0185	0.0355
RAGate-MHA: Context with / without Knowledge Input			
MHA(contx)-h(4)-l(5)-emb(64)	0.3210	0.5541	0.4065
MHA([contx⊕know])-h(4)-l(2)-emb(64)	0.2795	0.5201	0.3636
MHA(contx×know)-h(4)-l(2)-emb(64)	0.2272	**0.5835**	0.3271
RAGate-MHA: Context-Response Input			
MHA([contx⊕resp])-h(4)-l(4)-emb(64)	0.3500	0.5510	0.4281

Table 2: Classification accuracy on adaptive augmentation for system response. "contx", "resp", and "know" refer to the use of context, initial system response, and retrieved knowledge snippets as input. "syn-resp" and "ner" are the additional synthetic response and name entity recognition steps in the model fine-tuning prompts. *h*, *l* and *emb* refer to the best-performed configuration on the number of heads, layers and embedding size.

ture (RAGate-MHA).

RAGate performance with LLM prompting versus fine-tuning. By comparing the corresponding performance reported in Table 2, we observe that, on average, fine-tuning a Llama-2-7B with QLoRA (i.e., RAGate-PEFT) can significantly outperform RAGate-Prompt. For example, by looking at the RAG-PEFT with context-only input, without using extra input features and instruction updates, it can outperform all RAG-Prompt approaches by a big margin (e.g., 0.4082 versus the highest 0.1230 F1 scores). This reflects the difficulty of this adaptive knowledge augmentation task, which can not be properly addressed by prompting a general pre-trained language model. In particular, the use of larger language models and the in-context learning setup, which often result in improved performance (Arora et al., 2022), can not guarantee the enhancement of models' classification accuracy regarding this classification task.

Regarding the performance of RAGate-PEFT approaches, by first examining the effect of using synthetic response and recognised name entities, we observe significantly improved precision (0.5203 to 0.6818) but with the cost of lower recall (0.3359 to 0.2321). In addition, when we add the

retrieved knowledge to the input features for prediction, we observe a significant performance drop across all evaluated aspects. This can be caused by the additional complexity introduced by the included retrieved knowledge snippets. Furthermore, we also explored the performance impact of naming the source of the knowledge snippet. We use wikiHow[1] in this study, which can provide rich task instructions for offering informative task-oriented system response (Sen et al., 2023). However, the fine-tuned model cannot reasonably connect the promised rich resource from the knowledge source and the prediction of augmentation necessity.

RAGate Performance between fine-tuned LLM and MHA classifier. Next, by comparing the experimental results of RAGate-MHA and RAGate-PEFT in Table 2, we observe a wide-margin recall improvement using RAGate-MHA, reaching a minimum recall of 0.52, but with significantly lower precision accuracy. In Table 2, we also include the use of both the context and the initial system responses (i.e., MHA([contx, resp])) for additional insights. We can observe that a higher precision can be achieved but the use of response does not improve the recall performance. These results are consistent with the observed performance of RAGate-PEFT, which further encourages the use of a synthetic response due to the unavailability of a system response in a practical scenario. In addition, we also observe a similar performance drop when including the retrieved knowledge snippets for classification. Even though the RAGate-MHA model, using the interaction between context and retrieved knowledge snippets, can achieve the highest recall of 0.5835, it can not outperform the RAGate-MHA using context-only on other metrics. Hence, considering the similar F1 and AUC performance levels of RAGate-PEFT and RAGate-MHA leads to a trade-off balance between precision and recall for the two groups of approaches. To further evaluate the classification effectiveness of RAGate, in Appendix C, we provide a detailed discussion of a conducted user study that explores whether RAGate can also assess the potential contribution of retrieved snippets when predicting the decision for retrieval augmentation.

5.2 Adaptive Augmentation Analysis

In addition to the classification accuracy, we also compare the choice of human workers and RA-

---

[1]https://www.wikihow.com

Figure 3: Frequency analysis of adaptive augmentations about the position of a conversation.

Figure 4: Frequency analysis of adaptive augmentations about dialogue domains.

Variants	# Augs	BLEU	ROUGE-L	BERTScore	Confidence	
No-Aug	0	9.38	0.3780	0.8105	9.3425	–
Augment BERT Ranker Retrieved Knowledge						
RAGate-PEFT	230	10.45●	0.3825●	0.8144●	9.3374●	-0.05%
RAGate-MHA	787	12.14 ○●	0.3882 ○	0.8192 ○	9.3083 ○●	-0.36%
Random-Aug	230	9.53●	0.3784●	0.8110●	9.2984○●	-0.47%
Random-Aug	787	10.01●	0.3795●	0.8126●	9.1877○●	-1.65%
Human-label	631	11.66 ○●	0.3856○	0.8176○	9.2550○●	-0.93%
Aug-All	4964	16.08○	0.3927○	0.8258○	8.3677○	-10.43%
Augment Rank-1 Relevant Knowledge						
RAGate-PEFT	230	10.54●	0.3822●	0.8142●	9.3642○●	+0.23%
RAGate-MHA	787	11.99○●	0.3883○	0.8191●	**9.3774**○●	+0.37%
Random-Aug	230	9.51●	0.3784●	0.8110●	9.3328●	-0.10%
Random-Aug	787	10.01●	0.3800●	0.8127●	9.2982○●	-0.47%
Human-label	631	11.52○●	0.3846○	0.8170○	9.3218●	-0.22%
Aug-All	4964	16.05○	0.3944○	0.8259○	9.0655○	-2.9%

Table 3: Performance of applying RAGate and evaluate on the KETOD dataset. Confidence is calculated by the average value over the lowest logit of each generation. The significant difference compared to No-Aug or the corresponding Aug-all is indicated by ○ and ●, respectively, when p-value < 0.05, calculated by Wilcoxon signed-rank test.

Gate approaches in augmenting specific turns. Specifically, we analyse the frequency of augmentation in different positions of conversations and different domains covered in the KETOD dataset. We use the RAGate-PEFT (contx-(syn-resp)-ner) with the highest precision and RAGate-MHA (MHA(contx)) with the best overall performance in the above analysis as representatives for comparison. Figure 3 presents the frequency in different positions. Due to the unequal number of conversational turns, we use the ratio to indicate the relative position. According to the reported results in Figure 3, most human augmentation selections happen at the beginning of a conversation. This trend is also effectively captured by both RAGate approaches, especially RAGate-MHA. This can be caused by the reason that a conversation is semantically coherent, and once sufficient additional information is provided at the early stage, the value of knowledge augmentation to the later turns is naturally lower.

On the other hand, Figure 4 presents the augmentation frequency over different domains. We observe that system responses about certain domains are selected more often by humans than other domains, such as travel, hotels, trains, flights, service and rental cars, which require access to additional information to assist the *suggestion-making*, and the domains, like movies, music, media, events that often include entities require *enriched description*. By looking into the performance of RAGate-PEFT and RAGate-MHA, RAGate-MHA can make aligned selections for humans. However, the RAGate-PEFT does not guarantee the identification of appropriate augmentation use and often presents fewer augmentations, apart from the travel domain. Hence, by considering both position and domain augmentation frequency, we conclude that RAGate-MHA can outperform RAGate-MHA and effectively capture the trend of augmentation needs.

5.3 RAGate for Response Generation

To evaluate the effect of adaptive RAG for a conversational system, we use RAGate-PEFT (contx-(syn-resp)-ner) with the highest precision and RAGate-MHA (MHA(contx)) with the best overall performance in the above analysis, to support the adaptive retrieval augmented conversational response generation. Table 3 presents the results of applying RAGAte to the KETOD model for adaptive knowledge augmentation when evaluated on the KETOD dataset. We include four types of adaptive augmentation, namely the use of RAGate and comparison to the random selection with equal numbers of selections, human choice, and the commonly used "all" augmentation. In addition, to explore the effect of varied quality of knowledge snippets, we

also extend the evaluation of using the top-3 knowledge snippets ranked by different retrievers (i.e., BERT-ranker and TF-IDF) and the use of knowledge snippets at the 1st and 5th rank according to the BERT-ranker. Due to the space limit, we first present the results of using BERT-ranker retrieved and top-1 relevant knowledge and top-1 relevant in Table 3 and show the full results in the Appendix D.

At first, without adaptive knowledge augmentation, we compare the choice of response generation without augmentation and with "always" augmentation (i.e., No-Aug versus Aug-All). In Table 3, we observe that by augmenting a total of 4,964 system responses in the test collection, the conversational model can generate more informative and effective responses according to the reported scores of BLEU, ROUGE and BERTscore. This aligns with the reported effectiveness of RAG in many existing studies. However, we also identify a significant drop in the model's generation confidence level. As denoted by Varshney et al. (2023), a lower confidence level can correlate with a higher chance of generating hallucinated responses, which could be caused by the unnecessary use of external knowledge. Hence, to investigate the effectiveness of adaptive knowledge augmentation, we examine the impact of using RAGate. According to the reported experimental results in Table 3, the adaptive augmented response generation with fewer knowledge snippets can indeed result in a significantly higher confidence level than Aug-All.

Moreover, comparing the performance between RAGate and random selections shows that, considering equal numbers (230 or 787 according to the classification with RAGate) of system responses for augmentation, RAGate can further result in a higher quality of generated response. RAGate-MHA even enables results that are comparable to Aug-All's response quality, with only 787 turn augmentations instead of all 4964 turns. Specifically, the use of RAGate-PEFT, which identifies 230 turns of system responses for knowledge augmentation, can even outperform the random baseline that augments 787 system response turns with improved response quality. Apart from the improved response quality, RAGate also enables the conversational model to maintain a high confidence level and ensure faithful responses. Indeed, using RAGate-MHA, which augments 787 system responses, only lowers the average confidence score by 0.36%, instead of the 1.65% when randomly selecting an equal number of turns to augment.

In addition, considering the use of different quality and amount of knowledge snippets for augmentation, we also include the use of the most relevant knowledge snippet according to BERT-ranker in Table 3. We observe that the use of different amounts of knowledge snippets in different relevance levels has a marginal effect on this learned dialogue system. However, we observe a significant difference in the confidence level. We observe that using only the most relevant knowledge snippet enables the Aug-All to suffer less from a lower confidence level. In particular, the application of RAGate can even increase the confidence level of the conversation system in response generation. This indicates that the confidence score can also correlate with the quality of the augmented knowledge snippets. This observation is further validated using knowledge snippets with fifth-ranking positions by BERT-ranker and the use of TF-IDF ranker. We include the full experimental results in Table 5 and attached in the Appendix. In addition, we also extend our evaluations to replace the conversational agent with large pre-trained language models, llama-2-7B and llama-2-70B (see Appendix B) and obtain similar conclusions. These observations indicate the value of adaptive system response augmentation via RAGate in generating high-quality outputs, ensuring faithful responses, and potentially saving retrieval costs. We also show the value of using confidence scores to reflect the contribution of RAG.

6 Conclusions

Our study investigates a core research question about whether retrieval-augmented generation is always useful to a conversational system. To answer this research question, we propose adaptive retrieval-augmented generation for conversational systems and introduce corresponding gate functions, RAGate, for explicit control. A comprehensive set of experiments and results show the RAGate approaches can effectively identify augmentation needs. In addition, RAGate can capture human preference by augmenting the beginning turns of conversations, and RAGate can further identify knowledge augmentation for assisting suggestion-making and enriching description. When applying RAGate to conversational systems, we observe that it can ensure comparable quality of generated responses and enable the system to increase generation confidence for faithful outputs, especially with the appropriate use of relevant knowledge snippets.

Limitations

There are three limitations of this study. At first, due to the main focus of examining the adaptive retrieval-augmented generation for a conversation system. We only consider a few examples of retrieval techniques (TF-IDF and BERT-ranker), which can be further extended to recent retrieval techniques, such as dense passage retrieval for additional insights. The second limitation is the missing use of larger language models, such as GPT-4, due to the shortage of computational resources. Including larger language models for conversational systems could introduce additional experimental insights. The third limitation is the shortage of appropriate conversational data for extensive evaluations. This is mainly caused by the recent development of the retrieval augmented generation technique and its application to conversational systems. Future research is encouraged to address this limitation.

Ethics Statement

All experiments in this study were conducted using publicly available datasets and open-released language models, which do not contain any private information that could raise ethical concerns.

References

Simran Arora, Avanika Narayan, Mayee F Chen, Laurel Orr, Neel Guha, Kush Bhatia, Ines Chami, and Christopher Re. 2022. Ask me anything: A simple strategy for prompting language models. In *The Eleventh International Conference on Learning Representations*.

Jimmy Lei Ba, Jamie Ryan Kiros, and Geoffrey E Hinton. 2016. Layer normalization. *arXiv preprint arXiv:1607.06450*.

Zhiyu Chen, Bing Liu, Seungwhan Moon, Chinnadhurai Sankar, Paul A Crook, and William Yang Wang. 2022. Ketod: Knowledge-enriched task-oriented dialogue. In *Findings of the Association for Computational Linguistics: NAACL 2022*, pages 2581–2593.

Tim Dettmers, Artidoro Pagnoni, Ari Holtzman, and Luke Zettlemoyer. 2024. Qlora: Efficient finetuning of quantized llms. *Advances in Neural Information Processing Systems*, 36.

Emily Dinan, Stephen Roller, Kurt Shuster, Angela Fan, Michael Auli, and Jason Weston. 2018. Wizard of wikipedia: Knowledge-powered conversational agents. In *International Conference on Learning Representations*.

Alex Graves and Alex Graves. 2012. Long short-term memory. *Supervised sequence labelling with recurrent neural networks*, pages 37–45.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. 2016. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778.

Taesuk Hong, Junhee Cho, Haeun Yu, Youngjoong Ko, and Jungyun Seo. 2023. Knowledge-grounded dialogue modelling with dialogue-state tracking, domain tracking, and entity extraction. *Computer Speech & Language*, 78:101460.

Edward J Hu, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, Weizhu Chen, et al. 2021. Lora: Low-rank adaptation of large language models. In *International Conference on Learning Representations*.

Xinxian Huang, Huang He, Siqi Bao, Fan Wang, Hua Wu, and Haifeng Wang. 2021. Plato-kag: Unsupervised knowledge-grounded conversation via joint modeling. In *Proc. of NLP4ConvAI*.

Di Jin, Shuyang Gao, Seokhwan Kim, Yang Liu, and Dilek Hakkani-Tur. 2021. Towards zero and few-shot knowledge-seeking turn detection in task-orientated dialogue systems. In *3rd Workshop on Natural Language Processing for Conversational AI, NLP4ConvAI 2021*, pages 281–288.

Minki Kang, Jin Myung Kwak, Jinheon Baek, and Sung Ju Hwang. 2023. Knowledge graph-augmented language models for knowledge-grounded dialogue generation. *arXiv preprint arXiv:2305.18846*.

Vladimir Karpukhin, Barlas Oguz, Sewon Min, Patrick Lewis, Ledell Wu, Sergey Edunov, Danqi Chen, and Wen-tau Yih. 2020. Dense passage retrieval for open-domain question answering. In *Proc. of EMNLP*.

Atoosa Kasirzadeh and Iason Gabriel. 2023. In conversation with artificial intelligence: aligning language models with human values. *Philosophy & Technology*, 36(2):27.

Seokhwan Kim, Mihail Eric, Karthik Gopalakrishnan, Behnam Hedayatnia, Yang Liu, and Dilek Hakkani-Tur. 2020. Beyond domain apis: Task-oriented conversational modeling with unstructured knowledge access. In *Proc. of SIGDIAL*.

Mojtaba Komeili, Kurt Shuster, and Jason Weston. 2022. Internet-augmented dialogue generation. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 8460–8478.

Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, et al. 2020. Retrieval-augmented generation for knowledge-intensive nlp tasks. *Advances in Neural Information Processing Systems*, 33:9459–9474.

Yu Li, Baolin Peng, Yelong Shen, Yi Mao, Lars Liden, Zhou Yu, and Jianfeng Gao. 2022. Knowledge-grounded dialogue generation with a unified knowledge representation. In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 206–218.

Rongzhong Lian, Min Xie, Fan Wang, Jinhua Peng, and Hua Wu. 2019. Learning to select knowledge for response generation in dialog systems. In *Proc. of IJCAI*.

Sourab Mangrulkar, Sylvain Gugger, Lysandre Debut, Younes Belkada, Sayak Paul, and Benjamin Bossan. 2022. Peft: State-of-the-art parameter-efficient fine-tuning methods. https://github.com/huggingface/peft.

Erik Miehling, Manish Nagireddy, Prasanna Sattigeri, Elizabeth M Daly, David Piorkowski, and John T Richards. 2024. Language models in dialogue: Conversational maxims for human-ai interactions. *arXiv preprint arXiv:2403.15115*.

Jinjie Ni, Tom Young, Vlad Pandelea, Fuzhao Xue, and Erik Cambria. 2023. Recent advances in deep learning based dialogue systems: A systematic survey. *Artificial intelligence review*, 56(4):3055–3155.

Yasumasa Onoe, Michael Zhang, Eunsol Choi, and Greg Durrett. 2022. Entity cloze by date: What lms know about unseen entities. In *Proc. of NAACL*.

Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. 2019. Language models are unsupervised multitask learners. *OpenAI blog*, 1(8):9.

Liliang Ren, Kaige Xie, Lu Chen, and Kai Yu. 2018. Towards universal dialogue state tracking. In *Proc. of EMNLP*.

Alireza Salemi and Hamed Zamani. 2024. Evaluating retrieval quality in retrieval-augmented generation. *Preprint*, arXiv:2404.13781.

Procheta Sen, Xi Wang, Ruiqing Xu, and Emine Yilmaz. 2023. Task2kb: A public task-oriented knowledge base. In *Proceedings of the AAAI Conference on Artificial Intelligence*.

Weizhou Shen, Yingqi Gao, Canbin Huang, Fanqi Wan, Xiaojun Quan, and Wei Bi. 2023. Retrieval-generation alignment for end-to-end task-oriented dialogue system. *arXiv preprint arXiv:2310.08877*.

Tianyuan Shi, Liangzhi Li, Zijian Lin, Tao Yang, Xiaojun Quan, and Qifan Wang. 2023. Dual-feedback knowledge retrieval for task-oriented dialogue systems. *arXiv preprint arXiv:2310.14528*.

Kurt Shuster, Spencer Poff, Moya Chen, Douwe Kiela, and Jason Weston. 2021. Retrieval augmentation reduces hallucination in conversation. In *Proc. of EMNLP*.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, Dan Bikel, Lukas Blecher, Cristian Canton-Ferrer, Moya Chen, Guillem Cucurull, David Esiobu, Jude Fernandes, Jeremy Fu, Wenyin Fu, Brian Fuller, Cynthia Gao, Vedanuj Goswami, Naman Goyal, Anthony Hartshorn, Saghar Hosseini, Rui Hou, Hakan Inan, Marcin Kardas, Viktor Kerkez, Madian Khabsa, Isabel Kloumann, Artem Korenev, Punit Singh Koura, Marie-Anne Lachaux, Thibaut Lavril, Jenya Lee, Diana Liskovich, Yinghai Lu, Yuning Mao, Xavier Martinet, Todor Mihaylov, Pushkar Mishra, Igor Molybog, Yixin Nie, Andrew Poulton, Jeremy Reizenstein, Rashi Rungta, Kalyan Saladi, Alan Schelten, Ruan Silva, Eric Michael Smith, Ranjan Subramanian, Xiaoqing Ellen Tan, Binh Tang, Ross Taylor, Adina Williams, Jian Xiang Kuan, Puxin Xu, Zheng Yan, Iliyan Zarov, Yuchen Zhang, Angela Fan, Melanie Kambadur, Sharan Narang, Aurélien Rodriguez, Robert Stojnic, Sergey Edunov, and Thomas Scialom. 2023. Llama 2: Open foundation and fine-tuned chat models. *CoRR*, abs/2307.09288.

Neeraj Varshney, Wenlin Yao, Hongming Zhang, Jianshu Chen, and Dong Yu. 2023. A stitch in time saves nine: Detecting and mitigating hallucinations of llms by validating low-confidence generation. *arXiv preprint arXiv:2307.03987*.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. 2017. Attention is all you need. *Advances in neural information processing systems*, 30.

Hongru Wang, Wenyu Huang, Yang Deng, Rui Wang, Zezhong Wang, Yufei Wang, Fei Mi, Jeff Z Pan, and Kam-Fai Wong. 2024. Unims-rag: A unified multi-source retrieval-augmented generation for personalized dialogue systems. *arXiv preprint arXiv:2401.13256*.

Shiquan Yang, Rui Zhang, and Sarah Erfani. 2020. Graphdialog: Integrating graph knowledge into end-to-end task-oriented dialogue systems. In *Proc. of EMNLP*.

Linhao Ye, Zhikai Lei, Jianghao Yin, Qin Chen, Jie Zhou, and Liang He. 2024. Boosting conversational question answering with fine-grained retrieval-augmentation and self-check. *arXiv preprint arXiv:2403.18243*.

Hao Yu, Aoran Gan, Kai Zhang, Shiwei Tong, Qi Liu, and Zhaofeng Liu. 2024. Evaluation of retrieval-augmented generation: A survey. *Preprint*, arXiv:2405.07437.

Xueliang Zhao, Wei Wu, Can Xu, Chongyang Tao, Dongyan Zhao, and Rui Yan. 2020. Knowledge-grounded dialogue generation with pre-trained language models. In *Proc. of EMNLP*.

Kangyan Zhou, Shrimai Prabhumoye, and Alan W Black. 2018. A dataset for document grounded conversations. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pages 708–713.

A Prompts for RAGate-Prompt

In this section, we list the used prompts for the RAGate-Prompt gate mechanism.

Zero-Shot Prompt:

Below is an instruction that describes a task. Please respond with 'True' or 'False' only that appropriately completes the request.

Instruction: Analyse the conversational context so far. Generate an appropriate response. Consider the invovled entites. Estimate if augmenting the response with external knowledge is helpful with an output of 'True' or 'False' only.

Input: [Converstion Context Input]

Response:

In-Context Learning Prompt:

Below is an instruction that describes a task. Please respond with 'True' or 'False' only that appropriately completes the request.

Instruction: Analyse the conversational context so far. Generate an appropriate response. Consider the invovled entites. Estimate if augmenting the response with external knowledge is helpful with an output of 'True' or 'False' only.

Example 1: USER: I'm planning a trip, can you help me look for a flight? SYSTEM: Which day are you planning to return and from which city? USER: I want to go from NYC the day after tomorrow and return on the 13th of this month. SYSTEM: Where would you like to go? USER: I want to go to Vancouver, BC. Can you look for a Premium Economy class ticket. SYSTEM: I found 1 flight for you. It is a Delta Airlines flight that takes off at 6 am and returns at 2:50 am. The price is $505. USER: What is the departure airport, and how many stops does the flight have?

Response: True

Example 2: USER: Get me bus tickets to a Cher event on March 6th. SYSTEM: How many to buy? USER: only one, please.

Response: False

Input: [Converstion Context Input]

Response:

B Extended Evaluation with larger language models as Conversational Agent

To further validate the reliability of our conclusions, we include additional experiments by replacing the KETOD model with recent advanced large language models, namely llama-2-7b and llama-2-70b (Touvron et al., 2023). The generation is instructed by the following prompt:

"*You are a conversational assistant. given the following input as context, generate an appropriate system response to the last user utterance to continue the conversation:*

Input: {input_text}

Response: "

We repeat the experiments using top BERT-ranker retrieved knowledge and apply the many variants of selective augmentation strategies. Table 4 reports the corresponding experimental results. According to the experimental results and compared to the results reported in Table 3, the increasing size of language models does not easily outperform the fine-tuned conversational agent in providing high quality responses. Indeed, the best performance llama-2-70b variant, which uses our RAGate-PEFT, can merely achieve the BLEU, ROUGE-L and BERTScore of 3.0910, 0.1064, 0.6972. This is significantly lower than the KE-TOD model even without knowledge augmentation (9.38, 0.3780 and 0.8105 of BLEU, ROUGE-L and BERTScore).

On the other hand, regarding the effectiveness of RAGate, we observe similar conclusions as in Section 5.2. At first, the confidence level decreases from using no augmentation to augment knowledge to every response. However, different from the performance increases with the use of additional knowledge in Table 3, we observe a consistent performance drop from No-Aug to Aug-All. This indicates that without conversational model fine-tuning, it is challenging for a model to leverage external knowledge to improve response quality, even on a large scale (e.g., Llama-2-70b). Meanwhile, comparing the approaches that consider an equal number of augmentations using RAGate and random sampling, the RAGate-based strategies remain outperforming with higher generation quality and confidence. In particular, when applied to the Llama-2-70b, the use of RAGate-PEFT can even improve the generation quality without model fine-tuning.

Variants	# Augs	BLEU	ROUGE-L	BERTScore	Confidence	
Llama-2-7b						
No-Aug	0	**1.9179**	**0.0859**	**0.6901**	16.8174	–
RAGate-PEFT	230	1.7161	0.0823	0.6886	16.4665	
RAGate-MHA	787	1.5579	0.0787	0.6880	16.1309	
Random-Aug	230	1.6429	0.0808	0.6890	15.2705	
Random-Aug	787	1.5019	0.0783	0.6871	15.3122	
Human-label	631	1.8130	0.0831	0.6885	**17.0015**	
Aug-All	4964	1.6148	0.0799	0.6868	16.3096	
Llama-2-70b						
No-Aug	0	3.0175	0.1045	0.6965	15.1094	–
RAGate-PEFT	230	**3.0910**	**0.1064**	**0.6972**	14.8349	
RAGate-MHA	787	3.0365	0.1039	0.6957	**15.1906**	
Random-Aug	230	3.0898	0.1055	0.6969	14.6211	
Random-Aug	787	3.0124	0.1039	0.6961	14.7746	
Human-label	631	3.0152	0.1037	0.6957	14.5912	
Aug-All	4964	2.6605	0.0976	0.6909	15.0136	

Table 4: Performance of applying RAGate and compared to Llama2-7b and Llama2-70b on the KETOD dataset. Confidence is calculated by the average value over the lowest logit of each generation.

Overall, these observations indicate the consistent need for adaptive retrieval augmented generation to both conversational models in different scales and with or without fine-tuning.

C Impact of Retrieval Quality on Adaptive RAG

To have a successful conversation model with a retrieval-augmented system, two main criteria must be met. One is identifying insufficient context, and the other is the quality of retrieved information (Salemi and Zamani, 2024; Yu et al., 2024). A conversational model performs better when both criteria are satisfied. In our proposed approach, as shown in Table 2, we have already assessed whether our adaptive retrieval method can detect insufficient context. We further explored to determine whether our model can inherently estimate the quality of the retrieved snippets to address such insufficiency and, based on that, decide on the retrieval. Although we do not explicitly provide retrieved snippets to our model, retrieval comes with a corpus that includes potentially relevant knowledge snippets. Consequently, given a query and a retrieval collection, it can be estimated whether useful information for the query exists in the corpus to address the insufficient context. To investigate by following this direction, we randomly selected 50 samples from instances where our proposed approach (RAGate-MHA, the best-performing gate model) predicted using retrieval augmentation. We asked domain experts (co-authors) to score whether they thought the retrieved snippets in those scenarios could be useful to response generation. Users

rated the snippets on a scale of $0 - 4$, with scores of 3 or 4 indicating 'useful' or 'highly useful'. We found that in 54% of cases where the prediction was for augmentation, users also found the snippets useful. This indicates that our proposed approach can implicitly capture the potential for obtaining high-quality retrieval snippets.

D Additional experimental results about RAGate for Response Generation

In Table 5, we include the complete experimental results of applying RAGate for adaptive retrieval-augmented system response generation. Specifically, explore the use of retrieved knowledge snippets to different extents of relevance. We include top-3 knowledge snippets retrieved by BERT-ranker and TF-IDF. In addition, we also explore the use of knowledge snippets in different ranking positions (rank 1 and 5) according to the BERT-ranker retriever. The experimental result shows that precisely using a suitable amount of relevant knowledge can generate a response with higher confidence (i.e., less is more). In addition, this observation also indicates the potential use of confidence levels to evaluate the quality of the augmented knowledge.

Augmentation Variants	# Augs	BLEU	ROUGE-1	ROUGE-2	ROUGE-L	BERTScore	Confidence
No-Aug	0	9.38	0.4111	0.2246	0.3780	0.8105	9.3425
Augment BERT Ranker Retrieved Knowledge							
RAGate-Llama	230	10.45●	0.4165●	0.2273●	0.3825●	0.8144●	9.3374●
RAGate-MHA	787	12.14○●	0.4227○	0.2318○	0.3882○	0.8192○	9.3083○●
Random-Aug	230	9.53●	0.4119●	0.2250●	0.3784●	0.8110●	9.2984○●
Random-Aug	787	10.01●	0.4138●	0.2265●	0.3795●	0.8126●	9.1877○●
Human-label	631	11.66○●	0.4198●	0.2297	0.3856○●	0.8176○●	9.2550○●
Augment-All	4964	16.08○	0.4301○	0.2364○	0.3927○	0.8258○	8.3677○
Augment TF-IDF Ranker Retrieved Knowledge							
RAGate-Llama	230	10.52●	0.4165●	0.2273●	0.3826●	0.8144●	9.3418●
RAGate-MHA	787	12.11○●	0.4233○	0.2319○	0.3889○	0.8193○	9.3058○●
Random-Aug	230	9.47●	0.4118●	0.2251●	0.3783●	0.8110●	9.3006●
Random-Aug	787	9.93●	0.4136●	0.2259●	0.3793●	0.8125●	9.1942●
Human-label	631	11.60○●	0.4198○●	0.2293○	0.3854○	0.8175○●	9.2639○●
Augment-All	4964	15.76○	0.4289○	0.2345○	0.3914○	0.8256○	8.4188○
Augment Rank-1 Relevant Knowledge							
RAGate-Llama	230	10.54●	0.4162●	0.2271●	0.3822●	0.8142●	9.3642●
RAGate-MHA	787	11.99○●	0.4227○	0.2316○	0.3883○	0.8191○	**9.3774**○●
Random-Aug	230	9.51●	0.4117●	0.2250●	0.3784●	0.8110●	9.3328●
Random-Aug	787	10.01●	0.4140●	0.2267●	0.3800●	0.8127●	9.2982●
Human-label	631	11.52○●	0.4189●	0.2289	0.3846	0.8170○●	9.3218●
Augment-All	4964	16.05○	0.4308○	0.2365○	0.3944○	0.8259○	9.0655○
Augment Rank-5 Relevant Knowledge							
RAGate-Llama	230	10.47●	0.4161●	0.2272●	0.3823●	0.8142●	9.3592●
RAGate-MHA	787	12.18○●	0.4224○	0.2314○	0.3883○	0.8192○	9.3704●
Random-Aug	230	9.52●	0.4118●	0.2252●	0.3785●	0.8110●	9.3315●
Random-Aug	787	10.01●	0.4135●	0.2263●	0.3794●	0.8127●	9.2961●
Human-label	631	11.58○●	0.4186●	0.2287	0.3845	0.8170○●	9.3210●
Augment-All	4964	15.97○	0.4290○	0.2349○	0.3927○	0.8256○	9.0604○

Table 5: Performance of applying RAGate and compared to KETOD on the SGD dataset. Confidence is calculated by the average value over the lowest logit of each generation. The significant difference compared to No-Aug or the corresponding Aug-all is indicated by ○ and ●, respectively, when p-value < 0.05, calculated by Wilcoxon signed-rank test.