IMAGINARYNET: LEARNING OBJECT DETECTORS WITHOUT REAL IMAGES AND ANNOTATIONS

ABSTRACT

Humans can easily detect a known concept without the demand of training in reality. Equipping this ability to deep learning may allow the neural network to learn complex vision models, *e.g.*, object detection, without collecting and annotating real images. In this paper, we define a novel paradigm as Imaginary-Supervised Object Detection (ISOD), where no real images and manual annotations are used for training object detectors. To resolve this challenge, we propose IMAGINARYNET, a framework to learn object detectors by combining pretrained language model as well as text-to-image synthesis models. In particular, photo-realistic images can be generated by the text-to-image model, and class labels can be obtained by the text generated by the language model. Then, weakly supervised object detection is leveraged to learn the detector without real images and manual annotations. By gradually introducing real images and manual annotations, IMAGINARYNET can collaborate with other supervision settings to further boost detection performance. Experiments show that IMAGINARYNET can (i) obtain about 70% performance in ISOD compared with the weakly supervised counterpart of the same backbone trained on real data, (ii) significantly improve the baseline while achieving state-of-the-art or comparable performance by incorporating real images and manual annotations.

1 INTRODUCTION

Humans can easily detect a known concept from language description without the demand of training in reality. Equipping this ability to deep learning may allow the neural network to handle complex vision tasks, *e.g.*, object detection, without real images and annotations. Recently, we witness the rise of Contrastive Language-Image Pre-training (CLIP) (Radford et al., 2021), where general knowledge can be learned by pre-training and then be applied to various downstream tasks via task-specific fine-tuning. Unlike image classification, object detection is more challenging and has a larger gap than the pre-training tasks. Several methods, such as RegionCLIP (Zhong et al., 2022), ViLD (Gu et al., 2021), and Detic (Zhou et al., 2022), have been suggested to transfer knowledge from pre-trained CLIP (Radford et al., 2021) model to some modules of object detectors. However, real images and annotations are still required for some key modules of the object detectors, such as RPNs or RoI heads.

In this work, we aim to raise and answer a question: given suitable pre-trained models, can we learn object detectors without real images and manual annotations? To this end, we introduce a novel learning paradigm, *i.e.*, Imaginary-Supervised Object Detection (ISOD), where no real images and manual annotations can be used for training object detection. Fortunately, ISOD is practically feasible and benefited from the progress in vision-language pre-training. Here we propose IMAGINARYNET, a framework to learn object detectors by combining pretrained language model as well as text-to-image synthesis models. In particular, the text-to-image synthesis model is adopted to generate photo-realistic images, and the language model can be used to improve the diversity and provide class labels for the synthesized images. Then, ISOD can be conducted by leveraging weakly supervised object detection (WSOD) algorithms on the synthesized images with class labels to learn object detectors without real images and manual annotations. We set up a strong CLIP-based model as the baseline to verify the effectiveness of IMAGINARYNET. Experiments show that IMAGINARYNET can outperform the CLIP-based model with a large margin. Compared with the

fully supervised counterpart trained by real data, IMAGINARYNET obtain about 70% performance in ISOD compared with the weakly supervised model of the same backbone trained on real data.

By gradually introducing real images and manual annotations, IMAGINARYNET can collaborate with other supervision settings to further boost detection performance. We note that the performance of existing object detection models may be constrained by the limited amount of training data. As a result, we extend IMAGINARYNET to incorporate real images and manual annotations. Further experiments show that IMAGINARYNET significantly improves the performance of the baselines while achieving state-of-the-art or comparable performance in the supervision setting.

To sum up, the contributions of this work are as follows:

- We propose IMAGINARYNET, a framework to learn object detectors without real images and manual annotations. To the best of our knowledge, we are among the first work to explore the training of deep networks for object detection with this learning paradigm.

- We propose a novel paradigm of object detection, Imaginary-Supervised Object Detection (ISOD), where no real images and annotations can be used for training object detection tasks. We set up the benchmark of ISOD and obtain about 70% performance in ISOD compared with the weakly supervised model of the same backbone trained on real data.

- By incorporating real images and manual annotations, ImaginaryNet significantly improves the baseline model while achieving state-of-the-art or comparable performance.

2 RELATED WORK

2.1 OBJECT DETECTION

Most object detection methods (FSOD) (Ren et al., 2015; Redmon et al., 2016; Tian et al., 2019; Carion et al., 2020) rely on large amount of training data with box-level annotations. To reduce the costs of data labeling, some works attempt to train a detector with incompletely supervised training data. For example, weakly-supervised object detection (WSOD) (Huang et al., 2022; Dong et al., 2021; Bilen & Vedaldi, 2016; Tang et al., 2017) requires only image-level labels. While semi-supervised object detection (SSOD) (Liu et al., 2021; Xu et al., 2021; Chen et al., 2022) leverages unlabeled data combining with box-level labeled data. Although these works use relatively less or weak supervision, all of these works still rely on real images and manual annotations. In this paper, we propose ISOD, where no real images and manual annotations can be used for training object detection, which can further save the demand for data acquisition and annotation costs.

2.2 SIM2REAL

Many works explore to use of simulation to learn real skills for models, especially in robotics. Some works (Horváth et al., 2022; Akhyani et al., 2022; Sadeghi & Levine, 2016) also explore the feasibility of combining simulation in computer vision tasks. Wang et al. (2018) use simulated images to train the classification model. Recently, Ge et al. (2022) used a simulated scene with real foreground object images to learn object detection. However, due to the domain gap between simulated and real images, these models still need real images or annotations to transfer knowledge to the real domain.

2.3 PRE-TRAINED MODELS

Pre-trained models have shown effectiveness in many vision tasks including object detection. Some CLIP-based models can transfer knowledge from pre-trained CLIP (Radford et al., 2021) model. However, real images and manual annotations are still needed for their RPNs or RoI heads. Visual synthesis models, such as GAN (Goodfellow et al., 2016), StyleGAN (Karras et al., 2019), and ImageBART Esser et al. (2021) aim to generate plausible images. In recent years, we witness the rise of text-to-image synthesis models with high quality and capability of language controlling, such as DALL-E (Ramesh et al., 2021), Stable Diffusion (Rombach et al., 2022), and Imagen (Saharia et al., 2022). However, existing methods did not use the knowledge from pre-trained text-to-image synthesis models to learn object detection without real images and manual annotations.

Figure 1: **Overview of IMAGINARYNET.** IMAGINARYNET samples the class label randomly and fulfills it to the prefix template. The language model extends the prefix to a complete description. The synthesis model generates imaginary images from random noise based on the description. Proposal representations are extracted from imaginary images. IMAGINARYNET optimizes Detection Head with proposal representations and class labels. If real data exists, Detection Head will also be optimized based on representations from real images and manual annotations.

3 METHODOLOGY

3.1 PRELIMINARIES AND PROBLEM FORMULATIONS

Object detection aims to find each object with the bounding box $\mathbf{b}_k \in \mathbb{R}^4$ and class label $c_k \in \mathbb{C}$ in a given image $\mathbf{I} \in \mathbb{R}^{C \times W \times H}$, where C, W and H denotes the channels, width and height of the image and k denotes the k-th object. In standard training process of object detection, $\mathcal{D}^{\mathrm{R}}$ is the dataset which contains real images and their corresponding annotations. In practice, $\mathcal{D}^{\mathrm{R}}$ may contain different types of data and annotations, where $\mathcal{D}^{\mathrm{R}} = \mathcal{D}^{\mathrm{R}}_s \cup \mathcal{D}^{\mathrm{R}}_w \cup \mathcal{D}^{\mathrm{R}}_u$. Class-labeled real data $\mathcal{D}^{\mathrm{R}}_w = \{(\mathbf{I}, \{(c)_i\})_k\}$ contains real images and corresponding class labels, which is used for WSOD setting. Box-labeled real data $\mathcal{D}^{\mathrm{R}}_s = \{(\mathbf{I}, \{(\mathbf{b}, c)_i\})_k\}$ contains real images, bounding box and class label of each object. Un-annotated real data $\mathcal{D}^{\mathrm{R}}_u = \{(\mathbf{I})_k\}$ only contains real images. Box-level annotated and un-annotated real data are used in SSOD setting.

In this paper, we propose Imaginary-Supervised Object Detection (ISOD), where no real images and annotations can be accessed with $\mathcal{D}^{\mathrm{R}} = \mathcal{D}^{\mathrm{R}}_s = \mathcal{D}^{\mathrm{R}}_w = \mathcal{D}^{\mathrm{R}}_u = \emptyset$.

3.2 IMAGINARY GENERATOR

IMAGINARYNET aims to learn object detectors with the generated images as well as supervision information. Given a class vocab $\mathbb{C}$, IMAGINARYNET samples uniformly to get a class label $c \in \mathbb{C}$. Then, the class name of c will be fulfilled into a prefix phrase, which is "*A photo of a*", to obtain the subject description P_c of the imaginary image.

To make the scene of image more specific and diverse, P_c will be the guidance prefix of the language model G^{L}, *e.g.*, GPT-2 (Radford et al., 2019), to imagine the full description of the scene of image. The language model G^{L}, which is a transformer-based autoregressive network, generates the full description token by token until meeting a full stop or exceeding the maximum of length M^{L} [1].

Let $\mathbf{t}_c = G^{\mathrm{L}}(P_c)$ be the generated full description of the imaginary image. IMAGINARYNET obtain the synthesized image by

$$\mathbf{I} = G^{\mathrm{V}}(z|\mathbf{t}_c), \tag{1}$$

where $z \sim \mathcal{N}(0, 1)$ is random noise sampled from normal distribution. The text-to-image synthesis model G^{V} usually adopts a transformer-based autoregressive or diffusion network, and generates the imaginary image $\mathbf{I}$ based on random noise z with the guidance of $\mathbf{t}_c$ in a step by step manner.

For the imaginary image $\mathbf{I}$, IMAGINARYNET obtain its feature map $\mathbf{h} = E^{\mathrm{I}}(\mathbf{I})$, where E^{I} is the image encoder consisted of multi-layers of convolutional networks. Simultaneously, proposals $\mathcal{P} = R(\mathbf{I})$ of the imaginary image $\mathbf{I}$ are extracted by proposal generator R, which is a selective

---

[1]We set M^{L} as 15. We tried different M^{L}, but no significant gain was obtained.

Figure 2: **The structure of Detection Head.** Based on different data settings, we use three types of detection heads. In (a) type of Detection Head, no real images and annotations will participate the training process. In types (b) and (c), real images and annotations will be trained with imaginary data together. In type (c), MIL Branch will be disabled due to box supervision exists.

search module or a RPN network without initilization. IMAGINARYNET apply RoI Pooling to each proposal $p_i \in \mathcal{P}$ in feature map h to obtain the proposal representation $\mathbf{f}_i \in \mathbb{R}^d$. Consequently, IMAGINARYNET obtain a set of imaginary proposal representations $\{\mathbf{f}_i\}$ with their corresponding class-label c, which allows it to learn object detectors without real images and annotations.

3.3 DETECTION NETWORK

We add an object detection head at the end of the **Representation Generator**, which takes the representation $\mathbf{f}_i$ as input and predicts the bounding box of an object. In standard object detection, training images and corresponding annotations are given, formulating a fully-supervised training paradigm (FSOD). Instead, we propose a new learning paradigm named ISOD, in which neither real training images nor manual annotations can be reached. This means that we cannot apply the traditional approach (Ren et al., 2015; Tian et al., 2019) straightforwardly. Fortunately, our IMAGINARYNET sample a target class c describing the semantics of the corresponding imaginary image. Note that both the set of proposal representation $\{\mathbf{f}_i\}$ and class label c are available. Thus, ISOD can be conducted by leveraging weakly-supervised object detection (WSOD) algorithms on the proposal representations and class labels obtained from IMAGINARYNET.

Following OICR(Tang et al., 2017), the object detection head consists of a **Multiple Instances Learning (MIL) branch** and a **Refinement branch** and the structure of them are shown in Fig (2). During the training phase, all object representations are first fed into the MIL branch. The MIL branch combines two parallel classification streams, each of which contains a softmax function. One softmax function is along the classes dimension to output the score matrix $\mathbf{x}_c^m \in \mathbb{R}^{|\mathcal{P}| \times |\mathbb{C}|}$, and the other is along the object dimension to output the score matrix $\mathbf{x}_r^m \in \mathbb{R}^{|\mathcal{P}| \times |\mathbb{C}|}$. Then we compute the element-wise product of these two scores matrix and get the $\mathbf{x}^m = \mathbf{x}_c^m \odot \mathbf{x}_r^m$. $\mathbf{x}^m$ indicates the final object-level classification scores. Then we get the c-th class image-level score s_c^m by sum over all object: $s_c^m = \sum_{i=1}^{|\mathcal{P}|} x_{i,c}^m$. We convert the target label c into one-hot form $\hat{\mathbf{y}}$ and calculate the Binary Cross Entropy loss (BCE loss):

$$\mathcal{L}_{mil}^{ign} = -\sum_{c=1}^{|\mathbb{C}|} \hat{y}_c \log s_c^m + (1 - \hat{y}_c) \log (1 - s_c^m) \tag{2}$$

To further improve the performance of the detector, we integrate the self-training methodology and construct the Refinement branch, which has a similar structure as the RoI head of the R-CNN-like detector (Ren et al., 2015). Following the (Tang et al., 2017), we keep the proposal with the highest classification score from $\mathbf{x}^m$ as the pseudo-ground-truth (PGT), which are used to optimize the Refinement branch by a refinement loss $\mathcal{L}_{ref}^{ign}$. Finally, the learning objective of our object detection head of ISOD is:

$$\mathcal{L} = \mathcal{L}_{mil}^{ign} + \mathcal{L}_{ref}^{ign} \tag{3}$$

The whole training pipeline of ISOD is shown in Fig. 2(a). We take the OICR as the example and it is feasible to employ other WSOD method.

Furthermore, by gradually introducing real images and manual annotations, IMAGINARYNET can collaborate with other supervision setting to boost detection performance. Here we present two examples by incorporating IMAGINARYNET with weakly supervision and full supervision on real

Table 1: **Comparison of our method in ISOD on PASCAL VOC 2007.** We compare IMAGI-NARYNET with supervised OICR trained with 5000 real images and class-labeled annotations and unsupervised CLIP model. Results shows significant improvements over the CLIP model.

METHODS	AERO	BIKE	BIRD	BOAT	BOTTLE	BUS	CAR	CAT	CHAIR	COW	TABLE	DOG	HORSE	MOTOR	PERSON	PLANT	SHEEP	SOFA	TRAIN	TV	MAP
OICR (WSOD)	54.97	55.32	47.64	29.25	24.94	69.32	64.76	76.07	18.16	56.59	20.17	70.13	69.03	64.42	19.82	20.12	49.14	27.42	68.61	52.72	47.93
CLIP	16.30	17.15	19.42	**8.80**	14.53	30.28	25.83	25.92	**20.34**	27.10	**21.85**	26.00	20.32	22.59	10.09	13.43	26.24	27.82	19.26	23.59	20.84
IMAGINARYNET	**47.18**	**43.13**	**35.51**	5.33	**19.23**	**32.58**	**41.23**	**66.72**	12.03	**43.98**	18.13	**43.98**	**36.71**	**51.68**	**19.04**	**14.97**	**34.12**	**42.74**	**23.04**	**33.36**	**33.23**

data. During training, both real images and synthesized images are fed into the Representation Generator and object detection head in order and optimize these two modules via back-propagation. And we only need to slightly modify the training pipeline of object detection head. When real images and class-level annotations are available, *i.e.*, $\mathcal{D}_w^{\mathrm{R}} \neq \emptyset$, as shown in Fig. 2(b) we can uniformly sample synthesized and real images and fed them into the WSOD training process. When both real images and box-level annotations are available, *i.e.*, $\mathcal{D}_s^{\mathrm{R}} \neq \emptyset$, we remove the MIL branch and treat the synthesis images as *unlabeled image*. As shown in Fig. 2(c), we simply leverage the teacher-student framework widely adopted in semi-supervised object detection to train the detection head. The teacher detection network generates pseudo-ground-truth (PGT) for unlabeled real images and imaginary images to train the student detection network. In addition, the student is also trained on real images with box-level ground-truth (GT) by supervised-learning manner (Ren et al., 2015).

3.4 TRAINING AND INFERENCE PIPELINE

During the training phase, IMAGINARYNET samples a target class c and generates the full description **t** via language model. Then we get an imaginary image by Eq. (1) and its feature map **h** by $\mathbf{h} = E^{\mathrm{I}}(\mathbf{I})$. Consequently, a set of region proposals is generated by the Proposals Generator, and proposal representations are obtained via RoI Pooling. Finally, the proposal representations are fed into different object detection heads according to the supervision settings. During the whole training process, only the parameters of the Representation Generator and Object Detection head need to be updated. In the inference phase, the language model and synthesis model will be abandoned. Taking a real image as the input, the Representation Generator generates proposal representations, and the detection head decodes them to predict the detection bounding box.

4 EXPERIMENTS

4.1 IMPLEMENTATION DETAILS

We use GPT-2 (Radford et al., 2019) as the language model and DALLE-mini, which can better follow the language guidance, as the text-to-image synthesis model. We implement the image encoder with ResNet50 pretrained on ImageNet dataset. For Proposal Generator, we use Selective Search following W2N (Huang et al., 2022) for reaching no real images and manual annotations. All training hyper-parameters follow OICR (Tang et al., 2017) and W2N (Huang et al., 2022) for a fair comparison. Unless otherwise specified, we generate 5,000 imaginary images during training, which has the similar amount of images in comparison to PASCAL VOC2007 trainval set.

4.2 EXPERIMENTAL SETUP

We first compare IMAGINARYNET with the baseline model in ISOD to verify whether it is feasible to learn object detectors without real images and manual annotations. To the best of our knowledge, we are among the first to investigate ISOD solely based on synthesized images. So we set up a strong baseline based on the CLIP model. For CLIP baseline, we use the Edge Boxes algorithm [2] to extract potential proposals on VOC test images for CLIP to classify what class it is, based on its similarity score with pre-designed prompts. Before computing AP, we apply the Non-Maximum Suppression (NMS) operation to remove redundant proposals based on CLIP scores. See Appendix A.1 for more details.

We also compare IMAGINARYNET with several other baseline models suggested for weakly supervised object detection based on real images. Here we use WSDDN (Bilen & Vedaldi, 2016), OICR

---

[2]We tried Selective Search but Edge Boxes is more effective, so we report the best results.

Table 2: **Comparison of our method in WSOD on PASCAL VOC 2007.** All models use 5000 VOC2007 as real training data and IMAGINARYNET (WSOD) generate extra 5000 imaginary samples. Compared to other WSOD models, we achieved state-of-the-art performance.

METHODS	AERO	BIKE	BIRD	BOAT	BOTTLE	BUS	CAR	CAT	CHAIR	COW	TABLE	DOG	HORSE	MOTOR	PERSON	PLANT	SHEEP	SOFA	TRAIN	TV	MAP
WSDDN	39.41	50.09	31.48	16.30	12.61	64.45	42.82	42.63	10.06	35.72	24.92	38.24	34.41	55.60	9.39	14.72	30.22	40.68	54.70	46.94	34.77
OICR	54.97	55.32	47.64	29.25	24.94	69.32	64.76	76.07	18.16	56.59	20.17	70.13	69.03	64.42	19.82	20.12	49.14	27.42	68.61	52.72	47.93
W2N	74.00	73.82	59.40	28.34	43.43	**80.03**	72.61	81.23	14.00	**76.75**	25.98	58.64	63.76	**75.69**	10.86	29.56	**60.38**	63.76	79.56	67.29	56.95
IMAGINARYNET (WSOD)	**74.66**	**81.36**	**64.72**	37.40	**49.97**	79.89	**74.79**	**84.23**	**34.31**	72.62	**49.59**	**79.27**	**76.99**	75.60	**40.52**	**34.80**	58.97	**64.82**	**81.60**	**72.81**	**64.45**

(Tang et al., 2017) and W2N (Huang et al., 2022) as the baseline detection networks. Compared with them, IMAGINARYNET in ISOD adopts similar training pipeline but does not require real images and manual annotations, whereas IMAGINARYNET in WSOD use the same real data with them.

4.3 OVERALL RESULTS

4.3.1 IMAGINARY-SUPERVISED OBJECT DETECTION

As shown in Tab. 1, IMAGINARYNET achieves an mAP of 33.23. This verifies the feasibility of learning object detectors without real images and annotations. Moreover, IMAGINARYNET outperforms the CLIP baseline model with a gain of 12.39 in mAP. This further supports that the competitiveness of a pre-trained generative model against pre-trained contrastive alignment models (*e.g.*, CLIP) for learning object detectors. For most classes, IMAGINARYNET can obtain a significant performance gain, and IMAGINARYNET has much fewer parameter amounts and computational cost in inference because the pre-trained modules can be abandoned after training. Especially, for some classes such as cat, the performance improved from 25.92 of CLIP to 66.72 of IMAGINARYNET. The results clearly show the feasibility of ISOD, *i.e.*, learning object detectors without real images and manual annotations.

We further compare ISOD with another baseline, WSOD on real images with class-level annotations. For a fair comparison, we only generate 5,000 imaginary samples during training. Compared with OICR, which has the same backbone with ours and trained on 5,000 real images and manual annotations in WSOD setting, we achieved about 70% performance of it. Considering that synthesized images and class-level annotations are free for IMAGINARYNET, our ISOD has the potential to further improve detetion accuracy by increasing training samples.

MSCOCO Results We also conduct the experiments on MSCOCO dataset, and obtain similar observations as VOC2007. See Appendix A.2 for more details.

4.3.2 INCORPORATING WITH WSOD ON REAL IMAGES AND MANUAL ANNOTATIONS

We further show that the synthesized images by IMAGINARYNET can collaborate with other supervision settings on real images and manual annotations for boost detection performance. Here we use WSOD as an example. As given in Tab. 2, IMAGINARYNET(WSOD) has achieved state-of-the-art performance in WSOD. This shows the effectiveness of IMAGINARYNET(WSOD) can not only learn object detectors without real images and annotations but also improve the performance of backbones without extra parameters or computational cost in inference. IMAGINARYNET(WSOD) obtain an mAP of 64.45, which is higher than the state-of-the-art WSOD models.

4.4 COMPARISON WITH REAL DATA

How effective is IMAGINARYNET in comparison with real data? To answer this question, we conduct comparison experiments in SSOD setting. We use the same backbone, RESNET50-FPN compared with the supervised model FASTERRCNN and the SSOD model UNBIASED TEACHER[3]. Note that, for a fair comparison, we use the same backbone, training hyper-parameters, and real data by following the existing methods.

As shown in Tab. 3, comparing with FASTER-RCNN and UNBIASED TEACHER, IMAGINARYNET(SSOD) has achieved comparable performance, about 99.3% performance of UNBIASED

---

[3]Although the performance in its original paper is lower, we obtain 81.08 by re-training the model.

Table 3: **Comparison of our method with real data on PASCAL VOC 2007.** Imaginary data can play a similar role in enhancing performance. 10K Imaginary data can improve the model by a similar margin compared with 10K real data. Moreover, introducing imaginary data when extra real data exists can further improve the performance to break through the upper bound of the model.

METHODS	ANNOTATED REAL DATA	UN-ANNOTATED REAL DATA	UN-REAL DATA	MAP
FASTERRCNN	5K VOC2007	∅	∅	76.00
UNBIASED TEACHER	5K VOC2007	10K VOC2012	∅	81.08 (+5.08)
IMAGINARYNET (SSOD)	5K VOC2007	∅	5K IMAGINARY	80.30 (+4.30)
IMAGINARYNET (SSOD)	5K VOC2007	∅	10K IMAGINARY	80.59 (+4.49)
IMAGINARYNET (SSOD)	5K VOC2007	10K VOC2012	10K IMAGINARY	82.00 (+6.00)

OVERALL RESULTS OF TOTAL IMAGINARY SAMPLES

Figure 3: **Visualization of extracted features.** We can observe that features can cluster based on the object type. This shows imaginary data contains similar knowledge like real data.

Figure 4: **Overall results of different total imaginary samples.** The performance improves steadily with the growth of imaginary samples.

TEACHER. This shows that generated data are almost as effective as real data but have much lower cost and higher controllability. Compared to the baseline UNBIASED TEACHER, we can observe that generated data are orthogonal with real data, where we can further improve the performance even when extra real data exists.

4.5 VISUALIZATION

To figure out why IMAGINARYNET can learn object detectors without real images and annotations, we conduct several visualizations to explain the reason from multi-perspectives.

4.5.1 EXTRACTED FEATURES

To verify whether the features extracted from imaginary images contain similar information to real images, we extracted their features from the same Representation Generator. For real images, we extract 10 features per class as anchors and 10 features for each class from imaginary images. We use T-SNE to project them to a 2D image.

In Fig. 3, we can observe that features of one class from imaginary images are in the feature cluster of the same class from real images. This proves that features from imaginary images contain similar information compared with real images, which explained why IMAGINARYNET can learn object detectors even without real images and annotations.

4.5.2 IMAGINARY IMAGES

We randomly sample imaginary images from the synthesis model and corresponding text descriptions from the language model to observe how they can play the role of real data. In Fig. 5, we can find that text descriptions are quite diverse. Meanwhile, high-quality images from the synthesis model follow the description well and contain vivid objects of the corresponding class. Although all images generated are not in real datasets, IMAGINARYNET successfully simulates the scene of the images from object detection datasets. This may explain why IMAGINARYNET can even enhance object detectors under settings that contain real images and annotations.

*a photo of a **cat** laying* | *a photo of a **horse** in a field on a Tuesday afternoon* | *a photo of a **aeroplane**, like a big big red plane* | *a photo of a **dog** that's in pain*

*a photo of a **potted plant** growing in the back yard* | *a photo of a **chair**, which was covered by a thin layer of ice* | *a photo of a **bottle** of beer on the bar* | *a photo of a **bird** that was white and beautiful*

Figure 5: **Visualization of imaginary images.** Language model extends the prefix to a full description of the scene and the synthesis model generated images followed the description.

Figure 6: **Visualization of detection results on PASCAL VOC 2007 test split.** Results show that it is feasible to learn object detectors in ISOD via IMAGINARYNET.

Table 4: **Comparison of different imaginary samples in ISOD on PASCAL VOC 2007.** We set the different scales of samples and report their mAP. The mAP increases with the growth of samples.

SAMPLES	AERO	BIKE	BIRD	BOAT	BOTTLE	BUS	CAR	CAT	CHAIR	COW	TABLE	DOG	HORSE	MOTOR	PERSON	PLANT	SHEEP	SOFA	TRAIN	TV	mAP
2K	39.35	43.68	33.36	4.51	13.84	29.39	38.71	59.48	10.69	35.75	21.06	37.43	28.97	43.64	17.20	13.55	33.10	35.71	17.51	29.73	29.33
3K	39.15	40.10	33.18	3.40	17.19	32.34	37.21	53.69	11.50	41.29	19.75	39.34	35.24	48.15	16.30	13.74	29.83	42.62	25.38	28.01	30.37
4K	41.92	41.99	**35.64**	4.71	17.88	35.88	38.28	58.10	11.06	35.17	**24.19**	33.36	36.34	45.88	17.80	14.30	30.71	41.97	**26.45**	**40.82**	31.62
5K	**47.18**	43.13	35.51	5.33	19.23	32.58	**41.23**	**66.72**	12.03	43.98	18.13	**43.98**	36.71	51.68	19.04	14.97	34.12	42.74	23.04	33.36	33.23
10K	45.10	**51.31**	34.22	**5.34**	**27.65**	**36.62**	39.35	62.00	**13.41**	**45.31**	20.45	41.41	**51.13**	**52.25**	**21.32**	**21.48**	**35.20**	**44.48**	22.06	33.82	**35.20**

4.5.3 CASE STUDIES

To better reveal the quality of IMAGINARYNET, we visualize detection results from VOC2007 test split in ISOD setting. In Fig. 6, many objects are detected correctly. In some hard cases, e.g., the 5-th image which contains many drivers and motors overlapping together, can also be detected well with nearly-correct boxes and classes. This proves the effectiveness of IMAGINARYNET in ISOD.

Although IMAGINARYNET shows pretty effectiveness in many cases, we still find out some failure cases. For example, in Fig. 6, some motorbikes are not detected well and persons are classified into the wrong class. This is because ISOD is a very strict setting, where the model cannot access any real images and annotations. Nonetheless, IMAGINARYNET still shows that it is feasible to learn object detectors in this hard setting.

5 ABLATION STUDIES

To further analyze the performance of IMAGINARYNET, we conduct several ablation studies to investigate the framework proposed.

5.1 INFLUENCE OF TOTAL IMAGINARY SAMPLES

Can the model obtain higher performance if IMAGINARYNET imagine more samples? To figure out this, we conduct experiments on ISOD with different scales of imaginary samples. In Tab. 4 and Fig. 4, we can find that the overall performance, mAP, increases steadily to 35.20 finally. This

Table 5: **Ablation of language model in ISOD on PASCAL VOC 2007.** We can observe that the language model improve the results of the model significantly.

Methods	Aero	Bike	Bird	Boat	Bottle	Bus	Car	Cat	Chair	Cow	Table	Dog	Horse	Motor	Person	Plant	Sheep	Sofa	Train	TV	mAP
w/o LM	31.32	**49.94**	32.13	3.24	**23.78**	**43.35**	34.66	30.95	**13.35**	38.59	15.77	38.51	**40.82**	42.34	15.84	**18.39**	**42.11**	38.86	18.99	**47.54**	31.02
w/ LM	**47.18**	43.13	**35.51**	**5.33**	19.23	32.58	**41.23**	**66.72**	12.03	**43.98**	**18.13**	**43.98**	36.71	**51.68**	**19.04**	14.97	34.12	**42.74**	**23.04**	33.36	**33.23**

Table 6: **Ablation of data augmentation strategies training on PASCAL VOC 2007.** We can observe that all augmentation strategies are effective on imaginary samples.

Train Aug.	Test Aug.	Aero	Bike	Bird	Boat	Bottle	Bus	Car	Cat	Chair	Cow	Table	Dog	Horse	Motor	Person	Plant	Sheep	Sofa	Train	TV	mAP
		86.05	86.75	81.92	66.66	71.11	86.72	88.13	87.68	61.24	84.58	74.15	87.37	86.73	86.95	85.65	56.45	81.45	76.94	85.03	76.89	79.92
√		86.84	87.55	82.99	70.01	73.50	86.85	88.45	87.56	62.07	83.92	73.88	87.26	87.45	87.62	85.76	57.09	81.14	78.93	84.51	78.42	80.59
√	√	87.83	88.55	84.83	76.29	76.08	87.68	89.19	88.28	66.40	87.34	75.66	88.52	88.77	88.62	86.58	62.33	82.23	79.86	87.71	81.22	82.70

proves that more imaginary samples can make the detector stronger. Meanwhile, IMAGINARYNET obtains mAP of 29.33 with 2K samples only. This shows the effectiveness of imaginary samples, which can train the detector with very limited samples. We also notice the fluctuation of several classes. This can be explained by the instability of class-level annotation learning. But from the overall perspective, more samples will improve the final performance.

5.2 EFFECTIVENESS OF LANGUAGE MODEL

Whether the various scene descriptions are useful for detector learning? To figure out this question, we re-train an IMAGINARYNET without a language model. In Tab. 5, we can observe a significant drop in mAP. The performance of each class also drops in most cases. Such class, like cat, drops over 30 of AP50. This proves language model is also important. We also notice the unexpected drop in some classes and we believe this can be explained by the failure of the language model to generate a scene similar to the real dataset in some cases. We will leave this as future work to generate images that are more suitable for learning detectors.

5.3 VERIFICATION OF ORTHOGONALITY WITH DATA AUGMENTATIONS

Whether the data augmentation strategies still work on imaginary images? To answer the question, we conduct several ablation studies with different data augmentation strategies, training augmentation, and testing augmentation. For most WSOD method, which are also employed into our ISOD setting, no training augmentation is needed because it is relatively hard to learn with class-labeled images. Consequently, we conduct this experiment in SSOD setting. As Tab. 6 shows, we can observe that IMAGINARYNET obtain better performance after activating training augmentation and testing augmentation. These results give strong proof that our framework is orthogonality with data augmentations. Moreover, orthogonality with data augmentation strategies may imply that imaginary samples have a similar property to real data.

6 BROADER IMPACT

IMAGINARYNET is an effective framework to learn detectors without real images and annotations or further improve the performance with real data. It can provide the potential for low-resource scenarios and motivate the following works to build stronger artificial intelligence. For example, it will be possible to learn models in other deep learning tasks without any real data. However, the performance is limited by synthesis models, which may not abide by the text description and lead to extra noise for learning. We leave this as future work to explore.

7 CONCLUSION

In this paper, we propose a novel learning paradigm of object detection, Imaginary-Supervised Object Detection (ISOD), where no real images and manual annotations can be used for training object detectors, and IMAGINARYNET, a framework to learn object detectors without real images and annotations. Experiments shows that ISOD can obtain about 70% of performance in comparison with the WSOD counterpart trained using real data and class-level annotations. Moreover, IMAGINARYNET can collaborate with other supervision settings on real data to further boost detection performance.

REFERENCES

Saba Akhyani, Mehryar Abbasi Boroujeni, Mo Chen, and Angelica Lim. Towards inclusive hri: Using sim2real to address underrepresentation in emotion expression recognition. *arXiv preprint arXiv:2208.07472*, 2022.

Hakan Bilen and Andrea Vedaldi. Weakly supervised deep detection networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 2846–2854, 2016.

Nicolas Carion, Francisco Massa, Gabriel Synnaeve, Nicolas Usunier, Alexander Kirillov, and Sergey Zagoruyko. End-to-end object detection with transformers. In *European conference on computer vision*, pp. 213–229. Springer, 2020.

Binbin Chen, Weijie Chen, Shicai Yang, Yunyi Xuan, Jie Song, Di Xie, Shiliang Pu, Mingli Song, and Yueting Zhuang. Label matching semi-supervised object detection. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 14381–14390, 2022.

Bowen Dong, Zitong Huang, Yuelin Guo, Qilong Wang, Zhenxing Niu, and Wangmeng Zuo. Boosting weakly supervised object detection via learning bounding box adjusters. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 2876–2885, 2021.

Patrick Esser, Robin Rombach, Andreas Blattmann, and Bjorn Ommer. Imagebart: Bidirectional context with multinomial diffusion for autoregressive image synthesis. *Advances in Neural Information Processing Systems*, 34:3518–3532, 2021.

Yunhao Ge, Jiashu Xu, Brian Nlong Zhao, Laurent Itti, and Vibhav Vineet. Dall-e for detection: Language-driven context image synthesis for object detection. *arXiv preprint arXiv:2206.09592*, 2022.

Ian Goodfellow, Yoshua Bengio, Aaron Courville, and Yoshua Bengio. *Deep learning*, volume 1. MIT Press, 2016.

Xiuye Gu, Tsung-Yi Lin, Weicheng Kuo, and Yin Cui. Open-vocabulary object detection via vision and language knowledge distillation. In *International Conference on Learning Representations*, 2021.

Dániel Horváth, Gábor Erdős, Zoltán Istenes, Tomáš Horváth, and Sándor Földi. Object detection using sim2real domain randomization for robotic applications. *arXiv preprint arXiv:2208.04171*, 2022.

Zitong Huang, Yiping Bao, Bowen Dong, Erjin Zhou, and Wangmeng Zuo. W2n: Switching from weak supervision to noisy supervision for object detection. *arXiv preprint arXiv:2207.12104*, 2022.

Tero Karras, Samuli Laine, and Timo Aila. A style-based generator architecture for generative adversarial networks. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 4401–4410, 2019.

Yen-Cheng Liu, Chih-Yao Ma, Zijian He, Chia-Wen Kuo, Kan Chen, Peizhao Zhang, Bichen Wu, Zsolt Kira, and Peter Vajda. Unbiased teacher for semi-supervised object detection. *arXiv preprint arXiv:2102.09480*, 2021.

Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. Language models are unsupervised multitask learners. *OpenAI blog*, 1(8):9, 2019.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International Conference on Machine Learning*, pp. 8748–8763. PMLR, 2021.

Aditya Ramesh, Mikhail Pavlov, Gabriel Goh, Scott Gray, Chelsea Voss, Alec Radford, Mark Chen, and Ilya Sutskever. Zero-shot text-to-image generation. In *International Conference on Machine Learning*, pp. 8821–8831. PMLR, 2021.

Joseph Redmon, Santosh Divvala, Ross Girshick, and Ali Farhadi. You only look once: Unified, real-time object detection. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 779–788, 2016.

Shaoqing Ren, Kaiming He, Ross Girshick, and Jian Sun. Faster r-cnn: Towards real-time object detection with region proposal networks. *Advances in neural information processing systems*, 28, 2015.

Robin Rombach, Andreas Blattmann, Dominik Lorenz, Patrick Esser, and Björn Ommer. High-resolution image synthesis with latent diffusion models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 10684–10695, 2022.

Fereshteh Sadeghi and Sergey Levine. Cad2rl: Real single-image flight without a single real image. *arXiv preprint arXiv:1611.04201*, 2016.

Chitwan Saharia, William Chan, Saurabh Saxena, Lala Li, Jay Whang, Emily Denton, Seyed Kamyar Seyed Ghasemipour, Burcu Karagol Ayan, S Sara Mahdavi, Rapha Gontijo Lopes, et al. Photorealistic text-to-image diffusion models with deep language understanding. *arXiv preprint arXiv:2205.11487*, 2022.

Peng Tang, Xinggang Wang, Xiang Bai, and Wenyu Liu. Multiple instance detection network with online instance classifier refinement. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 2843–2851, 2017.

Zhi Tian, Chunhua Shen, Hao Chen, and Tong He. Fcos: Fully convolutional one-stage object detection. In *Proceedings of the IEEE/CVF international conference on computer vision*, pp. 9627–9636, 2019.

Yu-Xiong Wang, Ross Girshick, Martial Hebert, and Bharath Hariharan. Low-shot learning from imaginary data. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 7278–7286, 2018.

Mengde Xu, Zheng Zhang, Han Hu, Jianfeng Wang, Lijuan Wang, Fangyun Wei, Xiang Bai, and Zicheng Liu. End-to-end semi-supervised object detection with soft teacher. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 3060–3069, 2021.

Yiwu Zhong, Jianwei Yang, Pengchuan Zhang, Chunyuan Li, Noel Codella, Liunian Harold Li, Luowei Zhou, Xiyang Dai, Lu Yuan, Yin Li, and Jianfeng Gao. Regionclip: Region-based language-image pretraining. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 16793–16803, June 2022.

Xingyi Zhou, Rohit Girdhar, Armand Joulin, Phillip Krähenbühl, and Ishan Misra. Detecting twenty-thousand classes using image-level supervision. *arXiv preprint arXiv:2201.02605*, 2022.

A APPENDIX

A.1 CLIP BASELINE

We use ViT-B/16 as the image encoder for CLIP and use Edge Boxes to extract 1000 proposals for each test image. Each proposal will be transformed to 384×384 to fit the CLIP input size. Then each proposal will be calculated similarity with the prompt which consists of the prefix "a photo of" and the class name. We select the highest CLIP similarity as the class of the proposal. Before computing AP, we apply the Non-Maximum Suppression (NMS) operation to remove redundant proposals according to their CLIP scores.

A.2 IMAGINARY-SUPERVISED OBJECT DETECTION RESULTS ON MSCOCO

Table 7: **Comparison of our method in ISOD on MSCOCO2014.** We obtain a much higher mAP compared with the CLIP baseline. This shows the feasibility of training the detector on a harder dataset of 80 classes without any real images and annotations.

METHODS	MAP
CLIP	6.3
IMAGINARYNET	**11.4**

We also verified our framework on MSCOCO2014, which is also a common dataset in object detection. As the results in Tab. 7, we outperform the CLIP baseline with nearly two times of mAP. This proves that our framework is also effective on the harder dataset, which contains 80 classes.

A.3 COMPARISON OF DIFFERENT VISUAL SYNTHESIS MODEL

Table 8: **Comparison of different visual synthesis models in ISOD on PASCAL VOC 2007.** We can observe that DALLE-MINI can provide higher performance for IMAGINARYNET.

METHODS	AERO	BIKE	BIRD	BOAT	BOTTLE	BUS	CAR	CAT	CHAIR	COW	TABLE	DOG	HORSE	MOTOR	PERSON	PLANT	SHEEP	SOFA	TRAIN	TV	MAP
STABLE DIFFUSION	35.71	24.26	13.67	14.96	1.17	**34.72**	31.76	41.43	9.76	20.66	25.39	36.04	27.37	35.90	10.46	3.78	17.50	36.68	30.89	13.53	23.28
DALLE-MINI	**47.18**	**43.13**	**35.51**	5.33	**19.23**	32.58	**41.23**	**66.72**	**12.03**	**43.98**	18.13	**43.98**	**36.71**	**51.68**	**19.04**	**14.97**	**34.12**	**42.74**	23.04	**33.36**	**33.23**

We noticed that the generated images are different from different generative models. In this paper, we use two effective open-source visual synthesis models, STABLE DIFFUSION and DALLE-MINI. We conduct a comparison on ISOD to verify the influence of synthesis models. In Tab. 8, we can find that DALLE-MINI can provide higher performance for IMAGINARYNET. We explained this as DALLE-MINI's results contain fewer objects, which are easier for the model to learn in the training.