Retaining Knowledge for Learning with Dynamic Definition

Abstract

Machine learning models are often deployed in settings where they must be constantly updated in response to the changes in class definitions while retaining high accuracy on previous learned definitions. A classical use case is the task of fraud detection, where new fraud scheme comes one after another. While such an update can be accomplished by re-training on the complete data, the process is inefficient and prevents real-time and on-device learning. On the other hand, efficient methods that incrementally learn from new data often result in the forgetting of previously-learned knowledge. We formally define this problem as Learning with Dynamic Definition (LDD) and demonstrate that popular models, such as the Vision Transformer and Roberta, exhibit substantial forgetting of past definitions. We present a first practical and provable solution to LDD. Our proposal is a hash-based memory model *RIDDLE* that solves evolving definitions by associating different instances only to relevant parameters. We prove that our model is a universal function approximater and theoretically bounds the knowledge lost during the update process. On practical tasks with evolving class definition in vision and NLP, our model outperforms baselines by up to 30% on the original dataset while providing competitive accuracy on the update dataset.

1 Introduction

Motivation: A common machine learning workflow is to first develop a task objective based on historical experience, then deploy a model trained to optimize the objective over a dataset. However, machine learning models rarely operate in such a static environment. Instead, models must be dynamically updated to accommodate changes in class definitions without forgetting previous knowledge. Consider the case of fraud detection, where models must adapt to emerging scam patterns while also providing protection against previously-known patterns. Also, machine learning models are used to identify harmful microbes given gene sequences. And it is important to perform well on new variants or newly discovered microorganisms. A similar situation arises when models are used to filter inappropriate content such as hate speech and violence. New phrases or previously-innocuous language may become inappropriate due to world events or attempts by users to circumvent the filter. While the supervised task remains the same (fraud or safe, harmful or not, inappropriate or appropriate, etc.), class definition evolves over time and likely differ significantly from the point of the first training. We refer to this setting as *Learning under Dynamic Definition* (LDD). It should be noted that this notion is very different for several other notions of distribution shift in the literature which we review in the next section.

A standard solution is to retrain the model on all available data (original dataset and data for the new definitions). This methodology is inefficient due to data storage and extra computation, and even prohibitive in large data or streaming scenarios. Furthermore, it prevents real-time and on-device learning. An ideal and efficient solution is to update the trained model incrementally only with data for the new definitions (e.g. using online gradient descent). However, this is a challenging process due to the tendency of machine learning models, in particular neural networks, to forget previous

knowledge. This situation, known as collapse/catastrophic forgetting [24], causes performance on the old definitions to decay.

Our Proposal: Catastrophic forgetting occurs because gradient updates from training examples in the update process are able to change parameters that are tuned for optimal performance on the original dataset [28]. Inspired by recent connections between random partitions and distribution models [19], we propose RIDDLE (Retaining Information in a Dynamically Defined Learning Environment), a novel architecture with meaningful parameter groupings. RIDDLE works by partitioning the input space and assigning a set of parameters to each partition. Gradient updates are forced to avoid parameters that are critical to prior knowledge. We summarize our technical contributions below.

- We introduce the RIDDLE (in Section 3), consisting of a set of parameters indexed using locality-sensitive hash functions. RIDDLE is computationally efficient and requires less memory than popular machine learning models with similar accuracy.

- We prove that RIDDLE is universal function approximator and can therefore represent any function(Section 4). We prove a formal connection between parameter usage and distribution similarity in Theorem 3.2.

- In Section 5, we apply RIDDLE in the dynamic definition setting for four real-world tasks. Our method outperforms baselines by up to 30% on the original dataset while achieving competitive accuracy on the new dataset.

2 Related Work

Continual Learning: Continual learning refers to learning and remembering multiple tasks from a stream of information. Current approaches can be split into three main categories (1) memory replay to complement neural networks [41, 27], (2) constraints on network updates [35, 26, 48], and (3) dynamic architectural adjustments to accommodate new information, such as additional layers [45, 55]. Continual learning methods encounter similar challenges to the ones presented by learning under dynamic distribution, most notably catastrophic forgetting. However, continual learning attempts to solve a sequence of related tasks, often expressed as task embeddings, over data that does not necessarily reflect changes in class definitions.

Train-Test Distribution Shift: Transfer learning and test-time adaptation attempt to remedy misalignments between the training and test distribution. Although such methods may seem relevant in learning with dynamic definition, they have dramatically different goals. Transfer learning attempts to adapt a model from a data-rich source domain to a data-scarce target domain, without regard for the performance on the source domain [59, 51, 53]. While several works on train-test distribution shift focus on robustness, it is from the perspective of out-of-distribution detection [23, 36] or uncertainty estimation [40, 30, 52]. Our objective is to provide models that perform well on both the original dataset and new dataset, where class definitions are different, rather than simply detect or adapt to the distribution change.

Online Learning: Online learning regards optimization as a process where a model is trained by interacting with a stream of data. Online learning algorithms attempt to minimize the *regret*, or difference between the loss of the predictions by the incrementally-trained model and the loss of the globally optimal model [44, 42]. Online learning methods attain minimal regret against adaptive adversaries and could be expected to perform well in the dynamic distribution setting. However, the best performing methods for non-convex online learning require retraining over all previous data at every time step [50], making them practically unsuitable for the objectives we consider.

Locality-Sensitive Hashing in Machine Learning: Locality-sensitive hash (LSH) functions are a central component of our proposal. An LSH family is a set of functions that maps similar inputs to the same hash value (with high probability). LSH is an incredibly powerful and well-studied framework, with the following formal definition [25, 8, 20, 5].

Definition 2.1 ((S_0, cS_0, p_1, p_2)-**sensitive hash family**)**.** A family $\mathcal{H}$ is called (S_0, cS_0, p_1, p_2)-sensitive with respect to a similarity function $sim(\cdot, \cdot)$ if for any two points $x, y \in \mathbb{R}^D$ and h chosen uniformly from $\mathcal{H}$ satisfies:

- If $sim(x, y) \geq S_0$ then $Pr[h(x) = h(y)] \geq p_1$

- If $sim(x, y) \leq cS_0$ then $Pr[h(x) = h(y)] \leq p_2$

The probability $Pr[h(x) = h(y)]$ is known as the collision probability of x and y, where we use the term "collision" to mean that two points map to the same hash value. For the purpose of our arguments, we use a stronger notion of LSH, in which the collision probability is a monotonic increasing function of the similarity between x and y. That is $Pr[h(x) = h(y)] \propto f(\text{sim}(x, y))$.

Under the above conditions, the collision probability $Pr[h(x) = h(y)]$ forms a positive semi-definite radial kernel [19]. A number of useful kernels can be obtained via LSH, including MinHash for Jaccard kernel [12], signed random projections for the angular kernel [15], and p-stable LSH for a kernel in Euclidean space [20].

Recent works have shown that LSH can be used for efficient statistical estimation [49, 14, 38, 19, 32, 33, 34, 56], compressive machine learning [31],nearest neighbor search [6, 8, 7] and to accelerate neural network training and inference [17, 16, 29, 37, 57]. A particularly relevant result is the RACE sketch [19], which solve kernel density estimation using the number of examples that fall into the random partitions induced by an LSH function.

3 RIDDLE for Learning with Dynamic Definition

Learning with Dynamic Definition: We formally define the problem as follows.

Definition 3.1. Given a model $f(x; \theta)$ and a loss $\ell(f(x; \theta), y)$, consider an original dataset $D^o = \{(x_i^o, y_i^o)\}_{i=1}^m$ drawn i.i.d. from a distribution P^o and an update dataset $D^u = \{(x_i^u, y_i^u)\}_{i=0}^n$ drawn i.i.d from distribution P^u. Let θ^o be the parameters that optimizes $\mathcal{L}_o(\theta) = \sum_{D^o} \ell(f(x; \theta), y)$. The dynamic definition learning problem is to find a solution minimizing $\mathcal{L}_{o+u}(\theta)$ when we are only given access to θ^o and D^u.

$$\mathcal{L}_{o+u}(\theta) = \sum_{(x,y) \in D^o} \ell(f(x; \theta), y) + \sum_{(x,y) \in D^u} \ell(f(x; \theta), y)$$

In this paper, we consider the model performance in response to the changes from P^o to P^u, specifically by allowing x to be drawn from different input spaces. Note that Definition 3.1 generalizes in a straightforward way to sequences of updating dataset by considering D^o to be the union of all prior data. The difficulty of the problem may be expressed in terms of the Kullback-Leibler divergence $D_{KL}(P^o \| P^u)$. Intuitively, small changes in distribution are easier to handle because θ need not change substantially to perform well on D^u.

Figure 1: The figure demonstrates a toy RIDDLE model with $L = 5$ and $R = 4$. Given an input x, we calculate its hash code $h(x)$ and access the weights at those locations. We return the average as the output.

3.1 Architecture

RIDDLE is a 2D parameter array S that contains L rows and R columns $S \in \mathbb{R}^{L \times R}$. The model is indexed by a set of L randomly generated LSH functions $h_l \to \{1, \dots R\} \in \mathbb{Z}$ for $l = 1, \dots L$. The prediction evaluated at a query x is defined as follows:

$$f(x; S, h) = \frac{1}{L} \sum_{l=1}^{L} S[l, h_l(x)] \tag{1}$$

Algorithmically, the process consists of three steps: (1) hash code computation, (2) partition look-ups, and (3) output averaging. Specifically, the model output for a query x is an average over the L parameters retrieved from S using the hash codes $h(x)$. Figure 3 illustrates a toy example.

For a classification problem with C classes, the 2D array is repeated C times, resulting in a 3D tensor of parameters $S \in \mathbb{R}^{C \times L \times R}$. The same LSH functions are used for all C repetitions, and the classification prediction for query x is defined as follows:

$$f(x; S, h) = \text{argmax}_{c \in C} \left(\frac{1}{L} \sum_{l=1}^{L} S[c, l, h_l(x)] \right)$$

RIDDLE can be used as a stand alone machine learning model, or combined with existing neural network architectures, see Figure 2. RIDDLE can be implemented in standard deep learning frameworks and trained using SGD (Algorithm 1). It should be noted that the parameters of LSH functions $h(x)$ are not trainable. Only the values in $S \in \mathbb{R}^{L \times R}$ will be updated by SGD. The inference process consists only of inexpensive hash evaluations and memory look-ups. We use LSH functions based on sparse projections [3], which compute $h(x)$ via an inner product with parameter vectors randomly drawn from $\{-1, 0, 1\}$ with probability $\{1/6, 2/3, 1/6\}$. With such a hash function, computation can be reduced to addition, subtraction and memory lookup.

Algorithm 1 RIDDLE Training

Input: Training Dataset D, $|D| = m$, number of rows L, number of cells R, learning rate η, error function $E(\cdot)$, number of epochs e, batch size b, random seed s.
Output: Trained Model S, Counters C
Initialize: Zero initialize $S \in \mathbb{R}^{L \times R}$; Zero initialize counters $C \in \mathbb{R}^{L \times R}$;Random generated L independent LSH functions $h_1, \ldots, h_L$ using random seed s;
for $i = 1 \to e$ **do**
    Shuffle dataset D
    for $j = 0 \to m/b - 1$ **do**
        Take b samples $\{x_{jb}, x_{jb+1}, \ldots, x_{(j+1)b-1}\}$ with labels $\{y_{jb}, y_{jb+1}, \ldots, y_{(j+1)b-1}\}$
        Compute gradient $g = \frac{1}{m} \nabla_S \sum_i E(f_{S,h}(x_i), y_i)$
        Apply update $S \to S - \eta g$
    end for
end for
for every $x_i \in D$ **do**
    Increase counters $C[l, h_l(x_i)] + = 1$ *for* $l = 1 \ldots L$
end for

3.2 RIDDLE for Learning with Dynamic Definition

Before we determine the class of functions that are representable using our model, we first demonstrate that this architecture addresses the problem from Definition 3.1. We consider a RIDDLE model $f(x; S, h)$ following the notation from Section 3.1. That is, we are given a model with parameters $\theta = (S, h)$ trained on D^o. We wish to adapt the model on D^u using gradient descent.

Parameter Separation: The RIDDLE partitions parameters in such a way that inputs from different distributions are likely to use different parameters. The parameter update may be written as:

$$S_{t+1} = S_t[l, h_l(x)] + \eta g[l] \text{ for } l = 1 \ldots L, \text{ where } g = \nabla \ell \left(\frac{1}{L} \sum_{l=1}^{L} S[l, h_l(x)], y \right)$$

From this expression, we can see that L parameters are involved in the computation of $f(x; S, h)$ - specifically, the parameters selected by the hash functions $\{h_1(x) \ldots h_L(x)\}$. Based on the LSH property (Definition 2.1), we expect unrelated inputs to have different hash values and therefore use different parameters. When P^u is significantly different from P^o, $x^u \in D^u$ and $x^o \in D^u$ are likely to activate different partition and thus use different parameter sets.

We formalize this intuition below by showing that the difference between $f(x; S, h)$ and its initialization is bounded by an estimate of the distribution P^o.

Theorem 3.2. *Given a dataset D, train a RIDDLE model $f(x; S, h)$ by running Algorithm 1 for e epochs with learning rate η and initialization S_0. Suppose the gradient norms are bounded by G. Then*

$$|\mathbb{E}_h[f(x; S, h) - f(x; S_0, h)]| \leq e\eta G \, \text{KDE}(x, D)$$

where $\text{KDE}(x, D)$ is the kernel density of x over D using the kernel of the LSH function h.

Theorem 3.2 allows us to prove the following guarantee:

Theorem 3.3. *Using the notation from Definition 3.1, let S_o be the sketch that optimizes the loss $\mathcal{L}_o(S)$ over D^o and S_{o+u} be the sketch obtained by training over D^u for e epochs with learning rate*

η and initialization S_o. If the loss is L-Lipschitz with G-bounded gradients, then:

$$\mathbb{E}_h[\mathcal{L}_o(S_{o+u}) - \mathcal{L}_o(S_o)] \leq \sum_{x \in D^o} GLe\eta \text{KDE}(x, D^u)$$

The loss difference in Theorem 3.3 quantifies the amount of information about D^o that is forgotten by the model when trained on D^u. The excess loss on example $x \in D^o$ is bounded by the kernel density estimate $\text{KDE}(x, D^u)$. When D^o and D^u are drawn from different distributions, which is the characteristic of learning under dynamic distribution, the density becomes small (i.e. as the divergence $D_{KL}(P^o \| P^u) \to \infty$, $\text{KDE}(x, D^u) \to 0$).

Parameter Importance: The RIDDLE allows us to determine the importance level of each parameter for encoding information from the original distribution with simple counting. We may do this by counting the number of inputs from D^o that fall into each partition, using a set of counters $C \in \mathbb{R}^{L \times R}$. Parameters with a large counter c can be regarded as important for the original distribution, as they participate in prediction for a large fraction of examples from D^o. Our intuition is that parameters corresponding to partitions with large count values are critical for performance on D^o and should not be adjusted. We use this idea to improve performance via partition-dependent learning rates. Specifically, we allow the learning rate $\eta(c)$ depend on the partition count c. We find that the following update rule provides good empirical results:

$$\eta(c) \propto \frac{\bar{c} + \alpha}{c \log c + 1}, \text{ where } \alpha \text{ is a constant}$$

4 RIDDLE is a Universal Function Approximator

In this section, we analyze the class of functions that can be represented using the RIDDLE. Using techniques from the sketching literature, we prove a probabilistic guarantee.

Intuition: To see why it is reasonable for our model to be a universal function approximator, observe that the function learned by RIDDLE is a piecewise-constant spline function. Splines are an incredibly powerful representation that can approximate any function, given sufficient flexibility in choosing the partitions (or knots) of the spline [47, 46]. For example, many neural networks can be written as compositions of piecewise-linear splines over a constrained set of partitions[11, 10, 9, 54]. In our case, the partition boundaries are determined by the intersection of LSH functions. With sufficient independent overlapping partitions (large L), our model attains a high-quality representation.

Proof Sketch: We prove that the expected output of our model is a universal function approximator, where the expectation is taken over the choice of LSH functions. We begin with a proof that any continuous and bounded function can be approximated arbitrarily well by a weighted kernel sum over an N point dataset. We then develop a process that constructs a RIDDLE $S \in \mathbb{R}^{L \times R}$ whose expected output is this kernel sum. Using Chernoff bounds, we show that the error between the model and the kernel sum becomes arbitrarily small as $L \to \infty$ (with high probability). Taken together, we have a probabilistic guarantee for the error between the RIDDLE and any continuous and bounded function.

Simplified optimization in practice: Constructing a RIDDLE over a carefully chosen N point dataset can approximate any continuous and bounded function. However, learning both the data and data weights with N being arbitrarily large poses difficulty in optimization. We simplify the optimization by observing that the output of the learning process is not a dataset but a model. Therefore, we consider the easier task of learning the model parameters values directly in practice as shown in Algorithm 1. This is a slight relaxation of the problem, however, we argue that with a row-sum constraint and a reasonable uniqueness assumption about the hash partitions, the two processes are equivalent in practice. Thus, the RIDDLE is a universal function approximator.

4.1 Weighted LSH Kernel Sums are Universal Function Approximators

We are interested in the representation capabilities of weighted kernel sums over an N-point dataset $D = \{x_1, ... x_N\}$. We consider the specific case where the kernel is the collision probability of an LSH function. Such kernels are referred to in the literature as *LSH kernels* [19].

$$f(x) = \sum_{i=1}^{N} \alpha_i \mathcal{K}(x, x_i)$$

The crucial property is that LSH kernels are *universal*. Informally, a kernel is universal if a weighted kernel sum over a carefully-chosen point set can approximate any function with arbitrary accuracy [39]. Some restrictions apply; the size of the point set is allowed to be arbitrarily large and the accuracy is computed over any compact subset of $\mathbb{R}^d$ rather than the entire space.

Definition 4.1. *Universal Kernel* [39]: Let $S(\mathcal{X})$ denote the space of bounded and continuous functions on a compact domain $\mathcal{X}$. Then a kernel $\mathcal{K}(x, y)$ is universal if it is continuous and induces a reproducing kernel Hilbert space that is dense in $S(\mathcal{X})$.

Applied to our problem, a universal kernel is one which can approximate any well-behaved function over compact subsets of $\mathbb{R}^d$ using a linear combination of kernels. The theory of universal kernels allows for a convergence-style proof for weighted LSH kernel sums. We begin by showing that the p-stable LSH functions are universal kernels. We defer proofs to the appendix.

Lemma 4.2. *The L2 LSH kernel [19] induced by the p-stable LSH function [20] is shift-invariant and universal.*

Theorem 4.3. *Given a continuous and bounded function $g(q)$ and any $\epsilon > 0$, there exists a set of coefficients $\{\alpha_n\}$, set of points $\{x_n\}$ and an integer N such that*

$$f_N(q) = \sum_{n=1}^{N} \alpha_N \mathcal{K}(x_n, q) \qquad \|f_N(q) - g(q)\|_{\mathcal{X}} \leq \epsilon$$

where $\mathcal{K}(x_n, q)$ is the L2 LSH kernel and $\mathcal{X}$ is any compact subset of $\mathbb{R}^d$.

4.2 RIDDLE for Weighted LSH Kernel Sums

The next step of our proof is to construct a RIDDLE capable of approximating $f_N(q)$ from Theorem 4.3. We consider a RIDDLE model with $S \in \mathbb{R}^{L \times R}$ constructed from a set of points $\{x_n\}$ with coefficient $\{\alpha_n\}$ in the following way. For every data point $x \in \{x_n\}$, we calculate the indices of x using a collection of L2 LSH functions $h_l(x)$ for $l = 1, \ldots, L$. Then, we increment the value of S at location $(l, h_l(x)$ with the weight α. To query the model, we calculate the index of the query q using the same LSH functions and retrieve the values $S[l, h_l(q)]$ for $l = 1, \ldots, L$, which we aggregate and return. It should be noted that recent algorithms from the sketching literature propose similar constructions [19, 18], but with the weights constrained to $\alpha_n \in \{+1, -1\}$.

One can prove S yields a sharp unbiased estimator for the weighted kernel sum (Proofs in appendix).

Theorem 4.4 (RIDDLE Estimator). *Given a dataset $\mathcal{D}$ of weighted samples $\{(\alpha_{x_i}, x_i)\}$, let $h(x)$ be an LSH function drawn from an LSH family with collision probability $\mathcal{K}(\cdot, \cdot)$. Let S be a 2d parameter array constructed using $h(x)$. For any query q,*

$$\mathbb{E}(S[h(q)]) = \sum_{i}^{|\mathcal{D}|} \alpha_{x_i} \mathcal{K}(x_i, q), \operatorname{var}(S[h(q)]) \leq \left(\sum_{i}^{|\mathcal{D}|} \alpha_{x_i} \sqrt{\mathcal{K}(x_i, q)} \right)^2$$

The key insight is that each row of S is an unbiased estimator for weighted sums of LSH kernels. By finding the central tendency of the L rows, we can obtain a sharp concentration around $f_N(q)$. Although we often use the average to do the aggregation in practice, we analyze the median-of-means estimator [4, 14], as it allows us to prove an exponential concentration of the estimate around the weighted KDE. Note that while this simplifies the proof, it does not affect the convergence to $f_N(q)$ as $L \to \infty$. We combine the variance bound from Theorem 4.4 with the median-of-means guarantee to obtain a relationship between the RIDDLE parameters S, weighted kernel values, and estimation error.

Theorem 4.5 (Weighted-KDE Estimation Error). *Let $Z(q)$ be the median-of-means estimate constructed using the L unbiased estimators. Then with probability $1 - \delta$,*

$$|Z(q) - f_K(q)| \leq \epsilon \qquad \epsilon = 6 \frac{\tilde{f}_K(q)}{\sqrt{L}} \sqrt{\log 1/\delta}$$

where $f_K(q)$ and $\tilde{f}_K(q)$ are the weighted KDE with kernels $\mathcal{K}(x, q)$ and $\sqrt{\mathcal{K}(x, q)}$, respectively.

The universal approximation property of our model follows by observing that the error ϵ in Theorem 4.5 goes to zero as $N \to \infty$ and $\epsilon \to 0$ in Theorem 4.3 as $L \to \infty$.

Figure 2: RIDDLE can be used as a stand only model, as shown in (a). We use this setting for experiments on MNIST-binary and all experiments studying expressiveness. RIDDLE can also be combined with existing neural networks, as shown in (b). We replace the classification layer with RIDDLE for experiments on CIFAR10, ImageNet and News

5 Experiments

In this section, we evaluate the RIDDLE on practical dynamic distribution learning tasks. Specifically, we investigate whether the model can adapt to new distributions and whether it can retain good performance on the original. We also provide an extensive study on the expressiveness and efficiency.

5.1 RIDDLE for Learning under Dynamic Distribution

We consider a set of datasets that reflect dynamic distributions. We organize each dataset into two parts: the original dataset D^o and the update dataset D^u. D^o and D^u have significant semantic differences and do not share any overlapping training data. We perform grid search over the hyperparameter space and train all methods to full convergence on the original dataset D^o. Then, for updating the models, we train models on the update dataset D^u, where the initialization consists of the parameters obtained on D^o. We are interested in the performance on the original test set (drawn from distribution P^o) as well as the updated test set (drawn from P^u) after the updating process.

For tasks where it is reasonable (CIFAR10, ImageNet and News), we exploit recent advances in large scale pretrained models. Pretrained models are usually trained on a diverse corpus of unlabeled data and are likely to provide good featurization across distributions. [43] also observe that pretrained models are more resistant to forgetting. We replace the final layer with RIDDLE.

MNIST Binary: We randomly partitioned digits into two groups $(4, 1, 7, 5, 3$ and $9, 0, 8, 6, 2)$ and train the model to predict the group assignment of an image. For the original distribution, we randomly choose 3 digits from the first group and 3 digits from the second group. The update dataset consists of the remaining digits.

CIFAR10: The task is to predict whether the object in the image is capable of carrying things (e.g. a car can carry things, while a banana cannot). The original dataset contains images of 6 out of 10 objects that can and cannot carry things, and the update dataset contains the remaining 4 objects.

ImageNet: The task is to predict whether a person is allergic to the object in the image. We assign images to the allergen and non-allergen classes based on the national allergen directory [1]. The original dataset contains a subset of allergens and non-allergens, while the update dataset contains the remaining objects. This task was built to mimic the the seasonal addition and sensitization of new allergens.

News: [2] The task is to predict whether a person would be interested in a new article given a caption and short description. We organize this dataset to reflect changes in a user's interests. The news dataset can be divided into 34 topics. We randomly flag half of these topics as interesting. The original dataset contains news from some topics, while the update dataset contains the rest.

5.2 Results

Table A.1 summarizes the accuracy of all models after training on the original dataset and after the update. After training on the original dataset, we observe that all models achieve roughly the same

Figure 3: Accuracy on the original test set while training on the update distribution. We observe that the RIDDLE performance remains nearly constant for all datasets, while baseline methods degrade rapidly with inputs from the new distribution.

		Trained on original dataset		Updated on update dataset	
Dataset	Method	Original	Update	Original	Update
MNIST Binary	MLP	99.2	59.1	69.1	98.9
	RIDDLE	99.2	60.2	**98.3**	98.0
CIFAR	Resnet18	93.3	69.4	63.22	88.9
	ViT	93.3	72.6	74.4	92.7
	RIDDLE	93.0	75.7	**89.0**	90.9
ImageNet	Resnet18	76.0	45.2	46.53	62.5
	ViT	74.3	45.3	55.6	71.5
	RIDDLE	74.3	45.8	**67.1**	70.5
News	RoBERTa	96.1	54.8	74.0	85.7
	RIDDLE	96.6	54.6	**89.7**	86.4

Table 1: This table summarizes the accuracy after training on original dataset, and after training on update dataset. The RIDDLE obtains comparable accuracy on original test set and update test set after trained on corresponding train set. The RIDDLE's accuracy is significantly higher than all baselines on original test set after updating.

accuracy on original test set but much worse accuracy on update test set. This behavior is expected since the update dataset is significantly different from the original dataset.

We observe differences after training on the update dataset. Our baseline models experience significant performance degradation on the original test set. The RIDDLE outperforms all baselines by up to 30% in terms of original test set accuracy. Figure 3 shows the accuracy on the original test set during the update process. Unsurprisingly, the baseline performance decreases as we see more training samples from update test set. Models such as Resnet18 and ViT display catastrophic forgetting behavior, eventually performing no better than random. The RIDDLE model performance, on the other hand, remains nearly constant and lies above all baselines throughout the update process, especially on image datasets. On the updated test set, the RIDDLE achieves competitive accuracy (Table A.1), indicating that it is learning the properties of both distributions. Note that ViT outperforms Resnet18 on both CIFAR10 and ImageNet, which confirms our intuition that pretrained models are inherently more robust to distribution changes. By switching the final classification layer to the RIDDLE, we increase the accuracy by a large margin. The experiment results strongly support our hypothesis

Table 2: This table summarizes the accuracy comparison. NN1 and NN2 denote two different deep learning models. RIDDLE achieves higher accuracy than at least half of the baselines on all datasets.

Dataset	LightGBM	Random Forest	XGBoost	NN1	NN2	RIDDLE
Susy	0.7903	0.7880	0.7926	0.8019	0.8024	0.7924
HAR	0.8532	0.8387	0.8532	0.9027	0.9123	0.9001
Covtype	0.9565	0.9932	0.9874	0.9836	0.9936	0.9853
Connect4	0.8171	0.8335	0.8171	0.8558	0.8657	0.8586
Fashion MNIST	0.8848	0.8777	0.8848	0.8852	0.8889	0.8852
Boston Housing	1.77	2.05	1.62	2.57	2.16	1.74

Table 3: This table summarizes the efficiency comparison between the RIDDLE and a neural network (NN) with similar accuracy. The RIDDLE reduces memory by up to 3.7x, FLOPs by up to 17x and inference time by up to 3.9x.

Dataset	Method	Accuracy	Memory(MB)	Flops (M)	Inference Time (μs)
MNIST	NN	0.9815	3.59	0.90	164.177
	RS	0.9784	1.36(1.6X)	0.15(6.1X)	42.003 (3.9X)
Fashion MNIST	NN	0.8852	2.59	0.65	131.385
	RS	0.8852	1.92(1.6X)	0.13(5X)	39.228 (3.3X)
HAR	NN	0.9027	2.11	0.53	166.584
	RS	0.9001	1.18(1.8X)	0.18 (2.9X)	46.567 (3.6X)
Boston Housing	NN	2.16	1.96	0.51	61.338
	RS	1.74	0.53(3.7X)	0.03 (17X)	21.862 (2.8X)

that the RIDDLE retains the ability to adapt to new distributions while being less vulnerable than established methods to knowledge loss.

5.3 Study of Expressiveness and Efficiency

These experiments are intended to determine whether our model is competitive among popular machine learning models. Our goal is to show that RIDDLE provides a good model representation for a variety of tasks. We curated a diverse set of datasets from UCI and Kaggle. These datasets cover a wide range of tasks and domains and are widely used as benchmarks in other works [58, 22]. All experiments are conducted on a machine equipped with 96 24-core/2-thread/2-socket processors (Intel Xeon(R) Gold 5220R 2.20GHz) and 8 Nvidia V100 32GB.

In Table 2, we observe that RIDDLE outperforms popular linear methods and is competitive compared to deep learning methods. NN1 and NN2 denote two different neural network architectures(Details in Appendix). Both the architecture and evaluation metric is included in Table A.2. We also investigate the efficiency and memory requirement. This is important, as it shows that RIDDLE does not outperform other methods due to an increased parameter size. Table 3 shows that RIDDLE attains the same accuracy as baseline methods with a smaller memory footprint, fewer FLOPs and a faster inference speed. Specifically, we use up to 3.7X less memory, use 17X less FLOPs, and achieve 3.9x faster inference speed. The memory improvements likely arise from the meaningful parameter groupings, while the computational improvements are because it only uses addition, subtraction and array lookup operations. This experiment confirms that even though the RIDDLE allocates different parameters to different distributions, we do not require more parameters than existing methods to achieve robustness or accuracy. One limitation now is that memory grows linear with number of class, which can be address with smart hashing mechanism.

6 Conclusion

In this work, we propose an expressive model RIDDLE for learning under dynamic distribution. Our setup concerns common scenarios where model has to be updated given distribution changes. The model is structured to be invulnerable to forgetting because gradients updates are naturally restricted to only input relevant parameters. This work poses minimal negative social impact. Our method could be used to increase model robustness by updating model on interested distribution. Moreover, our method could save computation cost since updating doesn't require training over all data.

References

[1] Asthma and allergies foundation of america, https://www.aafa.org/types-of-allergies/.

[2] News category dataset, https://www.kaggle.com/datasets/rmisra/news-category-dataset.

[3] Dimitris Achlioptas. Database-friendly random projections: Johnson-lindenstrauss with binary coins. *Journal of Computer and System Sciences*, 66(4):671–687, 2003. Special Issue on PODS 2001.

[4] Noga Alon, Yossi Matias, and Mario Szegedy. The space complexity of approximating the frequency moments. *Journal of Computer and system sciences*, 58(1):137–147, 1999.

[5] Alexandr Andoni, Piotr Indyk, TMM Laarhoven, Ilya Razenshteyn, and Ludwig Schmidt. Practical and optimal lsh for angular distance. In *Advances in Neural Information Processing Systems (NIPS)*, pages 1225–1233. Curran Associates, 2015.

[6] Alexandr Andoni, Piotr Indyk, Huy L Nguyen, and Ilya Razenshteyn. Beyond locality-sensitive hashing. In *Proceedings of the twenty-fifth annual ACM-SIAM symposium on Discrete algorithms*, pages 1018–1028. SIAM, 2014.

[7] Alexandr Andoni, Thijs Laarhoven, Ilya Razenshteyn, and Erik Waingarten. Optimal hashing-based time-space trade-offs for approximate near neighbors. In *Proceedings of the Twenty-Eighth Annual ACM-SIAM Symposium on Discrete Algorithms (SODA)*, pages 47–66. SIAM, 2017.

[8] Alexandr Andoni and Ilya Razenshteyn. Optimal data-dependent hashing for approximate near neighbors. In *Proceedings of the forty-seventh annual ACM symposium on Theory of computing*, pages 793–801, 2015.

[9] Randall Balestriero and Richard G. Baraniuk. Mad max: Affine spline insights into deep learning. *Proceedings of the IEEE*, 109(5):704–727, 2021.

[10] Randall Balestriero, Romain Cosentino, Herve Glotin, and Richard Baraniuk. Spline filters for end-to-end deep learning. In Jennifer Dy and Andreas Krause, editors, *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pages 364–373. PMLR, 10–15 Jul 2018.

[11] Randall Balestriero and richard baraniuk. A spline theory of deep learning. In Jennifer Dy and Andreas Krause, editors, *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pages 374–383. PMLR, 10–15 Jul 2018.

[12] A. Broder. On the resemblance and containment of documents. In *Proceedings of the Compression and Complexity of Sequences 1997*, SEQUENCES '97, page 21, USA, 1997. IEEE Computer Society.

[13] Claudio Carmeli, Ernesto De Vito, Alessandro Toigo, and Veronica Umanitá. Vector valued reproducing kernel hilbert spaces and universality. *Analysis and Applications*, 8(01):19–61, 2010.

[14] Moses Charikar and Paris Siminelakis. Hashing-based-estimators for kernel density in high dimensions. In *2017 IEEE 58th Annual Symposium on Foundations of Computer Science (FOCS)*, pages 1032–1043. IEEE, 2017.

[15] Moses S. Charikar. Similarity estimation techniques from rounding algorithms. In *Proceedings of the Thiry-Fourth Annual ACM Symposium on Theory of Computing*, STOC '02, page 380–388, New York, NY, USA, 2002. Association for Computing Machinery.

[16] Beidi Chen, Zichang Liu, Binghui Peng, Zhaozhuo Xu, Jonathan Lingjie Li, Tri Dao, Zhao Song, Anshumali Shrivastava, and Christopher Re. {MONGOOSE}: A learnable {lsh} framework for efficient neural network training. In *International Conference on Learning Representations*, 2021.

[17] Beidi Chen, Tharun Medini, and Anshumali Shrivastava. SLIDE : In defense of smart algorithms over hardware acceleration for large-scale deep learning systems. *CoRR*, abs/1903.03129, 2019.

[18] Benjamin Coleman, Richard Baraniuk, and Anshumali Shrivastava. Sub-linear memory sketches for near neighbor search on streaming data. In *International Conference on Machine Learning*, pages 2089–2099. PMLR, 2020.

[19] Benjamin Coleman and Anshumali Shrivastava. *Sub-Linear RACE Sketches for Approximate Kernel Density Estimation on Streaming Data*, page 1739–1749. Association for Computing Machinery, New York, NY, USA, 2020.

[20] Mayur Datar, Nicole Immorlica, Piotr Indyk, and Vahab S. Mirrokni. Locality-sensitive hashing scheme based on p-stable distributions. In *Proceedings of the Twentieth Annual Symposium on Computational Geometry*, SCG '04, page 253–262, New York, NY, USA, 2004. Association for Computing Machinery.

[21] Mayur Datar, Nicole Immorlica, Piotr Indyk, and Vahab S Mirrokni. Locality-sensitive hashing scheme based on p-stable distributions. In *Proceedings of the twentieth annual symposium on Computational geometry*, pages 253–262, 2004.

[22] Nick Erickson, Jonas Mueller, Alexander Shirkov, Hang Zhang, Pedro Larroy, Mu Li, and Alexander Smola. Autogluon-tabular: Robust and accurate automl for structured data, 2020.

[23] Stanislav Fort, Jie Ren, and Balaji Lakshminarayanan. Exploring the limits of out-of-distribution detection. *CoRR*, abs/2106.03004, 2021.

[24] Ian J. Goodfellow, Mehdi Mirza, Da Xiao, Aaron Courville, and Yoshua Bengio. An empirical investigation of catastrophic forgetting in gradient-based neural networks, 2013.

[25] Piotr Indyk and Rajeev Motwani. Approximate nearest neighbors: Towards removing the curse of dimensionality. In *Proceedings of the Thirtieth Annual ACM Symposium on Theory of Computing*, STOC '98, page 604–613, New York, NY, USA, 1998. Association for Computing Machinery.

[26] Heechul Jung, Jeongwoo Ju, Minju Jung, and Junmo Kim. Less-forgetting learning in deep neural networks. *arXiv preprint arXiv:1607.00122*, 2016.

[27] Nitin Kamra, Umang Gupta, and Yan Liu. Deep generative dual memory network for continual learning. *arXiv preprint arXiv:1710.10368*, 2017.

[28] James Kirkpatrick, Razvan Pascanu, Neil Rabinowitz, Joel Veness, Guillaume Desjardins, Andrei A Rusu, Kieran Milan, John Quan, Tiago Ramalho, Agnieszka Grabska-Barwinska, et al. Overcoming catastrophic forgetting in neural networks. *Proceedings of the national academy of sciences*, 114(13):3521–3526, 2017.

[29] Nikita Kitaev, Łukasz Kaiser, and Anselm Levskaya. Reformer: The efficient transformer, 2020.

[30] Balaji Lakshminarayanan, Alexander Pritzel, and Charles Blundell. Simple and scalable predictive uncertainty estimation using deep ensembles. *Advances in neural information processing systems*, 30, 2017.

[31] Xiaoyun Li and Ping Li. Generalization error analysis of quantized compressive learning. *Advances in Neural Information Processing Systems*, 32, 2019.

[32] Xiaoyun Li and Ping Li. Random projections with asymmetric quantization. *Advances in Neural Information Processing Systems*, 32, 2019.

[33] Xiaoyun Li and Ping Li. Quantization algorithms for random fourier features. In *International Conference on Machine Learning*, pages 6369–6380. PMLR, 2021.

[34] Xiaoyun Li and Ping Li. Quantization algorithms for random fourier features. In *International Conference on Machine Learning*, pages 6369–6380. PMLR, 2021.

[35] Zhizhong Li and Derek Hoiem. Learning without forgetting. *IEEE transactions on pattern analysis and machine intelligence*, 40(12):2935–2947, 2017.

[36] Shiyu Liang, Yixuan Li, and R. Srikant. Principled detection of out-of-distribution examples in neural networks. *CoRR*, abs/1706.02690, 2017.

[37] Zichang Liu, Zhaozhuo Xu, Alan Baonan Ji, Jonathan Li, Beidi Chen, and Anshumali Shrivastava. Climbing the WOL: training for cheaper inference. *CoRR*, abs/2007.01230, 2020.

[38] Chen Luo and Anshumali Shrivastava. Arrays of (locality-sensitive) count estimators (ace): Anomaly detection on the edge. In *Proceedings of the 2018 World Wide Web Conference*, WWW '18, page 1439–1448, Republic and Canton of Geneva, CHE, 2018. International World Wide Web Conferences Steering Committee.

[39] Charles A Micchelli, Yuesheng Xu, and Haizhang Zhang. Universal kernels. *Journal of Machine Learning Research*, 7(12), 2006.

[40] Yaniv Ovadia, Emily Fertig, Jie Ren, Zachary Nado, David Sculley, Sebastian Nowozin, Joshua Dillon, Balaji Lakshminarayanan, and Jasper Snoek. Can you trust your model's uncertainty? evaluating predictive uncertainty under dataset shift. *Advances in neural information processing systems*, 32, 2019.

[41] German I Parisi, Jun Tani, Cornelius Weber, and Stefan Wermter. Lifelong learning of spatiotemporal representations with dual-memory recurrent self-organization. *Frontiers in neurorobotics*, page 78, 2018.

[42] Sebastian Pokutta and Huan Xu. Adversaries in online learning revisited: with applications in robust optimization and adversarial training. *CoRR*, abs/2101.11443, 2021.

[43] Vinay Venkatesh Ramasesh, Aitor Lewkowycz, and Ethan Dyer. Effect of scale on catastrophic forgetting in neural networks. In *International Conference on Learning Representations*, 2022.

[44] Alon Resler and Yishay Mansour. Adversarial online learning with noise. *CoRR*, abs/1810.09346, 2018.

[45] Andrei A Rusu, Neil C Rabinowitz, Guillaume Desjardins, Hubert Soyer, James Kirkpatrick, Koray Kavukcuoglu, Razvan Pascanu, and Raia Hadsell. Progressive neural networks. *arXiv preprint arXiv:1606.04671*, 2016.

[46] Jürgen Schmidhuber. Discovering problem solutions with low kolmogorov complexity and high generalization capability. Technical report, MACHINE LEARNING: PROCEEDINGS OF THE TWELFTH INTERNATIONAL CONFERENCE, 1994.

[47] Isaac J Schoenberg. Contributions to the problem of approximation of equidistant data by analytic functions. In *IJ Schoenberg Selected Papers*, pages 3–57. Springer, 1988.

[48] Joan Serra, Didac Suris, Marius Miron, and Alexandros Karatzoglou. Overcoming catastrophic forgetting with hard attention to the task. In *International Conference on Machine Learning*, pages 4548–4557. PMLR, 2018.

[49] Ryan Spring and Anshumali Shrivastava. A new unbiased and efficient class of lsh-based samplers and estimators for partition function computation in log-linear models, 2017.

[50] Arun Sai Suggala and Praneeth Netrapalli. Online non-convex learning: Following the perturbed leader is optimal. *CoRR*, abs/1903.08110, 2019.

[51] Yu Sun, Xiaolong Wang, Zhuang Liu, John Miller, Alexei A. Efros, and Moritz Hardt. Test-time training with self-supervision for generalization under distribution shifts, 2020.

[52] Joost Van Amersfoort, Lewis Smith, Yee Whye Teh, and Yarin Gal. Uncertainty estimation using a single deep deterministic neural network. In *International conference on machine learning*, pages 9690–9700. PMLR, 2020.

[53] Dequan Wang, Evan Shelhamer, Shaoteng Liu, Bruno Olshausen, and Trevor Darrell. Tent: Fully test-time adaptation by entropy minimization, 2021.

[54] Zichao Wang, Randall Balestriero, and Richard Baraniuk. A MAX-AFFINE SPLINE PERSPECTIVE OF RECURRENT NEURAL NETWORKS. In *International Conference on Learning Representations*, 2019.

[55] Jaehong Yoon, Eunho Yang, Jeongtae Lee, and Sung Ju Hwang. Lifelong learning with dynamically expandable networks. *arXiv preprint arXiv:1708.01547*, 2017.

[56] Amir Zandieh, Navid Nouri, Ameya Velingker, Michael Kapralov, and Ilya Razenshteyn. Scaling up kernel ridge regression via locality sensitive hashing. In *International Conference on Artificial Intelligence and Statistics*, pages 4088–4097. PMLR, 2020.

[57] Minjia Zhang, Xiaodong Liu, Wenhan Wang, Jianfeng Gao, and Yuxiong He. Navigating with graph representations for fast and scalable decoding of neural language models. *arXiv preprint arXiv:1806.04189*, 2018.

[58] Zhi-Hua Zhou and Ji Feng. Deep forest: Towards an alternative to deep neural networks. *CoRR*, abs/1702.08835, 2017.

[59] Fuzhen Zhuang, Zhiyuan Qi, Keyu Duan, Dongbo Xi, Yongchun Zhu, Hengshu Zhu, Hui Xiong, and Qing He. A comprehensive survey on transfer learning. *Proceedings of the IEEE*, 109(1):43–76, 2020.