BiPointNet: Binary Neural Network for Point Clouds

Haotong Qin[*1,2]**, Zhongang Cai**[*3]**, Mingyuan Zhang**[*3]**, Yifu Ding**[1]**, Haiyu Zhao**[3]**,
Shuai Yi**[3]**, Xianglong Liu**[†1]**, Hao Su**[4]
[1]State Key Lab of Software Development Environment, Beihang University
[2]Shen Yuan Honors College, Beihang University   [3]SenseTime Research
[4]University of California, San Diego
{qinhaotong,xlliu}@nlsde.buaa.edu.cn, zjdyf@buaa.edu.cn
{caizhongang, zhangmingyuan, zhaohaiyu, yishuai}@sensetime.com
haosu@eng.ucsd.edu

Abstract

To alleviate the resource constraint for real-time point cloud applications that run on edge devices, in this paper we present BiPointNet, the first model binarization approach for efficient deep learning on point clouds. We discover that the immense performance drop of binarized models for point clouds mainly stems from two challenges: aggregation-induced feature homogenization that leads to a degradation of information entropy, and scale distortion that hinders optimization and invalidates scale-sensitive structures. With theoretical justifications and in-depth analysis, our BiPointNet introduces *Entropy-Maximizing Aggregation* (EMA) to modulate the distribution before aggregation for the maximum information entropy, and *Layer-wise Scale Recovery* (LSR) to efficiently restore feature representation capacity. Extensive experiments show that BiPointNet outperforms existing binarization methods by convincing margins, at the level even comparable with the full precision counterpart. We highlight that our techniques are generic, guaranteeing significant improvements on various fundamental tasks and mainstream backbones. Moreover, BiPointNet gives an impressive $14.7\times$ speedup and $18.9\times$ storage saving on real-world resource-constrained devices.

1 Introduction

With the advent of deep neural networks that directly process raw point clouds (PointNet (Qi et al., 2017a) as the pioneering work), great success has been achieved in learning on point clouds (Qi et al., 2017b; Li et al., 2018; Wang et al., 2019a; Wu et al., 2019; Thomas et al., 2019; Liu et al., 2019b; Zhang et al., 2019b). Point cloud applications, such as autonomous driving and augmented reality, often require real-time interaction and fast response. However, computation for such applications is usually deployed on resource-constrained edge devices. To address the challenge, novel algorithms, such as Grid-GCN (Xu et al., 2020b), RandLA-Net (Hu et al., 2020), and PointVoxel (Liu et al., 2019d), have been proposed to accelerate those point cloud processing networks. While significant speedup and memory footprint reduction have been achieved, these works still rely on expensive floating-point operations, leaving room for further optimization of the performance from the model quantization perspective. Model binarization (Rastegari et al., 2016; Bulat & Tzimiropoulos, 2019; Hubara et al., 2016; Wang et al., 2020; Zhu et al., 2019; Xu et al., 2019) emerged as one of the most promising approaches to optimize neural networks for better computational and memory usage efficiency. Binary Neural Networks (BNNs) leverage 1) compact binarized parameters that take small memory space, and 2) highly efficient bitwise operations which are far less costly compared to the floating-point counterparts.

Despite that in 2D vision tasks (Krizhevsky et al., 2012; Simonyan & Zisserman, 2014; Szegedy et al., 2015; Girshick et al., 2014; Girshick, 2015; Russakovsky et al., 2015; Wang et al., 2019b;

---

[*]equal contributions
[†]corresponding author

Figure 1: Overview of our BiPointNet on PointNet base model, applying Entropy-Maximizing Aggregation (EMA) and Layer-wise Scale Recovery (LSR). EMA consists of the transformation unit and the aggregation unit for maximizing the information entropy of feature after binarization. LSR with the learnable layer-wise scaling factor α is applied to address the scale distortion of bi-linear layers (which form the BiMLPs), flexibly restore the distorted output to reasonable values

Zhang et al., 2021) has been studied extensively by the model binarization community, the methods developed are not readily transferable for 3D point cloud networks due to the fundamental differences between 2D images and 3D point clouds. First, to gain efficiency in processing *unordered* 3D points, many point cloud learning methods rely heavily on pooling layers with large receptive field to aggregate point-wise features. As shown in PointNet (Qi et al., 2017b), global pooling provides a strong recognition capability. However, this practice poses challenges for binarization. Our analyses show that the degradation of feature diversity, a persistent problem with binarization (Liu et al., 2019a; Qin et al., 2020b; Xie et al., 2017), is significantly amplified by the global aggregation function (Figure 2), leading to homogenization of global features with limited discriminability. Second, the binarization causes immense scale distortion at the point-wise feature extraction stage, which is detrimental to model performance in two ways: the saturation of forward-propagated features and backward-propagated gradients hinders optimization, and the disruption of the scale-sensitive structures (Figure 3) results in the invalidation of their designated functionality.

In this paper, we provide theoretical formulations of the above-mentioned phenomenons and obtain insights through in-depth analysis. Such understanding allows us to propose a method that turns full-precision point cloud networks into extremely efficient yet strong binarized models (see the overview in Figure 1). To tackle the homogenization of the binarized features after passing the aggregation function, we study the correlation between the information entropy of binarization features and the performance of point cloud aggregation functions. We thus propose *Entropy-Maximizing Aggregation* (EMA) that shifts the feature distribution towards the statistical optimum, effectively improving expression capability of the global features. Moreover, given maximized information entropy, we further develop *Layer-wise Scale Recovery* (LSR) to efficiently restore the output scale that enhances optimization, which allows scale-sensitive structures to function properly. LSR uses only one learnable parameter per layer, leading to negligible storage increment and computation overhead.

Our BiPointNet is the first binarizatoin approaches to deep learning on point clouds, and it outperforms existing binarization algorithms for 2D vision by convincing margins. It is even almost on par (within $\sim$ 1-2%) with the full-precision counterpart. Although we conduct most analysis on the PointNet baseline, we show that our methods are generic and can be readily extendable to other popular backbones, such as PointNet++ (Qi et al., 2017b), PointCNN (Li et al., 2018), DGCNN (Wang et al., 2019a), and PointConv (Wu et al., 2019), which are the representatives of mainstream categories of point cloud feature extractors. Moreover, extensive experiments on multiple fundamental tasks on the point cloud, such as classification, part segmentation, and semantic segmentation, highlight that our BiPointNet is task-agnostic. Besides, we highlight that our EMA and LSR are efficient and easy to implement in practice: in the actual test on popular edge devices, BiPointNet achieves $14.7\times$ speedup and $18.9\times$ storage savings compared to the full-precision PointNet. Our code is released at https://github.com/htqin/BiPointNet.

2 RELATED WORK

Network Binarization. Recently, various quantization methods for neural networks have emerged, such as uniform quantization (Gong et al., 2019; Zhu et al., 2020), mixed-precision quantization (Wu

et al., 2018; Yu et al., 2020), and binarization. Among these methods, binarization enjoys compact binarized parameters and highly efficient bitwise operations for extreme compression and acceleration (Rastegari et al., 2016; Qin et al., 2020a). In general, the forward and backward propagation of binarized models in the training process can be formulated as:

$$\text{Forward}: b = \texttt{sign}(x) = \begin{cases} +1, & \text{if } x \geq 0 \\ -1, & \text{otherwise} \end{cases} \qquad \text{Backward}: g_x = \begin{cases} g_b, & \text{if } x \in (-1, 1) \\ 0, & \text{otherwise} \end{cases} \quad (1)$$

where x denotes the element in floating-point weights and activations, b denotes the element in binarized weights $\mathbf{B_w}$ and activations $\mathbf{B_a}$. g_x, and g_b donate the gradient $\frac{\partial C}{\partial x}$ and $\frac{\partial C}{\partial b}$, respectively, where C is the cost function for the minibatch. In forward propagation, $\texttt{sign}$ function is directly applied to obtain the binary parameters. In backward propagation, the Straight-Through Estimator (STE) (Bengio et al., 2013) is used to obtain the derivative of the $\texttt{sign}$ function, avoiding getting all zero gradients. The existing binarization methods are designed to obtain accurate binarized networks by minimizing the quantization error (Rastegari et al., 2016; Zhou et al., 2016; Lin et al., 2017), improving loss function (Ding et al., 2019; Hou et al., 2017), reducing the gradient error (Liu et al., 2018; 2020), and designing novel structures and pipelines (Martinez et al., 2020). Unfortunately, we show in Sec 3 that these methods, designed for 2D vision tasks, are not readily transferable to 3D point clouds.

Deep Learning on Point Clouds. PointNet (Qi et al., 2017a) is the first deep learning model that processes raw point clouds directly. The basic building blocks proposed by PointNet such as MLP for point-wise feature extraction and max pooling for global aggregation (Guo et al., 2020) have become the popular design choices for various categories of newer backbones: 1) the pointwise MLP-based such as PointNet++ (Qi et al., 2017b); 2) the graph-based such as DGCNN (Xu et al., 2020b); 3) the convolution-based such as PointCNN (Li et al., 2018), PointConv (Wu et al., 2019) RS-CNN (Liu et al., 2019c) and KP-Conv (Thomas et al., 2019). Recently, methods are proposed for efficient deep learning on point clouds through novel data structuring (Xu et al., 2020b), faster sampling (Hu et al., 2020), adaptive filters (Xu et al., 2020a), efficient representation (Liu et al., 2019d) or convolution operation (Zhang et al., 2019b) . However, they still use expensive floating-point parameters and operations, which can be improved by binarization.

3 METHODS

Binarized models operate on efficient binary parameters, but often suffer large performance drop. Moreover, the unique characteristics of point clouds pose even more challenges. We observe there are two main problems: first, aggregation of a large number of points leads to a severe loss of feature diversity; second, binarization induces an immense scale distortion, that undermines the functionality of scale-sensitive structures. In this section, we discuss our observations, and propose our BiPointNet with theoretical justifications.

3.1 BINARIZATION FRAMEWORK

We first give a brief introduction to our framework that binarizes a floating-point network. For example, deep learning models on point clouds typically contain multi-layer perceptrons (MLPs) for feature extraction. In contrast, the binarized models contain binary MLPs (BiMLPs), which are composed of binarized linear (bi-linear) layers. Bi-linear layers perform the extremely efficient bitwise operations (XNOR and Bitcount) on the lightweight binary weight/activation. Specifically, the activation of the bi-linear layer is binarized to $\mathbf{B_a}$, and is computed with the binarized weight $\mathbf{B_w}$ to obtain the output $\mathbf{Z}$:

$$\mathbf{Z} = \mathbf{B_a} \odot \mathbf{B_w}, \qquad (2)$$

where $\odot$ denotes the inner product for vectors with bitwise operations XNOR and Bitcount. When B_w and B_a denote the random variables in $\mathbf{B_w}$ and $\mathbf{B_a}$, we represent their probability mass function as $p_{B_w}(b_w)$, and $p_{B_a}(b_a)$.

Moreover, we divide the BiPointNet into units for detailed discussions. In BiPointNet, the original data or feature $\mathbf{X} \in \mathbb{R}^{n \times c}$ first enters the symmetric function Ω, which represents a composite function built by stacking several permutation equivariant and permutation invariant layers (e.g., nonlinear layer, bi-linear layer, max pooling). And then, the output $\mathbf{Y} \in \mathbb{R}^{n \times k}$ is binarized to obtain

| (a) Point-wise features to be aggregated. | (b) Full-precision features aggregated with max pooling. | (c) Binarized features aggregated with max pooling. | (d) Binarized features aggregated with EMA. |

Figure 2: Aggregation-induced feature homogenization. (a) shows the activation of each test sample in a batch of ModelNet40. In (b)-(d), the single feature vectors pooled from all points are mapped to colors. The diversity of colors represents the diversity of pooled features. The original aggregation design is incompatible with binarization, leading to the homogenization of output features in (c), whereas our proposed EMA retains high information entropy, shown in (d)

the binary feature $\mathbf{B} \in \{-1, 1\}^{i \times k}$, where i takes n when the feature is modeled independently and takes 1 when the feature is aggregated globally. The single unit is thus represented as

$$\mathbf{B} = \text{sign}(\mathbf{Y}) = \text{sign}(\Omega(\mathbf{X})). \tag{3}$$

Similarly, when B, Y and X denote the random variables sampled from $\mathbf{B}$, $\mathbf{Y}$ and $\mathbf{X}$, we represent their probability mass function as $p_B(b)$, $p_Y(y)$ and $p_X(x)$.

3.2 ENTROPY-MAXIMIZING AGGREGATION

Unlike images pixels that are arranged in regular lattices, point clouds are sets of points without any specific order. Hence, features are usually processed in a point-wise manner and aggregated explicitly through pooling layers. Our study shows that the aggregation function is a performance bottleneck of the binarized model, due to severe homogenization as shown in Figure 2.

We apply information theory (Section 3.2.1) to quantify the effect of the loss of feature diversity, and find that global feature aggregation leads to a catastrophic loss of information entropy. In Section 3.2.2, we propose the concept of Entropy-Maximizing Aggregation (EMA) that gives the statistically maximum information entropy to effectively tackle the feature homogenization problem.

3.2.1 AGGREGATION-INDUCED FEATURE HOMOGENIZATION

Ideally, the binarized tensor $\mathbf{B}$ should reflect the information in the original tensor $\mathbf{Y}$ as much as possible. From the perspective of information, maximizing mutual information can maximize the information flow from the full-precision to the binarized parameters. Hence, our goal is equivalent to maximizing the mutual information $\mathcal{I}(Y; B)$ of the random variables Y and B:

$$\arg\max_{Y, B} \mathcal{I}(Y; B) = \mathcal{H}(B) - \mathcal{H}(B \mid Y) \tag{4}$$

where $\mathcal{H}(B)$ is the information entropy, and $\mathcal{H}(B \mid Y)$ is the conditional entropy of B given Y. $\mathcal{H}(B \mid Y) = 0$ as we use the deterministic sign function as the quantizer in binarization (see Section A.1 for details). Hence, the original objective function Eq. (4) is equivalent to:

$$\arg\max_{B} \mathcal{H}_B(B) = -\sum_{b \in \mathcal{B}} p_B(b) \log p_B(b), \tag{5}$$

where $\mathcal{B}$ is the set of possible values of B. We then study the information properties of max pooling, which is a common aggregation function used in popular point cloud learning models such as PointNet. Let the max pooling be the last layer ϕ of the multi-layer stacked Ω, and the input of ϕ is defined as $\mathbf{X}_\phi$. The data flow of Eq. (3) can be further expressed as $\mathbf{B} = \text{sign}(\phi(\mathbf{X}_\phi))$, and the information entropy $\mathcal{H}_B$ of binarized feature B can be expressed as

$$\mathcal{H}_B(X_\phi) = -\Big(\sum_{x_\phi \geq 0} p_{X_\phi}(x_\phi)\Big)^n \log \Big(\sum_{x_\phi \geq 0} p_{X_\phi}(x_\phi)\Big)^n - \Big(1 - \Big(\sum_{x_\phi \geq 0} p_{X_\phi}(x_\phi)\Big)^n\Big) \log \Big(1 - \Big(\sum_{x_\phi \geq 0} p_{X_\phi}(x_\phi)\Big)^n\Big) \tag{6}$$

where n is the number of elements aggregated by the max pooling, and X_ϕ is the random variable sampled from $\mathbf{X}_\phi$. The brief derivation of Eq (6) is shown in Appendix A.2. Theorem 1 shows the information properties of max pooling with the normal distribution input on the binarized network architecture.

Theorem 1 *For input X_ϕ of max pooling ϕ with arbitrary distribution, the information entropy of the binarized output goes to zero as n goes to infinity, i.e., $\lim_{n \to +\infty} \mathcal{H}_B = 0$. And there exists a constant c, for any n_1 and n_2, if $n_1 > n_2 > c$, we have $\mathcal{H}_{B,n_1} < \mathcal{H}_{B,n_2}$, where n is the number of elements to be aggregated.*

The proof of Theorem 1 is included in Appendix A.2, which explains the severe feature homogenization after global feature pooling layers. As the number of points is typically large (e.g. 1024 points by convention in ModelNet40 classification task), it significantly reduces the information entropy $\mathcal{H}_B$ of binarized feature $\mathbf{B}$, i.e., the information of $\mathbf{Y}$ is hardly retained in $\mathbf{B}$, leading to highly similar output features regardless of the input features to pooling layer as shown in Figure 2.

Furthermore, Theorem 1 provides a theoretical justification for the poor performance of existing binarization methods, transferred from 2D vision tasks to point cloud applications. In 2D vision, the aggregation functions are often used to gather local features with a small kernel size n (e.g. $n = 4$ in ResNet (He et al., 2016; Liu et al., 2018) and VGG-Net (Simonyan & Zisserman, 2014) which use 2×2 pooling kernels). Hence, the feature homogenization problem on images is not as significant as that on point clouds.

3.2.2 EMA FOR MAXIMUM INFORMATION ENTROPY

Therefore, we need a class of aggregation functions that maximize the information entropy of $\mathbf{B}$ to avoid the aggregation-induced feature homogenization.

We study the correlation between the information entropy $\mathcal{H}_B$ of binary random variable B and the distribution of the full-precision random variable Y. We notice that the sign function used in binarization has a fixed threshold and decision levels, so we get Proposition 1 about information entropy of B and the distribution of Y.

Proposition 1 *When the distribution of the random variable Y satisfies $\sum_{y<0} p_Y(y) = \sum_{y\geq0} p_Y(y) = 0.5$, the information entropy $\mathcal{H}_B$ is maximized.*

The proof of Proposition 1 is shown in Appendix A.3. Therefore, theoretically, there is a distribution of Y that can maximize the mutual information of $\mathbf{Y}$ and $\mathbf{B}$ by maximizing the information entropy of the binary tensor $\mathbf{B}$, so as to maximally retain the information of $\mathbf{Y}$ in $\mathbf{B}$.

To maximize the information entropy $\mathcal{H}_B$, we propose the EMA for feature aggregation in BiPoint-Net. The EMA is not one, but a class of binarization-friendly aggregation layers. Modifying the aggregation function in the full-precision neural network to a EMA keeps the entropy maximized by input transformation. The definition of EMA is

$$\mathbf{Y} = \text{EMA}(\mathbf{X}_\phi) = \varphi(\tau(\mathbf{X}_\phi)), \tag{7}$$

where φ denotes the aggregation function (e.g. max pooling and average pooling) and τ denotes the transformation unit. Note that a standard normal distribution $\mathcal{N}(0,1)$ is assumed for X_ϕ because batch normalization layers are placed prior to the pooling layers by convention. τ can take many forms; we discover that a simple constant offset is already effective. The offset shifts the input so that the output distribution satisfies $\sum_{y<0} p_Y(y) = 0.5$, to maximize the information entropy of binary feature B. The transformation unit τ in our BiPointNet can be defined as $\tau(\mathbf{X}_\phi) = \mathbf{X}_\phi - \delta^*$.

When max pooling is applied as φ, we obtain the distribution offset δ^* for the input X_ϕ that maximizes the information entropy $\mathcal{H}_B$ by solving the objective function

$$\arg\max_{\delta} \mathcal{H}_B(\delta) = -\Big(\sum_{x_\phi \geq 0} \frac{1}{\sqrt{2\pi}} e^{-\frac{(x_\phi - \delta)^2}{2}}\Big)^n \log\Big(\sum_{x_\phi \geq 0} \frac{1}{\sqrt{2\pi}} e^{-\frac{(x_\phi - \delta)^2}{2}}\Big)^n$$
$$- \Big(1 - \Big(\sum_{x_\phi \geq 0} \frac{1}{\sqrt{2\pi}} e^{-\frac{(x_\phi - \delta)^2}{2}}\Big)^n\Big) \log\Big(1 - \Big(\sum_{x_\phi \geq 0} \frac{1}{\sqrt{2\pi}} e^{-\frac{(x_\phi - \delta)^2}{2}}\Big)^n\Big), \tag{8}$$

where n denotes the number of elements in each batch. For each n, we can obtain an optimized $\delta^*_{\max}$ for Eq. (8), we include the pseudo code in the Appendix A.5.

Moreover, we derive in the Appendix A.6 that when average pooling is used as φ, the solution to its objective function is expressed as $\delta = 0$. We thus obtain $\delta^*_{\text{avg}} = 0$. This means the solution

(a) (b) (c)

Figure 4: (a) Information entropy of the aggregated features. With EMA, our BiPointNet achieves a higher information entropy. (b) Regularizer loss comparison. Our PointNet has a low loss, indicating that the scale distortion is reduced and T-Net is not disrupted. (c) Ratio of zero-gradient activations in back-propagation. LSR alleviates the scale distortion, enhancing the optimization process

is not related to n. Hence, average pooling can be regarded as a flexible alternative because its performance is independent of the input number n.

In a nutshell, we provide two possible variants of φ: first, we show that a simple shift is sufficient to turn a max pooling layer into an EMA (EMA-max); second, average pooling can be directly used (EMA-avg) without modification as a large number of points does not undermine its information entropy, making it adaptive to the dynamically changing number of point input. Note that modifying existing aggregation functions is only one way to achieve EMA; the theory also instructs the development of new binarization-friendly aggregation functions in the future.

3.3 ONE-SCALE-FITS-ALL: LAYER-WISE SCALE RECOVERY

In this section, we show that binarization leads to feature scale distortion and study its cause. We conclude that the distortion is directly related to the number of feature channels. More importantly, we discuss the detriments of scale distortion from the perspectives of the functionality of scale-sensitive structures and the optimization.

To address the severe scale distortion in feature due to binarization, we propose the Layer-wise Scale Recovery (LSR). In LSR, each bi-linear layer is added only *one* learnable scaling factor to recover the original scales of *all* binarized parameters, with negligible additional computational overhead and memory usage.

3.3.1 SCALE DISTORTION

The scale of parameters is defined as the standard deviation σ of their distribution. As we mentioned in Section 3.2, balanced binarized weights are used in the bi-linear layer aiming to maximize the entropy of the output after binarization, i.e., $p_{B_w}(1) = 0.5$ and $p_{B_a}(1) = 0.5$.

Theorem 2 *When we let* $p_{B_w}(1) = 0.5$ *and* $p_{B_a}(1) = 0.5$ *in bi-linear layer to maximize the mutual information, for the binarized weight* $\mathbf{B_w} \in \{-1, +1\}^{m \times k}$ *and activation* $\mathbf{B_a} \in \{-1, +1\}^{n \times m}$*, the probability mass function for the distribution of output* $\mathbf{Z}$ *can be represented as* $p_Z(2i - m) = 0.5^m C_m^i, i \in \{0, 1, 2, ..., m\}$*. The output has approximately a normal distribution* $\mathcal{N}(0, m)$*.*

(a) Input point cloud (b) PointNet

(c) BiPointNet (d) BNN

Figure 3: Scale Distortion. Figures (b)-(d) show the transformed input. Compared with the input (a), the scales of (b) in full-precision PointNet and (c) in our BiPointNet are normal, while the scale of (d) in BNN is significantly distorted

The proof of Theorem 2 is found in Appendix A.4. Theorem 2 shows that given the maximized information entropy, the scale of the output features is directly related to the number of feature channels. Hence, scale distortion is pervasive as a large number of channels is the design norm of deep learning neural networks for effective feature extraction.

We discuss two major impacts of the scale distortion on the performance of binarized point cloud learning models. First, the scale distortion invalidates structures designed for 3D deep learning that

Table 1: Ablation study for our BiPointNet of various tasks on ModelNet40 (classification), ShapeNet Parts (part segmentation), and S3DIS (semantic segmentation). EMA and LSR and complementary to each other, and they are useful across all three applications

Method	Bit-width	Aggr.	ModelNet40	ShapeNet Parts	S3DIS	
			OA	mIoU	mIoU	OA
Full Prec.	32/32	MAX	88.2	84.3	54.4	83.5
	32/32	AVG	86.5	84.0	51.5	81.5
BNN	1/1	MAX	7.1	54.0	9.5	45.0
BNN-LSR	1/1	MAX	4.1	58.7	2.0	25.4
BNN-EMA	1/1	EMA-avg	11.3	53.0	9.9	46.8
	1/1	EMA-max	16.2	47.3	8.5	47.2
Ours	1/1	EMA-avg	82.5	80.3	40.9	74.9
	1/1	EMA-max	**86.4**	**80.6**	**44.3**	**76.7**

are sensitive to the scale of values. For example, the T-Net in PointNet is designed to predict an orthogonal transformation matrix for canonicalization of input and intermediate features (Qi et al., 2017a). The predicted matrix is regularized by minimizing the loss term $L_{reg} = \left\| \mathbf{I} - \mathbf{Z}\mathbf{Z}^T \right\|^2$. However, this regularization is ineffective for the $\mathbf{Z}$ with huge variance as shown in Figure 3.

Second, the scale distortion leads to a saturation of forward-propagated activations and backward-propagated gradients (Ding et al., 2019). In the binary neural networks, some modules (such as sign and Hardtanh) rely on the Straight-Through Estimator (STE) Bengio et al. (2013) for feature binarization or feature balancing. When the scale of their input is amplified, the gradient is truncated instead of increased proportionally. Such saturation, as shown in Fig 4(c), hinders learning and even leads to divergence.

3.3.2 LSR FOR OUTPUT SCALE RECOVERY

To recover the scale and adjustment ability of output, we propose the LSR for bi-linear layers in our BiPointNet. We design a learnable layer-wise scaling factor α in our LSR. α is initialized by the ratio of the standard deviations between the output of bi-linear and full-precision counterpart:

$$\alpha_0 = \sigma(\mathbf{A} \otimes \mathbf{W})/\sigma(\mathbf{B_a} \odot \mathbf{B_w}), \tag{9}$$

where σ denotes as the standard deviation. And the α is learnable during the training process. The calculation and derivative process of the bi-linear layer with our LSR are as follows:

$$\text{Forward}: \mathbf{Z} = \alpha(\mathbf{B_a} \odot \mathbf{B_w}) \qquad \text{Backward}: g_\alpha = g_\mathbf{Z}(\mathbf{B_a} \odot \mathbf{B_w}), \tag{10}$$

where g_α and $g_\mathbf{Z}$ denotes the gradient $\frac{\partial C}{\partial \alpha}$ and $\frac{\partial C}{\partial \mathbf{Z}}$, respectively. By applying the LSR in BiPointNet, we mitigate the scale distortion of output caused by binarization.

Compared to existing methods, the advantages of LSR is summarized in two folds. First, LSR is efficient. It not only abandons the adjustment of input activations to avoid expensive inference time computation, but also recovers the scale of all weights parameters in a layer collectively instead of expensive restoration in a channel-wise manner. Second, LSR serves the purpose of scale recovery that we show is more effective than other adaptation such as minimizing quantization errors (Rastegari et al., 2016; Qin et al., 2020b; Liu et al., 2018).

4 EXPERIMENTS

In this section, we conduct extensive experiments to validate the effectiveness of our proposed Bi-PointNet for efficient learning on point clouds. We first ablate our method and demonstrate the contributions of EMA and LSR on three most fundamental tasks: classification on ModelNet40 (Wu et al., 2015), part segmentation on ShapeNet (Chang et al., 2015), and semantic segmentation on S3DIS (Armeni et al., 2016). Moreover, we compare BiPointNet with existing binarization methods where our designs stand out. Besides, BiPointNet is put to the test on real-world devices with limited computational power and achieve extremely high speedup ($14.7\times$) and storage saving ($18.9\times$). The details of the datasets and the implementations are included in the Appendix E.

Table 2: Comparison of binarization methods on PointNet. EMA is critical; even if all methods are equipped with our EMA, our LSR outperforms others with least number of scaling factors. OA: Overall Accuracy

Method	Bit-width	Aggr.	# Factors	OA
Full Prec.	32/32	MAX	-	88.2
	32/32	AVG	-	86.5
BNN	1/1	MAX	0	7.1
	1/1	EMA-avg	0	11.3
	1/1	EMA-max	0	16.2
IR-Net	1/1	MAX	10097	7.3
	1/1	EMA-avg	10097	22.0
	1/1	EMA-max	10097	63.5
Bi-Real	1/1	MAX	10097	4.0
	1/1	EMA-avg	10097	77.0
	1/1	EMA-max	10097	77.5
ABC-Net	1/1	MAX	51	4.1
	1/1	EMA-avg	51	68.9
	1/1	EMA-max	51	77.8
XNOR++	1/1	MAX	18	4.1
	1/1	EMA-avg	18	73.8
	1/1	EMA-max	18	78.4
XNOR	1/1	MAX	28529	64.9
	1/1	EMA-avg	28529	78.2
	1/1	EMA-max	28529	81.9
Ours	1/1	MAX	18	4.1
	1/1	EMA-avg	18	82.5
	1/1	EMA-max	18	**86.4**

Table 3: Our methods on mainstream backbones. We use XNOR as a strong baseline for comparison. The techniques in our BiPointNet are generic to point cloud learning. Hence, they are easily extendable to other backbones

Base Model	Method	Bit-width	Aggr.	OA
PointNet (Vanilla)	Full Prec.	32/32	MAX	86.8
	XNOR	1/1	MAX	61.0
	Ours	1/1	EMA-max	85.6
PointNet	Full Prec.	32/32	MAX	88.2
	XNOR	1/1	MAX	64.9
	Ours	1/1	EMA-max	86.4
PointNet++	Full Prec.	32/32	MAX	90.0
	XNOR	1/1	MAX	63.1
	Ours	1/1	EMA-max	87.8
PointCNN	Full Prec.	32/32	AVG	90.0
	XNOR	1/1	AVG	83.0
	Ours	1/1	EMA-avg	83.8
DGCNN	Full Prec.	32/32	MAX	89.2
	XNOR	1/1	MAX	51.5
	Ours	1/1	EMA-max	83.4
PointConv	Full Prec.	32/32	–	90.8
	XNOR	1/1	–	83.1
	Ours	1/1	–	87.9

4.1 ABLATION STUDY

As shown in Table 1, the binarization model baseline suffers a catastrophic performance drop in the classification task. EMA and LSR improve performance considerably when used alone, and they further close the gap between the binarized model and the full-precision counterpart when used together.

In Figure 4, we further validate the effectiveness of EMA and LSR. We show that BiPointNet with EMA has its information entropy maximized during training, whereas the vanilla binarized network with max pooling gives limited and highly fluctuating results. Also, we make use of the regularization loss $L_{reg} = \left\| \mathbf{I} - \mathbf{Z}\mathbf{Z}^T \right\|_F$ for the feature transformation matrix of T-Net in PointNet as an indicator, the L_{reg} of the BiPointNet with LSR is much smaller than the vanilla binarized network, demonstrating LSR's ability to reduce the scale distortion caused by binarization, allowing proper prediction of orthogonal transformation matrices.

Moreover, we also include the results of two challenging tasks, part segmentation, and semantic segmentation, in Table 1. As we follow the original PointNet design for segmentation, which concatenates pointwise features with max pooled global feature, segmentation suffers from the information loss caused by the aggregation function. EMA and LSR are proven to be effective: BiPointNet is approaching the full precision counterpart with only $\sim 4\%$ mIoU difference on part segmentation and $\sim 10.4\%$ mIoU gap on semantic segmentation. The full results of segmentation are presented in Appendix E.6.

4.2 COMPARATIVE EXPERIMENTS

In Table 2, we show that our BiPointNet outperforms other binarization methods such as BNN (Hubara et al., 2016), XNOR (Rastegari et al., 2016), Bi-Real (Liu et al., 2018), ABC-Net (Lin

Figure 5: (a) Time cost comparison. Our BiPointNet achieves $14.7\times$ speedup on ARM A72 CPU device. (b) Storage usage comparison. Our BiPointNet enjoys $18.9\times$ storage saving on all devices. (c) Speed vs accuracy trade-off plot. We evaluate various binarization methods (with our EMA-max) upon PointNet architecture on ARM A72 CPU device, our BiPointNet is the leading method in both speed and accuracy

et al., 2017), XNOR++ (Bulat & Tzimiropoulos, 2019), and IR-Net (Qin et al., 2020b). Although these methods have been proven effective in 2D vision, they are not readily transferable to point clouds due to aggregation-induced feature homogenization.

Even if we equip these methods with our EMA to mitigate information loss, our BiPointNet still performs better. We argue that existing approaches, albeit having many scaling factors, focus on minimizing quantization errors instead of recovering feature scales, which is critical to effective learning on point clouds. Hence, BiPointNet stands out with a negligible increase of parameters that are designed to restore feature scales. The detailed analysis of the performance of XNOR is found in Appendix C. Moreover, we highlight that our EMA and LSR are generic, and Table 3 shows improvements across several mainstream categories of point cloud deep learning models, including PointNet (Qi et al., 2017a), PointNet++ (Qi et al., 2017b), PointCNN (Li et al., 2018), DGCNN (Wang et al., 2019a), and PointConv (Wu et al., 2019).

4.3 DEPLOYMENT EFFICIENCY ON REAL-WORLD DEVICES

To further validate the efficiency of BiPointNet when deployed into the real-world edge devices, we further implement our BiPointNet on Raspberry Pi 4B with 1.5 GHz 64-bit quad-core ARM CPU Cortex-A72 and Raspberry Pi 3B with 1.2 GHz 64-bit quad-core ARM CPU Cortex-A53.

We compare our BiPointNet with the PointNet in Figure 5(a) and Figure 5(b). We highlight that BiPointNet achieves $14.7\times$ inference speed increase and $18.9\times$ storage reduction over PointNet, which is recognized as a fast and lightweight model itself. Moreover, we implement various binarization methods over PointNet architecture and report their real speed performance on ARM A72 CPU device. As Figure 5(c), our BiPointNet surpasses all existing binarization methods in both speed and accuracy. Note that all binarization methods adopt our EMA and report their best accuracy, which is the important premise that they can be reasonably applied to binarize the PointNet.

5 CONCLUSION

We propose BiPointNet, the first binarization approach for efficient learning on point clouds. We build a theoretical foundation to study the impact of binarization on point cloud learning models, and proposed EMA and LSR in BiPointNet to improve the performance. BiPointNet outperforms existing binarization methods, and it is easily extendable to a wide range of tasks and backbones, giving an impressive $14.7\times$ speedup and $18.9\times$ storage saving on resource-constrained devices. Our work demonstrates the great potential of binarization. We hope our work can provide directions for future research.

Acknowledgement This work was supported by National Natural Science Foundation of China (62022009, 61872021), Beijing Nova Program of Science and Technology (Z191100001119050), and State Key Lab of Software Development Environment (SKLSDE-2020ZX-06).

REFERENCES

Iro Armeni, Ozan Sener, Amir R. Zamir, Helen Jiang, Ioannis Brilakis, Martin Fischer, and Silvio Savarese. 3d semantic parsing of large-scale indoor spaces. In *IEEE CVPR*, 2016.

Yoshua Bengio, Nicholas Léonard, and Aaron Courville. Estimating or propagating gradients through stochastic neurons for conditional computation. *arXiv preprint arXiv:1308.3432*, 2013.

Adrian Bulat and Georgios Tzimiropoulos. Xnor-net++: Improved binary neural networks. In *BMVC*, 2019.

Angel X. Chang, T. Funkhouser, L. Guibas, P. Hanrahan, Qixing Huang, Zimo Li, S. Savarese, M. Savva, Shuran Song, H. Su, J. Xiao, L. Yi, and F. Yu. Shapenet: An information-rich 3d model repository. *CoRR*, abs/1512.03012, 2015.

Ruizhou Ding, Ting-Wu Chin, Zeye Liu, and Diana Marculescu. Regularizing activation distribution for training binarized deep networks. In *IEEE CVPR*, 2019.

Matthias Fey and Jan Eric Lenssen. Fast graph representation learning with pytorch geometric. *CoRR*, abs/1903.02428, 2019.

Ross Girshick, Jeff Donahue, Trevor Darrell, and Jitendra Malik. Rich feature hierarchies for accurate object detection and semantic segmentation. In *IEEE CVPR*, 2014.

Ross B. Girshick. Fast r-cnn. *IEEE ICCV*, 2015.

Ruihao Gong, Xianglong Liu, Shenghu Jiang, Tianxiang Li, Peng Hu, Jiazhen Lin, Fengwei Yu, and Junjie Yan. Differentiable soft quantization: Bridging full-precision and low-bit neural networks. In *IEEE ICCV*, 2019.

Yulan Guo, Hanyun Wang, Qingyong Hu, Hao Liu, Li Liu, and Mohammed Bennamoun. Deep learning for 3d point clouds: A survey. *IEEE TPAMI*, 2020.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *IEEE CVPR*, 2016.

Lu Hou, Quanming Yao, and James T. Kwok. Loss-aware binarization of deep networks. *ICLR*, 2017.

Qingyong Hu, Bo Yang, Linhai Xie, Stefano Rosa, Yulan Guo, Zhihua Wang, Niki Trigoni, and Andrew Markham. Randla-net: Efficient semantic segmentation of large-scale point clouds. 2020.

Itay Hubara, Matthieu Courbariaux, Daniel Soudry, Ran El-Yaniv, and Yoshua Bengio. Binarized neural networks. In *NeurIPS*, 2016.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. In *NeurIPS*, 2012.

Yangyan Li, Rui Bu, Mingchao Sun, Wei Wu, X. Di, and B. Chen. Pointcnn: Convolution on x-transformed points. In *NeurIPS*, 2018.

Xiaofan Lin, Cong Zhao, and Wei Pan. Towards accurate binary convolutional neural network. In *NeurIPS*, 2017.

Chunlei Liu, Wenrui Ding, Xin Xia, Baochang Zhang, Jiaxin Gu, Jianzhuang Liu, Rongrong Ji, and David S. Doermann. Circulant binary convolutional networks: Enhancing the performance of 1-bit dcnns with circulant back propagation. In *IEEE CVPR*, 2019a.

Yongcheng Liu, Bin Fan, Shiming Xiang, and Chunhong Pan. Relation-shape convolutional neural network for point cloud analysis. *IEEE CVPR*, 2019b.

Yongcheng Liu, Bin Fan, Shiming Xiang, and Chunhong Pan. Relation-shape convolutional neural network for point cloud analysis. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 8895–8904, 2019c.

Zechun Liu, Baoyuan Wu, Wenhan Luo, Xin Yang, Wei Liu, and Kwang-Ting Cheng. Bi-real net: Enhancing the performance of 1-bit cnns with improved representational capability and advanced training algorithm. In *ECCV*, 2018.

Zechun Liu, Zhiqiang Shen, Marios Savvides, and Kwang-Ting Cheng. Reactnet: Towards precise binary neural network with generalized activation functions. In *ECCV*, 2020.

Zhijian Liu, Haotian Tang, Yujun Lin, and Song Han. Point-voxel cnn for efficient 3d deep learning. In *NeurIPS*, 2019d.

Brais Martinez, Jing Yang, Adrian Bulat, and Georgios Tzimiropoulos. Training binary neural networks with real-to-binary convolutions. In *ICLR*, 2020.

Charles R. Qi, Hao Su, Kaichun Mo, and Leonidas J. Guibas. Pointnet: Deep learning on point sets for 3d classification and segmentation. *IEEE CVPR*, 2017a.

Charles R. Qi, Li Yi, Hao Su, and Leonidas J. Guibas. Pointnet++: Deep hierarchical feature learning on point sets in a metric space. In *NeurIPS*, 2017b.

Haotong Qin, Ruihao Gong, Xianglong Liu, Xiao Bai, Jingkuan Song, and Nicu Sebe. Binary neural networks: A survey. *Pattern Recognition*, 2020a.

Haotong Qin, Ruihao Gong, Xianglong Liu, Mingzhu Shen, Ziran Wei, Fengwei Yu, and Jingkuan Song. Forward and backward information retention for accurate binary neural networks. In *IEEE CVPR*, 2020b.

Mohammad Rastegari, Vicente Ordonez, Joseph Redmon, and Ali Farhadi. Xnor-net: Imagenet classification using binary convolutional neural networks. In *ECCV*, 2016.

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael S Bernstein, et al. Imagenet large scale visual recognition challenge. *IJCV*, 2015.

Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *arXiv preprint arXiv:1409.1556*, 2014.

Christian Szegedy, Wei Liu, Yangqing Jia, Pierre Sermanet, Scott Reed, Dragomir Anguelov, Dumitru Erhan, Vincent Vanhoucke, and Andrew Rabinovich. Going deeper with convolutions. In *IEEE CVPR*, 2015.

Hugues Thomas, Charles R. Qi, Jean-Emmanuel Deschaud, Beatriz Marcotegui, François Goulette, and Leonidas J. Guibas. Kpconv: Flexible and deformable convolution for point clouds. *IEEE ICCV*, 2019.

Yiru Wang, Weihao Gan, Wei Wu, and Junjie Yan. Dynamic curriculum learning for imbalanced data classification. In *IEEE ICCV*, 2019a.

Yunhe Wang, Chang Xu, Chao Xu, and Dacheng Tao. Packing convolutional neural networks in the frequency domain. *IEEE TPAMI*, 2019b.

Ziwei Wang, Ziyi Wu, Jiwen Lu, and Jie Zhou. Bidet: An efficient binarized object detector. In *IEEE CVPR*, 2020.

B. Wu, Y. Wang, P. Zhang, Yuandong Tian, P. Vajda, and K. Keutzer. Mixed precision quantization of convnets via differentiable neural architecture search. *CoRR*, abs/1812.00090, 2018.

Wenxuan Wu, Zhongang Qi, and Fuxin Li. Pointconv: Deep convolutional networks on 3d point clouds. *IEEE CVPR*, 2019.

Zhirong Wu, Shuran Song, Aditya Khosla, Fisher Yu, Linguang Zhang, Xiaoou Tang, and Jianxiong Xiao. 3d shapenets: A deep representation for volumetric shapes. In *IEEE CVPR*, 2015.

Zizhao Wu, Ruyang Shou, Yunhai Wang, and Xinguo Liu. Interactive shape co-segmentation via label propagation. *Computers & Graphics*, 38:248–254, 2014.

Bo Xie, Yingyu Liang, and Le Song. Diverse neural network learns true target functions. In *Artificial Intelligence and Statistics*, 2017.

Chenfeng Xu, Bichen Wu, Zining Wang, Wei Zhan, Peter Vajda, Kurt Keutzer, and Masayoshi Tomizuka. Squeezesegv3: Spatially-adaptive convolution for efficient point-cloud segmentation. In *ECCV*, 2020a.

Qiangeng Xu, Xudong Sun, Cho-Ying Wu, Panqu Wang, and U. Neumann. Grid-gcn for fast and scalable point cloud learning. 2020b.

Yinghao Xu, Xin Dong, Yudian Li, and Hao Su. A main/subsidiary network framework for simplifying binary neural networks. In *IEEE CVPR*, 2019.

Li Yi, Vladimir G Kim, Duygu Ceylan, I-Chao Shen, Mengyan Yan, Hao Su, Cewu Lu, Qixing Huang, Alla Sheffer, and Leonidas Guibas. A scalable active framework for region annotation in 3d shape collections. *ACM Transactions on Graphics (ToG)*, 35(6):1–12, 2016.

Haibao Yu, Q. Han, Jianbo Li, Jianping Shi, Guang-Liang Cheng, and Bin Fan. Search what you want: Barrier panelty nas for mixed precision quantization. In *ECCV*, 2020.

Jianhao Zhang, Yingwei Pan, Ting Yao, He Zhao, and Tao Mei. dabnn: A super fast inference framework for binary neural networks on ARM devices. In *ACM MM*, 2019a.

Xiangguo Zhang, Haotong Qin, Yifu Ding, Ruihao Gong, Qinghua Yan, Renshuai Tao, Yuhang Li, Fengwei Yu, and Xianglong Liu. Diversifying sample generation for data-free quantization. In *IEEE CVPR*, 2021.

Zhiyuan Zhang, Binh-Son Hua, and Sai-Kit Yeung. Shellnet: Efficient point cloud convolutional neural networks using concentric shells statistics. In *IEEE ICCV*, 2019b.

Shuchang Zhou, Yuxin Wu, Zekun Ni, Xinyu Zhou, He Wen, and Yuheng Zou. Dorefa-net: Training low bitwidth convolutional neural networks with low bitwidth gradients. *arXiv*, abs/1606.06160, 2016.

Feng Zhu, Ruihao Gong, Fengwei Yu, Xianglong Liu, Yanfei Wang, Zhelong Li, Xiuqi Yang, and Junjie Yan. Towards unified int8 training for convolutional neural network. In *IEEE CVPR*, 2020.

Shilin Zhu, Xin Dong, and Hao Su. Binary ensemble neural network: More bits per network or more networks per bit? In *IEEE CVPR*, 2019.