BiPointNet: Binary Neural Network for Point Clouds

Abstract

To alleviate the resource constraint for real-time point clouds applications that run on edge devices, we present BiPointNet, the first model binarization approach for efficient deep learning on point clouds. In this work, we discover that the immense performance drop of binarized models for point clouds is caused by two main challenges: aggregation-induced feature homogenization that leads to a degradation of information entropy, and scale distortion that hinders optimization and invalidates scale-sensitive structures. With theoretical justifications and in-depth analysis, we propose *Entropy-Maximizing Aggregation* (EMA) to modulate the distribution before aggregation for the maximum information entropy, and *Layer-wise Scale Recovery* (LSR) to efficiently restore feature scales. Extensive experiments show that our BiPointNet outperforms existing binarization methods by convincing margins, at the level even comparable with the full precision counterpart. We highlight that our techniques are generic which show significant improvements on various fundamental tasks and mainstream backbones. BiPoint-Net gives an impressive $14.7\times$ speedup and $18.9\times$ storage saving on real-world resource-constrained devices.[1]

1 Introduction

With the advent of deep neural networks that directly process raw point clouds (PointNet (Qi et al., 2016) as the pioneering work), great success has been achieved in learning on point clouds (Qi et al., 2017; Li et al., 2018; Wang et al., 2019a). Such networks are in strong need for applications that require real-time interaction and fast response, such as autonomous driving and augmented reality; however, their deployment environments are often those resource-constrained edge devices. To address the challenge, novel algorithms, such as Grid-GCN (Xu et al., 2019), RandLA-Net (Hu et al., 2019), and PointVoxel (Liu et al., 2019b), have been proposed to accelerate those point cloud processing networks. While significant speedup and memory footprint reduction have been achieved, these works still rely on expensive floating-point operations, leaving room for further optimizing the performance from the model binarization perspective. Model binarization (Rastegari et al., 2016; Bulat & Tzimiropoulos, 2019; Hubara et al., 2016; Wang et al., 2020; Zhu et al., 2019; Xu et al.) emerged as one of the most promising approaches to optimize neural networks for better computational and memory usage efficiency. Binary Neural Networks (BNNs) leverage 1) compact binarized parameters that take small memory space, and 2) highly efficient bitwise operations which are far less costly compared to the floating-point counterparts.

Despite that model binarization has been studied extensively in 2D vision tasks (Krizhevsky et al., 2012; Simonyan & Zisserman, 2014; Szegedy et al., 2015; Girshick et al., 2014; Girshick, 2015; Russakovsky et al., 2015; Wang et al., 2019b), they are not readily transferable for 3D point cloud networks due to the fundamental differences between 2D images and 3D point clouds. First, to gain efficiency in processing *unordered* 3D points, many point cloud learning methods rely heavily on pooling layers with large receptive field to aggregate point-wise features. As shown in PointNet (Qi et al., 2017), even global pooling provides strong recognition performance. However, this practice poses challenges for binarization. Our analyses show that the degradation of feature diversity, a persistent problem with binarization (Liu et al., 2019a; Qin et al., 2019; Xie et al., 2017), is significantly amplified by the global aggregation function (Figure 2), leading to homogenization of global

---

[1]Our code will be available upon publication.

Figure 1: Overview of our BiPointNet on PointNet base model, applying Entropy-Maximizing Aggregation (EMA) and Layer-wise Scale Recovery (LSR). EMA consists of the transformation unit and aggregation unit for maximizing the information entropy of feature after binarized. LSR with learnable layer-wise scaling factor is applied to address the scale distortion of bi-linear layer, restoring the output from fixed and distorted to flexible and reasonable

features with limited discriminability. Second, the binarization causes immense scale distortion at the point-wise feature extraction stage, which is detrimental to model performance in two ways: the saturation of forward-propagated features and backward-propagated gradients hinders optimization; and the disruption of the scale-sensitive structures (Figure 4) results in the invalidation of their designated functionality.

In this paper, we provide theoretical formulations of the phenomenon and obtain insights through in-depth analysis. Such understanding allows us to propose a method that turns full-precision point cloud networks into extremely efficient yet strong binarized models (see the overview in Figure 1). We study the correlation between the information entropy of binarization features and the performance of point cloud aggregation functions. To tackle the homogenization of the binarized features after passing the aggregation function, we propose *Entropy-Maximizing Aggregation* (EMA) that shifts the feature distribution towards the statistical optimum, effectively improving expression capability of the global features. Moreover, given maximized information entropy, we further develop *Layer-wise Scale Recovery* (LSR) to efficiently restore the output scale that enhances optimization, which allows scale-sensitive structures to function properly. LSR uses only one learnable parameter per layer, leading to negligible storage increment and computation overhead.

Our BiPointNet is the first binarizatoin approaches to deep learning on point clouds, and it outperforms existing binarization algorithms for 2D vision by convincing margins. It is even almost on par (within $\sim$ 1-2%) with the full-precision counterpart. Although we conduct most analysis on the PointNet baseline, we show that our methods are generic and can be readily extendable to other mainstream point cloud feature extractors, such as PointNet++ (Qi et al., 2017), PointCNN (Li et al., 2018), and DGCNN (Wang et al., 2019a). Moreover, extensive experiments on multiple fundamental tasks on the point cloud, such as classification, part segmentation, and semantic segmentation, highlight that our BiPointNet is task-agnostic. Besides, we perform the actual test of BiPointNet on popular edge devices, where BiPointNet achieves $14.7\times$ speedup and $18.9\times$ storage savings compared to the full-precision PointNet.

2 RELATED WORK

Network Binarization. Binarized parameters and bitwise operations (Rastegari et al., 2016; Qin et al., 2020) are used for extreme compression and acceleration. In general, the forward and backward propagation of binarized models in the training process can be formulated as:

$$\text{Forward} : b = \texttt{sign}(x) = \begin{cases} +1, & \text{if } x \geq 0 \\ -1, & \text{otherwise} \end{cases} \qquad \text{Backward} : g_x = \begin{cases} g_b, & \text{if } x \in (-1, 1) \\ 0, & \text{otherwise} \end{cases} \quad (1)$$

where x denotes the element in floating-point weights and activations, and b denotes the element in binarized weights $\mathbf{B_w}$ and activations $\mathbf{B_a}$. g_x and g_b donate the gradient $\frac{\partial C}{\partial x}$ and $\frac{\partial C}{\partial b}$, respectively, where C is the cost function for the minibatch. In forward propagation, $\texttt{sign}$ function is directly applied to obtain the binary parameters. In backward propagation, the Straight-Through Estimator (STE) (Bengio et al., 2013) is used to obtain the derivative of the $\texttt{sign}$ function, avoiding getting all zero gradients. The existing binarization methods are designed to obtain accurate binarized networks by minimizing the quantization error (Rastegari et al., 2016; Zhou et al., 2016; Lin et al., 2017), improving loss function (Ding et al., 2019; Hou et al., 2017), reducing the gradient error (Liu et al., 2018; 2020), and designing novel structures and pipelines (Martinez et al., 2020). Unfortunately, we

(a) Point-wise features to be aggregated.   (b) Full-precision features aggregated with max pooling.   (c) Binarized features aggregated with max pooling.   (d) Binarized features aggregated with EMA.

Figure 2: Aggregation-induced feature homogenization. (a) shows the activation of each test sample in a batch of ModelNet40. In (b)-(d), the single feature vectors pooled from all points are mapped to colors. The diversity of colors represents the diversity of pooled features. The original aggregation design is incompatible with binarization, leading to the homogenization of output features in (c), whereas our proposed EMA retains high information entropy, shown in (d)

show in Sec 3 that these methods, designed for 2D vision tasks, are not readily transferable to point clouds.

Deep Learning on Point Clouds. PointNet (Qi et al., 2016) is the first deep learning model that processes raw point clouds directly. The basic building blocks proposed by PointNet such as MLP for point-wise feature extraction and max/average pooling for global aggregation (Guo et al., 2020) have become the popular design choices for various categories of newer backbones, such as PointNet++ (Qi et al., 2017) (point-based), PointCNN (Li et al., 2018) (convolution-based), and DGCNN (Xu et al., 2019) (graph-based). Recently, methods are proposed for efficient deep learning on point clouds through novel data structuring (Xu et al., 2019), faster sampling (Hu et al., 2019), adaptive filters (Xu et al., 2020), and efficient representation (Liu et al., 2019b). However, they still use expensive floating-point parameters and operations, which can be improved by binarization.

3 METHODS

Binarized models operate on efficient binary parameters, but often suffer large performance drop. Moreover, the unique characteristics of point clouds pose even more challenges. We observe there are two main problems: first, aggregation of a large number of points leads to a severe loss of feature diversity; second, binarization induces an immense scale distortion, that undermines the functionality of scale-sensitive structures. In this section, we discuss our observations, and propose our BiPointNet with theoretical justifications.

3.1 BINARIZATION FRAMEWORK

We first give a brief introduction to our framework that binarizes a floating-point network. For example, deep learning models on point clouds typically contain multi-layer perceptrons (MLPs) for feature extraction. In contrast, the binarized models contain binary MLPs (BiMLPs), which are composed of binarized linear (bi-linear) layers. Bi-linear layers perform the extremely efficient bitwise operations (XNOR and Bitcount) on the lightweight binary weight/activation. Specifically, the activation of the bi-linear layer is binarized to $\mathbf{B_a}$, and is computed with the binarized weight $\mathbf{B_w}$ to obtain the output $\mathbf{Z}$:

$$\mathbf{Z} = \mathbf{B_a} \odot \mathbf{B_w}, \tag{2}$$

where $\odot$ denotes the inner product for vectors with bitwise operations XNOR and Bitcount. When B_w and B_a denote the random variables in $\mathbf{B_w}$ and $\mathbf{B_a}$, we represent their probability mass function as $p_{B_w}(b_w)$, and $p_{B_a}(b_a)$.

Moreover, we divide the data flow in BiPointNet into units for detailed discussions. In BiPointNet, the original data or feature $\mathbf{X} \in \mathbb{R}^{n \times c}$ first enters the symmetric function Ω, which represents a composite function built by stacking several permutation equivariant and permutation invariant layers (*e.g.*, nonlinear layer, bi-linear layer, max pooling). And then, the output $\mathbf{Y} \in \mathbb{R}^{n \times k}$ is binarized to obtain the binary feature $\mathbf{B} \in \{-1, 1\}^{i \times k}$, where i takes n when the feature is modeled independently and takes 1 when the feature is aggregated globally. The single unit is thus represented as

$$\mathbf{B} = \text{sign}(\mathbf{Y}) = \text{sign}(\Omega(\mathbf{X})). \tag{3}$$

Similarly, when B, Y and X denote the random variables sampled from $\mathbf{B}$, $\mathbf{Y}$ and $\mathbf{X}$, we represent their probability mass function as $p_B(b)$, $p_Y(y)$ and $p_X(x)$.

3.2 Entropy-maximizing Aggregation

Unlike images pixels that are arranged in regular lattices, point clouds are sets of points without any specific order. Hence, features are usually processed in a point-wise manner and aggregated explicitly through pooling layers. Our study shows that the aggregation function is a performance bottleneck of the binarized model, due to severe homogenization as shown in Figure 2.

We apply information theory (Section 3.2.1) to quantify the effect of the loss of feature diversity, and find that global feature aggregation leads to a catastrophic loss of information entropy. In Section 3.2.2, we propose the concept of Entropy-Maximizing Aggregation (EMA) that gives the statistically maximum information entropy to effectively tackle the feature homogenization problem.

3.2.1 Aggregation-induced Feature Homogenization

Ideally, the binarized tensor $\mathbf{B}$ should reflect the information in the original tensor $\mathbf{Y}$ as much as possible. From the perspective of information, maximizing mutual information can maximize the information flow from the full-precision to the binarized parameters. Hence, our goal is equivalent to maximizing the mutual information $\mathcal{I}(Y;B)$ of the random variables Y and B:

$$\arg\max_{Y,B} \mathcal{I}(Y;B) = \mathcal{H}(B) - \mathcal{H}(B \mid Y) \tag{4}$$

where $\mathcal{H}(B)$ is the information entropy, and $\mathcal{H}(B \mid Y)$ is the conditional entropy of B given Y. $\mathcal{H}(B \mid Y) = 0$ as we use the deterministic sign function as the quantizer in binarization (see Sec A.1 for details). Hence, the original objective function Eq. (4) is equivalent to:

$$\arg\max_{B} \mathcal{H}_B(B) = -\sum_{b \in \mathcal{B}} p_B(b) \log p_B(b), \tag{5}$$

where $\mathcal{B}$ is the set of possible values of B. We then study the information properties of max pooling, which is a common aggregation function used in popular point cloud learning models such as PointNet. Let the max pooling be the last layer ϕ of the multi-layer stacked Ω, and the input of ϕ is defined as $\mathbf{X}_\phi$. The data flow of Eq. (3) can be further expressed as $\mathbf{B} = \text{sign}(\phi(\mathbf{X}_\phi))$, and the information entropy $\mathcal{H}_B$ of binarized feature B can be expressed as

$$\mathcal{H}_B(X_\phi) = -\Big(\sum_{x_\phi \geq 0} p_{X_\phi}(x_\phi)\Big)^n \log\Big(\sum_{x_\phi \geq 0} p_{X_\phi}(x_\phi)\Big)^n - \Big(1 - \Big(\sum_{x_\phi \geq 0} p_{X_\phi}(x_\phi)\Big)^n\Big) \log\Big(1 - \Big(\sum_{x_\phi \geq 0} p_{X_\phi}(x_\phi)\Big)^n\Big) \tag{6}$$

where n is the number of elements aggregated by the max pooling, and X_ϕ is the random variable sampled from $\mathbf{X}_\phi$. The brief derivation of Eq (6) is shown in Appendix A.2. Theorem 1 shows the information properties of max pooling with the normal distribution input on the binarized network architecture.

Theorem 1 *For input X_ϕ of max pooling ϕ with arbitrary distribution, the information entropy of the binarized output goes to zero as n goes to infinity, i.e, $\lim\limits_{n \to +\infty} \mathcal{H}_B = 0$. And there exists a constant c, for any n_1 and n_2, if $n_1 > n_2 > c$, we have $\mathcal{H}_{B,n_1} > \mathcal{H}_{B,n_2}$, where n is the number of elements to aggregated.*

The proof of Theorem 1 is shown in Appendix A.2. Theorem 1 explains the severe feature homogenization after global feature pooling layers. As the number of points is typically large (*e.g.* 1024 points by convention in ModelNet40 classification task), it significantly limits the information entropy $\mathcal{H}_B$ of binarized feature $\mathbf{B}$, *i.e.*, the information of $\mathbf{Y}$ is hardly retained in $\mathbf{B}$, leading to highly similar output features regardless of the input features to pooling layer as shown in Figure 2.

Furthermore, Theorem 1 provides a theoretical justification for the poor performance of existing binarization methods, transferred from 2D vision tasks to point cloud applications. In 2D vision, the aggregation functions are often used to gather local features with a small kernel size n (*e.g.* $n = 4$ in ResNet and VGG-Net which use 2×2 pooling kernels). Hence, the feature homogenization problem on images is not as significant as that on point clouds.

3.2.2 EMA for Maximum Information Entropy

Therefore, we need a class of aggregation functions that maximize the information entropy of $\mathbf{B}$ to avoid the aggregation-induced feature homogenization.

We study the correlation between the information entropy $\mathcal{H}_B$ of binary random variable B and the distribution of the full-precision random variable Y. We notice that the sign function used in binarization has a fixed threshold and decision levels, so we get Proposition 1 about information entropy of B and the distribution of Y.

Proposition 1 *When the distribution of the random variable Y satisfies $\sum_{y<0} p_Y(y) = \sum_{y\geq 0} p_Y(y) = 0.5$, the information entropy $\mathcal{H}_B$ is maximized.*

The proof of Proposition 1 is shown in Appendix A.3. Therefore, theoretically, there is a distribution of Y that can maximize the mutual information of $\mathbf{Y}$ and $\mathbf{B}$ by maximizing the information entropy of the binary tensor $\mathbf{B}$, so as to the maximally retained the information of $\mathbf{Y}$ in $\mathbf{B}$.

To maximize the information entropy $\mathcal{H}_B$, we propose the EMA for feature aggregation in Bi-PointNet. The EMA is a class of binarization-friendly aggregation layers, which is based on the aggregation function in the full-precision neural network and further keeps the entropy maximized by input transformation. The definition of EMA is

$$\mathbf{Y} = \text{EMA}(\mathbf{X}_\phi) = \varphi(\tau(\mathbf{X}_\phi)), \tag{7}$$

where φ denotes the aggregation function (*e.g.* max pooling and average pooling) and τ denotes the transformation unit. Note that a standard normal distribution $\mathcal{N}(0,1)$ is assumed for X_ϕ because batch normalization layers are placed prior to the pooling layers by convention. τ can take many forms; we discover that a simple constant offset is already effective. The offset shifts the input so that the output distribution satisfies $\sum_{y<0} p_Y(y) = 0.5$, to maximize the information entropy of binary feature B. The transformation unit τ in our BiPointNet can be defined as $\tau(\mathbf{X}_\phi) = \mathbf{X}_\phi - \delta^*$.

When max pooling is applied as φ, we obtain the distribution offset δ^* for the input X_ϕ that maximizes the information entropy $\mathcal{H}_B$ by solving the objective function

$$\arg\max_\delta \mathcal{H}_B(\delta) = -\Big(\sum_{x_\phi \geq 0} \frac{1}{\sqrt{2\pi}} e^{-\frac{(x_\phi - \delta)^2}{2}} \Big)^n \log \Big(\sum_{x_\phi \geq 0} \frac{1}{\sqrt{2\pi}} e^{-\frac{(x_\phi - \delta)^2}{2}} \Big)^n$$
$$- \Big(1 - \Big(\sum_{x_\phi \geq 0} \frac{1}{\sqrt{2\pi}} e^{-\frac{(x_\phi - \delta)^2}{2}} \Big)^n \Big) \log \Big(1 - \Big(\sum_{x_\phi \geq 0} \frac{1}{\sqrt{2\pi}} e^{-\frac{(x_\phi - \delta)^2}{2}} \Big)^n \Big), \tag{8}$$

where n denotes the number of elements in each batch. For each n, we can obtain an optimized $\delta^*_{\max}$ for Eq. (8), we include the pseudo code in the Appendix A.5.

Moreover, we derive in the Appendix A.6 that when average pooling is used as φ, the solution to its objective function is expressed as $n^{-1}\delta = 0$. We thus obtain $\delta^*_{\text{avg}} = 0$ since $n^{-1} > 0$. This means the solution is not related to n. Hence, it can be regarded as a flexible alternative because its performance is independent of the input number n.

In a nutshell, we provide two possible variants of φ: first, we show that a simple shift is sufficient to turn a max pooling layer into an EMA (EMA-MAX); second, average pooling can be directly used (EMA-AVG) without modification as a large number of points does not undermine its information entropy, making it adaptive to the dynamically changing number of point input.

3.3 ONE-SCALE-FITS-ALL: LAYER-WISE SCALE RECOVERY

In this section, we show that binarization leads to the feature scale distortion and study its cause. We conclude that the distortion is directly related to the number of feature channels. More importantly, we discuss the detriments of scale distortion from the perspectives of the functionality of scale-sensitive structures and the optimization.

To address the severe scale distortion in feature due to binarization, we propose the Layer-wise Scale Recovery (LSR). In LSR, each bi-linear layer is added only *one* learnable scaling factor to recover the original scales of *all* binarized parameters, with negligible additional computational overhead and memory usage.

(a)   (b)   (c)

Figure 3: (a) Information entropy of the aggregated features. Our BiPointNet has a higher information entropy thanks to EMA. (b) Regularizer loss comparison. Our PointNet has a low loss, indicating that the scale distortion is reduced and T-Net is not disrupted. (c) Ratio of zero-gradient activations in backpropagation. LSR alleviates the scale distortion, enhancing the optimization process

3.3.1   SCALE DISTORTION

The scale of parameters is defined as the standard deviation σ of their distribution. As we mentioned in Section 3.2, balanced binarized weights are used in the bi-linear layer aiming to maximize the entropy of the output after binarization, *i.e.*, $p_{B_w}(1) = 0.5$ and $p_{B_a}(1) = 0.5$.

Theorem 2 *When we let $p_{B_w}(1) = 0.5$ and $p_{B_a}(1) = 0.5$ in bi-linear layer to maximize the mutual information, for the binarized weight $\mathbf{B_w} \in \{-1, +1\}^{m \times k}$ and activation $\mathbf{B_a} \in \{-1, +1\}^{n \times m}$, the probability mass function for the distribution of output $\mathbf{Z}$ can be represented as $p_Z(2i - m) = 0.5^m C_m^i, i \in \{0, 1, 2, ..., m\}$. The output has approximately a normal distribution $\mathcal{N}(0, m)$.*

The proof of Theorem 2 is found in Appendix A.4. Theorem 2 shows that given the maximized information entropy, the scale of the output features is directly related to the number of feature channels. Hence, scale distortion is pervasive as a large number of channels is the design norm of deep learning neural networks for effective feature extraction.

We discuss two major impacts of the scale distortion on the performance of binarized point cloud learning models. First, the scale distortion invalidates structures designed for 3D deep learning that are sensitive to the scale of values. For example, the T-Net in PointNet is designed to predict an orthogonal transformation matrix for canonicalization of input and intermediate features (Qi et al., 2016). The predicted matrix is regularized by minimizing the loss term $L_{reg} = \left\| \mathbf{I} - \mathbf{ZZ}^T \right\|^2$. However, this regularization is ineffective for the $\mathbf{Z}$ with huge variance as shown in Figure 4.

(a) Input point cloud   (b) PointNet

(c) BiPointNet   (d) BNN

Second, the scale distortion leads to a saturation of forward-propagated activations and backward-propagated gradients (Ding et al., 2019). In the binary neural networks, some modules (such as sign and $\mathrm{Hardtanh}$) rely on the Straight-Through Estimator (STE) Bengio et al. (2013) for feature binarization or feature balancing. When the scale of their input is amplified, the gradient is truncated instead of increased proportionally. Such saturation, as shown in Fig 3(c), hinders learning and even leads to divergence.

Figure 4: Scale Distortion. Figures (b)-(d) show the transformed input. Compared with the input (a), the scale of (b) in full-precision PointNet and (c) in our BiPointNet are normal, while the scale of (d) in BNN is significantly distorted

3.3.2   LSR FOR OUTPUT SCALE RECOVERY

To recover the scale and adjustment ability of output, we propose the LSR for bi-linear layers in our BiPointNet. We design a learnable layer-wise scaling factor α in our LSR. α is initialized by the ratio of the standard deviations between the output of bi-linear and full-precision counterpart:

$$\alpha_0 = \sigma(\mathbf{A} \otimes \mathbf{W}) / \sigma(\mathbf{B_a} \odot \mathbf{B_w}), \tag{9}$$

where σ denotes as the standard deviation. And the α is learnable during the training process. The calculation and derivative process of the bi-linear layer with our LSR are as follows:

$$\text{Forward}: \mathbf{Z} = \alpha(\mathbf{B_a} \odot \mathbf{B_w}) \qquad \text{Backward}: g_\alpha = g_{\mathbf{Z}}(\mathbf{B_a} \odot \mathbf{B_w}), \tag{10}$$

where g_α and $g_{\mathbf{Z}}$ denotes the gradient $\frac{\partial C}{\partial \alpha}$ and $\frac{\partial C}{\partial \mathbf{Z}}$, respectively. By applying the LSR in BiPointNet, we mitigate the scale distortion of output caused by binarization.

Table 1: Ablation study for our BiPointNet of various tasks on ModelNet40 (classification), ShapeNet Parts (part segmentation), and S3DIS (semantic segmentation). EMA and LSR and complementary to each other, and they are useful across all three applications

Method	Bit-width	Aggr.	ModelNet40	ShapeNet Parts	S3DIS	
			OA	mIoU	mIoU	OA
Full Prec.	32/32	MAX	88.2	84.3	54.4	83.5
	32/32	AVG	86.5	84.0	51.5	81.5
BNN	1/1	MAX	7.1	54.0	9.5	45.0
BNN-LSR	1/1	MAX	4.1	58.7	2.0	25.4
BNN-EMA	1/1	EMA-avg	11.3	53.0	9.9	46.8
	1/1	EMA-max	16.2	47.3	8.5	47.2
Ours	1/1	EMA-avg	82.5	80.3	40.9	74.9
	1/1	EMA-max	**86.4**	**80.6**	**44.3**	**76.7**

Compared to existing methods, the advantages of LSR is summarized in two folds. First, LSR is efficient. It not only abandons the adjustment of input activations to avoid expensive inference time computation, but also recovers the scale of all weights parameters in a layer collectively instead of expensive restoration in a channel-wise manner. Second, LSR serves the purpose of scale recovery that we show is more effective than other adaptation such as minimizing quantization errors (Rastegari et al., 2016; Qin et al., 2019; Liu et al., 2018).

4 EXPERIMENTS

In this section, we conduct extensive experiments to validate the effectiveness of our proposed BiPointNet for efficient learning on point clouds. We first ablate our method and demonstrate the contributions of EMA and LSR on three most fundamental tasks: classification on ModelNet40 (Wu et al., 2015), part segmentation on ShapeNet (Chang et al., 2015), and semantic segmentation on S3DIS (Armeni et al., 2016). Moreover, we compare BiPointNet with existing binarization methods where our designs stand out. Besides, BiPointNet is put to the test on real-world devices with limited computational power and achieve extremely high speedup ($14.7\times$) and storage saving ($18.9\times$). The details of the datasets and the implementations are included in the Appendix E.

4.1 ABLATION STUDY

As shown in Table 1, the binarization model baseline suffers a catastrophic performance drop in the classification task. EMA and LSR improve performance considerably when used alone, and they further close the gap between the binarized model and the full-precision counterpart when used together.

In Figure 3, we further validate the effectiveness of EMA and LSR. We show that BiPointNet with EMA has its information entropy maximized during training, whereas the vanilla binarized network with max pooling gives limited and highly fluctuating results. Also, we make use of the regularization loss $L_{reg} = \left\| \mathbf{I} - \mathbf{Z}\mathbf{Z}^T \right\|_F$ for the feature transformation matrix of T-Net in PointNet as an indicator, the L_{reg} of the BiPointNet with LSR is much smaller than the vanilla binarized network, demonstrating LSR's ability to reduce the scale distortion caused by binarization, allowing proper prediction of orthogonal transformation matrices.

Moreover, we also include the results of two challenging tasks, part segmentation, and semantic segmentation, in Table 1. As we follow the original PointNet design for segmentation, which has a branch that retains pointwise features and bypasses global max pooling, segmentation suffers from the information loss caused by the aggregation function. Nevertheless, EMA and LSR are proven to be effective: BiPointNet is approaching the full precision counterpart with only $\sim 4\%$ mIoU difference on part segmentation and $\sim 10.4\%$ mIoU gap on semantic segmentation. The full results of segmentation are presented in Appendix E.6.

4.2 COMPARATIVE EXPERIMENTS

In Table 2, we show that our BiPointNet outperforms other binarization methods such as BNN (Hubara et al., 2016), XNOR (Rastegari et al., 2016), Bi-Real (Liu et al., 2018), and IR-

Table 2: Comparison of binarization methods on PointNet. EMA is critical; even if all methods are equipped with our EMA, our LSR outperforms others with least number of scaling factors. OA: Overall Accuracy

Method	Bit-width	Aggr.	# Factors	OA
Full Prec.	32/32	MAX	-	88.2
	32/32	AVG	-	86.5
BNN	1/1	MAX	0	7.1
	1/1	EMA-avg	0	11.3
	1/1	EMA-max	0	16.2
IR-Net	1/1	MAX	10097	7.3
	1/1	EMA-avg	10097	22.0
	1/1	EMA-max	10097	63.5
Bi-Real	1/1	MAX	10097	4.0
	1/1	EMA-avg	10097	77.0
	1/1	EMA-max	10097	77.5
XNOR	1/1	MAX	28529	64.9
	1/1	EMA-avg	28529	78.2
	1/1	EMA-max	28529	81.9
Ours	1/1	MAX	18	4.1
	1/1	EMA-avg	18	82.5
	1/1	EMA-max	18	**86.4**

Table 3: Our methods on mainstream backbones. We use XNOR as a strong baseline for comparison. The techniques in our BiPointNet are generic to point cloud learning. Hence, they are easily extendable to other backbones

Base Model	Method	Bit-width	Aggr.	OA
PointNet (Vanilla)	Full Prec.	32/32	MAX	86.8
	XNOR	1/1	MAX	61.0
	Ours	1/1	EMA-max	85.6
PointNet	Full Prec.	32/32	MAX	88.2
	XNOR	1/1	MAX	64.9
	Ours	1/1	EMA-max	86.4
PointNet++	Full Prec.	32/32	MAX	90.0
	XNOR	1/1	MAX	63.1
	Ours	1/1	EMA-max	87.8
PointCNN	Full Prec.	32/32	AVG	90.0
	XNOR	1/1	AVG	83.0
	Ours	1/1	EMA-avg	83.8
DGCNN	Full Prec.	32/32	MAX	89.2
	XNOR	1/1	MAX	51.5
	Ours	1/1	EMA-max	83.4

Net (Qin et al., 2019). Although these methods have been proven effective in 2D vision, they are not readily transferable to point clouds due to aggregation-induced feature homogenization.

Even if we equip these methods with our EMA to mitigate information loss, our BiPointNet still performs better. We argue that existing approaches, albeit having many scaling factors, focus on minimizing quantization errors instead of recovering feature scales critical to effective learning on point clouds. Hence, BiPointNet stands out with a negligible increase of parameters that are designed to restore feature scales. The detailed analysis of the performance of XNOR is found in Appendix C. Moreover, we highlight that our EMA and LSR are generic, and Table 3 shows improvements across several mainstream categories of point cloud deep learning models.

4.3 Deployment Efficiency on Real-world Devices

To further validate the efficiency of BiPointNet when deployed into the real-world edge devices, we further implement our BiPointNet on Raspberry Pi 4B with 1.5 GHz 64-bit quad-core ARM CPU Cortex-A72 and Raspberry Pi 3B with 1.2 GHz 64-bit quad-core ARM CPU Cortex-A53. In Figure 5, we compare our BiPointNet with the PointNet. We highlight that BiPointNet achieves $14.7\times$ inference speed increase and $18.9\times$ storage reduction over PointNet, which is recognized as a fast and lightweight model itself.

Figure 5: Experiments on resource-constrained devices with ARM CPUs

5 Conclusion

We propose BiPointNet, the first binarization approach for efficient learning on point clouds. We build a theoretical foundation to study the impact of binarization on point cloud learning models, and proposed EMA and LSR in BiPointNet to improve the performance. BiPointNet outperforms existing binarization methods, and it is easily extendable to a wide range of tasks and backbones, giving an impressive $14.7\times$ speedup and $18.9\times$ storage saving on resource-constrained devices. Our work demonstrates the great potential of binarization. We hope our work can serve as a strong foundation for future research.

REFERENCES

I. Armeni, O. Sener, A. R. Zamir, H. Jiang, I. Brilakis, M. Fischer, and S. Savarese. 3d semantic parsing of large-scale indoor spaces. In *IEEE CVPR*, pp. 1534–1543, 2016.

Yoshua Bengio, Nicholas Léonard, and Aaron Courville. Estimating or propagating gradients through stochastic neurons for conditional computation. *arXiv preprint arXiv:1308.3432*, 2013.

Adrian Bulat and Georgios Tzimiropoulos. Xnor-net++: Improved binary neural networks. *CoRR*, abs/1909.13863, 2019.

Angel X. Chang, Thomas Funkhouser, Leonidas Guibas, Pat Hanrahan, Qixing Huang, Zimo Li, Silvio Savarese, Manolis Savva, Shuran Song, Hao Su, Jianxiong Xiao, Li Yi, and Fisher Yu. Shapenet: An information-rich 3d model repository, 2015.

Ruizhou Ding, Ting-Wu Chin, Zeye Liu, and Diana Marculescu. Regularizing activation distribution for training binarized deep networks. In *IEEE CVPR*, June 2019.

Matthias Fey and Jan E. Lenssen. Fast graph representation learning with PyTorch Geometric. In *ICLR Workshop on Representation Learning on Graphs and Manifolds*, 2019.

Ross Girshick. Fast r-cnn. In *IEEE ICCV*, 2015.

Ross Girshick, Jeff Donahue, Trevor Darrell, and Jitendra Malik. Rich feature hierarchies for accurate object detection and semantic segmentation. In *IEEE CVPR*, 2014.

Yulan Guo, Hanyun Wang, Qingyong Hu, Hao Liu, Li Liu, and Mohammed Bennamoun. Deep learning for 3d point clouds: A survey. *IEEE TPAMI*, 2020.

Lu Hou, Quanming Yao, and James T. Kwok. Loss-aware binarization of deep networks. *ICLR*, 2017.

Qingyong Hu, Bo Yang, Linhai Xie, Stefano Rosa, Yulan Guo, Zhihua Wang, Niki Trigoni, and Andrew Markham. Randla-net: Efficient semantic segmentation of large-scale point clouds, 2019.

Itay Hubara, Matthieu Courbariaux, Daniel Soudry, Ran El-Yaniv, and Yoshua Bengio. Binarized neural networks. In *NeurIPS*. 2016.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. In *NeurIPS*. 2012.

Yangyan Li, Rui Bu, Mingchao Sun, Wei Wu, Xinhan Di, and Baoquan Chen. Pointcnn: Convolution on $\mathcal{X}$-transformed points, 2018.

Xiaofan Lin, Cong Zhao, and Wei Pan. Towards accurate binary convolutional neural network. In *NeurIPS*. 2017.

Chunlei Liu, Wenrui Ding, Xin Xia, Baochang Zhang, Jiaxin Gu, Jianzhuang Liu, Rongrong Ji, and David S. Doermann. Circulant binary convolutional networks: Enhancing the performance of 1-bit dcnns with circulant back propagation. In *IEEE CVPR*, 2019a.

Zechun Liu, Baoyuan Wu, Wenhan Luo, Xin Yang, Wei Liu, and Kwang-Ting Cheng. Bi-real net: Enhancing the performance of 1-bit cnns with improved representational capability and advanced training algorithm. In *ECCV*, 2018.

Zechun Liu, Zhiqiang Shen, Marios Savvides, and Kwang-Ting Cheng. Reactnet: Towards precise binary neural network with generalized activation functions, 2020.

Zhijian Liu, Haotian Tang, Yujun Lin, and Song Han. Point-voxel cnn for efficient 3d deep learning, 2019b.

Brais Martinez, Jing Yang, Adrian Bulat, and Georgios Tzimiropoulos. Training binary neural networks with real-to-binary convolutions. In *ICLR*, 2020.

Charles R. Qi, Hao Su, Kaichun Mo, and Leonidas J. Guibas. Pointnet: Deep learning on point sets for 3d classification and segmentation, 2016.

Charles R. Qi, Li Yi, Hao Su, and Leonidas J. Guibas. Pointnet++: Deep hierarchical feature learning on point sets in a metric space, 2017.

Haotong Qin, Ruihao Gong, Xianglong Liu, Mingzhu Shen, Ziran Wei, Fengwei Yu, and Jingkuan Song. Forward and backward information retention for accurate binary neural networks, 2019.

Haotong Qin, Ruihao Gong, Xianglong Liu, Xiao Bai, Jingkuan Song, and Nicu Sebe. Binary neural networks: A survey. *Pattern Recognition*, 2020.

Mohammad Rastegari, Vicente Ordonez, Joseph Redmon, and Ali Farhadi. Xnor-net: Imagenet classification using binary convolutional neural networks. In *ECCV*, 2016.

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael S Bernstein, et al. Imagenet large scale visual recognition challenge. *IJCV*, 2015.

Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *arXiv preprint arXiv:1409.1556*, 2014.

Christian Szegedy, Wei Liu, Yangqing Jia, Pierre Sermanet, Scott Reed, Dragomir Anguelov, Dumitru Erhan, Vincent Vanhoucke, and Andrew Rabinovich. Going deeper with convolutions. In *IEEE CVPR*, 2015.

Yiru Wang, Weihao Gan, Wei Wu, and Junjie Yan. Dynamic curriculum learning for imbalanced data classification. In *IEEE ICCV*, 2019a.

Yunhe Wang, Chang Xu, Chao Xu, and Dacheng Tao. Packing convolutional neural networks in the frequency domain. *IEEE TPAMI*, 2019b.

Ziwei Wang, Ziyi Wu, Jiwen Lu, and Jie Zhou. Bidet: An efficient binarized object detector, 2020.

Zhirong Wu, Shuran Song, Aditya Khosla, Fisher Yu, Linguang Zhang, Xiaoou Tang, and Jianxiong Xiao. 3d shapenets: A deep representation for volumetric shapes, 2015.

Zizhao Wu, Ruyang Shou, Yunhai Wang, and Xinguo Liu. Interactive shape co-segmentation via label propagation. *Computers & Graphics*, 38:248–254, 2014.

Bo Xie, Yingyu Liang, and Le Song. Diverse neural network learns true target functions. In *Artificial Intelligence and Statistics*, 2017.

Chenfeng Xu, Bichen Wu, Zining Wang, Wei Zhan, Peter Vajda, Kurt Keutzer, and Masayoshi Tomizuka. Squeezesegv3: Spatially-adaptive convolution for efficient point-cloud segmentation, 2020.

Qiangeng Xu, Xudong Sun, Cho-Ying Wu, Panqu Wang, and Ulrich Neumann. Grid-gcn for fast and scalable point cloud learning, 2019.

Yinghao Xu, Xin Dong, Yudian Li, and Hao Su. A main/subsidiary network framework for simplifying binary neural networks. In *IEEE CVPR*, June .

Li Yi, Vladimir G Kim, Duygu Ceylan, I-Chao Shen, Mengyan Yan, Hao Su, Cewu Lu, Qixing Huang, Alla Sheffer, and Leonidas Guibas. A scalable active framework for region annotation in 3d shape collections. *ACM Transactions on Graphics (ToG)*, 35(6):1–12, 2016.

Jianhao Zhang, Yingwei Pan, Ting Yao, He Zhao, and Tao Mei. dabnn: A super fast inference framework for binary neural networks on ARM devices. In *ACM MM*, 2019.

Shuchang Zhou, Yuxin Wu, Zekun Ni, Xinyu Zhou, He Wen, and Yuheng Zou. Dorefa-net: Training low bitwidth convolutional neural networks with low bitwidth gradients. *CoRR*, abs/1606.06160, 2016.

Shilin Zhu, Xin Dong, and Hao Su. Binary ensemble neural network: More bits per network or more networks per bit? In *IEEE CVPR*, 2019.

APPENDIX FOR BIPOINTNET

A MAIN PROOFS AND DISCUSSION

A.1 PROOF OF ZERO CONDITIONAL ENTROPY

In our BiPointNet, we hope that the binarized tensor $\mathbf{B}$ reflects the information in the original tensor $\mathbf{Y}$ as much as possible. From the perspective of information, our goal is equivalent to maximizing the mutual information $\mathcal{I}(Y; B)$ of the random variables Y and B:

$$\arg\max_{Y,B} \mathcal{I}(Y; B) \tag{11}$$

$$= \sum_{y\in\mathcal{Y}, b\in\mathcal{B}} p_{(Y,B)}(y,b) \log \frac{p_{(Y,B)}(y,b)}{p_Y(y)p_B(b)} \tag{12}$$

$$= \sum_{y\in\mathcal{Y}, b\in\mathcal{B}} p_{(Y,B)}(y,b) \log \frac{p_{(Y,B)}(y,b)}{p_Y(y)} - \sum_{y\in\mathcal{Y}, b\in\mathcal{B}} p_{(Y,B)}(y,b) \log p_B(b) \tag{13}$$

$$= \sum_{y\in\mathcal{Y}, b\in\mathcal{B}} p_Y(y)p_{B|Y=y}(b) \log p_{B|Y=y}(b) - \sum_{y\in\mathcal{Y}, b\in\mathcal{B}} p_{(Y,B)}(y,b) \log p_B(b) \tag{14}$$

$$= \sum_{y\in\mathcal{Y}} p_Y(y) \Big(\sum_{b\in\mathcal{B}} p_{B|Y=y}(b) \log p_{B|Y=y}(b) \Big) - \sum_{b\in\mathcal{B}} \Big(\sum_{y} p_{(Y,B)}(y,b) \Big) \log p_B(b) \tag{15}$$

$$= -\sum_{y\in\mathcal{Y}} p(y)\mathcal{H}(B \mid Y=y) - \sum_{b\in\mathcal{B}} p_B(b) \log p_B(b) \tag{16}$$

$$= -\mathcal{H}(B \mid Y) + \mathcal{H}(B) \tag{17}$$

$$= \mathcal{H}(B) - \mathcal{H}(B \mid Y) \tag{18}$$

where $p_{(Y,B)}$ and p_Y, p_B are the joint and marginal probability mass functions of these discrete variables. $\mathcal{H}(B)$ is the information entropy, and $\mathcal{H}(B|Y)$ is the conditional entropy of B given Y. According to the Eq. (15) and Eq. (18), the conditional entropy $\mathcal{H}(Y \mid X)$ can be expressed as

$$\mathcal{H}(B \mid Y) = \sum_{y\in\mathcal{Y}} p_Y(y) \Big(\sum_{b\in\mathcal{B}} p_{B|Y=y}(b) \log p_{B|Y=y}(b) \Big) \tag{19}$$

Since we use the deterministic sign function as the quantizer in binarization, the value of B fully depends on the value of Y, $p_{B|Y=y}(b) = 0$ or 1 in Eq. (4), *i.e.* every value y has a fixed mapping to a binary value b. Then we have:

$$\mathcal{H}(B \mid Y) = \sum_{y\in\mathcal{Y}} p_Y(y)(0 + 0 + \cdots + 0) = 0 \tag{20}$$

Thus the original objective function can be equivalent to maximizing the information entropy $\mathcal{H}(B)$:

$$\arg\max_{B} \mathcal{H}_B(B) = -\sum_{b\in\mathcal{B}} p_B(b) \log p_B(b). \tag{21}$$

A.2 PROOFS OF THEOREM 1

Theorem 1 *For input X_ϕ of max pooling ϕ with arbitrary distribution, the information entropy of the binarized output to zero as n to infinity, i.e, $\lim\limits_{n\to+\infty} \mathcal{H}_B = 0$. And there is a constant c, for any n_1 and n_2, if $n_1 > n_2 > c$, we have $\mathcal{H}_{B,n_1} > \mathcal{H}_{B,n_2}$, where n is the number of aggregated elements.*

Proof. We have the correlation between the probability mass function of input $\mathbf{X}_\phi$ and output $\mathbf{Y}$ of max pooling, intuitively, all values are negative to give a negative maximum value:

$$\sum_{y<0} p_Y(y) = \Big(\sum_{x_\phi<0} p_{X_\phi}(x_\phi) \Big)^n \tag{22}$$

Since the sign function is applied as the quantizer, the $\mathcal{H}_B(B)$ of binarized feature can be expressed as Eq. (6).

(1) When X_ϕ obeys a arbitrary distribution, the probability mass function $p_{X_\phi}(x_\phi)$ must satisfies $\sum_{x_\phi<0} p_{X_\phi}(x_\phi) \le 1$. According to Eq. (6), let $t = \sum_{x_\phi<0} p_{X_\phi}(x_\phi)$, we have

$$\lim_{n\to\infty} \mathcal{H}_B(X_\phi) = \lim_{n\to\infty} \left(-t^n \log t^n - (1-t)^n \log (1-t)^n \right) \tag{23}$$

$$= - \Big(\lim_{n\to\infty} t^n \Big) \log \Big(\lim_{n\to\infty} t^n \Big) - \Big(\lim_{n\to\infty} (1-t)^n \Big) \log \Big(\lim_{n\to\infty} (1-t)^n \Big) \tag{24}$$

$$= -0 \log 0 - 1 \log 1 \tag{25}$$

$$= 0 \tag{26}$$

(2) For any $n \ge 1$, we can obtain the representation of the information entropy $\mathcal{H}_{B,n}(X_\phi)$:

$$\mathcal{H}_{B,n}(X_\phi) = - \Big(\sum_{x_\phi<0} p_{X_\phi}(x_\phi) \Big)^n \log \Big(\sum_{x_\phi<0} p_{X_\phi}(x_\phi) \Big)^n$$
$$- \Big(1 - \Big(\sum_{x_\phi<0} p_{X_\phi}(x_\phi) \Big)^n \Big) \log \Big(1 - \Big(\sum_{x_\phi<0} p_{X_\phi}(x_\phi) \Big)^n \Big), \tag{27}$$

Let $p_n = \Big(\sum_{x_\phi<0} p_{X_\phi}(x_\phi) \Big)^n$, the $\mathcal{H}_{B,n}(p_n)$ can be expressed as:

$$\mathcal{H}_{B,n}(p_n) = -p_n \log p_n - (1-p_n) \log(1-p_n), \tag{28}$$

and the derivative of $\mathcal{H}_{B,n}(p_n)$ is

$$\frac{d \, \mathcal{H}_{B,n}(p_n)}{d \, p_B(p_n)} = \log \Big(\frac{1-p_n}{p_n} \Big), \tag{29}$$

the $\mathcal{H}_{B,n}(p_n)$ is maximized when p_n takes 0.5, and is positive correlation with p_n when $p_n < 0.5$ since the $\frac{d \, \mathcal{H}_{B,n}(p_n)}{d \, p_B(p_n)} > 0$ when $p_n < 0.5$.

Therefore, when the constant c satisfies $p_c = \Big(\sum_{x_\phi<0} p_{X_\phi}(x_\phi) \Big)^c \ge 0.5$, given the $n_1 > n_2 > c$, we have $p_{n_1} < p_{n_2} < p_c$, and $\mathcal{H}_{B,n_1}(X_\phi) < \mathcal{H}_{B,n_2}(X_\phi) < \mathcal{H}_{B,c}(X_\phi)$.

$\square$

A.3 PROOFS OF PROPOSITION 1

Proposition 1 *When the distribution of the random variable Y satisfies $\sum_{y<0} p_Y(y) = \sum_{y\ge0} p_Y(y) = 0.5$, the information entropy $\mathcal{H}_B$ is maximized.*

Proof. According to Eq (21), we have:

$$\mathcal{H}_B(B) = - \sum_{b\in\mathcal{B}} p_B(b) \log p_B(b) \tag{30}$$

$$= - \left(p_B(-1) \log p_B(-1) + p_B(1) \log p_B(1) \right) \tag{31}$$

$$= - \left(p_B(-1) \log p_B(-1) + (1 - p_B(-1)) \log (1 - p_B(-1)) \right) \tag{32}$$

Then we can get the derivative of $\mathcal{H}_B(B)$ with respect to $p_B(-1)$:

$$\frac{d\,\mathcal{H}_B(B)}{d\,p_B(-1)} = -\left(\log p_B(-1) + \frac{p_B(-1)}{p_B(-1)\ln 2}\right) + \left(\log\left(1 - p_B(-1)\right) + \frac{1 - p_B(-1)}{(1 - p_B(-1))\ln 2}\right) \tag{33}$$

$$= -\log p_B(-1) + \log\left(1 - p_B(-1)\right) - \frac{1}{\ln 2} + \frac{1}{\ln 2} \tag{34}$$

$$= \log\left(\frac{1 - p_B(-1)}{p_B(-1)}\right) \tag{35}$$

When we let $\frac{d\,\mathcal{H}_B(B)}{d\,p_B(-1)} = 0$ to maximize the $\mathcal{H}_B(B)$, we have $p_B(-1) = 0.5$. Sine the deterministic $sign$ function with the zero threshold is applied as the quantizer, the probability mass function of B is represented as:

$$p_B(b) = \begin{cases} \sum\limits_{y<0} p_Y(y)\,dy, & \text{if } b = -1 \\ \sum\limits_{y\geq 0} p_Y(y)\,dy, & \text{if } b = 1, \end{cases} \tag{36}$$

and when the information entropy is maximized, we have:

$$\sum_{y<0} p_Y(y)\,dy = 0.5 \tag{37}$$

$\square$

A.4 Discussion and Proofs of Theorem 2

The bi-linear layers are widely used in our BiPointNet to model each point independently, and each linear layer outputs an intermediate feature. The calculation of the bi-linear layer is represented as Eq. (2). Since the random variable B is sampled from $\mathbf{B_w}$ or $\mathbf{B_a}$ obeying Bernoulli distribution, the probability mass function of B can be represented as

$$p_B(b) = \begin{cases} p, & \text{if } b = +1 \\ 1 - p, & \text{if } b = -1, \end{cases} \tag{38}$$

where p is the probability of taking the value +1. The distribution of output $\mathbf{Z}$ can be represented by the probability mass function of $\mathbf{B_w}$ and $\mathbf{B_a}$.

Proposition 2 *In bi-linear layer, for the binarized weight $\mathbf{B_w} \in \{-1, +1\}^{m\times k}$ and activation $\mathbf{B_a} \in \{-1, +1\}^{n\times m}$ with probability mass function $p_{B_w}(1) = p_w$ and $p_{B_a}(1) = p_a$, the probability mass function for the distribution of output $\mathbf{Z}$ can be represented as $p_Z(2i - m) = C_m^i(1 - p_w - p_a + 2p_wp_a)^i(p_w + p_a - 2p_wp_a)^{m-i}, i \in \{0, 1, 2, ..., m\}$.*

Proof. To simplify the notation in the following statements, we define $\mathbf{A} = \mathbf{B_a}$ and $\mathbf{W} = \mathbf{B_w}$. Then, for each element $\mathbf{Z}_{i,j}$ in output $\mathbf{Z} \in \{-1, +1\}^{n\times k}$, we have:

$$x_{i,j} = \sum_{k=1}^{m} \mathbf{A}_{i,k} \times \mathbf{W}_{k,j} \tag{39}$$

Observe that $\mathbf{A}_{i,k}$ is independent to $\mathbf{W}_{k,j}$ and the value of both variables are either -1 or $+1$. Therefore, the discrete probability distribution of $\mathbf{A}_{i,k} \times \mathbf{W}_{k,j}$ can be defined as below:

$$p(x) = \begin{cases} p_wp_a + (1 - p_w) \times (1 - p_a), & \text{if } x = 1 \\ p_w \times (1 - p_a) + (1 - p_w) \times p_a, & \text{if } x = -1 \\ 0, & \text{otherwise.} \end{cases} \tag{40}$$

Simplify the above equation

$$p(x) = \begin{cases} 1 - p_w - p_a + 2p_w p_a, & \text{if } x = 1 \\ p_w + p_a - 2p_w p_a, & \text{if } x = -1 \\ 0, & \text{otherwise.} \end{cases} \tag{41}$$

Notice that $x_{i,j}$ can be parameterized as a binomial distribution. Then we have

$$\Pr(x_{i,j} = l - (m - l)) = C_m^l (1 - p_w - p_a + 2p_w p_a)^l (p_w + p_a - 2p_w p_a)^{m-l} \tag{42}$$

Observe that p_Z obeys the same distribution as $x_{i,j}$. Finally we have

$$p_Z(2i - m) = C_m^i (1 - p_w - p_a + 2p_w p_a)^i (p_w + p_a - 2p_w p_a)^{m-i}, i \in \{0, 1, 2, ..., m\} \tag{43}$$

$\square$

Proposition 2 shows that the output distribution of bi-linear layer depends the probability mass functions of binarized weight and activation. Then we present the proofs of Theorem 2.

Theorem 2 *When we let $p_{B_w}(1) = 0.5$ and $p_{B_a}(1) = 0.5$ in bi-linear layer to maximize the mutual information, for the binarized weight $\mathbf{B_w} \in \{-1, +1\}^{m \times k}$ and activation $\mathbf{B_a} \in \{-1, +1\}^{n \times m}$, the probability mass function for the distribution of output $\mathbf{Z}$ can be represented as $p_Z(2i - m) = 0.5^m C_m^i, i \in \{0, 1, 2, ..., m\}$. The distribution of output is approximate normal distribution $\mathcal{N}(0, m)$.*

Proof. First, we prove that the distribution of Z can be approximated as a normal distribution. For bi-linear layers in our BiPointNet, all weight and activation are binarized, which can be represented as $\mathbf{B_w}$ and $\mathbf{B_a}$, respectively. And the value of element $z_{(i,j)}$ in $\mathbf{Z}$ can be expressed as

$$z_{(i,j)} = \sum_{k=1}^{m} \left(b_{w(i,k)} \times b_{a(k,j)} \right),$$

and the value of the element $b_{w(i,k)} \times b_{a(k,j)}$ can be expressed as

$$b_{w(i,k)} \times b_{a(k,j)} = \begin{cases} 1, & \text{if } b_{w(i,k)} \veebar b_{a(k,j)} = 1 \\ -1, & \text{if } b_{w(i,k)} \veebar b_{a(k,j)} = -1. \end{cases} \tag{44}$$

The $b_{w(i,k)} \times b_{a(k,j)}$ only can be take from two values and its value can be considered as the result of one Bernoulli trial. Thus for the random variable Z sampled from the output tensor $\mathbf{Z}$, the probability mass function p_Z can be expressed as

$$p_Z(2i - m) = C_m^i p_e^k (1 - p_e)^{n-k}, \tag{45}$$

where p_e denotes the probability that the element $b_{w(i,k)} \times b_{a(k,j)}$ takes 1. Note that the Eq. (45) is completely equivalent the representation in Proposition 2. According to the *De Moivre–Laplace* theorem, the normal distribution $\mathcal{N}(\mu, \sigma^2)$ can be used as an approximation to the binomial distribution under certain conditions, and the $p_Z(2i - m)$ can be approximated as

$$p_Z(2i - m) = C_m^i p_e^k (1 - p_e)^{n-k} \simeq \frac{1}{\sqrt{2\pi n p_e (1 - p_e)}} e^{-\frac{(k - n p_e)^2}{2 n p_e (1 - p_e)}}, \tag{46}$$

and then, we can get the mean $\mu = 0$ and variance $\sigma = \sqrt{m}$ of the approximated distribution $\mathcal{N}$ with the help of equivalent representation of p_Z in Proposition 2. Now we give proof of this below.

According to Proposition 2, when $p_w = p_a = 0.5$, we can rewrite the equation as below

$$p_Z(2i - m) = 0.5^m C_m^i, i \in \{0, 1, 2, ..., m\} \tag{47}$$

Then we move to calculate the mean and standard variation of this distribution. The mean of this distribution is defined as below

$$\mu(p_Z) = \sum (2i - m)0.5^m C_m^i, i \in \{0, 1, 2, ..., m\} \tag{48}$$

By the virtue of binomial coefficient, we have

$$(2i - m)0.5^m C_m^i + (2(m - i) - m)0.5^m C_m^{m-i} = 0.5^m((2i - m)C_m^i + (m - 2i)C_m^{m-i}) \tag{49}$$
$$= 0.5^m((2i - m)C_m^i + (m - 2i)C_m^i) \tag{50}$$
$$= 0 \tag{51}$$

Besides, when m is an even number, we have $(2i - m)0.5^m C_m^i = 0, i = \frac{m}{2}$. These equations prove the symmetry of function $(2i - m)0.5^m C_m^i$. Finally we have

$$\mu(p_Z) = \sum (2i - m)0.5^m C_m^i, i \in \{0, 1, 2, ..., m\} \tag{52}$$
$$= \sum ((2i - m)0.5^m C_m^i + (2(m - i) - m)0.5^m C_m^{m-i}), i \in \{0, 1, 2, ..., \frac{m}{2}\} \tag{53}$$
$$= 0 \tag{54}$$

The standard variation of p_Z is defined as below

$$\sigma(p_Z) = \sqrt{\left(\sum |2i - m|^2 0.5^m C_m^i\right)} \tag{55}$$
$$= \sqrt{\sum (4i^2 - 4im + m^2) 0.5^m C_m^i} \tag{56}$$
$$= \sqrt{0.5^m \left(4 \sum i^2 C_m^i - 4m \sum i C_m^i + m^2 \sum C_m^i\right)} \tag{57}$$

To calculate the standard variation of p_Z, we use Binomial Theorem and have several identical equations

$$\sum C_m^i = (1 + 1)^m = 2^m \tag{58}$$
$$\sum i C_m^i = m(1 + 1)^{m-1} = m2^{m-1} \tag{59}$$
$$\sum i^2 C_m^i = m(m + 1)(1 + 1)^{m-2} = m(m + 1)m2^{m-2} \tag{60}$$

These identical equations help simplify Equation 57

$$\sigma(p_Z) = \sqrt{0.5^m \left(4 \sum i^2 C_m^i - 4m \sum i C_m^i + m^2 \sum C_m^i\right)} \tag{61}$$
$$= \sqrt{0.5^m(4m(m + 1)2^{m-2} - 4m^2 2^{m-1} + m^2 2^m)} \tag{62}$$
$$= \sqrt{0.5^m((m^2 + m)2^m - 2m^2 2^m + m^2 2^m)} \tag{63}$$
$$= \sqrt{0.5^m(m2^m)} \tag{64}$$
$$= \sqrt{m} \tag{65}$$

Now we proved that, the distribution of output is approximate normal distribution $\mathcal{N}(0, m)$. $\qquad \square$

A.5 Discussion of the Optimal δ for EMA-max

When the $X_\phi \sim \mathcal{N}(0,1)$, the objective function of EMA-max to obtain optimal δ^* is represented as Eq. (8). It is difficult to directly solve the objective function. To circumvent this issue, we use Monte Carlo simulation to approximate the value of the optimal $\delta^*_{\max}$ as shown Algorithm 1.

Algorithm 1: Monte Carlo Simulation for EMA-max

Input: The number n of points to be aggregated; the number of simulations m (*e.g.* 10000)
Output: Estimated optimal $\delta^*_{\max}$ for EMA-max

1: Creating an empty list F (represents elements sampled form distribution of aggregated feature)
2: **for** $i = 0$ to m **do**
3:     Creating an empty list T_i (representing one channel of input feature)
4:     **for** $j = 0$ to n **do**
5:         Sampling an element e_{ij} from the distribution $\mathcal{N}(0,1)$
6:         Adding the sampled element e_{ij} to the list T_i
7:     **end for**
8:     Adding an element represents the aggregated feature $\text{MAX}(T_i)$ to F
9: **end for**
10: Estimating the optimal $\delta^*_{\max}$ as $\delta^*_{\max} = \text{Median}(F)$ (follow Proposition 1)

A.6 Discussion of the Optimal δ for EMA-avg

When the $X_\phi \sim \mathcal{N}(0,1)$, the $Y \sim \mathcal{N}(n^{-1}\delta, 1)$ and the objective function of EMA-avg for obtaining optimal δ^*_{avg} can be represented as

$$
\begin{aligned}
\arg\max_\delta \mathcal{H}_B(\delta) = &- \Big(\sum_{x_\phi < 0} \frac{1}{\sqrt{2\pi}} e^{-\frac{\left(x_\phi - n^{-1}\delta\right)^2}{2}} \Big) \log \Big(\sum_{x_\phi < 0} \frac{1}{\sqrt{2\pi}} e^{-\frac{\left(x_\phi - n^{-1}\delta\right)^2}{2}} \Big) \\
&- \Big(\sum_{x_\phi \geq 0} \frac{1}{\sqrt{2\pi}} e^{-\frac{\left(x_\phi - n^{-1}\delta\right)^2}{2}} \Big) \log \Big(\sum_{x_\phi \geq 0} \frac{1}{\sqrt{2\pi}} e^{-\frac{\left(x_\phi - n^{-1}\delta\right)^2}{2}} \Big),
\end{aligned}
\tag{66}
$$

The solution of Eq. (66) is expressed as $n^{-1}\delta = 0$, we thus obtain $\delta^*_{\text{avg}} = 0$ since $n^{-1} > 0$. This means the solution is not related to n.

B   Implementation of BiPointNet on ARM Devices

B.1   Overview

We further implement our BiPointNet on Raspberry Pi 4B with 1.5 GHz 64-bit quad-core ARM Cortex-A72 and Raspberry Pi 3B with 1.2 GHz 64-bit quad-core ARM Cortex-A53, and test the real speed in practice. Although the PointNet is a recognized high-efficient model, the inference speed of BiPointNet is much faster. Compared with the PointNet, BiPointNet enjoys up to $14.7\times$ speedup and $18.9\times$ storage saving.

We utilize the SIMD instruction SSHL on ARM NEON to make inference framework daBNN (Zhang et al., 2019) compatible with our BiPointNet, and further optimize the implementation for a more efficient inference.

B.2   Implementation Detail

Figure 6 shows the detailed structures of six PointNet implementations. In Full-Precision version (a), BN is merged into the later fully connected layer for speedup, which is widely opted during deployment in real-world applications. In Binarization version (b)(c)(d)(e), we have to keep BN unmerged due to the binarization of later layers. Instead, we merge the scaling factor of LSR into BN layers. The hardtanh function is removed because it does not affect the banarized value of input

for the later layers. We test the quantization for first layer and last layer in variant (b)(c)(d)(e). In the last variant(f), we try to drop the BN layers during training. The scaling factor is ignored during deployment because it does not change the sign of output.

Figure 6: Structures of different PointNet implementations. Three fully connected layers are used in all six variants: Full Precision FC, Binarization FC with BN, Binarization FC w/o BN. Full Precision FC contains a full precision fully connected layer and a ReLU layer. Original BN is merged into the later layer. Binarization FC with BN also contains two layers: a quantized fully connected layer and a batch normalization layer. Binarization FC w/o BN is formed by a single quantized fully connected layer

B.3   ABLATION ANALYSIS OF TIME COST AND QUANTIZATION SENSITIVITY

Setup	Bit-width	FL	LL	BN	OA	Storage & Saving Ratio	Time & Speedup Ratio A72	Time & Speedup Ratio A53
(a)	32/32	32/32	32/32	Merged	86.5	3.16MB / 1.0×	131ms / 1.0×	67ms / 1.0×
(b)	1/1	32/32	32/32	Not Merged	85.62	0.17MB / 18.9×	9.0ms / 14.7×	5.5ms / 12.1×
(c)	1/1	32/32	1/1	Not Merged	84.60	0.12MB / 26.3×	9.0ms / 14.7×	5.3ms / 12.6×
(d)	1/1	1/1	32/32	Not Merged	5.31	0.16MB / 19.7×	11.5ms / 11.4×	6.5ms / 10.3×
(e)	1/1	1/1	1/1	Not Merged	4.86	0.12MB / 26.3×	11.4ms / 11.5×	6.4ms / 10.4×
(f)	1/1	32/32	32/32	Not Used	85.13	0.15MB / 21.0×	8.1ms / 16.1×	4.8ms / 13.9×

Table 4: Comparison of different configurations in deployment on ARM devices. The storage saving ratio and speedup ratio are calculated according to the full precision model as the first row illustrates. All the models use PointNet as base model and opt EMA-max as aggregation function. The accuracy performance is reported on point cloud classification task with the ModelNet40 dataset. FL: First Layer; LL: Last Layer

Table 4 shows the detailed configuration including overall accuracy, storage usage and time cost of above-mentioned six implementations. The result shows that binarization of the middle fully connected layers can extremely speed up the original model. We achieve 18.9× storage saving, 14.7× speedup on A72 and 12.1× speed on A53. The quantization of the last layer further helps save storage consumption and improves the speed with a slight performance drop. However, the quantization of the first layer causes a dramatic drop on accuracy with barely no computational cost reduction. The variant (f) without BN achieves comparable performance with variant (b). It suggests that our LSR method could be an ideal alternative to the original normalization layers to achieve a fully quantized model except for first layer.

C   COMPARISON BETWEEN LAYER-WISE SCALE RECOVERY AND OTHER METHODS

In this section we will analyse the difference between LSR method with other classical methods. Theorem 2 shows the significance of recovering scale in point cloud learning. However, IRNet and BiReal only consider the scale of weight but ignore the scale of input feature. Therefore, these two methods cannot recover the scale of output due to scale distortion on the input feature. A major difference between these two methods is that LSR opts layer-wise scaling factor while XNOR opts point-wise scaling factor. Point-wise scale recovery needs dynamical computation during inference while our proposed LSR only has a layer-wise global scaling factor, which is independent on the input. As a result, our method can achieve higher speed in practice.

Figure 7: The information entropy of BNN, XNOR and our BiPointNet

Table 3 shows that XNOR can alleviate the aggregation-induced feature homogenization. The point-wise scaling factor helps the model to achieve comparable adjustment capacity as full-precision linear layers. Therefore, although XNOR suffers from feature homogenization at the beginning of the training process, it can alleviate this problem with the progress of training and achieve acceptable performance, as shown in Figure 7.

D   COMPARISON WITH OTHER EFFICIENT LEARNING METHODS

We compare our computation speedup and storage savings with several recently proposed methods to accelerate learning on point clouds. Note that the comparison is for reference only; tests are conducted on different hardwares, and for different tasks. Hence, direct comparison *cannot* give any meaningful conclusion. In Table 5, we show that BiPointNet achieves the most impressive acceleration.

Table 5: Comparison between BiPointNet and other approaches to efficient learning on point clouds. Grid-GCN (Xu et al., 2019) leverages novel data structuring strategy; RAND-LA Net (Hu et al., 2019) designs a faster sampling method; PointVoxel (Liu et al., 2019b) proposes an efficient representation. These works, albeit achieving high performance, are not as effective as our binarization method in terms of model acceleration. The asterisk indicates the vanilla version

Method	Hardware	Dataset	Base Model	Metric/Performance	Speedup
BiPointNet	ARM Cortex-A72	ModelNet4	PointNet*	OA/85.6	12.1×
BiPointNet	ARM Cortex-A53	ModelNet40	PointNet*	OA/85.6	14.7×
Grid-GCN	RTX 2080 GPU	S3DIS	PointNet	mIoU/53.21	1.62×
RandLA-Net	RTX 2080Ti GPU	S3DIS	PointNet*	mIoU/70.00	1.04×
PointVoxel	GTX 1080Ti GPU	ShapeNet	PointNet	mIoU/46.94	2.46×

E EXPERIMENTS

E.1 DATASETS

ModelNet40: ModelNet40 (Wu et al., 2015) for part segmentation. The ModelNet40 dataset is the most frequently used datasets for shape classification. ModelNet is a popular benchmark for point cloud classification. It contains 12,311 CAD models from 40 representative classes of objects.

ShapeNet Parts: ShapeNet Parts (Chang et al., 2015) for part segmentation. ShapeNet contains 16,881 shapes from 16 categories, 2,048 points are sampled from each training shape. Each shape is split into two to five parts depending on the category, making up to 50 parts in total.

S3DIS: S3DIS for semantic segmentation (Armeni et al., 2016). S3DIS includes 3D scan point clouds for 6 indoor areas including 272 rooms in total, each point belongs to one of 13 semantic categories. We follow the official code (Qi et al., 2016) for training and testing.

E.2 IMPLEMENTATION DETAILS OF BIPOINTNET

We follow the popular PyTorch implementation of PointNet and the recent geometric deep learning codebase (Fey & Lenssen, 2019) for the implementation of PointNet baselines. Our BiPointNet is built by binarizing the full-precision PointNet. All linear layers in PointNet except the first and last one are binarized to bi-linear layer, and we select Hardtanh as our activation function instead of ReLU when we binarize the activation before bi-linear layer. For part segmentation task, we follow the convention (Wu et al., 2014; Yi et al., 2016) to train a model for each of the 16 classes. We also provide our PointNet baseline under this setting.

Following previous works, we train 200 epochs, 250 epochs, 128 epochs on point cloud classification, part segmentation, semantic segmentation respectively. Adam with learning rate 0.01 is opted for all tasks. To stably train the binarized models, we use learning rate 0.001 with Adam and Cosine Annealing learning rate decay for all binarized models on all three tasks.

E.3 MORE BACKBONES

We also propose three other models: BiPointCNN, BiPointNet++, BiDGCCN, which is binarized from PointCNN (Li et al., 2018), PointNet++ (Qi et al., 2017), DGCNN (Wang et al., 2019a) respectively. This is attributed to the fact that all these variants have characteristics in common, such as linear layers for point-wise feature extraction and global pooling layers for feature aggregation. In PointNet++ and DGCNN, we keep the first layer and the last layer full precision and binarize all the other layers. In PointCNN, we keep every first layer of XConv full precision and keep the last layer of whole model full precision.

E.4 BINARIZATION METHODS

For exhaustive comparison, we implement various representative existing binarization methods for 2D vision, including BNN (Hubara et al., 2016), XNOR-Net (Rastegari et al., 2016), Bi-Real Net (Liu et al., 2018), and IR-Net (Qin et al., 2019), which are easy to be applied to the networks for 3D deep learning. All these methods are implemented according to their open source code, and the implementation of bi-linear layer for their methods refer their 3x3 convolution. We follow their

training process and hyperparameter settings as much as possible, but note that, the specific shortcut structure in Bi-Real and IR-Net is ignored since it only applies to the ResNet architecture.

E.5 INITIALIZATION

Our BiPointNet is trained from scratch (random initialization) without leveraging any pre-trained model. Among the experiments, we apply Adam as our optimization algorithm, and use the cosine annealing learning rate schedule to fully optimize the networks. To evaluate our BiPointNet on various network architectures, we mostly follow the hyper-parameter settings of their original papers (Qi et al., 2016; Li et al., 2018; Qi et al., 2017; Wang et al., 2019a).

E.6 DETAILED RESULTS OF SEGMENTATION

We present the detailed results of part segmentation on ShapeNet Part in Table 6 and semantic segmentation on S3DIS in Table 7. The detailed results further proves the conclusion of Section 4.1. EMA and LSR improve performance considerably in most of the subtasks of segmentation, and not just rely on huge improvements in a few subcategories. This further proves the effectiveness and robustness of our method.

Table 6: Detailed results of our BiPointNet for part segmentation on ShapeNet Parts.

	aggr.	mean	aero	bag	cap	car	chair	ear phone	guitar	knife	lamp	laptop	motor	mug	pistol	rocket	skate board	table
# shapes		2690	76	55	898	3758	69	787	392	1547	451	202	184	283	66	152	5271	
FP	max	84.3	83.6	79.4	92.5	76.8	90.8	70.2	91.0	85.6	81.9	95.6	64.4	93.5	80.9	54.5	70.6	81.5
FP	avg	84.0	83.4	78.5	90.8	76.3	90.0	73.1	90.8	84.3	80.8	95.5	61.7	93.8	81.6	56.2	72.2	81.8
BNN	max	54.0	35.1	48.1	65.5	26.5	55.8	57.1	48.8	62.2	48.6	90.1	23.1	68.3	57.5	31.3	43.7	66.8
BNN	ema-avg	53.0	39.8	46.5	57.5	24.1	58.2	56.2	44.0	50.0	53.0	81.0	16.9	48.8	36.3	25.7	43.7	63.3
BNN	ema-max	47.3	37.9	46.2	44.6	24.1	61.3	38.2	33.5	42.6	50.8	48.6	16.9	49.0	25.2	26.8	43.7	50.30
LSR	max	58.7	41.5	46.2	80.2	39.2	75.3	46.0	47.8	75.5	50.0	93.8	25.4	51.0	60.2	36.2	43.7	61.4
Ours	ema-avg	80.3	79.3	**71.9**	85.5	66.1	87.7	65.6	84.1	82.8	**76.0**	94.8	42.7	**91.8**	75.9	47.2	**59.1**	**79.7**
Ours	ema-max	**80.6**	**79.5**	69.7	**86.1**	**67.4**	**88.6**	**68.5**	**87.4**	**83.0**	74.9	**95.1**	**44.8**	91.6	**76.3**	**47.7**	56.9	79.5

Table 7: Detailed results of our BiPointNet for semantic segmentation on S3DIS.

method	aggr	overall mIoU	overall acc.	area1 (mIoU/acc.)	area2 (mIoU/acc.)	area3 (mIoU/acc.)	area4 (mIoU/acc.)	area5 (mIoU/acc.)	area6 (mIoU/acc.)	ceiling IoU	floor IoU	wall IoU	beam IoU	column IoU	window IoU	door IoU	table IoU	chair IoU	sofa IoU	bookcase IoU	board IoU	clutter IoU
FP	max	54.4	83.5	61.7/86.2	38.0/76.8	62.4/88.0	45.0/82.4	45.3/83.3	70.0/89.2	91.1	93.8	72.8	50.3	34.6	52.0	58.0	55.8	51.3	14.5	44.4	43.4	45.2
FP	avg	51.5	81.5	59.9/84.6	35.4/72.4	61.2/87.2	43.8/81.2	42.0/81.2	68.2/88.3	90.1	89.1	71.7	46.1	33.7	53.5	53.8	53.8	47.8	9.4	40.4	38.7	41.8
BNN	max	9.5	45.0	9.6/44.0	9.8/50.5	8.3/41.9	9.3/42.5	9.5/45.8	9.8/41.6	45.5	40.6	28.1	0	0	0	0	0	7.7	0	0	0	2.1
BNN	ema-avg	9.9	46.8	7.6/36.6	11.2/51.2	7.1/36.5	9.8/46.0	11.4/54.8	8.6/41.6	51.5	35.1	32.1	0	0	0	0.6	9.3	0	0	0	0	0.6
BNN	ema-max	8.5	47.2	7.7/44.0	10.1/54.4	7.1/46.8	7.8/39.7	7.6/49.2	7.2/45.3	50.8	43.5	15.9	0	0	0	0	0	0	0	0	0	0
LSR	max	2.0	25.4	2.0/26.0	2.1/27.0	2.0/25.7	1.8/22.8	2.0/25.8	1.9/24.5	25.4	0	0	0	0	0	0	0	0	0	0	0	0
Ours	ema-avg	40.9	74.9	47.1/75.8	29.1/68.3	48.0/79.9	34.2/73.2	34.7/76.1	53.3/79.8	84.6	84.6	60.5	32.0	19.0	39.6	43.0	43.5	39.2	5.8	30.5	18.5	31.3
Ours	ema-max	**44.3**	**76.7**	**50.9/78.3**	**31.0/70.3**	**53.4/82.4**	**36.6/73.9**	**36.9/77.6**	**57.9/82.3**	**85.1**	**86.1**	**62.6**	**34.5**	**23.8**	**43.0**	**48.0**	**45.7**	**40.6**	**9.6**	**36.9**	**26.2**	**33.9**