DARA: Dynamics-Aware Reward Augmentation in Offline Reinforcement Learning

Abstract

Offline reinforcement learning algorithms promise to be applicable in settings where a fixed dataset is available and no new experiment can be acquired. However, such formulation is inevitably offline-data-hungry and, in practice, collecting a large offline dataset for one specific task over one specific environment is also costly and laborious. In this paper, we thus 1) formulate the offline dynamics adaptation by using (source) offline data collected from another dynamics to relax the requirement for the extensive (target) offline data, 2) characterize the dynamics shift problem in which prior offline methods do not scale well, and 3) derive a simple dynamics-aware reward augmentation (DARA) framework from both model-free and model-based offline settings. Specifically, DARA emphasizes learning from those source transition pairs that are adaptive for the target environment and mitigates the offline dynamics shift by characterizing state-action-next-state pairs instead of the typical state-action distribution sketched by prior offline RL methods. The experimental evaluation demonstrates that DARA, by augmenting rewards in the source offline dataset, can acquire an adaptive policy for the target environment and yet significantly reduce the requirement of target offline data. With only modest amounts of target offline data, our performance consistently outperforms the prior offline RL methods in both simulated and real-world tasks.

1 Introduction

Offline reinforcement learning (RL) (Levine et al., 2020; Lange et al., 2012), the task of learning from the previously collected dataset, holds the promise of acquiring policies without any costly active interaction required in the standard online RL paradigm. However, we note that although the active trail-and-error (online exploration) is eliminated, the performance of offline RL method heavily relies on the amount of offline data that is used for training. As shown in Figure 1, the performance deteriorates dramatically as the amount of offline data decreases. A natural question therefore arises: can we reduce the amount of the (target) offline data without significantly affecting the final performance for the target task?

Figure 1: Solid and dashed lines denote offline Medium-Replay and Medium-Expert data in D4RL (Walker2d) resp.

Bringing the idea from the transfer learning (Pan & Yang, 2010), we assume that we have access to another (source) offline dataset, hoping that we can leverage this dataset to compensate for the performance degradation caused by the reduced (target) offline dataset. In the offline setting, previous work (Siegel et al., 2020; Chebotar et al., 2021) has characterized the reward (goal) difference between the source and target, relying on the "conflicting" or multi-goal offline dataset (Fu et al., 2020), while we focus on the relatively unexplored transition dynamics difference between the source dataset and the target environment. Meanwhile, we believe that this dynamics shift is not arbitrary in reality: in healthcare treatment, offline data for a particular patient is often limited, whereas we can obtain diagnostic data from other patients with the same case (same reward/goal) and there often exist individual differences between patients (source dataset with different transition dynamics). Careful treatment with respect to the individual differences is thus a crucial requirement.

Given source offline data, the main challenge is to cope with the transition dynamics difference, *i.e.*, strictly tracking the state-action supported by the source offline data can not guarantee that the same

transition (state-action-next-state) can be achieved in the target environment. However, in the offline setting, such dynamics shift is not explicitly characterized by the previous offline RL methods, where they typically attribute the difficulty of learning from offline data to the state-action distribution shift (Chen & Jiang, 2019; Liu et al., 2018). The corresponding algorithms (Fujimoto et al., 2019; Abdolmaleki et al., 2018; Yu et al., 2020) that model the support of state-action distribution induced by the learned policy, will inevitably suffer from the transfer problem where dynamics shift happens.

Motivated by the (approximate) equivalence[1] between the dynamics change and the rewards modification (Kumar et al., 2020b; Eysenbach & Levine, 2019; Eysenbach et al., 2021), we propose to modify rewards in the source offline data to compensate for the dynamics shift. Specifically, we outline state-action-next-state: besides characterizing the state-action distribution shift, we additionally penalize the agent with a dynamics-aware reward modification. This modification aims to discourage the learning from these source offline transitions (next-state) that are hard to be achieved in the target environment. Unlike the concurrent work (Ball et al., 2021; Mitchell et al., 2021) paying attention to the offline domain generalization, we explicitly focus on the offline domain (dynamics) adaptation.

Our principal contribution in this work is the characterization of the dynamics shift in offline RL and the derivation of dynamics-aware reward augmentation (DARA) framework built on prior model-free and model-based formulations. DARA is simple and general, can accommodate various offline RL methods, and can be implemented in just a few lines of code on top of dataloader at training. In our offline dynamics adaptation setting, we also release a dataset, including the Gym-MuJoCo tasks (Walker2d, Hopper and HalfCheetah), with dynamics (mass, joint) shift compared to D4RL, and a 12-DoF quadruped robot in both simulator and real-world. With only modest amounts of target offline data, we show that DARA-based offline methods can acquire an adaptive policy for the target tasks and achieve better performance compared to baselines in both simulated and real-world tasks.

2 PRELIMINARIES

We study RL in the framework of Markov decision processes (MDPs) specified by the tuple $M := (\mathcal{S}, \mathcal{A}, r, T, \rho_0, \gamma)$, where $\mathcal{S}$ and $\mathcal{A}$ denote the state and action spaces, $r(\mathbf{s}, \mathbf{a}) \in [-R_{max}, R_{max}]$ is the reward function, $T(\mathbf{s}'|\mathbf{s}, \mathbf{a})$ is the transition dynamics, $\rho_0(\mathbf{s})$ is the initial state distribution, and γ is the discount factor. The goal in RL is to optimize a policy $\pi(\mathbf{a}|\mathbf{s})$ that maximizes the expected discounted return $\eta_M(\pi) := \mathbb{E}_{\tau \sim p_M^\pi(\tau)} [\sum_{t=0}^\infty \gamma^t r(\mathbf{s}_t, \mathbf{a}_t)]$, where $\tau := (\mathbf{s}_0, \mathbf{a}_0, \mathbf{s}_1, \mathbf{a}_1, ...)$. We also define Q-values $Q(\mathbf{s}, \mathbf{a}) := \mathbb{E}_{\tau \sim p_M^\pi(\tau)} [\sum_{t=0}^\infty \gamma^t r(\mathbf{s}_t, \mathbf{a}_t)|\mathbf{s}_0 = \mathbf{s}, \mathbf{a}_0 = \mathbf{a}]$, V-values $V(\mathbf{s}) := \mathbb{E}_{\mathbf{a} \sim \pi(\mathbf{a}|\mathbf{s})} [Q(\mathbf{s}, \mathbf{a})]$, and the (unnormalized) state visitation distribution $d_M^\pi(\mathbf{s}) := \sum_{t=0}^\infty \gamma^t P(\mathbf{s}|\pi, M, t)$, where $P(\mathbf{s}|\pi, M, t)$ denotes the probability of reach state $\mathbf{s}$ at time t by running π in M.

In the *offline RL* problem, we are provided with a static dataset $\mathcal{D} := \{(\mathbf{s}, \mathbf{a}, r, \mathbf{s}')\}$, which consists of transition tuples from trajectories collected by running one or more behavioral policies, denoted by π_b, on MDP M. With a slight abuse of notation, we write $\mathcal{D} = \{(\mathbf{s}, \mathbf{a}, r, \mathbf{s}') \sim d_\mathcal{D}(\mathbf{s})\pi_b(\mathbf{a}|\mathbf{s})r(\mathbf{s}, \mathbf{a})T(\mathbf{s}'|\mathbf{s}, \mathbf{a})\}$, where the $d_\mathcal{D}(\mathbf{s})$ denotes state-marginal distribution in $\mathcal{D}$. In the offline setting, the goal is typically to learn the best possible policy using the fixed offline dataset.

Model-free RL algorithms based on dynamic programming typically perform policy iteration to find the optimal policy. Such methods iteratively conduct 1) policy improvement with $\mathcal{G}_M Q := \arg\max_\pi \mathbb{E}_{\mathbf{s} \sim d_M^\pi(\mathbf{s}), \mathbf{a} \sim \pi(\mathbf{a}|\mathbf{s})} [Q(\mathbf{s}, \mathbf{a})]$ and 2) policy evaluation by iterating the Bellman equation $Q(\mathbf{s}, \mathbf{a}) = \mathcal{B}_M^\pi Q(\mathbf{s}, \mathbf{a}) := r(\mathbf{s}, \mathbf{a}) + \gamma \mathbb{E}_{\mathbf{s}' \sim T(\mathbf{s}'|\mathbf{s}, \mathbf{a}), \mathbf{a}' \sim \pi(\mathbf{a}'|\mathbf{s}')} [Q(\mathbf{s}', \mathbf{a}')]$ over $d_M^\pi(\mathbf{s})\pi(\mathbf{a}|\mathbf{s})$. Given off-policy data $\mathcal{D}$, we resort to 1) improvement with $\mathcal{G}_\mathcal{D} Q := \arg\max_\pi \mathbb{E}_{\mathbf{s} \sim d_\mathcal{D}(\mathbf{s}), \mathbf{a} \sim \pi(\mathbf{a}|\mathbf{s})} [Q(\mathbf{s}, \mathbf{a})]$ and 2) evaluation by iterating $Q(\mathbf{s}, \mathbf{a}) = \mathcal{B}_\mathcal{D}^\pi Q(\mathbf{s}, \mathbf{a}) := r(\mathbf{s}, \mathbf{a}) + \gamma \mathbb{E}_{\mathbf{s}' \sim T(\mathbf{s}'|\mathbf{s}, \mathbf{a}), \mathbf{a}' \sim \pi(\mathbf{a}'|\mathbf{s}')} [Q(\mathbf{s}', \mathbf{a}')]$ over all $(\mathbf{s}, \mathbf{a})$ in $\mathcal{D}$. Specifically, given any initial Q^0, it iterates[2]

$$\text{Policy improvement: } \pi^{k+1} = \mathcal{G}_\mathcal{D} Q^k, \qquad \text{Policy evaluation: } Q^{k+1} = \mathcal{B}_\mathcal{D}^{\pi^{k+1}} Q^k. \qquad (1)$$

Model-free offline RL based on the above iteration suffers from the state-action distribution shift, *i.e.*, policy evaluation $\mathcal{B}_\mathcal{D}^{\pi^k} Q^{k-1}$ may encounter unfamiliar state action regime that is not covered

---

[1] The equivalence hints that, by modifying rewards, one can train a policy in one environment and make the learned policy to be suitable for another environment (the two environments have different transition dynamics).

[2] For parametric Q-function, we actually perform policy evaluation by taking $\mathcal{B}_\mathcal{D}^{\pi^{k+1}} Q^k$ as a target and minimizing the (squared) temporal difference error $Q^{k+1} \leftarrow \arg\min_Q \mathbb{E}_{(\mathbf{s}, \mathbf{a}) \sim \mathcal{D}} [(\mathcal{B}_\mathcal{D}^{\pi^{k+1}} Q^k(\mathbf{s}, \mathbf{a}) - Q(\mathbf{s}, \mathbf{a}))^2]$.

by the fixed offline dataset $\mathcal{D}$, causing erroneous estimation of Q^k. Policy improvement $\mathcal{G}_{\mathcal{D}} Q^k$ further exaggerates such error, biasing policy π^{k+1} towards out-of-distribution (OOD) actions with erroneously high Q-values. To address this distribution shift, prior works 1) explicitly constrain policy to be close to the behavior policy (Fujimoto et al., 2019; Kumar et al., 2019; Wu et al., 2019; Ghasemipour et al., 2021), introducing penalty $\alpha D(\pi(\mathbf{a}|\mathbf{s}), \pi_b(\mathbf{a}|\mathbf{s}))$ into $\mathcal{G}_{\mathcal{D}}$ or $\mathcal{B}_{\mathcal{D}}^{\pi}$ in Equation 1:

$$\mathcal{G}_{\mathcal{D}} Q = \arg\max_{\pi} \mathbb{E}_{\mathbf{s} \sim d_{\mathcal{D}}(\mathbf{s}), \mathbf{a} \sim \pi(\mathbf{a}|\mathbf{s})} \left[Q(\mathbf{s}, \mathbf{a}) - \alpha D(\pi(\mathbf{a}|\mathbf{s}), \pi_b(\mathbf{a}|\mathbf{s})) \right],$$

$$\mathcal{B}_{\mathcal{D}}^{\pi} Q(\mathbf{s}, \mathbf{a}) = r(\mathbf{s}, \mathbf{a}) + \gamma \mathbb{E}_{\mathbf{s}' \sim T(\mathbf{s}'|\mathbf{s}, \mathbf{a}), \mathbf{a}' \sim \pi(\mathbf{a}'|\mathbf{s}')} \left[Q(\mathbf{s}', \mathbf{a}') - \alpha D(\pi(\mathbf{a}'|\mathbf{s}'), \pi_b(\mathbf{a}'|\mathbf{s}')) \right], \tag{2}$$

where D is a divergence function between distributions over actions (*e.g.*, MMD or KL divergence), or 2) train pessimistic value functions (Kumar et al., 2020a; Yu et al., 2021; Xu et al., 2021), penalizing Q-values at states in the offline dataset $\mathcal{D}$ for actions generated by the current policy π:

$$Q = \arg\min_{Q} \mathbb{E}_{\mathbf{s} \sim d_{\mathcal{D}}(\mathbf{s}), \mathbf{a} \sim \pi(\mathbf{a}|\mathbf{s})} \left[Q(\mathbf{s}, \mathbf{a}) \right], \quad \text{s.t. } Q = \mathcal{B}_{\mathcal{D}}^{\pi} Q. \tag{3}$$

Model-based RL algorithms iteratively 1) model the transition dynamics $T(\mathbf{s}'|\mathbf{s}, \mathbf{a})$, using the data collected in M: $\max_{\hat{T}} \mathbb{E}_{\mathbf{s}, \mathbf{a}, \mathbf{s}' \sim d_M^{\pi}(\mathbf{s})\pi(\mathbf{a}|\mathbf{s})T(\mathbf{s}'|\mathbf{s}, \mathbf{a})}[\log \hat{T}(\mathbf{s}'|\mathbf{s}, \mathbf{a})]$, and 2) infer a policy π from the modeled $\hat{M} = (\mathcal{S}, \mathcal{A}, r, \hat{T}, \rho_0, \gamma)$, where we assume that r and ρ_0 are known, maximizing $\eta_{\hat{M}}(\pi)$ with a planner or the Dyna-style algorithms (Sutton, 1990). In this paper, we focus on the latter.

Model-based offline RL algorithms similarly suffer from OOD state-action (Kidambi et al., 2020; Cang et al., 2021) if we directly apply policy iteration over $\hat{T} := \max_{\hat{T}} \mathbb{E}_{\mathbf{s}, \mathbf{a}, \mathbf{s}' \sim \mathcal{D}}[\log \hat{T}(\mathbf{s}'|\mathbf{s}, \mathbf{a})]$. Like the conservative estimation approach described in Equation 3, recent conservative model-based offline RL methods provide the policy with a penalty for visiting states under the estimated $\hat{T}$ where $\hat{T}$ is likely to be incorrect. Taking $u(\mathbf{s}, \mathbf{a})$ as the oracle uncertainty (Yu et al., 2020) that provides a consistent estimate of the accuracy of model $\hat{T}$ at $(\mathbf{s}, \mathbf{a})$, we can modify the reward function to obtain a conservative MDP: $\hat{M}_c = (\mathcal{S}, \mathcal{A}, r - \alpha u, \hat{T}, \rho_0, \gamma)$, then learn a policy π by maximizing $\eta_{\hat{M}_c}(\pi)$.

3 PROBLEM FORMULATION

In standard offline RL problem, the static offline dataset $\mathcal{D}$ consists of samples $\{(\mathbf{s}, \mathbf{a}, r, \mathbf{s}') \sim d_{\mathcal{D}}(\mathbf{s})\pi_b(\mathbf{a}|\mathbf{s})r(\mathbf{s}, \mathbf{a})T(\mathbf{s}'|\mathbf{s}, \mathbf{a})\}$. Although offline RL methods learn policy for the target MDP $M := (\mathcal{S}, \mathcal{A}, r, T, \rho_0, \gamma)$ without (costly) online data, as we shown in Figure 1, it requires a fair amount of (target) offline data $\mathcal{D}$ collected on M. Suppose we have another (source) offline dataset $\mathcal{D}'$, consisting of samples $\{(\mathbf{s}, \mathbf{a}, r, \mathbf{s}') \sim d_{\mathcal{D}'}(\mathbf{s})\pi_{b'}(\mathbf{a}|\mathbf{s})r(\mathbf{s}, \mathbf{a})T'(\mathbf{s}'|\mathbf{s}, \mathbf{a})\}$ collected by the behavior policy $\pi_{b'}$ on MDP $M' := (\mathcal{S}, \mathcal{A}, r, T', \rho_0, \gamma)$, then we hope the transfer of knowledge between offline dataset $\{\mathcal{D}' \cup \mathcal{D}\}$ can reduce the data requirements on $\mathcal{D}$ for learning policy for the target M.

3.1 DYNAMICS SHIFT IN OFFLINE RL

Although offline RL methods in Section 2 have incorporate the state-action distribution constrained backups (policy constraints or conservative estimation), they also fail to learn an adaptive policy for the target MDP M with the mixed datasets $\{\mathcal{D}' \cup \mathcal{D}\}$, as we show in Figure 4 (Appendix). We attribute this failure to the dynamics shift (Definition 2) between $\mathcal{D}'$ and M in this adaptation setting.

Definition 1 *(Empirical MDP) An empirical MDP estimated from $\mathcal{D}$ is $\hat{M} := (\mathcal{S}, \mathcal{A}, r, \hat{T}, \rho_0, \gamma)$ where $\hat{T} = \max_{\hat{T}} \mathbb{E}_{\mathbf{s}, \mathbf{a}, \mathbf{s}' \sim \mathcal{D}} \left[\log \hat{T}(\mathbf{s}'|\mathbf{s}, \mathbf{a}) \right]$ and $\hat{T}(\mathbf{s}'|\mathbf{s}, \mathbf{a}) = 0$ for all $(\mathbf{s}, \mathbf{a}, \mathbf{s}')$ not in dataset $\mathcal{D}$.*

Definition 2 *(Dynamics shift) Let $\hat{M} := (\mathcal{S}, \mathcal{A}, r, \hat{T}, \rho_0, \gamma)$ be the empirical MDP estimated from $\mathcal{D}$. To evaluate a policy π for $M := (\mathcal{S}, \mathcal{A}, r, T, \rho_0, \gamma)$ with offline dataset $\mathcal{D}$, we say that the dynamics shift (between $\mathcal{D}$ and M) in offline RL happens if there exists at least one transition pair $(\mathbf{s}, \mathbf{a}, \mathbf{s}') \in \{(\mathbf{s}, \mathbf{a}, \mathbf{s}') : d_{\hat{M}}^{\pi}(\mathbf{s})\pi(\mathbf{a}|\mathbf{s})\hat{T}(\mathbf{s}'|\mathbf{s}, \mathbf{a}) > 0\}$ such that $\hat{T}(\mathbf{s}'|\mathbf{s}, \mathbf{a}) \neq T(\mathbf{s}'|\mathbf{s}, \mathbf{a})$.*

In practice, for a stochastic M and any finite offline data $\mathcal{D}$ collected in M, there always exists the dynamics shift. The main concern is that finite samples are always not sufficient to exactly model stochastic dynamics. Following Fujimoto et al. (2019), we thus assume both MDPs M and M' are deterministic, which means the empirical $\hat{M}$ and $\hat{M}'$ are both also deterministic. More importantly, such assumption enables us to explicitly characterize the dynamics shift under finite offline samples.

Lemma 1 *Under deterministic transition dynamics, there is no dynamics shift between $\mathcal{D}$ and M.*

For offline RL tasks, prior methods generally apply $\mathcal{B}_{\mathcal{D}}^{\pi}Q$ along with the state-action distribution correction (Equations 2 and 3), which overlooks the potential dynamics shift between the (source) offline dataset and the target MDP (*e.g.*, $\mathcal{D}' \to M$). As a result, these methods do not scale well to the setting in which dynamics shift happens, *e.g.*, learning an adaptive policy for M with (source) $\mathcal{D}'$.

3.2 DYNAMICS SHIFT IN MODEL-FREE AND MODEL-BASED OFFLINE FORMULATIONS

From the **model-free** (policy iteration) view, an exact policy evaluation on M is characterized by iterating $Q(\mathbf{s}, \mathbf{a}) = \mathcal{B}_{M}^{\pi}Q(\mathbf{s}, \mathbf{a})$ for all $(\mathbf{s}, \mathbf{a})$ such that $d_{M}^{\pi}(\mathbf{s})\pi(\mathbf{a}|\mathbf{s}) > 0$. Thus, to formalize the policy evaluation with offline $\mathcal{D}$ or $\mathcal{D}'$ (for an adaptive π on target M), we require that Bellman operator $\mathcal{B}_{\mathcal{D}}^{\pi}Q(\mathbf{s}, \mathbf{a})$ or $\mathcal{B}_{\mathcal{D}'}^{\pi}Q(\mathbf{s}, \mathbf{a})$ approximates the oracle $\mathcal{B}_{M}^{\pi}Q(\mathbf{s}, \mathbf{a})$ for all $(\mathbf{s}, \mathbf{a})$ in S_{π} or S_{π}', where S_{π} and S_{π}' denote the sets $\{(\mathbf{s}, \mathbf{a}) : d_{\mathcal{D}}(\mathbf{s})\pi(\mathbf{a}|\mathbf{s}) > 0\}$ and $\{(\mathbf{s}, \mathbf{a}) : d_{\mathcal{D}'}(\mathbf{s})\pi(\mathbf{a}|\mathbf{s}) > 0\}$ respectively.

1) To evaluate a policy π for M with $\mathcal{D}$ (*i.e.*, calling the Bellman operator $\mathcal{B}_{\mathcal{D}}^{\pi}$), notable model-free offline method BCQ (Fujimoto et al., 2019) translates the requirement of $\mathcal{B}_{\mathcal{D}}^{\pi} = \mathcal{B}_{M}^{\pi}$ into the requirement of $\hat{T}(\mathbf{s}'|\mathbf{s}, \mathbf{a}) = T(\mathbf{s}'|\mathbf{s}, \mathbf{a})$. Note that under deterministic environments, we have the property that for all $(\mathbf{s}, \mathbf{a}, \mathbf{s}')$ in offline data $\mathcal{D}$, $\hat{T}(\mathbf{s}'|\mathbf{s}, \mathbf{a}) = T(\mathbf{s}'|\mathbf{s}, \mathbf{a})$ (Lemma 1). As a result, such property permits BCQ to evaluate a policy π by calling $\mathcal{B}_{\mathcal{D}}^{\pi}$, replacing the oracle $\mathcal{B}_{M}^{\pi}$, meanwhile constraining S_{π} to be a subset of the support of $d_{\mathcal{D}}(\mathbf{s})\pi_{b}(\mathbf{a}|\mathbf{s})$. This means a policy π which only traverses transitions contained in (target) offline data $\mathcal{D}$, can be evaluated on $\mathcal{D}$ without error.

2) To evaluate a policy π for M with $\mathcal{D}'$ (*i.e.*, calling the Bellman operator $\mathcal{B}_{\mathcal{D}'}^{\pi}$), we have lemma 2:

Lemma 2 *Dynamics shift produces that $\mathcal{B}_{\mathcal{D}'}^{\pi}Q(\mathbf{s}, \mathbf{a}) \neq \mathcal{B}_{M}^{\pi}Q(\mathbf{s}, \mathbf{a})$ for some $(\mathbf{s}, \mathbf{a})$ in S_{π}'.*

With the offline data $\mathcal{D}'$, lemma 2 suggests that the above requirement $\mathcal{B}_{\mathcal{D}'}^{\pi} = \mathcal{B}_{M}^{\pi}$ becomes infeasible, which limits the practical applicability of prior offline RL methods under the dynamics shift. To be specific, characterizing an adaptive policy for target MDP M with $\mathcal{D}'$ moves beyond the reach of the off-policy evaluation based on iterating $Q = \mathcal{B}_{\mathcal{D}'}^{\pi}Q$ (Equations 2 and 3). Such iteration may cause the evaluated Q (or learned policy π) overfits to $\hat{T}'$ and struggle to adapt to the target T. To overcome the dynamics shift, we would like to resort an additional compensation $\Delta_{\hat{T}', T}$ such that

$$\mathcal{B}_{\mathcal{D}'}^{\pi}Q(\mathbf{s}, \mathbf{a}) + \Delta_{\hat{T}', T}(\mathbf{s}, \mathbf{a}) = \mathcal{B}_{M}^{\pi}Q(\mathbf{s}, \mathbf{a}) \tag{4}$$

for all $(\mathbf{s}, \mathbf{a})$ in S_{π}'. Thus, we can apply $\mathcal{B}_{\mathcal{D}'}^{\pi}Q + \Delta_{\hat{T}', T}$ to act as a substitute for the oracle $\mathcal{B}_{M}^{\pi}Q$.

From the **model-based** view, the oracle $\eta_{M}(\pi)$ (calling the Bellman operator $\mathcal{B}_{M}^{\pi}$ on the target M) and the viable $\eta_{\hat{M}'}(\pi)$ (calling $\mathcal{B}_{\hat{M}'}^{\pi}$ on the estimated $\hat{M}'$ from source $\mathcal{D}'$) have the following lemma.

Lemma 3 *Let $\mathcal{B}_{M}^{\pi}V(\mathbf{s}) = \mathbb{E}_{\mathbf{a} \sim \pi(\mathbf{a}|\mathbf{s})}\left[r(\mathbf{s}, \mathbf{a}) + \gamma\mathbb{E}_{\mathbf{s}' \sim T(\mathbf{s}'|\mathbf{s}, \mathbf{a})}[V(\mathbf{s}')]\right]$. For any π, we have:*

$$\eta_{\hat{M}'}(\pi) = \eta_{M}(\pi) + \mathbb{E}_{\mathbf{s} \sim d_{\hat{M}'}^{\pi}(\mathbf{s})}\left[\mathcal{B}_{\hat{M}'}^{\pi}V_{M}(\mathbf{s}) - \mathcal{B}_{M}^{\pi}V_{M}(\mathbf{s})\right].$$

Lemma 3 states that if we maximize $\eta_{\hat{M}'}(\pi)$ subject to $|\mathbb{E}_{\mathbf{s} \sim d_{\hat{M}'}^{\pi}(\mathbf{s})}[\mathcal{B}_{\hat{M}'}^{\pi}V_{M}(\mathbf{s}) - \mathcal{B}_{M}^{\pi}V_{M}(\mathbf{s})]| \leq \epsilon$, $\eta_{M}(\pi)$ will be improved. If $\mathcal{F}$ is a set of functions $f : \mathcal{S} \to \mathbb{R}$ that contains V_{M}, then we have

$$\left|\mathbb{E}_{\mathbf{s} \sim d_{\hat{M}'}^{\pi}(\mathbf{s})}\left[\mathcal{B}_{\hat{M}'}^{\pi}V_{M}(\mathbf{s}) - \mathcal{B}_{M}^{\pi}V_{M}(\mathbf{s})\right]\right| \leq \gamma\mathbb{E}_{\mathbf{s}, \mathbf{a} \sim d_{\hat{M}'}^{\pi}(\mathbf{s})\pi(\mathbf{a}|\mathbf{s})}\left[d_{\mathcal{F}}(\hat{T}'(\mathbf{s}'|\mathbf{s}, \mathbf{a}), T(\mathbf{s}'|\mathbf{s}, \mathbf{a}))\right], \tag{5}$$

where $d_{\mathcal{F}}(\hat{T}'(\mathbf{s}'|\mathbf{s}, \mathbf{a}), T(\mathbf{s}'|\mathbf{s}, \mathbf{a})) = \sup_{f \in \mathcal{F}}\left|\mathbb{E}_{\mathbf{s}' \sim \hat{T}'(\mathbf{s}'|\mathbf{s}, \mathbf{a})}[f(\mathbf{s}')] - \mathbb{E}_{\mathbf{s}' \sim T(\mathbf{s}'|\mathbf{s}, \mathbf{a})}[f(\mathbf{s}')]\right|$, which is the integral probability metric (IPM). Note that if we directly follow the *admissible error* assumption in MOPO (Yu et al., 2020) *i.e.*, assuming $d_{\mathcal{F}}(\hat{T}'(\mathbf{s}'|\mathbf{s}, \mathbf{a}), T(\mathbf{s}'|\mathbf{s}, \mathbf{a})) \leq u(\mathbf{s}, \mathbf{a})$ for all $(\mathbf{s}, \mathbf{a})$, this would be too restrictive: given that $\hat{T}'$ is estimated from the source offline samples collected under T', not the target T, thus such error would not decrease as the source data increases. Further, we find

$$d_{\mathcal{F}}(\hat{T}'(\mathbf{s}'|\mathbf{s}, \mathbf{a}), T(\mathbf{s}'|\mathbf{s}, \mathbf{a})) \leq d_{\mathcal{F}}(\hat{T}'(\mathbf{s}'|\mathbf{s}, \mathbf{a}), \hat{T}(\mathbf{s}'|\mathbf{s}, \mathbf{a})) + d_{\mathcal{F}}(\hat{T}(\mathbf{s}'|\mathbf{s}, \mathbf{a}), T(\mathbf{s}'|\mathbf{s}, \mathbf{a})). \tag{6}$$

Thus, we can bound the $d_{\mathcal{F}}(\hat{T}', T)$ term with the admissible error assumption over $d_{\mathcal{F}}(\hat{T}, T)$, as in MOPO, and the auxiliary constraints $d_{\mathcal{F}}(\hat{T}', \hat{T})$. See next section for the detailed implementation.

In summary, we show that both prior offline model-free and model-based formulations suffer from the dynamics shift, which also suggests we to learn a modification (Δ or $d_{\mathcal{F}}$) to eliminate this shift.

4 DYNAMICS-AWARE REWARD AUGMENTATION

In this section, we propose the dynamics-aware reward augmentation (DARA), a simple data augmentation procedure based on prior (model-free and model-based) offline RL methods. We first provide an overview of our offline reward augmentation motivated by the compensation $\Delta_{\hat{T}',T}$ in Equation 4 and the auxiliary constraints $d_{\mathcal{F}}(\hat{T}',\hat{T})$ in Equation 6, and then describe its theoretical derivation in both model-free and model-based formulations. With the (reduced) target offline data $\mathcal{D}$ and the source offline data $\mathcal{D}'$, we summarize the overall DARA framework in Algorithm 1.

Algorithm 1 Framework for Dynamics-Aware Reward Augmentation (DARA)

Require: Target offline data $\mathcal{D}$ (reduced) and source offline data $\mathcal{D}'$

1: Learn two classifiers $q_{\mathrm{sas}}(\cdot|\mathbf{s}_t,\mathbf{a}_t,\mathbf{s}_{t+1})$ and $q_{\mathrm{sa}}(\cdot|\mathbf{s}_t,\mathbf{a}_t)$ with $\mathcal{D}$ and $\mathcal{D}'$. (See Appendix A.1.3)
2: Set dynamics-aware $\Delta r(\mathbf{s}_t,\mathbf{a}_t,\mathbf{s}_{t+1}) = \log \frac{q_{\mathrm{sas}}(\mathrm{source}|\mathbf{s}_t,\mathbf{a}_t,\mathbf{s}_{t+1})}{q_{\mathrm{sas}}(\mathrm{target}|\mathbf{s}_t,\mathbf{a}_t,\mathbf{s}_{t+1})} - \log \frac{q_{\mathrm{sa}}(\mathrm{source}|\mathbf{s}_t,\mathbf{a}_t)}{q_{\mathrm{sa}}(\mathrm{target}|\mathbf{s}_t,\mathbf{a}_t)}$.
3: Modify rewards for all $(\mathbf{s}_t,\mathbf{a}_t,r_t,\mathbf{s}_{t+1})$ in $\mathcal{D}'$: $r_t \leftarrow r_t - \eta\Delta r$.
4: Learn policy with $\{\mathcal{D} \cup \mathcal{D}'\}$ using prior model-free or model-based offline RL algorithms.

4.1 DYNAMICS-AWARE REWARD AUGMENTATION IN MODEL-FREE FORMULATION

Motivated by the well established connection of RL and probabilistic inference (Levine, 2018), we first cast the model-free RL problem as that of inference in a particular probabilistic model. Specifically, we introduce the binary random variable $\mathcal{O}$ that denotes whether the trajectory $\tau := (\mathbf{s}_0,\mathbf{a}_0,\mathbf{s}_1,...)$ is optimal ($\mathcal{O} = 1$) or not ($\mathcal{O} = 0$). The likelihood of a trajectory can then be modeled as $p(\mathcal{O} = 1|\tau) = \exp\left(\sum_t r_t/\eta\right)$, where $r_t := r(\mathbf{s}_t,\mathbf{a}_t)$ and $\eta > 0$ is a temperature parameter.

(Reward Augmentation with Explicit Policy/Value Constraints) We now introduce a variational distribution $p_{\hat{M}'}^{\pi}(\tau) = p(\mathbf{s}_0)\prod_{t=1}\hat{T}'(\mathbf{s}_{t+1}|\mathbf{s}_t,\mathbf{a}_t)\pi(\mathbf{a}_t|\mathbf{s}_t)$ to approximate the posterior $p_M^{\pi}(\tau|\mathcal{O} = 1)$, which leads to the evidence lower bound of $\log p_M^{\pi}(\mathcal{O} = 1)$:

$$\log p_M^{\pi}(\mathcal{O} = 1) = \log \mathbb{E}_{\tau \sim p_M^{\pi}(\tau)}\left[p(\mathcal{O} = 1|\tau)\right] \geq \mathbb{E}_{\tau \sim p_{\hat{M}'}^{\pi}(\tau)}\left[\log p(\mathcal{O} = 1|\tau) + \log \frac{p_M^{\pi}(\tau)}{p_{\hat{M}'}^{\pi}(\tau)}\right]$$

$$= \mathbb{E}_{\tau \sim p_{\hat{M}'}^{\pi}(\tau)}\left[\sum_t \left(r_t/\eta - \log \frac{\hat{T}'(\mathbf{s}_{t+1}|\mathbf{s}_t,\mathbf{a}_t)}{T(\mathbf{s}_{t+1}|\mathbf{s}_t,\mathbf{a}_t)}\right)\right]. \tag{7}$$

Since we are interested in infinite horizon problems, we introduce the discount factor γ and take the limit $\lim_{H\to\infty}$. Thus, the RL problem on the MDP M, cast as the inference problem $\arg\max_{\pi}\log p_M^{\pi}(\mathcal{O} = 1)$, can be stated as a maximum of the lower bound $\mathbb{E}_{\tau \sim p_{\hat{M}'}^{\pi}(\tau)}\left[\sum_{t=0}^{\infty}\gamma^t\left(r_t - \eta\log\frac{\hat{T}'(\mathbf{s}_{t+1}|\mathbf{s}_t,\mathbf{a}_t)}{T(\mathbf{s}_{t+1}|\mathbf{s}_t,\mathbf{a}_t)}\right)\right]$. This is equivalent to an RL problem on $\hat{M}'$ with the augmented reward $r \leftarrow r(\mathbf{s},\mathbf{a}) - \eta\log\frac{\hat{T}'(\mathbf{s}'|\mathbf{s},\mathbf{a})}{T(\mathbf{s}'|\mathbf{s},\mathbf{a})}$. Intuitively, the $-\eta\log\frac{\hat{T}'(\mathbf{s}'|\mathbf{s},\mathbf{a})}{T(\mathbf{s}'|\mathbf{s},\mathbf{a})}$ term discourages transitions (state-action-next-state) in $\mathcal{D}'$ that have low transition probability in the target M. In the model-free offline setting, we can add the explicit policy or Q-value constraints (Equations 2 and 3) to mitigate the OOD state-actions. Thus, such formulation allows the oracle $\mathcal{B}_M^{\pi}$ to be re-expressed by $\mathcal{B}_{\mathcal{D}'}^{\pi}$ and the modification $\log\frac{\hat{T}'}{T}$, which makes the motivation in Equation 4 practical.

(Reward Augmentation with Implicit Policy Constraints) If we introduce the variational distribution $p_{\hat{M}'}^{\pi'}(\tau) := p(\mathbf{s}_0)\prod_{t=1}\hat{T}'(\mathbf{s}_{t+1}|\mathbf{s}_t,\mathbf{a}_t)\pi'(\mathbf{a}_t|\mathbf{s}_t)$, we can recover the weighted-regression-style (Wang et al., 2020; Peng et al., 2019; Abdolmaleki et al., 2018; Peters et al., 2010) objective by maximizing $\mathcal{J}(\pi',\pi) := \mathbb{E}_{\tau \sim p_{\hat{M}'}^{\pi'}(\tau)}\left[\sum_{t=0}^{\infty}\gamma^t\left(r_t - \eta\log\frac{\hat{T}'(\mathbf{s}_{t+1}|\mathbf{s}_t,\mathbf{a}_t)}{T(\mathbf{s}_{t+1}|\mathbf{s}_t,\mathbf{a}_t)} - \eta\log\frac{\pi'(\mathbf{a}_t|\mathbf{s}_t)}{\pi(\mathbf{a}_t|\mathbf{s}_t)}\right)\right]$ (lower bound of $\log p_M^{\pi}(\mathcal{O} = 1)$). Following the Expectation Maximization (EM) algorithm, we can maximize $\mathcal{J}(\pi',\pi)$ by iteratively (E-step) improving $\mathcal{J}(\pi',\cdot)$ w.r.t. π' and (M-step) updating π w.r.t. π'.

(E-step) We define $\tilde{Q}(\mathbf{s},\mathbf{a},\mathbf{s}') = \mathbb{E}_{\tau \sim p_{\hat{M}'}^{\pi'}(\tau)}\left[\sum_t \gamma^t\log\frac{\hat{T}'(\mathbf{s}'|\mathbf{s},\mathbf{a})}{T(\mathbf{s}'|\mathbf{s},\mathbf{a})}|\mathbf{s}_0 = \mathbf{s},\mathbf{a}_0 = \mathbf{a},\mathbf{s}_1 = \mathbf{s}'\right]$. Then, given offline data $\mathcal{D}'$, we can rewrite $\mathcal{J}(\pi',\cdot)$ as a constrained objective (Abdolmaleki et al., 2018):

$$\max_{\pi'}\mathbb{E}_{\mathbf{s},\mathbf{a},\mathbf{s}'\sim d_{\mathcal{D}'}(\mathbf{s})\pi'(\mathbf{a}|\mathbf{s})\hat{T}'(\mathbf{s}'|\mathbf{s},\mathbf{a})}\left[Q(\mathbf{s},\mathbf{a}) - \eta\tilde{Q}(\mathbf{s},\mathbf{a},\mathbf{s}')\right], \text{ s.t. } \mathbb{E}_{\mathbf{s}\sim d_{\mathcal{D}'}(\mathbf{s})}\left[D_{\mathrm{KL}}\left(\pi'(\mathbf{a}|\mathbf{s})\|\pi(\mathbf{a}|\mathbf{s})\right)\right] \leq \epsilon.$$

When considering a fixed π, the above optimization over π' can be solved analytically (Vieillard et al., 2020; Geist et al., 2019; Peng et al., 2019). The optimal π'_* is then given by $\pi'_*(\mathbf{a}|\mathbf{s}) \propto \pi(\mathbf{a}|\mathbf{s}) \exp{(Q(\mathbf{s},\mathbf{a}))} \exp(-\eta\tilde{Q}(\mathbf{s},\mathbf{a},\hat{T}'(\mathbf{s}'|\mathbf{s})))$. As the policy evaluation in Equation 1 (Footnote-2), we estimate $Q(\mathbf{s},\mathbf{a})$ and $\tilde{Q}(\mathbf{s},\mathbf{a},\mathbf{s}')$ by minimizing the Bellman error with offline samples in $\mathcal{D}'$.

(M-step) Then, we can project π'_* onto the manifold of the parameterized π:

$$\arg\min_{\pi} \quad \mathbb{E}_{\mathbf{s}\sim d_{\mathcal{D}'}(\mathbf{s})} \left[D_{\mathrm{KL}}\left(\pi'_*(\mathbf{a}|\mathbf{s}) \| \pi(\mathbf{a}|\mathbf{s})\right) \right]$$

$$= \arg\max_{\pi} \quad \mathbb{E}_{\mathbf{s},\mathbf{a},\mathbf{s}'\sim\mathcal{D}'} \left[\log\pi(\mathbf{a}|\mathbf{s}) \exp{(Q(\mathbf{s},\mathbf{a}))} \exp\left(-\eta\tilde{Q}(\mathbf{s},\mathbf{a},\mathbf{s}')\right) \right]. \tag{8}$$

From the regression view, prior work MPO (Abdolmaleki et al., 2018) infers actions with Q-value weighted regression, progressive approach compared to behavior cloning, however, such paradigm lacks the ability to capture transition dynamics. We explicitly introduce the $\exp(-\eta\tilde{Q}(\mathbf{s},\mathbf{a},\mathbf{s}'))$ term, which as we show in experiments, is a crucial component for eliminating the dynamics shift.

Implementation: In practice, we adopt offline samples in $\mathcal{D}$ to approximate the true dynamics T of M, and introduce a pair of binary classifiers, $q_{\mathrm{sas}}(\cdot|\mathbf{s},\mathbf{a},\mathbf{s}')$ and $q_{\mathrm{sa}}(\cdot|\mathbf{s},\mathbf{a})$, to replace $\log\frac{\hat{T}'(\mathbf{s}'|\mathbf{s},\mathbf{a})}{T(\mathbf{s}'|\mathbf{s},\mathbf{a})}$ as in Eysenbach et al. (2021): $\log\frac{\hat{T}'(\mathbf{s}'|\mathbf{s},\mathbf{a})}{T(\mathbf{s}'|\mathbf{s},\mathbf{a})} = \log\frac{q_{\mathrm{sas}}(\mathrm{source}|\mathbf{s},\mathbf{a},\mathbf{s}')}{q_{\mathrm{sas}}(\mathrm{target}|\mathbf{s},\mathbf{a},\mathbf{s}')} - \log\frac{q_{\mathrm{sa}}(\mathrm{source}|\mathbf{s},\mathbf{a})}{q_{\mathrm{sa}}(\mathrm{target}|\mathbf{s},\mathbf{a})}$. (See Appendix-A.1.3 for details). Although the amount of data $\mathcal{D}$ sampled from the target M is reduced in our problem setup, we experimentally find that such classifiers are sufficient to achieve good performance.

4.2 DYNAMICS-AWARE REWARD AUGMENTATION IN MODEL-BASED FORMULATION

Following Equation 6, we then characterize the dynamics shift compensation term as in the above model-free analysis in the model-based offline formulation. We will find that across different derivations, our reward augmentation Δr has always maintained the functional consistency and simplicity.

Following MOPO, we assume $\mathcal{F} = \{f : \|f\|_\infty \leq 1\}$, then we have $d_{\mathcal{F}}(\hat{T}'(\mathbf{s}'|\mathbf{s},\mathbf{a}), \hat{T}(\mathbf{s}'|\mathbf{s},\mathbf{a})) = D_{\mathrm{TV}}(\hat{T}'(\mathbf{s}'|\mathbf{s},\mathbf{a}), \hat{T}(\mathbf{s}'|\mathbf{s},\mathbf{a})) \leq (D_{\mathrm{KL}}(\hat{T}'(\mathbf{s}'|\mathbf{s},\mathbf{a}), \hat{T}(\mathbf{s}'|\mathbf{s},\mathbf{a}))/2)^{\frac{1}{2}}$, where D_{TV} is the total variance distance. Then we introduce the admissible error $u(\mathbf{s},\mathbf{a})$ such that $d_{\mathcal{F}}(\hat{T}(\mathbf{s}'|\mathbf{s},\mathbf{a}), T(\mathbf{s}'|\mathbf{s},\mathbf{a})) \leq u(\mathbf{s},\mathbf{a})$ for all $(\mathbf{s},\mathbf{a})$, and η and δ such that $(D_{\mathrm{KL}}(\hat{T}',\hat{T})/2)^{\frac{1}{2}} \leq \eta D_{\mathrm{KL}}(\hat{T}',\hat{T}) + \delta$. Following Lemma 3, we thus can maximize the following lower bound with the samples in $\hat{M}'$ ($\lambda := \frac{\gamma R_{max}}{1-\gamma}$):

$$\eta_M(\pi) \geq \mathbb{E}_{\mathbf{s},\mathbf{a},\mathbf{s}'\sim d_{\hat{M}'}^\pi(\mathbf{s})\pi(\mathbf{a}|\mathbf{s})\hat{T}'(\mathbf{s}'|\mathbf{s},\mathbf{a})} \left[r(\mathbf{s},\mathbf{a}) - \eta\lambda\log\frac{\hat{T}'(\mathbf{s}'|\mathbf{s},\mathbf{a})}{\hat{T}(\mathbf{s}'|\mathbf{s},\mathbf{a})} - \lambda u(\mathbf{s},\mathbf{a}) - \lambda\delta \right]. \tag{9}$$

Implementation: We model the dynamics $\hat{T}'$ and $\hat{T}$ with an ensemble of 2*N parameterized Gaussian distributions: $\mathcal{N}_{\hat{T}'}^i(\mu_{\theta'}(\mathbf{s},\mathbf{a}), \Sigma_{\phi'}(\mathbf{s},\mathbf{a}))$ and $\mathcal{N}_{\hat{T}}^i(\mu_\theta(\mathbf{s},\mathbf{a}), \Sigma_\phi(\mathbf{s},\mathbf{a}))$, where $i \in [1,N]$. We approximate u with the maximum standard deviation of the learned models in the ensemble: $u(\mathbf{s},\mathbf{a}) = \max_{i=1}^N \|\Sigma_\phi(\mathbf{s},\mathbf{a})\|_{\mathrm{F}}$, omit the training-independent δ, and treat λ as a hyperparameter as in MOPO. For the $\log\frac{\hat{T}'}{\hat{T}}$ term, we resort to the above classifiers (q_{sas} and q_{sa}) in model-free setting. (See Appendix-A.3.2 for comparison between using classifiers and estimated-dynamics ratio.)

4.3 REGULARIZATION VIEW OF DYNAMICS-AWARE REWARD AUGMENTATION

Here we shortly characterize our dynamics-aware reward augmentation from the density regularization. Note the standard max-return objective $\eta_M(\pi)$ in RL can be written exclusively in terms of the on-policy distribution $d_M^\pi(\mathbf{s})\pi(\mathbf{a}|\mathbf{s})$. To introduce an off-policy distribution $d_{\mathcal{D}}(\mathbf{s})\pi_b(\mathbf{a}|\mathbf{s})$ in the objective, prior works often incorporate a regularization (penalty): $D(d_M^\pi(\mathbf{s})\pi(\mathbf{a}|\mathbf{s})\|d_{\mathcal{D}}(\mathbf{s})\pi_b(\mathbf{a}|\mathbf{s}))$, as in Equations 2 and 3. However, facing dynamics shift, such regularization should take into account the transition dynamics, which is penalizing $D(d_M^\pi(\mathbf{s})\pi(\mathbf{a}|\mathbf{s})T(\mathbf{s}'|\mathbf{s},\mathbf{a})\|d_{\mathcal{D}'}(\mathbf{s})\pi_{b'}(\mathbf{a}|\mathbf{s})\hat{T}'(\mathbf{s}'|\mathbf{s},\mathbf{a}))$. From this view, it is also straightforward to derive the reward modification built on prior regularized off-policy max-return objective[3] *e.g.*, the off-policy approach AlgaeDICE (Nachum et al., 2019b).

---

[3]We list some related works in Appendix A.2, where the majority of the existing work focuses on regularizing state-action distribution, while dynamics shift receives relatively little attention. Thus, we hope to shift the focus of the community towards analyzing how the dynamics shift affects RL and how to eliminate the effect.

5 RELATED WORK

Offline RL describes the setting in which a learner has access to only a fixed dataset of experience, while no interactive data collection is allowed during policy learning (Levine et al., 2020). Prior work commonly *assumes* that the offline experience is collected by some behavior policies on the same environment that the learned policy be deployed on. Thus, the main difficulty of such offline setting is the state-action distribution shift (Fujimoto et al., 2019; Liu et al., 2018). Algorithms address this issue by following the two main directions: the *model-free* and *model-based* offline RL.

Model-free methods for such setting typically fall under three categories: 1) Typical methods mitigate this problem by explicitly (Fujimoto et al., 2019; Kumar et al., 2019; Wu et al., 2019) or implicitly (Siegel et al., 2020; Peng et al., 2019; Abdolmaleki et al., 2018) constraining the learned policy away from OOD state-action pairs. 2) Conservative estimation based methods learn pessimistic value functions to prevent the overestimation (Kumar et al., 2020a; Xu et al., 2021). 3) Importance sampling based methods directly estimate the state-marginal importance ratio and obtain an unbiased value estimation (Zhang et al., 2020; Nachum & Dai, 2020; Nachum et al., 2019b).

Model-based methods typically eliminate the state-action distribution shift by incorporating a reward penalty, which relies on the uncertainty quantification of the learned dynamics (Kidambi et al., 2020; Yu et al., 2020). To remove this uncertainty estimation, Yu et al. (2021) learns conservative critic function by penalizing the values of the generated state-action pairs that are not in the offline dataset.

These methods, however, define their objective based on the state-action distribution shift, and ignore the potential dynamics shift between the fixed offline data and the target MDP. In contrast, we account for dynamics (state-action-next-state) shift and explicitly propose the dynamics aware reward augmentation. A counterpart, close to our work, is off-dynamics RL (Eysenbach et al., 2021), where they set up dynamics shift in the interactive environment while we focus on the offline setting.

6 EXPERIMENTS

We present empirical demonstrations of our dynamics-aware reward augmentation (DARA) in a variety of settings. We start with two simple control experiments that illustrate the significance of DARA under the domain (dynamics) adaptation setting. Then we incorporate DARA into state-of-the-art (model-free and model-based) offline RL methods and evaluate the performance on the D4RL tasks. Finally, we compare our framework to several cross-domain-based baselines on simulated and real-world tasks. Note that for the dynamics adaptation, we also release a (source) dataset as a complement to D4RL, along with the quadruped robot dataset in simulator (source) and real (target).

6.1 HOW DOES DARA HANDLE THE DYNAMICS SHIFT IN OFFLINE SETTING?

Figure 2: External dynamics shift: (left) source and target MDPs (target contains a obstacle represented with the dashed line); (middle) acquired policies are deployed on both source and target MDPs, where the top (*w/o Aug.*) denotes the vanilla MPO and the bottom (*DARA*) denotes MPO with our reward augmentation; (right) learned Q-values on the state-action pairs in left.

Figure 3: Internal dynamics shift: (left) source and target MDPs (range of the the right-back-leg is limited: ± 0.52 in $M' \rightarrow \pm 0.26$ in M); (right) the solid (orange) line denotes the state of the right-back-leg over one trajectory collected in source, dashed (blue) line denotes the learned reward modification $-\Delta r$ over the trajectory, and green and red slices denote transition pairs where $-\Delta r \geq$ and $-\Delta r < 0$, resp.

Here we characterize both external and internal dynamics shifts: In Map tasks (Figure 2 left), the source dataset $\mathcal{D}'$ is collected in a 2D map and the target $\mathcal{D}$ is collected in the same environment but with a obstacle (the dashed line); In Ant tasks (Figure 3 left), the source dataset $\mathcal{D}'$ is collected using the Mujoco Ant and the target $\mathcal{D}$ is collected with the same Ant but one joint of which is restricted.

Table 1: Normalized scores for the (target) D4RL tasks, where our results are averaged over 3 seeds. The arrows in each four-tuple indicate whether the current performance has improved (↑) or not (↓) compared to the previous value. If *1T+10S DARA* achieves comparable (less than 10% degradation) or better performance compared to baseline *10T*, we highlight our scores in bold (in each four-tuple).

Body Mass Shift		10T	1T	1T+10S w/o Aug.	1T+10S DARA	10T	1T	1T+10S w/o Aug.	1T+10S DARA	10T	1T	1T+10S w/o Aug.	1T+10S DARA
		BEAR				BRAC-p				AWR			
Hopper	Random	11.4	1.2↓	5.6↑	9.1↑	11.0	10.9↓	11.6↑	**10.9**↓	10.2	10.4↑	3.5↓	4.1↑
	Medium	52.1	0.8↓	0.8↓	1.2↑	32.7	32.3↓	30.4↓	**31.0**↑	35.9	30.9↓	22.2↓	28.2↑
	Medium-R	33.7	1.8↓	16.0↑	**33.6**↑	0.6	3.9↑	23.4↑	**28.5**↑	28.4	10.5↓	5.0↓	5.6↑
	Medium-E	96.3	0.9↓	0.6↓	1.2↑	1.9	31.2↑	32.6↑	**28.6**↓	27.1	26.9↓	27.0↑	**27.7**↑
		BCQ				CQL				MOPO			
Hopper	Random	10.6	10.5↓	8.3↓	**9.6**↑	10.8	10.6↓	10.3↓	**10.5**↑	11.7	4.4↓	2.8↓	3.0↑
	Medium	54.5	36.0↓	24.0↓	37.9↑	58.0	39.9↓	42.9↑	**62.2**↑	28.0	3.7↓	5.5↑	10.1↑
	Medium-R	33.1	10.8↓	29.2↑	**32.4**↑	48.6	11.3↓	1.6↓	3.8↑	67.5	1.1↓	7.4↑	10.0↑
	Medium-E	110.9	52.5↓	71.0↑	83.4↑	98.7	54.4↓	39.5↓	**93.3**↑	23.7	1.7↓	5.3↑	5.8↑
		BEAR				BRAC-p				AWR			
Walker2d	Random	7.3	2.1↓	2.6↑	3.0↑	-0.2	0.0↑	1.1↑	**1.6**↑	1.5	1.0↓	1.6↑	**1.9**↑
	Medium	59.1	-0.5↓	0.3↑	0.1↓	77.5	0.2↓	68.9↑	**76.4**↑	17.4	15.1↓	17.2↑	**17.3**↑
	Medium-R	19.2	0.4↓	6.7↑	8.1↑	-0.3	8.0↑	10.5↑	**21.9**↑	15.5	8.5↓	1.7↓	1.4↓
	Medium-E	40.1	-0.1↓	0.2↑	2.8↑	76.9	30.0↓	59.0↑	**76.0**↑	53.8	33.1↓	52.2↑	**53.4**↑
		BCQ				CQL				MOPO			
Walker2d	Random	4.9	2.3↓	4.4↑	**4.7**↑	7.0	1.5↓	2.5↑	2.5↑	13.6	-0.3↓	-0.1↑	-0.2↓
	Medium	53.1	31.1↓	49.5↑	**51.9**↑	79.2	29.6↓	79.0↑	**79.2**↑	17.8	8.8↓	8.8↑	10.8↑
	Medium-R	15.0	7.1↓	14.8↑	**15.1**↑	26.7	4.6↓	1.0↓	1.0↑	39.0	8.2↓	3.8↓	16.0↑
	Medium-E	57.5	37.5↓	53.9↑	**57.4**↑	111.0	34.1↓	63.2↑	94.4↑	44.6	8.1↓	6.8↓	22.0↑

Using MPO, as an example of offline RL method, we train a policy on dataset $\{\mathcal{D}' \cup \mathcal{D}\}$ and deploy the acquired policy in both source and target MDPs. As shown in Figure 2 (middle-top, *w/o Aug.*), such training paradigm does not produce an adaptive policy for the target. By modifying rewards in source $\mathcal{D}'$, we show that applying the same training paradigm on the reward augmented data exhibits a positive transfer ability in Figure 2 (middle-bottom, *DARA*). In Figure 2 (right), we show that our DARA produces low Q-values on the obstructive state-action pairs (in left) compared to the vanilla MPO, which thus prevents the Q-value weighted-regression on these unproductive state-action pairs.

More generally, we illustrate how DARA can handle the dynamics adaptation from the reward modification view. In Figure 3 (right), the learned reward modification $-\Delta r$ (dashed green line) clearly produces a penalty (red slices) on these state-action pairs (in source) that produce infeasible next-state transitions in the target MDP. If we directly apply prior offline RL methods, these transitions that are beyond reach in target and yet are high valued, would yield a negative transfer. Thus, we can think of DARA as finding out these transitions that exhibit dynamics shifts and enabling dynamics adaptation with reward modifications, *e.g.*, penalizing transitions covered by red slices ($-\Delta r < 0$).

6.2 CAN DARA ENABLE AN ADAPTIVE POLICY WITH REDUCED OFFLINE DATA IN TARGET?

To characterize the offline dynamics shift, we consider the Hopper, Walker2d and Halfcheetah from the Gym-MuJoCo environment, using offline samples from D4RL as our target offline dataset. For the source dataset, we change the body mass of agents or add joint noise to the motion, and, similar to D4RL, collect the Random, Medium, Medium-R and Medium-E offline datasets for the three environments. Based on various offline RL algorithms (BEAR, BRAC-p, BCQ, CQL, AWR, MOPO), we perform the following comparisons: 1) employing the 100% of D4RL data (*10T*), 2) employing only 10% of the D4RL data (*1T*), 3) employing 10% of the D4RL data and 100% of our collected source offline data (*1T+10S w/o Aug.*), and 4) employing 10% of the D4RL data and 100% of our collected source offline data along with our reward augmentation (*1T+10S DARA*). Due to page limit, here we focus on the dynamics shift concerning the body mass on Walker2d and Hopper. We refer the reader to appendix for more experimental details, tasks, and more baselines (BC, COMBO).

As shown in Table 1, in most of the tasks, the performance degrades substantially when we decrease the amount of target offline data, *i.e.*, *10T → 1T*. Training with additional ten times source offline data (*1T+10S w/o Aug.*) also does not bring substantial improvement (compensating for the reduced data in target), which even degrades the performance in some tasks. We believe that such degradation (compared to *10T*) is caused by the lack of target offline data as well as the dynamics shift (induced

Table 2: Normalized scores in (target) D4RL tasks, where "Tune" denotes baseline "fine-tune". We observe that with same amount (10%) of target offline data, DARA greatly outperforms baselines.

Body Mass Shift		Tune	DARA	Tune	DARA	Tune	DARA	Tune	DARA	Tune	DARA	$\pi_p\hat{T}$	$\hat{T}\pi_p$
			BEAR		BRAC-p		BCQ		CQL		MOPO		MABE
Hopper	Random	0.8	9.1 ↑	6.0	10.9 ↑	8.8	9.6 ↑	**31.6**	10.5 ↓	0.7	3.03 ↑	10.6	9.0
	Medium	0.8	1.2 ↑	22.7	31.0 ↑	31.7	37.9 ↑	44.5	**62.2** ↑	0.7	10.1 ↑	48.8	23.1
	Medium-R	0.7	**33.6** ↑	14.7	28.5 ↑	27.5	32.4 ↑	1.3	3.8 ↑	0.6	9.9 ↑	17.1	20.4
	Medium-E	0.9	1.2 ↑	19.2	28.6 ↑	85.9	83.4 ↓	47.6	**93.3** ↑	2.2	5.8 ↑	28.1	38.9
			BEAR		BRAC-p		BCQ		CQL		MOPO		MABE
Walker2d	Random	**6.6**	3.0 ↓	3.9	1.6 ↓	4.7	4.7 ↑	1.1	2.5 ↓	0.1	-0.2 ↓	6.0	-0.2
	Medium	0.3	0.1 ↓	76.0	76.4 ↑	28.4	51.9 ↑	72.3	**79.2** ↑	-0.2	10.8 ↑	30.1	56.7
	Medium-R	1.2	8.1 ↑	10.0	**21.9** ↑	10.4	15.1 ↑	1.8	1.0 ↓	0.0	16.0 ↑	13.3	12.5
	Medium-E	2.4	2.8 ↑	74.5	76.0 ↑	22.7	57.4 ↑	68.6	**94.4** ↑	7.3	22.0 ↑	43.7	82.7

by the source data). Incorporating our reward augmentation, we observe that compared to *1T* and *1T+10S w/o Aug.* that both use 10% of the target offline data, our *1T+10S DARA* significantly improves the performance across a majority of tasks. Moreover, DARA can achieve comparable or better performance compared to baseline *10T* that training with ten times as much target offline data.

6.3 CAN DARA PERFORM BETTER THAN CROSS-DOMAIN BASELINES?

In Section 6.2, *1T+10S w/o Aug.* does not explicitly learn policy for the target dynamics, thus one proposal (*1T+10S fine-tune*) for adapting the target dynamics is fine-tuning the model that learned with source offline data, using the (reduced) target offline data. Moreover, we also compare DARA with the recently proposed MABE (Cang et al., 2021), which is suitable well for our cross-dynamics setting by introducing behavioral priors π_p in the model-based offline setting. Thus, we implement two baselines: 1) *1T+10S MABE $\pi_p\hat{T}$* and 2) *1T+10S MABE $\hat{T}\pi_p$*, which denotes 1) learning π_p with target domain data and $\hat{T}$ with source domain data, and 2) learning π_p with source domain data and $\hat{T}$ with target domain data, respectively. We show the results for the Walker (with body mass shift) in Table 2, and more experiments in Appendix A.3.5. Our results show that DARA achieves significantly better performance than the naïve fine-tune-based approaches in a majority of tasks (67 "↑" vs. 13 "↓", including results in appendix). On eleven out of the sixteen tasks (including results in appendix), DARA-based methods outperform the MABE-based methods. We attribute MABE's failure to the difficulty of the reduced target offline data, which limits the generalization of the learned π_p or $\hat{T}$ under such data. However, such reduced data (10% of target) is sufficient to modify rewards in the source offline data, which thus encourages better performance for our DARA.

For real-world tasks, we also test DARA in a new offline dataset on the quadruped robot (see appendix for details). Note that we can not access the privileged information (*e.g.*, coordinate) in real robot, thus the target offline data (collected in real-world) does not contain rewards. This means that prior fine-tune-based and MABE-based methods become unavailable. However, our reward augmentation frees us from the requisite of rewards in

Table 3: Average distance covered in an episode in real robot.

(BCQ)	w/o Aug.	DARA
Medium	0.85	1.35 ↑
Medium-E	1.15	1.41 ↑
Medium–R-E	1.27	1.55 ↑

target domain. We can freely perform offline training only using the augmented source offline data as long as the learned Δr is sufficient. For comparison, we also employ a baseline (*w/o Aug.*): directly deploying the learned policy with source data into the (target) real-world. We present the results (deployed in real with obstructive stairs) in Table 3 and videos in supplementary material. We can observe that training with our reward augmentation, this performance can be substantially improved. Due to page limit, we refer readers to Appendix A.3.6 for more experimental results and discussion.

7 CONCLUSION

In this paper, we formulate the dynamics shift in offline RL. Based on prior model-based and model-free offline algorithms, we propose the dynamics-award reward augmentation (DARA) framework that characterizes constraints over state-action-next-state distributions. Empirically we demonstrate DARA can eliminate the dynamics shift and outperform baselines in simulated and real-world tasks.

REFERENCES

Abbas Abdolmaleki, Jost Tobias Springenberg, Yuval Tassa, Rémi Munos, Nicolas Heess, and Martin A. Riedmiller. Maximum a posteriori policy optimisation. In *6th International Conference on Learning Representations, ICLR 2018, Vancouver, BC, Canada, April 30 - May 3, 2018, Conference Track Proceedings*. OpenReview.net, 2018.

Philip J. Ball, Cong Lu, Jack Parker-Holder, and Stephen J. Roberts. Augmented world models facilitate zero-shot dynamics generalization from a single offline environment. In Marina Meila and Tong Zhang (eds.), *Proceedings of the 38th International Conference on Machine Learning, ICML 2021, 18-24 July 2021, Virtual Event*, volume 139 of *Proceedings of Machine Learning Research*, pp. 619–629. PMLR, 2021.

Catherine Cang, Aravind Rajeswaran, Pieter Abbeel, and Michael Laskin. Behavioral priors and dynamics models: Improving performance and domain transfer in offline RL. *CoRR*, abs/2106.09119, 2021. URL https://arxiv.org/abs/2106.09119.

Yevgen Chebotar, Karol Hausman, Yao Lu, Ted Xiao, Dmitry Kalashnikov, Jacob Varley, Alex Irpan, Benjamin Eysenbach, Ryan Julian, Chelsea Finn, and Sergey Levine. Actionable models: Unsupervised offline reinforcement learning of robotic skills. In Marina Meila and Tong Zhang (eds.), *Proceedings of the 38th International Conference on Machine Learning, ICML 2021, 18-24 July 2021, Virtual Event*, volume 139 of *Proceedings of Machine Learning Research*, pp. 1518–1528. PMLR, 2021. URL http://proceedings.mlr.press/v139/chebotar21a.html.

Jinglin Chen and Nan Jiang. Information-theoretic considerations in batch reinforcement learning. In Kamalika Chaudhuri and Ruslan Salakhutdinov (eds.), *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*, volume 97 of *Proceedings of Machine Learning Research*, pp. 1042–1051. PMLR, 2019.

Xinyue Chen, Zijian Zhou, Zheng Wang, Che Wang, Yanqiu Wu, and Keith Ross. Bail: Best-action imitation learning for batch deep reinforcement learning. *arXiv preprint arXiv:1910.12179*, 2019.

Erwin Coumans and Yunfei Bai. Pybullet, a python module for physics simulation for games, robotics and machine learning. http://pybullet.org, 2016–2021.

Benjamin Eysenbach and Sergey Levine. If maxent RL is the answer, what is the question? *CoRR*, abs/1910.01913, 2019. URL http://arxiv.org/abs/1910.01913.

Benjamin Eysenbach, Shreyas Chaudhari, Swapnil Asawa, Sergey Levine, and Ruslan Salakhutdinov. Off-dynamics reinforcement learning: Training for transfer with domain classifiers. In *9th International Conference on Learning Representations, ICLR 2021, Virtual Event, Austria, May 3-7, 2021*. OpenReview.net, 2021.

Justin Fu, Aviral Kumar, Ofir Nachum, George Tucker, and Sergey Levine. D4RL: datasets for deep data-driven reinforcement learning. *CoRR*, abs/2004.07219, 2020. URL https://arxiv.org/abs/2004.07219.

Scott Fujimoto, David Meger, and Doina Precup. Off-policy deep reinforcement learning without exploration. In Kamalika Chaudhuri and Ruslan Salakhutdinov (eds.), *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*, volume 97 of *Proceedings of Machine Learning Research*, pp. 2052–2062. PMLR, 2019.

Matthieu Geist, Bruno Scherrer, and Olivier Pietquin. A theory of regularized markov decision processes. In Kamalika Chaudhuri and Ruslan Salakhutdinov (eds.), *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*, volume 97 of *Proceedings of Machine Learning Research*, pp. 2160–2169. PMLR, 2019.

Seyed Kamyar Seyed Ghasemipour, Dale Schuurmans, and Shixiang Shane Gu. Emaq: Expected-max q-learning operator for simple yet effective offline and online RL. In Marina Meila and Tong Zhang (eds.), *Proceedings of the 38th International Conference on Machine Learning, ICML*

2021, 18-24 July 2021, Virtual Event, volume 139 of *Proceedings of Machine Learning Research*, pp. 3682–3691. PMLR, 2021.

Tuomas Haarnoja, Aurick Zhou, Kristian Hartikainen, George Tucker, Sehoon Ha, Jie Tan, Vikash Kumar, Henry Zhu, Abhishek Gupta, Pieter Abbeel, and Sergey Levine. Soft actor-critic algorithms and applications. *CoRR*, abs/1812.05905, 2018. URL `http://arxiv.org/abs/1812.05905`.

Behzad Haghgoo, Allan Zhou, Archit Sharma, and Chelsea Finn. Discriminator augmented model-based reinforcement learning. *CoRR*, abs/2103.12999, 2021. URL `https://arxiv.org/abs/2103.12999`.

Atil Iscen, Ken Caluwaerts, Jie Tan, Tingnan Zhang, Erwin Coumans, Vikas Sindhwani, and Vincent Vanhoucke. Policies modulating trajectory generators. In *2nd Annual Conference on Robot Learning, CoRL 2018, Zürich, Switzerland, 29-31 October 2018, Proceedings*, volume 87 of *Proceedings of Machine Learning Research*, pp. 916–926. PMLR, 2018. URL `http://proceedings.mlr.press/v87/iscen18a.html`.

Nan Jiang and Jiawei Huang. Minimax value interval for off-policy evaluation and policy optimization. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin (eds.), *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020. URL `https://proceedings.neurips.cc/paper/2020/hash/1cd138d0499a68f4bb72bee04bbec2d7-Abstract.html`.

Rahul Kidambi, Aravind Rajeswaran, Praneeth Netrapalli, and Thorsten Joachims. Morel: Model-based offline reinforcement learning. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin (eds.), *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020.

Ilya Kostrikov, Rob Fergus, Jonathan Tompson, and Ofir Nachum. Offline reinforcement learning with fisher divergence critic regularization. In Marina Meila and Tong Zhang (eds.), *Proceedings of the 38th International Conference on Machine Learning, ICML 2021, 18-24 July 2021, Virtual Event*, volume 139 of *Proceedings of Machine Learning Research*, pp. 5774–5783. PMLR, 2021.

Aviral Kumar, Justin Fu, Matthew Soh, George Tucker, and Sergey Levine. Stabilizing off-policy q-learning via bootstrapping error reduction. In Hanna M. Wallach, Hugo Larochelle, Alina Beygelzimer, Florence d'Alché-Buc, Emily B. Fox, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, December 8-14, 2019, Vancouver, BC, Canada*, pp. 11761–11771, 2019.

Aviral Kumar, Aurick Zhou, George Tucker, and Sergey Levine. Conservative q-learning for offline reinforcement learning. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin (eds.), *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020a.

Saurabh Kumar, Aviral Kumar, Sergey Levine, and Chelsea Finn. One solution is not all you need: Few-shot extrapolation via structured maxent RL. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin (eds.), *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020b. URL `https://proceedings.neurips.cc/paper/2020/hash/5d151d1059a6281335a10732fc49620e-Abstract.html`.

Sascha Lange, Thomas Gabel, and Martin Riedmiller. Batch reinforcement learning. In *Reinforcement learning*, pp. 45–73. Springer, 2012.

Joonho Lee, Jemin Hwangbo, Lorenz Wellhausen, Vladlen Koltun, and Marco Hutter. Learning quadrupedal locomotion over challenging terrain. *Science Robotics*, 5(47), 2020. doi:

10.1126/scirobotics.abc5986. URL `https://robotics.sciencemag.org/content/5/47/eabc5986`.

Sergey Levine. Reinforcement learning and control as probabilistic inference: Tutorial and review. *CoRR*, abs/1805.00909, 2018. URL `http://arxiv.org/abs/1805.00909`.

Sergey Levine, Aviral Kumar, George Tucker, and Justin Fu. Offline reinforcement learning: Tutorial, review, and perspectives on open problems. *CoRR*, abs/2005.01643, 2020. URL `https://arxiv.org/abs/2005.01643`.

Qiang Liu, Lihong Li, Ziyang Tang, and Dengyong Zhou. Breaking the curse of horizon: Infinite-horizon off-policy estimation. pp. 5361–5371, 2018. URL `https://proceedings.neurips.cc/paper/2018/hash/dda04f9d634145a9c68d5dfe53b21272-Abstract.html`.

Eric Mitchell, Rafael Rafailov, Xue Bin Peng, Sergey Levine, and Chelsea Finn. Offline meta-reinforcement learning with advantage weighting. In Marina Meila and Tong Zhang (eds.), *Proceedings of the 38th International Conference on Machine Learning, ICML 2021, 18-24 July 2021, Virtual Event*, volume 139 of *Proceedings of Machine Learning Research*, pp. 7780–7791. PMLR, 2021.

Ofir Nachum and Bo Dai. Reinforcement learning via fenchel-rockafellar duality. *CoRR*, abs/2001.01866, 2020. URL `http://arxiv.org/abs/2001.01866`.

Ofir Nachum, Yinlam Chow, Bo Dai, and Lihong Li. Dualdice: Behavior-agnostic estimation of discounted stationary distribution corrections. *arXiv preprint arXiv:1906.04733*, 2019a.

Ofir Nachum, Bo Dai, Ilya Kostrikov, Yinlam Chow, Lihong Li, and Dale Schuurmans. Algaedice: Policy gradient from arbitrary experience. *CoRR*, abs/1912.02074, 2019b. URL `http://arxiv.org/abs/1912.02074`.

Ashvin Nair, Murtaza Dalal, Abhishek Gupta, and Sergey Levine. Accelerating online reinforcement learning with offline datasets. *CoRR*, abs/2006.09359, 2020. URL `https://arxiv.org/abs/2006.09359`.

Sinno Jialin Pan and Qiang Yang. A survey on transfer learning. *IEEE Trans. Knowl. Data Eng.*, 22 (10):1345–1359, 2010. doi: 10.1109/TKDE.2009.191. URL `https://doi.org/10.1109/TKDE.2009.191`.

Xue Bin Peng, Marcin Andrychowicz, Wojciech Zaremba, and Pieter Abbeel. Sim-to-real transfer of robotic control with dynamics randomization. In *2018 IEEE International Conference on Robotics and Automation, ICRA 2018, Brisbane, Australia, May 21-25, 2018*, pp. 1–8. IEEE, 2018. doi: 10.1109/ICRA.2018.8460528. URL `https://doi.org/10.1109/ICRA.2018.8460528`.

Xue Bin Peng, Aviral Kumar, Grace Zhang, and Sergey Levine. Advantage-weighted regression: Simple and scalable off-policy reinforcement learning. *CoRR*, abs/1910.00177, 2019. URL `http://arxiv.org/abs/1910.00177`.

Jan Peters, Katharina Mulling, and Yasemin Altun. Relative entropy policy search. In *Twenty-Fourth AAAI Conference on Artificial Intelligence*, 2010.

Y. Sakakibara, K. Kan, Y. Hosoda, M. Hattori, and M. Fujie. Foot trajectory for a quadruped walking machine. In *EEE International Workshop on Intelligent Robots and Systems, Towards a New Frontier of Applications*, pp. 315–322 vol.1, 1990. doi: 10.1109/IROS.1990.262407.

Noah Y Siegel, Jost Tobias Springenberg, Felix Berkenkamp, Abbas Abdolmaleki, Michael Neunert, Thomas Lampe, Roland Hafner, Nicolas Heess, and Martin Riedmiller. Keep doing what worked: Behavioral modelling priors for offline reinforcement learning. *arXiv preprint arXiv:2002.08396*, 2020.

Richard S. Sutton. Integrated architectures for learning, planning, and reacting based on approximating dynamic programming. In Bruce W. Porter and Raymond J. Mooney (eds.), *Machine Learning, Proceedings of the Seventh International Conference on Machine Learning, Austin, Texas, USA, June 21-23, 1990*, pp. 216–224. Morgan Kaufmann, 1990. doi: 10.1016/b978-1-55860-141-3.50030-4.

Josh Tobin, Rachel Fong, Alex Ray, Jonas Schneider, Wojciech Zaremba, and Pieter Abbeel. Domain randomization for transferring deep neural networks from simulation to the real world. 2017.

Masatoshi Uehara, Jiawei Huang, and Nan Jiang. Minimax weight and q-function learning for off-policy evaluation. In *Proceedings of the 37th International Conference on Machine Learning, ICML 2020, 13-18 July 2020, Virtual Event*, volume 119 of *Proceedings of Machine Learning Research*, pp. 9659–9668. PMLR, 2020. URL `http://proceedings.mlr.press/v119/uehara20a.html`.

Nino Vieillard, Tadashi Kozuno, Bruno Scherrer, Olivier Pietquin, Rémi Munos, and Matthieu Geist. Leverage the average: an analysis of KL regularization in reinforcement learning. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin (eds.), *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020.

Xingxing Wang. Unitree robotics. `https://www.unitree.com/products/a1`, 2020.

Ziyu Wang, Alexander Novikov, Konrad Zolna, Jost Tobias Springenberg, Scott Reed, Bobak Shahriari, Noah Siegel, Josh Merel, Caglar Gulcehre, Nicolas Heess, et al. Critic regularized regression. *arXiv preprint arXiv:2006.15134*, 2020.

Yifan Wu, George Tucker, and Ofir Nachum. Behavior regularized offline reinforcement learning. *CoRR*, abs/1911.11361, 2019. URL `http://arxiv.org/abs/1911.11361`.

Haoran Xu, Xianyuan Zhan, and Xiangyu Zhu. Constraints penalized q-learning for safe offline reinforcement learning. *CoRR*, abs/2107.09003, 2021. URL `https://arxiv.org/abs/2107.09003`.

Mengjiao Yang, Ofir Nachum, Bo Dai, Lihong Li, and Dale Schuurmans. Off-policy evaluation via the regularized lagrangian. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin (eds.), *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020. URL `https://proceedings.neurips.cc/paper/2020/hash/488e4104520c6aab692863cc1dba45af-Abstract.html`.

Tianhe Yu, Garrett Thomas, Lantao Yu, Stefano Ermon, James Y. Zou, Sergey Levine, Chelsea Finn, and Tengyu Ma. MOPO: model-based offline policy optimization. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin (eds.), *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020.

Tianhe Yu, Aviral Kumar, Rafael Rafailov, Aravind Rajeswaran, Sergey Levine, and Chelsea Finn. COMBO: conservative offline model-based policy optimization. *CoRR*, abs/2102.08363, 2021. URL `https://arxiv.org/abs/2102.08363`.

Ruiyi Zhang, Bo Dai, Lihong Li, and Dale Schuurmans. Gendice: Generalized offline estimation of stationary values. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020. URL `https://openreview.net/forum?id=HkxlcnVFwB`.

A APPENDIX

A.1 DERIVATION

A.1.1 PROOF OF LEMMA 3

Let $\mathcal{B}_M^{\pi} V(\mathbf{s}) = \mathbb{E}_{\mathbf{a} \sim \pi(\mathbf{a}|\mathbf{s})} \left[r(\mathbf{s}, \mathbf{a}) + \gamma \mathbb{E}_{\mathbf{s}' \sim T(\mathbf{s}'|\mathbf{s}, \mathbf{a})} \left[V(\mathbf{s}') \right] \right]$ and $r(\mathbf{s}) = \mathbb{E}_{\mathbf{a} \sim \pi(\mathbf{a}|\mathbf{s})} \left[r(\mathbf{s}, \mathbf{a}) \right]$. Then, we have

$$
\eta_{\hat{M}'}(\pi) - \eta_M(\pi) = \mathbb{E}_{\mathbf{s}_0 \sim \rho_0(\mathbf{s})} \left[V_{\hat{M}'}(\mathbf{s}_0) - V_M(\mathbf{s}_0) \right]
$$

$$
= \sum_{t=0}^{\infty} \gamma^t \mathbb{E}_{\mathbf{s}_t \sim P(\mathbf{s}_t|\pi, \hat{M}', t)} \mathbb{E}_{\mathbf{a}_t \sim \pi(\mathbf{a}_t|\mathbf{s}_t)} \left[r(\mathbf{s}_t, \mathbf{a}_t) \right] - \mathbb{E}_{\mathbf{s}_0 \sim \rho_0(\mathbf{s})} \left[V_M(\mathbf{s}_0) \right]
$$

$$
= \sum_{t=0}^{\infty} \gamma^t \mathbb{E}_{\mathbf{s}_t \sim P(\mathbf{s}_t|\pi, \hat{M}', t)} \left[r(\mathbf{s}_t) + V_M(\mathbf{s}_t) - V_M(\mathbf{s}_t) \right] - \mathbb{E}_{\mathbf{s}_0 \sim \rho_0(\mathbf{s})} \left[V_M(\mathbf{s}_0) \right]
$$

$$
= \sum_{t=0}^{\infty} \gamma^t \mathbb{E}_{\substack{\mathbf{s}_t \sim P(\mathbf{s}_t|\pi, \hat{M}', t) \\ \mathbf{s}_{t+1} \sim P(\mathbf{s}_{t+1}|\pi, \hat{M}', t+1)}} \left[r(\mathbf{s}_t) + \gamma V_M(\mathbf{s}_{t+1}) - V_M(\mathbf{s}_t) \right]
$$

$$
= \sum_{t=0}^{\infty} \gamma^t \mathbb{E}_{\substack{\mathbf{s}_t \sim P(\mathbf{s}_t|\pi, \hat{M}', t) \\ \mathbf{s}_{t+1} \sim P(\mathbf{s}_{t+1}|\pi, \hat{M}', t+1)}} \left[r(\mathbf{s}_t) + \gamma V_M(\mathbf{s}_{t+1}) - \left(r(\mathbf{s}_t) + \gamma \mathbb{E}_{\mathbf{a} \sim \pi(\mathbf{a}|\mathbf{s}_t), \mathbf{s}' \sim T(\mathbf{s}_t, \mathbf{a})} \left[V_M(\mathbf{s}') \right] \right) \right]
$$

$$
= \sum_{t=0}^{\infty} \gamma^t \mathbb{E}_{\mathbf{s}_t \sim P(\mathbf{s}_t|\pi, \hat{M}', t)} \left[\mathcal{B}_{\hat{M}'}^{\pi} V_M(\mathbf{s}_t) - \mathcal{B}_M^{\pi} V_M(\mathbf{s}_t) \right]
$$

$$
= \mathbb{E}_{\mathbf{s} \sim d_{\hat{M}'}^{\pi}(\mathbf{s})} \left[\mathcal{B}_{\hat{M}'}^{\pi} V_M(\mathbf{s}) - \mathcal{B}_M^{\pi} V_M(\mathbf{s}) \right].
$$

A.1.2 MODEL-BASED FORMULATION

Here we provide detailed derivation of the lower bound in Equation 9 in the main text.

Assumption 1 *Assume a scale c and a function class $\mathcal{F}$ such that $V_M \in c\mathcal{F}$.*

Following MOPO (Yu et al., 2020), we set $\mathcal{F} = \{f : \|f\|_{\infty} \leq 1\}$. In Section Preliminaries, we have that the reward function is bounded: $r(\mathbf{s}, \mathbf{a}) \in [-R_{max}, R_{max}]$. Thus, we have $\|V_M\|_{\infty} \leq \sum_{t=0}^{\infty} \gamma^t R_{max} = \frac{R_{max}}{1-\gamma}$ and hence the scale $c = \frac{R_{max}}{1-\gamma}$.

As a direct corollary of Assumption 1 and Equation 5, we have

$$
\left| \mathbb{E}_{\mathbf{s} \sim d_{\hat{M}'}^{\pi}(\mathbf{s})} \left[\mathcal{B}_{\hat{M}'}^{\pi} V_M(\mathbf{s}) - \mathcal{B}_M^{\pi} V_M(\mathbf{s}) \right] \right| \leq \gamma c \cdot \mathbb{E}_{\mathbf{s}, \mathbf{a} \sim d_{\hat{M}'}^{\pi}(\mathbf{s})\pi(\mathbf{a}|\mathbf{s})} \left[d_{\mathcal{F}}(\hat{T}'(\mathbf{s}'|\mathbf{s}, \mathbf{a}), T(\mathbf{s}'|\mathbf{s}, \mathbf{a})) \right]. \tag{10}
$$

Further, we find

$$
d_{\mathcal{F}}(\hat{T}'(\mathbf{s}'|\mathbf{s}, \mathbf{a}), T(\mathbf{s}'|\mathbf{s}, \mathbf{a})) \leq d_{\mathcal{F}}(\hat{T}'(\mathbf{s}'|\mathbf{s}, \mathbf{a}), \hat{T}(\mathbf{s}'|\mathbf{s}, \mathbf{a})) + d_{\mathcal{F}}(\hat{T}(\mathbf{s}'|\mathbf{s}, \mathbf{a}), T(\mathbf{s}'|\mathbf{s}, \mathbf{a})) \tag{11}
$$

For the first term $d_{\mathcal{F}}(\hat{T}'(\mathbf{s}'|\mathbf{s}, \mathbf{a}), \hat{T}(\mathbf{s}'|\mathbf{s}, \mathbf{a}))$ in Equation 12, through Pinsker's inequality, we have

$$
d_{\mathcal{F}}(\hat{T}'(\mathbf{s}'|\mathbf{s}, \mathbf{a}), \hat{T}(\mathbf{s}'|\mathbf{s}, \mathbf{a})) = D_{\text{TV}}(\hat{T}'(\mathbf{s}'|\mathbf{s}, \mathbf{a}), \hat{T}(\mathbf{s}'|\mathbf{s}, \mathbf{a})) \leq \sqrt{\frac{1}{2} D_{\text{KL}}(\hat{T}'(\mathbf{s}'|\mathbf{s}, \mathbf{a}), \hat{T}(\mathbf{s}'|\mathbf{s}, \mathbf{a}))} \tag{12}
$$

To keep consistent with the DARA-based method-free offline methods, we introduce scale η and bias δ to eliminate the square root in Equation 12. To be specific, we assume[4] scale η and bias δ such that $\sqrt{\frac{1}{2} D_{\text{KL}}(\hat{T}', \hat{T})} \leq \eta D_{\text{KL}}(\hat{T}', \hat{T}) + \delta$. Thus, we obtain

$$
d_{\mathcal{F}}(\hat{T}'(\mathbf{s}'|\mathbf{s}, \mathbf{a}), \hat{T}(\mathbf{s}'|\mathbf{s}, \mathbf{a})) = D_{\text{TV}}(\hat{T}'(\mathbf{s}'|\mathbf{s}, \mathbf{a}), \hat{T}(\mathbf{s}'|\mathbf{s}, \mathbf{a})) \leq \eta D_{\text{KL}}(\hat{T}'(\mathbf{s}'|\mathbf{s}, \mathbf{a}), \hat{T}(\mathbf{s}'|\mathbf{s}, \mathbf{a})) + \delta \tag{13}
$$

---

[4]In implementation, we clip the maximum deviation of $\log \frac{\hat{T}'(\mathbf{s}'|\mathbf{s}, \mathbf{a})}{\hat{T}(\mathbf{s}'|\mathbf{s}, \mathbf{a})}$ for each $(\mathbf{s}, \mathbf{a}, \mathbf{s}')$, which thus makes $D_{\text{KL}}(\hat{T}'(\mathbf{s}'|\mathbf{s}, \mathbf{a}), \hat{T}(\mathbf{s}'|\mathbf{s}, \mathbf{a}))$ bounded.

For the second term $d_{\mathcal{F}}(\hat{T}(\mathbf{s}'|\mathbf{s}, \mathbf{a}), T(\mathbf{s}'|\mathbf{s}, \mathbf{a}))$ in Equation 11, we assume that we have access to an oracle uncertainty qualification module that provides an upper bound on the error of the estimated empirical MDP $\hat{M} := \{\mathcal{S}, \mathcal{A}, r, \hat{T}, \rho_0, \gamma\}$.

Assumption 2 *Let $\mathcal{F}$ be the function class in Assumption 1. We say $u : \mathcal{S} \times \mathcal{A} \to \mathbb{R}$ is an admissible error estimator for $\hat{T}$ if $d_{\mathcal{F}}(\hat{T}(\mathbf{s}'|\mathbf{s}, \mathbf{a}), T(\mathbf{s}'|\mathbf{s}, \mathbf{a})) \leq u(\mathbf{s}, \mathbf{a})$ for all $(\mathbf{s}, \mathbf{a})$.*

Thus, we have

$$\mathbb{E}_{\mathbf{s}, \mathbf{a} \sim d^{\pi}_{\hat{M}'}(\mathbf{s})\pi(\mathbf{a}|\mathbf{s})} \left[d_{\mathcal{F}}(\hat{T}(\mathbf{s}'|\mathbf{s}, \mathbf{a}), T(\mathbf{s}'|\mathbf{s}, \mathbf{a})) \right] \leq \mathbb{E}_{\mathbf{s}, \mathbf{a} \sim d^{\pi}_{\hat{M}'}(\mathbf{s})\pi(\mathbf{a}|\mathbf{s})} \left[u(\mathbf{s}, \mathbf{a}) \right] \tag{14}$$

Bring Inequations 10, 11, 13, and 14 into Lemma 3, we thus have

$$\eta_M(\pi) \geq \mathbb{E}_{\mathbf{s}, \mathbf{a}, \mathbf{s}' \sim d^{\pi}_{\hat{M}'}(\mathbf{s})\pi(\mathbf{a}|\mathbf{s})\hat{T}'(\mathbf{s}'|\mathbf{s}, \mathbf{a})} \left[r(\mathbf{s}, \mathbf{a}) - \eta\gamma c \log \frac{\hat{T}'(\mathbf{s}'|\mathbf{s}, \mathbf{a})}{\hat{T}(\mathbf{s}'|\mathbf{s}, \mathbf{a})} - \gamma c u(\mathbf{s}, \mathbf{a}) - \gamma c \delta \right]. \tag{15}$$

A.1.3 LEARNING CLASSIFIERS

Applying Bayes' rule, we have

$$\hat{T}'(\mathbf{s}'|\mathbf{a}, \mathbf{s}) := p(\mathbf{s}'|\mathbf{s}, \mathbf{a}, \text{source}) = \frac{p(\text{source}|\mathbf{s}, \mathbf{a}, \mathbf{s}')p(\mathbf{s}, \mathbf{a}, \mathbf{s}')}{p(\text{source}|\mathbf{s}, \mathbf{a})p(\mathbf{s}, \mathbf{a})},$$

$$\hat{T}(\mathbf{s}'|\mathbf{a}, \mathbf{s}) := p(\mathbf{s}'|\mathbf{s}, \mathbf{a}, \text{target}) = \frac{p(\text{target}|\mathbf{s}, \mathbf{a}, \mathbf{s}')p(\mathbf{s}, \mathbf{a}, \mathbf{s}')}{p(\text{target}|\mathbf{s}, \mathbf{a})p(\mathbf{s}, \mathbf{a})}.$$

Then we parameterize $p(\cdot|\mathbf{s}, \mathbf{a}, \mathbf{s}')$ and $p(\cdot|\mathbf{s}, \mathbf{a})$ with the two classifiers q_{sas} and q_{sa} respectively. Using the standard cross-entropy loss, we learn q_{sas} and q_{sa} with the following optimization objective:

$$\max \quad \mathbb{E}_{(\mathbf{s}, \mathbf{a}, \mathbf{s}') \sim \mathcal{D}'} \left[\log q_{\text{sas}}(\text{source}|\mathbf{s}, \mathbf{a}, \mathbf{s}') \right] + \mathbb{E}_{(\mathbf{s}, \mathbf{a}, \mathbf{s}') \sim \mathcal{D}} \left[\log q_{\text{sas}}(\text{target}|\mathbf{s}, \mathbf{a}, \mathbf{s}') \right],$$

$$\max \quad \mathbb{E}_{(\mathbf{s}, \mathbf{a}) \sim \mathcal{D}'} \left[\log q_{\text{sa}}(\text{source}|\mathbf{s}, \mathbf{a}) \right] + \mathbb{E}_{(\mathbf{s}, \mathbf{a}) \sim \mathcal{D}} \left[\log q_{\text{sa}}(\text{target}|\mathbf{s}, \mathbf{a}) \right].$$

With the trained q_{sas} and q_{sa}, we have

$$\log \frac{\hat{T}'(\mathbf{s}'|\mathbf{s}, \mathbf{a})}{\hat{T}(\mathbf{s}'|\mathbf{s}, \mathbf{a})} = \log \frac{q_{\text{sas}}(\text{source}|\mathbf{s}, \mathbf{a}, \mathbf{s}')}{q_{\text{sas}}(\text{target}|\mathbf{s}, \mathbf{a}, \mathbf{s}')} - \log \frac{q_{\text{sa}}(\text{source}|\mathbf{s}, \mathbf{a})}{q_{\text{sa}}(\text{target}|\mathbf{s}, \mathbf{a})}. \tag{16}$$

In our implementation, we also clip the above reward modification between -10 and 10.

A.2 REGULARIZATION VIEW

In Table 4, we provide some related works with respect to the (state-action pair) $d_{\mathcal{D}}(\mathbf{s})\pi_b(\mathbf{a}|\mathbf{s})$ regularization and the (state-action-next-state pair) $d_{\mathcal{D}'}(\mathbf{s})\pi_{b'}(\mathbf{a}|\mathbf{s})\hat{T}'(\mathbf{s}'|\mathbf{s}, \mathbf{a})$ regularization.

Table 4: Some related works with **explicit** (state-action $p(\mathbf{s}, \mathbf{a})$ or state-action-next-state $p(\mathbf{s}, \mathbf{a}, \mathbf{s}')$) **regularization**. More papers with respect to unsupervised RL, inverse RL (imitation learning), meta RL, multi-agent RL, and hierarchical RL are not included.

reg. with $d_{\mathcal{D}}(\mathbf{s})\pi_b(\mathbf{a}|\mathbf{s})$		reg. with $d_{\mathcal{D}'}(\mathbf{s})\pi_{b'}(\mathbf{a}|\mathbf{s})\hat{T}'(\mathbf{s}'|\mathbf{s}, \mathbf{a})$
Online: see summarization in Geist et al. (2019) and Vieillard et al. (2020).		Eysenbach et al. (2021) (DARC); Haghgoo et al. (2021)
Offline (off-policy evaluation):		
Fujimoto et al. (2019) (BCQ);	Kumar et al. (2019) (BEAR);	
Wu et al. (2019) (BRAC-p);	Abdolmaleki et al. (2018) (MPO);	
Peng et al. (2019) (AWR);	Nair et al. (2020) (AWAC);	
Wang et al. (2020) (CRR);	Siegel et al. (2020);	
Chen et al. (2019); (BAIL)	Kumar et al. (2020a) (CQL);	
Xu et al. (2021) (CPQ);	Kostrikov et al. (2021) (Fisher-BRC);	
Liu et al. (2018);	Nachum et al. (2019a) (DualDICE);	
Nachum et al. (2019b) (AlgaeDICE);	Zhang et al. (2020) (GenDICE);	
Yang et al. (2020);	Nachum & Dai (2020);	
Jiang & Huang (2020);	Uehara et al. (2020);	
Yu et al. (2020) (MOPO);	Kidambi et al. (2020) (MOReL);	
Yu et al. (2021) (COMBO);	Cang et al. (2021) (MABE);	

A.3   ADDITIONAL EXPERIMENTS

A.3.1   TRAINING WITH $\{\mathcal{D}' \cup \mathcal{D}\}$

As we show in Figure 1 in Section Introduction, the performance of prior offline RL methods deteriorates dramatically as the amount of (target) offline data $\mathcal{D}$ decreases. In Figure 4, we show that directly training with the mixed dataset $\{\mathcal{D}' \cup \mathcal{D}\}$ will not compensate for the deteriorated performance caused by the reduced target offline data, and training with such additional source offline data can even lead the performance degradation in some tasks.

Figure 4: Final performance on the D4RL (Walker2d) task: The orange bars denote the final performance with different amount ($50\%\mathcal{D}$, $20\%\mathcal{D}$, $10\%\mathcal{D}$, $5\%\mathcal{D}$) of target offline data; The blue bars denote the final performance of mixing 100% of source offline data $\mathcal{D}'$ and different amount of target data $x\%\mathcal{D}$ ($x \in [50, 20, 10, 5]$), *i.e.*, training with $\{100\%\mathcal{D}' \cup x\%\mathcal{D}\}$; The red lines denote the final performance of training with 100% of target offline data $\mathcal{D}$. We can observe that 1) the performance deteriorates dramatically as the amount of (target) offline data decreases ($100\%\mathcal{D}$ (red line) $\rightarrow$ $50\%\mathcal{D}$ (orange bar) $\rightarrow$ $20\%\mathcal{D}$ (orange bar) $\rightarrow$ $10\%\mathcal{D}$ (orange bar) $\rightarrow$ $5\%\mathcal{D}$ (orange bar)), 2) after training with the additional 100% of source offline data, $\{100\%\mathcal{D}' \cup x\%\mathcal{D}\}$, the final performance is improved in most tasks, but most of the improvement is a pittance compared to the original performance degradation (compared to that training with the 100% of target offline data, *i.e.*, the red lines).

A.3.2 COMPARISON BETWEEN LEARNING CLASSIFIERS AND LEARNING DYNAMICS (FOR THE REWARD MODIFICATION)

Table 5: Normalized scores for the Hopper tasks with the body mass (dynamics) shift. Rat. and Cla. denote estimating the reward modification with the estimated-dynamics ratio and learned classifiers (Appendix A.1.3), respectively.

Body Mass Shift		BEAR			BRAC-p			AWR			BCQ			CQL			MOPO		
		Rat.		Cla.	Cla.		Cla.	Rat.		Cla.	Rat.		Cla.	Rat.		Cla.	Rat.		Cla.
Hopper	Random	9.9	>	9.1	11.2	>	10.9	3.7	<	4.1	8.5	<	9.6	11.8	>	10.5	1.8	<	3.0
	Medium	0.8	<	1.2	31.7	>	31.0	18.0	<	28.2	33.2	<	37.9	45.9	<	62.2	3.1	<	10.1
	Medium-R	28.4	<	33.6	36.5	>	28.5	2.5	<	5.6	33.9	>	32.4	2.0	<	3.8	3.8	<	9.9
	Medium-E	0.8	<	1.2	50.9	>	28.6	45.8	<	27.7	68.4	<	83.4	107.3	>	93.3	5.7	<	5.8

In Table 5, we show the comparison between learning classifiers and learning dynamics (for our reward modification) in the Hopper tasks. We can observe that the two schemes for estimating the reward modification have similar performance. Thus, for simplicity and following Eysenbach et al. (2021), we adopt the classifiers to modify rewards in the source offline data in our experiments.

A.3.3 MORE EXAMPLES WITH RESPECT TO THE REWARD AUGMENTATION

Figure 5: We can observe that our reward augmentation 1) encourages ($-\Delta r > 0$, *i.e.*, the green slice parts) these transitions ($-0.26 \leq$ next-state[11] ≤ 0.26) that have the same dynamics with the target environment, and 2) discourages ($-\Delta r < 0$, *i.e.*, the red slice parts) these transitions that have different (unreachable) dynamics (next-state[11] ≤ -0.26 or next-state[11] ≥ 0.26) in the target.

In Figure 5, we provide more examples with respect to the reward augmentation in the Ant task in Figure 3 (left).

A.3.4 COMPARISON BETWEEN *10T*, *1T*, *1T+10S w/o Aug.*, AND *1T+10S DARA*

Based on various offline RL algorithms (BEAR (Kumar et al., 2019), BRAC-p (Wu et al., 2019), BCQ (Fujimoto et al., 2019), CQL (Kumar et al., 2020a), AWR (Peng et al., 2019), MOPO (Yu et al., 2020), BC (behavior cloning), COMBO (Yu et al., 2021)), we provide the additional results in Tables 6, 7, 8, 9, and 10.

Table 6: Normalized scores for the Hopper tasks with the body mass (dynamics) shift. (The comparison results for BEAR, BRAC-p, AWR, CQL, and MOPO are provided in the main text.)

Body Mass Shift		10T	1T	1T+10S w/o Aug.	1T+10S DARA	10T	1T	1T+10S w/o Aug.	1T+10S DARA	10T	1T	1T+10S w/o Aug.	1T+10S DARA
				BC				COMBO					
Hopper	Random	9.8	9.8 ↑	6.9 ↓	10.1 ↑	17.9	0.7 ↓	5.4 ↑	4.6 ↓				
	Medium	29.0	27.9 ↓	17.6 ↓	25.0 ↑	94.9	1.8 ↓	33.7 ↑	45.7 ↑				
	Medium-R	11.8	7.8 ↓	7.7 ↓	11.6 ↑	73.1	13.1 ↓	11.0 ↓	27.9 ↑				
	Medium-E	111.9	21.5 ↓	20.8 ↓	35.7 ↑	111.1	0.8 ↓	14.9 ↑	108.1 ↑				

Table 7: Normalized scores for the Hopper tasks with the joint noise (dynamics) shift.

Joint Noise Shift	10T	1T	1T+10S w/o Aug.	1T+10S DARA	10T	1T	1T+10S w/o Aug.	1T+10S DARA	10T	1T	1T+10S w/o Aug.	1T+10S DARA
	BEAR				BRAC-p				AWR			
Random	11.4	0.7↓	7.9↑	7.8↓	11.0	10.9↓	10.8↓	10.8↓	10.2	10.1↓	3.6↓	4.4↑
Medium	52.1	0.8↓	3.1↑	2.0↓	32.7	31.3↓	30.4↓	44.5↑	35.9	30.2↓	35	35.9↑
Medium-R	33.7	4.3↓	4.0↓	3.6↓	0.6	19.8↑	97.7↑	101.2↑	28.4	18.4↓	10.9↓	7.5↓
Medium-E	96.3	1.0↓	0.8↓	0.8↓	1.9	5.8↑	80.9↑	101.1↑	27.1	26.6↓	27.0↑	27.1↑
	BCQ				CQL				MOPO			
Random	10.6	10.6↓	7.0↓	9.6↑	10.8	10.5↓	10.8↑	10.8↑	11.7	0.7↓	1.8↑	4.4↑
Medium	54.5	43.6↓	50.7↑	54.3↑	58.0	34.3↓	58.0↑	58.0↑	28.0	0.6↓	3.9↑	13.9↑
Medium-R	33.1	18.0↓	20.6↑	32.9↑	48.6	20.0↓	2.9↓	4.2↑	67.5	0.7↓	4.0↓	5.6↑
Medium-E	110.9	26.0↓	96.5↑	108.8↑	98.7	23.8↓	71.9↑	108.2↑	23.7	0.8↓	4.7↑	6.9↑
	BC				COMBO							
Random	9.8	9.8↑	7.5↓	9.1↑	17.9	0.7↓	1.8↑	4.9↑				
Medium	29.0	27.9↓	29.0↑	29.0↑	94.9	1.8↓	0.7↓	9.6↑				
Medium-R	11.8	7.8↓	8.5↑	11.3↑	73.1	13.1↓	4.0↓	9.6↑				
Medium-E	111.9	21.5↓	53.5↑	77.9↑	111.1	0.8↓	34.0↑	45.9↑				

Row groups labeled: Hopper

Table 8: Normalized scores for the Walker2d tasks with the body mass (dynamics) shift. (The comparison results for BEAR, BRAC-p, AWR, CQL, and MOPO are provided in the main text.)

Body Mass Shift	10T	1T	1T+10S w/o Aug.	1T+10S DARA	10T	1T	1T+10S w/o Aug.	1T+10S DARA	10T	1T	1T+10S w/o Aug.	1T+10S DARA
	BC				COMBO							
Random	1.6	0.1↓	1.7↑	2.7↑	7.0	1.8↓	2.0↑	3.5↑				
Medium	6.6	5.5↓	3.8↓	6.6↑	75.5	-1.0↓	23.9↑	36.6↑				
Medium-R	11.3	6.6↓	8.1↑	11.0↑	56.0	0.1↓	11.4↑	22.6↑				
Medium-E	6.4	3.1↓	6.0↑	6.2↑	96.1	-0.9↓	-0.1↑	-0.1↑				

Row group labeled: Walker2d

Table 9: Normalized scores for the Walker2d tasks with the joint noise (dynamics) shift.

Joint Noise Shift	10T	1T	1T+10S w/o Aug.	1T+10S DARA	10T	1T	1T+10S w/o Aug.	1T+10S DARA	10T	1T	1T+10S w/o Aug.	1T+10S DARA
	BEAR				BRAC-p				AWR			
Random	7.3	2.1↓	0.4↓	2.9↑	-0.2	-0.1↑	0.4↑	0.7↑	1.5	1.0↓	0.8↓	1.7↑
Medium	59.1	-0.3↓	0.7↑	-0.2↓	77.5	0.4↓	39.5↓	63.8↑	17.4	12.6↓	17.0↑	17.4↑
Medium-R	19.2	0.2↓	4.3↑	12.8↑	-0.3	7.5↑	20.2↑	24.2↑	15.5	7.1↓	1.3↓	3.0↑
Medium-E	40.1	0.0↓	1.2↑	1.2↑	76.9	40.2↓	49.2↑	76.1↑	53.8	27.8↓	53.1↑	53.6↑
	BCQ				CQL				MOPO			
Random	4.9	1.9↓	3.0↑	4.9↑	7.0	1.5↓	2.5↑	5.7↑	13.6	-0.2↓	-0.2↓	-0.4↓
Medium	53.1	34.7↓	41.6↑	52.4↑	79.2	22.2↓	72.4↑	80.0↑	17.8	11.7↓	14.0↑	17.2↑
Medium-R	15.0	6.2↓	4.5↓	14.2↑	26.7	0.6↓	0.9↑	1.5↑	39.0	1.5↓	14.5↑	21.3↑
Medium-E	57.5	40.9↓	24.1↓	57.5↑	111.0	6.8↓	105.4↑	107.4↑	44.6	6.0↓	28.0↑	44.7↑
	BC				COMBO							
Random	1.6	0.1↓	0.9↑	1.6↑	7.0	1.8↓	0.1↓	1.5↑				
Medium	6.6	5.5↓	6.4↑	6.5↑	75.5	-1.0↓	0.4↑	0.7↑				
Medium-R	11.3	6.6↓	4.6↓	10.4↑	56.0	0.1↓	5.6↑	7.4↑				
Medium-E	6.4	3.1↓	6.2↑	6.4↑	96.1	-0.9↓	0.8↑	-0.1↓				

Row groups labeled: Walker2d

Table 10: Normalized scores for the Halfcheetah tasks with the joint noise (dynamics) shift.

Joint Noise Shift	10T	1T	1T+10S w/o Aug.	1T+10S DARA	10T	1T	1T+10S w/o Aug.	1T+10S DARA	10T	1T	1T+10S w/o Aug.	1T+10S DARA
	BEAR				BRAC-p				AWR			
Random	25.1	17.8↓	25.0↑	25.1↑	24.1	10.0↓	25.0↑	26.7↑	2.5	2.7↑	3.1↑	48.9↑
Medium	41.7	-0.2↓	0.8↑	1.5↑	43.8	43.0↓	52.4↑	53.0↑	37.4	38.2↑	48.7↑	37.4↓
Medium-R	38.6	9.3↓	-0.6↓	-0.5↑	45.4	2.5↓	-2.3↓	45.3↑	40.3	2.6↓	2.3↓	2.3↓
Medium-E	53.4	-1.2↓	1.0↑	-1.4↓	44.2	6.9↓	0.9↑	45.3↑	52.7	32.2↓	80.6↑	79.2↓
	BCQ				CQL				MOPO			
Random	2.2	2.3↑	2.2↓	2.3↑	35.4	-2.3↓	-2.4↓	10.4↑	35.4	2.3↓	1.2↓	1.1↓
Medium	40.7	37.6↓	40.0↑	48.6↑	44.4	35.4↓	40.7↑	52.6↑	42.3	3.2↓	3.5↓	5.3↑
Medium-R	38.2	1.1↓	39.4↑	41.3↑	46.2	0.6↓	2.0↑	1.9↓	53.1	-0.1↓	2.6↑	4.2↑
Medium-E	64.7	37.3↓	55.3↑	76.9↑	62.4	-3.3↓	7.7↑	1.7↓	63.3	4.2↓	1.5↓	7.2↑
	BC				COMBO							
Random	2.1	2.0↓	2.2↑	2.2↑	38.8	24.0↓	18.7↓	20.3↑				
Medium	36.1	36.5↑	49.4↑	49.8↑	54.2	15.7↓	14.9↓	15.9↑				
Medium-R	38.4	36.5↓	24.6↓	15.7↓	55.1	-2.6↓	-2.4↓	4.8↑				
Medium-E	35.8	36.3↑	49.0↑	49.3↑	90.0	4.4↓	6.5↑	11.1↑				

A.3.5 COMPARISON WITH THE CROSS-DOMAIN BASED BASELINES

In Tables 11 and 12, we provide the comparison between our DARA-based methods, fine-tune based methods, and MABE-based methods in Hopper and Walker2d tasks, over the dynamics shift concerning the joint noise of motion. We can observe that in a majority of tasks, our DARA-based methods outperforms the fine-tune-based method (67 "↑" vs. 13 "↓", including the results in the main text). Moreover, our DARA can achieve comparable or better performance compared to MABE-based baselines on eleven out of sixteen tasks (including the results in the main text).

Table 11: Normalized scores in the (target) D4RL Hopper tasks with the joint noise shift., where "Tune" denotes baseline "fine-tune".

Joint Noise Shift	Tune	DARA	Tune	DARA	Tune	DARA	Tune	DARA	Tune	DARA	$\pi_p \hat{T}$	$\hat{T} \pi_p$
	BEAR		BRAC-p		BCQ		CQL		MOPO		MABE	
Random	0.8	7.8↑	6.4	10.8↑	8.1	9.6↑	**32.2**	10.8↓	0.6	4.4↑	10.8	8.1
Medium	1.9	2.0↑	44.9	44.5↓	47.7	54.3↑	52.5	58.0↑	0.8	13.9↑	**63.5**	57.7
Medium-R	0.7	3.6↑	32.4	**101.2**↑	29.6	32.9↑	1.3	4.2↑	1.8	5.6↑	21.5	35.4
Medium-E	0.8	0.8↑	98.2	101.1↑	90.5	**108.8**↑	107.3	108.2↑	4.9	6.9↑	15.5	104.8

Table 12: Normalized scores in the (target) D4RL Walker2d tasks with the joint noise shift., where "Tune" denotes baseline "fine-tune".

Joint Noise Shift	Tune	DARA	Tune	DARA	Tune	DARA	Tune	DARA	Tune	DARA	$\pi_p \hat{T}$	$\hat{T} \pi_p$
	BEAR		BRAC-p		BCQ		CQL		MOPO		MABE	
Random	2.7	2.9↑	1.4	0.7↓	3.0	4.9↑	**6.7**	5.7↓	-0.4	-0.4↓	5.0	-0.2
Medium	0.5	-0.2↓	55.8	63.8↑	45.1	52.4↑	76.6	**80.0**↑	7.0	17.2↑	49.4	48.7
Medium-R	3.2	12.8↑	12.2	**24.2**↑	13.5	14.2↑	-0.4	1.5↑	1.9	21.3↑	4.5	1.6
Medium-E	-0.4	1.2↑	71.7	76.1↑	44.8	57.5↑	104	**107.4**↑	11.3	44.7↑	84.7	82.6

A.3.6 ADDITIONAL RESULTS ON THE QUADRUPED ROBOT

In this offline sim2real setting, we collect the source offline data in the simulator (10^6 or $2 * 10^6$ steps) and target offline data in the real world ($3 * 10^4$ steps). See Appendix A.4 for details. For testing, we directly deploy the learned policy in the real (flat or obstructive) environment and adopt the average distance covered in an episode (300 steps) as our evaluation metrics.

Figure 6: Illustration of the real environment (for testing): (left) the flat and static environment, (right) the obstructive and dynamic environment.

Table 13: Average distance (m) covered in an episode (300 steps) in flat and static (real) environment.

Sim2real (Flat and Static)		w/o Aug.	DARA	w/o Aug.	DARA	w/o Aug.	DARA
		BCQ		CQL		MOPO	
Quadruped Robot	Medium	1.56	1.64 ↑	1.80	**1.82** ↑	0.00	0.00
	Medium-R	0.00	0.00	—	—	—	—
	Medium-E	2.16	**2.47** ↑	2.03	2.02 ↓	0.00	0.00
	Medium-R-E	1.69	**2.28** ↑	0.00	0.00	—	—
Average performance improvement			13.6%		0.2%		0.0%

(Flat and static environment) We first deploy our learned policy in the flat and static environment. The results (distance covered in an episode) are provided in Table 13.

1) BCQ (Figure 7): We find that with Medium-R offline data, *w/o Aug. BCQ* and *DARA BCQ* both could not acquire the locomotion skills, which we think is caused by the lack of high-quality offline data. With more "expert" data (Medium-R → Medium → Medium-E, or Medium-R → Medium-R-E), *w/o-Aug. BCQ* allows for progressive performance (0.00 → 1.56 → 2.16, or 0.00 → 1.69 in BCQ), but with our reward augmentation, such performance can be further improved (with average improvement 13.6%).

2) CQL (Figure 8): We find that with Medium-R or Medium-R-E offline data, *w/o Aug. CQL* and *DARA CQL* both could not learn the locomotion skills, which we think is caused by the low-quality "Replay" offline data. With Medium or Medium-E offline data, *w/o Aug. CQL* and *DARA CQL* acquire similar performance on this flat and static environment.

3) MOPO: We find that the model-based MOPO (both *w/o Aug.* and *DARA*) could hardly learn the locomotion skill under the provided offline data.

Table 14: Average distance (m) covered in an episode (300 steps) in the obstructive and dynamic (real) environment.

Sim2real (Obstructive and Dynamic)		w/o Aug.	DARA	w/o Aug.	DARA	w/o Aug.	DARA
		BCQ		CQL		MOPO	
Quadruped Robot	Medium	0.85	1.35 ↑	0.92	**1.40** ↑	—	—
	Medium-R	—	—	—	—	—	—
	Medium-E	1.15	**1.41** ↑	0.77	1.32 ↑	—	—
	Medium-R-E	1.27	**1.55** ↑	—	—	—	—
Average performance improvement			25.9%		30.9%		—

(Obstructive and dynamic environment) We then deploy our learned policy in the obstructive and dynamic environment. The results (distance covered in an episode) are provided in Table 14.

1) BCQ (Figure 9): In this obstructive environment, we can obtain similar results as in the flat environment. With more "expert" data (Medium → Medium-E → Medium-R-E), *w/o Aug. BCQ* allows for progressive performance (0.85 → 1.15 → 1.27), and with our reward augmentation, such performance can be further improved (with average improvement 25.9%). At the same time, we can also find that due to the presence of environmental obstacles, the performance of both *w/o*

Aug. BCQ and *w/o Aug. DARA* is decreased compared to the deployment on the flat environment. However, we find that our DARA exhibits greater average performance improvement under this obstructive environment ($13.6\% \rightarrow \textbf{25.9\%}$) compared to that in the flat environment. *These results demonstrate that our DARA can learn an adaptive policy for the target environment and thus show a greater advantage over* w/o-Aug. *in more complex environments.*

2) CQL (Figure 10): Similar to BCQ, our *DARA CQL* exhibits a greater performance improvement over baseline in the obstructive and dynamic environment ($0.2\% \rightarrow \textbf{30.9\%}$) compared to that in the flat and static environment.

In summary, The results in the quadruped robot tasks support our conclusion in the main text regarding the dynamics shift problem in offline RL — with only modest amounts of target offline data ($3 * 10^4$ steps), DARA-based methods can acquire an adaptive policy for the (both flat and obstructive) target environment and exhibit better performance compared to baselines under the dynamics adaptation setting.

Figure 7: Deployment on the flat and static environment of BCQ.

Figure 8: Deployment on the flat and static environment of CQL.

Figure 9: Deployment on the obstructive and dynamic environment of BCQ.

Figure 10: Deployment on the obstructive and dynamic environment of CQL.

A.3.7 ABLATION STUDY WITH RESPECT TO THE AMOUNT OF TARGET OFFLINE DATA

To see whether the amount of target offline data can be further reduced, we show the results of the ablation study with respect to the amount of target offline data in Tables 15 and 16.

Table 15: Ablation study with respect to the amount of target Hopper data (body mass shift tasks). 10%, 5% and 1% denote training with 10%, 5% and 1% of target offline data, respectively, and additional 100% source offline data.

Body Mass Shift		10%	5%	1%	10%	5%	1%	10%	5%	1%	10%	5%	1%
			BEAR			BRAC-p			BCQ			CQL	
Hopper	Medium-R	33.6	10.7	6.4	28.5	27.7	20.0	32.4	20.5	16.3	3.8	3.2	2.3
	Medium-E	1.2	0.6	0.6	28.6	25.1	20.6	83.4	65.1	55.6	93.3	52.3	38.5

Table 16: Ablation study with respect to the amount of target Walker2d data (body mass shift tasks). 10%, 5% and 1% denote training with 10%, 5% and 1% of target offline data, respectively, and additional 100% source offline data.

Body Mass Shift		10%	5%	1%	10%	5%	1%	10%	5%	1%	10%	5%	1%
			BEAR			BRAC-p			BCQ			CQL	
Walker2d	Medium-R	8.1	5.9	1.3	21.9	21.6	15.8	15.1	12.7	9.7	1.0	1.3	0.5
	Medium-E	2.8	-0.2	-0.3	76.0	2.0	-0.2	57.4	29.7	20.6	94.4	0.1	-0.3

A.4 ENVIRONMENTS AND DATASET

Figure 11: Illustration of the suite of tasks considered in this work: (from left to right) Hopper, Walker2d, Halfcheetah, simulated and real-world quadruped robots. These tasks require the RL agent to learn locomotion gaits for the illustrated characters.

In this work, the tasks include Hopper, Walker2d, HalfCheetah, simulated and real-world quadruped robot, which are illustrated in Figure 11.

Table 17: Dynamics shift for Hopper, Walker2d, and Halfcheetah tasks. For the body mass shift, we change the mass of the body in the source MDP M'. For the joint noise shift, we add a noise (randomly sampling in $[-0.05, +0.05]$) to the actions when we collect the source offline data, *i.e.*, $\mathcal{D}' := \{(\mathbf{s}, \mathbf{a}, r, \mathbf{s}')\} \sim d_{\mathcal{D}'}(\mathbf{s})\pi_{b'}(\mathbf{a}|\mathbf{s})r(\mathbf{s}, \mathbf{a})T'(\mathbf{s}'|\mathbf{s}, \mathbf{a} + \text{noise})$.

	Hopper		Walker2d		HalfCheetah	
	Body Mass Shfit	Joint Noise Shift	Body Mass Shfit	Joint Noise Shift	Body Mass Shfit	Joint Noise Shift
Source	mass[-1]=2.5	action[-1]+noise	mass[-1]=1.47	action[-1]+noise	mass[4]=0.5	action[-1]+noise
Target	mass[-1]=5.0	action[-1]+0	mass[-1]=2.94	action[-1]+0	mass[4]=1.0	action[-1]+0

In the Hopper, Walker2d and HalfCheetah dynamics adaptation setting, we set the D4RL (Fu et al., 2020) benchmark as our target dynamics. For the source dynamics, we change the body mass (body mass shift) or add noises to joints (joint noise shift) of the agents (see Figure 17 for the details) and then collect the source offline dataset in the changed environment. Following Fu et al. (2020), on the changed environment, we collect the 1) "Random" offline data, generated by unrolling a randomly initialized policy, 2) "Medium" offline data, generated by a trained policy with the "medium" level of performance, 3) "Medium-Replay" (Medium-R) offline data, consisting of recording all samples in the replay buffer observed during training until the policy reaches the "medium" level of performance, 4) "Medium-Expert" (Medium-E) offline data, mixing equal amounts of expert demonstrations and "medium" data.

In the sim2real setting (for the quadruped robot), we use the A1 dog from Unitree (Wang, 2020). We collect the target offline data using five target behavior policies in the real-world with changing terrains, as shown in Figure 12, and collect the "Medium", "Medium-Replay" (Medium-R), "Medium-Expert" (Medium-E), "Medium-Replay-Expert" (Medium-R-E) source offline data in the simulator, where "Medium-Replay-Expert" denotes mixing equal amounts of "Medium-Replay" data and expert demonstrations. In Section A.5, we provide the details of how to obtain the target and source behavior policy, so as to collect our target and source offline data.

Figure 12: Real-world terrains (for collecting the target offline data).

We list our tasks properties in Table 18 and provide our collected dataset in supplementary material.

A.5 TRAINING THE (TARGET AND SOURCE) BEHAVIOR POLICY FOR THE QUADRUPED ROBOT

To obtain a behavior policy that can be deployed in simulator (for collecting the source offline data) or real-world (for collecting the target offline data), we introduce the prior knowledge (Iscen et al., 2018) and domain randomization (Tobin et al., 2017; Peng et al., 2018).

Prior Knowledge: To reduce the impact of the foot at the moment of touching the ground during the robot locomotion, we designed a compound cycloid trajectory (Sakakibara et al., 1990) as prior knowledge. In our implementation for the foot trajectory, four aspects are mainly considered: 1) The

Table 18: Statistics for each task in our adaptation setting.

Environment	Dynamics Shift	Task Name	Target (1T)	Source (10S)
Hopper	Body Mass Shfit	Random	10^5 (D4RL)	10^6
		Medium	10^5 (D4RL)	10^6
		Medium-Replay	20092 (D4RL)	10^6
		Medium-Expert	$2 * 10^5$ (D4RL)	$2 * 10^6$
	Joint Noise Shift	Random	10^5 (D4RL)	10^6
		Medium	10^5 (D4RL)	10^6
		Medium-Replay	20092 (D4RL)	10^6
		Medium-Expert	$2 * 10^5$ (D4RL)	$2 * 10^6$
Walker2d	Body Mass Shfit	Random	10^5 (D4RL)	10^6
		Medium	10^5 (D4RL)	10^6
		Medium-Replay	10093 (D4RL)	10^6
		Medium-Expert	$2 * 10^5$ (D4RL)	$2 * 10^6$
	Joint Noise Shift	Random	10^5 (D4RL)	10^6
		Medium	10^5 (D4RL)	10^6
		Medium-Replay	10093 (D4RL)	10^6
		Medium-Expert	$2 * 10^5$ (D4RL)	$2 * 10^6$
HalfCheetah	Body Mass Shfit	Random	10^5 (D4RL)	10^6
		Medium	10^5 (D4RL)	10^6
		Medium-Replay	10100 (D4RL)	10^6
		Medium-Expert	$2 * 10^5$ (D4RL)	$2 * 10^6$
	Joint Noise Shift	Random	10^5 (D4RL)	10^6
		Medium	10^5 (D4RL)	10^6
		Medium-Replay	10100 (D4RL)	10^6
		Medium-Expert	$2 * 10^5$ (D4RL)	$2 * 10^6$
A1 robot (Unitree)	Sim2Real	Medium	$3 * 10^4$ (real-world)	10^6 (simulator)
		Medium-Replay	$3 * 10^4$ (real-world)	10^6 (simulator)
		Medium-Expert	$3 * 10^4$ (real-world)	$2 * 10^6$ (simulator)
		Medium-Replay-Expert	$3 * 10^4$ (real-world)	$2 * 10^6$ (simulator)

robot walks stably without obvious shaking; 2) The joint impact of the robot during the locomotion is small; 3) The joint speed and acceleration of the robot during the locomotion are continuous and smooth; 4) The feet of the robot will not slide when they are in contact with the ground. Similar to Lee et al. (2020), we define a periodic phase variable $\phi_i \in [0.0, 0.6), i = 1, 2, 3, 4$ for each leg, which represents swing phase if $\phi_i \in [0.0, 0.3)$ and contact phase if $\phi_i \in [0.3, 0.6)$. At every time step t, $\phi_i = (t * f_0 + \phi_0[i] + \phi_{\text{offset}}[i])(\text{mod } 2T_m)$ where $T_m = 0.3$, and $f_0 = 1.1$ is the base frequency, and $\phi_0 = [0, 0.3, 0.3, 0]$ is the initial phase. ϕ_{offset} is part of the output of the controller. The trajectory of the swing leg is:

$$\begin{cases} x_i = S \left[\frac{t}{T_m} - \frac{1}{2\pi} \sin \left(\frac{2\pi t}{T_m} \right) \right] + S_0, i = 1, 2 \\ x_i = S \left[\frac{t}{T_m} - \frac{1}{2\pi} \sin \left(\frac{2\pi t}{T_m} \right) \right] - S + S_0, i = 3, 4 \\ y = Y_0 \\ z = H \left[\text{sgn} \left(\frac{T_m}{2} - t \right) (2f_E(t) - 1) + 1 \right] + Z_0 \end{cases},$$

where

$$f_E(t) = \frac{t}{T_m} - \frac{1}{4\pi} \sin \left(\frac{4\pi t}{T_m} \right),$$

and

$$\text{sgn} \left(\frac{T_m}{2} - t \right) = \begin{cases} 1 & 0 \le t < \frac{T_m}{2} \\ -1 & \frac{T_m}{2} \le t < T_m \end{cases}.$$

The trajectory of the standing leg is:

$$
\begin{cases}
x_i = S\left(\frac{2T_m - t}{T_m} + \frac{1}{2\pi}\sin\left(\frac{2\pi t}{T_m}\right)\right) + S_0, i = 1, 2 \\
x_i = S\left(\frac{2T_m - t}{T_m} + \frac{1}{2\pi}\sin\left(\frac{2\pi t}{T_m}\right)\right) - S + S_0, i = 3, 4 \\
y = Y_0 \\
z = Z_0
\end{cases}
.
$$

where $S = 0.14m, H = 0.18m$ are the maximum foot length and height. $S_0 = [0.17, 0.17, -0.2, -0.2], Y_0 = [-0.13, 0.13, -0.13, 0.13], Z_0 = [-0.32, -0.32, -0.32, -0.32]$ are the default target foot position in body frame.

Domain Randomization: To encourage the policy to be robust to variations in the dynamics, we incorporate the domain randomization. In Table 19, we provide the dynamics parameters and their respective range of values.

Table 19: Dynamic parameters and their respective range of values utilized during training.

Parameter	Range
Mass	$[0.95, 1.1]$ ×default value
Inertia	$[0.80, 1.2]$ ×default value
Motor Strength	$[0.80, 1.2]$ ×default value
Latency	$[0, 0.04]$ s
Lateral Friction	$[0.5, 1.25]$ Ns/m
Joint Friction	$[0, 0.05]$ Nm

State Space, Action Space and Reward Function: The action is a 16-dimensional vector consisting of leg phase and target foot position residuals in the body frame. The design of state space and reward function mainly follows the prior work Lee et al. (2020). In Table 20, we provide the state representation.

Table 20: State representation for the behavior policy.

Data	Dimension
Desired direction$\left(\left(^{B}_{IB}\hat{v}_d\right)_{xy}\right)$	2
Euler angle(rpy)	3
Base angular velocity$\left(^{B}_{IB}\omega\right)$	3
Base linear velocity$\left(^{B}_{IB}v\right)$	3
Joint position/velocity$\left(\theta_i, \dot{\theta}_i\right)$	24
FTG phases$(\sin(\phi_i), \cos(\phi_i))$	8
FTG frequencies(f_i)	4
Base frequency(f_o)	1
Joint position error history	24
Joint velocity history	24
Foot target history$\left(\left(r_{f,d}\right)_{t-1,t-2}\right)$	24

The reward function is defined as

$$
0.1r_{lv} + 0.05r_y + 0.05r_{rp} + 0.005r_b + 0.02r_{bc} + 0.025r_s + 2\cdot 10^{-5}r_\tau.
$$

The individual terms are defined as follows.

1) Linear velocity reward r_{lv} :

$$
r_{lv} := \begin{cases} exp(-30|v_{pr} - 0.2|) & v_{pr} < 0.2 \\ 1 & v_{pr} \ge 0.2 \end{cases},
$$

where $v_{pr} = v_{xy} \cdot \hat{v}_{xy}$ is the base linear velocity projected onto the command direction.

2) Yaw angle reward r_y :

$$r_y := exp(-(y - \hat{y})^2),\tag{17}$$

where y and $\hat{y}$ is the yaw and desired yaw angle.

3) Roll and pitch reward r_{rp} :

$$r_{rp} := exp(-1.5 \sum (\phi - [0, \arccos(\frac{< P_{xz}, (0, 0, 1)^T >}{\| P_{xz} \|}) - \pi/2])^2),\tag{18}$$

where ϕ are the roll and pitch angle. $P_{xz} = P_1 - P_4$ or $P_{xz} = P_2 - P_3$, $P_i, i \in [1, 4]$ are the foot position in world frame. The advantage of designing the target pitch angle in this way is to ensure that the body of the robot is parallel to the supporting surface of the stand legs, thereby ensuring that the robot can smoothly over challenge terrain, such as upward stairs.

4) Base motion reward r_b :

$$r_b := exp(-1.5 \sum (v_{xy} - v_{pr} * \hat{v}_{xy})^2) + exp(-1.5 \sum (\omega_{xy})^2),\tag{19}$$

where ω_{xy} are the roll and pitch rates.

5) Body collision reward r_{bc} :

$$r_{bc} := -|I_{body}/I_{foot}|,\tag{20}$$

where I_{body} and I_{foot} are the contact numbers of robot's body parts and foot with the terrain, respectively.

6) Target smooth reward r_s :

$$r_s := -||f_{d,t} - 2f_{d,t-1} + f_{d,t-2}||,\tag{21}$$

where $f_{d,i}(i = t, t - 1, t - 2)$ are the target foot positions in the time-step t, $t - 1$ and $t - 2$.

7) Torqure reward r_τ:

$$r_\tau := -\sum_i |\tau_i|,\tag{22}$$

where τ_i is the joint torques.

Training Details: Both the behavior policy and value networks are Multilayer Perceptron (MLP) with 3 hidden layers, which have 256, 128 and 64 nodes. The activation function is the *Tanh* function, and the optimizer is *Adam*. With the above prior knowledge, domain randomization and reward function, we train our behavior policy with SAC (Haarnoja et al., 2018) in PyBullet (Coumans & Bai, 2016–2021).