DenseMixer: Improving MoE Post-Training via Precise Router Gradient

Abstract

The widely adopted Top-K router in Mixture-of-Experts (MoE) models is mathematically non-differentiable, making them harder to train than dense counterparts. We propose DenseMixer, a simple and effective MoE post-training technique that provides a more precise router gradient estimation by trading in some extra compute. It is universally applicable to TopK routed MoE, operates in a plug-and-play manner, preserves inference-time efficiency, and remains fully compatible with popular training libraries as well as parameter-efficient methods such as LoRA. Extensive experiments demonstrate that DenseMixer consistently outperforms conventional approaches when fine-tuning MoE models across scales (7B–30B), architectures (with and without shared experts), pre-training regimes of the underlying MoE models (from scratch or via up-cycling), and post-training data types (instruction tuning and long chain-of-thought). Furthermore, our analysis on efficiency shows that the additional computation introduced by DenseMixer remains modest, providing substantial improvements at an acceptable cost.

1 Introduction

Mixture-of-Experts (MoE) has emerged as a powerful paradigm for scaling neural networks while maintaining computational efficiency (Comanici et al., 2025; Liu et al., 2024a; Yang et al., 2025). At the same time, MoE has been observed to be harder to train than dense models.

The challenge stems from the cornerstone of MoE – the sparse routing mechanism, which is typically implemented via a TopK router that is mathematically non-differentiable (Shazeer et al., 2017; Liu et al., 2023). This issue blocks straightforward back-propagation and significantly complicates gradient computation, particularly for the router parameters that determine expert selection. The non-differentiability problem forces existing training methods to rely on imprecise gradient approximations, where the problematic TopK operation is treated as having zero gradient during automatic differentiation, or to freeze router parameters entirely during fine-tuning (Unsloth AI, 2025).

To address the non-differentiability problem, as shown in Figure 1, we introduce DenseMixer for MoE post-training, which trades additional compute (on inactive experts during the forward pass) for more precise router gradient estimation. Specifically, DenseMixer employs straight-through estimators (Bengio et al., 2013) to approximate the gradient for the TopK operation, requiring outputs from all experts during training while maintaining sparse computation during inference.

Unlike previous solutions that depends on gradient approximations under restrictive routing assumptions (Wang et al., 2024b) or only works for small activated expert counts (e.g., K=1 or 2) (Liu et al., 2023), DenseMixer is universally applicable to modern MoE models that employ fine-grained TopK routing and activate multiple experts (e.g., K=8). Our method can be applied in a plug-and-play post-training manner, preserves inference behavior, and remains fully compatible with existing training frameworks and parameter-efficient techniques such as LoRA (Hu et al., 2022).

To verify the effectiveness of DenseMixer, we conduct experiments on four representative MoE models spanning scales from 7B to 30B, architectures with or without shared experts, pre-training regimes from scratch or up-cycling, and post-training data types such as instruction or long chain-of-thought data. Across these settings, DenseMixer consistently outperforms conventional MoE training, Expert-Specialized Fine-Tuning (ESFT) (Wang et al., 2024a), frozen-router approaches (Unsloth AI, 2025), DefaultMoE (Panda et al., 2025), ReMoE (Wang et al., 2024b) and SparseMixer (Liu et al., 2023) on a variety of downstream tasks, under both full fine-tuning and LoRA.

Figure 1: Comparison of router-gradient computation in MoE training. Solid arrows denote forward propagation, and dashed arrows denote backpropagation. Conventional training uses outputs from selected experts only, while DenseMixer additionally collects outputs from all experts for more accurate router gradient estimation.

We further evaluate the computational overhead introduced by DenseMixer. Although it adds approximately 46% additional FLOPs (measured on Qwen3-30B-A3B MoE), the actual time overhead is significantly lower—particularly for smaller models or moderate datasets, where the extra cost is almost negligible. This is because DenseMixer increases FLOPs only in the forward pass during post-training, while other factors such as communication often dominate runtime. In post-training scenarios, where dataset scales are much smaller than in pre-training and performance gains are prioritized over efficiency, this overhead remains well within acceptable bounds.

To summarize, our contributions are three-fold:

- We propose DenseMixer, a novel MoE post-training technique that provides a more precise gradient estimation for the router through the straight-through estimator, and thus yields better downstream performance.

- We provide comprehensive empirical validation across multiple MoE scales, architectures, checkpoints, and training scenarios, demonstrating consistent improvements over conventional methods.

- We offer a plug-and-play implementation that can be easily installed, requires minimal code changes and is compatible with existing popular training frameworks, enabling easy adoption for practitioner.

2 Preliminaries

In this section, we provide background and the training challenges of MoE arising from the non-differentiability issue (Section 2.1), and revisit how conventional methods attempt to address it, highlighting the limitations (Section 2.2) that motivate our DenseMixer approach.

2.1 MoE Training Challenges

In Transformer-based MoE models, the standard feed-forward network (FFN) layer is replaced by a Mixture-of-Experts (MoE) layer, consisting of a set of N parallel FFNs referred to as experts: $\{E_0(x), E_1(x), \ldots, E_{N-1}(x)\}$. A lightweight router network – typically a linear layer parameterized by θ – followed by a softmax produces routing probabilities and dynamically selects a subset of experts to activate for each input x (Jacobs et al., 1991; Jordan and Jacobs, 1994; Shazeer et al., 2017).

MoE Forward Propagation. The forward pass consists of the following stages.
(1) The routing weight for each expert E_i is computed with the softmax function as

$$\pi_i = \text{softmax}(x \cdot \theta^T)_i. \tag{1}$$

(2) The output of the MoE layer is computed as the weighted sum of expert outputs, with TopK selection activating only the highest-scoring experts:

$$y = \sum_{i=0}^{N-1} \pi_i \cdot \text{TopK}(\pi)_i \cdot E_i(x), \tag{2}$$

where:

$$\text{TopK}(\pi)_i = \begin{cases} 1, & \text{if } \pi_i \text{ is among the top-}K \\ & \text{values of } \pi, \\ 0, & \text{otherwise.} \end{cases} \tag{3}$$

(3) The final loss is computed using a differentiable loss function:

$$\mathcal{L} = L(y). \tag{4}$$

The forward computation proceeds much like a standard network and scales efficiently because each token activates only a small subset of experts. However, the discrete TopK routing makes the selection step non-differentiable and introduces training challenges to the following backward pass.

MoE Backward Propagation. The gradient computation for all components except the router follows the same procedure as dense models and can be handled by standard backpropagation. The main challenge lies in computing the router's gradient, as it involves non-differentiable operations. To backpropagate from the expert output y to the router parameters θ, we apply the chain rule:

$$\nabla_\theta \mathcal{L} = \frac{\partial \mathcal{L}}{\partial y} \cdot \frac{\partial y}{\partial \theta}$$

$$= \sum_{j=0}^{N-1} \sum_{i=0}^{N-1} \frac{\partial \mathcal{L}}{\partial y} \cdot E_i(x) \cdot \frac{\partial(\pi_i \cdot \mathrm{TopK}(\pi)_i)}{\partial \pi_j} \cdot \frac{\partial \pi_j}{\partial \theta} \tag{5}$$

Non-Differentiable Routing Problem. This problem occurs when calculating the router gradient. 1. In Equation (5), the last term is straightforward to compute:

$$\frac{\partial \pi_j}{\partial \theta} = \frac{\partial \, \mathrm{softmax}(x \cdot \theta^T)_j}{\partial \theta} \tag{6}$$

2. The middle term in Equation (5) expands to:

$$\frac{\partial(\pi_i \cdot \mathrm{TopK}(\pi)_i)}{\partial \pi_j} = \underbrace{\pi_i \cdot \frac{\partial \mathrm{TopK}(\pi)_i}{\partial \pi_j}}_{\text{term1}} \tag{7}$$

$$+ \underbrace{\mathrm{TopK}(\pi)_i \cdot \delta_{ij}}_{\text{term2}} \tag{8}$$

where:

$$\delta_{ij} = \begin{cases} 1, & i = j, \\ 0, & i \neq j. \end{cases} \tag{9}$$

Clearly, the TopK mask is non-differentiable — specifically, the term $\frac{\partial \mathrm{TopK}(\pi)_i}{\partial \pi_j}$ is not defined. Therefore, the router's gradient is not straightforward to compute, blocking standard gradient-based optimization for router parameters (Shazeer et al., 2017; Lepikhin et al., 2021; Fedus et al., 2022).

2.2 How Conventional Method Works

Conventional MoE training method sidesteps the non-differentiable routing issue by treating $\mathrm{TopK}(\pi)$ as constant during backpropagation, thus neglecting the non-differentiable term $\frac{\partial \mathrm{TopK}(\pi)_i}{\partial \pi_j}$, namely it adopts the following approximation:

$$\frac{\partial \mathrm{TopK}(\pi)_i}{\partial \pi_j} \approx 0 \tag{10}$$

Thus, the non-differentiable term becomes:

$$\frac{\partial(\pi_i \, \mathrm{TopK}(\pi)_i)}{\partial \pi_j} \approx \mathrm{TopK}(\pi)_i \cdot \delta_{ij} \tag{11}$$

And finally, the router gradient is computed as:

$$\nabla_\theta \mathcal{L} \approx \nabla_{\text{Conventional}}$$

$$= \sum_{j=0}^{N-1} \sum_{i=0}^{N-1} \frac{\partial \mathcal{L}}{\partial y} \cdot E_i(x) \cdot \mathrm{TopK}(\pi)_i \cdot \delta_{ij} \cdot \frac{\partial \pi_j}{\partial \theta}$$

$$= \sum_{j=0}^{N-1} \frac{\partial \mathcal{L}}{\partial y} \cdot E_j(x) \cdot \mathrm{TopK}(\pi)_j \cdot \frac{\partial \pi_j}{\partial \theta}. \tag{12}$$

Although widely used, the conventional surrogate retains only one of the two terms in the router-gradient decomposition as shown in Eq. 2, discarding the selection-sensitivity term $\pi_i \cdot \frac{\partial \mathrm{TopK}(\pi)_i}{\partial \pi_j}$. While often empirically effective, it is inherently biased — leaving clear room for more faithful and effective estimators for such gradient computation.

3 DenseMixer: Trade Extra Compute for Gradient Precision

In this section, we present DenseMixer, our solution to address the non-differentiability problem in MoE training. We first introduce how our DenseMixer approach works with the straightforward estimator (Section 3.1) and then provide an analysis of its methodology design (Section 3.2).

3.1 DenseMixer Walkthrough

To bridge discrete variables and backpropagation make the gradient approximation more accurate, DenseMixer adopts the **straight-through estimator** (STE) (Bengio et al., 2013).

$$\frac{\partial \mathrm{TopK}(\pi)_i}{\partial \pi_j} \approx \delta_{ij} \tag{13}$$

This means:

$$\frac{\partial(\pi_i \, \mathrm{TopK}(\pi)_i)}{\partial \pi_j} \approx (\pi_i + \mathrm{TopK}(\pi)_i) \cdot \delta_{ij} \tag{14}$$

Finally:

$$\nabla_\theta \mathcal{L} \approx \nabla_{\text{DenseMixer}}$$

$$= \sum_{j=0}^{N-1} \sum_{i=0}^{N-1} \frac{\partial \mathcal{L}}{\partial y} \cdot E_i(x) \cdot (\pi_i + \text{TopK}(\pi)_i) \cdot \delta_{ij}$$

$$\cdot \frac{\partial \pi_j}{\partial \theta}$$

$$= \sum_{j=0}^{N-1} \frac{\partial \mathcal{L}}{\partial y} \cdot E_j(x) \cdot (\pi_j + \text{TopK}(\pi)_j) \cdot \frac{\partial \pi_j}{\partial \theta}. \tag{15}$$

Intuitively, STE pretends that the TopK selection is an identity function with respect to the router logits during backpropagation. In practice, we implement this by: 1. Forward — computing with the original hard TopK as before; 2. Backward — overriding the gradient of the TopK node to be the identity.

Handling Normalized TopK. Some recently released MoE models (Yang et al., 2025) adopt `normalized_topk_prob` implementation, which normalizes the expert weights as follows:

$$y_{\text{normalized}} = \sum_{i=0}^{N-1} \frac{\pi_i \cdot \text{TopK}(\pi)_i}{\sum_{k=0}^{N-1} \pi_k \cdot \text{TopK}(\pi)_k} \cdot E_i(x) \tag{16}$$

Such normalization makes the gradient computation even more complicated, as both the numerator and denominator have the non-differentiable TopK term. We address this by letting gradients flow through the normalization denominator only for Top-K experts, while treating it as a constant (detached) for non-Top-K experts, providing a practical solution for modern MoE architectures.

3.2 DenseMixer Analysis

The core idea of DenseMixer can be summarized as trading in extra compute for more precise gradient estimation for the router. Different from conventional method that backpropagates only through active experts, DenseMixer enables the MoE model to perform backpropagation through all experts to achieve a better approximation of the router gradient.

Computation Overhead. A natural drawback of using DenseMixer's gradient approximation ($\nabla_{\text{DenseMixer}}$) is that it requires the outputs of all experts (i.e., $E_j(x)$ for all $j \in [0, N-1]$) for a given input x, while conventional method's gradient approximation ($\nabla_{\text{Conventional}}$) only requires those of the TopK selected experts. This means that DenseMixer requires the MoE layer to be densely activated during forward pass, which introduces more compute than the normal case.

Nevertheless, in the context of MoE post-training, computational cost is typically less critical than in large-scale pre-training. DenseMixer therefore provides a practical trade-off: it incurs only a single additional forward pass on those inactive experts — distinct from simply setting K equal to the total number of experts — and achieves improved router gradients at a manageable cost. This makes the additional overhead acceptable in practice, considering the performance gain it brings.

Compatibility with Existing MoEs. Previous methods for addressing router non-differentiability, such as SparseMixer (Liu et al., 2023) and Re-MoE (Wang et al., 2024b), rely on models being pre-trained with specialized routing mechanisms. This limits their applicability to post-training or fine-tuning, since most modern open-source MoEs are pre-trained with the standard TopK router. Moreover, sampling-based approaches like SparseMixer, which replace TopK with stochastic sampling, are only effective when K is very small (e.g., 1–2). They fail to scale to modern MoEs that typically employ fine-grained experts with much larger activation sizes (e.g., $K = 8$, 16, or more).

In contrast, DenseMixer is directly compatible with TopK routed MoEs, supports arbitrary numbers of activated experts, and delivers consistent post-training improvements without requiring any changes to the pre-training procedure. This plug-and-play property enables us to further provide an easy-to-use implementation package that can be seamlessly applied to existing MoE models.

4 Experiments

In this section, we verify the effectiveness of DenseMixer across multiple MoE models and training scenarios. We first introduce the experimental setup (Section 4.1), then present comparative results (Section 4.2), and conclude with efficiency analysis (Section 4.4).

4.1 Experimental Setup

Models. To validate the generality of DenseMixer, we select four base models

pre-trained with diverse configurations, including OLMoE-1B-7B (Muennighoff et al., 2025a), Qwen1.5-MoE-A2.7B[1], DeepSeek-V2-Lite (DeepSeek-AI, 2024), MiniCPM-MoE-8x2B (OpenBMB, 2024) and Qwen3-30B-A3B-Base (Yang et al., 2025). The detailed configurations of these models are summarized in Table 1.

Datasets. We adopt two data configurations: a *general task* configuration for lightweight backbones and a *long CoT* configuration for the stronger backbone model.

- **General tasks.** For OLMoE-1B–7B, Qwen1.5-MoE-A2.7B, and DeepSeek-V2-Lite, we follow the training and test sets from (Wang et al., 2024a). The training set covers GSM8K (math) (Cobbe et al., 2021), CodeAlpaca (Chaudhary, 2023), intent classification, law, summarization, and translation (Wang et al., 2024a). The test set covers GSM8K (math) (Cobbe et al., 2021), MBPP(Austin et al., 2021), and HumanEval (coding) (Chen et al., 2021), as well as intent classification, law, summarization, and translation (Wang et al., 2024a).

- **Long CoT.** For Qwen3-30B-A3B-Base, due to its improved pre-training techniques, post-training on the tasks above yields limited gains. Therefore, we focus on solving more challenging competition-level math and coding questions by generating long chain-of-thoughts (CoT). Specifically, for math reasoning, we train the model with a filtered subset of the Stanford S1 dataset (Muennighoff et al., 2025b) (about 1,000 examples with reasoning trajectories distilled from DeepSeek-R1 (DeepSeek-AI, 2025)), and evaluate the model on GPQA (Rein et al., 2024), AIME (Mathematical Association of America, 2025), MATH-500 (Hendrycks et al., 2021), OlympiadBench (He et al., 2024). For coding, we train the model with a filtered subset of the Llama-Nemotron Post-Training Dataset (Nathawani et al., 2025) (about 35,000 coding examples), and evaluate the model on HumanEval(Chen et al., 2021), HumanEval+ (Team, 2023–2025), MBPP (Austin et al., 2021), and LiveCodeBench (Jain et al., 2024).

The training and evaluation datasets statistics of the general tasks are shown below and those of the Long CoT tasks are provided in Appendix D.

Baselines Training Methods. We compare DenseMixer against several representative MoE training methods that have been widely adopted.

- **Conventional**: Standard MoE training method which treats the non-differentiable Top-K operation as having zero gradient in automatic differentiation.
- **ESFT**: Expert-Specialized Fine-Tuning (Wang et al., 2024a) proposed by DeepSeekAI, which updates only a pre-selected subset of experts for a given task. We include both ESFT-gate (selection based on average gating scores) and ESFT-token (selection based on token-selection ratios) for fair comparison.
- **Frozen Router**: Freezing the router and only updating other components in MoE – as suggested by practitioners for stable MoE finetuning[2].

We also compare these methods in parameter-efficient fine-tuning (PEFT) settings, where we apply LoRA to all modules except for the router.

Evaluation Setup. For each method, we conduct a grid search on training hyperparameters (learning rate and batch size) and report the best performance. We evaluate models across multiple downstream tasks relevant to each model's domain, measuring task-specific metrics such as accuracy for classification tasks and pass rates for coding tasks. Specifically, for the long CoT task, we report the evaluation metrics under three sets of decoding hyperparameters (temperature and top_p) due to the instability of long CoT evaluation. The details are provided in Appendix C.

4.2 Main Results

Extensive experimental results demonstrate that DenseMixer consistently outperforms conventional MoE training across MoE models of varying scales, architectures, and pre-training recipes, as well as across diverse training and evaluation datasets. This performance advantage holds for both full fine-tuning and parameter-efficient fine-tuning methods (e.g., LoRA). This is shown by Table 3 under General Tasks configuration, and Table 4 and Table 5 under Long CoT configuration.

Such performance improvement remains robust under different hyperparameters for LLM generation, for example, under different popular temperature and Top-p combinations. This is demonstrated

---

[1]`https://huggingface.co/Qwen/Qwen1.5-MoE-A2.7B`

[2]`https://unsloth.ai/docs/models/qwen3-how-to-run-and-fine-tune#qwen3-moe-models-fine-tuning`

Table 1: Information of base MoE models used in our experiments.

Model Name	Active Param.	Total Param.	Active/Total Expert Num.	Shared Expert Num.	Context Length	Normalize TopK Prob	Training Strategy
OLMoE-1B-7B	1B	7B	8 / 64	0	4k	False	from scratch
Qwen1.5-MoE-A2.7B	2.7B	14B	8 / 64	4	8k	False	up-cycling
DeepSeek-V2-Lite	2.4B	16B	6 / 64	2	32k	False	from scratch
Qwen3-30B-A3B-Base	3B	30B	8 / 128	0	32k	True	from scratch

Table 2: Training and test sample sizes for different datasets.

	GSM	MBPP	HE	Intent	Law	Sum.	Trans.
#Train	7473	22000	22000	7280	927	19587	11639
#Test	1319	500	164	500	100	100	100

Here, "HE" denotes HumanEval, "Sum." denotes Summarization dataset, and "Trans." denotes Translation dataset.

extensively by Table 4 and Table 5.

Interestingly, as shown in Table 3, we find that Frozen Router can occasionally outperform Conventional Training, where the router is trained end-to-end with imprecise gradients. However, it consistently underperforms DenseMixer, which benefits from more accurate gradient signals for the router. Therefore, we confirm that the routing training is important in MoE optimization.

4.3 Additional Results

In addition, we compare DenseMixer with several representative MoE training methods that are designed to mitigate the non-differentiability of sparse routing. Specifically, these methods seek to improve gradient propagation through some kind of "differentiable" router, which is different than the standard TopK routing.

- **DefaultMoE** (Panda et al., 2025): Sparse expert activation is preserved during training, while exponential moving average–based substitutions are used for inactive expert outputs to enable dense gradient propagation to the router.
- **ReMoE** (Wang et al., 2024b): The standard top-k routing is replaced with a ReLU-based routing mechanism to alleviate the non-differentiability of hard expert selection.
- **SparseMixer** (Liu et al., 2023): A scalable approximation of router gradients is constructed via an ordinary differential equation (ODE) formulation, while sparse computation is maintained. It only works well for small K values (K=1, 2).

As shown in Table 7 (Appendix A), we compare DenseMixer with all these methods using Qwen1.5-MoE and find that our method consis-

tently outperforms the alternatives. Moreover, since SparseMixer is only effective for small routing widths (Top-k with $k \in 1, 2$), we additionally evaluate a Top-1 activated MoE variant of MiniCPM [3] for a fairer comparison. DenseMixer still achieves better performance in this setting.

Finally, we note that these baselines were originally proposed for MoE *pre-training*, which require large-scale data for training a good router and thus does not directly suit for MoE post-training. In contrast, DenseMixer does not depend on such large-scale router training and remains effective in the post-training setting.

4.4 Efficiency Analysis

Computational Overhead. Though DenseMixer requires extra computation on inactive experts, the time consumption does not grow linearly with the number of experts. It only requires an extra forward pass and does not require backward gradient computation on inactive experts.

For Qwen3-30B-A3B, DenseMixer incurs approximately 1.46× the FLOPs compared to conventional training. The detailed FLOPs analysis in table 6 shows that DenseMixer mainly requires more FLOPs in the forward pass. Overall, since post-training prioritizes performance over efficiency and typically involves substantially smaller datasets than pre-training, the extra computation is acceptable during the post-training stage, and the peak memory usage does not increase substantially.

Training Time Comparison. We provide actual training time comparisons across different scales of model datasets.

As shown in Table 8 (Appendix B), the training time overhead of DenseMixer is <20% on Qwen1.5-MoE, and $\sim 30\%$ on Qwen3-MoE. Though increased with the size of model and training data, it is still acceptable in most post-training scenarios.

Overall, the results demonstrate that DenseMixer consistently outperforms conventional MoE train-

---
[3] https://huggingface.co/openbmb/MiniCPM-MoE-8x2B

Table 3: **Post-training results on general tasks with three MoE backbones.** We highlight the best score for each task in dark green and the second in light green for each setting.

Backbone (Total Param.)	Method	GSM	MBPP	HE	Intent	Law	Sum.	Trans.	Avg
OLMoE (7B)	Base Model	15.85	19.80	10.97	0.20	5.70	7.40	11.09	10.14
	Frozen Router	44.88	17.80	7.23	72.80	22.50	36.05	28.29	32.79
	Conventional	45.94	23.40	18.92	74.60	22.35	35.99	26.89	35.44
	DenseMixer	49.00	25.12	20.73	77.40	23.02	40.64	32.55	38.35
	Frozen Router +LoRA	45.03	24.20	17.07	55.80	21.30	37.70	28.19	32.76
	Conventional +LoRA	44.58	24.20	15.85	60.20	21.60	37.30	26.22	32.85
	DenseMixer+LoRA	45.38	26.20	16.48	66.60	24.70	40.80	29.43	35.66
	ESFT-gate	43.06	20.80	14.02	21.20	22.39	19.50	17.37	22.62
	ESFT-token	43.82	19.60	12.80	20.80	22.60	17.80	16.67	22.01
Qwen1.5-MoE (14B)	Base Model	38.69	38.84	32.31	16.83	18.20	28.29	16.53	27.10
	Frozen Router	53.37	35.20	37.10	82.20	33.01	38.29	32.75	44.56
	Conventional	53.42	34.60	36.43	81.80	29.25	37.80	33.02	43.76
	DenseMixer	55.16	35.40	39.68	83.40	33.83	40.56	33.90	45.99
	Frozen Router +LoRA	46.77	31.40	36.58	71.00	30.30	30.19	28.08	39.19
	Conventional +LoRA	43.89	34.00	38.41	64.80	28.80	37.99	26.14	39.15
	DenseMixer+LoRA	47.24	35.40	38.41	71.80	31.80	40.20	29.25	42.01
	ESFT-gate	50.72	34.00	36.59	76.40	27.10	35.89	28.49	41.31
	ESFT-token	52.76	35.80	37.20	76.00	28.20	33.39	28.86	41.74
DeepSeek-V2-Lite (16B)	Base Model	19.00	43.00	27.44	3.00	14.90	16.50	16.20	12.65
	Frozen Router	32.95	46.60	31.11	69.30	28.10	43.70	24.80	41.48
	Conventional	48.50	46.00	31.71	81.80	29.70	43.00	24.30	44.70
	DenseMixer	51.50	47.00	32.32	82.40	32.10	45.80	25.36	46.42
	Frozen Router +LoRA	48.06	45.20	34.76	68.40	24.10	46.20	32.60	42.83
	Conventional +LoRA	50.60	46.50	35.66	70.20	22.90	39.90	28.80	40.45
	DenseMixer+LoRA	52.16	46.80	36.59	71.00	24.30	47.80	33.80	44.23
	ESFT-gate	29.49	43.90	28.05	25.20	16.80	15.20	17.20	15.51
	ESFT-token	28.66	43.80	26.22	26.00	18.00	16.00	17.21	19.30

"HE" denotes HumanEval, "Sum." denotes Summarization, and "Trans." denotes Translation.

Table 4: Results on post-training Qwen3-30B-A3B-Base across different decoding configurations (Math Benchmarks). DenseMixer consistently surpasses conventional training methods.

Method	Temp & Top-p	GPQA (avg@8)	AIME2024 (avg@32)	AIME2025 (avg@32)	Olympiad (avg@1)	MATH500 (avg@1)
Base Model	0.6 & 0.95	38.88	20.63	7.71	34.81	72.80
	0.7 & 0.8	39.89	20.53	8.33	33.92	75.40
	1.0 & 0.7	36.36	18.75	8.75	31.70	68.00
Conventional	0.6 & 0.95	54.80	61.56	45.63	57.33	93.40
	0.7 & 0.8	54.23	61.67	44.27	55.41	92.20
	1.0 & 0.7	56.55	**63.65**	46.15	**59.11**	93.00
DenseMixer	0.6 & 0.95	**58.52**	**63.85**	45.83	58.51	93.60
	0.7 & 0.8	**55.80**	**63.13**	45.31	57.18	93.00
	1.0 & 0.7	**58.14**	62.71	**47.50**	57.77	**93.80**

Table 5: Results on post-training Qwen3-30B-A3B-Base across different decoding configurations (Code Benchmarks and Average). DenseMixer consistently outperforms conventional training.

Method	Temp & Top-p	HumanEval (avg@4)	HumanEval+ (avg@4)	MBPP (avg@1)	LiveCodeBench (avg@4)	Avg
Base Model	0.6 & 0.95	65.24	60.06	53.60	16.85	48.94
	0.7 & 0.8	62.80	61.12	55.60	16.48	49.00
	1.0 & 0.7	62.65	59.14	49.80	13.26	46.21
Conventional	0.6 & 0.95	92.23	86.89	80.80	32.26	67.21
	0.7 & 0.8	91.01	85.37	76.80	29.39	65.59
	1.0 & 0.7	90.85	86.59	79.00	33.42	67.59
DenseMixer	0.6 & 0.95	**93.59**	**89.02**	**82.00**	**34.31**	**68.80**
	0.7 & 0.8	**91.92**	**86.89**	**80.80**	**31.89**	**67.32**
	1.0 & 0.7	**93.29**	**88.87**	**84.39**	**34.40**	**68.99**

Table 6: FLOPs and memory usage analysis for Qwen3-30B-A3B.

Method	Fwd TFLOPs	Bwd TFLOPs	Total TFLOPs	Peak mem (GB)
Conventional	16.85	33.70	50.54	157.93
DenseMixer	40.04	33.70	73.74	164.96
Ratio	**2.38×**	**1.00×**	**1.46×**	**1.04×**

Note. Fwd = Forward, Bwd = Backward.

ing methods across different model scales, architectures, and training scenarios, while maintaining reasonable computational overhead suitable for post-training applications.

5 Related Work

Current approaches to MoE training handle the non-differentiability problem through several paradigms, each with inherent limitations.

SparseMixer (Liu et al., 2023) and Grin-MoE (Liu et al., 2024b) use numerical ODE methods with the mid-point method to provide scalable gradient approximations for expert routing while maintaining sparse computation. However, both methods require sampling over the routing distribution, which works well when few experts are activated (1-2) but becomes computationally challenging and difficult to implement efficiently for modern MoEs (e.g., Qwen3-MoE (Yang et al., 2025)) that typically activate many more experts (8, 16, or higher). DenseMixer does not have such restriction and proves to work well on 8 active experts in the training of modern MoEs.

ReMoE (Wang et al., 2024b) addresses the non-differentiability of expert routing by replacing the discrete Top-K selection with a fully differentiable ReLU-based routing mechanism. This design enables end-to-end gradient propagation without relying on surrogate gradient estimators. However, ReMoE introduces restrictive routing assumptions that deviate from the fine-grained Top-K routing widely adopted in modern large-scale MoE systems.In contrast, DenseMixer preserves the original Top-K routing mechanism and directly improves routing gradient quality through exact expert output computation, making it universally applicable to modern MoE models.

DS-MoE (Pan et al., 2024) employs dense computation across all experts during training combined with sparse inference, requiring dense activation during both forward and backward passes, which is much slower,while our DenseMixer only requires dense activation during the forward pass. Because the dominant training time cost lies in the backward pass, and DenseMixer does not require dense activations in this phase, it is significantly more efficient than DS-MoE. DefaultMoE (Panda et al., 2025) shares a similar philosophy by maintaining sparse training while providing dense gradients through substituting inactive expert outputs with exponential moving averages of previously computed expert values in the same batch. However, such approximations are less precise than DenseMixer's direct computation approach, and notably, the performance improvements Default-MoE achieves after pre-training on large token volumes are comparable to or smaller than what DenseMixer achieves through post-training on significantly fewer tokens. Additionally, DefaultMoE focuses on pre-training scenarios where computational efficiency is relatively critical, while we target the more practical post-training setting where the extra computational cost is more acceptable in exchange for improved gradient precision and consistently better performance.

6 Conclusion

We confirm that the non-differentiability of Top-K routing is a key obstacle to effective MoE training. By trading an extra forward pass on inactive experts, DenseMixer enables more precise routing gradients, consistently improving post-training quality as measured by downstream performance, beyond conventional approaches under various settings.

We further contextualize DenseMixer with prior methods that address the non-differentiability of sparse routing, including DefaultMoE, ReMoE, and SparseMixer. These approaches typically require the routing or gradient approximation mechanisms to remain consistent between pre-training and post-training for stable optimization, which limits their flexibility when applied only in post-train. In contrast, DenseMixer can be applied purely at the post-training stage. Incurring an additional forward pass on inactive experts, DenseMixer yields more accurate routing gradients while preserving the original architecture and training pipeline, resulting in consistent post-training gains.

Limitations

DenseMixer introduces an additional forward pass over all experts, which raises the computational cost of training. On Qwen3-30B-A3B this amounts to roughly 46 percent more FLOPs, and the wall-clock overhead reaches about one third on our largest model and dataset. This cost makes the method less attractive in settings with limited compute, where the gain in routing accuracy may not justify the added expense. We also restrict our study to post-training, namely supervised fine-tuning and parameter-efficient adaptation. We do not examine how the method behaves during pre-training, where the same overhead would compound over far larger token budgets.

The largest model we evaluate has 30 billion parameters, so the effectiveness of DenseMixer on substantially larger mixture-of-experts models remains unverified. Our experiments also center on Top-K routing under supervised post-training. Whether the approach transfers to other routing mechanisms, or to reinforcement learning style training, is a question we leave to future work.

Ethical Considerations

All datasets used in this work (GSM8K (Cobbe et al., 2021),MBPP (Austin et al., 2021),HumanEval (Chen et al., 2021), Intent classification, Law, Summary, and Translation (Wang et al., 2024a), Stanford S1 (Muennighoff et al., 2025b), Llama-Nemotron-Post-Training-Dataset (Nathawani et al., 2025)) are publicly available academic benchmarks that do not contain personally identifiable or sensitive information. All datasets and base models are publicly released, and we use them in accordance with their respective licenses and intended research use. Our study focuses on post-training mixture-of-experts (MoE) models and does not involve the collection of new human-subject data. As with other LLM fine-tuning methods, models trained with DenseMixer may still produce incorrect, biased, or misleading content, and code-related outputs may contain insecure or faulty patterns. Our method does not eliminate these risks, and deployments in high-stakes settings should include appropriate safeguards (e.g., content filtering, human oversight, and domain-specific evaluations). The potential societal benefits of this work include improved performance of MoE models, which may help humans in various domains.

References

Jacob Austin, Augustus Odena, Maxwell Nye, Maarten Bosma, Henryk Michalewski, David Dohan, Ellen Jiang, Carrie Cai, Michael Terry, Quoc V. Le, and Charles Sutton. 2021. Program synthesis with large language models. *arXiv preprint arXiv:2108.07732*.

Yoshua Bengio, Nicholas Léonard, and Aaron C. Courville. 2013. Estimating or propagating gradients through stochastic neurons for conditional computation. *arXiv preprint arXiv:1308.3432*.

Sahil Chaudhary. 2023. Code alpaca: An instruction-following llama model for code generation. https://github.com/sahil280114/codealpaca. Accessed: 2025-09-25.

Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde de Oliveira Pinto, Jared Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, and 1 others. 2021. Evaluating large language models trained on code. *arXiv preprint arXiv:2107.03374*.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, Christopher Hesse, and John Schulman. 2021. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*.

Gheorghe Comanici, Eric Bieber, Mike Schaekermann, Ice Pasupat, Noveen Sachdeva, Inderjit Dhillon, Marcel Blistein, Ori Ram, Dan Zhang, Evan Rosen, and 1 others. 2025. Gemini 2.5: Pushing the frontier with advanced reasoning, multimodality, long context, and next generation agentic capabilities. *arXiv preprint arXiv:2507.06261*.

DeepSeek-AI. 2024. Deepseek-v2: A strong, economical, and efficient mixture-of-experts language model. *Preprint*, arXiv:2405.04434.

DeepSeek-AI. 2025. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *Preprint*, arXiv:2501.12948.

William Fedus, Barret Zoph, and Noam Shazeer. 2022. Switch transformers: Scaling to trillion parameter models with simple and efficient sparsity. *Journal of Machine Learning Research*, 23(120):1–39.

Chaoqun He, Renjie Luo, Yuzhuo Bai, Shengding Hu, Zhen Leng Thai, Junhao Shen, Jinyi Hu, Xu Han, Yujie Huang, Yuxiang Zhang, and 1 others. 2024. Olympiadbench: A challenging benchmark for promoting agi with olympiad-level bilingual multimodal scientific problems. *arXiv preprint arXiv:2402.14008*.

Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arora, Steven Basart, Eric Tang, Dawn Song, and Jacob Steinhardt. 2021. Measuring mathematical problem solving with the math dataset. *NeurIPS*.

Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Lu Wang, and Weizhu Chen. 2022. Lora: Low-rank adaptation of large language models. In *International Conference on Learning Representations (ICLR)*.

Robert A Jacobs, Michael I Jordan, Steven J Nowlan, and Geoffrey E Hinton. 1991. Adaptive mixtures of local experts. *Neural computation*, 3(1):79–87.

Naman Jain, King Han, Alex Gu, Wen-Ding Li, Fanjia Yan, Tianjun Zhang, Sida Wang, Armando Solar-Lezama, Koushik Sen, and Ion Stoica. 2024. Livecodebench: Holistic and contamination free evaluation of large language models for code. *arXiv preprint arXiv:2403.07974*.

Michael I Jordan and Robert A Jacobs. 1994. Hierarchical mixtures of experts and the em algorithm. *Neural computation*, 6(2):181–214.

Dmitry Lepikhin, HyoukJoong Lee, Yuanzhong Xu, Dehao Chen, Orhan Firat, Yanping Huang, Maxim Krikun, Noam Shazeer, and Zhifeng Chen. 2021. Gshard: Scaling giant models with conditional computation and automatic sharding. In *Proceedings of the International Conference on Learning Representations (ICLR)*. Poster.

Aixin Liu, Bei Feng, Bing Xue, Bingxuan Wang, Bochao Wu, Chengda Lu, Chenggang Zhao, Chengqi Deng, Chenyu Zhang, Chong Ruan, and 1 others. 2024a. Deepseek-v3 technical report. *arXiv preprint arXiv:2412.19437*.

Liyuan Liu, Jianfeng Gao, and Weizhu Chen. 2023. Sparsemixer: Mixture-of-experts via learned sparse backpropagation. *arXiv preprint arXiv:2310.00811*.

Liyuan Liu and 1 others. 2024b. Grinmoe: Gradient-informed mixture-of-experts. *arXiv preprint arXiv:2409.12136*.

Mathematical Association of America. 2025. American invitational mathematics examination (aime). https://maa.org/maa-invitational-competitions/. Official competition; credit problems to MAA AMC.

Niklas Muennighoff, Luca Soldaini, Dirk Groeneveld, Kyle Lo, Jacob Morrison, Sewon Min, Weijia Shi, Pete Walsh, Oyvind Tafjord, Nathan Lambert, Yuling Gu, Shane Arora, Akshita Bhagia, Dustin Schwenk, David Wadden, Alexander Wettig, Binyuan Hui, Tim Dettmers, Douwe Kiela, and 5 others. 2025a. Olmoe: Open mixture-of-experts language models. In *International Conference on Learning Representations (ICLR)*.

Niklas Muennighoff, Zitong Yang, Weijia Shi, Xiang Lisa Li, Li Fei-Fei, Hannaneh Hajishirzi, Luke Zettlemoyer, Percy Liang, Emmanuel Candès, and Tatsunori Hashimoto. 2025b. s1: Simple test-time scaling. *arXiv preprint arXiv:2501.19393*.

Dhruv Nathawani, Igor Gitman, Somshubra Majumdar, Evelina Bakhturina, Ameya Sunil Mahabaleshwarkar, , Jian Zhang, and Jane Polak Scowcroft. 2025. Nemotron-Post-Training-Dataset-v1.

OpenBMB. 2024. Minicpm-moe-8x2b technical report. Technical report, Open Lab for Big Model Base (OpenBMB). Technical report on the Mixture-of-Experts variation of MiniCPM.

Bowen Pan, Yikang Shen, Haokun Liu, Mayank Mishra, Gaoyuan Zhang, Aude Oliva, Colin Raffel, and Rameswar Panda. 2024. Dense training, sparse inference: Rethinking training of mixture-of-experts language models. *arXiv preprint arXiv:2404.05567*.

Ashwinee Panda, Vatsal Baherwani, Zain Sarwar, Benjamin Therien, Supriyo Chakraborty, and Tom Goldstein. 2025. Dense backpropagation improves training for sparse mixture-of-experts. *arXiv preprint arXiv:2504.12463*.

David Rein, Betty Li Hou, Asa Cooper Stickland, Jackson Petty, Richard Yuanzhe Pang, Julien Dirani, Julian Michael, and Samuel R Bowman. 2024. Gpqa: A graduate-level google-proof q&a benchmark. In *First Conference on Language Modeling*.

Noam Shazeer, Amin Mirhoseini, Niki Maziarz, Andy Davis, Quoc V. Le, and Geoffrey Hinton. 2017. Outrageously large neural networks: The sparsely-gated mixture-of-experts layer. In *Proceedings of the International Conference on Learning Representations (ICLR)*. Workshop Track.

EvalPlus Team. 2023–2025. Evalplus: Rigorous evaluation framework for llm4code (humaneval+, mbpp+). https://github.com/evalplus/evalplus. Accessed: 2025-09-25.

Unsloth AI. 2025. Qwen3: How to run & fine-tune. Section "Qwen3 MOE models fine-tuning" states router layer fine-tuning is disabled by default.

Zihan Wang, Deli Chen, Damai Dai, Runxin Xu, Zhuoshu Li, and Yu Wu. 2024a. Expert-specialized fine-tuning for sparse architectural large language models. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing (EMNLP)*.

Ziteng Wang, Jun Zhu, and Jianfei Chen. 2024b. Remoe: Fully differentiable mixture-of-experts with relu routing. *arXiv preprint arXiv:2412.14711*.

An Yang and 1 others. 2025. Qwen3 technical report. Technical report, arXiv.

A Additional Comparison with Pre-Training Baselines

B Training Time Comparison

C Hyperparameters

We use the following hyperparameters across different models. Experiments were run on $2\times$A100,

Table 7: Additional comparison results. We highlight the best score in each column within the same backbone block.

Backbone	Method	GSM	MBPP	HE	Intent	Law	Sum.	Trans.	Avg
Qwen1.5-MoE	DefaultMoE*	51.00	33.20	35.33	80.60	31.20	38.40	24.00	41.96
	SparseMixer*	1.30	0.00	3.90	3.80	3.40	2.10	3.50	2.57
	ReMoE*	46.30	33.00	36.80	60.80	25.50	25.80	16.99	35.03
	DenseMixer	55.16	35.40	39.68	83.40	33.83	40.56	33.90	45.99
MiniCPM (8×2B)	DefaultMoE*	53.18	39.62	39.40	70.00	28.20	37.80	16.00	40.89
	SparseMixer*	42.20	34.68	40.82	63.40	23.30	29.70	16.80	35.08
	DenseMixer	56.10	40.60	44.50	72.40	29.70	41.80	17.40	43.21

Table 8: Training time comparison indicating acceptable overhead in post-training scenarios.

Model	Dataset	Conventional	DenseMixer	Overhead
Qwen1.5-MoE (14B)	Intent (7K)	22 min	24 min	9%
	Law (1K)	8.5 min	9.5 min	12%
	Summary (19K)	1.2 h	1.4 h	17%
	Translation (11K)	39 min	45 min	15%
Qwen3-MoE (30B)	S1 (1K)	2.8 h	3.6 h	29%
	Nemotron-Code (35K)	21 h	28 h	33%

$4\times$H200, or $8\times$H200 GPUs (depending on the setting). We set warmup_ratio = 0.1 and use bf16 as the data type. Using these settings, our results can be reproduced on the same or equivalent hardware. We use grid search to select the optimal hyperparameters. The grid search rage of learning rate, batch size are shown as follows:

Table 9: **Search ranges for hyperparameters.**

Model	Method	BS	LR
Qwen1.5-MoE	full	{32, 64, 128}	{5e-7, 1e-6, 2e-6, 5e-6, 1e-5, 2e-5, 3e-5, 4e-5}
	lora	{32, 64, 128}	{5e-5, 1e-4, 2e-4, 3e-4, 4e-4, 5e-4, 6e-4, 8e-4}
OLMoE	full	{64, 128, 256, 512}	{5e-7, 1e-6, 2e-6, 5e-6, 1e-5, 2e-5, 3e-5, 4e-5}
	lora	{128, 256, 512}	{5e-5, 1e-4, 2e-4, 3e-4, 4e-4, 5e-4, 6e-4, 8e-4}
DeepSeek-V2-Lite	full	{32, 64, 128}	{5e-7, 1e-6, 2e-6, 5e-6, 1e-5, 2e-5, 3e-5, 4e-5}
	lora	{32, 64, 128}	{5e-7, 1e-6, 2e-6, 5e-6, 1e-5, 2e-5, 3e-5, 4e-5}
Qwen3-30B-A3B	full	{8, 16, 32}	{5e-6, 1e-5, 2e-5, 3e-5, 4e-5, 5e-5}

D Data Statistics for Long CoT Tasks

The training and test sample sizes of Long Cot Tasks are shown in table 10.

Table 10: Training and test sample sizes for different datasets.

	AIME 2024	AIME 2025	MATH-500	Olympiad Bench	GPQA_Diamond	MBPP	HumanEval	HumanEvalPlus	LiveCodeBench
#Training Samples	1000	1000	1000	1000	1000	35000	35000	35000	35000
#Test Samples	30	30	500	674	100	500	164	164	~ 500