VRPO: Rethinking Value Modeling for Robust RL under Noisy Supervision in LLM Post-Training

Abstract

Reinforcement Learning (RL) in real-world environments often suffers from ambiguous or incomplete reward supervision, which undermines policy stability and generalization. Such noise may cause models to ignore key information or even collapse in advantage estimation. We find that a strong value model is essential for absorbing unstable signals and producing reliable advantages, offering denser and more robust supervision than the reward model. To better optimize noisy supervision, we propose VRPO, a framework that enhances value modeling for robust RL in LLM post-training. VRPO integrates (1) auxiliary losses guided by entropy and perplexity from a frozen language model, and (2) a variational information bottleneck, enabling the value model to filter noise and capture key words. This design allows the value model to correct noise rewards and generate more reliable advantage estimates, transforming it from a passive predictor into an active noise regulator. Experiments on multi-turn dialogue, math reasoning, and science QA with both rule-based and model-based rewards show that VRPO consistently outperforms baselines such as PPO and GRPO. Our work highlight the central role of the value model in Robust RL and provide a principled and practical approach to policy optimization under noisy supervision.

1 Introduction

Reinforcement Learning has achieved remarkable success across a wide range of applications (Perolat et al., 2022; Chen et al., 2022; Bellemare et al., 2020; Zhou et al., 2020; Yue et al., 2024; Caregnato-Neto et al., 2024). However, deploying RL in real-world scenarios often involves noisy or imperfect supervision, particularly when optimization depends on human feedback or learned reward models. This challenge is especially evident in LLM Post-Training RL and preference-based Reinforcement Learning from Human Feedback (RLHF) (Casper et al., 2023; Zhang et al., 2025), where reward signals are approximate and not directly derived from ground-truth annotations, such as those generated by Generalized Advantage Estimation (GAE) (Schulman et al., 2018).

To address this issue, recent works have proposed robust RL training methods by either denoising reward models (Cheng et al., 2025; Miao et al., 2024) or filtering corrupted data before policy updates (Cheng et al., 2024; Wang et al., 2024b). However, these methods implicitly assume that reward errors can be corrected during training, which often does not hold in practice: training reward are frequently ambiguous, sparse, or fundamentally unreliable (Poiani et al., 2024). As a result, inaccurate reward signals can propagate throughout RL training, leading to instability in textual perception, loss of critical information during advantage estimation, and ultimately degraded policy optimization performance and convergence stability.

While noisy reward modeling has received considerable attention, the value model, which provides denser supervision and plays a central role in training, has been largely overlooked as a potential denoising mechanism. In this paper, we adopt an information-theoretic perspective (Hung et al., 2023) and propose an alternative approach: rather than relying solely on reward estimation or data filtering, we enhance RL robustness by directly optimizing the value model to absorb uncertainty and stabilize training. This perspective highlights the value model as a critical component for guiding language perception under noisy supervision.

We introduce **VRPO** (Value Model Boosting for Robust Policy Optimization), a novel framework that integrates a noise-resilient and semantically aware value model into RL training. VRPO combines two key innovations: (1) an auxiliary loss guided by entropy and perplexity from a frozen language model, and (2) a variational information bottleneck (IB) architecture for robust value model-

Figure 1: Comparison between the Standard Value Model and our Semantic-aware Information Theoretic Value Model. The standard model fits noisy rewards and labels, leading to unstable advantage estimates. VRPO enhances robustness by guiding learning with entropy and perplexity signals, and filtering noise via a variational information bottleneck, yielding more reliable value predictions and improved PPO stability.

ing. The IB mechanism constrains irrelevant information flow, enhancing tolerance to noise, while language signals from the frozen LM guide model to capture key words under noisy training. These auxiliary objectives further align the model's internal feature space with the semantic space of language, effectively suppressing spurious noise while retaining task-relevant information. Moreover, VRPO alleviates overfitting (Gao et al., 2022) and mitigates contextual noise (Wang et al., 2022), thereby improving training robustness.

We evaluate VRPO across multiple tasks, including multi-turn dialogue, mathematical reasoning, and scientific question answering, under both rule-based and model-based noisy reward settings. Experimental results show that VRPO consistently outperforms baselines such as PPO and GRPO in noisy supervision scenarios. By incorporating information-theoretic regularization and semantic guidance into RL training, VRPO transforms the value model from a passive estimator into an active, noise-aware regulator. Through context-appropriate advantage estimation and robust key-signal extraction, our method significantly enhances stability and generalization in complex environments.

Our contributions are as follows:

- We propose entropy and perplexity-based auxiliary losses that mitigate advantage collapse from noisy rewards improving the semantic robustness of the value model.

- We introduce a variational information bottleneck structure that constrains irrelevant information flow.

- We empirically demonstrate that VRPO improves RL robustness and generalization in noisy RLHF and RL scenarios, offering a principled and scalable solution for real-world RL applications.

2 Related Work

Robust RL methods primarily focus on improving reward models or filtering noisy data. Reward-oriented approaches build noise-resistant discriminators via conservative gradients (Liang et al., 2024), ensemble models (Wang et al., 2024a), or uncertainty-aware losses (Wu et al., 2024). For example, data-centric methods like RIME (Cheng et al., 2024) use pre-trained denoisers with KL bounds or apply reward consensus to remove inconsistent preferences (Wang et al., 2024a). Our work shifts robustness efforts from reward correction to value model compensation. Through value model optimization, we partially absorb and filter out the noise propagation throughout the training process.

The Information Bottleneck (IB) framework offers a principled way to learn compact (Dai et al., 2018; Goyal et al., 2019; Hafner et al., 2019; Ibarz et al., 2018), robust representations by balancing compression and prediction (Wang et al., 2022) through variational approximations (Martini et al., 2024). In RL, IB has enhanced policy or reward robustness under noisy supervision (Miao et al., 2024) but has rarely been applied to value models. We fill this gap by integrating IB regularization into the value function, enabling it to absorb noise during RL training.

3 Method

3.1 Motivation

In standard Proximal Policy Optimization (PPO), policy updates depend on the joint contribution of reward signals and value estimates via advantage computation. The core optimization objective is:

$$\mathcal{L}_{\text{PPO}} = \mathbf{E}_t\left[\min\left(r_t(\theta)\hat{A}_t, \text{clip}(r_t(\theta), 1 - \epsilon, 1 + \epsilon)\hat{A}_t\right)\right],$$
(1)

where the advantage $\hat{A}_t$ is typically computed through Generalized Advantage Estimation (GAE):

$$\hat{A}_t = \delta_t + (\gamma\lambda)\delta * t + 1 + (\gamma\lambda)^2\delta_{t+2} + \cdots, \quad (2)$$

$$\delta_t = r_t + \gamma V(s_{t+1}) - V(s_t). \quad (3)$$

This definition highlights the strong coupling between reward signals r_t and the value function $V(s)$. When r_t is noisy, its error propagates through $\hat{A}_t$, leading to unstable training and degraded final policy performance.

We observe that under noisy supervision, the model often **misallocates advantage values** and fails to emphasize semantically important tokens. As illustrated in Figure 2 (right), for correct answers, the model tends to concentrate higher advantages toward the sequence end, resulting in **length hacking** (Chaudhari et al., 2024; Laidlaw et al., 2025), where longer responses are rewarded regardless of quality. For incorrect answers, advantages are incorrectly assigned to irrelevant tokens. The root cause of such errors lies in biased reward signals: noisy r_t induces distorted advantages under GAE.

To address this, we propose a complementary perspective: **enhancing the value model itself to compensate for biased advantage estimation under noisy rewards**. Specifically, we design value models guided by semantic signals from a frozen language model, ensuring robustness to linguistic noise and preserving attention to key tokens. Additionally, we incorporate an information bottleneck mechanism to constrain irrelevant information flow, thereby improving the value model's noise tolerance and stabilizing training. As shown in Figures 2 , this design not only preserves critical signals in advantage estimation but also suppresses fluctuations under irrelevant perturbations.

Compared with reward-only denoising approaches, our framework leverages denser value supervision to more effectively correct distorted advantages, leading to superior training stability and final policy performance.

3.2 Information-Theoretic Value Modeling

To mitigate reward noise propagation in PPO, the value model must extract return-relevant information while filtering task-irrelevant details. This capability is essential for robust training under ambiguous, sparse, or inconsistent reward signals.

We address this by reformulating value modeling from an information-theoretic perspective. Let the input be a random variable X, the latent representation Z, and the return Y. Assuming Z follows a Gaussian distribution, we define:

$$I_{\text{bottleneck}} = I(X; Z), \quad I_{\text{value}} = I(Z; Y) \quad (4)$$

Here, $I_{\text{bottleneck}}$ measures information retained from the input, while I_{value} quantifies predictive information for returns. The objective is to learn a latent representation that maximizes return relevance while minimizing input redundancy:

$$\max J(\theta) = I(Z; Y) - \beta I(X; Z) \quad (5)$$

where β controls the trade-off between compression and relevance, and θ denotes model parameters.

Since mutual information is intractable in high-dimensional settings, we optimize a variational lower bound using training data $D = \{(x_i, y_i)\}_{i=1}^N$:

$$J(\phi, \psi) \geq J_{\text{VLB}}(\phi, \psi) = \mathbf{E}_{(x,y)\sim D}[J_{\text{value}} - \beta J_{\text{bottleneck}}] \quad (6)$$

$$J_{\text{value}} = \mathbf{E}_{z\sim p_\phi(z|x)}[\log q_\psi(y|z)] \quad (7)$$

$$J_{\text{bottleneck}} = \text{KL}[p_\phi(z|x)\|r(z)] \quad (8)$$

where $p_\phi(z|x)$ is the variational encoder, $q_\psi(y|z)$ the return predictor, and $r(z)$ the standard Gaussian prior. Parameters ϕ and ψ correspond to the encoder and decoder.

In practice, we model $p_\phi(z|x)$ as a diagonal Gaussian:

$$z = f_\phi^\mu(x) + f_\phi^\sigma(x) \cdot \epsilon, \quad \epsilon \sim \mathcal{N}(0, I) \quad (9)$$

and use a lightweight MLP q_ψ to predict returns from z. The final training objective becomes:

$$\mathcal{L}_{\text{value}} = \mathbf{E}_{(x,y)\sim D}[-\log q_\psi(z) + \beta \cdot \text{KL}(p_\phi(z|x)\|r(z))] \quad (10)$$

This structure encourages the value model to learn compact, reward-relevant latent representations while suppressing irrelevant or noisy input signals.

Figure 2: Token-level advantage estimation for the same response across different methods. Our method exhibits sharper **focus on critical reasoning steps**.

3.3 Enhancing Semantic Awareness for Noise-Resistant Value Modeling

While the information bottleneck in Section 3.2 helps filter out irrelevant features, it does not directly address semantic misalignment. Under noisy reward supervision, the value model may still lose attention on key words, resulting in prediction errors. To mitigate this, we introduce a semantic-level regularization mechanism that enhances the alignment between the model's feature space and the language space.

Concretely, we incorporate a frozen LM head into the value model to express its internal token-level understanding. We then guide this understanding using auxiliary losses based on entropy and perplexity, encouraging semantic consistency with the actor model despite noisy rewards. Let $P_V(y_t|x)$ denote the token-level prediction distribution from the LM head. We define the auxiliary losses as:

$$L_{\text{ent}} = \sum_{t \in T_{\text{ent}}} H[P_V(y_t|x)], \quad (11)$$

$$L_{\text{ppl}} = \sum_{t \in T_{\text{ppl}}} -\log P_V(y_t = y_t^*|x) \quad (12)$$

where $H[\cdot]$ is entropy, and $T_{\text{ent}}, T_{\text{ppl}}$ are dynamically selected token subsets with high entropy and perplexity respectively:

$$T_{\text{ent}} = \{t : H[P_V(y_t|x)] > \hat{T}_{\text{entropy}}\}, \quad (13)$$

$$T_{\text{ppl}} = \{t : -\log P_V(y_t = y_t^*|x) > \hat{T}_{\text{perplexity}}\} \quad (14)$$

where $\hat{T}_{\text{entropy}}$ and $\hat{T}_{\text{perplexity}}$ represent the threshold of entropy and perplexity. The final semantic regularization loss is:

$$L_{\text{semantic}} = \lambda_{\text{ent}} L_{\text{ent}} + \lambda_{\text{ppl}} L_{\text{ppl}} \quad (15)$$

where λ_{ent} and λ_{ppl} represent the weight of the loss.

This method provides the value model with stable, semantically meaningful supervision, helping it stay anchored to the input's linguistic structure and resist reward noise. Combined with the information bottleneck from Section 3.2, it reinforces both semantic alignment and robustness.

4 Experiments

4.1 Setup

We evaluate VRPO in two distinct but complementary settings: **rule-based rewards** and **model-based rewards**, both designed to test robustness under noisy supervision.

Rule-based reward setting This scenario mainly **considers the noise in unsupervised learning**. We simulate supervision by performing majority voting over multiple outputs from pretrained models. Two variants are considered: (i) *training-time augmentation* where noisy pseudo-labels from the training set supervise RL training and (ii) *test-time augmentation*, where noisy pseudo-labels from the test set supervise RL training. Models are cold-started via supervised fine-tuning and constrained to specific answer formats. The results of test-time augmentation can be found in the appendix.

Model-based reward setting We conduct experiments on multi-turn dialogue, using a separate reward model trained on annotated dialogue data. A policy model is optimized via RL under this noisy reward.

Baselines In both settings, we compare VRPO with PPO and GRPO under identical initialization. All models are based on Qwen2.5 (Qwen et al., 2025), Qwen3 (Yang et al., 2025) or Llama3.1 variants, fine-tuned appropriately.

Figure 3: Noise statistics in the various tasks. A significant portion of rewards contains inaccuracies.

Training Noise Noise is pervasive in RL training , especially under model-based feedback. Figure 3 illustrates the error rate in various reward signals. The noise in the rule-based reward from the majority vote generated data.

Implementation Details In the majority voting during test-time optimization, 32 samples are used, while 5 samples are used for voting during training-time optimization. The weights for the auxiliary losses (entropy and perplexity) are set to 0.5, making 80% of the labels effective. The experiments are conducted on 8 NVIDIA A100 80GB GPUs. For further dataset construction, training details, and model initialization, please refer to Appendix.

4.2 Evaluation Metrics

To evaluate the effectiveness of our value model, we consider both task-level performance and value estimation capabilities across different task domains.

4.2.1 Task-Level Metrics

For mathematical reasoning and scientific knowledge tasks, we adopt accuracy as the primary metric to measure whether the model produces correct answers. For multi-turn dialogue tasks, we employ a tripartite evaluation framework that captures both task execution and communicative quality: (1) Task Completion Rate (TCR), assessing whether the model successfully fulfills the user-intended objective; (2) Ask Completion Rate (ACR), measuring whether detailed aspects of the user query are adequately addressed; and (3) Goal Completion Rate (GCR), evaluating the fluency, coherence, and appropriateness of the model's responses. This comprehensive evaluation allows us to examine not only whether the model achieves the intended outcomes, but also how effectively it aligns with human communication standards.

4.2.2 Value Model Performance Metrics

To directly evaluate the accuracy and robustness of the value model, we adopt the following criteria:

Explained Variance We use the explained variance to measure how much of the empirical return is captured by the predicted value:

$$\text{Explained Variance} = 1 - \frac{\text{Var}[\hat{R} - V]}{\text{Var}[\hat{R}]} \quad (16)$$

where $\hat{R}$ denotes the empirical return and V is the predicted value. A value near 1 indicates high explanatory power, while values near or below zero indicate poor or misleading predictions.

Prediction Error Evaluation To assess the value model's prediction accuracy, we adopt Mean Squared Error (MSE) and Mean Absolute Error (MAE) between the predicted value $V_\theta(s_t)$ and the reference target $V_{\text{target}}(s_t)$:

$$\mathcal{L}_{\text{MSE}} = \frac{1}{T} \sum_{t=0}^{T-1} \left(V_\theta(s_t) - V_{\text{target}}(s_t) \right)^2, \quad (17)$$

$$\mathcal{L}_{\text{MAE}} = \frac{1}{T} \sum_{t=0}^{T-1} \left| V_\theta(s_t) - V_{\text{target}}(s_t) \right| \quad (18)$$

Here, T denotes the trajectory length, and $V_{\text{target}}(s_t)$ is computed via n-step Temporal Difference (TD) with Generalized Advantage Estimation (GAE):

$$V_{\text{target}}(s_t) = \sum_{k=0}^{n-1} \gamma^k r_{t+k} + \gamma^n V(s_{t+n}) \quad (19)$$

If $t + n \geq T$, the bootstrap term $\gamma^n V(s_{t+n})$ is set to zero to account for episode termination. MSE emphasizes large errors and captures prediction stability, while MAE reflects overall distributional deviation. As the rewards are obtained through simulation, **these metrics primarily serve as relative indicators of training quality rather than absolute performance benchmarks**.

Figure 4: Average response length across training. Our method maintains stable lengths (94 to 95), while PPO and GRPO increase significantly due to length reward hacking.

4.2.3 Advantage Visualization

To qualitatively assess the robustness introduced by value model training, we visualize token-level advantage values across generated sequences. In reinforcement learning-based language generation, the advantage function quantifies the relative benefit of taking action a_t in state s_t, and is computed as:

$$A_t = Q(s_t, a_t) - V(s_t) \tag{20}$$

where $Q(s_t, a_t)$ represents the estimated return of taking action a_t in state s_t, and $V(s_t)$ denotes the baseline value of the current state.

Higher advantage values indicate that the corresponding token exhibits significantly better performance compared to the average policy behavior under the current context. These tokens function as positive learning signals and reflect directions along which the policy should be reinforced. Therefore, visualizing token-level advantages enables us to analyze which parts of the generation are being prioritized during optimization and how the learned policy aligns with high-reward behaviors.

4.3 Dialogue Task under Model-Based Reward RL Training

To assess the effectiveness of our approach in realistic settings with model-based reward supervision, we conduct multi-turn dialogue experiments on the **Honor-Dialogue Dataset**. This dataset, constructed by us, contains multi-domain, task-oriented dialogues collected from real-world scenarios. The task requires the model to act as a dialogue assistant, producing natural and effective responses. Under noisy dialogue reward model supervision, the model is trained with reinforcement learning on real multi-turn dialogues. Performance is evaluated through interactions with GPT-4o using the dialogue standards in Section 4.2.1. Dataset statistics are provided in the Appendix, and Fig-

Figure 5: Training performance on dialogue tasks. VRPO (the top lines) improves task completion from 72.1% to 75.9%, avoids collapse under noise, and achieves a final average performance of 83.80%, outperforms GRPO (36.17%) and PPO (40.13%) in stability.

ure 6 shows the training dynamics. All real information in the data has undergone anonymization, and the use of the data has been authorized.

VRPO enhances training stability in real-world general scenarios Despite noisy supervision, our method effectively improves dialogue agent performance, surpassing the cold-start baseline from 85.87% to 88.13%. In contrast, PPO and GRPO exhibit severe performance collapse under noisy rewards, with GRPO performing the worst. This demonstrates our method's stability and resilience in noisy settings. For further experimental data results, please refer to Appendix.

Strong Value Model Helps Reduce Reward Hacking A stronger value model helps mitigate reward model hacking by resisting length bias during training. As shown in Figure 4, the performance collapse largely stems from length-based reward exploitation. Our method stabilizes advantage estimation, preventing it from scaling with response length. In contrast, PPO and GRPO exhibit sharp length inflation, revealing greater vulnerability to

biased rewards.

Value model better corrects model training bias compared to Reward model We applied our method to the reward model for the experiment. The results show that the value model provides denser supervision, leading to superior correction of the final advantage estimates. Compared to reward model optimization methods, VRPO better preserves training performance in dialogue tasks, achieving an optimal average performance improvement of 75.90%, with a final average performance exceeding 36.13%. During training, length fluctuations are more stable, effectively addressing reward biases caused by length during training.

4.4 Math and Science Task under Rule-Based Rewards RL Training

To further assess the effectiveness of our approach in realistic settings where supervision comes from rule-based rewards, we conduct a series of experiments on mathematical and scientific reasoning tasks during training-time optimization. Specifically, we use the Light-R1 dataset (Wen et al., 2025) for math tasks and the SuperGPQA(Team et al., 2025) dataset for scientific tasks. For each dataset, we perform multiple inferences with the original model, followed by voting to filter the results before training. The evaluation is then conducted on math and scientific QA datasets. The test datasets include four math-focused tasks: MATH500 (Hendrycks et al., 2021), AIME24, Minerva-Math (Lewkowycz et al., 2022), AMC23, as well as three scientific knowledge tasks: SampleQA (Wei et al., 2024), GPQA , and HLE (Humanity's Last Exam)(Phan et al., 2025). Table 5 reports the accuracy of models before and after RL training, comparing weak and strong models under noisy conditions. Due to the limitation of memory, multiple rounds of generation are carried out here. In each round, the generated length is at most 4096 tokens, and the result of the last round is used for evaluation.

VRPO achieves optimization under noisy supervision across multiple domains By utilizing a value model with stronger language perception, VRPO consistently outperforms other baseline methods in multiple domains. This improvement is particularly evident in math reasoning and scientific knowledge tasks. For example, after training with the Qwen3-8B model, the average accuracy on math tasks increased from 58.40% to 60.55%, and on scientific tasks from 2.96% to 3.82%. These results highlight the model's ability to extract relevant information from noisy or fuzzy feedback and showcase its strong generalization across various domains.

VRPO shows significant effectiveness in scenarios with severe training collapse In math tasks with a weaker model (Qwen2.5-7B cold-start), model training is heavily impacted by noise, leading to a notable performance drop in GRPO, with accuracy on MATH500 dropping to 50.40%. With a stronger model (Qwen3-8B), noise impact decreases, and all methods improve. Our method still provides stable gains, achieving 38.14% average accuracy on all datasets, outperforming Reinforce++ by 1.54%. In the weaker model setup, the gain is even higher (6.49%), demonstrating the advantage of our method under more challenging conditions.

VRPO helps guide the model's advantage estimates to focus on key words Figure 2 visualizes the advantage estimation for the same response across different methods. While PPO disperses attention across tokens, our model focuses on critical text information. It not only captures the key elements of the response but also shows a more appropriate perception and judgment of its answer.

4.5 Ablation Experiment and Discussion

Enhanced Semantic Awareness rather than Semantic Understanding As shown in Table 2, we conduct an ablation study to evaluate how different forms of language-awareness affect model robustness under noisy reward supervision. Our results suggest that directly solving tasks via cross-entropy is suboptimal for the value model. Instead, regularizing with entropy and perplexity, focusing on semantic perception, leads to stronger generalization and robustness. Specifically, minimizing these losses improves the value model's ability to identify meaningful signals amid noisy feedback, boosting average accuracy to 42.41%, compared to 39.51% under standard cross-entropy training. This improvement stems from the model's enhanced alignment with linguistic structure, enabling it to act not as a task solver, but as a semantic signal regulator, assessing responses with higher fidelity and filtering unstable patterns. While actor improvements help with comprehension, our results show that the value model is more effective in absorbing reward uncertainty, yielding a 4% gain over actor-centric training on average.

Domain	Math				Factuality	Science	Knowledge	ALL
Method	MATH500	AIME24	Minerva-Math	AMC23	SampleQA	GPQA	HLE	AVG
Qwen2.5-7B-Cold Start(Weak Model)								
Base	71.60%	6.67%	18.75%	52.50%	2.36%	1.45%	3.29%	22.37%
GRPO	50.40%	6.67%	13.60%	22.50%	2.36%	2.36%	2.97%	14.41%
PPO	67.40%	13.33%	19.12%	35.83%	2.54%	2.54%	3.43%	20.60%
Reinforce++	63.80%	6.67%	10.66%	40.83%	2.64%	2.17%	3.34%	18.59%
Dr.GRPO	**73.00%**	13.33%	18.75%	**53.33%**	2.54%	1.27%	3.34%	23.65%
Ours	72.20%	**23.33%**	**19.85%**	50.00%	**2.82%**	**3.44%**	**3.94%**	**25.08%**
Qwen3-8B(Strong Model)								
Base	87.40%	41.67%	28.68%	75.83%	2.89%	3.10%	2.89%	34.64%
GRPO	89.20%	35.00%	28.68%	84.17%	3.03%	2.98%	3.24%	35.19%
PPO	86.40%	36.67%	30.51%	80.00%	2.82%	2.17%	3.29%	34.55%
Reinforce++	89.00%	45.00%	27.21%	84.17%	3.19%	**4.35%**	3.29%	36.60%
Dr.GRPO	87.80%	45.00%	27.94%	85.83%	2.50%	3.99%	3.10%	36.59%
Ours	**90.20%**	**46.67%**	**31.99%**	**86.67%**	**3.21%**	**4.35%**	**3.89%**	**38.14%**

Table 1: Accuracy (%) on train-time optimization with rule-based rewards across multiple reasoning benchmarks. Our method achieves consistent improvements under both weaker and stronger base models.

Method	MATH500	AIME24	Minerva-Math	AMC23	AVG
Actor Model					
Cross-Entropy Loss	73.20%	10.00%	19.12%	50.83%	38.29%
CE with Entropy/Perplexity Filtering	70.40%	13.33%	19.12%	50.83%	38.42%
Entropy + Perplexity Minimization	69.40%	10.00%	18.01%	54.17%	37.90%
Value Model					
Cross-Entropy Loss	73.00%	10.00%	18.38%	56.67%	39.51%
CE with Entropy/Perplexity Filtering	72.20%	10.00%	18.75%	57.50%	39.61%
Entropy + Perplexity Minimization(Ours)	**74.40%**	**13.33%**	**20.22%**	**61.67%**	**42.41%**

Table 2: Comparison of different training objectives on math reasoning tasks under test-time reward perturbation. Entropy- and perplexity-based regularization improves value model robustness (+2.9%) over standard cross-entropy, confirming its role as a semantic signal regulator.

Activation	MATH 500	AIME 24	Minerva Math	AMC 23	AVG
20%	75.00%	6.67%	18.38%	54.17%	38.56%
50%	73.40%	13.33%	19.49%	55.83%	40.51%
80%(Ours)	**74.40%**	13.33%	**20.22%**	**61.67%**	**42.41%**
100%	73.80%	**16.67%**	19.12%	55.00%	41.15%

Table 3: Impact of partial token activation on performance via entropy/perplexity-based loss, activating 80% of high-uncertainty tokens yields the best accuracy.

Partial Token Activation may Strengthen Semantic Learning We investigate how partially activating high-uncertainty tokens affects robustness in noisy reward training by selectively applying language-aware losses. As shown in Table 3, activating 80% of high-entropy/perplexity tokens yields the best performance (42.41%), demonstrating that focusing supervision on uncertain regions strengthens the value model's alignment with language semantics. Interestingly, fully activating all tokens (100%) slightly reduces performance (to 41.15%), likely due to the inclusion of noisy or uninformative tokens, which destabilize value es-

timation. This reveals a trade-off: while broader activation promotes semantic sensitivity, indiscriminate supervision can introduce harmful variance. Partial token activation offers a balanced solution that enhances robustness without compromising core value function stability.

5 Conclusion

In this study, we rethink the often-overlooked role of the value model in RL frameworks, particularly under noisy reward supervision in LLM post-training. We propose VRPO, a novel training framework that improves the robustness of RL by incorporating information flow filtering and enhancing language perception through guidance from a frozen language model in the value model. This approach effectively corrects reward biases, leading to more accurate advantage estimation. Experiments on math, science and dialogue tasks show that VRPO outperforms baseline methods such as PPO and GRPO, highlighting the untapped potential of the value model in robust RL training.

Limitations

In this section, we discuss the potential threats to the validity of our method. Due to limited computational resources, the experiments with rule-based rewards were only conducted on mathematics and science tasks, where each model was trained and evaluated on a single dataset. Moreover, the ablation studies were primarily performed during test-time optimization under rule-based reward settings. To mitigate this potential threat, we further conducted experiments across a wide range of datasets and tasks, and performed ablation studies under rule-based reward conditions during training-time optimization as well. Although current results indicate no significant differences between the two settings, this broader evaluation helps ensure the robustness of our conclusions.

References

Marc G. Bellemare, Salvatore Candido, Pablo Samuel Castro, Jun Gong, Marlos C. Machado, Subhodeep Moitra, Sameera S. Ponda, and Ziyun Wang. 2020. Autonomous navigation of stratospheric balloons using reinforcement learning. *Nature*, 588:77 – 82.

Angelo Caregnato-Neto, Luciano Cavalcante Siebert, Arkady Zgonnikov, Marcos Ricardo Omena de Albuquerque Maximo, and Rubens Junqueira Magalhães Afonso. 2024. ARMCHAIR: integrated inverse reinforcement learning and model predictive control for human-robot collaboration. *arXiv e-prints*, arXiv:2402.19128.

Stephen Casper, Xander Davies, Claudia Shi, Thomas Krendl Gilbert, Jérémy Scheurer, Javier Rando, Rachel Freedman, Tomasz Korbak, David Lindner, Pedro Freire, Tony Wang, Samuel Marks, Charbel-Raphaël Segerie, Micah Carroll, Andi Peng, Phillip Christoffersen, Mehul Damani, Stewart Slocum, Usman Anwar, and 13 others. 2023. Open Problems and Fundamental Limitations of Reinforcement Learning from Human Feedback. *arXiv e-prints*, arXiv:2307.15217.

Shreyas Chaudhari, Pranjal Aggarwal, Vishvak Murahari, Tanmay Rajpurohit, Ashwin Kalyan, Karthik Narasimhan, Ameet Deshpande, and Bruno Castro da Silva. 2024. Rlhf deciphered: A critical analysis of reinforcement learning from human feedback for llms. *Preprint*, arXiv:2404.08555.

Yuanpei Chen, Tianhao Wu, Shengjie Wang, Xidong Feng, Jiechuang Jiang, Stephen Marcus McAleer, Yiran Geng, Hao Dong, Zongqing Lu, Song-Chun Zhu, and Yaodong Yang. 2022. Towards Human-Level Bimanual Dexterous Manipulation with Reinforcement Learning. *arXiv e-prints*, arXiv:2206.08686.

Jie Cheng, Gang Xiong, Xingyuan Dai, Qinghai Miao, Yisheng Lv, and Fei-Yue Wang. 2024. RIME: Robust Preference-based Reinforcement Learning with Noisy Preferences. *arXiv e-prints*, arXiv:2402.17257.

Ruoxi Cheng, Haoxuan Ma, Weixin Wang, Zhiqiang Wang, Xiaoshuang Jia, Simeng Qin, Xiaochun Cao, Yang Liu, and Xiaojun Jia. 2025. Inverse Reinforcement Learning with Dynamic Reward Scaling for LLM Alignment. *arXiv e-prints*, arXiv:2503.18991.

Bin Dai, Chen Zhu, and David Wipf. 2018. Compressing Neural Networks using the Variational Information Bottleneck. *arXiv e-prints*, arXiv:1802.10399.

Leo Gao, John Schulman, and Jacob Hilton. 2022. Scaling Laws for Reward Model Overoptimization. *arXiv e-prints*, arXiv:2210.10760.

Anirudh Goyal, Riashat Islam, Daniel Strouse, Zafarali Ahmed, Matthew Botvinick, Hugo Larochelle, Yoshua Bengio, and Sergey Levine. 2019. InfoBot: Transfer and Exploration via the Information Bottleneck. *arXiv e-prints*, arXiv:1901.10902.

Danijar Hafner, Timothy Lillicrap, Jimmy Ba, and Mohammad Norouzi. 2019. Dream to Control: Learning Behaviors by Latent Imagination. *arXiv e-prints*, arXiv:1912.01603.

Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arora, Steven Basart, Eric Tang, Dawn Song, and Jacob Steinhardt. 2021. Measuring mathematical problem solving with the math dataset. *Preprint*, arXiv:2103.03874.

Yu-Heng Hung, Ping-Chun Hsieh, Akshay Mete, and P. R. Kumar. 2023. Value-biased maximum likelihood estimation for model-based reinforcement learning in discounted linear mdps. *Preprint*, arXiv:2310.11515.

Borja Ibarz, Jan Leike, Tobias Pohlen, Geoffrey Irving, Shane Legg, and Dario Amodei. 2018. Reward learning from human preferences and demonstrations in Atari. *arXiv e-prints*, arXiv:1811.06521.

Cassidy Laidlaw, Shivam Singhal, and Anca Dragan. 2025. Correlated proxies: A new definition and improved mitigation for reward hacking. *Preprint*, arXiv:2403.03185.

Aitor Lewkowycz, Anders Andreassen, David Dohan, Ethan Dyer, Henryk Michalewski, Vinay Ramasesh, Ambrose Slone, Cem Anil, Imanol Schlag, Theo Gutman-Solo, Yuhuai Wu, Behnam Neyshabur, Guy Gur-Ari, and Vedant Misra. 2022. Solving quantitative reasoning problems with language models. *Preprint*, arXiv:2206.14858.

Xize Liang, Chao Chen, Shuang Qiu, Jie Wang, Yue Wu, Zhihang Fu, Zhihao Shi, Feng Wu, and Jieping Ye. 2024. ROPO: Robust Preference Optimization for Large Language Models. *arXiv e-prints*, arXiv:2404.04102.

K. Michael Martini, Eslam Abdelaleem, and Ilya Nemenman. 2024. Deep Variational Multivariate Information Bottleneck. In *APS March Meeting Abstracts*, volume 2024 of *APS Meeting Abstracts*, page T28.009.

Yuchun Miao, Sen Zhang, Liang Ding, Rong Bao, Lefei Zhang, and Dacheng Tao. 2024. InfoRM: Mitigating Reward Hacking in RLHF via Information-Theoretic Reward Modeling. *arXiv e-prints*, arXiv:2402.09345.

Niklas Muennighoff, Zitong Yang, Weijia Shi, Xiang Lisa Li, Li Fei-Fei, Hannaneh Hajishirzi, Luke Zettlemoyer, Percy Liang, Emmanuel Candès, and Tatsunori Hashimoto. 2025. s1: Simple test-time scaling. *Preprint*, arXiv:2501.19393.

Julien Perolat, Bart De Vylder, Daniel Hennes, Eugene Tarassov, Florian Strub, Vincent de Boer, Paul Muller, Jerome T. Connor, Neil Burch, Thomas Anthony, Stephen McAleer, Romuald Elie, Sarah H. Cen, Zhe Wang, Audrunas Gruslys, Aleksandra Malysheva, Mina Khan, Sherjil Ozair, Finbarr Timbers, and 15 others. 2022. Mastering the game of Stratego with model-free multiagent reinforcement learning. *Science*, 378(6623):990–996.

Long Phan, Alice Gatti, Ziwen Han, Nathaniel Li, Josephina Hu, Hugh Zhang, Chen Bo Calvin Zhang, Mohamed Shaaban, John Ling, Sean Shi, Michael Choi, Anish Agrawal, Arnav Chopra, Adam Khoja, Ryan Kim, Richard Ren, Jason Hausenloy, Oliver Zhang, Mantas Mazeika, and 1090 others. 2025. Humanity's last exam. *Preprint*, arXiv:2501.14249.

Riccardo Poiani, Gabriele Curti, Alberto Maria Metelli, and Marcello Restelli. 2024. Inverse Reinforcement Learning with Sub-optimal Experts. *arXiv e-prints*, arXiv:2401.03857.

Qwen, :, An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chengyuan Li, Dayiheng Liu, Fei Huang, Haoran Wei, Huan Lin, Jian Yang, Jianhong Tu, Jianwei Zhang, Jianxin Yang, Jiaxi Yang, Jingren Zhou, and 25 others. 2025. Qwen2.5 technical report. *Preprint*, arXiv:2412.15115.

John Schulman, Philipp Moritz, Sergey Levine, Michael Jordan, and Pieter Abbeel. 2018. High-dimensional continuous control using generalized advantage estimation. *Preprint*, arXiv:1506.02438.

M-A-P Team, Xinrun Du, Yifan Yao, Kaijing Ma, Bingli Wang, Tianyu Zheng, Kang Zhu, Minghao Liu, Yiming Liang, Xiaolong Jin, Zhenlin Wei, Chujie Zheng, Kaixing Deng, Shuyue Guo, Shian Jia, Sichao Jiang, Yiyan Liao, Rui Li, Qinrui Li, and 76 others. 2025. Supergpqa: Scaling llm evaluation across 285 graduate disciplines. *Preprint*, arXiv:2502.14739.

Binghai Wang, Rui Zheng, Lu Chen, Yan Liu, Shihan Dou, Caishuang Huang, Wei Shen, Senjie Jin, Enyu Zhou, Chenyu Shi, Songyang Gao, Nuo Xu, Yuhao Zhou, Xiaoran Fan, Zhiheng Xi, Jun Zhao, Xiao

Wang, Tao Ji, Hang Yan, and 8 others. 2024a. Secrets of RLHF in Large Language Models Part II: Reward Modeling. *arXiv e-prints*, arXiv:2401.06080.

Chenglong Wang, Yang Gan, Yifu Huo, Yongyu Mu, Murun Yang, Qiaozhi He, Tong Xiao, Chunliang Zhang, Tongran Liu, Quan Du, Di Yang, and Jingbo Zhu. 2024b. RoVRM: A Robust Visual Reward Model Optimized via Auxiliary Textual Preference Data. *arXiv e-prints*, arXiv:2408.12109.

Xiao Wang, Shihan Dou, Limao Xiong, Yicheng Zou, Qi Zhang, Tao Gui, Liang Qiao, Zhanzhan Cheng, and Xuanjing Huang. 2022. MINER: Improving Out-of-Vocabulary Named Entity Recognition from an Information Theoretic Perspective. *arXiv e-prints*, arXiv:2204.04391.

Jason Wei, Nguyen Karina, Hyung Won Chung, Yunxin Joy Jiao, Spencer Papay, Amelia Glaese, John Schulman, and William Fedus. 2024. Measuring short-form factuality in large language models. *Preprint*, arXiv:2411.04368.

Liang Wen, Yunke Cai, Fenrui Xiao, Xin He, Qi An, Zhenyu Duan, Yimin Du, Junchen Liu, Lifu Tang, Xiaowei Lv, Haosheng Zou, Yongchao Deng, Shousheng Jia, and Xiangzheng Zhang. 2025. Light-r1: Curriculum sft, dpo and rl for long cot from scratch and beyond. *Preprint*, arXiv:2503.10460.

Junkang Wu, Yuexiang Xie, Zhengyi Yang, Jiancan Wu, Jiawei Chen, Jinyang Gao, Bolin Ding, Xiang Wang, and Xiangnan He. 2024. Towards Robust Alignment of Language Models: Distributionally Robustifying Direct Preference Optimization. *arXiv e-prints*, arXiv:2407.07880.

Mingqi Wu, Zhihao Zhang, Qiaole Dong, Zhiheng Xi, Jun Zhao, Senjie Jin, Xiaoran Fan, Yuhao Zhou, Huijie Lv, Ming Zhang, Yanwei Fu, Qin Liu, Songyang Zhang, and Qi Zhang. 2025. Reasoning or memorization? unreliable results of reinforcement learning due to data contamination. *Preprint*, arXiv:2507.10532.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, Chujie Zheng, Dayiheng Liu, Fan Zhou, Fei Huang, Feng Hu, Hao Ge, Haoran Wei, Huan Lin, Jialong Tang, and 41 others. 2025. Qwen3 technical report. *Preprint*, arXiv:2505.09388.

Tongtian Yue, Jie Cheng, Longteng Guo, Xingyuan Dai, Zijia Zhao, Xingjian He, Gang Xiong, Yisheng Lv, and Jing Liu. 2024. SC-Tune: Unleashing Self-Consistent Referential Comprehension in Large Vision Language Models. *arXiv e-prints*, arXiv:2403.13263.

Jiazheng Zhang, Wenqing Jing, Zizhuo Zhang, Zhiheng Xi, Shihan Dou, Rongxiang Weng, Jiahuan Li, Jingang Wang, Mingxu Chai, Shibo Hong, Tao Gui, and Qi Zhang. 2025. Two Minds Better Than One: Collaborative Reward Modeling for LLM Alignment. *arXiv e-prints*, arXiv:2505.10597.

Ming Zhou, Jun Luo, Julian Villella, Yaodong Yang, David Rusu, Jiayu Miao, Weinan Zhang, Montgomery Alban, Iman Fadakar, Zheng Chen, Aurora Chongxi Huang, Ying Wen, Kimia Hassanzadeh, Daniel Graves, Dong Chen, Zhengbang Zhu, Nhat Nguyen, Mohamed Elsayed, Kun Shao, and 18 others. 2020. SMARTS: Scalable Multi-Agent Reinforcement Learning Training School for Autonomous Driving. *arXiv e-prints*, arXiv:2010.09776.

A Additional Details for VRPO

A.1 Pseudocode

The full algorithm of VRPO is detailed in Algorithm 1.

B Additional Experimental Details

B.1 Setup

B.1.1 Dataset Construction

Rule-based Setting. For **test-time augmentation**, we use four math benchmarks: AIME 2024, AMC 2023, Minerva-Math, and MATH-500, as well as three QA datasets: GPQA-Extended, SimpleQA, and Humanity's Last Exam (HLE).

For **training-time augmentation**, as an illustrative example based on the Qwen3-8B model, pseudo-labels for mathematical tasks are generated from 39,000 samples in the Light-R1 (Wen et al., 2025) dataset. After 5 rounds of majority voting, samples with at least 3 identical responses are retained, yielding 31,209 instances for reinforcement learning training. For scientific tasks, pseudo-labels are generated from 26,529 samples in the SuperGPQA dataset. After the same 5-round majority voting procedure, 10,075 samples with at least 2 consistent responses are preserved for RL training. Evaluation is conducted on non-overlapping mathematical benchmarks to ensure fairness.

Model-based Setting. A real-world dialogue dataset (Honor-Dialogue) is used. The reward model is trained on 36,000 labeled samples, with 3,000 for validation. The policy model is fine-tuned and trained on 80,000 additional conversations, with 8,000 for evaluation. This dataset contains various dialogue tasks in real-life scenarios. It truly reflects the actual conditions of real situations. Such multi-category real-scenario dialogue task data is not available in other datasets.

B.1.2 Baseline Initialization

Rule-based Setting. Test-time augmentation: Qwen2.5-7B-Base (math task) and Qwen2.5-7B-Instruct (QA task), fine-tuned on OpenR1-Math

---

Algorithm 1: VRPO training process

Require: Dataset $\mathcal{D} = \{(x_t, a_t, r_t)\}_{t=1}^{T}$, policy π_θ, decoder model q_ψ, encoder model f_ϕ, bottleneck prior $r(z)$; coefficients $\beta, \lambda_{\text{ent}}, \lambda_{\text{ppl}}$

Ensure: Actor model π_θ, value model f_ϕ, q_ψ

  for each VRPO iteration **do**

    Sample trajectories using current policy π_θ

    Compute rewards $\{r_t\}$ and actions $\{a_t\}$

    Compute policy ratio: $\rho_t = \frac{\pi_\theta(a_t|x_t)}{\pi_{\theta_{\text{old}}}(a_t|x_t)}$

    for each timestep t **do**

      Encode latent: sample $\epsilon \sim \mathcal{N}(0, I)$, compute $z_t = f_\phi^\mu(x_t) + f_\phi^\sigma(x_t) \cdot \epsilon$

      Predict value: $\hat{V}_t = q_\psi(z_t)$

    end for

    Compute GAE advantage: $A_t = \text{GAE}(r_t, \hat{V}_t, \hat{V}_{t+1})$

    Compute returns: $R_t = A_t + \hat{V}_t$

  Value Model Update

    // Value Loss with IB Structure

    Compute value loss: $\mathcal{L}_{\text{MSE}} = \frac{1}{T} \sum_t (q_\psi(f\phi(x_t)) - R_t)^2$

    Compute KL loss: $\mathcal{L}_{\text{KL}} = \frac{1}{T} \sum_t \text{KL}(p_\phi(z_t|x_t) \| r(z))$

    // Semantic Alignment via Frozen LM Head

    for each timestep t **do**

      Get token distribution $P_V(y_t|x_t)$ from frozen LM head

      Identify high-uncertainty tokens:

        $T_{\text{ent}} = \{t : H[P_V(y_t|x_t)] > \hat{T}_{\text{entropy}}\}$

        $T_{\text{ppl}} = \{t : -\log P_V(y_t = y_t^*|x_t) > \hat{T}_{\text{perplexity}}\}$

      Compute entropy loss: $L_{\text{ent}} = \sum_{t \in T_{\text{ent}}} H[P_V(y_t|x_t)]$

      Compute perplexity loss: $L_{\text{ppl}} = \sum_{t \in T_{\text{ppl}}} -\log P_V(y_t = y_t^*|x_t)$

    end for

    Compute semantic loss: $\mathcal{L}_{\text{sem}} = \lambda_{\text{ent}} \cdot L_{\text{ent}} + \lambda_{\text{ppl}} \cdot L_{\text{ppl}}$

    Combine value loss: $\mathcal{L}_{\text{value}} = \mathcal{L}_{\text{MSE}} + \beta \cdot \mathcal{L}_{\text{KL}} + \mathcal{L}_{\text{sem}}$

    Update value model $\{\phi, \psi\}$ using $\nabla \mathcal{L}_{\text{value}}$

  Actor Model Update

    Compute clipped PPO objective: $\mathcal{L}_{\text{PPO}} = \mathbf{E}_t [\min(\rho_t A_t, \text{clip}(\rho_t, 1 - \epsilon, 1 + \epsilon)A_t)]$

    Update actor model π_θ, using $\nabla \mathcal{L}_{\text{PPO}}$

  end for

---

and S1.1(Muennighoff et al., 2025), respectively. **Training-time augmentation:** Qwen2.5-7B-Cold Start, Qwen3-1.7B , Qwen3-8B and LLaMA 3.1-8B-Instruct are used as baselines.The Qwen2.5-7B-Cold Start model has the same model settings as those in the Test-time augmentation.

Model-based Setting. Both the policy and reward models are initialized from Qwen3-8B, fine-tuned on the Honor-Dialogue dataset.

B.1.3 Training Configuration

Training parameters. In the majority voting during testing, 32 samples are used, while 5 samples are used for voting during training. The weights for the auxiliary losses (entropy and perplexity) are set to 0.5, making 80% of the labels effective. The RL training runs for 1 iteration. During both training and testing, the model generates dialogue tasks of length 4096 for reasoning tasks and 1024 for dialogue tasks. The experiments are conducted on 8 NVIDIA A100 80GB GPUs.

B.2 Additional experimental details in the Dialogue Task

To further analyze the behavior of different methods in the dialogue task, Table 4 presents the full training trajectory across various steps. A notable observation is that both PPO and GRPO experience severe performance degradation during training, likely due to reward over-optimization or instability, resulting in significantly lower final scores than both the initial model and our method. Specifically, their final average scores drop to 40.13% and 36.17%, respectively.

In contrast, our proposed method (VRPO) maintains high robustness throughout training. While the final performance slightly decreases compared to the cold-start model (from 85.87% to 83.80%), our method avoids collapse and achieves high task performance in early training stages. For example, at step 50 and 100, VRPO reaches 75.90% task completion rate (TCR) and an overall average (AVG) score of 88.13%, outperforming all baselines at these stages.

These results suggest that VRPO effectively preserves model capabilities under heavy noisy supervision and raises the lower bound of post-training performance. This stabilizing effect makes it significantly less prone to reward hacking or collapse compared to standard PPO approaches.

Step	TCR	ACR	GCR	AVG
Cold Start				
0	72.10%	94.30%	91.20%	85.87%
GRPO				
50	69.40%	91.90%	89.60%	83.63%
100	35.80%	50.00%	58.50%	48.10%
150	40.90%	35.00%	41.40%	39.10%
200	41.70%	30.20%	36.90%	36.27%
Last	40.70%	30.10%	37.70%	36.17%
PPO				
50	75.70%	**95.40%**	93.40%	**88.17%**
100	65.90%	90.00%	88.30%	81.40%
150	36.00%	58.90%	62.30%	52.40%
200	37.50%	50.90%	55.80%	48.07%
Last	39.10%	38.60%	42.70%	40.13%
Reward model improvement method base PPO				
50	71.90%	92.80%	91.70%	85.47%
100	65.30%	88.80%	88.90%	81.00%
150	37.50%	64.30%	64.80%	55.53%
200	35.70%	56.20%	57.40%	49.77%
Last	34.80%	54.30%	53.90%	47.67%
OURS				
50	75.60%	94.70%	**94.10%**	88.13%
100	**75.90%**	94.50%	93.80%	88.07%
150	72.40%	91.70%	91.90%	85.33%
200	70.00%	89.40%	91.90%	83.77%
Last	68.90%	91.30%	91.20%	83.80%

Table 4: Trajectory-level generalization performance across different methods and training steps. Our method maintains high performance even in last stages, beyond GRPO, PPO, and the reward model improvement method based on PPO.

B.3 Additional experimental details in the Math and Science Task

To further evaluate the effectiveness of our approach in rule-based reward scenarios, we conducted a series of experiments covering both mathematical and factual reasoning domains in test-time inference settings. Specifically, we trained and evaluated the model using seven datasets. For each dataset, we performed multiple inferences with the original model and conducted voting-based result filtering, then trained on the filtered data before evaluating the model on the respective datasets. The datasets include four math-focused tasks: MATH500 (Hendrycks et al., 2021), AIME24, Minerva-Math (Lewkowycz et al., 2022), AMC23, and three factual knowledge tasks: SampleQA (Wei et al., 2024), GPQA, and HLE (Humanity's Last Exam). Table 5 presents accuracy after reasoning-enhanced training using different RL methods.

Despite noisy feedback, our value model learns effectively. As shown in Figure 7, the explained

Figure 6: Noise statistics in the math and science tasks with rule-based reward supervision during test-time optimization.

Figure 7: Prediction error of the value model across training steps.

variance of our method increases steadily during training, indicating closer alignment between predicted and GAE-derived returns. This trend is accompanied by a consistent drop in reward prediction error and reduction in high-variance outliers. As shown in Table 5, our method consistently outperforms other baseline methods in various domains by leveraging a strong value model with semantic-aware filtering. This improvement is evident in both mathematical and knowledge reasoning tasks. For instance, accuracy on AIME24 increases from 6.67% to 13.33%, and on HLE from 2.55% to 4.45%. These results highlight the model's ability to extract relevant information from noisy or ambiguous feedback and demonstrate its robust generalization across diverse domains.

B.4 Additional Ablation Experiment

VRPO effectively mitigates noise in mathematical tasks when applied to the LLaMA model series Recent studies(Wu et al., 2025) suggest that Qwen models may be less reliable for mathematical reasoning. Therefore, we design experiments using the LLaMA 3.1-8B-Instruct model. Tables 6 and 7 present its performance on four mathematical reasoning benchmarks under rule-based reward supervision. Specifically, Table 6 reports results in the test-time optimization setting, while Table 7

shows training-time optimization outcomes.

In the test-time optimization setting, only our proposed method achieves improvements over the base model, whereas PPO and GRPO both suffer performance degradation, underscoring VRPO's robustness under noisy supervision. In the training-time optimization setting, due to limited model capacity and the prevalence of noisy samples (with overall data accuracy of only 42.33%), all methods experience performance drops. Nevertheless, our method exhibits the smallest decline and even achieves gains on Minerva-Math and AMC23, demonstrating stronger resilience in noisy training environments. These findings further highlight the generalizability of VRPO across different model architectures, confirming its effectiveness beyond Qwen models.

Effect of Variational Bottleneck on Noise Filtering As shown in Table 8, we compare different information bottleneck designs across tasks and obtain three takeaways: (1) A single-layer bottleneck delivers the best overall performance, with 4.17% and 4.45% accuracy on GPQA and HLE, indicating strong noise-filtering capability. (2) A two-layer bottleneck excels on high-complexity math tasks but underperforms on others, likely due to overfitting to noise. However, for language models like

Domain	Math				Factuality	Science	Knowledge	ALL
Method	MATH500	AIME24	Minerva-Math	AMC23	SampleQA	GPQA	HLE	AVG
Cold Start	71.60%	6.67%	18.75%	52.50%	1.62%	2.53%	2.55%	22.32%
GRPO	73.40%	11.67%	19.49%	56.67%	2.47%	3.08%	3.80%	24.37%
PPO	73.60%	10.00%	19.49%	55.00%	2.43%	2.54%	3.56%	23.80%
Ours	**74.40%**	**13.33%**	**20.22%**	**61.67%**	**2.61%**	**4.17%**	**4.45%**	**25.84%**

Table 5: Accuracy (%) on test-time optimization with rule-based rewards. Our method achieves gains across various datasets and domains.

Method	MATH 500	AIME 24	Minerva Math	AMC 23	AVG
Base	**49.80%**	**10.00%**	17.28%	24.17%	25.31%
GRPO	49.20%	6.67%	16.18%	**27.50%**	24.89%
PPO	46.20%	6.67%	**18.01%**	25.00%	23.97%
Ours	49.40%	**10.00%**	17.65%	**27.50%**	**26.14%**

Table 6: Test-time optimization results on mathematical reasoning benchmarks using LLaMA 3.1-8B-Instruct under noisy rule-based reward supervision. Our method is the only one that improves upon the base model, demonstrating superior robustness under noisy feedback.

Method	MATH 500	AIME 24	Minerva Math	AMC 23	AVG
Base	**49.80%**	**10.00%**	17.28%	24.17%	**25.31%**
GRPO	42.40%	3.33%	17.28%	**32.50%**	23.88%
PPO	41.00%	6.67%	17.65%	25.83%	22.79%
Ours	41.40%	**10.00%**	**18.01%**	30.00%	24.85%

Table 7: Training-time optimization results on the math task using LLaMA 3.1-8B-Instruct under noisy reward conditions. Due to weak base performance and high noise, all methods show a performance drop, but ours degrades the least and even improves results on Minerva-Math and AMC23.

Qwen, which are pretrained on rich mathematical data, deeper value structures may facilitate deeper understanding, yielding benefits in math domains. (3) No bottleneck yields modest gains on low-noise datasets but collapses on noisy ones (e.g., AMC23 drops to 50.83%), showing high susceptibility to noisy or uncertain rewards. Overall, moderate architectural bottlenecks substantially improve the robustness and cross-task generalization of value modeling under noisy RL Training.

VRPO remains effective across models of different scales   Table 9 presents the results of the Qwen3-1.7B model on mathematical and scientific tasks under rule-based reward supervision during training-time optimization. The results demonstrate that, under noisy supervision, our method consistently outperforms baseline approaches such as PPO and GRPO, achieving an average accuracy of 58.37% on mathematical tasks and 2.81% on scientific tasks. These findings confirm the effectiveness of VRPO across model scales, and further highlight its robustness and generalization ability even in small-model settings.

C Additional Visualization

Figures 9, 10, 11, and 12 present a comparison of advantage estimations between PPO and our method (VRPO) on the same question outputs regardless of semantic quality. Furthermore, in the incorrect answer case (Figure 8), under both correct and incorrect answer conditions.

Our method demonstrates a clear ability to capture key semantic components. In the correct answer case (Figure 9), it effectively identifies meaningful concepts such as "massive" and "initial mass M", while also showing a higher advantage estimate for the correct answer (Figure 9) compared to the incorrect one (Figure 10). The model not only captures answer structures like box-based outputs but also makes more accurate judgments based on correctness.

In contrast, PPO fails to capture such distinctions. As seen in Figure 11, the advantage estimation for the correct answer collapses, with later tokens receiving increasing advantage values. This pattern can lead to length hacking, where the model learns to generate longer outputs regardless of semantic quality. Furthermore, in the incorrect answer case (Figure 12), PPO assigns high advantages to both relevant and irrelevant content, indicating a lack of focus on key semantic cues and ultimately degrading training performance.

Domain	Math				Factuality	Science	Knowledge
Method	MATH500	AIME24	Minerva-Math	AMC23	SampleQA	GPQA	HLE
Zero bottleneck	70.20%	**16.67%**	19.49%	50.83%	2.47%	2.17%	3.80%
Two bottleneck	73.20%	**16.67%**	**21.32%**	60.00%	2.45%	3.44%	3.62%
One bottleneck(**Ours**)	**74.40%**	13.33%	20.22%	**61.67%**	**2.61%**	**4.17%**	**4.45%**

Table 8: Performance comparison across domains and datasets using different bottleneck strategies.

Domain	Math				Factuality	Science	Knowledge	ALL
Method	MATH500	AIME24	Minerva-Math	AMC23	SampleQA	GPQA	HLE	AVG
Qwen3-1.7B								
Base	84.80%	35.00%	19.49%	69.17%	1.78%	2.36%	2.87%	30.78%
GRPO	84.20%	33.33%	22.79%	**79.17%**	1.60%	1.99%	3.94%	32.43%
PPO	83.80%	35.00%	22.06%	78.33%	**1.91%**	2.54%	3.94%	32.51%
Reinforce++	84.40%	41.67%	23.53%	75.83%	1.48%	2.36%	3.52%	33.26%
Dr.GRPO	83.40%	36.67%	22.43%	75.83%	1.50%	2.36%	3.10%	32.19%
Ours	**85.40%**	**46.67%**	**23.90%**	77.50%	1.50%	**2.72%**	**4.22%**	**34.56%**
Qwen3-8B								
Base	87.40%	41.67%	28.68%	75.83%	2.89%	3.10%	2.89%	34.64%
GRPO	89.20%	35.00%	28.68%	84.17%	3.03%	2.98%	3.24%	35.19%
PPO	86.40%	36.67%	30.51%	80.00%	2.82%	2.17%	3.29%	34.55%
Reinforce++	89.00%	45.00%	27.21%	84.17%	3.19%	**4.35%**	3.29%	36.60%
Dr.GRPO	87.80%	45.00%	27.94%	85.83%	2.50%	3.99%	3.10%	36.59%
Ours	**90.20%**	**46.67%**	**31.99%**	**86.67%**	**3.21%**	**4.35%**	**3.89%**	**38.14%**

Table 9: Accuracy (%) on train-time optimization with rule-based rewards across models of different scales. Our method achieves consistent improvements under both Qwen3-1.7B and Qwen3-8B models.

Physics Fission Problem

Problem: An atomic nucleus of mass M is at rest. A spontaneous fission occurs in which the nucleus splits into two fragments (and nothing else), such that one fragment is 2 times more massive than the other (in terms of their rest-masses). The sum of rest-masses of the two fragments is 99% of the initial mass M. If the rest-mass energy of the initial nucleus (before fission) was 300 GeV, what is the kinetic energy of the more massive fragment?

Assumptions: Velocities of the fragments are significantly smaller than the speed of light. Ignore the electrons.

Figure 8: Example problem from the GPQA dataset

Figure 9: Our method on correct answer. Key information such as "initial mass M" is successfully captured.

user An atomic nucleus of mass M is at rest. A spontaneous fission occurs in which the nucleus splits into two fragments (and nothing else), such that one fragment is 2 times more massive than the other (in terms of their rest-masses). The sum of rest-masses of the two fragments is 99% of the initial mass M. If the rest-mass energy of the initial nucleus (before fission) was 300 GeV, what is the kinetic energy of the more massive fragment (Assume that velocities of the fragments are significantly smaller than the speed of light. Ignore the electrons.) assistant 1. **Initial Setup** - The initial nucleus has mass M and rest-mass energy $300 \, \text{GeV}$ - After fission, two fragments with masses $m_1 = 0.33M$ and $m_2 = 0.66M$. Their combined rest mass is $0.99M$, which is 99% of the initial mass 2. **Conservation Laws** - **Momentum**: Since the initial momentum is zero, the total momentum of the fragments must also be zero. Thus, the momenta of the two fragments are equal in magnitude and opposite in direction. Let the velocities be v and $-v$ - **Energy**: The total energy after fission is the sum of the rest energies of the fragments and their kinetic energies. The initial rest energy is 300 GeV, so the kinetic energy must be 3 GeV (since $0.99 \times 300 = 297 \, \text{GeV}$, and $297 + 3 = 300$) 3. **Relativistic Energy-Momentum Relation** - For each fragment, the total energy $E = \gamma m c^2$, where $\gamma = \frac{1}{\sqrt{1 - v^2/c^2}}$ - The kinetic energy $K = E - m c^2$ 4. **Key Relationship** - The momenta of the fragments are related by $p_1 = \gamma_1 m_1 v$ and $p_2 = \gamma_2 m_2 v$. Since the total momentum is zero, $\gamma_1 m_1 v = \gamma_2 m_2 v$, leading to $\gamma_1 m_1 = \gamma_2 m_2$ 5. **Solving for Kinetic Energies** - Using the energy-momentum relation and the mass ratio, we find that the kinetic energy of the more massive fragment ($m_2 = 0.66M$) is twice that of the less massive fragment ($m_1 = 0.33M$) - Given the total kinetic energy is 3 GeV, the more massive fragment has $K_2 = 2 \, \text{GeV}$, and the less massive fragment has $K_1 = 1 \, \text{GeV}$ **Final Answer**: The kinetic energy of the more massive fragment is $\boxed{2 \, \text{GeV}}$.

Advantage Scale:

-1.651   0.013 (Avg)   2.018

Figure 10: Our method on incorrect answer. The wrong prediction is appropriately assigned low advantage.

user An atomic nucleus of mass M is at rest. A spontaneous fission occurs in which the nucleus splits into two fragments (and nothing else), such that one fragment is 2 times more massive than the other (in terms of their rest-masses). The sum of rest-masses of the two fragments is 99% of the initial mass M. If the rest-mass energy of the initial nucleus (before fission) was 300 GeV, what is the kinetic energy of the more massive fragment (Assume that velocities of the fragments are significantly smaller than the speed of light. Ignore the electrons.) assistant Answer: The problem involves an atomic nucleus at rest undergoing spontaneous fission into two fragments. Here's the analysis 1. **Initial Mass and Energy** - The initial mass M of the nucleus is related to its rest-mass energy: $E_0 = 300 \, \text{GeV}$, so $M = \frac{300 \, \text{GeV}}{c^2}$ 2. **Mass Distribution of Fragments** - One fragment is twice as massive as the other. Let the less massive fragment have mass m, so the more massive fragment has mass $2m$ - The sum of rest masses is 99% of the initial mass: $3m = 0.99M$, so $m = 0.33M$, giving masses $0.33M$ and $0.66M$ 3. **Conservation of Momentum** - Since the initial momentum is zero, the velocities of the fragments must be equal in magnitude and opposite in direction. Let the velocities be v and $-v$ - Momenta: $2m v$ and $m v$ 4. **Kinetic Energy Calculation** - Using non-relativistic kinetic energy approximation - Total kinetic energy $K_{\text{total}} = 3 \, \text{GeV}$ - Kinetic energies are proportional to the masses: $K_1 = \frac{p^2}{2m_1}$, $K_2 = \frac{p^2}{2m_2}$ - Ratio $\frac{K_2}{K_1} = \frac{m_1}{m_2} = \frac{0.33M}{0.66M} = \frac{1}{2}$ - Therefore, $K_2 = \frac{1}{2} K_1$. Solving $K_1 + K_2 = 3 \, \text{GeV}$ gives $K_1 = 2 \, \text{GeV}$ and $K_2 = 1 \, \text{GeV}$ 5. **Verification** - Relativistic energy-momentum relations confirm the non-relativistic approximation is valid **Final Answer**: The kinetic energy of the more massive fragment is $\boxed{1 \, \text{GeV}}$.

Advantage Scale:

-0.123   0.005 (Avg)   0.901

Figure 11: PPO on correct answer. The model fails to capture the semantic core and assigns low or inconsistent advantage.

user An atomic nucleus of mass M is at rest. A spontaneous fission occurs in which the nucleus splits into two fragments (and nothing else), such that one fragment is 2 times more massive than the other (in terms of their rest-masses). The sum of rest-masses of the two fragments is 99% of the initial mass M. If the rest-mass energy of the initial nucleus (before fission) was 300 GeV, what is the kinetic energy of the more massive fragment (Assume that velocities of the fragments are significantly smaller than the speed of light. Ignore the electrons.) assistant 1. **Initial Setup** - The initial nucleus has mass M and rest-mass energy $300 \, \text{GeV}$ - After fission, two fragments with masses $m_1 = 0.33M$ and $m_2 = 0.66M$. Their combined rest mass is $0.99M$, which is 99% of the initial mass 2. **Conservation Laws** - **Momentum**: Since the initial momentum is zero, the total momentum of the fragments must also be zero. Thus, the momenta of the two fragments are equal in magnitude and opposite in direction. Let the velocities be v and $-v$ - **Energy**: The total energy after fission is the sum of the rest energies of the fragments and their kinetic energies. The initial rest energy is 300 GeV, so the kinetic energy must be 3 GeV (since $0.99 \times 300 = 297 \, \text{GeV}$, and $297 + 3 = 300$) 3. **Relativistic Energy-Momentum Relation** - For each fragment, the total energy $E = \gamma m c^2$, where $\gamma = \frac{1}{\sqrt{1 - v^2/c^2}}$ - The kinetic energy $K = E - m c^2$ 4. **Key Relationship** - The momenta of the fragments are related by $p_1 = \gamma_1 m_1 v$ and $p_2 = \gamma_2 m_2 v$. Since the total momentum is zero, $\gamma_1 m_1 v = \gamma_2 m_2 v$, leading to $\gamma_1 m_1 = \gamma_2 m_2$ 5. **Solving for Kinetic Energies** - Using the energy-momentum relation and the mass ratio, we find that the kinetic energy of the more massive fragment ($m_2 = 0.66M$) is twice that of the less massive fragment ($m_1 = 0.33M$) - Given the total kinetic energy is 3 GeV, the more massive fragment has $K_2 = 2 \, \text{GeV}$, and the less massive fragment has $K_1 = 1 \, \text{GeV}$ **Final Answer**: The kinetic energy of the more massive fragment is $\boxed{2 \, \text{GeV}}$.

Advantage Scale:

-0.161   -0.019 (Avg)   0.103

Figure 12: PPO on incorrect answer. High advantage is mistakenly assigned to both key and irrelevant content, weakening semantic discrimination.