Counterfactual Fairness with Partially Known Causal Graph

Abstract

Fair machine learning aims to avoid treating individuals or sub-populations un-favourably based on *sensitive attributes*, such as gender and race. Those methods in fair machine learning that are built on causal inference ascertain discrimination and bias through causal effects. Though causality-based fair learning is attracting increasing attention, current methods assume the true causal graph is fully known. This paper proposes a general method to achieve the notion of counterfactual fairness when the true causal graph is unknown. To be able to select features that lead to counterfactual fairness, we derive the conditions and algorithms to identify ancestral relations between variables on a *Partially Directed Acyclic Graph (PDAG)*, specifically, a class of causal DAGs that can be learned from observational data combined with domain knowledge. Interestingly, we find that counterfactual fairness can be achieved as if the true causal graph were fully known, when specific background knowledge is provided: the sensitive attributes do not have ancestors in the causal graph. Results on both simulated and real-world datasets demonstrate the effectiveness of our method.

1 Introduction

With the widespread application of machine learning in various fields (e.g., hiring decisions [17], recidivism predictions [10, 1], and finance [46, 20]), the ethical and social impact of machine learning is receiving increasing attention. In particular, machine learning algorithms are sensitive to the bias in training data, which may render their decisions discriminatory against individual or sub-population group with respect to *sensitive attributes*, e.g., gender and race. For example, bias against African-Americans was found with COMPAS, a decision support tool used by U.S. courts to assess the likelihood of a defendant becoming a recidivist [11].

To achieve fair machine learning, a large body of methods have been proposed to mitigate bias according to different fairness measures. These methods can be roughly categorized into two groups. The first group focuses on devising statistical fairness notions, which typically indicate the statistical discrepancy between individuals or sub-populations, e.g., statistical parity [12], equalized odds [16], and predictive parity [7]. Built on the causal inference framework [32], the second group treats the presence of causal effect of the sensitive attribute on the decision as discrimination [56, 21, 23, 53, 52, 29, 49, 19, 3, 40, 57, 55, 22, 41, 47].

Among the causal fairness works, counterfactual fairness [23], which considers the causal effect of sensitive attributes on the individual level, has received much attention. Given the true causal graph, Kusner et al. [23] provide the conditions and algorithms for achieving counterfactual fairness in the constructed predictive model. Wu et al. [49] and Chiappa [3] extend counterfactual fairness by considering path-specific effects. When the counterfactual effect is unidentifiable, counterfactual fairness can be approximately achieved by lower and upper bounds of counterfactual effects [48].

Existing counterfactual fairness methods assume the availability of a causal directed acyclic graph (DAG) [31], which encodes causal relationships between variables. However, in many real-world scenarios, the causal DAG is often unknown due to insufficient understanding of the system under investigation. An obvious path forward is to infer the causal DAG from observational data using causal discovery methods [44, 8, 43, 5, 42, 18, 54, 36, 35]. Unfortunately, without strong assumptions on the data generating process, such as linearity [42] and additive noise [18, 36], one cannot uniquely recover the underlying true causal graph from observational data alone. In the general case, causal discovery methods could output a Markov equivalence class of DAGs that encode the same set of conditional independencies from data, which can be represented by a completely partially directed acyclic graph (CPDAG) [45, 5]. With additional background knowledge, we can discern more causal directions, which can be represented by a maximally partially directed acyclic graph (MPDAG) [27], but we still cannot obtain a unique causal DAG.

Following this augment, we have a natural question to answer: can we learn causal fairness with a partially known causal graph represented by MPDAG? [1] In a causal DAG, if a variable S has a causal path to another variable T, then S is an ancestor of T and T is a descendant of S. Counterfactual fairness deems the prediction to be counterfactually fair if it is a function of the non-descendants of sensitive attributes [23], which are straightforward to identify in DAGs. However, in an MPDAG, with respect to a variable S, a variable T can be either

- a *definite descendant* of S if T is a descendant of S in every equivalent DAG,
- a *definite non-descendant* of S if T is a non-descendant of S in every equivalent DAG,
- a *possible descendant* of S if T is neither a definite descendant nor a definite non-descendant of S.

To achieve counterfactual fairness in MPDAGs, we need to select the definite non-descendants and some possible descendants of the sensitive attributes that could be non-descendants in the true DAG to make prediction. This comes to the core challenge: the identifiability of the ancestral relation between two distinct variables in an MPDAG. We refer the interested readers to a summary of existing identifiability results in Appendix G.

In this paper, we assume no selection bias and presence of confounders because the causal discovery algorithms themselves will not work well in such challenging scenarios. Under this assumption, which can also be found in the most related work [56, 3, 6, 48], but removing the assumption on a fully directed causal DAG, we make the following main contributions towards achieving counterfactual fairness on MPDAGs:

- We provide a sufficient and necessary graphical criterion (Theorem 4.5) to check whether a variable is a definite descendant of another variable on an MPDAG;
- Based on the proposed criterion, we give an efficient algorithm (Algorithm 2) to identify ancestral relations between any two variables on an MPDAG;
- We propose the first approach for achieving counterfactual fairness on partially known causal graphs, specifically MPDAGs;
- We find that on an MPDAG, counterfactual fairness can be achieved as if the true causal graph is fully known with the assumption that the sensitive attributes can not have ancestors in the causal graph.

2 Background

In this section, we first review the structural causal model, causal graph and counterfactual inference. Then we introduce counterfactual fairness criterion and its intuitive implications.

2.1 Structural causal model, causal graph, and counterfactual inference

Structural causal model (SCM) [32] is a framework to model causal relations between variables. It is defined by a triple (U, V, F), where V are observable endogenous variables and U are unobserved exogenous variables that cannot be caused by any variable in V. F is a set of functions $f_1, ..., f_n$, one

---

[1]CPDAG is a special case of MPDAG without background knowledge, so we deal with MPDAG generally.

for each $V_i \in V$ expressing how V_i is dependant on its direct causes: $V_i = f_i(pa_i, U_i)$, where pa_i is the observed direct causes of V_i and U_i is the set of unobserved direct causes of V_i. The exogenous U_is are required to be jointly independent. The set of equations F induces a causal graph $\mathcal{D}$ over the variables, usually in the form of a directed acyclic graph (DAG), where the directed causes of V_i represents its parent set in the causal graph.

Based on SCM, one can perform counterfactual inference to answer the problems in the counterfactual world. For example, consider in a fairness context, A, Y and $\mathcal{X}$ represent the sensitive attributes, outcome of interest, and other observable attributes, respectively. For an individual $U = u$ with $A = a, Y = y$ and $\mathcal{X} = \mathbf{x}$, a common counterfactual query is: "For this individual u, what would the value of Y have been had A taken value a'". The solution, denoted as $Y_{A \leftarrow a'}(u)$ can be obtained by three steps in the deterministic case: Abduction, Action and Prediction [32, Chapter 7.1]. In probabilistic counterfactual inference, the procedure can be modified to estimate the posterior of u and the distribution of $Y_{A \leftarrow a'}(u)$.

DAGs, PDAGs and CPDAGs. In a directed acyclic graph (DAG), all edges are directed and there is no directed cycle in the graph; when some edges are undirected, we say it is a partially directed graph (PDAG). A DAG encodes a set of conditional independence relations based on the notion *d-seperation* [30]. Multiple DAGs are Markov equivalent if they encode the same set of conditional independence relations. A *Markov equivalence class* of a DAG $\mathcal{D}$ can be uniquely represented by a completed partially directed acyclic graph (CPDAG) $\mathcal{G}^*$, denoted by $[\mathcal{G}^*]$.

MPDAGs. The CPDAGs with background knowledge constraint is known as maximally oriented PDAGs (MPDAGs) [27], which can be obtained by applying Meek's rules R1, R2, R3 and R4 in [27]. The Algorithm 1 in [34] can be used to construct the MPDAG $\mathcal{G}$ from the CPDAG $\mathcal{G}^*$ and backgroud knowledge $\mathcal{B}$, where the background knowledge $\mathcal{B}$ is assumed to be the *direct causal information* in the form $X \rightarrow Y$, meaning that X is a direct cause of Y. The subset of Markov equivalent DAGs consistent with the background knowledge $\mathcal{B}$ can be uniquely represented by an MPDAG $\mathcal{G}$, denoted by $[\mathcal{G}]$. Both a DAG and a CPDAG can be regarded as special cases of an MPDAG when the background knowledge is completely known and not known, respectively.

2.2 Counterfactual fairness

Counterfactual fairness [23] is a fairness criterion based on SCM [32]. Let A, Y and $\mathcal{X}$ represent the sensitive attributes, outcome of interest and other observable attributes, respectively and the prediction of Y is denoted by $\hat{Y}$. For an individual with $\mathcal{X} = \mathbf{x}$ and $A = a$, we say the prediction $\hat{Y}$ is counterfactually fair if it would have been the same had A been a' in the counterfactual world as in the real world that A is a.

Definition 2.1 (Counterfactual fairness). *[23, Definition 5] We say the prediction $\hat{Y}$ is counterfactually fair if under any context $\mathcal{X} = \mathbf{x}$ and $A = a$,*

$$P(\hat{Y}_{A \leftarrow a}(U) = y | \mathcal{X} = \mathbf{x}, A = a) = P(\hat{Y}_{A \leftarrow a'}(U) = y | \mathcal{X} = \mathbf{x}, A = a),$$

for all y and any value a' attainable by A.

The definition of counterfactual fairness immediately suggests the following approach in Lemma 2.2 to design a counterfactually fair model.

Lemma 2.2. *[23, Lemma 1] Let $\mathcal{G}$ be the causal graph of the given model (U, V, F). Then $\hat{Y}$ will be counterfactually fair if it is a function of the non-descendants of A.*

3 Problem formulation

In this section, we introduce the task of achieving counterfactual fairness given PDAGs, especially MPDAGs that can be learned from observational data using causal discovery algorithms [44, 8, 4].

Lemma 2.2 in Section 2.2 implies learning a counterfactually fair prediction can be framed as selecting the non-descendants of A to predict Y. If a causal DAG is used to encode the causal relations of all attributes, finding all non-descendants of A is straightforward. However, as mentioned in Section 1, given observational data and optional background knowledge about direct causal information, we

132 can only learn a CPDAG or an MPDAG $\mathcal{G}$, instead of the true DAG $\mathcal{D} \in [\mathcal{G}]$. Unfortunately, not all
133 ancestral relations between A and attributes in $\mathcal{X}$ are identifiable in a CPDAG or MPDAG.

134 Therefore, to achieve counterfactually fair prediction, we have two problems to solve:

- 135 Identify the type of ancestral relations of any other attributes with A in $\mathcal{G}$, *i.e.*, identifying
  136 the definite non-descendants, definite descendants, and possible descendants of A in an
  137 MPDAG (Section 4);
- 138 Build a counterfactually fair model based on the identified ancestral relations (Section 5).

139 4 Identifiability of ancestral relations in MPDAGs

140 In this section, we give a sufficient and necessary graphical criterion on identifying the definite
141 ancestral relations between two distinct vertices in an MPDAG. We also provide an efficient algorithm
142 for implementing the proposed criterion. We denote the parents, children, siblings and adjacencies of
143 the node W in a graph $\mathcal{G}$ as $pa(W, \mathcal{G})$, $ch(W, \mathcal{G})$, $sib(W, \mathcal{G})$ and $adj(W, \mathcal{G})$, respectively. A *chord*
144 of a path in $\mathcal{G}$ is any edge joining two non-consecutive vertices on the path. A path without any chord
145 is called *chordless path*. In a graph $\mathcal{G} = (V, E)$, where V and E represent the node set and edge set
146 in $\mathcal{G}$, the *induced subgraph* of $\mathcal{G}$ over $V' \subset V$ is the graph with vertex V' and edges between vertices
147 in V', that is $E' \subset E$. A graph is *complete* if any two distinct vertices are adjacent.

148 4.1 Graphical criterion on identifying ancestral relations in MPDAGs

149 We first introduce the term *b-possibly causal path* [34] in MPDAGs where the prefix b- stands for
150 background.

151 **Definition 4.1** (b-possibly causal path, b-non-causal path). *[34, Definition 3.1] Suppose $p = \langle S = $*
152 *$V_0, ..., V_k = T \rangle$ is a path from S to T in an MPDAG $\mathcal{G}$, p is b-possibly causal in $\mathcal{G}$ if and only if no*
153 *edge $V_i \leftarrow V_j$, $0 \leq i \leq j \leq k$ is in $\mathcal{G}$, including the edge not on p. Otherwise, p is a b-non-causal*
154 *path in $\mathcal{G}$.*

155 Perković et al. [34] state that T is a definite non-descendant of S in an MPDAG $\mathcal{G}$ if and only if there
156 is no b-possibly causal path from S to T in $\mathcal{G}$. In this section, to identify whether T is a definite
157 descendant of S in an MPDAG, we provide a sufficient and necessary condition.

158 We extend the term *critical set* [14] in CPDAGs to *b-critical set* in MPDAGs.

159 **Definition 4.2** (b-Critical Set). *Let $\mathcal{G}$ be an MPDAG, S and T be two distinct vertices in $\mathcal{G}$. The*
160 *b-critical set of S with respect to T in $\mathcal{G}$ consists of all adjacent vertices of S lying on at least one*
161 *chordless b-possibly causal path from S to T.*

162 Based on Definition 4.2, we provide a sufficient and necessary graphical condition in Lemma 4.3 for
163 identifying the definite ancestral relation between two distinct vertices in an MPDAG.

164 **Lemma 4.3.** *Let $\mathcal{G}$ be an MPDAG and S, T be two distinct vertices in $\mathcal{G}$, then T is a definite*
165 *descendant of S in $\mathcal{G}$ if and only if the b-critical set of S with respect to T always contains a child of*
166 *S in every DAG $\mathcal{D} \in [\mathcal{G}]$.*

167 The proof of Lemma 4.3 is in Appendix B.1. Note that we have to enumerate all Markov equivalent
168 DAGs for checking the condition given in Lemma 4.3. To resolve this problem, we provide a
169 condition in Lemma 4.4 to check the graphical characteristic of the corresponding b-critical set in the
170 MPDAG directly. The graphical criterion in Lemma 4.4 has been proved by [14, Lemma 2] and [2,
171 Lemma 1] for CPDAGs. We extend it to general MPDAGs here.

172 **Lemma 4.4.** *Let $\mathcal{G}$ be an MPDAG and S, T be two distinct vertices in $\mathcal{G}$. Denote by $\mathbf{C}$ the b-critical*
173 *set of S with respect to T in $\mathcal{G}$, then $\mathbf{C} \cap ch(S, \mathcal{D}) = \varnothing$ for some DAG $\mathcal{D} \in [\mathcal{G}]$, if and only if $\mathbf{C} = \varnothing$,*
174 *or $\mathbf{C}$ induces a complete subgraph of $\mathcal{G}$ but $\mathbf{C} \cap ch(S, \mathcal{G}) = \varnothing$.*

175 The proof of Lemma 4.4 is in Appendix B.2. Building on Lemma 4.3 and Lemma 4.4, we arrived at
176 the desired sufficient and necessary graphical criterion in Theorem 4.5.

177 **Theorem 4.5.** *Let S and T be two distinct vertices in an MPDAG $\mathcal{G}$, and $\mathbf{C}$ be the b-critical set of S*
178 *with respect to T in $\mathcal{G}$. Then T is a definite descendant of S if and only if either S has a definite arrow*

into **C**, *that is* **C** $\cap ch(S, \mathcal{G}) \neq \varnothing$, *or S does not have a definite arrow into* **C** *but* **C** *is non-empty and induces an incomplete subgraph of $\mathcal{G}$.*

With Theorem 4.5, we can identify whether T is a definite descendant of S in an MPDAG by finding all chordless b-possibly causal path from S to T and checking graphical characteristic of the corresponding b-critical set. We provide an example to illustrate Theorem 4.5 in Appendix C.

4.2 Algorithms

Here we provide an efficient algorithm to identify the ancestral relation between any two distinct vertices in an MPDAG based on the theoretical results in Theorem 4.5. It is straightforward to identify the non-ancestral relation by checking if there exists a b-possibly causal path from the source to the target. However, discriminating between a definite ancestral relation and a possible ancestral relation in an MPDAG by Theorem 4.5 requires finding the b-critical set.

According to the definition of the b-critical set, we need to find all chordless b-possibly causal paths from the source variable to the target variable first. However, it is cumbersome to check whether a path is chordless, since it involves considering many edges not on the path. In Proposition 4.7 we propose a more efficient way to find b-critical sets by leveraging the relation between chordless path and definite status path in Lemma 4.6. We first provide the notion of *collider* and *definite status path*.

Colliders and Definite Status paths. In a path $p = \langle S = V_0, ..., V_k = T \rangle$, if $V_{i-1} \to V_i$ and $V_i \gets V_{i+1}$, then we say V_i is a *collider* on p. If V_{i-1} and V_{i+1} are not adjacent, then the triple $\langle V_{i-1}, V_i, V_{i+1} \rangle$ is called a *v-structure collided* on V_i, and V_i can be called *unshielded collider*. A node V_i is a *definite non-collider* on a path p if there is at least one edge out of V_i on p or $V_{i-1} - V_i - V_{i+1}$ is a subpath of p and V_{i-1} is not adjacent with V_{i+1}. A node is of *definite status* on a path if it is a collider, a definite non-collider or an endpoint on the path. A path p is of definite status if every node on p is of definite status.

Lemma 4.6. *Let S and T be two distinct vertices in an MPDAG $\mathcal{G}$. If p is a chordless path from S to T in $\mathcal{G}$, then p is of definite status.*

Proposition 4.7. *Let $\mathcal{G}$ be an MPDAG, S and T be two distinct vertices in $\mathcal{G}$. Denote by $\mathbf{C}_{ST}$ the b-critical set of S with respect to T in $\mathcal{G}$, then $\mathbf{C}_{ST} = \mathbf{F}_{ST}$, where $\mathbf{F}_{ST}$ denotes all adjacent vertices of S lying on at least one b-possibly causal path of definite status from S to T in $\mathcal{G}$ that there is no chord with S as an endpoint.*

Proposition 4.7 implies that, instead of enumerating all chordless b-possibly causal path from the source vertex to the target vertex, we enumerate b-possibly causal paths of definite status, excluding paths that contain any chord where the source vertex is an end node. The nodes adjacent to the source vertex on these paths constitute the desired b-critical set.

The proof of Lemma 4.6 and Proposition 4.7 are in Appendix B.4 and Appendix B.5, respectively.

Following from Proposition 4.7, Algorithm 1 shows how to efficiently find the b-critical set of S w.r.t. T in an MPDAG $\mathcal{G}$. Given an MPDAG $\mathcal{G}$, the source vertex S and the target vertex T, the output of Algorithm 1 is the b-critical set of S w.r.t. T in $\mathcal{G}$. Using the breadth-first-search algorithm, Algorithm 1 searches b-possibly causal path of definite status without any chord ending in S from S to T. A detailed explanation of this algorithm is provided in Appendix D.

Finally, we present Algorithm 2 to identify the type of ancestral relation. We first find the b-critical set **C** of S with respect to T. When $\mathbf{C} = \varnothing$, there is no b-possibly causal path from S to T, so T is a definite non-descendant of S. When $\mathbf{C} \neq \varnothing$, using Theorem 4.5, we can decide whether T is a definite descendant or a possible descendant of S.

Since in Algorithm 1, the same triple like (α, ϕ, τ) can only be visited at most once, where α is a sibling or a child of S in the MPDAG $\mathcal{G}$, τ is a node on a b-possibly causal path of definite status from S to T without any chord ending in S, and ϕ lies immediately before τ on such path. The complexity of Algorithm 1 in the worst case is $\mathcal{O}(|sib(S, \mathcal{G}) + ch(S, \mathcal{G})| * |E(\mathcal{G})|)$, where $|E(\mathcal{G})|$ is the number of edges in $\mathcal{G}$. Consequently, the computational complexity of Algorithm 2 is $\mathcal{O}(|sib(S, \mathcal{G}) + ch(S, \mathcal{G})| * |E(\mathcal{G})|)$.

Algorithm 1 Finding the b-critical set of S with respect to T in an MPDAG

1: **Input:** MPDAG $\mathcal{G}$, two distinct vertices S and T in $\mathcal{G}$.
2: **Output:** The b-critical set $\mathbf{C}$ of S with respect to T in $\mathcal{G}$.
3: Initialize $\mathbf{C} = \varnothing$, a waiting queue $\mathcal{Q} = [\,]$, and a set $\mathcal{H} = \varnothing$,
4: **for** $\alpha \in sib(S) \cup ch(S)$ **do**
5:     add (α, S, α) to the end of $\mathcal{Q}$,
6: **while** $\mathcal{Q} \neq \varnothing$ **do**
7:     take the first element (α, ϕ, τ) out of $\mathcal{Q}$ and add it to $\mathcal{H}$;
8:     **if** $\tau = T$ **then**
9:         add α to $\mathbf{C}$, and remove from $\mathcal{S}$ all triples where the first element is α;
10:     **else**
11:         **for** each node β in $\mathcal{G}$ **do**
12:             **if** $\tau \rightarrow \beta$ or $\tau - \beta$ **then**
13:                 **if** $\tau \rightarrow \beta$ or ϕ is not adjacent with β or τ is the endnode **then**
14:                     **if** β and S are not adjacent **then**
15:                         **if** $(\alpha, \tau, \beta) \notin \mathcal{H}$ and $(\alpha, \tau, \beta) \notin \mathcal{Q}$ **then**
16:                             add (α, τ, β) to the end of $\mathcal{Q}$,
17: **return C**

Algorithm 2 Identify the type of ancestral relation of S with respect to T in an MPDAG

1: **Input:** MPDAG $\mathcal{G}$, two distinct variables S and T in $\mathcal{G}$.
2: **Output:** The type of ancestral relation between S and T.
3: Find the b-critical set $\mathbf{C}$ of S with respect to T in $\mathcal{G}$ by Algorithm 1.
4: **if** $|\mathbf{C}| = 0$ **then**
5:     **return** T is a definite non-descendant of S.
6: **if** S has an arrow into $\mathbf{C}$ or $\mathbf{C}$ induces an incomplete subgraph of $\mathcal{G}$ **then**
7:     **return** T is a definite descendant of S.
8: **return** T is a possible descendant of S.

---

5 Counterfactual fairness in MPDAGs

Now, we return to our problem of learning counterfactually fair models via selecting features from $\mathcal{X}$. We will consider two cases: 1) a general MPDAG and 2) an MPDAG learned with background knowledge that A is a root node.

5.1 General case

We can identify the set of definite descendants, possible descendants and definite non-descendants of the sensitive attribute by simply applying Algorithm 2 to each pair of sensitive and any other attribute, which is concluded in Algorithm 4. The detailed description of Algorithm 4 is provided in Appendix E. As the computational complexity of Algorithm 2 in the worst case is $\mathcal{O}(|sib(S, \mathcal{G}) + ch(S, \mathcal{G})| * |E(\mathcal{G})|)$, the complexity of Algorithm 4 is directly $\mathcal{O}(|sib(S, \mathcal{G}) + ch(S, \mathcal{G})| * |E(\mathcal{G})| * |V(\mathcal{G})|)$, where $|E(\mathcal{G})|$ is the number of edges and $|V(\mathcal{G})|$ is the number of nodes in $\mathcal{G}$. We consider two feature selection methods. The first method (called `Fair`) only selects the definite non-descendants, which ensures counterfactual fairness. However, the number of definite non-descendants in an MPDAG might be too small, resulting in low prediction accuracy. Therefore, we also propose a second method (called `FairRelax`), which uses possible descendants of A to increase the prediction accuracy at the cost of a (possibly small) violation of counterfactual fairness.

5.2 Under root node assumption

Kusner et al. [23, Section 3.2] mentioned the ancestral closure of sensitive attributes, meaning that typically we should expect the sensitive attribute set A to be closed under ancestral relationships given by the causal graph. For instance, in the example that religion can be affected by the geographical place of origin, if *religion* is a sensitive attribute and *geographical place of origin* is a parent of *religion*, then it should also be in A. Therefore, A will be the root node in most cases except some

counterintuitive scenarios. Thus, we consider the following assumption, which is often true in real-world datasets.

Assumption 5.1. *The sensitive attribute can only be a root node in a causal MPDAG.*

For example, 'sex' cannot be caused by factors like 'education' and 'salary'. In an MPDAG $\mathcal{G}$, given Assumption 5.1, the ancestral relation between the sensitive attribute and any other attribute is fully identified, as shown in the following proposition.

Proposition 5.2. *In a MPDAG $\mathcal{G}$ with sensitive attribute A, if Assumption 5.1 holds, then any other attribute is either a definite descendant or definite non-descendant of A. Moreover, an arbitrary attribute W is a definite descendant of A if and only if there is a causal path from A to W in $\mathcal{G}$.*

The proof of Proposition 5.2 is in Appendix B.6. From Proposition 5.2, it is very interesting to see that fitting a model with the definite non-descendants of A in $\mathcal{G}$ is exactly the same thing as fitting a model with the non-descendants of A in the true DAG $\mathcal{D}$. Thus, the counterfactual fairness can be achieved as if the true causal DAG is fully known.

Under Assumption 5.1, since there is a causal path from A to any definite descendant of A, we can directly identify whether a target attribute is a descendants of A by checking if there is a causal path from A to the target. To find all definite descendants in an MPDAG, we can use a breath first search algorithm with computational complexity $\mathcal{O}(|V| + |E|)$, where $|V|$ is the number of nodes and $|E|$ is the number of edges in $\mathcal{G}$. Then the remaining nodes are definite non-descendants of A in $\mathcal{G}$.

6 Experiment

In this section, we illustrate our approach on a simulated and a real-world dataset by evaluating the prediction performance and fairness of our approach. The prediction performance is evaluated by root mean squared error (RMSE). The counterfactual unfairness can be measured by the discrepancy of the predictions in the real world and counterfactual world for each individual. In addition, unfairness can also be revealed by comparing the distributions of the predictions in two worlds, which coincide if the prediction is counterfactually fair.

Baselines. We consider three baselines: 1) `Full` is a standard model that uses all attributes, including the sensitive attributes to make predictions, 2) `Unaware` is a model that uses all attributes except the sensitive attributes to make predictions, and 3) `Oracle` is a model that makes predictions with all attributes that are non-descendants of the sensitive attribute given the groundtruth DAG. As mentioned in Section 5, our proposed methods include `FairRelax`, which makes predictions using all definite non-descendants and possible descendants of the sensitive attribute in an MPDAG, and `Fair`, which makes predictions using all definite non-descendants of the sensitive attribute in an MPDAG.

6.1 Synthetic data

The synthetic data is generated from linear structural equation models according to a random DAG. As the simulated DAG is known, we obtain the CPDAG from the true DAG without running the causal discovery algorithms.[2] We also add background knowledge to turn a CPDAG into its corresponding MDPAG.

We first randomly generate DAGs with d nodes and $2 \times d$ directed edges from the graphical model Erdős-Rényi (ER), where d is chosen from $\{10, 20, 30, 40\}$. For each setting, we generate 100 DAGs. For each DAG $\mathcal{D}$, two nodes are randomly chosen as the outcome and the sensitive attribute, respectively. The sensitive attribute can have two or three values, drawn from a Binomial([0,1]) or Multinomial([0,1,2]) distribution separately. The weight, β_{ij}, of each directed edges $X_i \rightarrow X_j$ in the generated DAG, is drawn from a Uniform($[-2, -0.5] \cup [0.5, 2]$) distribution. The data are generated according to the following linear structural equation model:

$$X_i = \sum_{X_j \in pa(X_i)} \beta_{ij} X_j + \epsilon_i, i = 1, ..., n, \tag{1}$$

---

[2]Given a sufficiently large sample size, current causal discovery algorithms can recover the CPDAG with high accuracy on the simulated data.

where $\epsilon_1, ..., \epsilon_n$ are independent $N(0, 1.5)$. Then we generate one sample with size 1000 for each DAG. The proportion of training and test data is splitted as $0.8 : 0.2$. Once the CPDAG $\mathcal{G}^*$ is obtained, where $\mathcal{D} \in [\mathcal{G}^*]$, we randomly generate the direct causal information $A \rightarrow B$ as the background knowledge from the edges where $A \rightarrow B$ is in DAG $\mathcal{D}$, while $A - B$ is in CPDAG $\mathcal{G}^*$. We show a randomly generated DAG $\mathcal{D}$, the corresponding CPDAG $\mathcal{G}^*$ and MPDAG $\mathcal{G}$ as in Figure 6, see Appendix F.1. For additional experiments based on non-linear structural equations and varying proportion of possible background knowledge, please refer to Appendix F.6 and Appendix F.7, respectively.

Counterfactual fairness. According to the predefined linear causal model, we first generate the counterfactual data given counterfactual sensitive attributes. For each individual, the noise of any counterfactual feature is the same as that in the observational data. In order to evaluate the counterfactual fairness of the baseline methods, we sample data from both the original and counterfactual data and fit them with all the models. Here, unfairness can be measured by the absolute difference of two predictions, $\hat{Y}_{A \leftarrow a}(u)$ and $\hat{Y}_{A \leftarrow a'}(u)$. The results for each model with different graph settings are shown in Table 1 and Figure 1a. Obviously, `Oracle` and `Fair` is counterfactually fair, since they do not use any feature that is causally dependant on the sensitive attribute. `Full` and `Unaware` have high counterfactual unfairness, while our `FairRelax` has very low counterfactual unfairness. Additionally, when the model is counterfactually fair, the distributions of the predictions in two worlds should lie on top of each other, as in the `Oracle` and `Fair` models. Although counterfactual unfairness is exhibited in the other three models, `FairRelax` is closer to strictly counterfactually fair methods. An exemplary density plot of the predictions of all the models in one original and counterfactual dataset is included in Appendix F.2.

Table 1: Average unfairness and RMSE for synthetic datasets on held-out test set. For each graph setting, the unfairness gets decreasing from left to right and the RMSE gets increasing from left to right.

	Node	Edge	Full	Unaware	FairRelax	Oracle	Fair
Unfairness	10	20	0.288 ± 0.363	0.200 ± 0.322	0.023 ± 0.123	0.000 ± 0.000	0.000 ± 0.000
	20	40	0.203 ± 0.341	0.165 ± 0.312	0.019 ± 0.145	0.000 ± 0.000	0.000 ± 0.000
	30	60	0.155 ± 0.304	0.143 ± 0.312	0.02 ± 0.123	0.000 ± 0.000	0.000 ± 0.000
	40	80	0.095 ± 0.189	0.075 ± 0.182	0.009 ± 0.055	0.000 ± 0.000	0.000 ± 0.000
RMSE	10	20	0.621 ± 0.251	0.637 ± 0.261	1.031 ± 0.751	1.065 ± 0.751	1.137 ± 0.824
	20	40	0.595 ± 0.255	0.599 ± 0.253	0.818 ± 0.4888	0.847 ± 0.55	0.952 ± 0.645
	30	60	0.597 ± 0.24	0.601 ± 0.242	0.797 ± 0.489	0.849 ± 0.644	1.024 ± 0.908
	40	80	0.600 ± 0.273	0.601 ± 0.272	0.755 ± 0.441	0.766 ± 0.452	0.800 ± 0.480

(a) Average unfairness for each model and graph setting. (b) Average RMSE for each model and graph setting.

Figure 1: Average unfairness and RMSE for synthetic datasets on held-out test set. For each graph setting, the unfairness gets decreasing from left to right, while RMSE has the opposite trend. The extreme unfairness and high RMSE is because almost all attributes are descendants of the sensitive attribute in around $10/100$ randomly generated graphs. This also explains why the standard deviation of unfairness for the model `Full`, `Unware`, `FairRelax` and RMSE for `FairRelax`, `Oracle` and `Fair` is that large in Table 1.

Table 2: Average RMSE and unfairness for Student dataset on held-out test sets.

	Full	Unaware	FairRelax	Fair
Unfairness	0.761 ± 0.228	0.250 ± 0.085	0.000 ± 0.000	0.000 ± 0.000
RMSE	3.49 ± 0.292	3.482 ± 0.297	3.509 ± 0.356	3.509 ± 0.356

Accuracy. For each graph setting, we report average RMSE achieved on 100 causal graphs by fitting a linear regression model for the baselines and our proposed models in Table 1 and Figure 1b. We can observe that, for each graph setting, the `Full` model obtains the lowest RMSE, which is not surprising as it uses all features. In addition, our `FairRelax` methods obtains better accuracy than the strictly counterfactually fair methods `Fair` and `Oracle`, which is consistent with the accuracy-fairness trade-off phenomenon. More discussion on accuracy-fairness trade-off is included in Appendix H.

6.2 Real data

The UCI Student Performance Data Set [9] regarding students performance in Mathematics is used in this experiment. The data attributes include student grade in secondary education, demographic, social, and school related features. It contains 395 students records with 32 attributes. We regard *sex* as the sensitive attribute in this dataset. Besides, we remove the first, second and final period grade, denoted by *G1,G2*, and *G3* in the dataset and generate the value of target attribute *Grade* as the average of *G1,G2*, and *G3*.

In this section, we first learn the corresponding CPDAG from this dataset leveraging the GES structure learning algorithm [4], which is implemented by a general causal discovery software - TETRAD [37]. After uploading the preprocessed data, we can learn the CPDAG $\mathcal{G}^*$. The evolution of the CPDAG to MPDAG is shown in Appendix F.3.

Our experiments are carried out under the root node assumption on the MPDAG $\mathcal{G}$ in Figure 8c, as *sex* cannot be caused by other variables in the dataset. Due to the space limit, Figure 8c is provided in Appendix F.3. Thus, the ancestral relations can be fully identified according to our theoretical results in Section 5.2. Our algorithm will find all the non-descendants of the sensitive attribute. On this dataset, the definite descendants of *sex* can be identified as *{Walc, goout, Dalc, studytime}* and all the other nodes are definite non-descendants of *sex*.

The counterfactual fairness and accuracy are measured in almost the same way as in Section 6.1. The details on counterfactual data generation and model fitting can be referred to Appendix F.4. The results are reported in Table 2. Since under the root node assumption, there is no possible descendants of the sensitive attribute, the model `Fair` and `FairRelax` give the same RMSE result and both of them achieve counterfactual fairness at the cost of slight accuracy decrease. Instead, the model `Full` and `Unaware` are unfair and the `Full` model is more unfair than `Unaware`. Besides, the distribution of predictions for the original and counterfactual data for all models have the same trend as the synthetic data. The corresponding density plot is included in Appendix F.5.

7 Conclusion and discussions

In this paper, we have developed a general approach to achieve counterfactual fairness when the true causal graph is unknown. In order to select features that lead to counterfactual fairness, we propose a sufficient and necessary condition and an efficient algorithm to identify the ancestral relations between any distinct vertices on an MPDAG, a Markov equivalence class of causal DAGs that can be learnt from observational data and domain knowledge. Furthermore, an intriguing finding is that, under the assumption that the sensitive attribute can only be a root node in the graph, there is no possible descendant of the sensitive attribute, so that the fair features can be selected correctly whatever the true DAG is. Experiments on synthetic and real-world dataset show the effectiveness of our method. Throughout this paper, we assume no selection bias and presence of confounders because the causal discovery algorithms themselves will not work well in such challenging scenarios. Therefore, an interesting future direction is to achieve counterfactual fairness on partially ancestral graphs [38, 51].

References

[1] Tim Brennan, William Dieterich, and Beate Ehret. Evaluating the predictive validity of the compas risk and needs assessment system. *Criminal Justice and Behavior*, 36(1):21–40, 2009.

[2] Wenyu Chen, Mathias Drton, and Ali Shojaie. Definite non-ancestral relations and structure learning. *arXiv preprint arXiv:2105.10350*, 2021.

[3] Silvia Chiappa. Path-specific counterfactual fairness. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pages 7801–7808, 2019.

[4] David Maxwell Chickering. Learning equivalence classes of bayesian-network structures. *The Journal of Machine Learning Research*, 2:445–498, 2002.

[5] David Maxwell Chickering. Optimal structure identification with greedy search. *Journal of machine learning research*, 3(Nov):507–554, 2002.

[6] Yoichi Chikahara, Shinsaku Sakaue, Akinori Fujino, and Hisashi Kashima. Learning individually fair classifier with path-specific causal-effect constraint. In *International Conference on Artificial Intelligence and Statistics*, pages 145–153. PMLR, 2021.

[7] Alexandra Chouldechova. Fair prediction with disparate impact: A study of bias in recidivism prediction instruments. *Big data*, 5(2):153–163, 2017.

[8] Diego Colombo, Marloes H Maathuis, et al. Order-independent constraint-based causal structure learning. *J. Mach. Learn. Res.*, 15(1):3741–3782, 2014.

[9] Paulo Cortez and Alice Maria Gonçalves Silva. Using data mining to predict secondary school student performance. 2008.

[10] William Dieterich, Christina Mendoza, and Tim Brennan. Compas risk scales: Demonstrating accuracy equity and predictive parity. *Northpointe Inc*, 2016.

[11] Julia Dressel and Hany Farid. The accuracy, fairness, and limits of predicting recidivism. *Science advances*, 4(1):eaao5580, 2018.

[12] Cynthia Dwork, Moritz Hardt, Toniann Pitassi, Omer Reingold, and Richard Zemel. Fairness through awareness. In *Proceedings of the 3rd innovations in theoretical computer science conference*, pages 214–226, 2012.

[13] Zhuangyan Fang and Yangbo He. Ida with background knowledge. In *Conference on Uncertainty in Artificial Intelligence*, pages 270–279. PMLR, 2020.

[14] Zhuangyan Fang, Yue Liu, Zhi Geng, and Yangbo He. A local method for identifying causal relations under markov equivalence. *arXiv preprint arXiv:2102.12685*, 2021.

[15] Richard Guo and Emilija Perkovic. Minimal enumeration of all possible total effects in a markov equivalence class. In *International Conference on Artificial Intelligence and Statistics*, pages 2395–2403. PMLR, 2021.

[16] Moritz Hardt, Eric Price, and Nati Srebro. Equality of opportunity in supervised learning. *Advances in neural information processing systems*, 29:3315–3323, 2016.

[17] Mitchell Hoffman, Lisa B Kahn, and Danielle Li. Discretion in hiring. *The Quarterly Journal of Economics*, 133(2):765–800, 2018.

[18] Patrik O Hoyer, Dominik Janzing, Joris M Mooij, Jonas Peters, Bernhard Schölkopf, et al. Nonlinear causal discovery with additive noise models. In *NIPS*, volume 21, pages 689–696. Citeseer, 2008.

[19] Aria Khademi, Sanghack Lee, David Foley, and Vasant Honavar. Fairness in algorithmic decision making: An excursion through the lens of causality. In *The World Wide Web Conference*, pages 2907–2914, 2019.

[20] Amir E Khandani, Adlar J Kim, and Andrew W Lo. Consumer credit-risk models via machine-learning algorithms. *Journal of Banking & Finance*, 34(11):2767–2787, 2010.

[21] Niki Kilbertus, Mateo Rojas-Carulla, Giambattista Parascandolo, Moritz Hardt, Dominik Janzing, and Bernhard Schölkopf. Avoiding discrimination through causal reasoning. *arXiv preprint arXiv:1706.02744*, 2017.

[22] Matt Kusner, Chris Russell, Joshua Loftus, and Ricardo Silva. Making decisions that reduce discriminatory impacts. In *International Conference on Machine Learning*, pages 3591–3600. PMLR, 2019.

[23] Matt J Kusner, Joshua R Loftus, Chris Russell, and Ricardo Silva. Counterfactual fairness. *arXiv preprint arXiv:1703.06856*, 2017.

[24] Yue Liu, Zhuangyan Fang, Yangbo He, and Zhi Geng. Collapsible ida: Collapsing parental sets for locally estimating possible causal effects. In *Conference on Uncertainty in Artificial Intelligence*, pages 290–299. PMLR, 2020.

[25] Yue Liu, Zhuangyan Fang, Yangbo He, Zhi Geng, and Chunchen Liu. Local causal network learning for finding pairs of total and direct effects. *J. Mach. Learn. Res.*, 21:148–1, 2020.

[26] Marloes H Maathuis, Markus Kalisch, and Peter Bühlmann. Estimating high-dimensional intervention effects from observational data. *The Annals of Statistics*, 37(6A):3133–3164, 2009.

[27] Christopher Meek. Causal inference and causal explanation with background knowledge. In *Proceedings of the Eleventh conference on Uncertainty in artificial intelligence*, pages 403–410, 1995.

[28] Joris M Mooij and Tom Claassen. Constraint-based causal discovery using partial ancestral graphs in the presence of cycles. In *Conference on Uncertainty in Artificial Intelligence*, pages 1159–1168. PMLR, 2020.

[29] Razieh Nabi and Ilya Shpitser. Fair inference on outcomes. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 32, 2018.

[30] Judea Pearl. *Probabilistic reasoning in intelligent systems: networks of plausible inference*. Morgan kaufmann, 1988.

[31] Judea Pearl. *Causality*. Cambridge university press, 2009.

[32] Judea Pearl et al. Models, reasoning and inference. *Cambridge, UK: CambridgeUniversityPress*, 19, 2000.

[33] Emilija Perkovic. Identifying causal effects in maximally oriented partially directed acyclic graphs. In *Conference on Uncertainty in Artificial Intelligence*, pages 530–539. PMLR, 2020.

[34] Emilija Perković, Markus Kalisch, and Maloes H Maathuis. Interpreting and using cpdags with background knowledge. *arXiv preprint arXiv:1707.02171*, 2017.

[35] Jonas Peters and Peter Bühlmann. Identifiability of gaussian structural equation models with equal error variances. *Biometrika*, 101(1):219–228, 2014.

[36] Jonas Peters, Joris M Mooij, Dominik Janzing, and Bernhard Schölkopf. Causal discovery with continuous additive noise models. 2014.

[37] Joseph D Ramsey, Kun Zhang, Madelyn Glymour, Ruben Sanchez Romero, Biwei Huang, Imme Ebert-Uphoff, Savini Samarasinghe, Elizabeth A Barnes, and Clark Glymour. Tetrad—a toolbox for causal discovery. In *8th International Workshop on Climate Informatics*, 2018.

[38] Thomas Richardson and Peter Spirtes. Ancestral graph markov models. *The Annals of Statistics*, 30(4):962–1030, 2002.

[39] Anna Roumpelaki, Giorgos Borboudakis, Sofia Triantafillou, and Ioannis Tsamardinos. Marginal causal consistency in constraint-based causal learning. In *Causation: Foundation to Application Workshop, UAI*, 2016.

[40] Chris Russell, M Kusner, C Loftus, and Ricardo Silva. When worlds collide: integrating different counterfactual assumptions in fairness. In *Advances in neural information processing systems*, volume 30. NIPS Proceedings, 2017.

[41] Babak Salimi, Luke Rodriguez, Bill Howe, and Dan Suciu. Interventional fairness: Causal database repair for algorithmic fairness. In *Proceedings of the 2019 International Conference on Management of Data*, pages 793–810, 2019.

[42] Shohei Shimizu, Patrik O Hoyer, Aapo Hyvärinen, Antti Kerminen, and Michael Jordan. A linear non-gaussian acyclic model for causal discovery. *Journal of Machine Learning Research*, 7(10), 2006.

[43] Pater Spirtes, Clark Glymour, Richard Scheines, Stuart Kauffman, Valerio Aimale, and Frank Wimberly. Constructing bayesian network models of gene expression networks from microarray data. 2000.

[44] Peter Spirtes and Clark Glymour. An algorithm for fast recovery of sparse causal graphs. *Social science computer review*, 9(1):62–72, 1991.

[45] Peter Spirtes, Clark N Glymour, Richard Scheines, and David Heckerman. *Causation, prediction, and search*. MIT press, 2000.

[46] Latanya Sweeney. Discrimination in online ad delivery. *Communications of the ACM*, 56(5):44–54, 2013.

[47] Yongkai Wu, Lu Zhang, and Xintao Wu. On discrimination discovery and removal in ranked data using causal graph. In *Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pages 2536–2544, 2018.

[48] Yongkai Wu, Lu Zhang, and Xintao Wu. Counterfactual fairness: Unidentification, bound and algorithm. In *Proceedings of the Twenty-Eighth International Joint Conference on Artificial Intelligence*, 2019.

[49] Yongkai Wu, Lu Zhang, Xintao Wu, and Hanghang Tong. Pc-fairness: A unified framework for measuring causality-based fairness. *arXiv preprint arXiv:1910.12586*, 2019.

[50] Jiji Zhang. *Causal inference and reasoning in causally insufficient systems*. PhD thesis, Citeseer, 2006.

[51] Jiji Zhang. Causal reasoning with ancestral graphs. *Journal of Machine Learning Research*, 9:1437–1474, 2008.

[52] Junzhe Zhang and Elias Bareinboim. Equality of opportunity in classification: A causal approach. In *Proceedings of the 32nd International Conference on Neural Information Processing Systems*, pages 3675–3685, 2018.

[53] Junzhe Zhang and Elias Bareinboim. Fairness in decision-making—the causal explanation formula. In *Thirty-Second AAAI Conference on Artificial Intelligence*, 2018.

[54] Kun Zhang and Aapo Hyvarinen. On the identifiability of the post-nonlinear causal model. *arXiv preprint arXiv:1205.2599*, 2012.

[55] Lu Zhang and Xintao Wu. Anti-discrimination learning: a causal modeling-based framework. *International Journal of Data Science and Analytics*, 4(1):1–16, 2017.

[56] Lu Zhang, Yongkai Wu, and Xintao Wu. A causal framework for discovering and removing direct and indirect discrimination. *arXiv preprint arXiv:1611.07509*, 2016.

[57] Lu Zhang, Yongkai Wu, and Xintao Wu. Causal modeling-based discrimination discovery and removal: criteria, bounds, and algorithms. *IEEE Transactions on Knowledge and Data Engineering*, 31(11):2035–2050, 2018.