SCIPATHS: Forecasting Pathways to Scientific Discovery

Abstract

Scientific forecasting benchmarks often ask models to predict future papers, citations, or ideas. We introduce *discovery pathway forecasting*: given a target scientific contribution and the prior literature available at a specified time, models must identify the enabling contributions required to make the target feasible and determine which, if any, are realized by prior work. To support this task, we present SCIPATHS, a benchmark of 262 expert-annotated gold pathways and 2,444 silver pathways from machine learning and natural language processing papers. Each pathway records enabling contributions, functional roles, rationales, and prior-work groundings or unmapped decisions. Evaluating frontier and open-weight language models, we find that current systems recover only a small fraction of expert pathways under strict semantic matching, with the best model reaching 0.189 F1 and core methodological dependencies hardest to identify. Prior-work grounding improves substantially when gold enabling contributions are provided, indicating that decomposition quality is a major bottleneck for end-to-end scientific forecasting. SCIPATHS shifts evaluation from predicting relevant papers or isolated ideas toward forecasting the dependency structure that makes scientific contributions feasible.

1. Introduction

Forecasting scientific progress requires more than predicting which papers will be cited or which ideas may appear next. Scientific contributions rarely arise in isolation: they build on enabling contributions and, in turn, enable subsequent work (Fortunato et al., 2018; Uzzi et al., 2013; Wu et al., 2019). This raises a central question for scientific forecasting: *given a target contribution and the literature available before it, which enabling contributions are required to realize it?*

Existing work approaches this question indirectly. Meta-

science studies method recombination, concept prerequisites, and knowledge precedence to characterize how knowledge evolves (Chen et al., 2025; Zhu & Zamani, 2022; Xiang et al., 2026), but usually operates retrospectively over papers, concepts, or aggregate patterns. AI4Science systems support literature analysis, hypothesis generation, experiment design, and idea evaluation (Reddy & Shojaee, 2025; Boiko et al., 2023; Wang et al., 2024; Tomczak et al., 2025), but typically treat ideas as standalone outputs rather than forecasting the dependencies that make them feasible.

Closest to our work are citation-based scientific forecasting benchmarks. PRESCIENCE (Ajith et al., 2026) predicts key prior references that a target paper's authors are likely to build upon. GIANTS (He-Yueya et al., 2026) studies a complementary task: generating downstream insights from known parent papers. SCIPATHS targets the missing intermediate step: identifying the enabling contributions that make a target contribution feasible, and grounding each in prior work where such prior work exists. This contribution-level formulation avoids treating papers as atomic units and avoids evaluating models only by exact citation matching.

We introduce SCIPATHS, a benchmark for *discovery pathway forecasting*. Rather than forecasting citations or paper-level relevance, SCIPATHS asks models to forecast a pathway from a target contribution back to its enabling scientific building blocks. Expert annotators validate target contributions with downstream reuse evidence and decompose each under a necessity criterion: removing an enabling contribution would prevent the target from being realized in its claimed form. Each pathway records enabling contributions, functional roles, rationales, and prior-work groundings.

Our results show that this is a challenging forecasting capability. The best model reaches only 0.189 F1 under strict semantic matching, and core methodological dependencies are especially difficult to recover. Prior-work grounding improves substantially when gold enabling contributions are provided, showing that the main bottleneck is not only finding relevant papers, but identifying the right scientific building blocks to search for. This makes SCIPATHS directly relevant to forecasting-oriented AI systems: systems that propose future research directions must also identify the prerequisites and prior contributions needed to make those directions feasible.

Submitted to the AI Forecasting workshop (ICML 2026).

Figure 1. Example SCIPATHS instance and task structure. In Task A, the model receives a target contribution claim and predicts the enabling contributions required to realize it, with roles and rationales. Task B grounds each enabling contribution in prior work or marks it as unmapped. Selection provenance explains why the target contribution was included, but is not provided as input in the main forecasting setting. Rationale fragments are abbreviated for readability.

2. Discovery Pathway Forecasting

We formalize *discovery pathway forecasting* as the task of identifying the enabling contributions required to make a target contribution feasible and grounding those contributions in prior work where such prior work exists. A target contribution d is a method, dataset, benchmark, tool, resource, or finding that subsequent work demonstrably builds upon. Let t_d denote its publication time, and let $\mathcal{C}_{<t_d}$ denote the papers published before t_d.

Each target contribution d is associated with a set of enabling contributions

$$\mathcal{I}^*(d) = \{i_1, \ldots, i_k\},$$

where each i_j is a functional component required to realize d. We treat i_j as necessary if removing it would prevent d from being realized in its claimed form.

Each enabling contribution may be grounded in zero, one, or more representative prior papers. We define a grounding function

$$\phi : \mathcal{I}^*(d) \to 2^{\mathcal{C}_{<t_d}},$$

where $2^{\mathcal{C}_{<t_d}}$ denotes the power set of the pre-target corpus, so $\phi(i_j) \subseteq \mathcal{C}_{<t_d}$ is the set of prior papers that realize i_j. If no prior paper realizes i_j, then $\phi(i_j) = \emptyset$ and the contribution is marked as *unmapped*.

A discovery pathway is the annotated object

$$\mathcal{P}(d) = (d, \mathcal{I}^*(d), \phi, \rho, r),$$

where ρ assigns a functional role to each enabling contribution and r assigns a rationale. Since multiple decompositions may be valid, $\mathcal{P}(d)$ represents one plausible, evidence-grounded pathway rather than the only possible account of how the target contribution was realized.

We evaluate two stages. **Task A** is enabling-contribution generation: given d, models predict $\hat{\mathcal{I}}(d)$ with roles and rationales. **Task B** is prior-work grounding: models map each predicted contribution to prior work or mark it as unmapped. Unlike citation prediction, the objective is not to recover a target paper's reference list, but to identify the functional components required for a target contribution and the prior work, if any, that realizes them.

3. SCIPATHS Benchmark

Target selection. We construct SCIPATHS from machine learning and natural language processing papers published at NeurIPS, ICML, ACL, and EMNLP from 2023–2025. Our goal is not to annotate every contribution in each paper, but to select target contributions that later work demonstrably builds upon. Downstream reuse provides a practical selection signal: contexts indicating functional dependence suggest that the reused contribution is a suitable target for pathway annotation.

We first filter citation contexts for functional reuse. Following Shui et al. (2024), we apply a citation-intent classifier trained on ACL-ARC (Jurgens et al., 2018) to identify USES and EXTENDS contexts. We then apply LLM-based verification to remove false positives, such as contexts that mention another work using a cited paper rather than showing that the citing paper itself uses or extends it. From each verified context, we extract a concise contribution description, embed descriptions with a sentence encoder (Reimers & Gurevych, 2019), and cluster them to consolidate repeated uses across independent citing papers.

Expert annotation. For each validated target contribution, expert annotators construct a pathway. The protocol has four steps: rewrite the target contribution at the appropriate abstraction level; identify essential enabling contributions under the necessity criterion; ground each enabling contribution in representative prior work or mark it as unmapped; and assign roles, evidence spans, and rationales. Gold annotations were produced by five expert machine learning researchers. On an 8-paper pilot set, annotators agreed on target selection for all papers, yielding 10 shared target contributions. Enabling-contribution decomposition achieved 74.1% macro-averaged pairwise agreement after aligning semantically equivalent contributions, and grounding agreement over matched contributions was 90.3%.

Silver pathways. To support training and analysis, we also construct silver pathways in a hindsight setting using the target paper and downstream evidence clusters. A frontier LLM generates candidate pathways using the same schema as the gold annotations, and a critic selects among candidates based on necessity, sufficiency, functional relevance, grounding quality, and evidence support. SCIPATHS contains 262 expert-annotated gold pathways and 2,444 silver pathways. We split the gold set at the target-paper level into 50 development claims and 212 held-out test claims.

4. Experiments

Task A evaluation. Models generate enabling contributions for a target contribution. The main setting provides only the target contribution, with no additional paper context. We evaluate predicted contribution sets using semantic one-to-one matching. An LLM judge labels whether each predicted–gold pair expresses the same functional requirement; only full semantic matches count as positive. We then compute a maximum bipartite matching using the Hungarian algorithm so that each predicted and gold contribution can be matched at most once. We report precision, recall, F1, and average predicted contributions per target. Gemini 3.1 Pro is the primary judge, selected through a 60-pair human validation set because it is stricter and higher-precision than Gemini Flash (see Appendix D.2.

Task B evaluation. Task B evaluates whether systems can identify prior papers that realize enabling contributions. All conditions use the same fixed-budget Semantic Scholar pipeline: the system generates five queries, keeps the top 20 results per query, merges and deduplicates candidates, removes the target paper and post-target papers, ranks the remaining candidates, and evaluates top-K for $K \in \{5, 10\}$. We report paper-level precision, recall, and F1, as well as enabling-contribution Coverage@K: the fraction of mapped gold enabling contributions for which at least one acceptable grounding appears in the top-K list.

5. Results

Current models recover only a small fraction of expert pathways. Table 1 reports Task A in the main claim-only setting. Under strict one-to-one semantic matching, the best model, Gemini 3.1 Pro, reaches only 0.189 F1 and 0.246 recall. Gemini Flash and GPT-5.4 follow at 0.168 and 0.152 F1, while open-weight baselines remain near or below 0.06 F1. This shows that expert pathway recovery remains difficult even when the target contribution is given.

Additional evidence and silver supervision help, but do not close the gap. Citation-context evidence and target-paper Related Work improve over the claim-only setting for representative models. GPT-5.4 improves from 0.152 F1 to 0.200 with citation contexts and 0.212 with Related Work; Gemini 3.1 Pro improves from 0.189 to 0.217 with citation contexts. Fine-tuning Gemma-4-E4B-it on silver pathways improves claim-only performance from 0.061 to 0.101 F1. This shows that context and supervision help, but even richer inputs remain far below expert pathway recovery.

Core methods are hardest to recover. A role-level analysis shows that concrete dependencies such as model initializations and data sources are recovered more reliably than core methodological dependencies. At the target level, method contributions are also harder to decompose than datasets and benchmarks. Year-wise results show no consistent older-is-easier pattern, weakening a simple memorization explanation (Appendix D.5).

Gold enabling contributions substantially improve prior-work recovery. Table 2 reports Task B grounding at $K = 5$ with LLM reranking. Gold enabling contributions substantially improve Coverage@5 for both agents: from 0.083 to 0.357 with Gemini, and from 0.071 to 0.261 with GPT-5.4. Candidate coverage also increases, showing that gold contributions improve the retrieved candidate pool, not only reranking. Since candidate coverage remains above top-K coverage, failures reflect both missing relevant papers during retrieval and ranking retrieved groundings too low.

Table 1. Task A: enabling-contribution generation in the main claim-only setting on the held-out test set, evaluated with Gemini 3.1 Pro as the strict semantic matching judge.

Model	Recall	Precision	F1	Pred./target
Gemini 3.1 Pro	0.246	0.162	0.189	5.18
Gemini Flash	0.243	0.135	0.168	5.95
GPT-5.4	0.217	0.123	0.152	5.96
GPT-4.1	0.156	0.089	0.111	6.00
GPT-5 Mini	0.161	0.062	0.088	9.49
Gemma-4-E4B-it	0.069	0.058	0.061	4.39
Qwen3-4B-Instruct	0.070	0.056	0.060	4.43
GPT-4o	0.085	0.044	0.056	6.36
Llama-3-8B-Instruct	0.049	0.038	0.041	4.12
Llama-3.1-8B-Instruct	0.045	0.023	0.029	6.18

Table 2. Task B: prior-work grounding on the held-out test set at $K = 5$ with LLM reranking. The decomposition source indicates where enabling-contribution evidence comes from: none for claim-only, model-generated contributions for predicted conditions, semantically matched model outputs for matched-predicted diagnostics, and expert annotations for gold conditions.

Agent	Evidence condition	Source	Cov.@5	Rec.@5	Prec.@5	F1@5	Cand. cov.
Gemini	Claim only	—	0.083	0.055	0.038	0.041	0.120
	Predicted contributions	Gemini	0.062	0.042	0.030	0.033	0.122
	Matched predicted	Gemini	0.089	0.064	0.042	0.046	0.153
	Predicted contributions	Gemma-4	0.051	0.032	0.026	0.027	0.082
	Matched predicted	Gemma-4	0.107	0.053	0.045	0.046	0.141
	Gold contributions	Expert	**0.357**	**0.270**	**0.147**	**0.172**	**0.403**
GPT-5.4	Claim only	—	0.071	0.049	0.031	0.034	0.105
	Predicted contributions	GPT-5.4	0.055	0.041	0.027	0.028	0.067
	Matched predicted	GPT-5.4	0.065	0.042	0.024	0.027	0.104
	Gold contributions	Expert	0.261	0.195	0.109	0.127	0.303

Predicted decompositions do not yet improve end-to-end grounding. Model-predicted enabling contributions do not reliably improve over claim-only retrieval. Thus, current Task A outputs are not yet consistently useful search targets. In an enabling-contribution-level diagnostic, Gemini 3.1 Pro grounds only 26.8% of groundable gold contributions, though it correctly leaves most unmapped contributions unmapped, with 82.4% unmapped accuracy (Appendx E)

6. Discussion and Limitations

SCIPATHS evaluates a forecasting capability that sits between finding relevant prior work and generating new research ideas. Its contribution-level framing reveals failures that paper-level retrieval or idea-generation evaluations may miss: a model may retrieve a relevant paper, propose a plausible idea, or identify a broadly related prerequisite while still missing the specific functional component needed to realize the target contribution. Our diagnostics show this most clearly for core methodological dependencies, which are much harder to recover than nameable resources such as data sources or model initializations.

More broadly, SCIPATHS evaluates whether AI forecasting systems can reason backward from a target contribution to the scientific building blocks that would make it feasible: what must already exist, what remains unmapped, and what enabling contributions would need to be developed next. Our results caution against treating current language models as standalone scientific planners. Even for ML/NLP papers that may appear in pretraining data, models struggle to reconstruct the intermediate dependencies that made a target contribution feasible.

Limitations. SCIPATHS captures observed, evidence-grounded pathways rather than a unique account of how a target contribution was realized. Multiple decompositions may be valid, and experts may disagree about granularity or necessity despite our guidelines, rationales, and semantic matching protocol. Task A relies on an LLM judge for semantic matching; although we validate the judge against expert annotations and report higher-recall robustness results, judgment errors may affect absolute scores. Task B depends on Semantic Scholar search, so failures can reflect search limitations. Finally, the benchmark focuses on ML/NLP papers; extending it to other fields may require adapting role definitions and annotation guidelines.

References

Ajith, A., Singh, A., DeYoung, J., Kunievsky, N., Kozlowski, A. C., Tafjord, O., Evans, J., Weld, D. S., Hope, T., and Downey, D. Prescience: A benchmark for forecasting scientific contributions, 2026. URL https://arxiv.org/abs/2602.20459.

Boiko, D. A., MacKnight, R., Kline, B., and Gomes, G. Autonomous chemical research with large language models. *Nature*, 624:570 – 578, 2023. URL https://api.semanticscholar.org/CorpusID:266432059.

Chen, J., Zhang, K., Li, D., Feng, Y., Zhang, Y., and Deng, B. Structuring scientific innovation: A framework for modeling and discovering impactful knowledge combinations, 2025. URL https://arxiv.org/abs/2503.18865.

Fortunato, S., Bergstrom, C. T., Börner, K., Evans, J. A., Helbing, D., Milojević, S., Petersen, A. M., Radicchi, F., Sinatra, R., Uzzi, B., Vespignani, A., Waltman, L., Wang, D., and Barabási, A.-L. Science of science. *Science*, 359(6379):eaao0185, 2018. doi: 10.1126/science.aao0185. URL https://www.science.org/doi/abs/10.1126/science.aao0185.

He-Yueya, J., Singh, A., Gao, G., Li, M. Y., Yang, S., Finn, C., Brunskill, E., and Goodman, N. D. Giants: Generative insight anticipation from scientific literature, 2026. URL https://arxiv.org/abs/2604.09793.

Jurgens, D., Kumar, S., Hoover, R., McFarland, D., and Jurafsky, D. Measuring the evolution of a scientific field through citation frames. *Transactions of the Association for Computational Linguistics*, 6:391–406, 2018. doi: 10.1162/tacl_a_00028. URL https://aclanthology.org/Q18-1028/.

Reddy, C. K. and Shojaee, P. Towards scientific discovery with generative ai: Progress, opportunities, and challenges. In *AAAI*, pp. 28601–28609, 2025. URL https://doi.org/10.1609/aaai.v39i27.35084.

Reimers, N. and Gurevych, I. Sentence-BERT: Sentence embeddings using Siamese BERT-networks. In Inui, K., Jiang, J., Ng, V., and Wan, X. (eds.), *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 3982–3992, Hong Kong, China, November 2019. Association for Computational Linguistics. doi: 10.18653/v1/D19-1410. URL https://aclanthology.org/D19-1410/.

Shui, Z., Karypis, P., Karls, D. S., Wen, M., Manchanda, S., Tadmor, E. B., and Karypis, G. Fine-tuning language models on multiple datasets for citation intention classification. In Al-Onaizan, Y., Bansal, M., and Chen, Y.-N. (eds.), *Findings of the Association for Computational Linguistics: EMNLP 2024*, pp. 16718–16732, Miami, Florida, USA, November 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.findings-emnlp.974. URL https://aclanthology.org/2024.findings-emnlp.974/.

Tomczak, M., Park, Y., Hsu, C., Brown, P., Massa, D., Sankowski, P., Li, J., and Papanikolaou, S. Forecasting research trends using knowledge graphs and large language models. *Advanced Intelligent Systems*, 8, 09 2025. doi: 10.1002/aisy.202401124.

Uzzi, B., Mukherjee, S., Stringer, M., and Jones, B. Atypical combinations and scientific impact. *Science*, 342(6157):468–472, 2013. doi: 10.1126/science.1240474. URL https://www.science.org/doi/abs/10.1126/science.1240474.

Wang, Q., Downey, D., Ji, H., and Hope, T. SciMON: Scientific inspiration machines optimized for novelty. In Ku, L.-W., Martins, A., and Srikumar, V. (eds.), *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 279–299, Bangkok, Thailand, August 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.acl-long.18. URL https://aclanthology.org/2024.acl-long.18/.

Wu, L., Wang, D., and Evans, J. A. Large teams develop and small teams disrupt science and technology. *Nature*, 566:378 – 382, 2019. URL https://api.semanticscholar.org/CorpusID:61156556.

Xiang, S., Liu, B., Jiang, X., Huang, Z., and Ma, Y. Knowledge precedence networks: Mining progression patterns of scientific discoveries beyond prerequisites. *Information Processing Management*, 63(2, Part B):104424, 2026. ISSN 0306-4573. doi: https://doi.org/10.1016/j.ipm.2025.104424. URL https://www.sciencedirect.com/science/article/pii/S0306457325003656.

Zhu, Y. and Zamani, H. Predicting prerequisite relations for unseen concepts. In Goldberg, Y., Kozareva, Z., and Zhang, Y. (eds.), *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pp. 8542–8548, Abu Dhabi, United Arab Emirates, December 2022. Association for Computational Linguistics. doi: 10.18653/v1/2022.emnlp-main.585. URL https://aclanthology.org/2022.emnlp-main.585/.

A. Annotation Details

The annotation guidelines below summarize the annotator-facing protocol used during data collection.

A.1. Overview

The goal of SCIPATHS annotation is to identify, for each selected target contribution, the enabling contributions required to realize it and the prior work, if any, that realizes each enabling contribution. The annotation procedure has two substantive phases:

1. **Target contribution assessment**: validate downstream reuse evidence and rewrite the target contribution at the appropriate level of abstraction.

2. **Enabling-contribution annotation**: decompose the target contribution into necessary enabling contributions, ground each contribution in representative prior work when available or mark it as unmapped, assign roles, and justify each dependency.

The guiding counterfactual is:

If I had to realize this target contribution tomorrow, what enabling contributions would I still need?

This shifts annotation from citation recovery to enabling-contribution recovery. Annotators are not asked to list all relevant references, but to identify the functional requirements without which the target contribution could not be realized in its claimed form.

A.2. Phase 1: Target Contribution Assessment

Goal. The goal of Phase 1 is to determine whether a paper contains one or more valid target contributions supported by downstream reuse evidence, and to rewrite each target contribution at the correct level of abstraction.

A valid target contribution is:

A contribution, such as a method, dataset, benchmark, tool, resource, or finding, that subsequent work depends on to build, evaluate, or extend its own work.

This phase focuses on functional dependence, not popularity or citation frequency.

Decision procedure. Annotators inspect the candidate contribution and downstream usage clusters, verify whether later work functionally depends on the contribution, and then decide whether the contribution should be retained. Strong evidence includes direct reuse, training dependence, evaluation adoption, extension, adaptation, or other forms of functional dependence. Background citations, comparison-only usage, weak one-off mentions, or hallucinated cluster summaries are not sufficient.

A single paper may contain multiple target contributions. Annotators split contributions when a paper introduces distinct reusable outputs, such as a model and a benchmark, that enable different downstream uses and would require different enabling contributions. Annotators do not bundle multiple target contributions into a single claim.

Rewriting target contribution claims. Each rewritten target contribution should preserve:

$$[object] + [key\ property] + [what\ it\ enables].$$

A valid rewritten claim should be:

- **Atomic**: describes one contribution only;

- **Abstracted**: avoids paper-specific names when possible;

- **Functional**: states what the contribution does;

- **Causal**: specifies what the contribution enables;

- **Decomposable**: can be broken into enabling contributions in Phase 2.

For example:

> *Benchmark: A multi-turn dialogue sentiment reasoning benchmark, enabling evaluation of cross-utterance opinion*
> *and sentiment understanding.*

is preferred over:

> *The DiaASQ benchmark and dataset.*

Common failure modes include name-based claims, bundled claims, vague claims such as "improves performance," motivational claims, and implementation-level details.

A.3. Phase 2: Enabling-Contribution Annotation

Goal. The goal of Phase 2 is to identify the enabling contributions required to realize the validated target contribution and to ground each enabling contribution in prior work when available. This phase is not about selecting all relevant citations. It reconstructs the pathway through necessary functional components:

$$\text{target contribution} \rightarrow \text{enabling contributions} \rightarrow \text{prior-work grounding or unmapped.}$$

Core reasoning principles. Annotators follow three principles:

1. **Necessity**: each enabling contribution must be something without which the target contribution could not be realized in its claimed form.

2. **Functional abstraction**: enabling contributions should be expressed as capabilities, substrates, formulations, objectives, upstream resources, or mechanisms, not as paper sections, hyperparameters, or arbitrary citations.

3. **Evidence support**: evidence spans must come from the target paper and directly support the contribution–role–grounding decision.

Valid enabling contributions. A valid enabling contribution is a necessary functional requirement or upstream substrate for the target contribution. Common types include task formulations, conceptual paradigms, source datasets, training data, model initializations, objectives, representations, source websites or raw corpora, implementation resources, and evaluation protocols when central to the target contribution.

Good examples include:

- federated learning training and aggregation protocol for client–server PLM tuning;

- semantically aligned visual encoder for image understanding;

- upstream Turkish Wikipedia NER substrate for re-annotation;

- cross-utterance quadruple composition in dialogue.

Bad examples include:

- training for three epochs;

- stronger baseline models;

- methods section;

- evaluation on benchmark X when the benchmark is not part of the target contribution.

Grounding and unmapped decisions. For each enabling contribution, annotators choose a canonical grounding for annotation purposes:

- a representative prior study/resource, or

- NONE, meaning no single prior study or resource cleanly represents the enabling contribution.

A prior work should be selected when it directly provides, instantiates, or is reused as the enabling contribution. NONE should be selected when the enabling contribution is field-level, composite, paper-specific, or otherwise not attributable to a single clean prior study. This is a valid outcome: annotators should not force weak or fake groundings to avoid NONE. Additional valid studies/resources may be attached when several sources jointly instantiate an enabling contribution or when one canonical grounding is representative but not exhaustive.

A canonical grounding should be the cleanest representative of the enabling contribution: necessary rather than merely related, minimal rather than overly broad, and faithful to the actual role played in the target paper.

A.4. Functional Role Definitions

Annotators assign one role from the approved role set:

- **Core Method / Algorithm**: a prior method or algorithmic procedure that provides a necessary computational mechanism used to realize the target contribution, such as a training objective, model architecture, optimization procedure, or inference algorithm.

- **Conceptual Framework**: prior work that defines the task, problem formulation, representation, theoretical framework, or empirical phenomenon that the target contribution builds upon.

- **Data Source**: a dataset, corpus, website, or resource explicitly used as source material to construct another dataset or resource.

- **Training Data**: a dataset or labeled resource directly used to train, pretrain, fine-tune, or supervise a model. If a dataset is transformed, sampled, re-annotated, translated, or used to build a new dataset, annotators use **Data Source** instead.

- **Model Initialization**: a pretrained model or initialization essential to realizing the target contribution, such as initializing with pretrained BERT weights.

- **Evaluation Protocol**: a benchmark, metric, or annotation scheme directly reused and necessary to realize the target contribution. Benchmarks used only for breadth or comparison are excluded.

- **Implementation / Tooling**: software, infrastructure, or tooling explicitly required to implement the target contribution.

A.5. Annotation Fields

For each enabling contribution, annotators record:

- **Enabling contribution**: the functional component needed for the target contribution.

- **Canonical grounding**: the representative prior study/resource or NONE.

- **Additional groundings**: optional additional valid studies/resources.

- **Role**: one of the approved functional roles.

- **Contribution**: what the selected study/resource provides.

- **Rationale**: why the enabling contribution is necessary and why the grounding, if any, realizes it.

- **Evidence span**: a sentence or short span from the target paper supporting the dependency.

A good rationale answers: what is needed, why it is needed, and why the selected prior work provides it. Evidence spans should directly support the dependency and role assignment, not merely provide background or related-work context.

A.6. Quality Checklist

Before finalizing an annotation, annotators check:

- Is each enabling contribution truly necessary?

- Is it a functional requirement rather than an implementation detail?

- Is the selected prior study/resource the cleanest representative?

- Should the contribution instead be marked as NONE?

- Are additional groundings genuinely needed?

- Does the rationale explain necessity rather than similarity?

- Does the evidence span directly support the assigned role and grounding?

Common mistakes include listing citations instead of enabling contributions, choosing a study because it is famous rather than necessary, including evaluation datasets used only for comparison, forcing a grounding when NONE is correct, writing vague rationales, using evidence from the wrong stage of the pipeline, and ignoring direct source resources such as websites or corpora when they are explicitly used to construct a dataset.

A.7. Inter-Annotator Agreement

We measure inter-annotator agreement (IAA) for both stages of the enabling-contribution annotation: (i) identifying the necessary enabling contributions for a target contribution, and (ii) grounding those enabling contributions in prior studies or resources.

Enabling-contribution agreement. For each target contribution, we first construct an aligned enabling-contribution universe by grouping semantically equivalent annotations. Each annotator is then represented as a binary vector over this aligned universe, indicating whether they included each enabling contribution. Pairwise agreement is computed as the fraction of enabling contributions included by either annotator that were included by both annotators:

$$\text{Agreement}(a, b) = \frac{|\{i \in \mathcal{E} : x_{a,i} = 1 \land x_{b,i} = 1\}|}{|\{i \in \mathcal{E} : x_{a,i} = 1 \lor x_{b,i} = 1\}|},$$

where $\mathcal{E}$ is the aligned enabling-contribution universe for the target contribution and $x_{a,i}$ indicates whether annotator a included enabling contribution i.

Grounding agreement. Grounding agreement is computed separately from enabling-contribution agreement. For each pair of annotators, we consider only enabling contributions that both annotators included. We then compare whether their selected groundings refer to the same prior study, resource, or source family. When the same source appears as canonical for one annotator and as an additional grounding for another, we count it as agreement, since the disagreement is about placement rather than provenance. We also count NONE as agreement when both annotators judged that no single prior study or resource cleanly represents the enabling contribution.

For enabling contributions with multiple groundings, we compute fractional source overlap when needed. For example, if two annotators agree on two of four source-level groundings for a composite enabling contribution, that contribution receives partial grounding agreement. We then average grounding agreement across the enabling contributions shared by the annotator pair.

Qualitative disagreement patterns. Most disagreements are interpretable boundary cases rather than random contradictions. Annotators usually agree on the central enabling contributions for a target contribution, but sometimes differ on whether to represent an auxiliary or paper-specific component as a separate enabling contribution. The higher grounding agreement suggests that disagreements are mostly about enabling-contribution granularity rather than source provenance. When annotators identify the same enabling contribution, they generally select the same prior study or resource as the relevant grounding. This supports the reliability of the annotation framework: the task is difficult and high-granularity, but annotators converge on the main dependency structure and largely agree on the scientific provenance of matched enabling contributions.

A.8. LLM Usage in Annotation

Pathway annotation requires annotators to read the target paper, inspect downstream usage evidence, identify necessary enabling contributions, ground those contributions in prior work, and write evidence-backed rationales. During protocol development, we examined whether optional LLM-assisted review could improve annotation efficiency without changing the annotation target.

In the agreement pilot, two annotators completed the task without LLM assistance, while remaining annotators used different LLMs as auxiliary review tools. LLM-assisted annotators first read the target paper and drafted their own decomposition before consulting the model. They could then use the LLM to clarify paper details, check whether their draft omitted plausible enabling contributions, compare alternative phrasings, or help write clearer rationales and interface responses. All gold pathways were finalized by expert annotators; LLM outputs were used only as optional review aids and were never accepted without human verification.

Final annotation decisions always remained with the expert annotators. In particular, annotators made the final decisions about (i) which target contributions should be retained, (ii) which enabling contributions satisfied the necessity criterion, (iii) whether each enabling contribution should be grounded in prior work or marked as unmapped, and (iv) which evidence spans and rationales supported the decision.

We compared agreement across assisted and unassisted annotator pairs in the pilot. Agreement was similar across pairs: enabling-contribution decomposition pairwise means ranged from 69.3–78.1%, and grounding agreement ranged from 86.7–92.7%. The overall macro-averaged agreement was 74.1% for enabling-contribution decomposition and 90.3% for grounding over matched contributions. Based on these results, we allowed optional LLM-assisted review in the final workflow. In practice, LLM assistance was most useful for improving annotation efficiency, especially by helping annotators check draft decompositions and phrase rationales after substantive pathway decisions had been made.

B. Silver Pathway Construction

Figure 2. Silver annotation pipeline overview.

We construct silver pathways to provide additional training data and to support large-scale analyses of pathway structure. Silver pathways follow the same schema as the expert gold annotations, but are produced automatically in a hindsight setting using the target paper and downstream usage evidence clusters. They are intended for training and analysis only; all benchmark evaluation is conducted on expert-annotated gold pathways. Figure 2 provides our enabling contribution decomposition pipeline.

Inputs. For each candidate target contribution, the silver pipeline receives: (i) the target paper, (ii) downstream usage clusters indicating how later work reuses the contribution, and (iii) retrieved candidate prior work from the pre-t_d corpus. The use of the target paper makes this a hindsight construction setting, analogous to the expert annotation process, rather than a model-only forecasting setting.

Few-shot annotation prompting. To align automatic annotations with the expert schema, we prompt a frontier LLM with detailed few-shot examples of complete pathway annotations. We release the prompts as part of our code. These examples demonstrate how to split bundled contributions into separate target contributions, rewrite each target at the appropriate abstraction level, identify essential enabling contributions, exclude tempting non-enabling contributions, ground contributions in prior work or mark them as unmapped, assign functional roles, and provide evidence-backed rationales. The examples also emphasize the constructive necessity criterion: an enabling contribution should be included only if removing it would prevent the target contribution from being realized in its claimed form.

Candidate pathway generation. For each candidate target contribution, the model first validates the downstream usage evidence and expresses the target contribution at the appropriate level of abstraction, preserving the object, key property, and what the contribution enables. It then generates a candidate pathway containing enabling contributions, functional roles, grounding decisions, evidence spans, and rationales. For each enabling contribution, the model either selects representative prior work from the candidate pool or marks the contribution as unmapped when no prior study cleanly realizes it.

Candidate selection and formatting. Because a single target contribution can admit multiple plausible decompositions, the pipeline generates multiple candidate pathways. A critic then selects the best candidate according to necessity, sufficiency, functional relevance, grounding quality, and evidence support. The selected pathway is converted into the SciPaths schema, including target contribution, enabling contributions, roles, canonical and additional groundings when available, unmapped decisions, evidence spans, and rationales. We also run consistency checks to ensure that required fields are present and that grounding decisions are compatible with the available evidence.

Validation against gold annotations. We validate silver quality on the development set by comparing silver pathways against expert gold annotations. For target-contribution agreement, we compare whether the automatic pipeline identifies the same target contribution. For enabling-contribution decomposition, we use the same semantic matching protocol as Task A. For grounding, we evaluate matched enabling contributions and check whether the silver and gold annotations select the same grounding study. Under the strict judge used for the main benchmark, silver pathways achieve approximately 60% F1 for enabling-contribution decomposition; under a more permissive high-recall judge, F1 increases to 68.5%. The final silver pipeline improves enabling-contribution decomposition by 8.6 percentage points over the initial silver-generation baseline, with smaller gains in target splitting and grounding agreement which already had higher baseline agreement.

These results indicate that silver pathways provide useful supervision for training and large-scale analysis, while expert gold annotations remain the standard for benchmark evaluation.

C. Experimental Details

Task A evaluation. Task A evaluates enabling-contribution generation against expert annotations using semantic one-to-one matching. For each predicted–gold contribution pair within a target, an LLM judge assigns a semantic label. The main metric counts only full semantic matches as correct. After pairwise judgments are obtained, we enforce a one-to-one alignment between predicted and gold contributions using maximum bipartite matching over full-match edges. We then compute precision, recall, and F1 per target and report macro averages across targets. Partial matches are excluded from the main metric and used only in a separate diagnostic.

Judge model. Unless otherwise noted, Task A results use Gemini 3.1 Pro as the semantic matching judge. We selected this judge after validating Gemini 3.1 Pro and Gemini Flash against expert human labels: Gemini Flash is more permissive and higher-recall, while Gemini 3.1 Pro is stricter and higher-precision. We therefore use Gemini 3.1 Pro for the primary benchmark results and report Gemini Flash as a robustness check.

Task A settings. The main setting (**S1**) gives the model only the target contribution. **S2** additionally provides citation-context evidence about downstream reuse, and **S3** provides target-paper Related Work context. We also report a few-shot prompting condition and a silver fine-tuning condition. These diagnostic settings test whether models improve when given richer evidence, task demonstrations, or supervised pathway data.

Task B evaluation. Task B evaluates recovery of prior work that grounds a target contribution pathway. Given a target contribution and an evidence condition, the system retrieves candidate prior papers, optionally reranks them, and is scored against expert-annotated acceptable groundings. We report contribution coverage, paper-level recall, precision, F1, and candidate-pool contribution coverage. We include both deterministic ranking and LLM reranking at budgets $K \in \{5, 10\}$.

Contribution-level grounding diagnostic. To isolate grounding from decomposition, we additionally evaluate contribution-level grounding on the test set. In the oracle condition, the grounding agent receives gold enabling contributions. In the predicted condition, it receives model-predicted contributions from Task A. This diagnostic reports mapped accuracy, grounding recall, precision, recall conditioned on retrieval, and unmapped accuracy.

D. Task A Additional Results

D.1. Gemini Flash Judge Robustness

Table 3 reports Task A test results using Gemini Flash as the semantic matching judge. Scores are substantially higher than under Gemini 3.1 Pro because Flash is more permissive, as shown by the judge validation in Section D.2. The overall pattern is stable, with frontier closed-source models outperforming open-weight baselines and all models remaining far from complete pathway recovery.

D.2. Judge Validation

To select the primary semantic matching judge, we audited 60 stratified predicted–gold contribution pairs from the development set. The sample includes clear matches, clear non-matches, borderline partial matches, and cases where Gemini Flash and Gemini 3.1 Pro disagreed. Two human annotators independently assigned three-way labels: MATCH, PARTIAL,

Table 3. Task A enabling-contribution generation on the held-out test set in the main claim-only setting, using Gemini Flash as the semantic matching judge. Flash yields consistently higher absolute scores than Gemini 3.1 Pro, but the main qualitative conclusions remain unchanged.

Model	Recall	Precision	F1	Pred./target
Gemini 3.1 Pro	0.432	0.282	0.331	5.22
GPT-5.4	0.476	0.265	0.330	6.17
Gemini Flash	0.388	0.235	0.284	5.65
GPT-4.1	0.351	0.215	0.260	5.79
GPT-5 Mini	0.409	0.163	0.226	8.82
Gemma-4-E4B-it	0.250	0.198	0.214	4.42
GPT-4o	0.249	0.140	0.175	6.26
Qwen3-4B-Instruct	0.186	0.144	0.156	4.30
Gemma-2-2B-it	0.141	0.100	0.113	4.81
Llama-3-8B-Instruct	0.129	0.102	0.111	4.24
Llama-3.1-8B-Instruct	0.160	0.085	0.108	6.36
Qwen2.5-7B-Instruct	0.110	0.100	0.102	3.98
Llama-3.2-3B-Instruct	0.123	0.086	0.087	5.45

and NO MATCH. For validation, we collapse these labels to the official binary setting, where only MATCH counts as positive.

Table 4 shows that Gemini Flash behaves as a high-recall, lower-precision judge, while Gemini 3.1 Pro is substantially stricter and higher-precision. Because the official metric is intentionally strict and false positives inflate pathway-recovery scores, we use Gemini 3.1 Pro as the primary judge and report Gemini Flash as a higher-recall robustness check.

Table 4. Binary judge validation on 60 stratified predicted–gold contribution pairs. Only MATCH is treated as positive; PARTIAL and NO MATCH are treated as negative, matching the official Task A metric. Gemini Flash is more permissive, while Gemini 3.1 Pro is stricter and higher-precision.

Comparison	N	Accuracy	Precision	Recall	F1
Gemini Flash vs humans avg.	60	0.800	0.652	0.977	0.782
Gemini Pro vs humans avg.	60	0.833	0.900	0.614	0.730
Human vs human	60	0.900	0.864	0.864	0.864

D.3. Input and Prompting Variants

Table 5 reports Task A prompting and evidence variants on the held-out test set under Gemini 3.1 Pro judging. Adding citation context or Related Work context improves over the claim-only baseline, though the relative gains are model-dependent. Few-shot prompting generally improves precision and often improves F1, but does not consistently outperform richer context variants. Overall, these results suggest that models benefit from additional evidence and examples, but still struggle to infer contribution-level dependencies even when given more context than the main forecasting setting provides.

Table 5. Task A input and prompting variants on the held-out test set, evaluated with Gemini 3.1 Pro as the semantic matching judge. Additional citation and Related Work context improve over the claim-only setting; few-shot prompting often improves precision but does not consistently outperform richer context variants.

Model	Setting	Recall	Precision	F1
Gemini 3.1 Pro	Main (**S1**)	0.246	0.162	0.189
Gemini 3.1 Pro	Few-shot	0.232	0.226	0.221
Gemini 3.1 Pro	+Citations (**S2**)	0.276	0.192	0.217
Gemini 3.1 Pro	+Related Work (**S3**)	0.223	0.188	0.199
GPT-5.4	Main (**S1**)	0.217	0.123	0.152
GPT-5.4	Few-shot	0.253	0.174	0.200
GPT-5.4	+Citations (**S2**)	0.320	0.154	0.200
GPT-5.4	+Related Work (**S3**)	0.312	0.171	0.212
Gemma-4-E4B-it	Main (**S1**)	0.069	0.058	0.061
Gemma-4-E4B-it	Few-shot	0.079	0.125	0.094
Gemma-4-E4B-it	+Citations (**S2**)	0.114	0.082	0.092
Gemma-4-E4B-it	+Related Work (**S3**)	0.134	0.120	0.122
Gemma-4-E4B-it + LoRA	Fine-tuned	0.107	0.107	0.101

D.4. Year-Wise Results

Table 6 breaks down the main Task A setting by publication year. There is no consistent older-is-easier pattern. For the strongest models, 2025 papers are often as easy as or easier than 2023 papers. This weakens a simple memorization-based explanation of performance.

Table 6. Task A main-setting test F1 by publication year under Gemini 3.1 Pro judging. Performance does not systematically improve on older papers.

Model	2023 F1	2024 F1	2025 F1
Gemini 3.1 Pro	0.187	0.144	0.217
Gemini Flash	0.202	0.134	0.167
GPT-5.4	0.149	0.141	0.164
GPT-4.1	0.104	0.078	0.130
GPT-5 Mini	0.076	0.084	0.100
Gemma-4-E4B-it	0.063	0.055	0.066
Qwen3-4B	0.047	0.058	0.069
GPT-4o	0.067	0.057	0.045
Llama-3-8B	0.043	0.032	0.045
Llama-3.1-8B	0.045	0.029	0.020

D.5. Decomposition by Role and Target Contribution Type

Tables 7 and 8 provide a more fine-grained view of why Task A is difficult. The strongest pattern is that models recover concrete, nameable dependencies much more reliably than abstract methodological ones. For example, model initializations and data sources often correspond to salient artifacts that are explicitly named in papers, whereas CORE_METHOD contributions require reconstructing the mechanism that makes the target contribution work. This makes them harder to infer from the target claim alone.

The target-type breakdown shows a complementary pattern. Dataset, benchmark, resource, and tool targets tend to be easier because their pathways often involve visible upstream artifacts: source data, annotation protocols, pretrained models,

evaluation setups, or implementation resources. Method and finding targets are harder because their enabling contributions are less likely to be recoverable as named objects and more often involve design choices, conceptual commitments, or methodological mechanisms. Together, these results suggest that current models are not simply failing to retrieve relevant scientific objects; they struggle most when pathway recovery requires explaining how a target contribution is operationally realized.

Model	MI	DS	CF	IT	EP	TD	CM
Gemini 3.1 Pro	0.464	0.337	0.264	0.237	0.224	0.143	0.119
Gemini Flash	0.446	0.287	0.285	0.276	0.176	0.122	0.111
GPT-5.4	0.393	0.257	0.333	0.158	0.152	0.204	0.082
GPT-4.1	0.357	0.238	0.188	0.092	0.136	0.102	0.049
Gemma-4-E4B-it	0.089	0.099	0.090	0.026	0.064	0.102	0.045

Table 7. Recall by enabling-contribution role on the Task A test set under Gemini 3.1 Pro judging. Columns abbreviate `MODEL_INITIALIZATION` (MI), `DATA_SOURCE` (DS), `CONCEPTUAL_FRAMEWORK` (CF), `IMPLEMENTATION_TOOLING` (IT), `EVALUATION_PROTOCOL` (EP), `TRAINING_DATA` (TD), and `CORE_METHOD` (CM).

Model	Dataset	Benchmark	Tool	Resource	Method	Finding
Gemini 3.1 Pro	0.240	0.209	0.188	0.187	0.150	0.107
Gemini Flash	0.205	0.181	0.150	0.129	0.143	0.230
GPT-5.4	0.191	0.160	0.187	0.171	0.107	0.152
GPT-4.1	0.135	0.143	0.082	0.092	0.089	0.095
Gemma-4-E4B-it	0.109	0.057	0.036	0.090	0.036	0.026

Table 8. F1 by target contribution type on the Task A test set under Gemini 3.1 Pro judging. Method and finding targets are harder than artifact-like targets such as datasets and benchmarks.

D.6. Rationale-Quality Diagnostic

Task A evaluates whether models name the right enabling contributions, but a correct contribution name does not necessarily mean the model understands why that contribution is needed. We therefore run a rationale-quality diagnostic on predicted contributions that already match a gold contribution. For each matched pair, we ask whether the predicted rationale expresses the same necessity relation as the gold rationale. This diagnostic is not part of the main metric; it tests whether models recover the role of a contribution in the pathway, not only its surface identity.

Table 9 shows that stronger generators often capture the necessity relation once they recover the right contribution. Gemini 3.1 Pro rationales match the gold rationale for 75.1% of matched pairs, and GPT-5.4 reaches 68.8%. In contrast, Gemma-4-E4B-it reaches 44.2%, with nearly as many partial rationales as fully correct ones. This suggests that frontier models' Task A successes are often substantively meaningful: when they identify the correct enabling contribution, they frequently also explain why it is necessary.

Table 9. Rationale-quality diagnostic on the Task A test set. Only predicted contributions that already semantically match a gold contribution are scored. "Same" indicates that the predicted rationale expresses the same necessity relation as the gold rationale; "Partial" indicates that the rationale is related but misses an important constraint, role, or causal link.

Generator	Matched pairs	Same	Partial	Different	Same rate
Gemini 3.1 Pro	173	130	39	4	0.751
GPT-5.4	154	106	43	5	0.688
Gemma-4-E4B-it	52	23	24	5	0.442

E. Task B Additional Results

This appendix reports additional Task B results for deterministic ranking, $K = 10$ evaluation, and enabling-contribution-level grounding diagnostics. These results support three conclusions from the main paper. First, gold enabling contributions consistently improve prior-work recovery across retrieval agents, rankers, and values of K. Second, raw model-predicted

contributions remain weak search evidence, indicating that Task A errors propagate into retrieval. Third, candidate coverage is often much higher than top-K coverage, showing that both query generation and final ranking contribute to grounding failures.

Tables 10 and 11 report deterministic-ranking results for $K = 5$ and $K = 10$ on the held-out test set. The deterministic ranker uses retrieval frequency and best Semantic Scholar rank, without LLM reranking. Gold enabling contributions improve coverage substantially over claim-only retrieval for both agents. For example, with the Gemini agent at $K = 5$, deterministic Coverage increases from 0.054 for claim-only retrieval to 0.237 with gold contributions; with the GPT-5.4 agent, it increases from 0.029 to 0.171. Increasing K from 5 to 10 generally increases Coverage and Recall but lowers Precision, as expected when more candidate papers are returned.

Tables 12 and 13 report the corresponding $K = 10$ LLM-reranked results. The same qualitative pattern holds: gold contributions are consistently strongest, matched predicted contributions sometimes improve over raw predicted contributions, and raw predicted contributions generally do not improve over claim-only retrieval. LLM reranking improves over deterministic ranking most clearly in the gold-contribution setting, suggesting that reranking is useful when the candidate pool already contains relevant grounding papers. However, reranking cannot recover groundings that were never retrieved, as reflected by the candidate coverage columns.

Table 10. Task B deterministic-ranking results on the held-out test set with Gemini 3.1 Pro as the retrieval agent. Deterministic ranking orders candidates using retrieval frequency and best Semantic Scholar rank.

Input evidence (Gemini agent)	Coverage	Recall	Precision	F1	Cand. cov.
Claim only ($K = 5$)	0.054	0.040	0.024	0.027	0.120
Claim only ($K = 10$)	0.065	0.045	0.015	0.021	0.120
Gold contributions ($K = 5$)	0.237	0.186	0.095	0.114	0.403
Gold contributions ($K = 10$)	0.289	0.224	0.060	0.087	0.403
Predicted contributions ($K = 5$)	0.034	0.019	0.016	0.016	0.122
Predicted contributions ($K = 10$)	0.048	0.027	0.011	0.015	0.122
Matched predicted ($K = 5$)	0.056	0.043	0.026	0.029	0.153
Matched predicted ($K = 10$)	0.068	0.053	0.016	0.023	0.153

Table 11. Task B deterministic-ranking results on the held-out test set with GPT-5.4 as the retrieval agent. Deterministic ranking orders candidates using retrieval frequency and best Semantic Scholar rank.

Input evidence (GPT agent)	Coverage	Recall	Precision	F1	Cand. cov.
Claim only ($K = 5$)	0.029	0.019	0.012	0.013	0.105
Claim only ($K = 10$)	0.043	0.029	0.009	0.012	0.105
Gold contributions ($K = 5$)	0.171	0.136	0.072	0.085	0.303
Gold contributions ($K = 10$)	0.218	0.162	0.049	0.067	0.303
Predicted contributions ($K = 5$)	0.009	0.006	0.008	0.007	0.067
Predicted contributions ($K = 10$)	0.028	0.018	0.009	0.011	0.067
Matched predicted ($K = 5$)	0.027	0.019	0.009	0.010	0.104
Matched predicted ($K = 10$)	0.045	0.029	0.008	0.011	0.104

Table 12. Task B LLM-reranked results at $K = 10$ on the held-out test set with Gemini 3.1 Pro as the retrieval and reranking agent.

Input evidence (Gemini agent, $K = 10$)	Coverage	Recall	Precision	F1	Cand. cov.
Claim only	0.089	0.058	0.021	0.028	0.120
Gold contributions	0.362	0.277	0.077	0.111	0.403
Predicted contributions	0.068	0.045	0.016	0.023	0.122
Matched predicted	0.111	0.077	0.026	0.036	0.153

Table 13. Task B LLM-reranked results at $K = 10$ on the held-out test set with GPT-5.4 as the retrieval and reranking agent.

Input evidence (GPT agent, $K = 10$)	Coverage	Recall	Precision	F1	Cand. cov.
Claim only	0.080	0.054	0.018	0.025	0.105
Gold contributions	0.276	0.206	0.063	0.088	0.303
Predicted contributions	0.059	0.042	0.016	0.020	0.067
Matched predicted	0.085	0.053	0.016	0.022	0.104

Contribution-level grounding diagnostic. Table 14 reports the enabling-contribution-level grounding diagnostic on the test set. Unlike claim-level retrieval, this setting gives the grounding agent one enabling contribution at a time and asks it either to select an acceptable prior-work grounding or mark the contribution as unmapped. This isolates grounding decisions from the full claim-level query-generation problem.

The oracle gold condition shows that grounding remains difficult even when the correct enabling contribution is provided. With gold contributions and the Gemini grounding agent, mapped accuracy is 0.268 and agent recall is 0.235. However, recall conditioned on retrieval is much higher at 0.689, indicating that the agent is often able to select the right paper once it appears in the candidate pool. This suggests that candidate retrieval is a major bottleneck. At the same time, unmapped accuracy is high at 0.824, showing that the model is relatively good at not forcing a grounding when no clean prior study exists. GPT-5.4 performs substantially worse than Gemini in the oracle condition, with mapped accuracy of only 0.057 and agent recall of 0.038.

Grounding quality drops further when the input enabling contributions come from Task A predictions. Gemini-predicted contributions yield much lower precision and recall than gold contributions, and Gemma-4 predictions contain very few groundable contributions. This confirms that end-to-end Task B failure reflects two compounding difficulties: predicted decompositions often fail to provide useful grounding targets, and even correct targets require effective retrieval and selection over prior work.

Table 14. Enabling-contribution-level grounding diagnostic on the test set. The grounder receives one enabling contribution at a time and must either select an acceptable prior-work grounding or mark it as unmapped. Recall |retrieved conditions grounding recall on at least one acceptable grounding appearing in the retrieved candidate pool.

Input enabling contributions	Grounder	Mapped acc.	Recall	Recall |retrieved	Precision	Unmapped acc.
Gold contributions	Gemini 3.1 Pro	0.268	0.235	0.689	0.476	0.824
Gold contributions	GPT-5.4	0.057	0.038	0.420	0.134	0.843
Predicted contributions (Gemini)	Gemini 3.1 Pro	0.222	0.167	0.577	0.095	0.731
Predicted contributions (Gemma-4)	Gemini 3.1 Pro	0.273	0.159	0.292	0.046	0.839