ON SIZE GENERALIZATION IN GRAPH NEURAL NETWORKS

ABSTRACT

Graph neural networks (GNNs) can process graphs of different sizes but their capacity to generalize across sizes is still not well understood. Size generalization is key to numerous GNN applications, from solving combinatorial optimization problems to learning in molecular biology. In such problems, obtaining labels and training on large graphs can be prohibitively expensive, but training on smaller graphs is possible.

This paper puts forward the size-generalization question and characterizes important aspects of that problem theoretically and empirically. We show that even for very simple tasks, GNNs do not naturally generalize to graphs of larger size. Instead, their generalization performance is closely related to the distribution of patterns of connectivity and features and how that distribution changes from small to large graphs. Specifically, we show that in many cases, there are GNNs that can perfectly solve a task on small graphs but generalize poorly to large graphs and that these GNNs are encountered in practice. We then formalize size generalization as a domain-adaption problem and describe two learning setups where size generalization can be improved. First, as a self-supervised learning problem (SSL) over the target domain of large graphs. Second as a semi-supervised learning problem when few samples are available in the target domain. We demonstrate the efficacy of these solutions on a diverse set of benchmark graph datasets.

1 INTRODUCTION

Graphs are a flexible representation, widely used for representing diverse data and phenomena. Graph neural networks (GNNs) – Deep models that operate over graphs – have emerged as a prominent learning model (Bruna et al., 2013; Kipf and Welling, 2016; Veličković et al., 2017). They are used in natural sciences (Gilmer et al., 2017), social network analysis (Fan et al., 2019), for solving difficult mathematical problems (Luz et al., 2020) and for approximating solutions to combinatorial optimization problems (Li et al., 2018).

In many domains, graphs data vary significantly in size. This is the case for molecular biology, where molecules – represented as graphs over atoms as node – span from small compounds to proteins with many thousands of nodes. It is even more severe in social networks, which can reach billions of nodes. The success of GNNs for such data stems from the fact that the same GNN model can process input graphs regardless of their size. Indeed, it has been proposed that GNNs can generalize to graphs whose size is different from what they were trained on , but it is largely unknown in what problems such generalization occurs. Empirically, several papers report good generalization performance on specific tasks (Li et al., 2018; Luz et al., 2020). Other papers, like Veličković et al. (2019), show that size generalization can fail on several simple graph algorithms, and can be improved by using task-specific training procedures and specific architectures.

Given their flexibility to operate on variable-sized graphs, A fundamental question arises about generalization in GNNs: **"When do GNNs trained on small graphs generalize to large graphs?"**

Aside from being an intriguing theoretical question, this problem has important practical implications. In many domains, it is hard to label large graphs. For instance, in combinatorial optimization problems, labeling a large graph boils down to solving large and hard optimization problems. In other domains, it is often very hard for human raters to correctly label complex networks. One

approach to this problem could have been to resize graphs into a homogeneous size. This is the strategy taken in computer vision, where it is well understood how to resize an image while keeping its content. Unfortunately, there are no effective resizing procedures for graphs. It would therefore be extremely valuable to develop techniques that can generalize from training on small graphs.

As we discuss below, a theoretical analysis of size generalization is very challenging because it depends on several different factors, including the task, the architecture, and the data. For tasks, we argue that it is important to distinguish two types of tasks, *local* and *global*. Local tasks can be solved by GNNs whose depth does not depend on the size of the input graph. For example, the task of finding a constant-size pattern. Global tasks require that the depth of the GNN grows with the size of the input graph. For example, calculating the diameter of a graph.

In this paper, we focus on local tasks and study the ability of the most expressive message passing neural networks (Xu et al., 2018; Morris et al., 2019) to generalize to unseen sizes. Our key observation is that generalization to graphs of different sizes is strongly related to the distribution of patterns around nodes in the graphs of interest. These patterns, dubbed *d-patterns* (where d is the radius of the local neighborhood), describe the local feature-connectivity structure around each node, as seen by message-passing neural networks and are formally defined in Section 3.

We study the role of *d-patterns* both empirically and theoretically. First, we show that when there is a discrepancy between the d-pattern distributions, GNNs have multiple global minima for graphs of a specific size range, out of which only a subset of models can generalize well to larger graphs. We then show in experiments that GNNs tend to converge to non-generalizing global minima and that the size generalization problem is accentuated in deeper GNNs.

Following these observations, in the final part of this paper, we discuss two learning setups that help improve size-generalization by formulating the learning problem as a domain adaptation problem: (1) Training the GNNs on self-supervised tasks aimed at learning the d-pattern distribution of both the target (large graphs) and source (small graphs) domains. We also propose a novel SSL task that directly addresses over-fitting of d-patterns. (2) A semi-supervised learning setup with a limited number of labeled examples from the target domain. The idea behind both setups is to promote convergence of GNNs to local/global minima with good size generalization properties. We show that both setups are useful in a series of experiments on synthetic and real data.

To summarize, this paper makes the following contributions. (1) We identify a size generalization problem when learning local tasks with GNNs and analyze it empirically and theoretically. (2) We link the size-generalization problem with the distribution of d-patterns and suggest to approach it as a domain adaptation problem (3) We empirically show how several learning setups help improve size generalization.

2 RELATED WORK

Size generalization in set and graph learning. Several papers observed successful generalization across graph sizes, but the underlying reasons were not investigated (Li et al., 2018; Maron et al., 2018; Luz et al., 2020). More recently, (Veličković et al., 2019) showed that when training GNNs to perform simple graph algorithms step by step they generalize better to graphs of different sizes. Unfortunately, such training procedures cannot be easily applied to general tasks. Knyazev et al. (2019) studied the relationship between generalization and attention mechanisms. Tang et al. (2020) observed two issues that can harm generalization: (1) There are tasks for which a constant number of layers is not sufficient. (2) Some graph learning tasks are homogeneous functions. They then suggest a new GNN architecture to deal with these issues. Our work is complementary to these works as it explores another fundamental size generalization problem, focusing on constant depth GNNs. For more details on the distinction between constant depth and variable depth tasks see Appendix A. Several works also studied size generalization and expressivity when learning set-structured inputs (Zweig and Bruna, 2020; Bueno and Hylton, 2020).

Expressivity and generalization in graph neural networks. (Xu et al., 2018; Morris et al., 2019) established a fundamental connection between message-passing neural networks and the Weisfeiler-Leman (WL) graph-isomorphism test. We use similar arguments to show that GNNs have enough expressive power to solve a task on a set of small graphs and to fail on it on a set of large graphs. Several works studied generalization bounds for certain classes of GNNs (Garg et al., 2020; Puny

et al., 2020; Verma and Zhang, 2019), but did not discuss size-generalization. Sinha et al. (2020) proposed a benchmark for assessing the logical generalization abilities of GNNs.

3   THE SIZE GENERALIZATION PROBLEM

We now present the main problem discussed in the paper, that is, what determines if a GNN generalizes well to graphs of sizes not seen during training. We start with a simple motivating example showing the problem on single layer GNNs. We then show that the question of size generalization actually depends on *d-patterns*, the patterns of connectivity and features of the graphs, and not only on their actual size.

Setup. We are given two distributions over graphs P_1, P_2 that contain small and large graphs accordingly, and a task that can be solved with 0 error for all graph sizes using a constant depth GNN. We train a GNN on a training set $\mathcal{S}$ sampled i.i.d from P_1 and study its performance on P_2.

GNN model. We focus on the **first order GNN** (1-GNN) architecture from Morris et al. (2019) defined in the following way:

$$\mathbf{h}_v^{(t)} = \sigma \left(W_2^{(t)} \mathbf{h}_v^{(t-1)} + \sum_{u \in \mathcal{N}(v)} W_1^{(t)} \mathbf{h}_u^{(t-1)} + \mathbf{b}^{(t)} \right).$$

Here, $\mathbf{h}_v^{(t)}$ is the feature vector of node v after t layers, $W_1^{(t)}, W_2^{(t)} \in \mathbb{R}^{d_{t-1} \times d_t}$, $\mathbf{b}^{(t)} \in \mathbb{R}^{d_t}$ denotes the parameters of the t-th layer of the GNN, and σ is some non-linear activation (e.g ReLU). It was shown in Morris et al. (2019) that GNNs composed from these layers have maximal expressive power with respect to all message-passing neural networks. In the experimental section we also experiment with Graph Isomorphism Network (GIN) (Xu et al., 2018). For further details on GNNs see Appendix A. In this work we use the most expressive GNN variants that use the "sum" aggregation function. Using a "max" or "mean" reduces the expressive power of the network, making it not powerful enough to solve simple counting problems (e.g. counting edges or computing node degrees). On the other hand, these networks give rise to slightly different definitions of patterns and can generalize better in some cases as shown in (Veličković et al., 2019), yet still suffer from size overfit. Exploring these networks is beyond the scope of this work.

3.1   SIZE GENERALIZATION IN SINGLE-LAYER GNNS

We start our discussion on size generalization with a theoretical analysis of a simple setup. We consider a single-layer GNN and an easy task and show that: (1) The training objective has many different solutions, but only one of them generalizes to larger graphs; (2) Simple regularization techniques cannot mitigate the problem. This subsection serves as a warm-up for the next subsections that contain our main results.

Assume we train on a distribution of graphs with a fixed number of nodes n and a fixed number of edges m. Our goal is to predict the number of edges in the graph using a 1-GNN with a single linear layer and additive readout function, for simplicity also consider the squared loss. The objective boils down to the following function: $L(w, b; G) = \left(\sum_{u \in V(G)} \left(w_1 \cdot x_u + \sum_{v \in \mathcal{N}(u)} w_2 \cdot x_v + b \right) - y \right)^2$. Here, G is an input graph, $V(G)$ are the nodes of G, $\mathcal{N}(v)$ are all the neighbors of node v, w_1, w_2 and b are the trainable parameters, y is the target (m in this case) and x_v is the node feature for node v. Further, assume that we have no additional information on the nodes, so we can just embed each node as a one-dimensional feature vector with a fixed value of 1. In this simple case, the trainable parameters are also one-dimensional. We note that the training objective can also be written in the following form $L(w, b; G) = (nw_1 + 2mw_2 + nb - m)^2$, and that one can easily find its solutions space, which is an affine subspace defined by $w_2 = \frac{m - n(w_1 + b)}{2m}$. In particular, the solutions with $b + w_1 = 0$, $w_2 = 1/2$ are the only ones which do not depend on the specific training set graph size n, and generalize to graphs of any size. It can be readily seen that when training the model on graphs of fixed size (fixed m, n), gradient descent will have no reason to favor one solution over another and we will not be able to generalize. We also note that the generalizing solution is not the

least norm solution (with respect to both L_1 and L_2 norms) so simple regularization will not help here. On the other hand, it is easy to show that training on graphs with different number of edges will favor the generalizing solution. As we will see next, the problem gets worse when considering GNNs with multiple non-linear layers, and this simple solution will not help in this case: we can train deeper GNNs on a wide variety of graph sizes and the solution will not generalize to other sizes.

3.2 d-PATTERNS

We wish to understand theoretically when a GNN trained on on graphs with a small number of nodes can generalize to graphs with a large number of nodes. To answer that question, we first analyze what information is received by each node in the graph from its neighboring nodes after a graph is processed by a GNN with T layers. It is easy to see that every node can receive information about its neighbors which are at most T hops away. We also know that nodes do not have full information about their order T environment. For example, GNNs cannot determine if a triangle is present in a neighborhood of a given node Chen et al. (2020). In order to characterize the exact information that can be found in each node after a T layer GNN, we use the definition of the WL test, specifically its iteration structure, which has the same representational power as GNNs (see Xu et al. (2018); Morris et al. (2019)), For more details on the WL test see Appendix A.

Definition 3.1 (d-patterns). *Let C be a finite set of node features and $N \in \mathbb{N}$. For $d \geq 0$ we define the set of d-**patterns** P_d on graphs with maximal degree N and node features from C. The definition is recursive in the following way: For $d = 0$, $P_0 = C$. We define P_d to be the set of all tuples (a, b) where $a \in P_{d-1}$ and b is in multisets of size at most N consisting of elements from P_{d-1}.*

Let $G = (V, E)$ be a graph with maximal degree N and a node feature $c_v \in C$ for every node $v \in V$. We define the d-pattern of a node $v \in V$ for $d \geq 0$ recursively: For $d = 0$, its 0-pattern is c_v. For $d > 0$ we say that v has a d-pattern $p = (p_v, \{(p_{i_1}, m_{p_{i_1}}), \ldots, (p_{i_\ell}, m_{p_{i_\ell}})\})$ iff node v has $(d-1)$-pattern p_v and for every $j \in \{1, \ldots, \ell\}$ the number of neighbors of v with $(d-1)$-pattern p_{i_j} is exactly $m_{p_{i_j}}$.

The d-pattern of a node is an encoding of the $(d-1)$-patterns of itself and of its neighbors. For example, assume a graph has a maximal degree of N and all the nodes start with the same node feature. The 1-pattern of each node is its degree. The 2-pattern of each node is for each possible degree $i \in \{1, \ldots, N\}$ the number of neighbors with degree i. In the same manner, the 3-pattern of a node is for each possible 2-pattern, the number of its neighbors with this exact 2-pattern. The definition of d-patterns can naturally be extended to the case of unbounded degrees. In the next subsection, we prove that GNNs can compute d-patterns, and show that this capacity is tightly related to size generalization.

3.3 GNNs MAY OVERFIT d-PATTERNS

We can now connect the size generalization problem to the concept of d-patterns. We start with an example: consider a node prediction task in which an output is specified for each node in an input graph, and is solvable by a d-layer GNN. To perfectly solve this task, the model should produce the correct output for the d-pattern of all the nodes in the training set. Testing this GNN on a different set of graphs will succeed if the test set has graphs with similar d-patterns to those in the training set. Note that this requirement is not related to the *size* of the graphs but to the distribution of the d-patterns of the nodes in the test set.

In the following theorem we show rigorously, that given a set of d-patterns and output for each such pattern, there is an assignment of weights to a GNN with $O(d)$ layers that perfectly fits the output for each pattern. We will then use this theorem in order to show that, under assumptions on the distribution of d-patterns of the large graphs, GNNs can perfectly solve a task on a set of small graphs, and completely fail on a set on large graphs. In other words, we show that there are multiple global minima for the training objective that do not generalize to larger graphs.

Theorem 3.2. *Let C be a finite set of node features, P be a finite set of d-patterns on graphs with maximal degree $N \in \mathbb{N}$, and for each pattern $p \in P$ let $y_p \in [-1, 1]$ be some target label. Then there exists a 1-GNN F with $d + 2$ layers, width bounded by $\max\left\{(N+1)^d \cdot |C|, 2\sqrt{|P|}\right\}$*

and ReLU activation such that for every graph G with nodes $v_1, \ldots, v_n$, corresponding d-patterns $p_1, \ldots, p_n \subseteq P$ and node features from C, the output of F on node v_i is exactly y_{p_i}.

The full proof is in Appendix B. Note that the width of the required GNN from the theorem is not very large if d is small, where d represents the depth of the 1-GNN. In practice, shallow GNNs are very commonly used and are proven empirically successful, while training deep GNNs was shown to be hard due to many problems like over-smoothing (Zhao and Akoglu, 2019).

Using the above theorem we can claim that there are assignments of weights to GNN that cannot "size-generalize", that is, given a specific task, the GNN succeeds on the task for small graphs (up to some bound) and fails on larger graphs, as long as there is a notable discrepancy between their d-patterns distributions:

Corollary 3.3. *Let P_1 and P_2 be distributions of small and large graphs respectively with finite support, and Let P_1^{d-pat} be the distribution of d-patterns over small graphs and similarly P_2^{d-pat} for large graphs. For any node prediction task which is solvable by a 1-GNN with depth d and $\epsilon > 0$ there exists a 1-GNN with depth at most $d + 2$ that has 0-1 loss smaller then ϵ on P_1 and 0-1 loss Δ on P_2, where*

$$\Delta(\epsilon) = \max_{A : P_1^{d-pat}(A) < \epsilon} P_2^{d-pat}(A). \tag{1}$$

Here, A is a set of d-patterns and $P(A)$ is the total probability mass for that set under P.

Intuitively, large Δ means that there exists a set of d-patterns that have a low probability for small graphs and high probability for large graphs. Corollary 3.3 implies that the major factor in the success of GNN to generalize to larger graphs is not the graph size, but the distribution of the d-patterns. Different distributions of d-patterns lead to large Δ and thus to bad generalization to larger graphs. On the other hand, it can be easily seen that similar distributions of d-patterns imply that every GNN model that succeeds on small graphs will also succeed on large graphs.

Examples. The above corollary shows that even for simple tasks, GNN may fail, here are two simple examples. (i) Consider the task of calculating the node degree. From Corollary 3.3 there is a GNN that successfully output the degree of nodes with max degree up to N and fails on nodes with larger degrees. Note that this problem can easily be solved for any node degree with a 1-layer GNN. (ii) Consider some node regression task, when the training set consists of graphs sampled i.i.d from an Erdos-Renyi graph $G(n, p)$ [1], and the test set contains graphs sampled i.i.d from $G(2n, p)$. In this case, a GNN trained on the training set will be trained on graphs with an average degree np, while the test set contains graphs with an average degree $2np$. This means that the d-patterns in the train and test set are very different, and by Corollary 3.3 the GNN may overfit.

Graph prediction tasks. Our theoretical results discuss node prediction tasks. We note that they are also relevant for graph prediction tasks where there is a single output to each input graph. The reason for that is that in order to solve graph prediction tasks, a GNN first calculates node features and then pools them into a single global graph feature. Our analysis shows that the first part of the GNN, which is responsible for calculating the node features, might not generalize to large graphs. As a result, the GNN will generate an uninformative global graph feature and the GNN will fail on the original graph prediction task. In the experimental sections, we show that the size generalization problem is indeed relevant for both node and graph prediction tasks.

Relation to Morris et al. (2019); Xu et al. (2018). We note that Theorem 3.2 and Corollary 3.3 are somewhat related to the expressivity results in (Xu et al., 2018; Morris et al., 2019) that show that GNNs can be as powerful as the WL test. Here, we show that the expressive power of GNNs can cause negative effects when there is a discrepancy between the training and test sets.

3.4 EMPIRICAL VALIDATION

In the previous subsection we have shown that for any node task, and any two datasets of graphs with different sizes that significantly differ in their d-patterns distributions, there is a 1-GNN that successfully solves the task on one dataset but fails on the second. In this subsection, we show empirically that reaching these "overfitting" GNNs is actually very common. We also show that GNNs

---

[1]Graphs with n nodes such that each edge exists with probability p.

Figure 1: The effect of graph size and d-pattern distribution on generalization in G(n,p) graphs. **(left) The effect of distribution of d-patterns**. Train on n drawn uniformly from $[40, 50]$ and $p = 0.3$ test on $n = 100$ and varying p ; **(right) The effect of train-graph size.** Train on n drawn uniformly from $[40, x]$ where x varies and $p = 0.3$; test on $n = 150$, $p = 0.3$.

can generalize to larger graphs if the distribution of d-patterns remains similar to the distribution of patterns in the small graphs.

To show this, we use a controlled regression task in a student-teacher setting. In this setting, we sample a "teacher" GNN with random weights, freeze the network, and label each graph in the dataset using the output of the "teacher" network. Our goal is to train a "student" network, which has the same architecture as the "teacher" network, to fit the labels of the teacher network. The advantages of this setting are two-fold: (1) *A solution is guaranteed to exist*: The problem is solvable, as we know that there is an assignment to the weights of the student network which perfectly solve the task for graphs of any size. (2) *Generality*: This setup includes all tasks that are solvable by constant depth GNNs. We discuss more settings below.

Architecture and training protocol. We use 1-GNN as defined in (Morris et al., 2019). The number of GNN layers in the network we use is either $1, 2$ or 3; the width of the teacher network is 32, and of the student network 64, providing more expressive power to the student network. We obtained similar results when testing with a width of 32, same as the teacher network. We use a summation readout function followed by a two-layer fully connected suffix. We use ADAM with learning rate 10^{-3}. We performed a hyper-parameters search on the learning rate and weight decay and use validation-based early stopping on the source domain (small graphs). The results are averaged over 10 random seeds. All runs used Pytorch Geometric (Fey and Lenssen, 2019) on NVIDIA DGX-1 machines.

Results. Fig. 1 compares the loss of GNNs as the distribution of d-patterns changes, for the task of teacher-student graph level regression. The model was trained on graphs generated using the $G(n, p)$ model. We show the normalized L_2 loss computed on test, where output is normalized by the average test-set (target) output. The left panel shows the test loss when training on $n \in [40, 50]$ and $p = 0.3$ and testing on $G(n, p)$ graphs with $n = 100$ and p varying from 0.05 to 0.5. In this experiment, the expected node degree is np, hence the distribution of d-patterns is most similar to the one observed in the training set when $p = 0.15$. Indeed, this is the value of p where the test loss is minimized. The right panel is discussed in the caption. These results are consistent with Corollary 3.3, since when the distributions of d-patterns are far the model is not able to generalize well, and it does generalize well when these distributions are similar.

We also tested on the tasks of finding the max clique in a graph, calculating the number of edges, and the node prediction tasks of calculating the node degree, and the student-teacher task at the node level. In addition, we tested on the popular GIN architecture (Xu et al., 2018), and show that the size generalization problem also occurs there. We also tested on the ReLU, Tanh, and sigmoid activations. See additional experiments in Appendix C.

4 TOWARDS IMPROVING SIZE-GENERALIZATION

The results from the previous section show that the problem of size generalization is not only related to the size of the graph in terms of the number of nodes or edges but to the distribution of d-patterns induced by the distributions from which the graphs are sampled. Based on this observation, we now formulate the size generalization problem as a domain adaptation (DA) problem. We then build on techniques from domain adaptation and suggest two approaches to improve size generalization. (1) Self-supervised learning on the target domain (large graphs) and (2) Semi-supervised learning with a few labeled target samples. We consider the DA setting where we are given two distributions over graphs: a source distribution $\mathcal{D}_S$ (say, for small graphs) and a target distribution $\mathcal{D}_T$ (say, for large graphs). We consider two settings. First, the unlabeled DA setting, where we have access to labeled samples from the source $\mathcal{D}_S$ but the target data from $\mathcal{D}_T$ is unlabeled. Our goal is to infer labels on a test dataset sampled from the target $\mathcal{D}_T$. Second, we consider a semi-supervised setup, where we also have access to a small number of labeled examples from the target $\mathcal{D}_T$.

Size generalization with Self-supervised learning. In Self-supervised learning (SSL) for DA, a model is trained on unlabeled data to learn a *pretext* task, which is different from the main task at hand. If the pretext task is chosen wisely, the model learns useful representations (Doersch et al., 2015; Gidaris et al., 2018) that can help with the main task. Here, we train the pretext task on both the source and target domains, as was done for images and point clouds (Sun et al., 2019; Achituve et al., 2020). The idea is that the pretext task aligns the representations of the source and target domains leading to better predictions of the main task for target graphs. Given a pretext task we consider two different training procedures:

(1) **Multi-task learning (MTL)**: parallel training of the main task on a source domain and a pretext task on both the source of target domain (You et al., 2020). In this case, the architecture consists of a main GNN that acts as a feature extractor and two secondary networks (heads) that operate on the extracted features and try to predict the main task and the pretext task. (2) **Pretraining (PT)**: in this procedure (Hu et al., 2019), the GNN feature extractor is trained until convergence on the pretext task on both the source and target examples. After this phase, the GNN part is frozen, and only the head of the model is trained on labeled exampled from the source.

Figure 2: Left: a graph with node features represented by colors. Right: A tree that represents the d-patterns for the black node. The tree descriptor is the number of nodes from each class in each layer of the tree.

Pattern-tree pretext task. We propose a novel pretext task which is motivated by the definition of d-patterns. We do that by constructing a tree that fully represents the d-patterns of each node (see e.g., Xu et al. (2018)). We then calculate a descriptor of the tree, which is a vector containing counts of the number of nodes from each class in each layer of the tree. We treat this descriptor as the target label to be reconstructed by the SSL task. For more details see Figure 2. Intuitively, in order to be successful on a task on graphs, the GNN needs to correctly represent the pattern trees of the nodes of the graphs. This means, that to generalize to the target domain $\mathcal{D}_t$, the GNN needs to be forced to represent pattern trees from both the source and the target distributions. More details in Appendix D.

Semi-supervised setup. We also consider a case where a small number of labeled samples are available for the target domain. A natural approach is to train an SSL pretext task on samples from both the source and target domain, and train the main task on all the labeled samples available. We tested this setup with 1, 5, or 10 labeled examples from the target domain.

4.1 EXPERIMENTS

Architecture and training protocol. The setup is the same as in Subsection 3.4 with the following changes. We use a three-layer GNN in all experiments. Multi-task learning is used with equal weight to the main and SSL tasks. In the semi-supervised setup, we used an equal weight for the main task and the labeled examples from the target domain.

Baselines. We compare our new pretext task to the following baselines: (1) **Vanilla**: standard training on the source domain; (2) **HomoGNN** (Tang et al., 2020) a homogeneous GNN without the bias term trained on the source domain; (3) **Graph autoencoder (GAE)** pretext task (Kipf and Welling, 2016); (4) **Node masking (NM)** pretext task from Hu et al. (2019) where at each training iteration we mask 10% of the node features and the goal is to reconstruct them. In case the graph

DATASETS	DEEZER	IMDB - B	NCI1	NCI109	PROTEINS	TWITCH	DD	AVERAGE
SMALL GRAPHS	56.5 ± 0.8	63.2 ± 3.3	75.5 ± 1.6	78.4 ± 1.4	75.4 ± 3.1	69.7 ± 0.2	71.1 ± 4.4	70.0%
VANILLA	41.1 ± 6.8	55.9 ± 7.8	65.9 ± 4.3	68.9 ± 3.8	76.0 ± 8.5	60.5 ± 3.6	76.3 ± 3.2	63.5%
HOMO-GNN	40.5 ± 6.6	56.3 ± 7.0	66.0 ± 3.7	68.8 ± 3.2	77.1 ± 10	60.8 ± 2.3	$\mathbf{76.8 \pm 3}$	63.8%
NM MTL	$\mathbf{51.6 \pm 8.5}$	55.6 ± 6.8	49.9 ± 7.8	61.7 ± 5.7	78.8 ± 8.4	49.5 ± 2.8	67.4 ± 5.4	59.2%
NM PT	50.1 ± 7.5	54.9 ± 6.7	51.7 ± 6.6	55.8 ± 5.0	78.2 ± 8.2	48.4 ± 4.0	60.3 ± 15.9	57.1%
GAE MTL	49.4 ± 11.0	55.5 ± 6.0	51.2 ± 9.9	57.6 ± 9.4	79.5 ± 11.7	62.5 ± 5.1	67.8 ± 10.0	60.5%
GAE PT	47.1 ± 10.0	54.1 ± 6.8	58.9 ± 7.6	67.2 ± 5.6	70.5 ± 9.4	53.6 ± 4.7	69 ± 7.1	60.1%
NML MTL	46.4 ± 9.5	54.4 ± 7.0	52.3 ± 6.3	56.2 ± 6.5	78.7 ± 6.8	57.4 ± 4.1	64.7 ± 11.9	58.6%
NML PT	48.4 ± 10.7	53.8 ± 6.1	54.6 ± 6.2	56.1 ± 8.1	76.3 ± 8.0	54.9 ± 4.7	61.4 ± 15.1	57.9%
PATTERN MTL	45.6 ± 8.8	56.8 ± 9.2	60.5 ± 7.5	67.9 ± 7.2	75.8 ± 11.1	61.6 ± 3.5	$\mathbf{76.8 \pm 3}$	63.6%
PATTERN PT	44 ± 7.7	$\mathbf{61.9 \pm 3.2}$	$\mathbf{67.8 \pm 11.7}$	$\mathbf{74.8 \pm 5.7}$	$\mathbf{84.7 \pm 5.1}$	$\mathbf{64.5 \pm 3.3}$	74.9 ± 5.2	**67.5%**

Table 1: Test accuracy of compared methods in binary classification tasks. The Pattern task with pretraining achieves the highest accuracy in most tasks and has 4% higher average accuracy than the second-best method. High variance is due to the domain shift between the source and target domain.

does have node features then the task was to predict the degree of the masked nodes. (5) **Node metric learning (NML)**: we use metric learning to learn useful node representations. We use a corruption function that given a graph and corruption parameter $p \in [0, 1]$, replaces $p|E|$ of the edges with random edges, and thus can generate positive ($p = 0.1$) and negative ($p = 0.3$) examples for all nodes of the graph. we train with the triplet loss (Weinberger and Saul, 2009).

Datasets. We use datasets from Morris et al. (2020). We selected datasets that have a sufficient number of graphs (more than 1,000) and with a non-trivial split to small and large graphs as detailed in Appendix E.1. In total we used 7 datasets, 4 in molecular biology (NCI1, NCI109, D&D, Proteins), and 3 of social networks (Twitch ego nets, Deezer ego nets, IMDB-Binary). In all datasets, 50% smallest graphs were assigned to the training set, and the and 10% largest graphs assigned to the test set. We further split a random 10% of the small graphs as a validation set.

Results. Table 1 compares the effect of using the Pattern-tree pretext task to the baselines described above. The *small graphs* row presents vanilla results on a validation set with small graphs. The small graph accuracy on 5 out of 7 datasets is larger by 7.3%-15.5% than on large graphs, indicating that the size-generalization problem is indeed prevalent in real datasets. Pretraining with the d-patterns pretext task outperforms other baselines in 5 out 7 datasets, with an average 4% improved accuracy on all datasets. HOMO-GNN slightly improves over the vanilla while other pretext tasks do not improve average accuracy. Naturally, the accuracy here is much lower than SOTA on these datasets because the domain shift makes the problem much harder. Figure 3 compares the performance of vanilla training versus pretraining with the pattern-tree pretext task in the semi-

Figure 3: Mean accuracy over all datasets in Tab. 1 for d-pattern pre training and no SSL (Vanilla).

supervised setup. the accuracy monotonically increases with respect to the number of labeled examples in both cases. Moreover, pretraining with the pretext task yields better results in the case of 0,1,5 labeled examples and comparable results in the case we use 10 labeled examples. We additionally tested on the synthetic tasks discussed in Sec. 3, and show that the pattern-tree pretext task improves in the student-teacher setting, while it does not solve the edge count or degree prediction tasks. On the other hand, adding even a single labeled sample from the target distribution significantly improves performance on the synthetic tasks we tested on. For more details see Sec. E.

5 CONCLUSION AND DISCUSSION

This paper is a first step towards understanding the size generalization problem in graph neural networks. We showed that GNNs do not naturally generalize to larger graphs even on simple tasks, characterized how this failure depends on d-patterns, and suggested two approaches that can improve generalization. While these approaches are found useful for multiple tasks, there are tasks on which we could not improve generalization. Our characterization of d-patterns is likely to have implications to other problems where generalization is harmed by distribution shifts, and offer a way to mitigate those problems.

REFERENCES

[1] I. Achituve, H. Maron, and G. Chechik. Self-supervised learning for domain adaptation on point-clouds. *arXiv preprint arXiv:2003.12641*, 2020.

[2] J. Bruna, W. Zaremba, A. Szlam, and Y. LeCun. Spectral networks and locally connected networks on graphs. *arXiv preprint arXiv:1312.6203*, 2013.

[3] C. Bueno and A. G. Hylton. Limitations for learning from point clouds, 2020. URL `https://openreview.net/forum?id=r1x63grFvH`.

[4] Z. Chen, L. Chen, S. Villar, and J. Bruna. Can graph neural networks count substructures? *arXiv preprint arXiv:2002.04025*, 2020.

[5] C. Doersch, A. Gupta, and A. A. Efros. Unsupervised visual representation learning by context prediction. In *Proceedings of the IEEE international conference on computer vision*, pages 1422–1430, 2015.

[6] V. P. Dwivedi, C. K. Joshi, T. Laurent, Y. Bengio, and X. Bresson. Benchmarking graph neural networks. *arXiv preprint arXiv:2003.00982*, 2020.

[7] W. Fan, Y. Ma, Q. Li, Y. He, E. Zhao, J. Tang, and D. Yin. Graph neural networks for social recommendation. In *The World Wide Web Conference*, pages 417–426, 2019.

[8] M. Fey and J. E. Lenssen. Fast graph representation learning with pytorch geometric. *arXiv preprint arXiv:1903.02428*, 2019.

[9] V. K. Garg, S. Jegelka, and T. Jaakkola. Generalization and representational limits of graph neural networks. *arXiv preprint arXiv:2002.06157*, 2020.

[10] S. Gidaris, P. Singh, and N. Komodakis. Unsupervised representation learning by predicting image rotations. *arXiv preprint arXiv:1803.07728*, 2018.

[11] J. Gilmer, S. S. Schoenholz, P. F. Riley, O. Vinyals, and G. E. Dahl. Neural message passing for quantum chemistry. *arXiv preprint arXiv:1704.01212*, 2017.

[12] M. Grohe. *Descriptive complexity, canonisation, and definable graph structure theory*, volume 47. Cambridge University Press, 2017.

[13] W. Hu, B. Liu, J. Gomes, M. Zitnik, P. Liang, V. Pande, and J. Leskovec. Strategies for pre-training graph neural networks. *arXiv preprint arXiv:1905.12265*, 2019.

[14] T. N. Kipf and M. Welling. Semi-supervised classification with graph convolutional networks. *arXiv preprint arXiv:1609.02907*, 2016.

[15] T. N. Kipf and M. Welling. Variational graph auto-encoders. *arXiv preprint arXiv:1611.07308*, 2016.

[16] B. Knyazev, G. W. Taylor, and M. Amer. Understanding attention and generalization in graph neural networks. In *Advances in Neural Information Processing Systems*, pages 4202–4212, 2019.

[17] Z. Li, Q. Chen, and V. Koltun. Combinatorial optimization with graph convolutional networks and guided tree search. In *Advances in Neural Information Processing Systems*, pages 539–548, 2018.

[18] A. Loukas. What graph neural networks cannot learn: depth vs width. *arXiv preprint arXiv:1907.03199*, 2019.

[19] I. Luz, M. Galun, H. Maron, R. Basri, and I. Yavneh. Learning algebraic multigrid using graph neural networks. *arXiv preprint arXiv:2003.05744*, 2020.

[20] H. Maron, H. Ben-Hamu, N. Shamir, and Y. Lipman. Invariant and equivariant graph networks. *arXiv preprint arXiv:1812.09902*, 2018.

[21] C. Morris and P. Mutzel. Towards a practical k-dimensional weisfeiler-leman algorithm. *arXiv preprint arXiv:1904.01543*, 2019.

[22] C. Morris, M. Ritzert, M. Fey, W. L. Hamilton, J. E. Lenssen, G. Rattan, and M. Grohe. Weisfeiler and leman go neural: Higher-order graph neural networks. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pages 4602–4609, 2019.

[23] C. Morris, N. M. Kriege, F. Bause, K. Kersting, P. Mutzel, and M. Neumann. Tudataset: A collection of benchmark datasets for learning with graphs. In *ICML 2020 Workshop on Graph Representation Learning and Beyond (GRL+ 2020)*, 2020. URL `www.graphlearning.io`.

[24] E. Nachmani and L. Wolf. Molecule property prediction and classification with graph hypernetworks. *arXiv preprint arXiv:2002.00240*, 2020.

[25] O. Puny, H. Ben-Hamu, and Y. Lipman. From graph low-rank global attention to 2-fwl approximation. *arXiv preprint arXiv:2006.07846*, 2020.

[26] K. Sinha, S. Sodhani, J. Pineau, and W. L. Hamilton. Evaluating logical generalization in graph neural networks. *arXiv preprint arXiv:2003.06560*, 2020.

[27] Y. Sun, E. Tzeng, T. Darrell, and A. A. Efros. Unsupervised domain adaptation through self-supervision. *arXiv preprint arXiv:1909.11825*, 2019.

[28] H. Tang, Z. Huang, J. Gu, B.-L. Lu, and H. Su. Towards scale-invariant graph-related problem solving by iterative homogeneous graph neural networks. *ICML 2020 Workshop on Graph Neural Networks & Beyond*, 2020.

[29] P. Veličković, G. Cucurull, A. Casanova, A. Romero, P. Lio, and Y. Bengio. Graph attention networks. *arXiv preprint arXiv:1710.10903*, 2017.

[30] P. Veličković, R. Ying, M. Padovano, R. Hadsell, and C. Blundell. Neural execution of graph algorithms. *arXiv preprint arXiv:1910.10593*, 2019.

[31] S. Verma and Z.-L. Zhang. Stability and generalization of graph convolutional neural networks. In *Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pages 1539–1548, 2019.

[32] K. Q. Weinberger and L. K. Saul. Distance metric learning for large margin nearest neighbor classification. *Journal of Machine Learning Research*, 10(2), 2009.

[33] B. Weisfeiler and A. A. Lehman. A reduction of a graph to a canonical form and an algebra arising during this reduction. *Nauchno-Technicheskaya Informatsia*, 2(9):12–16, 1968.

[34] K. Xu, W. Hu, J. Leskovec, and S. Jegelka. How powerful are graph neural networks? *arXiv preprint arXiv:1810.00826*, 2018.

[35] Y. You, T. Chen, Z. Wang, and Y. Shen. When does self-supervision help graph convolutional networks? *arXiv preprint arXiv:2006.09136*, 2020.

[36] C. Yun, S. Sra, and A. Jadbabaie. Small relu networks are powerful memorizers: a tight analysis of memorization capacity. In *Advances in Neural Information Processing Systems*, pages 15558–15569, 2019.

[37] L. Zhao and L. Akoglu. Pairnorm: Tackling oversmoothing in gnns. *arXiv preprint arXiv:1909.12223*, 2019.

[38] A. Zweig and J. Bruna. A functional perspective on learning symmetric functions with neural networks. *arXiv preprint arXiv:2008.06952*, 2020.

A   PRELIMINARIES

This section discusses two key concepts that we use throughout the paper: (1) Graph Neural Networks; (2) The Weisfeiler-Lehman graph isomorphism test. At the end of the section, we also discuss the setup of constant GNN depth that we use in this paper.

Notation. We denote by $\{(a_1, m_{a_1}), \ldots, (a_n, m_{a_n})\}$ a **multiset**, that is a set where we allow multiple instances of the same element. Here $a_1, \ldots, a_n$ are distinct elements, and m_{a_i} is the number of times a_i appears in the multiset. bold-face letters represent vectors.

A.1   GRAPH NEURAL NETWORKS

We consider the common message-passing GNN architecture (34) defined as follows: Let $G = (V, E)$ be a graph, and for each node $v \in V$ let $\mathbf{h}_v^{(0)} \in \mathbb{R}^{d_0}$ be a node feature vector. Then for every $t > 0$ we define:

$$\mathbf{h}_v^{(t)} = \text{UPDATE}\left(\mathbf{h}_v^{(t-1)}, \text{AGG}\left(\left\{\mathbf{h}_u^{(t-1)} : \mathcal{N}(v)\right\}\right)\right).$$

Here, AGG is an permutation invariant aggregation function such as summation, averaging or taking max, UPDATE is an update function such as an MLP, and $\mathcal{N}(v)$ denotes the set of neighbors of node v. In case the graph is directed then $\mathcal{N}(v)$ denotes the set of nodes with edges incoming to v. For node prediction tasks, the output of a T-layer GNN for node v is $\mathbf{h}_v^{(T)}$, while for graph prediction tasks an additional readout layer is used:

$$g^{(T)} = \text{READOUT}\left\{\mathbf{h}_v^{(T)} : v \in V\right\},$$

where READOUT is some invariant function such as summation, averaging or taking the max, possibly followed by a fully connected network.

In our theoretical results, we focus on the **first order GNN** architecture from (22) defined in the following way:

$$\mathbf{h}_v^{(t)} = \sigma\left(W_2^{(t)}\mathbf{h}_v^{(t-1)} + \sum_{u \in \mathcal{N}(v)} W_1^{(t)}\mathbf{h}_u^{(t-1)} + \mathbf{b}^{(t)}\right).$$

Here, $W_1^{(t)}, W_2^{(t)} \in \mathbb{R}^{d_{t-1} \times d_t}$, $\mathbf{b}^{(t)} \in \mathbb{R}^{d_t}$ denotes the parameters of the t-th layer of the GNN, and σ is some non-linear activation (e.g ReLU). It was shown in (22) that GNNs composed from these layers have maximal expressive power with respect to all message passing neural networks. In general, we focus on GNNs that use the popular sum aggregation as it has maximal expressive power with respect to other aggregations used in message passing GNNs (34). We discuss other aggregation functions and the trade-of they present in Section 5.

A.2   THE WEISFEILER-LEHMAN TEST

The definition of d-patterns, which are used frequently in this paper, is closely related to the Weisfeiler-Lehman (WL) test (33; 12). The WL test is an algorithm to test whether two graphs are isomorphic and was recently coupled with the expressive power of GNNs. (34; 22). It is easiest to describe WL by using an equivalent algorithm called the color-refinement algorithm (12). The color refinement algorithm is executed sequentially, wherein each stage the algorithm generates a descriptor for each node according to the descriptors of its direct neighbors. The features in each stage can be used to define equivalence classes of nodes and the process continues until these equivalence classes cannot be refined anymore. The final graph descriptor is a histogram of the node features, and is closely related to the definition of d-patterns.

A.3   CONSTANT DEPTH VS. ADAPTIVE DEPTH TASKS

As stated earlier, multiple factors control size generalization. One important factor is the type of task: We make a distinction between two types of graph tasks. (1) Tasks that can be solved by constant depth GNN; A good example for such task is determining whether a certain, constant size connectivity pattern is found in the graph (2) Tasks that require the depth of the GNN to be related

to different parameters of the problem, such as the diameter of the graph. To exemplify, the task of calculating the diameter of a graph can be solved with a GNN only if its depth depends on the size of the graph (For more details see (28; 18)). On the other hand, tasks that require local information about each node can be solved with a constant depth GNN. We note that although there are several recent works about adaptive depth GNN, e.g. (28; 24), most currently used GNNs have constant relatively small depth (6)). In this paper, we focus on the first kind of tasks that require a constant number of GNN layers. We note that the size-generalization problem we discuss in this paper is also relevant for the second type of tasks, but we chose to discuss the problem in the simpler setup for clarity.

B PROOFS FROM SEC. 3

To prove Thm. 3.2 we will first need to following claim from (36) about the memorization power of ReLU networks:

Theorem B.1. *Let $\{\mathbf{x}_i, y_i\}_{i=1}^N \in \mathbb{R}^d \times \mathbb{R}$ such that all the $\mathbf{x}_i$ are distinct and $y_i \in [-1, 1]$ for all i. Then there exists a 3-layer fully connected ReLU neural network $f : \mathbb{R}^d \to \mathbb{R}$ with width $2\sqrt{N}$ such that $f(\mathbf{x}_i) = y_i$ for every i.*

We will also need the following lemma which will be used in the construction of each layer of the 1-GNN:

Lemma B.2. *Let $N \in \mathbb{N}$ and $f : \mathbb{N} \to \mathbb{R}$ be a function defined by $f(n) = \mathbf{w}_2^\top \sigma(\mathbf{w}_1 n - \mathbf{b})$ where $\mathbf{w}_1, \mathbf{w}_2, \mathbf{b} \in \mathbb{R}^N$, and σ is the ReLU function. Then for every $y_1, \ldots, y_N \in \mathbb{R}$ there exists $\mathbf{w}_1, \mathbf{w}_2, \mathbf{b}$ such that $f(n) = y_n$ for $n \leq N$ and $f(n) = (n - N + 1)y_N - (n - N)y_{N-1}$ for $n > N$.*

Proof. Define $\mathbf{w}_1 = \begin{pmatrix} 1 \\ \vdots \\ 1 \end{pmatrix}$, $\mathbf{b} = \begin{pmatrix} 0 \\ 1 \\ \vdots \\ N-1 \end{pmatrix}$. Let a_i be the i-th coordinate of $\mathbf{w}_2$, we will define a_i recursively in the following way: Let $a_1 = y_1$, suppose we defined $a_1, \ldots, a_{i-1}$, then define $a_i = y_i - 2a_{i-1} - \cdots - ia_1$. Now we have for every $n \leq N$:

$$f(n) = \mathbf{w}_2^\top \sigma(\mathbf{w}_1 n - \mathbf{b}) = na_1 + (n-1)a_2 + \cdots + a_n = y_n \ .$$

For $n > N$ we can write $n = N + k$ for $k \geq 1$, then we have:

$$
\begin{aligned}
f(n) = \mathbf{w}_2^\top \sigma(\mathbf{w}_1(N+k) - \mathbf{b}) &= (N+k)a_1 + (N+k-1)a_2 + \cdots + (k+1)a_N \\
&= y_N + k(a_1 + a_2 + \cdots + a_N) = y_N + k(y_N - a_{N-1} - 2a_{N-2} - \cdots - (N-1)a_1) \\
&= (k+1)y_N - ky_{N-1}
\end{aligned}
$$

$\square$

Now we are ready to prove the main theorem:

Proof of Thm. 3.2. We assume w.l.o.g that at the first iteration each node i is represented as a one-hot vector $\mathbf{h}_i^{(0)}$ of dimension $|C|$, with its corresponding node feature. Otherwise, since there are $|C|$ node features we can use one GNN layer that ignores all neighbors and only represent each node as a one-hot vector. We construct the first d layers of the 1-GNN F by induction on d. Denote by $a_i = |C| \cdot (N^i + N^{i-1})$ the dimension of the i-th layer of the GNN for $1 \leq i \leq d$, and $a_0 = |C|$.

The mapping has two parts, one takes the neighbors information and maps it into a feature representing the multiset of d-patterns, the other part is simply the identity saving information regarding the d-pattern of the node itself.

The d layer structure is

$$\mathbf{h}_v^{(d)} = U^{(d+1)}\sigma\left(W_2^{(d)}\mathbf{h}_v^{(d-1)} + \sum_{u \in \mathcal{N}(v)} W_1^{(d)}\mathbf{h}_u^{(d-1)} - \mathbf{b}^{(d)}\right)$$

We set $W_2^{(d)} = [0, I]^T$, $W_1^{(d)} = [\tilde{W}_1^{(d)T}, 0]^T$ and $U^{(d+1)} = [\tilde{U}^{(d+1)T}, 0]^T$ with $\tilde{W}_1^{(d)} \in \mathbb{R}^{Na_{d-1} \times a_{d-1}}$ and $\tilde{U}^{(d+1)} \in \mathbb{R}^{Na_{d-1} \times Na_{d-1}}$. For $\tilde{W}_1^{(d)}$ we set $\mathbf{w}_i^{(1)}$, its i-th row, to be equal to $\mathbf{e}_n$ where $n = \left\lceil \frac{i}{N} \right\rceil$. Let $b_i^{(1)}$ be the i-th coordinate of $\mathbf{b}^{(d)}$, be equal to $i - 1 \pmod{N}$ for $i \leq N \cdot a_{d-1}$ and zero otherwise. What this does for the first a_{d-1} elements of $W_2^{(d)} \mathbf{h}_v^{(d)} + \sum_{u \in \mathcal{N}(v)} W_1^{(d)} \mathbf{h}_u^{(d)}$ is that each dimension i hold the number of neighbors with a specific (d-1)-pattern. We then replicate this vector N times, and for each replica we subtract a different bias integer ranging from 0 to $N - 1$. To that output we concatenate the original $\mathbf{h}_v^{(d-1)}$

Next we construct $\tilde{U}^{(d+1)} \in \mathbb{R}^{Na_{d-1} \times Na_{d-1}}$ in the following way: Let $\mathbf{u}_i^{(d+1)}$ be its i-th row, and $u_{i,j}^{(d+1)}$ its j-th coordinate. We set $u_{i,j}^{(d+1)} = 0$ for every j with $j \neq \left\lceil \frac{i}{N} \right\rceil$ and the rest N coordinates to be equal to the vector $\mathbf{w}_2$ from Lemma B.2 with labels $y_\ell = 0$ for $\ell \in \{1, \ldots, N\} \setminus \{(i \bmod N) + 1\}$ and $y_\ell = 1$ for $\ell = (i \bmod N) + 1$.

Using the above construction we encoded the output on node v of the first layer of F as a vector:

This encoding is such that the i-th coordinate of $\mathbf{h}_v^{(d+1)}$ for $1 \leq i \leq N \cdot a_{d-1}$ is equal to 1 iff node v have $(i \bmod N) + 1$ neighbors with node feature $\left\lceil \frac{i}{N} \right\rceil \in \{1, \ldots, |C|\}$. The last a_{d-1} rows are a copy of $\mathbf{h}_v^{(d-1)}$.

Construction of the suffix. Next, we construct the last two layers. First we note that for a node v with d-pattern p there is a unique vector $\mathbf{z}_p$ such that the output of the 1-GNN on node v, $\mathbf{h}_v^{(d)}$, is equal to $\mathbf{z}_p$. From our previous construction one can reconstruct exactly the (d-1)-pattern of each node, and the exact number of neighbors with each (d-1)-pattern and therefore can recover the d-pattern correctly from the $\mathbf{h}_v^{(d)}$ embedding.

Finally, we use Thm. B.1 to construct the 3-layer fully connected neural network with width at most $2\sqrt{|P|}$ such that for every pattern $p_i \in P$ with corresponding unique representation $\mathbf{z}_{p_i}$ and label y_i, the output of the network on $\mathbf{z}_{p_i}$ is equal to y_i. We construct the last two layers of the 1-GNN such that $W_1^{(d+1)}, W_1^{(d)} = 0$, and $W_2^{(d+1)}, \mathbf{b}^{(d+1)}, W_2^{(d+2)}, \mathbf{b}^{(d+2)}, W^{(d+3)}$ are the matrices produced from Thm. B.1. Note that $W^{(d+3)}$ is the linear output layer constructed from the theorem, thus the final output of the 1-GNN for node v is $W^{(d+3)} \cdot h_v^{(d+2)}$, where $h_v^{(d+2)}$ is the output after $d + 2$ layers. $\qquad \square$

Proof of Corollary 3.3. By the assumption, the output of the task is determined by the d-patterns of the nodes. For each node with pattern p_i let y_i be the output of the node prediction task. Define

$$A = \arg \max_{A': P_1^{d-pat}(A') < \epsilon} P_2^{d-pat}(A') \tag{2}$$

By Thm. 3.2 there exists a 1-GNN such that for any d-pattern $p_i \in A$ gives a wrong label and for every pattern outside A, $p_j \in A^c$ gives the correct label. The 0-1 loss for small and large graphs is exactly $P_1^{d-pat}(A)$ and $P_2^{d-pat}(A)$ respectively.

$\qquad \square$

C ADDITIONAL EXPERIMENTS FROM SEC. 3.4

First, we consider the max-clique problem. The goal of this problem is given a graph, to output the size of the maximal clique. This is in general an NP-hard problem, hence a constant depth GNN will not be able to solve it for graphs of all sizes. For this task we sampled both the train and test graphs from a geometrical distribution defined as follows: given a number of nodes n and radius ρ we draw n points uniformly in $[0, 1]^2$, each point correspond to a node in the graph, and two nodes are connected if their corresponding points have a distance less than ρ. We further analyzed the effects of how the network depth and architecture affect size generalization.

Table 2 presents the test loss on the max-clique problem. Deeper networks are substantially more stricken due to the domain shift. If the test domain has a similar pattern distribution, increasing the

ρ_{train}/ρ_{test}	1-GNN			GIN		
	1-layer	2-layers	3-layers	1-layer	2-layers	3-layers
1	22.5 ± 3.2	41.6 ± 7.9	50.7 ± 70.4	25.9 ± 3.6	60.6 ± 15.6	134.2 ± 217.1
$\sqrt{2}$	9.6 ± 0.4	10.8 ± 0.6	11.7 ± 1.2	9.2 ± 0.5	10.5 ± 0.3	11.3 ± 0.5

Table 2: The difference is the predicted max clique size under size generalization domain shift. The train domain graphs were constructed by drawing $n \in [40, 50]$ points uniformly in the unit square, and connecting two point if their distance is less than $\rho_{train} = 0.3$. The test set domain graphs contain $n = 100$ nodes, effectively increasing their density by 2. We tested with two different values of ρ_{train}/ρ_{test}, the ratio between the train and test connectivity radius. A proper scaling that keeps the expected degree of each node is $\rho = \sqrt{2}$. Here, although proper scaling does not help solve the problem completely, it does improve performance.

		Node regression		Graph regression	
	p	Student - Teacher	Edge count	Student - Teacher	Edge count
1-GNN	0.3	187 ± 392	11.9 ± 19.4	60.4 ± 91.8	$(1.2 \pm 1.6) \cdot 10^3$
	0.15	$(\mathbf{3.7 \pm 5.1}) \cdot \mathbf{10^{-2}}$	$(\mathbf{7.2 \pm 3.7}) \cdot \mathbf{10^{-5}}$	$(\mathbf{9 \pm 10}) \cdot \mathbf{10^{-4}}$	$(\mathbf{6.9 \pm 3.3}) \cdot \mathbf{10^{-3}}$
GIN	0.3	125 ± 370	2.57 ± 2.88	33.8 ± 84.9	284 ± 286
	0.15	$\mathbf{1.35 \pm 4.5}$	$(\mathbf{2.2 \pm 0.3}) \cdot \mathbf{10^{-2}}$	$(\mathbf{5 \pm 17}) \cdot \mathbf{10^{-2}}$	$(\mathbf{9.1 \pm 7.1}) \cdot \mathbf{10^{-3}}$

Table 3: Comparing performance on different local distributions (a) A student-teacher graph regression task; (b) A graph regression task, where the graph label is the number of edges; (c) A student-teacher node regression task; (d) A node regression task, where the node label is its degree. In the edge count/degree tasks the loss is the mean difference from the ground-truths, divided by the average degree/number of edges. In the student-teacher tasks the loss is the mean L_2 loss between the teacher's value and the student's prediction, divided by the averaged student's prediction. Both the student and teacher share the same 3-layer architecture

neural network depth from one layer to three layers results in a small decrement of at most 20% to the loss. However, if the pattern distribution is different than the train pattern distribution, such change may increase the loss by more than $2.5\times$. We also show that the problem is consistent in both 1-GNN and GIN architectures.

Next, we tested on the student-teacher task, on both graph and node levels, on the degree prediction task of each node, and the task of predicting the number of edges in the graph. The goal of these experiments is to show that the size generalization problem persists on different tasks, two different architectures, and its intensity is increased for deeper GNN. In all the experiments we draw the graphs from $G(n, p)$ distribution, wherein the test set n is drawn uniformly between 40 and 50, and $p = 0.3$, and in the test set $n = 100$ and p is either 0.3 or 0.15. We note that when $p = 0.15$, the average degree of the test graph is equal to (approximately) the average degree of the train graph, while when $p = 0.3$ it is twice as large. We would expect that the model will generalize better when the average degree in the train and test set is similar, because then their d-patterns will also be more similar.

Table 3 compares the performance of these tasks when changing the graph size of the test data. We tested the performance with normalized test loss, where we normalized the output by the average output of the test set. This metric allows us to estimate the percentage of mistakes from the average output.

D SSL TASK ON WL TREE

First, we will need the following definition which constructs a tree out of the d-pattern introduced in the previous section. This tree enables us to extract certain properties for each node which can, later on, be learned using a GNN. This definition is similar to the definition of "unrolled tree" from (21).

Definition D.1 (d-pattern tree). *Let $G = (V, E)$ a graph, C a finite set of node features, where each $v \in V$ have a corresponding feature c_v, and $d \geq 0$. For a node $v \in V$, its d-**pattern tree** $T_v^{(d)} = (V_v^{(d)}, E_v^{(d)})$ is directed tree where each node corresponds to some node in G. It is defined recursively in the following way: For $d = 0$, $V_v^{(0)} = u_{(0,v)}$, and $E_v^{(0)} = \varnothing$. Suppose we defined $T_v^{(d-1)}$, and let $\tilde{V}_v^{(d-1)}$ be all the leaf nodes in $V_v^{(d-1)}$ (i.e. nodes without incoming edges). We define:*

TASKS	# TARGET SAMPLES	EDGE COUNT	DEGREE	TEACHER STUDENT	TEACHER STUDENT PER NODE
VANILLA	0	1318 ± 1398	12.22 ± 15.35	43.1 ± 38.1	30.47 ± 64.85
	1	0.46 ± 0.68	0.01 ± 0.01	0.13 ± 0.22	0.06 ± 0.15
	5	0.06 ± 0.07	$<$1E-3	0.08 ± 0.28	0.02 ± 0.05
	10	0.03 ± 0.03	$<$1E-3	0.01 ± 0.01	0.01 ± 0.03
d-PATTERN PT	0	1293 ± 918	53.24 ± 60.26	2.6 ± 3.96	0.39 ± 0.9
	1	1.7 ± 1.05	0.07 ± 0.04	$<$1E-3	$<$1E-4
	5	0.09 ± 0.19	0.02 ± 0.005	$<$1E-3	$<$1E-4
	10	0.05 ± 0.05	0.02 ± 0.01	$<$1E-3	$<$1E-4

Table 4: Test results est of synthetic datasets. Values are the loss divided by the mean over the test set of target output.

$$V_v^{(d)} = V_v^{(d-1)} \cup \left\{ u_{(d,v')} : v' \in \mathcal{N}(v''), \ u'_{(d-1,v'')} \in \tilde{V}_v^{(d-1)} \right\}$$

$$E_v^{(d)} = E_v^{(d-1)} \cup \left\{ (u_{(d,v')}, u'_{(d-1,v'')}) : v' \in \mathcal{N}(v''), \ u'_{(d-1,v'')} \in \tilde{V}_v^{(d-1)} \right\}$$

and for every node $u_{(d,v')} \in V_v^{(d)}$, its node feature is $c_{v'}$ - the node feature of v'

The main advantage of pattern trees is that they encode all the information that a GNN can produce for a given node by running the same GNN on the pattern tree.

This tree corresponds to the local patterns in the following way: the d-pattern tree of a node can be seen as a multiset of the children of the root, and each child is a multiset of its children, etc. This completely describes the d-pattern of a node.

Using the d-pattern tree we construct a simple regression SSL task where its goal is for each node to count the number of nodes in each layer of its d-pattern tree. This is a simple descriptor of the tree, which although loses some information about connectivity, does hold information about the structure of the layers.

For example, in Fig. 2 the descriptor for the tree would be that the root (zero) layer has a single black node, the first layer has two yellow nodes, the second layer has two yellow, two gray, and two black nodes, and the third layer has ten yellow, two black and two gray nodes.

E MORE EXPERIMENTS FROM SEC. 4

For synthetic datasets, we used the setting of Section 3.4. Source graphs were generated with $G(n, p)$ with n sampled uniformly in $[40, 50]$ and $p = 0.3$. Target graphs were sampled from $G(n, p)$ with $n = 100$ and $p = 0.3$.

Table 4 depicts the results of using the d-patterns SSL tasks, in addition to using the semi-supervised setting. It can be seen that adding the d-patterns SSL task significantly improves the performance on the teacher-student task, although it does not completely solve it. We also observe that adding labeled examples from the target domain significantly improves the performance of all tasks. Note that adding even a single example significantly improves performance. In all the experiments, the network was successful at learning the task on the source domain with less than 0.15 averaged error, and in most cases much less.

E.1 DATASETS STATISTICS

Table E.1 shows the statistics of the datasets that were used in the paper. In particular the table presents the split that was used in the experiments, we trained on graphs with sizes smaller or equal to the 50-th percentile and tested on graphs with sizes larger or equal to the 90-th percentile. In all the datasets there is a significant difference between the graph sizes in the train and test sets, and in some datasets there is also a difference between the distribution of the output class in the small and large graphs.

Table 5: Dataset statistics.

	NCI1			NCI109			DD		
	all	Smallest 50%	Largest 10%	all	Smallest 50%	Largest 10%	all	Smallest 50%	Largest 10%
Class A	49.95%	62.30%	19.17%	49.62%	62.04%	21.37%	58.65%	35.47%	79.66%
Class B	50.04%	37.69%	80.82%	50.37%	37.95%	78.62%	41.34%	64.52%	20.33%
Num of graphs	4110	2157	412	4127	2079	421	1178	592	118
Avg graph size	29	20	61	29	20	61	284	144	746

	Twitch_egos			Deezer_egos			IMDB-binary		
	all	Smallest 50%	Largest 10%	all	Smallest 50%	Largest 10%	all	Smallest 50%	Largest 10%
Class A	46.23%	39.05%	58.07%	56.80%	44.78%	64.97%	50.00%	48.98%	55.55%
Class B	53.76%	60.94%	41.92%	43.19%	55.21%	35.02%	50.00%	51.01%	44.44%
Num of graphs	127094	65016	14746	9629	4894	968	1000	543	108
Avg graph size	29	20	48	23	13	68	19	13	41

	PROTEINS		
	all	Smallest 50%	Largest 10%
Class A	59.56%	41.97%	90.17%
Class B	40.43%	58.02%	9.82%
Num of graphs	1113	567	112
Avg graph size	39	15	138