Learning a Compact, Parcel-independent Representation of the fMRI Functional Connectivity

Abstract

Functional connectivity in functional magnetic resonance imaging (fMRI) data is often calculated at the level of area parcels. Given the data's low-dimensional nature, we posit a substantial degree of redundancy in these representations. Moreover, establishing correspondence across different individuals poses a significant challenge in that framework. We hypothesize that learning a compact representation of the functional connectivity data without losing the essential structure of the original data is possible. Our analysis, based on various performance benchmarks, indicates that the pre-computed mapping to low-dimensional latent space learned from the functional connectivity of one dataset generalizes well to another with both linear and non-linear autoencoder-based methods. Notably, the latent space learned using a variational autoencoder represents the data more effectively than linear methods at lower dimensions (2 dimensions). However, at higher dimensions (32 dimensions), the differences between linear and nonlinear dimensionality reduction methods diminish, rendering the performance comparable to the parcel space representation with 333 dimensions. Our findings highlight the potential of employing an established transformation to obtain a low-dimensional latent representation in future functional connectivity research, thereby solving the correspondence problem across parcel definitions, promoting reproducibility, and supporting open science objectives.

1 Introduction

Spontaneous brain activity, as measured using the blood-oxygen-level dependent (BOLD) signals estimated with functional magnetic resonance imaging (fMRI), demonstrates a high correspondence between functionally homotopic brain regions (Biswal et al., 1995). Researchers have measured resting-state functional connectivity to delineate the functional organizations of the brain (Bijsterbosch et al., 2020; Eickhoff et al., 2015). Many studies omitted the spatial topography and described the brain organization as abstract nodes and edges, giving the pairwise "functional connectome" matrix and the associated network graph representations (Bassett & Sporns, 2017; Bullmore & Sporns, 2009; Cheirdaris, 2023; Rubinov & Sporns, 2010; Sporns et al., 2004). Nodes are predefined as 100-1000 area parcels (Arslan et al., 2018; Craddock et al., 2012; Gordon et al., 2016; Schaefer et al., 2018; Shen et al., 2013). In addition to the lack of consensus in node definition, recent work has demonstrated that the optimal definition of nodes can vary across individuals (Gordon et al., 2017b) and populations (Han et al., 2018; Myers et al., 2024). Secondly, recent studies showed that only a few dimensions can capture the majority of variance in functional connectivity data (Bolt et al., 2022; Gotts et al., 2020; Margulies et al., 2016; Snyder et al., 2022), potentially due to the high spatial correlation in the cerebral cortex (Pang et al., 2023; Shinn et al., 2023). Therefore, we explored the possibility of learning a pre-computed transformation that maps the functional connectivity seed maps (spatial patterns of connectivity from one node to the rest of the brain) to a low-dimensional latent representation with little compromise in preserving the key information for downstream analyses.

We obtained low-dimensional embeddings (2, 4, 32 dimensions) from the high-dimensional functional connectivity seed map (59412 dimensions) data using a few variants of autoencoders(Rumelhart et al., 1986) including the conventional autoencoder(Rumelhart et al., 1986), vari-

ational autoencoder(Kingma & Welling, 2022), β-variational autoencoder (β-VAE)(Higgins et al., 2017) , and adversarial autoencoder(Makhzani et al., 2016). We also compared the results with linear dimensionality reduction methods using Principal Component Analysis (PCA) and Independent Component Analysis (ICA). We explored the extent to which key features in the original data could be retained using these low-dimensional embeddings, and how it varied across dimensionality reduction methods and the number of dimensions. We adopted multiple performance metrics and used the parcel connectome with the Gordon parcellation (Gordon et al., 2016) of 333 nodes (a.k.a. 333 dimensions) as a reference benchmark.

2 RELATED WORK

Our current work is most similar to the representation of functional connectivity into principal gradients with diffusion embedding and other non-deep-learning-based methods (Langs et al., 2015; 2010; Margulies et al., 2016; Vos de Wael et al., 2020). However, learning the low-dimensional manifold in individuals and aligning them requires matched parcels across subjects using Procrustes analysis (Langs et al., 2015) and can be computationally expensive. Even more detrimentally, if the manifold spaces (e.g. across development or clinical conditions) differ substantially, the alignments may provide output that is not meaningful (Vos de Wael et al., 2020). Furthermore, this approach does not provide a backward projection to the original space from the embeddings to give an intuitive demonstration of a walk in the latent space. More discussion about challenges in establishing correspondence across subjects is provided in the Appendix A.1.

There are also numerous other deep-learning approaches to capture fMRI activity and connectivity with advanced deep neural network architectures(Caro et al., 2023; Zhang et al., 2020; Zhao et al., 2020; Zuo et al., 2023; Ryali et al., 2024; Qiang et al., 2021), which may make our work seem mundane at first look. However, many dealt with data in an abstract node format and did not respect the spatial topography in functional connectivity in the anatomical space. Moreover, most tested the model with performance on a specific task (e.g. disease classification(Qiang et al., 2021; Zhao et al. 2020)) or sex classification (Ryali et al., 2024) rather than a range of metrics as we suggested here. Most of them also consider the functional connectome (a.k.a. connectivity from each node to each other as one data sample) instead of the functional connectivity profile of each node as a single data sample. To our knowledge, limited prior work explored the possibility of using an unsupervised method to embed fMRI data into a latent space (Caro et al., 2023; Kim et al., 2021) for general-purpose visualization and analyses, or demonstrate the effect of traversing the latent space. None of them has attempted that on functional connectivity seed maps nor with an extremely low-dimensional bottleneck (2, 4, and 32) as we do here, and only one tried generalizing to a different dataset(Caro et al., 2023).

Here, we aim to find a pre-computed transformation that maps new functional connectivity seed map data onto a low-dimensional space downstream visualization and analyses. This approach is easy to apply and can help with results comparison across research labs. Furthermore, analyses such as clustering can benefit from the computational advantage in a low-dimensional embedding space (Langs et al., 2016; Zhakubayev & Hamerly, 2022) (more discussion on this in Appendix A.2).

3 METHODS

3.1 NEUROIMAGING DATA

We used resting-state fMRI data from the Washington University 120 (WU120) (Power et al., 2014) and the Human Connectome Project (HCP) (Glasser et al., 2016; Van Essen et al., 2012b) datasets for training and testing the models. Both datasets were collected from young adult subjects (19-35 years) while they were asked to fixate on a center cross on the screen in a 3-Tesla MRI scanner. Procedures were then applied to normalize intensity, correct for motion in the scanner, and transform the data onto a standard 32k-fsLR surface (Van Essen et al., 2012a). Details are available in the Appendix A.3. The WU120 dataset contains one resting-state session per subject for 120 subjects. Out of the 120 subjects from WU120, 100 subjects were selected as the training data, 10 as the validation data, and 10 as the test data. The HCP dataset contains 94 subjects from unrelated families, with two resting-state sessions for each subject. We used both sessions (Rest1 and Rest2) in the HCP dataset as the test data.

3.1.1 PREPARATION OF THE FUNCTIONAL CONNECTOME DATA

First, to make the functional connectome comparable across different nodal definitions, we used a functional connectivity seed map, where the values at each location in the cortical vertex represent its connectivity with a given seed region. This was calculated as the Pearson's correlation between the BOLD time series of the seed region and the BOLD time series at each vertex in the cerebral cortex surface (N = 59412 in the standard 32k-fsLR surface). This results in a matrix of N_{nodes} seed maps, each with a dimension of 59412 x 1. To encourage diversity and variability in the training data while keeping computational demand manageable, we used the cortical vertices as seed regions (N_{nodes} = 59412 per subject) and randomly sampled 10% of the seed maps for each subject (total training samples = 591200). In the test data, we used individual parcels from the Gordon parcellation (Gordon et al., 2016) as seed regions (N_{nodes} = 333 per subject) for each subject.

Figure 1: **Geometric reformatting and model architecture.** A) Geometric reformatting. The cortical distribution of fMRI activity is converted onto a spherical surface and then to an image by evenly resampling the spherical surface with respect to sin(e) and a, where e and a indicate elevation and azimuth, respectively. B) Architecture of VAE. Simplified block diagram of VAE model (upper panel in B). An encoder network samples latent variables given an input image under the inference model while a decoder network generates a genuine input image from under the generative model. Details of VAE model (bottom panel in B). Both the encoder and decoder networks contain 5 convolutional layers. Blue and red boxes represent the input images from the left and right hemispheres, respectively. *Adapted with permission from Kim, J., Zhang, Y., Han, K., Wen, Z., Choi, M., & Liu, Z. (2021). Representation learning of resting state fMRI with variational autoencoder. NeuroImage, 241, 118423. Copyright 2021 by Elsevier Inc.*

For the autoencoder-based models, the input was passed on as a 2-D image to take advantage of the convolutional layers of the model (Figure 1A, see details in Appendix A.4). This transformation would result in a small distortion such that the reconstructed 59412 x 1 seed maps from this 192 x 192 grid explain ẽ9.9% variance from the original seed maps. To ensure fairness across algorithms, we passed the reconstructed seed maps (with distortion) instead of the original seed map from the 192 x 192 grid to PCA and ICA.

3.2 DIMENSIONALITY REDUCTION METHODS

3.2.1 AUTOENCODER-BASED METHODS

Autoencoders are neural networks designed to encode the input into a compressed representation, and then decode it back to a reconstructed input similar to the original one. The variational autoencoders (VAE) (Kingma & Welling, 2022) are especially useful in obtaining a smooth, continuous latent space for generating new data. The β-VAE variant (Higgins et al., 2017) is most effective in disentangling latent generative factors from images. Unlike t-SNE and diffusion maps, the AE-based models feature an intrinsic encoder for easy new data embedding and a decoder for data reconstruction. We adopted the same model architecture as described in (Kim et al., 2021; 2023; 2024) with five convolutional layers and one fully-connected layer in the encoder, and one fully-connected layer

and five convolutional layers in the decoder. The encoder transformed an fMRI seed map (a pair of left and right hemisphere images formatted to two 192 x 192 grids) into a probabilistic distribution of N latent variables (or a deterministic N latent variables in the case of a conventional autoencoder). Each convolutional layer performed linear convolutions and rectified the outputs (Nair & Hinton, 2010). The 1st layer applied 8×8 convolutions to inputs from each hemisphere, concatenating the results. Layers 2 to 5 then applied 4×4 convolutions to this concatenated output. Circular padding was used at azimuth boundaries, and zero padding was applied at elevation boundaries. The fully connected layer used linear weighting to produce the mean and standard deviation for each latent variable's distribution. The decoder mirrored this architecture, connecting the layers in reverse order to reconstruct the fMRI seed map from a sample latent variable. Details of the model design and different variants of autoencoder-based models are available in Appendix A.5. The VAE variant was optimized to reconstruct the input while constraining the distribution of every latent variable to be close to an independent and standard normal distribution. This is achieved through optimizing the encoding parameters, ϕ, and the decoding parameters, θ, to minimize the loss function below:

$$L(\phi, \theta \mid x) = \| x - x' \|_2 + \beta \cdot D_{KL} \left[N(\mu_z, \sigma_z) \parallel N(0, I) \right] \tag{1}$$

where x is the input data from both hemispheres, x' is the reconstructed data, and $N(\mu_z, \sigma_z)$ is the posterior distribution, $N(0, I)$ is the prior distribution. D_{KL} measures the Kullback-Leibler (KL) divergence between the posterior and prior distributions, and β is a hyperparameter balancing the two terms in the loss function. A $\beta < 1$ places less emphasis on the KL divergence and focuses more on reconstruction, while a $\beta > 1$ places a higher emphasis on KL divergence, enforcing stricter regularization of the latent space. When $\beta = 0$, the loss function only depends on the reconstruction error and is thus the conventional autoencoder. Instead of using the KL-divergence loss for regularization, the adversarial autoencoder used a separate discriminator network (3-layers, with the first two with a leaky ReLU activation function with a negative slope angle of 0.2 and the last one with a sigmoid activation function) for regularization (Makhzani et al., 2016).

Models were trained with stochastic gradient descent with a batch size of 128, initial learning rate of 1×10^{-4}, and 50 epochs with random data selection in each batch. An Adam optimizer (Kingma & Ba, 2014) was implemented, and the learning rate decayed by a factor of 10 every 20 epochs for the AE and VAE models. Final hyperparameters including the number of latent dimensions and the beta value were determined by the trade-off between KL divergence and reconstruction loss on the validation data (See Appendix A.6). The model was trained in Python 3.8 using PyTorch (v2.1.2+cu118) using a server with an NVIDIA A100 GPU (40 GB memory). A brief demonstration of model performance variability using different subsets of training data is provided in Appendix A.7.

3.2.2 LINEAR DIMENSIONALITY REDUCTION METHODS

We chose principal component analysis (PCA) and independent component analysis (ICA) as alternative linear dimensionality reduction methods. PCA uses Singular Value Decomposition of the data, keeping only the most significant singular vectors to project the data to a lower dimensional space. ICA attempts to decompose the data into a set of independent spatial maps. For memory management, we performed PCA with incremental PCA (IPCA) from the Scikit-learn package (v1.3.2) in Python 3.8 (Golub & Loan, 2013; Ross et al., 2008). IPCA builds a low-rank approximation for the input data using a memory amount that is independent of the number of samples. ICA was performed on the reduced data using the first 100 PCs with FastICA in Scikit-learn.

3.3 ASSESSING THE QUALITY OF EMBEDDINGS

3.3.1 RECONSTRUCTION PERFORMANCE

Reconstruction performance was calculated with η^2, namely, the fraction of variance in the original seed map accounted for by variance in the reconstructed seed map on a point-by-point basis (Cohen et al., 2008). η^2 ranged from 0 (no similarity) to 1 (identical) and is formally defined by:

$$\eta^2 = 1 - \frac{SS_{\text{Within}}}{SS_{\text{Total}}} = 1 - \frac{\sum_{i=1}^{n} \left[(a_i - \mu_i)^2 + (b_i - \mu_i)^2 \right]}{\sum_{i=1}^{n} \left[(a_i - \bar{M})^2 + (b_i - \bar{M})^2 \right]} \tag{2}$$

where a_i and b_i represent the values at position i in maps a and b, respectively. μ_i is the mean value of the two images at position i, $(a_i + b_i)/2$. $\bar{M}$ is the grand mean value across the mean image m.

Self-connectivity at all positions was excluded. This similarity matrix is sensitive to the difference in a and b in scales and offsets, unlike correlation. For convenience, we used the inversely formatted seed maps from the 2D image in Figure 1A as the reference ground truth data ($\eta^2 > 0.99$ to the original data) to be compared with the reconstructed data from latent representations. Note that perfect reconstruction is not necessarily desirable because the original data might be noisy, and the reconstructed data could potentially represent a "denoised" version of the data. We calculated two additional reference measures: the first one is the η^2 between the ground truth data in HCP Rest1 and HCP Rest2 of the same subject, which provides the noise ceiling of the reconstruction; the second one is the η^2 between each subject to the rest 93 subjects in each session (averaged across the Rest1 and Rest2 sessions), which provides the null baseline of group-average.

3.3.2 SEPARATION BY CANONICAL FUNCTIONAL NETWORKS

One key feature of functional connectivity is that nodes within the same functional network tend to possess similar seed maps (Yeo et al., 2011). The 333 parcels in the Gordon parcellation were grouped into 12 functional networks and one additional group (named "None") of 47 parcels which covered the low-SNR regions and cannot be confidently grouped into any of the 12 functional networks and omitted from this analysis (Gordon et al., 2016). We evaluated the segregation of seed maps from different functional networks with the silhouette index (SI) (Rousseeuw, 1987; Yeo et al., 2011), calculated as:

$$SI(i) = \frac{b_i - a_i}{max(a_i, b_i)} \tag{3}$$

where b_i is the mean Euclidean distance between the current parcel i to the parcels in the best alternative network, and a_i is the mean within-network Euclidean distance of the latent. A 95% confidence interval was calculated by bootstrapping the individuals 1000 times.

3.3.3 INTRASUBJECT AND INTERSUBJECT VARIABILITY

To capture individual differences in functional network assignments (Gordon et al., 2017a;b), we ran a k-means clustering algorithm on the latent embeddings with the cluster centroid initialized to be the center of each of the 12 Gordon networks (Gordon et al., 2016). 12 clusters were optimized by minimizing Euclidean distances between latent embeddings (dimensions = 2, 4, 32) within a cluster. Intersubject variability was calculated as the average normalized Hamming distance (a.k.a. proportion of mismatches, with 0 indicating perfect match) from each subject to other subjects; the intrasubject variability was calculated as the average normalized Hamming distance between the two resting sessions of the same subject. The latent representations that capture the most individual differences need to exhibit low intrasubject reliability while simultaneously maintaining a high intersubject variability. We calculated the variability signal-to-noise ratio (vSNR) to quantify the relative magnitude of the two sources of variability (Langs et al., 2016). Specifically:

$$vSNR = \frac{\text{Intersubject variability}}{\text{Intrasubject variability}} - 1 \tag{4}$$

4 RESULTS

4.1 SINGLE LATENT TRAVERSAL

To understand how the changes in the magnitude of each latent dimension affect the reconstructed seed map appearance, we plotted the single latent traversals when the number of dimensions = 2 (Figure 2). We varied the magnitude of one latent dimension while keeping the other latent dimension fixed at zero. We observed patterns reminiscent of sensorimotor networks and association networks (Margulies et al., 2016; Sydnor et al., 2021), as well as task-positive to task-negative networks (Buckner et al., 2008; Fox et al., 2005; Raichle, 2015). Notably, reconstructed maps similar to separate somatomotor and visual networks were only observable in VAE ($\beta = 20$). We also observed a gradual transition from somatomotor hand to somatomotor mouth networks when varying a single dimension in VAE ($\beta = 20$). The conventional AE has similar profiles in its first and second latent dimensions, suggesting ineffective disentangling of generative factors. In summary, a single latent dimension in VAE ($\beta = 20$) seems to disentangle the most subtle details in functional connectivity.

Figure 2: Single latent traversal. The reconstructed seed maps from latent values of one dimension varied in equal steps from one end to the other end and the other dimension was fixed to 0. A) VAE ($\beta = 20$), B) VAE ($\beta = 1$), C) AAE, D) AE, E) PCA, F) ICA.

4.2 RECONSTRUCTION PERFORMANCE

Next, we examined the reconstruction performance for parcel seed maps (functional connectivity from an area parcel defined from an atlas (Gordon et al., 2016)) to examine how effectively different dimensionality reduction methods retain information. 10 test subjects in the WU120 dataset and

both Rest1 and Rest2 sessions for the 94 subjects in the HCP dataset were chosen to test the out-of-sample and out-of-distribution generalization, respectively. Figure 3A shows reconstructed seed maps from one example parcel (parcel 15 in the medial visual cortex). Overall, the mean reconstruction performance across all parcels in each individual was similar across methods, with AE-based latent representations providing better reconstruction performance when the latent representation had only 2 dimensions (Figure 3B) and linear methods providing marginally better reconstruction performance at 32 dimensions (Figure 3D). In all cases, the reconstruction performance from the latent representations was on average higher than the null baseline, suggesting that the latent representations captured individual-specific features in additional to group-average features. With 32 dimensions, the reconstruction performance was approaching the noise ceiling (for the normalized reconstruction performance relative to the individuals' noise ceiling see Appendix A.9).

Figure 3: **Reconstruction performance in the test set.** A) Visualization of the original and reconstructed seed maps from parcel 15 in an example subject (subject 111). B-D) The reconstruction performance for all subjects in the HCP and WU120 test datasets. Reconstruction Green line: HCP Rest1, Red line: HCP Rest2, Blue line: WU120. Gray shaded area: mean and standard deviation of the noise ceiling and the null baseline. N.B.: 333 parcels always have 333 dimensions and were repeatedly displayed in all three panels as a reference. VAE = variational autoencoder. AAE = adversarial autoencoder. PCA = principal component analysis. ICA = independent component analysis. AE = autoencoder.

4.3 SEPARATION BY CANONICAL FUNCTIONAL NETWORKS

Seed maps from area parcels belonging to the same functional network should be similar to each other. We asked whether the functional network clusters defined in adult group-average data (Gordon et al., 2016) were preserved in the low-dimensional embeddings (examples for dimension = 2 in Figure 4). We quantified the distinguishability from the best alternative network for each of the 333 parcels with the silhouette index (SI) for the average latent embeddings of Rest1 sessions seed maps across 94 HCP subjects. First, we found the separation by functional networks in the parcellated functional connectome (dimension = 333, SI = 0.158, see Appendix A.10). Even at dimension =2, functional network segregation in the latent space was evident across all dimensionality reduction methods, particularly in the separation of sensorimotor networks from association networks (with the exception of AE). However, the distinction within the sensorimotor networks (visual, somato-

motor, auditory) was far more pronounced in the VAE and AAE latent spaces, especially with VAE ($\beta = 20$). Another interesting observation was that the default mode network (colored red in Figure 4A) appeared to separate into two distinct clusters for the VAE ($\beta = 20$) latent space (See Appendix A.11). At two dimensions, the average SI for VAE ($\beta = 20$) was 0.086 (95% CI: [0.066, 0.099]), higher than the VAE ($\beta = 1$) (0.044, 95% CI: [0.015, 0.063]), AAE (0.035, 95% CI: [0.006,0.054]), AE (0.014,[-0.018,0.030]), PCA (7×10^{-4}, 95% CI: [-0.016, 0.009]) and ICA (-0.010, 95% CI: [-0.028, 0.001]). When the latent dimensions were 4 or 32, the average SI can sometimes be higher than that in the parcel connectome (Table 2). Among the models tested, VAE ($\beta = 20$) with four dimensions (SI = 0.213, 95% CI: [0.197,0.221]) best separates the parcels according to the functional network labels (A.10). Notably, functional connectivity networks have hierarchical organization (Betzel & Bassett, 2017; Urchs et al., 2019), and the current functional network labels (Figure 4A) only represent one popular scale of investigation. The reduction in SI from dimension = 4 to dimension = 32 for some methods (A.10) might be due to the more pronounced separation of network sub-components at a relatively higher-dimension latent space.

Figure 4: **Separation by canonical functional networks.** A) Gordon network assignments. B/D/F/J/L/N) The functional connectome 2-dimensional embeddings. Small dots represent data from individual subjects and large circles represent data averaged across 94 subjects. C/E/I/K/M/O) The mean Euclidean distance between the latent representations of the average across 94 subjects. VAE = variational autoencoder. AAE = adversarial autoencoder. AE = autoencoder. PCA = principal component analysis. ICA = independent component analysis.

4.4 Intrasubject and Intersubject Variability

Despite the largely consistent topography of functional networks (Damoiseaux et al., 2006; Gratton et al., 2018), individual differences in functional network assignment have been observed in prior studies (Gordon et al., 2017b;a; Gratton et al., 2018). We tested how well the latent representations

preserve these individual differences. First, we examined the ability of the low-dimensional representation to capture the intersubject variability while preserving the similarity of intrasubject data in individual parcels. We used an example parcel (parcel 213) with a large variability. We found that the relative positions of the embeddings for different subjects were consistent across the two resting scan sessions (Rest1 and Rest2) in the VAE ($\beta = 20$) latent space (Figure 5). The two subjects at the extremes demonstrated very distinct seed map profiles (Figure 5). Next, we applied a k-means clus-

Figure 5: **Interindividual variability of an example parcel across sessions across 94 subjects in the VAE ($\beta = 20$) latent representation, at dimension = 2.** Each data point is a subject indicated by the numbers 1 to 94. The seed maps from parcel 213 for subject 8 and subject 33 in Rest1 and Rest2 were shown as an example.

tering with k = 12 to the low-dimensional embeddings for the 94 subjects in HCP across Rest1 and Rest2 sessions. We calculated the intrasubject and intersubject variability using Hamming distance (proportion of mismatch in the 333 parcel assignments) and vSNR as described in **section 3.3.3**. We found that independent of the dimensionality reduction method used, the intersubject variability was higher than the intrasubject variability by about 50%, suggestive of the preservation of individual specificity in the functional connectome in the latent spaces (See Table 3 in Appendix A.12). Across all subjects, the within-subject network assignment was more similar than the between-network subject assignment (Figure 6, also see Appendix A.12). vSNR was among the highest for VAE ($\beta = 20$) across 2, 4 and 32 dimensions. Furthermore, we tested whether different sessions of the same individual can be successfully identified from a list of subjects and found that the identification accuracy using the latent embeddings at various dimensionalities closely approximated the fingerprinting accuracy using the parcel connectome, especially when the scan length was long enough (> 20 min). (Details in Appendix A.13). Similarly, the prediction performance of age and sex from the different embeddings were similar and increased with the number of dimensions (Appendix A.14).

5 DISCUSSION

This work presents the learning of mappings of functional connectivity seed maps from vertex space to a low-dimensional latent space using data from one young adult dataset. Among different performance benchmarks, including the reconstruction performance, separation by functional networks, and the retention of individual specificity, the linear dimensionality-reduction methods PCA and ICA achieved similar performance to the nonlinear AE-based dimensionality-reduction methods, especially at higher dimensions. This is consistent with prior research finding comparable functional connectivity gradients with PCA, Laplacian eigenmaps, and diffusion mapping (Vos de Wael et al., 2020), suggesting that the functional connectivity data likely has a predominantly linear structure. Other supervised machine learning approaches also found comparable performance with deep neural networks and kernel regression (He et al., 2018), suggesting that more complex models are not always better. However, with only 2 dimensions, the VAE ($\beta = 20$) latent space preserves the structure in the data the best and separates the fine nuisances across functional networks. It may

Figure 6: **Individual-specific network using k-means clustering with 12 networks (VAE beta = 20, dimension = 32).** The functional network assignment for Rest1 and Rest2 sessions based on k-means clustering on latent representations across of all parcels in all subjects and sessions for A) subject 1 and B) subject 10. C) The normalized Hamming distance for between-subject network assignments (violins) and within-subject network assignments (asterisks).

make a useful visualization tool for simultaneously comparing the seed map profiles across sessions, individuals, and states independent of the definition of parcels. This could enable analyses such as community detection and behavioral phenotype prediction to be conducted in a much more manageable space, and allow efficient data sharing for big data initiatives (Horien et al., 2021).

We infer that our learned mappings will apply to new unseen datasets based on two lines of reasoning: 1) we demonstrated that the mappings were generalizable beyond the original training data, despite the differences in acquisition procedures and subjects; 2) extensive prior literature has observed low dimensionality in functional connectivity data (Gotts et al., 2020; Margulies et al., 2016; Snyder et al., 2022) with prominent patterns conserved across development (Dong et al., 2021; Xia et al., 2022). However, future studies could explicitly test this assumption in other populations, especially in developmental and clinical cohorts.

6 LIMITATIONS AND FUTURE WORK

We acknowledge that our training data is a small sample with a narrow profile of demographics. The training dataset could be extended to incorporate diverse demographics, acquisition parameters, developmental stages, etc. However, with the continuous, regularized latent space learned by a VAE, it is reasonable to assume that even if the exact seed map does not exist in the original dataset, as long as they are dominated by the same generative factors (as expected by the constraints of physical and biological properties), the latent space representation mapped using our existing model would still retain key information of the new dataset. Additionally, the VAE latent space lacks interpretability and appreciation of structural-functional interplay unlike the popular methods exploring harmonic modes/eigenmodes in the brain from anatomy. Therefore, our model is a phenomenological model rather than a mechanistic model. Moreover, our framework targets (resting-state) functional connectivity analyses and overlooks the temporal information in the neural data. Similar methods of representational learning of temporal information in the neural data exist in the literature(Caro et al., 2023; Kim et al., 2021), and we explained our motivation for embedding the functional connectivity data instead of time series data with more detailed comparison in appendix A.15.

REFERENCES

Salim Arslan, Sofia Ira Ktena, Antonios Makropoulos, Emma C. Robinson, Daniel Rueckert, and Sarah Parisot. Human brain mapping: A systematic comparison of parcellation methods for the human cerebral cortex. *NeuroImage*, 170:5–30, April 2018. ISSN 1053-8119. doi: 10.1016/j.neuroimage.2017.04.014. URL https://www.sciencedirect.com/science/article/pii/S1053811917303026.

D. S. Bassett, N. F. Wymbs, M. A. Porter, P. J. Mucha, J. M. Carlson, and S. T. Grafton. Dynamic reconfiguration of human brain networks during learning. *Proceedings of the National Academy of Sciences*, 108(18):7641–7646, May 2011. ISSN 0027-8424, 1091-6490. doi: 10.1073/pnas.1018985108. URL http://www.pnas.org/cgi/doi/10.1073/pnas.1018985108.

Danielle S Bassett and Olaf Sporns. Network neuroscience. *Nature neuroscience*, 20(3):353–364, February 2017. ISSN 1097-6256. doi: 10.1038/nn.4502. URL https://www.ncbi.nlm.nih.gov/pmc/articles/PMC5485642/.

Richard F. Betzel and Danielle S. Bassett. Multi-scale brain networks. *NeuroImage*, 160:73–83, October 2017. ISSN 1053-8119. doi: 10.1016/j.neuroimage.2016.11.006. URL https://www.sciencedirect.com/science/article/pii/S1053811916306152.

Richard F. Betzel, Lisa Byrge, Ye He, Joaquín Goñi, Xi-Nian Zuo, and Olaf Sporns. Changes in structural and functional connectivity among resting-state networks across the human lifespan. *NeuroImage*, 102:345–357, November 2014. ISSN 10538119. doi: 10.1016/j.neuroimage.2014.07.067. URL https://linkinghub.elsevier.com/retrieve/pii/S1053811914006508.

Richard F. Betzel, Maxwell A. Bertolero, Evan M. Gordon, Caterina Gratton, Nico U. F. Dosenbach, and Danielle S. Bassett. The community structure of functional brain networks exhibits scale-specific patterns of inter- and intra-subject variability. *NeuroImage*, 202, November 2019. ISSN 1053-8119. doi: 10.1016/j.neuroimage.2019.07.003. URL https://www.sciencedirect.com/science/article/pii/S1053811919305658.

Janine Bijsterbosch, Samuel J. Harrison, Saad Jbabdi, Mark Woolrich, Christian Beckmann, Stephen Smith, and Eugene P. Duff. Challenges and future directions for representations of functional brain organization. *Nature Neuroscience*, 23(12):1484–1495, December 2020. ISSN 1546-1726. doi: 10.1038/s41593-020-00726-z. URL https://www.nature.com/articles/s41593-020-00726-z.

Bharat Biswal, F. Zerrin Yetkin, Victor M. Haughton, and James S. Hyde. Functional connectivity in the motor cortex of resting human brain using echo-planar mri. *Magnetic Resonance in Medicine*, 34(4):537–541, 1995. ISSN 1522-2594. doi: 10.1002/mrm.1910340409. URL https://onlinelibrary.wiley.com/doi/abs/10.1002/mrm.1910340409.

Taylor Bolt, Jason S. Nomi, Danilo Bzdok, Jorge A. Salas, Catie Chang, B. T. Thomas Yeo, Lucina Q. Uddin, and Shella D. Keilholz. A parsimonious description of global functional brain organization in three spatiotemporal patterns. *Nature Neuroscience*, 25(8):1093–1103, August 2022. ISSN 1097-6256, 1546-1726. doi: 10.1038/s41593-022-01118-1. URL https://www.nature.com/articles/s41593-022-01118-1.

Randy L. Buckner, Jessica R. Andrews-Hanna, and Daniel L. Schacter. The brain's default network. *Annals of the New York Academy of Sciences*, 1124(1):1–38, 2008. ISSN 1749-6632. doi: 10.1196/annals.1440.011. URL https://onlinelibrary.wiley.com/doi/abs/10.1196/annals.1440.011.

Ed Bullmore and Olaf Sporns. Complex brain networks: Graph theoretical analysis of structural and functional systems. *Nature Reviews Neuroscience*, 10(3):186–198, March 2009. ISSN 1471-003X, 1471-0048. doi: 10.1038/nrn2575. URL http://www.nature.com/articles/nrn2575.

Gregory C. Burgess, Sridhar Kandala, Dan Nolan, Timothy O. Laumann, Jonathan D. Power, Babatunde Adeyemo, Michael P. Harms, Steven E. Petersen, and Deanna M. Barch. Evaluation

of denoising strategies to address motion-correlated artifacts in resting-state functional magnetic resonance imaging data from the human connectome project. *Brain Connectivity*, 6(9): 669–680, November 2016. ISSN 2158-0014. doi: 10.1089/brain.2016.0435. URL https://www.ncbi.nlm.nih.gov/pmc/articles/PMC5105353/.

Josue Ortega Caro, Antonio H. de O. Fonseca, Christopher Averill, Syed A. Rizvi, Matteo Rosati, James L. Cross, Prateek Mittal, Emanuele Zappala, Daniel Levine, Rahul M. Dhodapkar, Chadi G. Abdallah, and David van Dijk. Brainlm: A foundation model for brain activity recordings, September 2023. URL https://www.biorxiv.org/content/10.1101/2023.09.12.557460v1.

Dionysios G. Cheirdaris. Graph theory-based approach in brain connectivity modeling and alzheimer's disease detection. In Panagiotis Vlamos (ed.), *GeNeDis 2022*, pp. 49–58, Cham, 2023. Springer International Publishing. ISBN 978-3-031-31982-2. doi: 10.1007/978-3-031-31982-2_5.

Rastko Ciric, Daniel H. Wolf, Jonathan D. Power, David R. Roalf, Graham L. Baum, Kosha Ruparel, Russell T. Shinohara, Mark A. Elliott, Simon B. Eickhoff, Christos Davatzikos, Ruben C. Gur, Raquel E. Gur, Danielle S. Bassett, and Theodore D. Satterthwaite. Benchmarking of participant-level confound regression strategies for the control of motion artifact in studies of functional connectivity. *NeuroImage*, 154:174–187, July 2017. ISSN 1053-8119. doi: 10.1016/j.neuroimage.2017.03.020. URL https://www.sciencedirect.com/science/article/pii/S1053811917302288.

Alexander L. Cohen, Damien A. Fair, Nico U. F. Dosenbach, Francis M. Miezin, Donna Dierker, David C. Van Essen, Bradley L. Schlaggar, and Steven E. Petersen. Defining functional areas in individual human brains using resting functional connectivity mri. *NeuroImage*, 41(1):45–57, May 2008. ISSN 1053-8119. doi: 10.1016/j.neuroimage.2008.01.066. URL https://www.sciencedirect.com/science/article/pii/S1053811908001171.

R. Cameron Craddock, G.Andrew James, Paul E. Holtzheimer III, Xiaoping P. Hu, and Helen S. Mayberg. A whole brain fmri atlas generated via spatially constrained spectral clustering. *Human Brain Mapping*, 33(8):1914–1928, 2012. ISSN 1097-0193. doi: 10.1002/hbm.21333. URL https://onlinelibrary.wiley.com/doi/abs/10.1002/hbm.21333.

J. S. Damoiseaux, S. a. R. B. Rombouts, F. Barkhof, P. Scheltens, C. J. Stam, S. M. Smith, and C. F. Beckmann. Consistent resting-state networks across healthy subjects. *Proceedings of the National Academy of Sciences*, 103(37):13848–13853, September 2006. ISSN 0027-8424, 1091-6490. doi: 10.1073/pnas.0601417103. URL https://www.pnas.org/content/103/37/13848.

Manlio de Domenico. Multilayer modeling and analysis of human brain networks. *GigaScience*, 6(5):1, February 2017. doi: 10.1093/gigascience/gix004. URL https://pmc.ncbi.nlm.nih.gov/articles/PMC5437946/.

Hao-Ming Dong, Daniel S. Margulies, Xi-Nian Zuo, and Avram J. Holmes. Shifting gradients of macroscale cortical organization mark the transition from childhood to adolescence. *Proceedings of the National Academy of Sciences*, 118(28):e2024448118, July 2021. doi: 10.1073/pnas.2024448118. URL https://www.pnas.org/doi/abs/10.1073/pnas.2024448118.

Simon B. Eickhoff, Bertrand Thirion, Gaël Varoquaux, and Danilo Bzdok. Connectivity-based parcellation: Critique and implications. *Human Brain Mapping*, 36(12):4771–4792, 2015. ISSN 1097-0193. doi: 10.1002/hbm.22933. URL https://onlinelibrary.wiley.com/doi/abs/10.1002/hbm.22933.

Damien A Fair. Correction of respiratory artifacts in mri head motion estimates. *NeuroImage*, pp. 17, 2020.

Emily S. Finn, Xilin Shen, Dustin Scheinost, Monica D. Rosenberg, Jessica Huang, Marvin M. Chun, Xenophon Papademetris, and R. Todd Constable. Functional connectome fingerprinting: Identifying individuals using patterns of brain connectivity. *Nature Neuroscience*, 18 (11):1664–1671, November 2015. ISSN 1546-1726. doi: 10.1038/nn.4135. URL https://www.nature.com/articles/nn.4135!

Bruce Fischl. Freesurfer. *NeuroImage*, 62(2):774–781, August 2012. ISSN 1053-8119. doi: 10. 1016/j.neuroimage.2012.01.021. URL https://www.sciencedirect.com/science/ article/pii/S1053811912000389.

Bruce Fischl, David H. Salat, Evelina Busa, Marilyn Albert, Megan Dieterich, Christian Hasel-grove, Andre van der Kouwe, Ron Killiany, David Kennedy, Shuna Klaveness, Albert Montillo, Nikos Makris, Bruce Rosen, and Anders M. Dale. Whole brain segmentation: Automated labeling of neuroanatomical structures in the human brain. *Neuron*, 33(3):341–355, January 2002. ISSN 0896-6273. doi: 10.1016/S0896-6273(02)00569-X. URL https://www.cell.com/ neuron/abstract/S0896-6273(02)00569-X.

Michael D. Fox, Abraham Z. Snyder, Justin L. Vincent, Maurizio Corbetta, David C. Van Essen, and Marcus E. Raichle. The human brain is intrinsically organized into dynamic, anticorrelated functional networks. *Proceedings of the National Academy of Sciences*, 102(27):9673–9678, July 2005. ISSN 0027-8424, 1091-6490. doi: 10.1073/pnas.0504136102. URL https://pnas. org/doi/full/10.1073/pnas.0504136102.

Karl J. Friston, Steven Williams, Robert Howard, Richard S. J. Frackowiak, and Robert Turner. Movement-related effects in fmri time-series. *Magnetic Resonance in Medicine*, 35(3):346–355, 1996. ISSN 1522-2594. doi: 10.1002/mrm.1910350312. URL https://onlinelibrary. wiley.com/doi/abs/10.1002/mrm.1910350312.

Matthew F. Glasser, Stamatios N. Sotiropoulos, J. Anthony Wilson, Timothy S. Coalson, Bruce Fischl, Jesper L. Andersson, Junqian Xu, Saad Jbabdi, Matthew Webster, Jonathan R. Polimeni, David C. Van Essen, and Mark Jenkinson. The minimal preprocessing pipelines for the human connectome project. *NeuroImage*, 80:105–124, October 2013. ISSN 1053-8119. doi: 10. 1016/j.neuroimage.2013.04.127. URL https://www.sciencedirect.com/science/ article/pii/S1053811913005053.

Matthew F. Glasser, Timothy S. Coalson, Emma C. Robinson, Carl D. Hacker, John Harwell, Essa Yacoub, Kamil Ugurbil, Jesper Andersson, Christian F. Beckmann, Mark Jenkinson, Stephen M. Smith, and David C. Van Essen. A multi-modal parcellation of human cerebral cortex. *Nature*, 536(7615):171–178, August 2016. ISSN 0028-0836, 1476-4687. doi: 10.1038/nature18933. URL http://www.nature.com/articles/nature18933.

Gene H. Golub and Charles F. Van Loan. *Matrix Computations*. JHU Press, February 2013. ISBN 978-1-4214-0859-0.

Evan M. Gordon, Timothy O. Laumann, Babatunde Adeyemo, Jeremy F. Huckins, William M. Kelley, and Steven E. Petersen. Generation and evaluation of a cortical area parcellation from resting-state correlations. *Cerebral Cortex*, 26(1):288–303, January 2016. ISSN 1047-3211, 1460-2199. doi: 10.1093/cercor/bhu239. URL https://academic.oup.com/cercor/ article-lookup/doi/10.1093/cercor/bhu239.

Evan M. Gordon, Timothy O. Laumann, Babatunde Adeyemo, and Steven E. Petersen. Individual variability of the system-level organization of the human brain. *Cerebral Cortex*, 27(1):386–399, January 2017a. ISSN 1047-3211. doi: 10.1093/cercor/bhv239. URL https://doi.org/ 10.1093/cercor/bhv239.

Evan M. Gordon, Timothy O. Laumann, Adrian W. Gilmore, Dillan J. Newbold, Deanna J. Greene, Jeffrey J. Berg, Mario Ortega, Catherine Hoyt-Drazen, Caterina Gratton, Haoxin Sun, Jacque-line M. Hampton, Rebecca S. Coalson, Annie L. Nguyen, Kathleen B. McDermott, Joshua S. Shimony, Abraham Z. Snyder, Bradley L. Schlaggar, Steven E. Petersen, Steven M. Nelson, and Nico U.F. Dosenbach. Precision functional mapping of individual human brains. *Neuron*, 95(4), August 2017b. ISSN 08966273. doi: 10.1016/j.neuron.2017.07.011. URL https: //linkinghub.elsevier.com/retrieve/pii/S089662731730613X.

Evan M. Gordon, Timothy O. Laumann, Scott Marek, Ryan V. Raut, Caterina Gratton, Dillan J. Newbold, Deanna J. Greene, Rebecca S. Coalson, Abraham Z. Snyder, Bradley L. Schlaggar, Steven E. Petersen, Nico U. F. Dosenbach, and Steven M. Nelson. Default-mode network streams for coupling to language and control systems. *Proceedings of the National Academy of Sci-ences of the United States of America*, 117(29):17308–17319, July 2020. ISSN 0027-8424. doi:

10.1073/pnas.2005238117. URL https://www.ncbi.nlm.nih.gov/pmc/articles/PMC7382234/.

Stephen J. Gotts, Adrian W. Gilmore, and Alex Martin. Brain networks, dimensionality, and global signal averaging in resting-state fmri: Hierarchical network structure results in low-dimensional spatiotemporal dynamics. *NeuroImage*, 205:116289, January 2020. ISSN 1053-8119. doi: 10.1016/j.neuroimage.2019.116289. URL https://www.ncbi.nlm.nih.gov/pmc/articles/PMC6919311/.

Caterina Gratton, Timothy O. Laumann, Ashley N. Nielsen, Deanna J. Greene, Evan M. Gordon, Adrian W. Gilmore, Steven M. Nelson, Rebecca S. Coalson, Abraham Z. Snyder, Bradley L. Schlaggar, Nico U. F. Dosenbach, and Steven E. Petersen. Functional brain networks are dominated by stable group and individual factors, not cognitive or daily variation. *Neuron*, 98(2):439–452.e5, April 2018. ISSN 0896-6273. doi: 10.1016/j.neuron.2018.03.035. URL https://www.sciencedirect.com/science/article/pii/S0896627318302411.

David S. Grayson and Damien A. Fair. Development of large-scale functional networks from birth to adulthood: A guide to the neuroimaging literature. *NeuroImage*, 160:15–31, October 2017. ISSN 1053-8119. doi: 10.1016/j.neuroimage.2017.01.079. URL https://www.sciencedirect.com/science/article/pii/S1053811917301027.

Liang Han, Neil K Savalia, Micaela Y Chan, Phillip F Agres, Anupama S Nair, and Gagan S Wig. Functional parcellation of the cerebral cortex across the human adult lifespan. *Cerebral Cortex*, 28 (12):4403–4423, December 2018. ISSN 1047-3211. doi: 10.1093/cercor/bhy218. URL https://doi.org/10.1093/cercor/bhy218.

Tong He, Ru Kong, Avram J. Holmes, Mert R. Sabuncu, Simon B. Eickhoff, Danilo Bzdok, Jiashi Feng, and B. T. Thomas Yeo. Is deep learning better than kernel regression for functional connectivity prediction of fluid intelligence? In *2018 International Workshop on Pattern Recognition in Neuroimaging (PRNI)*, pp. 1–4, June 2018. doi: 10.1109/PRNI.2018.8423958. URL https://ieeexplore.ieee.org/document/8423958/?arnumber=8423958.

Irina Higgins, Loic Matthey, Arka Pal, Christopher Burgess, Xavier Glorot, Matthew Botvinick, Shakir Mohamed, and Alexander Lerchner. β-vae: Learning basic visual concepts with a constrained variational framework. In *ICLR*, 2017.

K. Hocke and N. Kämpfer. Gap filling and noise reduction of unevenly sampled data by means of the lomb-scargle periodogram. *Atmospheric Chemistry and Physics*, 9(12):4197–4206, June 2009. ISSN 1680-7316. doi: 10.5194/acp-9-4197-2009. URL https://acp.copernicus.org/articles/9/4197/2009/.

Corey Horien, Stephanie Noble, Abigali S. Greene, Kangjoo Lee, Daniel S. Barron, Siyuan Gao, David O'Connor, Mehraveh Salehi, Javid Dadashkarimi, Xilin Shen, Evelyn M. R. Lake, R. Todd Constable, and Dustin Scheinost. A hitchhiker's guide to working with large, open-source neuroimaging datasets. *Nature human behaviour*, 5(2):185–193, February 2021. ISSN 2397-3374. doi: 10.1038/s41562-020-01005-4. URL https://www.ncbi.nlm.nih.gov/pmc/articles/PMC7992920/.

Brittany R. Howell, Martin A. Styner, Wei Gao, Pew-Thian Yap, Li Wang, Kristine Baluyot, Essa Yacoub, Geng Chen, Taylor Potts, Andrew Salzwedel, Gang Li, John H. Gilmore, Joseph Piven, J. Keith Smith, Dinggang Shen, Kamil Ugurbil, Hongtu Zhu, Weili Lin, and Jed T. Elison. The unc/umn baby connectome project (bcp): An overview of the study design and protocol development. *NeuroImage*, 185:891–905, January 2019. ISSN 1053-8119. doi: 10.1016/j.neuroimage.2018.03.049. URL https://www.sciencedirect.com/science/article/pii/S1053811918302593.

Jung-Hoon Kim, Yizhen Zhang, Kuan Han, Zheyu Wen, Minkyu Choi, and Zhongming Liu. Representation learning of resting state fmri with variational autoencoder. *NeuroImage*, 241:118423, November 2021. ISSN 1053-8119. doi: 10.1016/j.neuroimage.2021.118423. URL https://www.sciencedirect.com/science/article/pii/S1053811921006984.

Jung-Hoon Kim, Josepheen De Asis-Cruz, Dhineshvikram Krishnamurthy, and Catherine Limperopoulos. Toward a more informative representation of the fetal–neonatal brain connectome using variational autoencoder. *eLife*, 12:e80878, May 2023. ISSN 2050-084X. doi: 10.7554/eLife. 80878. URL `https://doi.org/10.7554/eLife.80878`.

Jung-Hoon Kim, Josepheen De Asis-Cruz, and Catherine Limperopoulos. Separating group- and individual-level brain signatures in the newborn functional connectome: A deep learning approach. *NeuroImage*, 299:120806, October 2024. ISSN 1053-8119. doi: 10.1016/j.neuroimage. 2024.120806. URL `https://www.sciencedirect.com/science/article/pii/S1053811924003033`.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Diederik P. Kingma and Max Welling. Auto-encoding variational bayes, December 2022. URL `http://arxiv.org/abs/1312.6114`.

Jack L. Lancaster, Thomas G. Glass, Bhujanga R. Lankipalli, Hunter Downs, Helen Mayberg, and Peter T. Fox. A modality-independent approach to spatial normalization of tomographic images of the human brain. *Human Brain Mapping*, 3(3):209–223, 1995. ISSN 1097-0193. doi: 10.1002/ hbm.460030305. URL `https://onlinelibrary.wiley.com/doi/abs/10.1002/hbm.460030305`.

Georg Langs, Polina Golland, Yanmei Tie, Laura Rigolo, and Alexandra J. Golby. Functional geometry alignment and localization of brain areas. *Advances in neural information processing systems*, 1:1225–1233, 2010. ISSN 1049-5258. URL `https://www.ncbi.nlm.nih.gov/pmc/articles/PMC4010233/`.

Georg Langs, Polina Golland, and Satrajit S. Ghosh. Predicting activation across individuals with resting-state functional connectivity based multi-atlas label fusion. In Nassir Navab, Joachim Hornegger, William M. Wells, and Alejandro Frangi (eds.), *Medical Image Computing and Computer-Assisted Intervention – MICCAI 2015*, pp. 313–320, Cham, 2015. Springer International Publishing. ISBN 978-3-319-24571-3. doi: 10.1007/978-3-319-24571-3_38.

Georg Langs, Danhong Wang, Polina Golland, Sophia Mueller, Ruiqi Pan, Mert R. Sabuncu, Wei Sun, Kuncheng Li, and Hesheng Liu. Identifying shared brain networks in individuals by decoupling functional and anatomical variability. *Cerebral Cortex*, 26(10):4004–4014, October 2016. ISSN 1047-3211. doi: 10.1093/cercor/bhv189. URL `https://doi.org/10.1093/cercor/bhv189`.

Timothy O. Laumann, Evan M. Gordon, Babatunde Adeyemo, Abraham Z. Snyder, Sung Jun Joo, Mei-Yen Chen, Adrian W. Gilmore, Kathleen B. McDermott, Steven M. Nelson, Nico U.F. Dosenbach, Bradley L. Schlaggar, Jeanette A. Mumford, Russell A. Poldrack, and Steven E. Petersen. Functional system and areal organization of a highly sampled individual human brain. *Neuron*, 87(3):657–670, August 2015. ISSN 08966273. doi: 10.1016/j.neuron.2015.06.037. URL `https://linkinghub.elsevier.com/retrieve/pii/S0896627315006005`.

Alireza Makhzani, Jonathon Shlens, Navdeep Jaitly, Ian Goodfellow, and Brendan Frey. Adversarial autoencoders. ICLR, May 2016. doi: 10.48550/arXiv.1511.05644. URL `http://arxiv.org/abs/1511.05644`.

Daniel S. Margulies, Satrajit S. Ghosh, Alexandros Goulas, Marcel Falkiewicz, Julia M. Huntenburg, Georg Langs, Gleb Bezgin, Simon B. Eickhoff, F. Xavier Castellanos, Michael Petrides, Elizabeth Jefferies, and Jonathan Smallwood. Situating the default-mode network along a principal gradient of macroscale cortical organization. *Proceedings of the National Academy of Sciences*, 113(44):12574–12579, November 2016. ISSN 0027-8424, 1091-6490. doi: 10.1073/pnas. 1608282113. URL `https://pnas.org/doi/full/10.1073/pnas.1608282113`.

F. M. Miezin, L. Maccotta, J. M. Ollinger, S. E. Petersen, and R. L. Buckner. Characterizing the hemodynamic response: Effects of presentation rate, sampling procedure, and the possibility of ordering brain activity based on relative timing. *NeuroImage*, 11(6):735–759, June 2000. ISSN 1053-8119. doi: 10.1006/nimg.2000.0568. URL `https://www.sciencedirect.com/science/article/pii/S1053811900905688`.

Anish Mitra, Abraham Z. Snyder, Enzo Tagliazucchi, Helmut Laufs, Jed Elison, Robert W. Emerson, Mark D. Shen, Jason J. Wolff, Kelly N. Botteron, Stephen Dager, Annette M. Estes, Alan Evans, Guido Gerig, Heather C. Hazlett, Sarah J. Paterson, Robert T. Schultz, Martin A. Styner, Lonnie Zwaigenbaum, The IBIS Network, Bradley L. Schlaggar, Joseph Piven, John R. Pruett Jr, and Marcus Raichle. Resting-state fmri in sleeping infants more closely resembles adult sleep than adult wakefulness. *PLOS ONE*, 12(11):e0188122, November 2017. ISSN 1932-6203. doi: 10.1371/journal.pone.0188122. URL `https://journals.plos.org/plosone/article?id=10.1371/journal.pone.0188122`.

Lucille A. Moore, Robert J. M. Hermosillo, Eric Feczko, Julia Moser, Sanju Koirala, Madeleine C. Allen, Claudia Buss, Greg Conan, Anthony C. Juliano, Mollie Marr, Oscar Miranda-Dominguez, Michael Mooney, Michael Myers, Jerod Rasmussen, Cynthia E. Rogers, Christopher D. Smyser, Kathy Snider, Chad Sylvester, Elina Thomas, Damien A. Fair, and Alice M. Graham. Towards personalized precision functional mapping in infancy. *Imaging Neuroscience*, 2:1–20, May 2024. ISSN 2837-6056. doi: 10.1162/imag_a_00165. URL `https://doi.org/10.1162/imag_a_00165`.

Sarah Feldt Muldoon and Danielle S. Bassett. Network and multilayer network approaches to understanding human brain dynamics. *Philosophy of Science*, 83(5):710–720, December 2016. ISSN 0031-8248, 1539-767X. doi: 10.1086/687857. URL `https://www.cambridge.org/core/journals/philosophy-of-science/article/network-and-multilayer-network-approaches-to-understanding-human-brain-dynamics/9F495DE23816D53D4C99BF8840B610E4`.

Michael J Myers, Alyssa K Labonte, Evan M Gordon, Timothy O Laumann, Jiaxin C Tu, Muriah D Wheelock, Ashley N Nielsen, Rebecca F Schwarzlose, M Catalina Camacho, Dimitrios Alexopoulos, Barbara B Warner, Nandini Raghuraman, Joan L Luby, Deanna M Barch, Damien A Fair, Steven E Petersen, Cynthia E Rogers, Christopher D Smyser, and Chad M Sylvester. Functional parcellation of the neonatal cortical surface. *Cerebral Cortex*, 34(2):bhae047, February 2024. ISSN 1460-2199. doi: 10.1093/cercor/bhae047. URL `https://doi.org/10.1093/cercor/bhae047`.

Vinod Nair and Geoffrey E Hinton. Rectified linear units improve restricted boltzmann machines. In *Proceedings of the 27th International Conference on Machine Learning (ICML-10)*, pp. 807–814, 2010.

James C. Pang, Kevin M. Aquino, Marianne Oldehinkel, Peter A. Robinson, Ben D. Fulcher, Michael Breakspear, and Alex Fornito. Geometric constraints on human brain function. *Nature*, 618(7965):566–574, June 2023. ISSN 1476-4687. doi: 10.1038/s41586-023-06098-1. URL `https://www.nature.com/articles/s41586-023-06098-1`.

Jonathan D. Power, Kelly A. Barnes, Abraham Z. Snyder, Bradley L. Schlaggar, and Steven E. Petersen. Spurious but systematic correlations in functional connectivity mri networks arise from subject motion. *NeuroImage*, 59(3):2142–2154, February 2012. ISSN 1053-8119. doi: 10.1016/j.neuroimage.2011.10.018. URL `https://www.sciencedirect.com/science/article/pii/S1053811911011815`.

Jonathan D. Power, Anish Mitra, Timothy O. Laumann, Abraham Z. Snyder, Bradley L. Schlaggar, and Steven E. Petersen. Methods to detect, characterize, and remove motion artifact in resting state fmri. *NeuroImage*, 84:320–341, January 2014. ISSN 1053-8119. doi: 10.1016/j.neuroimage.2013.08.048. URL `https://www.sciencedirect.com/science/article/pii/S1053811913009117`.

Maria Grazia Puxeddu, Joshua Faskowitz, Richard F. Betzel, Manuela Petti, Laura Astolfi, and Olaf Sporns. The modular organization of brain cortical connectivity across the human lifespan. *NeuroImage*, 218:116974, September 2020. ISSN 10538119. doi: 10.1016/j.neuroimage.2020.116974. URL `https://linkinghub.elsevier.com/retrieve/pii/S1053811920304602`.

Ning Qiang, Qinglin Dong, Fangfei Ge, Hongtao Liang, Bao Ge, Shu Zhang, Yifei Sun, Jie Gao, and Tianming Liu. Deep variational autoencoder for mapping functional brain networks. *IEEE Transactions on Cognitive and Developmental Systems*, 13(4):841–852, December 2021. ISSN

2379-8939. doi: 10.1109/TCDS.2020.3025137. URL https://ieeexplore.ieee.org/document/9204760/?arnumber=9204760.

Marcus E. Raichle. The brain's default mode network. *Annual Review of Neuroscience*, 38(1): 433–447, 2015. doi: 10.1146/annurev-neuro-071013-014030. URL https://doi.org/10.1146/annurev-neuro-071013-014030.

David A. Ross, Jongwoo Lim, Ruei-Sung Lin, and Ming-Hsuan Yang. Incremental learning for robust visual tracking. *International Journal of Computer Vision*, 77(1-3):125–141, May 2008. ISSN 0920-5691, 1573-1405. doi: 10.1007/s11263-007-0075-7. URL http://link.springer.com/10.1007/s11263-007-0075-7.

Peter J. Rousseeuw. Silhouettes: A graphical aid to the interpretation and validation of cluster analysis. *Journal of Computational and Applied Mathematics*, 20:53–65, November 1987. ISSN 0377-0427. doi: 10.1016/0377-0427(87)90125-7. URL https://www.sciencedirect.com/science/article/pii/0377042787901257.

Mikail Rubinov and Olaf Sporns. Complex network measures of brain connectivity: Uses and interpretations. *NeuroImage*, 52(3):1059–1069, September 2010. ISSN 10538119. doi: 10.1016/j.neuroimage.2009.10.003. URL https://linkinghub.elsevier.com/retrieve/pii/S105381190901074X.

D. E. Rumelhart, G. E. Hinton, and R. J. Williams. Learning internal representations by error propagation. In *Parallel Distributed Processing: Explorations in the Microstructure of Cognition, Vol. 1: Foundations*, pp. 318–362. MIT Press, Cambridge, MA, USA, January 1986. ISBN 978-0-262-68053-0.

Srikanth Ryali, Yuan Zhang, Carlo De Los Angeles, Kaustubh Supekar, and Vinod Menon. Deep learning models reveal replicable, generalizable, and behaviorally relevant sex differences in human functional brain organization. *Proceedings of the National Academy of Sciences*, 121(9): e2310012121, February 2024. ISSN 0027-8424, 1091-6490. doi: 10.1073/pnas.2310012121. URL https://pnas.org/doi/10.1073/pnas.2310012121.

Alexander Schaefer, Ru Kong, Evan M Gordon, Timothy O Laumann, Xi-Nian Zuo, Avram J Holmes, Simon B Eickhoff, and B T Thomas Yeo. Local-global parcellation of the human cerebral cortex from intrinsic functional connectivity mri. *Cerebral Cortex (New York, NY)*, 28(9):3095–3114, September 2018. ISSN 1047-3211. doi: 10.1093/cercor/bhx179. URL https://www.ncbi.nlm.nih.gov/pmc/articles/PMC6095216/.

Benjamin A. Seitzman, Caterina Gratton, Scott Marek, Ryan V. Raut, Nico U.F. Dosenbach, Bradley L. Schlaggar, Steven E. Petersen, and Deanna J. Greene. A set of functionally-defined brain regions with improved representation of the subcortex and cerebellum. *NeuroImage*, 206: 116290, February 2020. ISSN 10538119. doi: 10.1016/j.neuroimage.2019.116290. URL https://linkinghub.elsevier.com/retrieve/pii/S105381191930881X.

X. Shen, F. Tokoglu, X. Papademetris, and R. T. Constable. Groupwise whole-brain parcellation from resting-state fmri data for network node identification. *NeuroImage*, 82:403–415, November 2013. ISSN 1053-8119. doi: 10.1016/j.neuroimage.2013.05.081. URL https://www.sciencedirect.com/science/article/pii/S1053811913005818.

Maxwell Shinn, Amber Hu, Laurel Turner, Stephanie Noble, Katrin H. Preller, Jie Lisa Ji, Flora Moujaes, Sophie Achard, Dustin Scheinost, R. Todd Constable, John H. Krystal, Franz X. Vollenweider, Daeyeol Lee, Alan Anticevic, Edward T. Bullmore, and John D. Murray. Functional brain networks reflect spatial and temporal autocorrelation. *Nature Neuroscience*, 26(5): 867–878, May 2023. ISSN 1546-1726. doi: 10.1038/s41593-023-01299-3. URL https://www.nature.com/articles/s41593-023-01299-3.

Joshua S. Siegel, Anish Mitra, Timothy O. Laumann, Benjamin A. Seitzman, Marcus Raichle, Maurizio Corbetta, and Abraham Z. Snyder. Data quality influences observed links between functional connectivity and behavior. *Cerebral Cortex*, 27(9):4492–4502, September 2017. ISSN 1047-3211. doi: 10.1093/cercor/bhw253. URL https://doi.org/10.1093/cercor/bhw253.

Stephen M. Smith, Mark Jenkinson, Mark W. Woolrich, Christian F. Beckmann, Timothy E. J. Behrens, Heidi Johansen-Berg, Peter R. Bannister, Marilena De Luca, Ivana Drobnjak, David E. Flitney, Rami K. Niazy, James Saunders, John Vickers, Yongyue Zhang, Nicola De Stefano, J. Michael Brady, and Paul M. Matthews. Advances in functional and structural mr image analysis and implementation as fsl. *NeuroImage*, 23:S208–S219, January 2004. ISSN 1053-8119. doi: 10.1016/j.neuroimage.2004.07.051. URL https://www.sciencedirect.com/science/article/pii/S1053811904003933.

Abraham Z. Snyder, Tomoyuki Nishino, Joshua S. Shimony, Eric J. Lenze, Julie Loebach Wetherell, Michelle Voegtle, J. Philip Miller, Michael D. Yingling, Daniel Marcus, Jenny Gurney, Jerrel Rutlin, Drew Scott, Lisa Eyler, and Deanna Barch. Covariance and correlation analysis of resting state functional magnetic resonance imaging data acquired in a clinical trial of mindfulness-based stress reduction and exercise in older individuals. *Frontiers in Neuroscience*, 16:825547, March 2022. ISSN 1662-453X. doi: 10.3389/fnins.2022.825547. URL https://www.frontiersin.org/articles/10.3389/fnins.2022.825547/full.

Olaf Sporns, Dante R. Chialvo, Marcus Kaiser, and Claus C. Hilgetag. Organization, development and function of complex brain networks. *Trends in Cognitive Sciences*, 8(9):418–425, September 2004. ISSN 1364-6613. doi: 10.1016/j.tics.2004.07.008. URL https://www.sciencedirect.com/science/article/pii/S1364661304001901.

Lianglong Sun, Tengda Zhao, Xinyuan Liang, Mingrui Xia, Qiongling Li, Xuhong Liao, Gaolang Gong, Qian Wang, Chenxuan Pang, Qian Yu, Yanchao Bi, Pindong Chen, Rui Chen, Yuan Chen, Taolin Chen, Jingliang Cheng, Yuqi Cheng, Zaixu Cui, Zhengjia Dai, Yao Deng, Yuyin Ding, Qi Dong, Dingna Duan, Jia-Hong Gao, Qiyong Gong, Ying Han, Zaizhu Han, Chu-Chung Huang, Ruiwang Huang, Ran Huo, Lingjiang Li, Ching-Po Lin, Qixiang Lin, Bangshan Liu, Chao Liu, Ningyu Liu, Ying Liu, Yong Liu, Jing Lu, Leilei Ma, Weiwei Men, Shaozheng Qin, Jiang Qiu, Shijun Qiu, Tianmei Si, Shuping Tan, Yanqing Tang, Sha Tao, Dawei Wang, Fei Wang, Jiali Wang, Pan Wang, Xiaoqin Wang, Yanpei Wang, Dongtao Wei, Yankun Wu, Peng Xie, Xiufeng Xu, Yuehua Xu, Zhilei Xu, Liyuan Yang, Huishu Yuan, Zilong Zeng, Haibo Zhang, Xi Zhang, Gai Zhao, Yanting Zheng, Suyu Zhong, Cam-CAN Alzheimer's Disease Neuroimaging Initiative, and Yong He. Functional connectome through the human life span, September 2023. URL https://www.biorxiv.org/content/10.1101/2023.09.12.557193v2.

Valerie J. Sydnor, Bart Larsen, Danielle S. Bassett, Aaron Alexander-Bloch, Damien A. Fair, Conor Liston, Allyson P. Mackey, Michael P. Milham, Adam Pines, David R. Roalf, Jakob Seidlitz, Ting Xu, Armin Raznahan, and Theodore D. Satterthwaite. Neurodevelopment of the association cortices: Patterns, mechanisms, and implications for psychopathology. *Neuron*, 109(18):2820–2846, September 2021. ISSN 0896-6273. doi: 10.1016/j.neuron.2021.06.016. URL https://www.sciencedirect.com/science/article/pii/S0896627321004578.

Enzo Tagliazucchi, Frederic von Wegner, Astrid Morzelewski, Verena Brodbeck, Kolja Jahnke, and Helmut Laufs. Breakdown of long-range temporal dependence in default mode and attention networks during deep sleep. *Proceedings of the National Academy of Sciences*, 110(38):15419–15424, September 2013. ISSN 0027-8424, 1091-6490. doi: 10.1073/pnas.1312848110. URL https://pnas.org/doi/full/10.1073/pnas.1312848110.

PT Jean Talairach. Co-planar stereotaxic atlas of the human brain. *(No Title)*, 1988.

Sebastian Urchs, Jonathan Armoza, Clara Moreau, Yassine Benhajali, Jolène St-Aubin, Pierre Orban, and Pierre Bellec. Mist: A multi-resolution parcellation of functional brain networks. *MNI Open Research*, 1:3, 2019. ISSN 2515-5059.

D. C. Van Essen, M. F. Glasser, D. L. Dierker, J. Harwell, and T. Coalson. Parcellations and hemispheric asymmetries of human cerebral cortex analyzed on surface-based atlases. *Cerebral Cortex*, 22(10):2241–2262, October 2012a. ISSN 1047-3211, 1460-2199. doi: 10.1093/cercor/bhr291. URL https://academic.oup.com/cercor/article-lookup/doi/10.1093/cercor/bhr291.

D. C. Van Essen, K. Ugurbil, E. Auerbach, D. Barch, T. E. J. Behrens, R. Bucholz, A. Chang, L. Chen, M. Corbetta, S. W. Curtiss, S. Della Penna, D. Feinberg, M. F. Glasser, N. Harel, A. C. Heath, L. Larson-Prior, D. Marcus, G. Michalareas, S. Moeller, R. Oostenveld, S. E.

Petersen, F. Prior, B. L. Schlaggar, S. M. Smith, A. Z. Snyder, J. Xu, and E. Yacoub. The human connectome project: A data acquisition perspective. *NeuroImage*, 62(4):2222–2231, October 2012b. ISSN 1053-8119. doi: 10.1016/j.neuroimage.2012.02.018. URL https://www.sciencedirect.com/science/article/pii/S1053811912001954.

David C. Van Essen, Heather A. Drury, James Dickson, John Harwell, Donna Hanlon, and Charles H. Anderson. An integrated software suite for surface-based analyses of cerebral cortex. *Journal of the American Medical Informatics Association*, 8(5):443–459, September 2001. ISSN 1067-5027. doi: 10.1136/jamia.2001.0080443. URL https://doi.org/10.1136/jamia.2001.0080443.

Reinder Vos de Wael, Oualid Benkarim, Casey Paquola, Sara Lariviere, Jessica Royer, Shahin Tavakol, Ting Xu, Seok-Jun Hong, Georg Langs, Sofie Valk, Bratislav Misic, Michael Milham, Daniel Margulies, Jonathan Smallwood, and Boris C. Bernhardt. Brainspace: A toolbox for the analysis of macroscale gradients in neuroimaging and connectomics datasets. *Communications Biology*, 3(1):1–10, March 2020. ISSN 2399-3642. doi: 10.1038/s42003-020-0794-7. URL https://www.nature.com/articles/s42003-020-0794-7.

Gagan S. Wig. Segregated systems of human brain networks. *Trends in Cognitive Sciences*, 21(12): 981–996, December 2017. ISSN 1364-6613. doi: 10.1016/j.tics.2017.09.006. URL https://www.sciencedirect.com/science/article/pii/S1364661317301948.

Yunman Xia, Mingrui Xia, Jin Liu, Xuhong Liao, Tianyuan Lei, Xinyu Liang, Tengda Zhao, Ziyi Shi, Lianglong Sun, Xiaodan Chen, Weiwei Men, Yanpei Wang, Zhiying Pan, Jie Luo, Siya Peng, Menglu Chen, Lei Hao, Shuping Tan, Jia-Hong Gao, Shaozheng Qin, Gaolang Gong, Sha Tao, Qi Dong, and Yong He. Development of functional connectome gradients during childhood and adolescence. *Science Bulletin*, 67(10):1049–1061, May 2022. ISSN 2095-9273. doi: 10.1016/j.scib.2022.01.002. URL https://www.sciencedirect.com/science/article/pii/S2095927322000020.

B T Thomas Yeo, Fenna M. Krienen, Jorge Sepulcre, Mert R. Sabuncu, Danial Lashkari, Marisa Hollinshead, Joshua L. Roffman, Jordan W. Smoller, Lilla Zöllei, Jonathan R. Polimeni, Bruce Fischl, Hesheng Liu, and Randy L. Buckner. The organization of the human cerebral cortex estimated by intrinsic functional connectivity. *Journal of Neurophysiology*, 106(3):1125–1165, September 2011. ISSN 0022-3077, 1522-1598. doi: 10.1152/jn.00338.2011. URL https://www.physiology.org/doi/10.1152/jn.00338.2011.

Alibek Zhakubayev and Greg Hamerly. Clustering faster and better with projected data. In *Proceedings of the 6th International Conference on Information System and Data Mining*, pp. 1–6, 2022.

Lu Zhang, Li Wang, and Dajiang Zhu. Recovering brain structural connectivity from functional connectivity via multi-gcn based generative adversarial network. In Anne L. Martel, Purang Abolmaesumi, Danail Stoyanov, Diana Mateus, Maria A. Zuluaga, S. Kevin Zhou, Daniel Racoceanu, and Leo Joskowicz (eds.), *Medical Image Computing and Computer Assisted Intervention – MICCAI 2020*, pp. 53–61, Cham, 2020. Springer International Publishing. ISBN 978-3-030-59728-3. doi: 10.1007/978-3-030-59728-3_6.

Jianlong Zhao, Jinjie Huang, Dongmei Zhi, Weizheng Yan, Xiaohong Ma, Xiao Yang, Xianbin Li, Qing Ke, Tianzi Jiang, Vince D. Calhoun, and Jing Sui. Functional network connectivity (fnc)-based generative adversarial network (gan) and its applications in classification of mental disorders. *Journal of Neuroscience Methods*, 341:108756, July 2020. ISSN 0165-0270. doi: 10.1016/j.jneumeth.2020.108756. URL https://www.sciencedirect.com/science/article/pii/S0165027020301795.

Qiankun Zuo, Junhua Hu, Yudong Zhang, Junren Pan, Changhong Jing, Xuhang Chen, Xiaobo Meng, and Jin Hong. Brain functional network generation using distribution-regularized adversarial graph autoencoder with transformer for dementia diagnosis. *Computer modeling in engineering & sciences : CMES*, 137(3):2129, August 2023. doi: 10.32604/cmes.2023.028732. URL https://pmc.ncbi.nlm.nih.gov/articles/PMC7615791/.

N (number of nodes)	L (number of layers)	Time in seconds to run 100 repetitions
200	5	8.3
200	50	120
200	500	3265
333	5	17
333	50	380
333	500	6694

Table 1: Computational time monitoring for multilayer modularity maximization

A APPENDIX

A.1 COMMUNITY DETECTION IN A SHARED LATENT SPACE HELPS ESTABLISH CORRESPONDENCE

One key pursuit of system neuroscience is to group the nodes in functional connectomes into functional networks or communities across states, individuals, and the lifespan (Betzel et al., 2014; Grayson & Fair, 2017; Mitra et al., 2017; Puxeddu et al., 2020; Tagliazucchi et al., 2013; Wig, 2017). A key hurdle for examining those communities is the establishment of correspondence across the different connectomes. Prior work has attempted this by detecting communities in individual connectomes and then matching the degree of overlap in their topography either through visualization (Gordon et al., 2017b) or using a Hungarian matching algorithm to minimize the Hamming distance (Langs et al., 2016). Alternatively, a multilayer network can be constructed by linking multiple functional connectomes as layers (Bassett et al., 2011; Betzel et al., 2019; Puxeddu et al., 2020), where community detection methods were then applied. Both approaches could not be applied to functional connectomes with different nodal definitions optimized for individuals (Gordon et al., 2017b; Laumann et al., 2015) or populations (Han et al., 2018; Myers et al., 2024).

A.2 COMMUNITY DETECTION IN A REDUCED DIMENSION IMPROVES COMPUTATIONAL EFFICIENCY

The idea of improving computational efficiency on clustering by first performing dimensionality reduction rather than using the original high-dimension data has proven effective in other domains(Zhakubayev & Hamerly, 2022). While the number of nodes (100-1000) and edges (4950-499500) might not seem big for an individual functional connectivity matrix, the total data space can become large when considering all individuals (e.g., for UK Biobank it would be 40000+ (Horien et al. 2021)), longitudinal sessions, different data modality, and time windows within a session (de Domenico, 2017; Muldoon & Bassett, 2016; Betzel et al., 2019). In addition, recently people combine across multiple datasets for life span studies (Sun et al., 2023) which can increase the sample size further.

The theoretical time complexity of the Louvain algorithm in single-layer modularity maximization is O(n(log(n))) where n is the number of nodes. We can approximately calculate the time complexity of the Louvain algorithm in multi-layer modularity maximization to be O(N*L(log(N*L))) where N is the number of nodes per layer and L is the number of layers. Here, we present one computational time monitoring for community detection with a multilayer network using the MATLAB code provided by (Betzel et al., 2019). For each repetition, we randomly draw hyperparameters ω and γ which control the strength of interlayer coupling and resolution scale, respectively. The experiments were conducted on a server equipped with two AMD EPYC 7713 64-core Processors, providing 128 cores and 256 threads, with a base clock speed of 2.56 GHz. We saw that our empirical results matched the theoretical expectations (Table 1).

A.3 NEUROIMAGING DATA ACQUISITION AND PROCESSING DETAILS

A.3.1 WASHINGTON UNIVERSITY 120 (WU120) DATA

In summary, data was obtained from 120 healthy young adults (60 females, average age = 25 years, age range = 19–32 years). Participants were right-handed, native English speakers recruited from the Washington University community. Screening via self-report questionnaire ensured no history of neurological or psychiatric diagnosis, nor head injuries resulting in more than 5 minutes of unconsciousness. All participants provided informed consent, and the study was approved by the Wash-

ington University School of Medicine Human Studies Committee and Institutional Review Board. Data is available at https://openneuro.org/datasets/ds000243/versions/00001/file-display/00001

Structural and functional MRI data were obtained with a Siemens MAGNETOM Trio Tim 3.0-T Scanner and a Siemens 12-channel Head Matrix Coil. Structural imaging included a T1-weighted sagittal magnetization-prepared rapid acquisition gradient-echo (MP-RAGE) structural image was obtained [time echo (TE) = 3.08 ms, time repetition, TR (partition) = 2.4 s, time to inversion (TI) = 1000 ms, flip angle = 8°, 176 slices with $1 \times 1 \times 1$ mm voxels]. Functional scan slices were aligned parallel to the anterior commissure–posterior commissure plane of the MP-RAGE and centered on the brain using an auto-align pulse sequence protocol available in Siemens software. This alignment corresponds to the Talairach atlas(Talairach, 1988).

For the functional MRI data acquisition, subjects were instructed to relax while maintaining fixation on a black crosshair against a white background. Functional imaging used a BOLD contrast-sensitive gradient-echo echo-planar imaging (EPI) sequence (TE = 27 ms, flip angle = 90°, in-plane resolution = 4×4 mm). Full-brain EPI volumes (MR frames) of 32 contiguous, 4-mm-thick axial slices were obtained every 2.5 seconds. Additionally, a T2-weighted turbo spin-echo structural image (TE = 84 ms, TR = 6.8 s, 32 slices with $1 \times 1 \times 4$ mm voxels) in the same anatomical planes as the BOLD images was also captured to augment atlas alignment. The fMRI acquisition used Anterior→Posterior (AP) phase encoding. The number of volumes collected per subject ranged from 184 to 724, with an average of 336 frames (14.0 min).

Functional images were first processed to reduce artifacts including (1) correction of odd versus even slice intensity differences due to interleaved acquisition without gaps, (2) head movement correction within and across runs, and (3) across-run intensity normalization to a whole-brain mode value of 1000. Each individual's functional data was transformed into an atlas space using the MP-RAGE scan and resampled to an isotropic 3-mm atlas space(Talairach, 1988), using a single cubic spline interpolation(Lancaster et al., 1995).

Additional preprocessing mitigated high-motion frame effects in two iterations. The first iteration included: (1) demeaning and detrending, (2) multiple regression including whole-brain, ventricular cerebrospinal fluid (CSF), and white matter signals, and motion regressors derived by Volterra expansion and (3) a band-pass filter ($0.009Hz < f < 0.08Hz$). Temporal masks were created in this iteration to flag motion-contaminated frames, identified using framewise displacement (FD), calculated as the squared sum of the motion vectors (Power et al., 2012). Volumes exceeding FD > 0.2 mm and segments of fewer than 5 contiguous volumes were flagged for removal.

The data were then reprocessed in a second iteration, incorporating the temporal masks described above. This reprocessing was identical to the initial processing stream but ignored censored data. Data were interpolated across censored frames using least squares spectral estimation (Power et al., 2014) of the values at censored frames so that continuous data could be passed through the band-pass filter ($0.009Hz < f < 0.08Hz$) without contaminating frames near high motion frames. Censored frames were ultimately ignored during functional connectivity matrix generation.

Individual surfaces were generated from the structural images and functional data were sampled to surface space (Glasser et al., 2013). Following volumetric registration, left and right hemisphere anatomical surfaces were created from each subject's MP-RAGE image using FreeSurfer's recon-all processing pipeline (v5.0)(Fischl, 2012). This involved brain extraction, segmentation, white matter and pial surface generation, surface inflation to a sphere, and spherical registration of the subject's "native" surface to the fsaverage surface. The fsaverage-registered surfaces were then aligned and resampled to a resolution of 164000 vertices using Caret tools (Van Essen et al., 2001) and down-sampled to a 32492 vertex surface (32k-fsLR). Functional BOLD volumes were sampled to each subject's individual "native" midthickness surface (generated as the average of the white and pial surfaces) using the ribbon-constrained sampling procedure available in Connectome Workbench (v0.84) and then deformed and resampled from the individual's "native" surface to the 32k-fsLR surface. The final time series were smoothed along the 32k-fsLR surface using a Gaussian smoothing kernel ($\sigma = 2.55$ mm).

A.3.2 HUMAN CONNECTOME PROJECT (HCP) DATA

Data for the Human Connectome Project (Young Adult) was collected at Washington University in St. Louis and the University of Minnesota. The participants, healthy adults aged between

22 to 35 years, underwent high-resolution T1-weighted (MP-RAGE, TR = 2.4s, voxel size = 0.7×0.7×0.7mm) and BOLD contrast-sensitive imaging (gradient echo EPI, multiband factor 8, TR = 0.72s, voxels = 2×2×2mm) using a custom Siemens SKYRA 3.0T MRI scanner equipped with a custom 32-channel Head Matrix Coil. Sequences with both left-to-right (LR) and right-to-left (RL) phase encoding were employed, with each participant completing a single run in each direction over two consecutive days, resulting in four runs in total, two for Rest 1 and another two for Rest 2. Data is available at https://www.humanconnectome.org/study/hcp-young-adult/document/1200-subjects-data-release

Previous research has indicated that minimally pre-processed data does not sufficiently control for confounds such as subject head motion (Burgess et al., 2016). In addition, reliable associations between functional connectivity and behavior require sufficient low-motion functional connectivity data for each subject Gordon et al. (2017b); Laumann et al. (2015). A similar preprocessing method as before was implemented (Seitzman et al., 2020). First, to account for magnetization equilibrium and any responses evoked by the scan start (Laumann et al., 2015), the first 29.52 seconds or – 41 frames – of each resting-state run were discarded. Then, the functional data were aligned to the first frame of the first run using rigid body transforms, motion corrected (3D-cross realigned), and whole-brain mode 1000 normalized (Miezin et al., 2000). The data, with 2x2x2mm voxels, was then registered to the T1-weighted image and a WashU MNI atlas using affine and FSL transformations (Smith et al., 2004).

Further preprocessing of the resting-state BOLD data was applied to remove artifacts (Ciric et al., 2017; Power et al., 2014). This involved calculating frame-wise displacement (FD) to quantify motion between consecutive frames in fMRI data (Power et al., 2012) and artifact removal using a low-pass filter at 0.1 Hz to address respiration artifacts affecting the FD estimates (Fair, 2020; Siegel et al., 2017), along with a threshold for removing frames with FD greater than 0.04 mm after the low-pass filter (N.B. for section A.6, no frame removal was applied because this leaves different numbers of valid frames for each subject). For functional connectivity (FC) analysis preparation, regression of nuisance variables was performed, including 36 regressors: (1) 3 time series (whole-brain mean, mean ventricular CSF, mean white matter) with temporal derivatives from the Volterra expansion (12 total parameters)(Friston et al., 1996), and (2) 6 head motion parameters with temporal derivatives from the Volterra expansion (24 total parameters). Spatial masks of the gray matter, white matter, and ventricles were created from the T1-weighted images for each of the individual-specific regressors using Freesurfer 5.3 automatic segmentation (Fischl et al., 2002). Data segments shorter than 5 contiguous frames were excluded, and least squares spectral estimation was used for interpolation over the censored frames (Hocke & Kämpfer, 2009; Power et al., 2014). The final data were then bandpass filtered from 0.009 to 0.08 Hz, and censored frames were excluded from the time series (Seitzman et al., 2020). It is crucial to perform censoring and interpolation before filtering to prevent high-motion noise artifacts from smearing into adjacent frames.

Following that, the preprocessed BOLD time series data underwent surface processing, which involved using the ribbon-constrained sampling procedure in Connectome Workbench to sample the BOLD volumes to each subject's native surface and exclude voxels with a time series coefficient with a variation of 0.5 SDs above that of the mean of nearby voxels (Glasser et al., 2013). After being sampled to the surface, time courses were deformed, resampled, and smoothed with a Gaussian smoothing kernel (FWHM = 4mm, σ = 1.7). Connectome Workbench was then used to combine these surfaces with volumetric subcortical and cerebellar data into the CIFTI format, generating full-brain time courses while excluding non-gray matter tissue (Glasser et al., 2013).

A.4   GEOMETRIC REFORMATTING INTO 2-D IMAGES

The geometric reformatting procedure was done in four steps. First, the seed maps were mapped to the cortical surface using their coordinates in the 32k-fsLR mesh of the left and right hemispheres (32492 vertices per hemisphere with some of them empty due to the presence of the medial wall). Then, the surfaces in each hemisphere were inflated to a sphere using FreeSurfer (Fischl, 2012). After that, we used cart2sph.m in MATLAB to convert its Cartesian coordinates (x,y,z) to spherical coordinates (a,e), which reported the azimuth and elevation angles in a range from $-\pi$ to $+\pi$ and from $-\pi/2$ to $+\pi/2$, respectively. Lastly, we defined a 192 × 192 grid to resample the spherical surface with respect to azimuth and sin(elevation) such that the resampled locations were uniformly distributed at approximation.

Figure 7: **Network architecture.** A) Variational autoencoder. B) Autoencoder. C) Adversarial autoencoder. *Adapted with permission from Kim, J., Zhang, Y., Han, K., Wen, Z., Choi, M., & Liu, Z. (2021). Representation learning of resting state fMRI with variational autoencoder. NeuroImage, 241, 118423. Copyright 2021 by Elsevier Inc. and Makhzani, A., Shlens, J., Jaitly, N., Goodfellow, I., Frey, B., ICLR 2016. Adversarial Autoencoders.*

A.5 AUTOENCODER NETWORK ARCHITECTURE

In the encoder network, the size of the output image of each convolutional layer (from left to right) is 96x96x64 (32 channels per hemisphere), 48x48x128, 24x24x128, 12x12x256, and 6x6x256; for the decoder network, 6x6x256, 12x12x256, 24x24x128, 48x48x128, and 96x96x64 (32 channels per image), from left to right. The convolution operations are defined as 1: convolution (kernel size=8, stride=2, padding=3) with rectified nonlinearity, 2-5: convolution (kernel size=4, stride=2, padding=1) with rectified nonlinearity, 6: fully-connected layer with re-parametrization, 7: fully-connected layer with rectified nonlinearity, 8-11: transposed convolution (kernel size=4, stride=2, padding=1) with rectified nonlinearity, 12: transposed convolution (kernel size=8, stride=2, padding=3). The code implementation was adapted from https://github.com/libilab/rsfMRI-VAE/.

The adversarial network had a separate discriminator component and the adversarial loss was combined with reconstruction loss for regularization of the latent space(Makhzani et al., 2016). The code implementation was adapted from https://github.com/eriklindernoren/PyTorch-GAN/blob/master/implementations/aae/aae.py.

A.6 DETERMINATION OF HYPERPARAMETERS

A.6.1 NUMBER OF LATENT DIMENSIONS

While it is desirable to have the lowest dimension possible for best computational efficiency, a dimension that is too small might not capture all crucial structures in the original data. Based on prior literature, we believed that a dimension greater than 40 would provide little additional information (Gotts et al., 2020; Margulies et al., 2016). We validated this in our data by evaluating the reconstruction loss and KL divergence in models with a range of dimensions (2, 4, 8, 16, 32, 64, 96, 128, 256) at $\beta = 1$ on the validation data (Figure 8A). We found that 32 dimensions were close to the elbow of the tradeoff between reconstruction performance and KL divergence, so we only

Figure 8: **Hyperparameter tuning.** A) Reconstruction loss and Kullback-Leibler divergence for different numbers of latent dimensions in the validation data. B) Reconstruction loss and Kullback-Leibler divergence for different β values in the validation data.

tested models with latent dimensions 2, 4, and 32, with the reasoning that a latent dimensionality beyond 32 is likely to provide little improvement in reducing the reconstruction loss but would keep increasing the KL divergence. The same metric for dimensions = 2,4,8,16,32 in $\beta = 20$ was plotted as a comparison. We applied the same latent dimensions to the PCA and ICA approaches.

A.6.2 VAE BETA

As above, we explored a range of beta values from X to Y and found that $\beta = 20$ provided a good balance between reconstruction performance and KL divergence on the validation data (Figure 8B).

A.7 MODEL VARIABILITY

One limitation is that the performance of the models could be biased by the samples selected to train the model. Here, we demonstrate the model variability with an example VAE at $\beta = 20$ with 5-fold cross-validation in the training data. The 100 subjects were divided into 20-subject groups. For each fold, we picked 4 groups to train the model and test on the same 10 subjects outside the 100 subjects as described in section A.3.1. We can see that the models achieved very similar performance on the training data, but had a larger variability in how well it generalize to an unseen validation set.

Figure 9: **5-fold cross-validation.** A)Reconstruction loss against KL-divergence for training data. B)Reconstruction loss against KL-divergence for test data. C-D) Same as A-B for validation data.

A.8 PSEUDO-CODE FOR ANALYSIS PIPELINE USING THE CONNECTOME LATENT REPRESENTATIONS

```
FOR each data session IN all_subjects:
    FOR each parcel i:
        // Compute the seed map for the parcel
        ParcelSeedMap = correlation(ParcelTimeSeries(:, i),
VertexTimeSeries(:, i))
        // Encode the seed map to obtain latent representation
        ParcelSeedMapLatents = Encoder(ParcelSeedMap)
        // Concatenate the latent representations across all parcels
        Append ParcelSeedMapLatents TO ParcelSeedMapAllLatents
    END FOR
    // Save the concatenated latent representations for
clustering/prediction
    SAVE ParcelSeedMapAllLatents
END FOR
```

A.9 RECONSTRUCTION PERFORMANCE NORMALIZED TO THE NOISE CEILING

Since there is some variability in noise ceilings (a.k.a. the η^2 between the two resting scan sessions for the same subject), we additionally plot the normalized reconstruction performance calculated by dividing the actual reconstruction performance (η^2) by the noise ceiling for each subject in the HCP dataset.

Figure 10: **Reconstruction performance in the HCP data.** A-C) The reconstruction performance for all subjects. Reconstruction Green line: HCP Rest1, Red line: HCP Rest2. Gray shaded area: mean and standard deviation of the noise ceiling and the null baseline. N.B.: 333 parcels always have 333 dimensions and were repeatedly displayed in all three panels as a reference. VAE = variational autoencoder. AAE = adversarial autoencoder. PCA = principal component analysis. ICA = independent component analysis. AE = autoencoder.

A.10 SEPARATION BY CANONICAL FUNCTIONAL NETWORKS

We found that the average SI of the 333 parcel connectome is 0.158 (95% CI: [0.145, 0.163], Figure 11). Also, the average SI was higher in dim = 4 and dim = 32 than in dim = 2 (Table 2).

Figure 11: **Separation of networks A) Mean distance between area parcels in the latent embeddings with the 333 parcels (dimension = 333). B) Mean $\pm$ standard error SI for each functional network with the 333 parcels. C-H) Same as B but for the dimension = 2 across dimensionality reduction methods as shown in Figure 4.**

A.11   PROPERTIES OF DEFAULT SUB-CLUSTERS IN VAE LATENT SPACE (DIM = 2)

We applied a k-means clustering algorithm on the connectome latent representations from all default network parcels from the Rest1 session in all HCP 94 subjects in the 2-D VAE latent space (Figure 12A-B). The resultant cluster contains data from similar parcels across the subjects (Figure 12C) with some variability across subjects (Figure 10D). Cluster 1 seems to contain mostly parcels in the medial prefrontal cortex, the temporal cortex and the dorsolateral prefrontal cortex, while cluster 2

Mean SI	VAE ($\beta = 20$)	VAE ($\beta = 1$)	AAE	AAE	PCA	ICA
dim = 2	0.086 [0.066, 0.099]	0.044 [0.015, 0.063]	0.035 [0.006, 0.054]	0.014 [-0.018, 0.030]	7×10^{-4} [-0.016, 0.009]	-0.010 [-0.028, 0.001]
dim = 4	**0.213** [0.197, 0.221]	0.193 [0.176, 0.200]	0.111 [0.085, 0.013]	0.177 [0.158, 0.184]	0.173 [0.155, 0.181]	0.173 [0.156, 0.182]
dim = 32	0.171 [0.158, 0.175]	0.191 [0.177, 0.194]	0.152 [0.136, 0.152]	0.117 [0.094, 0.120]	0.178 [0.164, 0.183]	0.114 [0.104, 0.118]

Table 2: **Silhouette index for different dimensionality reduction methods for the Gordon network clusters.**"dim" stands for dimensions.

seems to contain mostly parcels from the inferior parietal cortex and the posterior cingulate cortex (Figure 12E). Subtle differences can be seen in the reconstructed seed maps from the centroids of the two clusters (Figure 12F). While the distribution of cluster 1 resembles the ventromedial and pregenual components of the default network, and the distribution of cluster 2 resembles the dorsolateral and parietal components of the default network as identified in an earlier study (Gordon et al., 2020), the biological and functional relevance of the two clusters identified here requires further investigation. However, the key takeaway of this analysis is that this eluded the possibility of identifying different subcomponents or individual/developmental-specific variants of existing functional connectivity networks using clustering of parcel connectome latent representations across subjects.

Figure 12: **Separation of DMN into subclusters.** A) DMN parcels across all subjects. B) Clustering the data in A into two sub-clusters with the k-means algorithm. C) The sub-cluster membership across parcels and subjects. D) The sub-cluster membership in two example subjects. E) The relative frequency of cluster membership across subjects (darker = more subjects) for the two sub-clusters. F) The reconstructed seed maps from the centroids of the two sub-clusters.

A.12 K-MEANS CLUSTERING OF ALL PARCEL SEED MAPS IN THE LATENT SPACE

We illustrated the initial and final results of the optimization of cluster separation of the 12 functional networks using k-means clustering in Figure 13. Here we only show the Rest1 sessions of the 94 HCP subjects for visualization purposes, but the k-means algorithm was run on data from both Rest1 and Rest2 sessions. The k-means algorithm minimizes the squared distance between all the points to their closest cluster center by changing the cluster membership of the data points. More details can be seen in Table 3 and Figure 14-21.

Figure 13: **k-means clustering in the latent space (2 dimensions).** (Left) Data from Rest1 in HCP 94 subjects with the original labels (dots) and centroid (triangle). (Right) Data from Rest1 in HCP 94 subjects with the optimized label after k-means clustering with 12 clusters.

Intrasubject variability	dim = 2	dim = 4	dim = 32
VAE (β = 20)	0.39 ± 0.07	0.31 ± 0.07	0.29 ± 0.08
VAE (β = 1)	0.41 ± 0.08	0.40 ± 0.08	0.35 ± 0.08
AAE	0.40 ± 0.08	0.48 ± 0.18	0.45 ± 0.10
AE	0.39 ± 0.08	0.40 ± 0.09	0.54 ± 0.10
PCA	0.47 ± 0.11	0.38 ± 0.10	0.34 ± 0.09
ICA	0.48 ± 0.10	0.36 ± 0.09	0.27 ± 0.05
333 parcels		0.33 ± 0.08	
Intersubject variability	dim = 2	dim = 4	dim = 32
VAE (β = 20)	0.60 ± 0.03	0.51 ± 0.03	0.48 ± 0.03
VAE (β = 1)	0.62 ± 0.03	0.60 ± 0.03	0.58 ± 0.03
AAE	0.60 ± 0.03	0.63 ± 0.07	0.69 ± 0.03
AE	0.57 ± 0.04	0.60 ± 0.04	0.74 ± 0.02
PCA	0.70 ± 0.02	0.61 ± 0.03	0.57 ± 0.03
ICA	0.70 ± 0.02	0.58 ± 0.03	0.47 ± 0.05
333 parcels		0.55 ± 0.03	
vSNR	dim = 2	dim = 4	dim = 32
VAE (β = 20)	0.61 ± 0.29	0.74 ± 0.38	$\mathbf{0.81 \pm 0.50}$
VAE (β = 1)	0.58 ± 0.31	0.59 ± 0.34	0.73 ± 0.36
AAE	0.57 ± 0.31	0.48 ± 0.51	0.57 ± 0.33
AE	0.51 ± 0.32	0.56 ± 0.35	0.43 ± 0.28
PCA	0.57 ± 0.38	0.71 ± 0.42	0.76 ± 0.45
ICA	0.53 ± 0.31	0.71 ± 0.41	0.78 ± 0.38
333 parcels		0.74 ± 0.40	

Table 3: **Variability of parcel assignment within and between subjects using k-means clustering (k = 12 clusters).**

Figure 14: **Individual-specific network using k-means clustering with 12 networks (VAE (β = 20), 2 dimensions).**

Figure 15: **Individual-specific network using k-means clustering with 12 networks (VAE (β = 20), 4 dimensions).**

Figure 16: **Individual-specific network using k-means clustering with 12 networks (333 parcels).**

Figure 17: **Individual specificity of network assignment using k-means clustering with 12 networks (VAE ($\beta = 1$)).** A) dimension = 2, B) dimension = 4, C) dimension = 32

Figure 18: **Individual specificity of network assignment using k-means clustering with 12 networks (AAE).** A) dimension = 2, B) dimension = 4, C) dimension = 32

Figure 19: **Individual specificity of network assignment using k-means clustering with 12 networks (AE).** A) dimension = 2, B) dimension = 4, C) dimension = 32

Figure 20: **Individual specificity of network assignment using k-means clustering with 12 networks (PCA).** A) dimension = 2, B) dimension = 4, C) dimension = 32

Figure 21: **Individual specificity of network assignment using k-means clustering with 12 networks (ICA).** A) dimension = 2, B) dimension = 4, C) dimension = 32

A.13 IDENTIFICATION OF INDIVIDUALS USING THE FINGERPRINTING ANALYSIS

An alternative measure of individual specificity is the "fingerprinting" analysis (Finn et al., 2015). Since the parcel-wise connectome matrix (333 x 333) is symmetric, we concatenated the lower trian-

gle into a vector as a "barcode" for the first and second sessions, respectively. The similarity across sessions for the same and different subjects was calculated using Pearson's correlation between those "barcodes". For the latent representations with dimensions 2,4, and 32, we concatenated the values from all dimensions for each session as the "barcode" for the session and repeated the fingerprinting analysis. The average accuracy of identification was calculated as the average of two quantities: the proportion of correct identification of the subject from the session 1 data, and the proportion of correct identification from the session 2 data. We additionally calculated a Z-score which describes the relative magnitude of correlation between the sessions from the same subject and the sessions from different subjects. A Z-score was calculated for each subject as:

$$Z = \frac{r_{within} - Mean(r_{between})}{SD(r_{between})} \tag{5}$$

We found that both the accuracy (Figure 22A-C) and within-subject to between-subject contrast (Figure 22D-F) increased with the amount of data. Across all dimensions of 2,4 and 32 using VAE, PCA, and ICA, the fingerprinting accuracy in latent spaces was similar to that in the parcel space, especially for a long scan time (> 20 min). Overall, the difference in accuracy is larger with a shorter scan time, with the accuracy from the VAE ranked the highest among the dimensionality reduction methods with a marginal difference. Since incorrect identification would occur when even if only one other subject had a similar connectome (or connectome latents) to the subject in query, we also quantify the within-subject to between-subject contrast which is defined as the Z-score of the within-subject correlation normalized by the mean and standard deviation of the between-subject correlations. This contrast was higher with increasing latent dimensions and is higher for VAE compared to PCA and ICA, especially at higher latent dimensions (Figure 22D-F).

Figure 22: **Fingerprinting performance for 94 HCP subjects.** A-C) Fingerprinting accuracy. D-F) Mean Z-score of within-subject to between-subject contrast.

A.14 PREDICTION OF BEHAVIORAL PHENOTYPE IN INDIVIDUALS

To demonstrate the ability of the embedded data to retain information about behavioral phenotypes in individual functional connectomes, we applied the learned dimensionality reduction mappings to a separate infant dataset (Baby Connectome Project(Howell et al., 2019)) with 301 sessions. We

predicted the sex and chronological age of each data sample in the parcel space (326 parcels with $326 \times (326\text{-}1)/2 = 52975$ unique features) and the latent space ($326 \times$ zdim features, where zdim = 2, 4, 32) using AE-based or linear dimensionality reduction methods. We use a support vector machine regression for age and support vector machine classification for sex with 80% of the data used for training and the remaining 20% used in testing. We applied a ridge regularization where the hyper-parameter λ was optimized with a 5-fold cross-validation approach from a range of 15 λ values from 10^{-5} to 10^{-1} evenly distributed on a log scale. This process was repeated 1000 times by randomly splitting training and test data to generate an error bar. The age prediction performance was measured with correlation (r) and mean absolute error (MAE). The sex prediction performance was measured with accuracy and F1-score. We found that prediction performance generally increased with the number of dimensions, but the difference across methods was small except for when dimension = 2 (Figure 23).

Figure 23: **Prediction of behavioral phenotype in individuals.** A) Age prediction correlation (r). B) Age prediction Mean absolute error (MAE). C) Sex prediction (accuracy). D) Sex prediction (F1-score). Error bars show mean and standard deviation across the 1000 samples. The horizontal line and shaded area show the performance (mean and standard deviation) using features in the parcel space.

A.15 DIMENSIONALITY REDUCTION ON TIME SERIES DATA

In theory, one can run dimensionality reduction directly on spatiotemporal fMRI time series data, and then generate the seed map embeddings by correlating the original time series with this low-dimensional time series. However, the seed map correlations are likely less noisy than the raw time series because it is a summary metric. Latent embeddings obtained from dimensionality reduction directly on the seed maps could be easily projected back to original seed map images, which can then be overlaid with anatomy to provide intuitive visualizations and neuroscience insights (Figure 3). Also, doing dimensionality reduction directly on seed maps weighs each subject's data equally even when they have very different data acquisition lengths, and it is less likely that a few subjects with long acquisition in the training data would bias the embedding axes. Furthermore, the seed map correlations have constrained values ranging between -1 and 1 but the raw time series data can have different scales depending on the type of normalization. Direct seed map embedding can also

be applied to higher-level summary data such as the network-average functional connectivity across a group of subjects (Moore et al., 2024) so that individual seed maps can be juxtaposed with those network-average profiles to illustrate their positions relative to those network priors.

To empirically compare the dimensionality reduction on time series data and seed maps, we also conducted additional experiments using the time series data as the input to the model instead. We now have 27255 samples instead of the 594200 samples (5942 samples per subject x 100 subjects) in the training data. Similarly, the validation data samples decreased from 59420 to 3758. Overall, the reconstruction performance on the validation data is marginally lower when dimensionality reduction was performed on time series than on seed maps (Table 4). This difference in performance may be driven by the difference in the number of samples used to train the model.

	Dimensionality reduction on time series	Dimensionality reduction on functional connectivity
VAE ($\beta = 20$)		
dim = 2	0.57 ± 0.05	0.71 ± 0.10
dim = 4	0.54 ± 0.04	0.74 ± 0.08
dim = 32	0.51 ± 0.01	0.79 ± 0.07
VAE ($\beta = 1$)		
dim = 2	0.57 ± 0.05	0.71 ± 0.09
dim = 4	0.54 ± 0.04	0.73 ± 0.08
dim = 32	0.52 ± 0.02	0.83 ± 0.06
AAE		
dim = 2	0.57 ± 0.06	0.72 ± 0.09
dim = 4	0.61 ± 0.06	0.73 ± 0.08
dim = 32	0.73 ± 0.05	0.83 ± 0.06
AE		
dim = 2	0.57 ± 0.05	0.72 ± 0.09
dim = 4	0.55 ± 0.04	0.73 ± 0.07
dim = 32	0.52 ± 0.02	0.82 ± 0.06
PCA		
dim = 2	0.58 ± 0.07	0.67 ± 0.10
dim = 4	0.63 ± 0.07	0.74 ± 0.09
dim = 32	0.76 ± 0.05	0.84 ± 0.06
ICA		
dim = 2	0.58 ± 0.07	0.67 ± 0.10
dim = 4	0.63 ± 0.07	0.74 ± 0.09
dim = 32	0.76 ± 0.05	0.84 ± 0.06

Table 4: Reconstruction performance (η^2) on the validation data (10 subjects in WU120)

Next, we look at the embedded seed maps for 10 adult subjects from the test dataset of WU120 generated from 1) indirect embedding by embedding the time series ($2 \times T$) and then correlating with the parcel time series ($333 \times T$), and 2) direct embedding. We found that the results from embedding the time series with linear methods give similar embedded seed map distributions to the direct embedding of seed maps (Figure 24). In addition, we repeated the behavioral phenotype prediction with the new seed map embeddings using the indirect method (a.k.a. embedding the time series first). The performance in predicting age and sex is similar between the direct and indirect embeddings (Figure 25).

Figure 24: **Seed map latent embeddings using direct or indirect dimensionality reduction.** A) PCA on the time series data. B) PCA on the seed maps. C) ICA on the time series data. D) ICA on the seed maps. The colors correspond to the functional network labels in Figure 4A. The colors follow the network colors in Figure 4.

Figure 25: **Prediction of behavioral phenotypes using seed map embeddings generated directly or indirectly through dimensionality reduction on the time series.** The two darker bars on the