Integrating Protein Dynamics into Structure-Based Drug Design via Full-Atom Stochastic Flows

Abstract

The dynamic nature of proteins, influenced by ligand interactions, is essential for comprehending protein function and progressing drug discovery. Traditional structure-based drug design (SBDD) approaches typically target binding sites with rigid structures, limiting their practical application in drug development. While molecular dynamics simulation can theoretically capture all the biologically relevant conformations, the transition rate is dictated by the intrinsic energy barrier between them, making the sampling process computationally expensive. To overcome the aforementioned challenges, we propose to use generative modeling for SBDD considering conformational changes of protein pockets. We curate a dataset of apo and multiple holo states of protein-ligand complexes, simulated by molecular dynamics, and propose a full-atom flow model (and a stochastic version), named DynamicFlow, that learns to transform apo pockets and noisy ligands into holo pockets and corresponding 3D ligand molecules. Our method uncovers promising ligand molecules and corresponding holo conformations of pockets. Additionally, the resultant holo-like states provide superior inputs for traditional SBDD approaches, playing a significant role in practical drug discovery.

1 Introduction

Modern deep learning is advancing several areas within drug discovery. Notably, among these, structure-based drug design (SBDD) (Anderson, 2003) emerges as a particularly significant and challenging domain. SBDD aims to discover drug-like ligand molecules specifically tailored to target binding sites with high binding affinity. However, the complexity of chemical space and the dynamic nature of molecule conformations make traditional methods such as high throughput and virtual screenings inefficient and time-consuming. Additionally, relying on compound databases limits the diversity of identified molecules. Thus, deep generative models, such as autoregressive models (Liu et al., 2022b; Luo et al., 2021; Peng et al., 2022) and diffusion models (Guan et al., 2023; Schneuing et al., 2022), have been introduced as a tool for *de novo* 3D ligand molecule design based on binding pockets, significantly transforming research paradigms.

Figure 1: Comparison of Abl kinase domain conformations. In the top panel, the transition between the apo active and apo inactive conformations is shown. In the bottom panel, the active conformation with Dasatinib bound (DFG-in state) is compared to the inactive conformation with Imatinib bound (DFG-out state). The transformations between these states highlight the structural shifts critical for ligand binding.

However, most SBDD methods based on deep generative models assume that proteins are rigid during interactions and modeling (Peng et al., 2022; Guan et al., 2024). While this simplification aids efficient modeling, the dynamic behavior of proteins is crucial for practical drug discovery

(Karelina et al., 2023; Boehr et al., 2009). Thermodynamic fluctuations result in proteins existing as an ensemble of various conformational states, and such states may interact with different drug molecules. The interconversion between these states often leads to the formation of cryptic pockets, which are closely tied to the biological functions of the protein. During binding, the protein's structure may undergo fine-tuning, adopting different conformations to optimize its interaction with the drug, a phenomenon referred to as induced fit (Sherman et al., 2006). This binding can affect the protein's function by inhibiting the biological signaling pathway associated with a disease. The underlying mechanism might involve blocking the binding of a natural substrate or shifting the protein's conformational distribution. For instance, kinases, which catalyze phosphorylation reactions by transferring phosphate groups from ATP to substrates, exist primarily in two conformations with different mainchain conformations: active (DFG-in) and inactive (DFG-out) (Panjarian et al., 2013). As illustrated in Fig. 1, the Abl kinase exists in both active and inactive apo states (PDB IDs: 6XR6, 6XR7), which differ in their DFG conformations. Type I kinase inhibitors, such as Dasatinib (PDB ID: 2GQG), bind and stabilize the DFG-in conformation. In contrast, type II inhibitors like Imatinib (PDB ID: 2HYY) stabilize the inactive conformation by occupying the ATP-binding pocket. Considering these dynamic conformational shifts is crucial for designing compounds that precisely target this kinase, as such structural nuances directly influence binding and efficacy.

To bridge the gap between SBDD and practical drug discovery, we take a step towards integrating protein dynamics into structure-based drug design. To achieve this goal, we curate a dataset based on a large collection of molecular dynamics traces of protein-ligand complexes. Our dataset comprises both apo and multiple holo states of each protein-ligand complex. We propose an SE(3)-equivariant full-atom flow model, named DYNAMICFLOW, that simultaneously transforms the apo state of protein pockets and noisy ligands into holo states and their corresponding binding ligand molecules. Our method integrates insights from both machine learning and biology, utilizing the flow model's ability to transport one arbitrary distribution to another. We employ apo and holo state pairs as a natural coupling for conditional flow matching to train our flow model, making it learn the dynamics of both backbone frames and side-chain torsions of protein pockets. Simultaneously, we use continuous and discrete flow matching to model the distribution of atom positions, atom types, and bond types of ligand molecules. Additionally, we propose a stochastic version of our flow to further promote the robustness. Notably, to comprehensively capture the protein-ligand interaction, we meticulously design a full-atom model that incorporates both SE(3)-equivariant geometrical message passing layers and residue-level Transformer layers. The experimental results demonstrate the ability of our method to discover biologically meaningful protein conformation and promising ligand molecules. Interestingly, we find that the conformation states of protein pockets discovered by our method can serve as improved input for SBDD methods that treat proteins as rigid entities. We highlight our main contributions as follows:

- We present a meticulously curated dataset consisting of both apo and multiple holo states of protein-ligand complexes derived from molecular dynamics simulation, offering new opportunities for AI-driven drug discovery.

- We propose a full-atom flow model and a stochastic version that transform apo states of protein pockets to holo states and generates the corresponding 3D ligand molecules simultaneously.

- We design a full-atom model with both atom-level SE(3)-equivariant geometrical message passing layers and residue-level Transformer layers, which captures comprehensive protein-ligand interactions and flexibly models protein backbone frames and side-chain torsions.

- Our method generates meaningful protein conformation shifts and promising ligand molecules with high binding affinity. The discovered conformations also further enhance SBDD methods with rigid pockets as input.

2 RELATE WORK

Structure-based Drug Design. Structure-based drug design (SBDD) aims to develop ligand molecules capable of binding to specific protein targets. The advent of deep generative models has revolutionized the field, producing significant results. Luo et al. (2021); Peng et al. (2022); Liu et al. (2022a) and Zhang et al. (2022) employed an autoregressive model to generate atoms (and bonds) or fragments of a ligand molecule given a specific binding site with 3D structure. Guan et al. (2023); Schneuing et al. (2022); Lin et al. (2022) integrated diffusion models (Ho et al., 2020) into SBDD. These models initially generate the types and positions of atoms through iterative denoising, followed by determining bond types through post-processing. Some recent studies have sought

to enhance these methods by incorporating biochemical prior knowledge. Guan et al. (2024) introduced decomposed priors and validity guidance to improve the quality of ligand molecules generated by diffusion models. Zhang & Liu (2023) enhanced molecule generation through global interactions between subpocket prototypes and molecular motifs. Huang et al. (2023) integrated protein-ligand interaction priors into both the forward and reverse processes to refine the diffusion models. Lee et al. (2024) proposed to simultaneously denoise non-covalent interaction types of protein-ligand edges along with a 3D graph of a ligand molecule. While these studies have shown promising results in *in silico* evaluations, their disregard for protein dynamics limits their applicability in practical drug development. A recent work (Schneuing et al., 2024) considers protein flexibility in terms of side-chain torsions in SBDD. Our work differs in that our method models the dynamics of both the protein backbone structure and side-chain torsion, and utilizes rigorous discrete flow matching for modeling atom and bond types of ligand molecules. Importantly, our model employs an apo-holo transformation paradigm, offering a biologically informative prior for the flow model. In contrast, Schneuing et al. (2024) focuses on denoising side-chain torsions from a non-informative prior derived from a static protein-ligand complex dataset.

Generative Modeling of Protein Structures. Deep generative models, especially diffusion models (Ho et al., 2020) (also known as score-based generative models (Song et al., 2021)) and flow models (Lipman et al., 2022; Liu et al., 2022c; Albergo & Vanden-Eijnden, 2022), have been widely utilized in modeling distributions of protein structures and attained impressive results. Protein structures are usually described with frames, which can be represented with elements of the Lie group SE(3), and side-chain torsion angles, which can be represented with elements of the Lie group SO(2) (Jumper et al., 2021; Watson et al., 2023). Both diffusion (De Bortoli et al., 2022; Huang et al., 2022) and flow (Chen & Lipman, 2023) models have been well extended to Riemannian manifolds, theoretically providing complete tools for modeling protein structures. These techniques have been extensively applied to various tasks related to protein structure modeling. Watson et al. (2023); Yim et al. (2023b;a); Bose et al. (2024) employed diffusion and flow models for protein backbone generation. Yim et al. (2024) and Lu et al. (2024a) further utilized these models for motif scaffolding and protein conformation sampling, respectively. Zhang et al. (2024); Lee & Kim (2024) applied diffusion and flow models to protein side-chain packing. Plainer et al. (2023); Zhu et al. (2024); Huang et al. (2024) proposed protein-ligand docking with flexibility on protein side-chain torsion under the framework of diffusion models. Lu et al. (2024b) considered flexibility on both protein backbone structure and side-chain torsion in protein-ligand docking. The above works inspire us to consider the complete degrees of freedom of proteins in the scenario of structure-based drug design.

3 METHOD

In this section, we will present our method, named DYNAMICFLOW, as illustrated in Fig. 2. In Section 3.1, we provide a clear statement about our problem setting and notations about SBDD considering protein dynamics along with a background on flow matching. In Section 3.2, we show the details about the training and inference of the full-atom flow, named DYNAMICFLOW-ODE, for this novel task. In Section 3.3, we show how to extend this flow model to a stochastic version, named DYNAMICFLOW-SDE, to improve its robustness. Finally, in Section 3.4, we introduced details about the multiscale full-atom architecture design of our flow model as shown in Fig. 3.

3.1 BACKGROUND AND PRELIMINARIES

We aim to generate a holo state of a protein pocket and its binding ligand molecule given its apo state. The ligand molecule can be represented as a set of N_m atoms $\mathcal{M} = \{(\mathbf{x}_m^{(i)}, \mathbf{v}_m^{(i)}, \mathbf{b}_m^{(ij)})\}_{i,h \in \{1,...,N_m\}}$. The apo state of a protein pocket can be represented in atom level as a set of N_p atoms $\mathcal{P}_0 = \{(\mathbf{x}_{p0}^{(i)}, \mathbf{v}_{p0}^{(i)})\}_{i=1}^{N_p}$. It can also be represented in residue level as a length-D_p sequence of residues $\mathcal{S}_0 = [(\mathbf{a}_0^{(i)}, \mathbf{t}_0^{(i)}, \mathbf{r}_0^{(i)}, \chi_{00}^{(i)}, \chi_{10}^{(i)}, \chi_{20}^{(i)}, \chi_{30}^{(i)}, \chi_{40}^{(i)})]_{i=1}^{D_p}$. For the holo state, the first digits in all subscripts change from 0 to 1. Here $\mathbf{x} \in \mathbb{R}^3$ is the atom position, $\mathbf{v} \in \mathbb{R}^K$ is the atom type, $\mathbf{b} \in \mathbb{R}^B$ is the bond type, $\mathbf{a} \in \mathbb{R}^S$ is the amino acid type, $\mathbf{t} \in \mathbb{R}^3$ is the translation of the residue frame, $\mathbf{r} \in \mathrm{SO}(3)$ is the rotation of the residue frame, $\chi_0 \in \mathrm{SO}(2)$ is backbone torsion angle that governs the position of atom O, and $\chi_1, \chi_2, \chi_3, \chi_4 \in \mathrm{SO}(2)$ are the side-chain torsion angles (see definitions in App. C). Note that $\mathbf{a}_0^{(i)} = \mathbf{a}_1^{(i)}$ and $\mathbf{v}_0^{(i)} = \mathbf{v}_1^{(i)}$ for all i since protein conformation changes do not impact the amino acid types and atom types. The SBDD task, incorporating protein dynamics, can be formulated as modeling the conditional distribution $q(\mathcal{P}_1, \mathcal{M}|\mathcal{P}_0)$.

Figure 2: Overview of DYNAMICFLOW. (a) Our dataset consists of apo and multiple holo states of protein-ligand complexes derived from molecular dynamics simulation. (b) Our flow models, DYNAMICFLOW-ODE and DYNAMICFLOW-SDE, the generative process of ligand molecules along with the protein dynamics from apo to holo. The protein pocket is represented as both (i) residue frames and side-chain torsions and (ii) full atoms. The ligand molecule is represented as atom types, bond types, and atom positions.

We will use flow models to model the above conditional distribution. In the following, we provide a background on flow matching for modeling both continuous (Lipman et al., 2022; Liu et al., 2022c; Albergo & Vanden-Eijnden, 2022) and discrete (Campbell et al., 2024; Gat et al., 2024) variables, which we will use in the following sections.

We start with the continuous case. In flow matching, we consider a predefined *marginal probability path* p_t that interpolates prior distribution p_0 and data distribution $p_1 = q$ to train a generative model that transports a source sample $\mathbf{x}_0 \sim p_0$ to a target sample $\mathbf{x}_1 \sim q_1$. We denote the joint distribution of p_0 and p_1 as $\pi(\mathbf{x}_0, \mathbf{x}_1)$ (also known as the data coupling). The probability path corresponds to a time-dependent flow $\psi_t : [0,1] \times \mathbb{R}^d \to \mathbb{R}^d$ and an associated vector field $u_t : [0,1] \times \mathbb{R}^d \to \mathbb{R}^d$, which can be defined via the ordinary differential equation (ODE) as $\dot{\mathbf{x}}_t = u_t(\mathbf{x}_t)$ where $\mathbf{x}_t = \psi_t(\mathbf{x}_0)$. One could use a neural network $v_\theta(\mathbf{x}_t, t)$ to regress the ground truth vector field $u_t(\mathbf{x}_t)$. However, the flow matching objective is intractable since we have no knowledge about the closed-form of the vector field u_t that generates marginal distribution path p_t. The key insight by (Lipman et al., 2022; Liu et al., 2022c) is to regress v_θ against the conditional vector field $u_t(\mathbf{x}_t|\mathbf{x}_0, \mathbf{x}_1)$, which generates the conditional probability path $p_t(\mathbf{x}_t|\mathbf{x}_0, \mathbf{x}_1)$, and use it to construct the target marginal path $p_t(\mathbf{x}_t) = \int_{\mathbf{x}_0, \mathbf{x}_1} p_t(\mathbf{x}_t|\mathbf{x}_0, \mathbf{x}_1)\pi(\mathbf{x}_0, \mathbf{x}_1)d\mathbf{x}_0 d\mathbf{x}_1$. The corresponding marginal vector field can also be constructed as $u_t(\mathbf{x}_t) := \int_{\mathbf{x}_0, \mathbf{x}_1} u_t(\mathbf{x}_t|\mathbf{x}_0, \mathbf{x}_1)\frac{p_t(\mathbf{x}_t|\mathbf{x}_0, \mathbf{x}_1)\pi(\mathbf{x}_0, \mathbf{x}_1)}{p_t(\mathbf{x}_t)}d\mathbf{x}_0 d\mathbf{x}_1$. The conditional flow matching loss is as follows:

$$\mathcal{L} = \mathbb{E}_{t \sim \mathcal{U}(0,1), \pi(\mathbf{x}_0, \mathbf{x}_1), p_t(\mathbf{x}_t|\mathbf{x}_0, \mathbf{x}_1)} \|v_\theta(\mathbf{x}_t, t) - u_t(\mathbf{x}_t|\mathbf{x}_1, \mathbf{x}_0)\|^2. \quad (1)$$

For modeling discrete variables, we follow the framework of Discrete Flow Matching (Campbell et al., 2024) which is based on Continuous-Time discrete Markov Chain (CTMC). Here $\mathbf{x} \in \{1, \ldots, S\}^D$ is a random discrete variable, e.g., a length-D sequence where each element takes on one of S states, and we denote $\boldsymbol{j}$ as a specific state of $\mathbf{x}$. We first introduce the concept of rate matrix $R_t \in \mathbb{R}^{S \times S}$, which plays a similar role to the vector field u_t in the continuous case. The probability that $\mathbf{x}_t$ jumps to a different state $\boldsymbol{j}$ is $R_t(\mathbf{x}_t, \boldsymbol{j})dt$ after a infinitesimal time step dt is $R(\mathbf{x}_t, \boldsymbol{j})dt$, i.e., $p_{t+dt|t}(\boldsymbol{j}|\mathbf{x}) = \delta\{\mathbf{x}_t, \boldsymbol{j}\} + R_t(\mathbf{x}_t, \boldsymbol{j})dt$ where $\delta\{\boldsymbol{i}, \boldsymbol{j}\}$ is an element-wise Kronecker delta which 1 in dimension d when $\boldsymbol{i}^d = \boldsymbol{j}^d$ and 0 otherwise. To

build a discrete flow, we also use the conditional probability path to construct the marginal one as $p_t(\mathbf{x}_t) := \mathbb{E}_{p(x_1)}[p_t(\mathbf{x}_t|\mathbf{x}_1)]$. We define $R_t(\mathbf{x}_t, \boldsymbol{j}|\mathbf{x}_1)$ as a conditional rate matrix that generates $p_t(\mathbf{x}_t|\mathbf{x}_1)$. Notably, $R_t(\mathbf{x}_t, \boldsymbol{j}|\mathbf{x}_1)$ can usually be in a simple formula. For example, it can be that $R_t(\mathbf{x}_t, \boldsymbol{j}|\mathbf{x}_1) := \delta\{\mathbf{x}_1, \boldsymbol{j}\}\delta\{\mathbf{x}_t, M\}/(1-t)$ where M is the mask token. It can be proved that the marginal rate matrix $R_t(\mathbf{x}_t, \boldsymbol{j}) := \mathbb{E}_{p(\mathbf{x}_1|\mathbf{x}_t)}[R_t(\mathbf{x}_t, \boldsymbol{j}|\mathbf{x}_1)]$ corresponds to the marginal probability path $p_t(\mathbf{x}_t)$ which we have defined above, where $p(\mathbf{x}_1|\mathbf{x}_t) = p_t(\mathbf{x}_t|\mathbf{x}_1)q(\mathbf{x}_1)/p_t(\mathbf{x}_t)$. We can use a neural network $p_t^\theta(\mathbf{x}_1|\mathbf{x}_t)$ to approximate the posterior $p_t(\mathbf{x}_1|\mathbf{x}_t)$. We denote $R_t^\theta(\mathbf{x}_t, \cdot) := \mathbb{E}_{p_t^\theta(\mathbf{x}_1|\mathbf{x}_t)}[R_t(\mathbf{x}_t, \cdot|\mathbf{x}_1)]$. We can generate a sample by iteratively sampling from the process as

$$p_{t+dt}(\mathbf{x}_{t+dt}|\mathbf{x}_t) = \delta\{\mathbf{x}_{t+dt}, \mathbf{x}_t\} + R_t^\theta(\mathbf{x}_t, \mathbf{x}_{t+dt})dt + o(dt). \tag{2}$$

3.2 FULL-ATOM FLOW FOR SBDD WITH PROTEIN DYNAMICS

One advantage of flow models is their ability to transport any arbitrary distribution to another, without imposing constraints on the source or target distribution. Fully leveraging this advantage to model the conditional distribution $q(\mathcal{P}_1, \mathcal{M}|\mathcal{P}_0)$, we build a flow, named DYNAMICFLOW-ODE, that transforms apo to holo states and generates ligand molecules from a noisy prior distribution simultaneously. The apo state $\mathcal{P}_0$ and holo state $\mathcal{P}_1$ naturally serve as samples from the source and target distribution for flow matching. Formally, we define the source distribution p_0 as

$$p_0(\mathcal{P}, \mathcal{M}|\mathcal{P}_0) := \delta(\mathcal{P}, \mathcal{P}_0) \prod_{i=1}^{N_m} \mathcal{N}(\mathbf{x}_m^{(i)}; \text{CoM}(\mathcal{P}_0), \boldsymbol{I})\delta\{\mathbf{v}_m^{(i)}, M_v\} \prod_{i,j=1}^{N_m} \delta\{\mathbf{b}_m^{(ij)}, M_b\}, \tag{3}$$

where $\delta(\cdot, \cdot)$ is the Dirac delta function, $\delta\{\cdot, \cdot\}$ is the discrete Kronecker delta function, $\text{CoM}(\cdot)$ is the function that calculates center of mass, and M_v (resp. M_b) is the token for atom (resp. bond) type. This means that the pocket directly starts with the apo state, atom/bond types of ligand molecules start with mask tokens, and atom positions of molecules start with a normal distribution around the CoM of the apo pocket. The target distribution $p_1(\mathcal{P}, \mathcal{M}|\mathcal{P}_0)$ is the data distribution q. Specifically, we use the multiple holo states and binding ligand molecules that correspond to apo state $\mathcal{P}_0$ in our training dataset as the data coupling $\pi(\mathcal{M}_0, \mathcal{P}_0, \mathcal{M}_1, \mathcal{P}_1|\mathcal{P}_0)$ and use the predefined conditional probability path $p_t(\mathcal{M}_t, \mathcal{P}_t|\mathcal{M}_0, \mathcal{P}_0, \mathcal{M}_1, \mathcal{P}_1)$ to sample "interpolant" to train our flow model.

Next, we show how to derive the vector field u_t for the continuous variables (i.e., pocket residues' translation, rotation, torsion angles, and ligand molecules' atom positions). Both pocket residues' translation $\mathbf{t}$ and ligand molecules' atom positions $\mathbf{x}_m$ live in 3D Euclidean space. Taking $\mathbf{t}$ as an example, given samples from source and target distribution, i.e., $\mathbf{t}_0$ and $\mathbf{t}_1$, we define the conditional probability path as the linear interpolant between these two samples and derive the conditional vector field as follows (t in superscript stands for "translation" and t in subscript stands for "time"):

$$p_t^t(\mathbf{t}_t^{(i)}|\mathbf{t}_0^{(i)}, \mathbf{t}_1^{(i)}) := \delta(\mathbf{t}_t^{(i)}, t\mathbf{t}_1^{(i)} + (1-t)\mathbf{t}_0^{(i)}) \quad \text{and} \quad u_t^t(\mathbf{t}_t^{(i)}|\mathbf{t}_1^{(i)}, \mathbf{t}_0^{(i)}) = \mathbf{t}_1^{(i)} - \mathbf{t}_0^{(i)} = \frac{\mathbf{t}_1^{(i)} - \mathbf{t}_0^{(i)}}{1-t}. \tag{4}$$

Instead of directly predicting the vector field, we use $\mathbf{t}_\theta(\mathbf{t}_t^{(i)}, t)$ to predict the "clean" sample at time 1 and express the predicted vector field as $v_\theta(\mathbf{t}_t^{(i)}, t) := (\mathbf{t}_\theta(\mathbf{t}_t^{(i)}, t) - \mathbf{t}_0^{(i)})/(1-t)$. Please note that while the complete context $(\mathcal{M}_t, \mathcal{P}_t)$ is indeed input into the network parameterized with θ, we omit it here for simplicity. This convention is maintained throughout the entire paper. The conditional flow matching (CFM) objective for translation of residue frame at time t can be formulated as:

$$\mathcal{L}_t^t = \mathbb{E}_{\pi(\mathbf{t}_0, \mathbf{t}_1), p_t^t(\mathbf{t}_t^{(i)}|\mathbf{t}_0^{(i)}, \mathbf{t}_1^{(i)})} \big\| v_\theta(\mathbf{t}_t^{(i)}, t) - (\mathbf{t}_1^{(i)} - \mathbf{t}_0^{(i)}) \big\|_2^2. \tag{5}$$

For the rotation of residue frames, we use the geodesic interpolant to define the conditional probability path and conditional vector path as follows:

$$p_t^r(\mathbf{r}_t^{(i)}|\mathbf{r}_0^{(i)}, \mathbf{r}_1^{(i)}) := \delta\big(\mathbf{r}_t^{(i)}, \exp_{\mathbf{r}_0^{(i)}}\big(t \log_{\mathbf{r}_0^{(i)}}\big(\mathbf{r}_1^{(i)}\big)\big)\big) \quad \text{and} \quad u_t^r(\mathbf{r}_t^{(i)}|\mathbf{r}_0^{(i)}, \mathbf{r}_1^{(i)}) = \frac{\log_{\mathbf{r}_t^{(i)}}(\mathbf{r}_1^{(i)})}{1-t}. \tag{6}$$

Similar to the case for translation, we use $\mathbf{r}_\theta(\mathbf{r}_t^{(i)}, t)$ to predict the "clean" sample at time 1 and express the predicted vector field on SO(3) manifold as $v_\theta(\mathbf{r}_t^{(i)}, t) := \log_{\mathbf{r}_t^{(i)}}(\mathbf{r}_\theta(\mathbf{r}_t^{(i)}, t))/(1-t)$. The CFM objective for rotation of residue frame at time t can be formulated as:

$$\mathcal{L}_t^r = \mathbb{E}_{\pi(\mathbf{r}_0, \mathbf{r}_1), p_t^t(\mathbf{r}_t^{(i)}|\mathbf{r}_0^{(i)}, \mathbf{r}_1^{(i)})} \bigg\| v_\theta(\mathbf{r}_t^{(i)}, t) - \frac{\log_{\mathbf{r}_t^{(i)}}(\mathbf{r}_1^{(i)})}{1-t} \bigg\|_{\text{SO(3)}}^2. \tag{7}$$

Torsion angles of protein pockets lie on high-dimensional tori. Note the slight abuse of notation that we use $\mathcal{M}$ to represent both the manifold and the molecule. For a torus $\mathcal{M} := [0, k\pi] \, (k = 1, 2)$, the exponential and logarithm maps are as follows Chen & Lipman (2023):

$$\exp_u(x) = (x + u)\%(k\pi) \quad \text{and} \quad \log_x(y) = \text{arctan2}(\sin(y - x), \cos(y - x)), \tag{8}$$

where $x, y \in \mathcal{M}$ and $u \in \mathcal{T}_x\mathcal{M}$. Following Li et al. (2024), we define $\text{wrap}(u) := (u + \pi)\%(2\pi) - \pi$. While we model 5 torsion angles, here we use χ for brevity. The conditional probability path and conditional vector field can be defined as follows:

$$p_t^\chi(\chi_t^{(i)}|\chi_0^{(i)}, \chi_t^{(i)}) := \delta\Big(\chi_t^{(i)}, \big(\chi_0^{(i)} + t\text{wrap}(\chi_1^{(i)} - \chi_0^{(i)})\big)\%(k\pi)\Big), \tag{9}$$

$$u_t(\chi_t^{(i)}|\chi_0^{(i)}, \chi_1^{(i)}) = \text{wrap}(\chi_1^{(i)} - \chi_0^{(i)}) = \frac{\text{wrap}(\chi_1^{(i)} - \chi_t^{(i)})}{1 - t}. \tag{10}$$

Here we introduce $k = 1$ to handle the special cases where some side-chain torsion angles of certain residues exhibit π-rotation-symmetry (e.g., χ_2 of ASP). For other general cases, $k = 2$. Refer to App. C for details. We use $\chi_\theta(\chi_t^{(i)}, t)$ to predict the "clean" sample at time 1 and express the predicted vector field on tori as $v_\theta(\chi_t^{(i)}, t) := \text{wrap}(\chi_\theta(\chi_t^{(i)}, t) - \chi_0^{(i)})/(1 - t)$. Also following Li et al. (2024), we use the flat metric on tori in CFM objective as follows:

$$\mathcal{L}_t^\chi = \mathbb{E}_{\pi(\chi_0, \chi_1), p_t^t(\chi_t^{(i)}|\chi_0^{(i)}, \chi_1^{(i)})}\Big\|\text{wrap}\Big(v_\theta(\chi_t^{(i)}, t) - \frac{\chi_1^{(i)} - \chi_0^{(i)}}{1 - t}\Big)\Big\|^2. \tag{11}$$

So far, We have now covered all cases of the continuous variables. The sampling (i.e., inference) procedure of these continuous variables is solving ODEs defined on the corresponding space.

Next, we show how we model discrete variables, i.e., atom types and bond types of ligand molecules. We take bond types $\mathbf{b}_m^{(ij)}$ of ligand molecules as an example. In the following, we omit the subscript m that stands for "molecule" for brevity without ambiguity. We define the conditional probability path and the conditional rate matrix as follows:

$$p_t^b(\mathbf{b}_t^{(ij)}|\mathbf{b}_0^{(ij)}, \mathbf{b}_1^{(ij)}) := \text{Cat}(t\delta\{\mathbf{b}_1^{(ij)}, \mathbf{b}_t^{(ij)}\} + (1 - t)\delta\{\mathbf{b}_t^{(ij)}, M\}), \tag{12}$$

$$R_t^b(\mathbf{b}_t^{(ij)}, n|\mathbf{b}_1^{(ij)}) = \frac{\delta\{\mathbf{b}_1^{(ij)}, n\}\delta\{\mathbf{b}_t^{(ij)}, M\}}{1 - t}, \tag{13}$$

where $n \in \{1, \dots, B\}$ is a specific bond type. A straightforward interpretation of the above conditional discrete flow is that we linearly interpolate between a probability mass concentrated entirely on the mask token and the data distribution. As introduced in Section 3.1, we train a neural network $p_\theta^b(\mathbf{b}_1^{(ij)}|\mathbf{b}_t^{(ij)})$ with simple cross-entropy loss as follows:

$$\mathcal{L}_t^b = \mathbb{E}_{\pi(\mathbf{b}_0, \mathbf{b}_1), p_t^b(\mathbf{b}_t^{(ij)}|\mathbf{b}_0^{(ij)}, \mathbf{b}_1^{(ij)})}[-\log p_\theta^b(\mathbf{b}_1^{(ij)}|\mathbf{b}_t^{(ij)})]. \tag{14}$$

The estimated marginal rate matrix can be expressed as

$$R_\theta^b(\mathbf{b}_t^{(ij)}, n) = \mathbb{E}_{p_\theta^b(\mathbf{b}_1^{(ij)}|\mathbf{b}_t^{(ij)})}[R_t^b(\mathbf{b}_t^{(ij)}, n|\mathbf{b}_1^{(ij)})] = \frac{p_\theta^b(\mathbf{b}_1^{(ij)}|\mathbf{b}_t^{(ij)})}{1 - t}\delta\{\mathbf{b}_t^{(ij)}, M\}. \tag{15}$$

During sampling, the transition step from t to $t + dt$ is

$$p_{t+dt}(n|\mathbf{b}_t^{(ij)}) = \delta\{\mathbf{b}_t^{(ij)}, n\} + R_\theta^b(\mathbf{b}_t^{(ij)}, n)dt. \tag{16}$$

To better capture interactions between atoms, we propose an interaction loss that directly regresses the distances between predicted atom pairs and the ground-truth distances in local space. For time t, we denote the predicted "clean" holo state and ligand molecule as

$$\hat{\mathcal{S}}_1 := [(\mathbf{a}_0^{(i)}, \mathbf{t}_\theta^{(i)}, \mathbf{r}_\theta^{(i)}, \chi_{1\theta}^{(i)}, \chi_{2\theta}^{(i)}, \chi_{3\theta}^{(i)}, \chi_{4\theta}^{(i)})]_{i=1}^{D_p} \quad \text{and} \quad \hat{\mathcal{M}}_1 := \{(\hat{\mathbf{x}}_{m1}^{(i)}, \hat{\mathbf{v}}_{m1}^{(i)})\}_{i=1}^{N_p}, \tag{17}$$

where we denote $\mathbf{r}_\theta(\mathbf{r}_t^{(i)}, t)$ as $\mathbf{t}_\theta^{(i)}$ for brevity and similarly for other variables. Note that here we omit the bond types in $\hat{\mathcal{M}}_1$ because we do not use it in the interaction loss. The frame representation is then converted to atom representation $\hat{\mathcal{P}}_1 := \{(\hat{\mathbf{x}}_{p1}^{(i)}, \hat{\mathbf{v}}_{p1}^{(i)})\}_{i=1}^{N_p} = \text{FrameToAtom}(\hat{\mathcal{S}}_1)$. See details about FrameToAtom($\cdot$) in App. B. We denote all predicted atoms in the protein-ligand complex as $\hat{\mathcal{A}}_1 := \{(\hat{\mathbf{x}}_1^{(i)}, \hat{\mathbf{v}}_1^{(i)})\}_{i=1}^{N_p + N_m} = \hat{\mathcal{P}}_1 \cup \hat{\mathcal{M}}_1$ and the corresponding ground truth as $\mathcal{A}_1 := \{(\mathbf{x}_1^{(i)}, \mathbf{v}_1^{(i)})\}_{i=1}^{N_p + N_m} = \mathcal{P}_1 \cup \mathcal{M}_1$. The interaction loss can be formulated as follows:

$$\mathcal{L}_t^{\text{int}} = \sum_{i=1}^{N_p + N_m} \sum_{j=i+1}^{N_p + N_m} \|\hat{d}_1^{(ij)} - d_1^{(ij)}\|^2 \cdot \mathbb{1}\{d_1^{(ij)} \le 3.5\} \cdot \mathbb{1}\{t > 0.65\}, \tag{18}$$

where $\hat{d}_1^{(ij)} = \|\hat{\mathbf{x}}_1^{(i)} - \hat{\mathbf{x}}_1^{(j)}\|$, $d_1^{(ij)} = \|\mathbf{x}_1^{(i)} - \mathbf{x}_1^{(j)}\|$, and $\mathbb{1}\{\cdot\}$ is the indicator function.

Figure 3: Illustration of our multiscale full-atom model architecture: (a) atom-level SE(3)-equivariant graph neural network; (b) residue-level Transformers.

3.3 EXTENSION TO STOCHASTIC FULL-ATOM FLOW

The probability path induced by linear interpolant between apo and holo state of pocket has limited set-theoretic support, thus potentially leading to inferior robustness. This motivates us to build a stochastic flow, named DYNAMICFLOW-SDE, since SDEs offer the significant advantage of being more robust to noise in high-dimensional spaces compared to ODEs (Tong et al., 2023; Shi et al., 2023; Liu et al., 2023). Based on the way that we build DYNAMICFLOW-ODE as we introduced in Section 3.2, we can easily extend to SDEs via simply updating the conditional probability paths in training and sampling. Bose et al. (2024) offers theoretical justification that conditional flow matching loss and original flow matching loss remain equivalent with respect to optimization.

For variables lie in Euclidean space, i.e., the translation of residue frames $\mathbf{t}^{(i)}$ and the atom positions $\mathbf{a}^{(i)}$, we can update the conditional probability path from Eq. (4) to:

$$p_t^t(\mathbf{t}_t^{(i)}|\mathbf{t}_0^{(i)}, \mathbf{t}_1^{(i)}) := \mathcal{N}(\mathbf{t}_t^{(i)}; t\mathbf{t}_1^{(i)} + (1-t)\mathbf{t}_0^{(i)}, \gamma^2 t(1-t)\boldsymbol{I}), \tag{19}$$

where γ is a constant hyperparameter that controls the noise scale.

For variables lie on SO(3) manifold, i.e., the rotation of residue frames $\mathbf{r}^{(i)}$, we update the conditional probability path in Eq. (6) to an efficient simulation-free approximation of correct conditional stochastic flow on SO(3) suggested by Bose et al. (2024):

$$p_t^r(\mathbf{r}_t^{(i)}|\mathbf{r}_0^{(i)}, \mathbf{r}_t^{(i)}) := \mathcal{IG}_{\text{SO(3)}}(\mathbf{r}_t^{(i)}; \exp_{\mathbf{r}_0^{(i)}}(t\log_{\mathbf{r}_0^{(i)}}(\mathbf{r}_1^{(i)})), \gamma t(1-t)), \tag{20}$$

where $\mathcal{IG}_{\text{SO(3)}}$ denotes the isotropic Gaussian distribution on SO(3) (Nikolayev & Savyolov, 1900).

For variables lie on tori, i.e., the torsion angles of residues $\chi^{(i)}$, we update the conditional probability path in Eq. (10) to:

$$p_t^\chi(\chi_t^{(i)}|\chi_0^{(i)}, \chi_t^{(i)}) \propto \sum_{d\in\mathbb{Z}} \exp\left(-\frac{\left\|\chi_t^{(i)} - (\chi_0^{(i)} + t\text{wrap}(\chi_1^{(i)} - \chi_0^{(i)}))\%(k\pi) + k\pi d\right\|^2}{2\gamma^2 t(t-1)}\right), \tag{21}$$

which is a wrapped normal distribution. This can be sampled directly (Jing et al., 2022).

3.4 MULTISCALE FULL-ATOM MODEL ARCHITECTURE

Our flow models employ a multiscale scheme as shown in Fig. 3, which is comprised of two main parts: (a) atom-level SE(3)-equivariant graph neural network; (b) residue-level Transformers.

In the atom-level GNN, inspired by Guan et al. (2024), we maintain both node-level and edge-level hidden states in the neural network by modifying widely used EGNN (Satorras et al., 2021). During training, for time t, we build a k-nearest neighbors (knn) graph G_c upon the atoms of the protein-ligand complex to capture the protein-ligand interaction:

$$\Delta\mathbf{h}_c^{(i)} \leftarrow \sum_{j\in\mathcal{N}_c(i)} \phi_c(\mathbf{h}^{(i)}, \mathbf{h}^{(j)}, \|\mathbf{x}^{(i)} - \mathbf{x}^{(j)}\|, E^{(ij)}, t), \tag{22}$$

Table 1: Summary of properties of reference molecules and molecules generated by our model and other baselines. (↑) / (↓) denotes a larger / smaller number is better.

	Vina Score (↓)	QED (↑)	SA (↑)	Linpiski (↑)	logP	High Affi. (↑)	Comp. Rate (↑)
Reference	-7.84±3.11	0.53±0.19	0.67±0.15	4.45±0.77	1.64±2.17	N/A	N/A
Pocket2Mol	-5.50±1.25	0.54±0.12	0.83±0.10	1.70±1.52	4.98±0.14	28.6%	N/A
TargetDiff	-5.09±4.81	0.42±0.18	0.53±0.13	3.20±2.39	4.32±0.81	44.0%	68.2%
TargetDiff*	-5.53±4.09	0.39±0.21	0.55±0.15	3.02±2.75	4.11±1.10	45.7%	62.4%
IPDiff	-7.55±5.59	0.38±0.17	0.50±0.14	4.10±0.77	5.07±2.94	51.0%	67.8%
IPDiff*	-6.23±5.26	0.40±0.20	0.55±0.15	3.94±1.00	5.04±3.34	49.5%	67.3%
DYNAMICFLOW-ODE	-7.28±1.98	0.53±0.20	0.61±0.14	3.13±2.62	4.45±0.81	51.0%	70.2%
DYNAMICFLOW-SDE	-7.65±1.59	0.53±0.15	0.53±0.17	4.34±2.58	4.25±0.90	52.5%	73.6%

where $\mathbf{h}$ is the atom-level hidden state, $\mathcal{N}_c(i)$ is the neighbors of i in $\mathcal{G}_c$, $E^{(ij)}$ indicates the edge ij is a protein-protein, ligand-ligand, or protein-ligand edge. We also build a fully connected ligand graph G_m upon all ligand atoms to model the chemical interaction inside the ligand molecule:

$$\mathbf{m}^{(ij)} \leftarrow \phi_m(\|\mathbf{x}^{(i)} - \mathbf{x}^{(j)}\|, \mathbf{e}^{(ij)}) \quad \text{and} \quad \Delta\mathbf{h}_m^{(i)} \leftarrow \sum_{j \in \mathcal{N}_m(i)} \phi_m(\mathbf{h}^{(i)}, \mathbf{h}^{(j)}, \mathbf{m}^{(ji)}, t), \quad (23)$$

where $\mathbf{e}$ is the bond-level hidden state. We then update the atom and bond's hidden state as follows:

$$\mathbf{h}^{(i)} \leftarrow \mathbf{h}^{(i)} + \phi_h(\Delta\mathbf{h}_c^{(i)} + \Delta_m^{(i)}), \quad (24)$$

$$\mathbf{e}^{(ji)} \leftarrow \sum_{k \in \mathcal{N}_m(j)\setminus\{i\}} \phi_e(\mathbf{h}^{(i)}, \mathbf{h}^{(j)}, \mathbf{h}^{(k)}, \mathbf{m}^{(jk)}, \mathbf{m}^{(ji)}, t), \quad (25)$$

Then we update the SE(3)-equivariant features (i.e. positions of ligand molecules) as:

$$\Delta\mathbf{x}_c^{(i)} \leftarrow \sum_{j \in \mathcal{N}_c(i)} \mathbf{d}^{(ji)} \phi_c^x(\mathbf{h}^{(i)}, \mathbf{h}^{(j)}, d^{(ij)}, t), \quad \Delta\mathbf{x}_m^{(i)} \leftarrow \sum_{j \in \mathcal{N}_m(i)} \mathbf{d}^{(ji)} \phi_m^x(\mathbf{h}^{(i)}, \mathbf{h}^{(j)}, d^{(ji)}, \mathbf{m}^{(ji)}, t) \quad (26)$$

where $\mathbf{d}^{(ji)} = \mathbf{x}^{(j)} - \mathbf{x}^{(i)}$ and $d^{(ij)} = \|\mathbf{d}^{(ji)}\|$. We only update ligand atom positions in the atom-level part as $\mathbf{x}^{(i)} \leftarrow \mathbf{x}^{(i)} + (\Delta\mathbf{x}_c^{(i)} + \Delta\mathbf{x}_m^{(i)}) \cdot \mathbb{1}_m(i)$, where $\mathbb{1}_m(i)$ is an indicator of ligand atom, and leave the pocket update in the residue-level part. The output equivariant (resp. invariant) hidden states of ligand nodes are used to predict atom positions (resp. atom/bond types) of ligand molecules.

We aggregate the final protein atom hidden states $\mathbf{h}$ output by the above full-atom GNN into residue level according to the atom37 template (Jumper et al., 2021). The aggregated residue-level hidden states along with amino acid type $\mathbf{a}$, 5 torsion angles χ, and frame $(\mathbf{t}, \mathbf{r})$ are input into a residue-level Transformer model which is composed of node embedding layer, edge embedding layer, multiple Invariant Point Attention (IPA) blocks, following Jumper et al. (2021); Yim et al. (2023b). In each IPA block, residue-level hidden state $\mathbf{h}$ and frame $(\mathbf{t}, \mathbf{r})$ are updated. The final updated frames are used as predictions. Torsion angles are predicted based on the final residue-level hidden states.

4 EXPERIMENTS

Data Curation. We curate our dataset based on MISATO dataset (Siebenmorgen et al., 2024). The original dataset contains approximately 20,000 protein-ligand complexes with associated 8ns molecular dynamics (MD) simulation trajectories. We filter out complexes where the ligands are oligopeptides, yielding 12,695 complexes for further processing. For each complex, we efficiently use the data by clustering the holo-ligand conformations with an RMSD threshold of 1.0 Å. Finally, to filter out the invalid MD simulation results, we select complexes whose averaged RMSD between the ligand conformations simulated by MD and native ligand structures is less than 3 Å. The above procedure results in a dataset containing 5,692 complexes with 46,235 holo-ligand conformations and corresponding apo structures. More details can be found in App. A.

Baselines. We compare our models with three representative baselines for SBDD: **Pocket2Mol** (Peng et al., 2022) generate 3D molecules by *sequentially* placing atoms around a given protein pocket; **TargetDiff** (Guan et al., 2023) generates atom coordinates and atom types based on a diffusion model and bonds are determined with a post-processing algorithm; **IPDiff** (Huang et al., 2023) incorporated protein-ligand interaction priors into both the forward and reverse processes to enhance the diffusion models. Since diffusion models require the number of atoms in the ligand molecule as input, we align TargetDiff and IPDiff with our methods based on the number of ligand atoms, denoting them as **TargetDiff*** and **IPDiff***. We also compare our methods on the ability of pocket conformation sampling with two baselines: a simple method that injected appropriate noise into

Table 2: Performance of SBDD methods with rigid pocket inputs on apo/our pockets.

	Vina Score (↓)	QED (↑)	SA (↑)	Linpiski (↑)	logP	High Affi. (↑)	Comp. Rate (↑)
Pocket2Mol	-5.50±1.25	0.54±0.12	0.83±0.10	1.70±1.52	4.98±0.14	28.6%	N/A
Pocket2Mol + Our Pocket	-5.92±0.88	0.57±0.07	0.88±0.10	2.09±1.24	5.00±0.00	28.6%	N/A
TargetDiff	-5.09±8.81	0.42±0.18	0.53±0.13	3.20±2.39	4.32±0.81	44.0%	68.2%
TargetDiff + Our Pocket	-9.00±3.19	0.44±0.18	0.53±0.14	3.82±2.29	4.22±0.91	61.2%	79.6%
TargetDiff*	-5.53±4.09	0.39±0.21	0.55±0.15	3.02±2.75	4.11±1.10	45.7%	62.4%
TargetDiff* + Our Pocket	-7.82±3.50	0.48±0.22	0.58±0.14	3.65±2.87	4.14±1.09	51.0%	79.72%
IPDiff	-7.55±5.59	0.38±0.17	0.50±0.14	4.10±0.77	5.07±2.94	51.0%	67.8%
IPDiff + Our Pocket	-11.04±3.76	0.40±0.16	0.46±0.15	3.84±0.74	6.97±3.33	83.7%	83.4%
IPDiff*	-6.23±5.26	0.40±0.20	0.55±0.15	3.94±1.00	5.04±3.34	49.5%	67.3%
IPDiff* + Our Pocket	-9.71±3.66	0.42±0.16	0.52±0.13	4.00±0.83	5.92±3.67	81.6%	82.1%

Figure 4: Distribution of differences in protein-ligand non-covalent interaction numbers of apo/our pockets and ligands designed by TargetDiff from those of ground-truth holo-ligand complexes.

apo structures; **Str2Str** (Lu et al., 2024a) that repurposed the protein backbone generation model, FrameDiff (Yim et al., 2023b), for protein conformation sampling by first injecting noise into apo structures and then denoising by diffusion models.

Evaluation. We select 50 complexes that have no overlap with the training set as the test set. We evaluate both the generated ligand molecules and the pocket conformations. For ligand molecules, we evaluate the binding affinity with AutoDock Vina (Eberhardt et al., 2021). There are three modes in AutoDock Vina: "vina_score_only", "vina_minimize", and "vina_dock". We use "vina_minimize" as reported **Vina Score** because this mode performs slight local structure energy minimization without disregarding the generated molecular conformations before estimation. We find an issue with the Vina Score for the complex 6SD9, so we exclude it from the 50 test samples. For each test target, we generate 100 molecules and select the one with the best Vina Score as the final design. For a fair comparison, all methods are provided with apo pockets as input. We collect the designed ligand molecule of all the test

Figure 5: Cover Ratio and minimum RMSD against holo states along the number of samples.

targets and report the mean and standard derivation of Vina Score and the following molecular properties: drug-likeness **QED** (Bickerton et al., 2012), synthesizability **SA** (Ertl & Schuffenhauer, 2009), the octanol-water partition coefficient **logP** (values ranging from -0.4 to 5.6 indicate good drug candidates) (Ghose et al., 1999), number of molecules that obeys Lipinski's rule of five **Lipinski** (Lipinski et al., 2012), the ratio of design molecules that exhibit higher binding affinity than the reference ligand in the test set **High Affi.** (High Affinity). We also report the ratio of generated molecules that are valid in valency and form a single connected graph as **Comp. Rate** (complete rate) for the diffusion-based methods. Since autoregressive models filter out the invalid entities during sampling and always form a connected graph, we do not report their Comp. Rate. For pocket conformation, we compute the minimum RMSD between the generated pocket conformation and ground-truth holo conformations for each target and report the average value over all the targets.

Figure 6: Distribution of apo / holo / our pocket volumes and Jensen-Shannon divergence (JSD) between apo / our and holo volumes.

Figure 7: Visualization of the protein-ligand non-covalent interactions of molecules generated by TargetDiff and apo (left) / pockets refined by our methods (right). Only interacted residues are visualized.

Figure 8: Examples of ligands and holo pockets generated by our model. The green surfaces are the holo pockets and the white surfaces with transparency are the apo pockets.

We compute the maximum RMSD between holo conformations for each complex, whose average is 1.42 Å. A ground-truth holo conformation is considered covered when at least one generated pocket conformation has an RMSD less than 1.42 Å against it. We compute the ratio of covered holo conformations for each target and report the average of this value over all the targets as **Cover Ratio**. We also compute the pocket volume using POcket Volume MEasurer 3 (POVME 3) (Wagner et al., 2017) and compare the distribution of volumes between apo/our pockets and ground-truth holo pockets. To further test the generated pocket conformations, for each target, we select the predicted pocket conformation corresponding to the designed ligand molecule with the best Vina Score among 100 candidates as "our pocket". We then use TargetDiff to design ligand molecules for "our pocket", summarize the properties of the designed molecules, and also profile the protein-ligand interactions using Protein-Ligand Interaction Profiler (PLIP) (Salentin et al., 2015).

Main Results. We report the properties of designed ligand molecules in Table 1. The molecules designed by our method show high binding affinity and also exhibit satisfactory drug-likeness and synthesizability. The performance of the baselines might be affected by the apo structures, which may not be suitable for designing a binding ligand. Fig. 5 shows the Cover Ratio and minimum RMSD against holo states along the number of samples. DYNAMICFLOW-ODE shows the best performance in RMSD, while DYNAMICFLOW-SDE shows the best performance in Cover Ratio due to the diversity enhanced by SDEs. Str2Str performs even worse than the naive perturbation baseline, possibly because it is designed for whole proteins rather than pockets and does not use sequence information as our methods do. Fig. 6 show the distribution of apo/holo/our pocket volumes. Our pocket volume distribution more closely resembles holo pockets than apo pockets. Table 2 shows that our refined pocket conformation can effectively improve the performance of SBDD methods with rigid pocket inputs. Fig. 4 shows the distribution in number differences of NCIs of apo/our pockets and molecules designed by Targetdiff (see an example in Fig. 7) against those of holo pockets along with the mean of differences in NCI numbers. These results demonstrate that our method effectively transforms apo states into holo-like states. Examples of generated examples are shown in Fig. 8 and App. E. More ablation studies can be found in App. D.

5 CONCLUSION

In this work, we introduce a generative modeling approach, DYNAMICFLOW, effectively transforming pockets from apo to holo states and generating ligand molecules simultaneously. Our method uncovers promising ligands and provides enhanced inputs for traditional drug discovery, advancing practical applications in the field. Our research lays the groundwork for integrating protein pocket dynamics into structure-based drug design, with future progress expected.

REFERENCES

Michael Samuel Albergo and Eric Vanden-Eijnden. Building normalizing flows with stochastic interpolants. In *The Eleventh International Conference on Learning Representations*, 2022.

Amy C Anderson. The process of structure-based drug design. *Chemistry & biology*, 10(9):787–797, 2003.

G Richard Bickerton, Gaia V Paolini, Jérémy Besnard, Sorel Muresan, and Andrew L Hopkins. Quantifying the chemical beauty of drugs. *Nature chemistry*, 4(2):90–98, 2012.

David D Boehr, Ruth Nussinov, and Peter E Wright. The role of dynamic conformational ensembles in biomolecular recognition. *Nature chemical biology*, 5(11):789–796, 2009.

Avishek Joey Bose, Tara Akhound-Sadegh, Guillaume Huguet, Killian Fatras, Jarrid Rector-Brooks, Cheng-Hao Liu, Andrei Cristian Nica, Maksym Korablyov, Michael Bronstein, and Alexander Tong. Se(3)-stochastic flow matching for protein backbone generation. In *The International Conference on Learning Representations (ICLR)*, 2024.

Andrew Campbell, Jason Yim, Regina Barzilay, Tom Rainforth, and Tommi Jaakkola. Generative flows on discrete state-spaces: Enabling multimodal flows with applications to protein co-design. In *Forty-first International Conference on Machine Learning*, 2024.

David A Case, H Metin Aktulga, Kellon Belfon, Ido Ben-Shalom, Scott R Brozell, David S Cerutti, Thomas E Cheatham III, Vinícius Wilian D Cruzeiro, Tom A Darden, Robert E Duke, et al. *Amber 2021*. University of California, San Francisco, 2021.

Ricky TQ Chen and Yaron Lipman. Riemannian flow matching on general geometries. *arXiv preprint arXiv:2302.03660*, 2023.

Peter JA Cock, Tiago Antao, Jeffrey T Chang, Brad A Chapman, Cymon J Cox, Andrew Dalke, Iddo Friedberg, Thomas Hamelryck, Frank Kauff, Bartek Wilczynski, et al. Biopython: freely available python tools for computational molecular biology and bioinformatics. *Bioinformatics*, 25(11):1422, 2009.

UniProt Consortium. Uniprot: a worldwide hub of protein knowledge. *Nucleic acids research*, 47 (D1):D506–D515, 2019.

Valentin De Bortoli, Emile Mathieu, Michael Hutchinson, James Thornton, Yee Whye Teh, and Arnaud Doucet. Riemannian score-based generative modelling. *Advances in Neural Information Processing Systems*, 35:2406–2422, 2022.

Jerome Eberhardt, Diogo Santos-Martins, Andreas F Tillack, and Stefano Forli. Autodock vina 1.2. 0: New docking methods, expanded force field, and python bindings. *Journal of chemical information and modeling*, 61(8):3891–3898, 2021.

RA Engh and R Huber. Structure quality and target parameters. 2012.

Peter Ertl and Ansgar Schuffenhauer. Estimation of synthetic accessibility score of drug-like molecules based on molecular complexity and fragment contributions. *Journal of cheminformatics*, 1(1):1–11, 2009.

Itai Gat, Tal Remez, Neta Shaul, Felix Kreuk, Ricky TQ Chen, Gabriel Synnaeve, Yossi Adi, and Yaron Lipman. Discrete flow matching. *arXiv preprint arXiv:2407.15595*, 2024.

Arup K Ghose, Vellarkad N Viswanadhan, and John J Wendoloski. A knowledge-based approach in designing combinatorial or medicinal chemistry libraries for drug discovery. 1. a qualitative and quantitative characterization of known drug databases. *Journal of combinatorial chemistry*, 1(1): 55–68, 1999.

Jiaqi Guan, Wesley Wei Qian, Xingang Peng, Yufeng Su, Jian Peng, and Jianzhu Ma. 3d equivariant diffusion for target-aware molecule generation and affinity prediction. In *International Conference on Learning Representations*, 2023.

Jiaqi Guan, Xiangxin Zhou, Yuwei Yang, Yu Bao, Jian Peng, Jianzhu Ma, Qiang Liu, Liang Wang, and Quanquan Gu. Decompdiff: diffusion models with decomposed priors for structure-based drug design. *arXiv preprint arXiv:2403.07902*, 2024.

Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. *Advances in neural information processing systems*, 33:6840–6851, 2020.

Chin-Wei Huang, Milad Aghajohari, Joey Bose, Prakash Panangaden, and Aaron C Courville. Riemannian diffusion models. *Advances in Neural Information Processing Systems*, 35:2750–2761, 2022.

Yufei Huang, Odin Zhang, Lirong Wu, Cheng Tan, Haitao Lin, Zhangyang Gao, Siyuan Li, Stan Li, et al. Re-dock: Towards flexible and realistic molecular docking with diffusion bridge. *arXiv preprint arXiv:2402.11459*, 2024.

Zhilin Huang, Ling Yang, Xiangxin Zhou, Zhilong Zhang, Wentao Zhang, Xiawu Zheng, Jie Chen, Yu Wang, CUI Bin, and Wenming Yang. Protein-ligand interaction prior for binding-aware 3d molecule diffusion models. In *The Twelfth International Conference on Learning Representations*, 2023.

Bowen Jing, Gabriele Corso, Jeffrey Chang, Regina Barzilay, and Tommi Jaakkola. Torsional diffusion for molecular conformer generation. *Advances in Neural Information Processing Systems*, 35:24240–24253, 2022.

John Jumper, Richard Evans, Alexander Pritzel, Tim Green, Michael Figurnov, Olaf Ronneberger, Kathryn Tunyasuvunakool, Russ Bates, Augustin Žídek, Anna Potapenko, et al. Highly accurate protein structure prediction with alphafold. *nature*, 596(7873):583–589, 2021.

Masha Karelina, Joseph J Noh, and Ron O Dror. How accurately can one predict drug binding modes using alphafold models? *Elife*, 12:RP89386, 2023.

Greg Landrum, Paolo Tosco, Brian Kelley, sriniker, gedeck, NadineSchneider, Riccardo Vianello, Ric, Andrew Dalke, Brian Cole, AlexanderSavelyev, Matt Swain, Samo Turk, Dan N, Alain Vaucher, Eisuke Kawashima, Maciej Wójcikowski, Daniel Probst, guillaume godin, David Cosgrove, Axel Pahl, JP, Francois Berenger, strets123, JLVarjo, Noel O'Boyle, Patrick Fuller, Jan Holst Jensen, Gianluca Sforna, and DoliathGavid. rdkit/rdkit: 2020_03_1 (q1 2020) release, March 2020. URL https://doi.org/10.5281/zenodo.3732262.

Byungkook Lee and Frederic M Richards. The interpretation of protein structures: estimation of static accessibility. *Journal of molecular biology*, 55(3):379–IN4, 1971.

Jin Sub Lee and Philip M Kim. Flowpacker: Protein side-chain packing with torsional flow matching. *bioRxiv*, pp. 2024–07, 2024.

Joongwon Lee, Wonho Zhung, and Woo Youn Kim. NCIDiff: Non-covalent interaction-generative diffusion model for improving reliability of 3d molecule generation inside protein pocket. In *ICML 2024 AI for Science Workshop*, 2024. URL https://openreview.net/forum?id=67qJwCsOMB.

Jiahan Li, Chaoran Cheng, Zuofan Wu, Ruihan Guo, Shitong Luo, Zhizhou Ren, Jian Peng, and Jianzhu Ma. Full-atom peptide design based on multi-modal flow matching. *arXiv preprint arXiv:2406.00735*, 2024.

Haitao Lin, Yufei Huang, Meng Liu, Xuanjing Li, Shuiwang Ji, and Stan Z. Li. Diffbp: Generative diffusion of 3d molecules for target protein binding, 2022.

Christopher A Lipinski, Franco Lombardo, Beryl W Dominy, and Paul J Feeney. Experimental and computational approaches to estimate solubility and permeability in drug discovery and development settings. *Advanced drug delivery reviews*, 64:4–17, 2012.

Yaron Lipman, Ricky TQ Chen, Heli Ben-Hamu, Maximilian Nickel, and Matthew Le. Flow matching for generative modeling. In *The Eleventh International Conference on Learning Representations*, 2022.

Guan-Horng Liu, Arash Vahdat, De-An Huang, Evangelos A Theodorou, Weili Nie, and Anima Anandkumar. I^{2}sb: Image-to-image schrödinger bridge. *arXiv preprint arXiv:2302.05872*, 2023.

Meng Liu, Youzhi Luo, Kanji Uchino, Koji Maruhashi, and Shuiwang Ji. Generating 3d molecules for target protein binding. *arXiv preprint arXiv:2204.09410*, 2022a.

Meng Liu, Youzhi Luo, Kanji Uchino, Koji Maruhashi, and Shuiwang Ji. Generating 3D molecules for target protein binding. In Kamalika Chaudhuri, Stefanie Jegelka, Le Song, Csaba Szepesvari, Gang Niu, and Sivan Sabato (eds.), *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Proceedings of Machine Learning Research*, pp. 13912–13924. PMLR, 17–23 Jul 2022b.

Tiqing Liu, Yuhmei Lin, Xin Wen, Robert N Jorissen, and Michael K Gilson. Bindingdb: a web-accessible database of experimentally determined protein–ligand binding affinities. *Nucleic acids research*, 35(suppl_1):D198–D201, 2007.

Xingchao Liu, Chengyue Gong, and Qiang Liu. Flow straight and fast: Learning to generate and transfer data with rectified flow. *arXiv preprint arXiv:2209.03003*, 2022c.

Jiarui Lu, Bozitao Zhong, Zuobai Zhang, and Jian Tang. Str2str: A score-based framework for zero-shot protein conformation sampling. In *The Twelfth International Conference on Learning Representations*, 2024a. URL https://openreview.net/forum?id=C4BikKsgmK.

Wei Lu, Jixian Zhang, Weifeng Huang, Ziqiao Zhang, Xiangyu Jia, Zhenyu Wang, Leilei Shi, Chengtao Li, Peter G Wolynes, and Shuangjia Zheng. Dynamicbind: Predicting ligand-specific protein-ligand complex structure with a deep equivariant generative model. *Nature Communications*, 15(1):1071, 2024b.

Shitong Luo, Jiaqi Guan, Jianzhu Ma, and Jian Peng. A 3d generative model for structure-based drug design. *Advances in Neural Information Processing Systems*, 34:6229–6239, 2021.

Dmitry I. Nikolayev and Tatjana I. Savyolov. Normal distribution on the rotation group so(3). *Textures and Microstructures*, 29:173236, Jan 1900. ISSN 1687-5397.

Shoghag Panjarian, Roxana E Iacob, Shugui Chen, John R Engen, and Thomas E Smithgall. Structure and dynamic regulation of abl kinases. *Journal of Biological Chemistry*, 288(8):5443–5450, 2013.

Xingang Peng, Shitong Luo, Jiaqi Guan, Qi Xie, Jian Peng, and Jianzhu Ma. Pocket2mol: Efficient molecular sampling based on 3d protein pockets. In *International Conference on Machine Learning*, pp. 17644–17655. PMLR, 2022.

Michael Plainer, Marcella Toth, Simon Dobers, Hannes Stark, Gabriele Corso, Céline Marquet, and Regina Barzilay. Diffdock-pocket: Diffusion for pocket-level docking with sidechain flexibility. In *NeurIPS 2023 Workshop on New Frontiers of AI for Drug Discovery and Development*, 2023.

Sebastian Salentin, Sven Schreiber, V Joachim Haupt, Melissa F Adasme, and Michael Schroeder. Plip: fully automated protein–ligand interaction profiler. *Nucleic acids research*, 43(W1):W443–W447, 2015.

Vıctor Garcia Satorras, Emiel Hoogeboom, and Max Welling. E (n) equivariant graph neural networks. In *International conference on machine learning*, pp. 9323–9332. PMLR, 2021.

Arne Schneuing, Yuanqi Du, Charles Harris, Arian Jamasb, Ilia Igashov, Weitao Du, Tom Blundell, Pietro Lió, Carla Gomes, Max Welling, et al. Structure-based drug design with equivariant diffusion models. *arXiv preprint arXiv:2210.13695*, 2022.

Arne Schneuing, Ilia Igashov, Thomas Castiglione, Michael M Bronstein, and Bruno Correia. Towards structure-based drug design with protein flexibility. In *ICLR 2024 Workshop on Generative and Experimental Perspectives for Biomolecular Design*, 2024.

Woody Sherman, Tyler Day, Matthew P Jacobson, Richard A Friesner, and Ramy Farid. Novel procedure for modeling ligand/receptor induced fit effects. *Journal of medicinal chemistry*, 49 (2):534–553, 2006.

Yuyang Shi, Valentin De Bortoli, Andrew Campbell, and Arnaud Doucet. Diffusion schrödinger bridge matching. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023. URL https://openreview.net/forum?id=qy07OHsJT5.

Till Siebenmorgen, Filipe Menezes, Sabrina Benassou, Erinc Merdivan, Kieran Didi, André Santos Dias Mourão, Radosław Kitel, Pietro Liò, Stefan Kesselheim, Marie Piraud, et al. Misato: machine learning dataset of protein–ligand complexes for structure-based drug discovery. *Nature Computational Science*, pp. 1–12, 2024.

Temple F Smith, Michael S Waterman, et al. Identification of common molecular subsequences. *Journal of molecular biology*, 147(1):195–197, 1981.

Yang Song, Jascha Sohl-Dickstein, Diederik P Kingma, Abhishek Kumar, Stefano Ermon, and Ben Poole. Score-based generative modeling through stochastic differential equations. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=PxTIG12RRHS.

Alexander Tong, Nikolay Malkin, Kilian Fatras, Lazar Atanackovic, Yanlei Zhang, Guillaume Huguet, Guy Wolf, and Yoshua Bengio. Simulation-free schr\" odinger bridges via score and flow matching. *arXiv preprint arXiv:2307.03672*, 2023.

Sandor Vajda, Dmitri Beglov, Amanda E Wakefield, Megan Egbert, and Adrian Whitty. Cryptic binding sites on proteins: definition, detection, and druggability. *Current opinion in chemical biology*, 44:1–8, 2018.

David Van Der Spoel, Erik Lindahl, Berk Hess, Gerrit Groenhof, Alan E Mark, and Herman JC Berendsen. Gromacs: fast, flexible, and free. *Journal of computational chemistry*, 26(16):1701–1718, 2005.

Jeffrey R Wagner, Jesper Sørensen, Nathan Hensley, Celia Wong, Clare Zhu, Taylor Perison, and Rommie E Amaro. Povme 3.0: software for mapping binding pocket flexibility. *Journal of chemical theory and computation*, 13(9):4584–4592, 2017.

Ercheng Wang, Huiyong Sun, Junmei Wang, Zhe Wang, Hui Liu, John ZH Zhang, and Tingjun Hou. End-point binding free energy calculation with mm/pbsa and mm/gbsa: strategies and applications in drug design. *Chemical reviews*, 119(16):9478–9508, 2019.

Renxiao Wang, Xueliang Fang, Yipin Lu, Chao-Yie Yang, and Shaomeng Wang. The pdbbind database: methodologies and updates. *Journal of medicinal chemistry*, 48(12):4111–4119, 2005.

Joseph L Watson, David Juergens, Nathaniel R Bennett, Brian L Trippe, Jason Yim, Helen E Eisenach, Woody Ahern, Andrew J Borst, Robert J Ragotte, Lukas F Milles, et al. De novo design of protein structure and function with rfdiffusion. *Nature*, 620(7976):1089–1100, 2023.

Jincai Yang, Cheng Shen, and Niu Huang. Predicting or pretending: artificial intelligence for protein-ligand interactions lack of sufficiently large and unbiased datasets. *Frontiers in pharmacology*, 11:69, 2020.

Jason Yim, Andrew Campbell, Andrew Y. K. Foong, Michael Gastegger, José Jiménez-Luna, Sarah Lewis, Victor Garcia Satorras, Bastiaan S. Veeling, Regina Barzilay, Tommi Jaakkola, and Frank Noé. Fast protein backbone generation with se(3) flow matching, 2023a. URL https://arxiv.org/abs/2310.05297.

Jason Yim, Brian L Trippe, Valentin De Bortoli, Emile Mathieu, Arnaud Doucet, Regina Barzilay, and Tommi Jaakkola. Se (3) diffusion model with application to protein backbone generation. In *Proceedings of the 40th International Conference on Machine Learning*, pp. 40001–40039, 2023b.

Jason Yim, Andrew Campbell, Emile Mathieu, Andrew Y. K. Foong, Michael Gastegger, José Jiménez-Luna, Sarah Lewis, Victor Garcia Satorras, Bastiaan S. Veeling, Frank Noé, Regina Barzilay, and Tommi S. Jaakkola. Improved motif-scaffolding with se(3) flow matching, 2024. URL https://arxiv.org/abs/2401.04082.

Yangtian Zhang, Zuobai Zhang, Bozitao Zhong, Sanchit Misra, and Jian Tang. Diffpack: A torsional diffusion model for autoregressive protein side-chain packing. *Advances in Neural Information Processing Systems*, 36, 2024.

Zaixi Zhang and Qi Liu. Learning subpocket prototypes for generalizable structure-based drug design. In *International Conference on Machine Learning*, pp. 41382–41398. PMLR, 2023.

Zaixi Zhang, Yaosen Min, Shuxin Zheng, and Qi Liu. Molecule generation for target protein binding with structural motifs. In *The Eleventh International Conference on Learning Representations*, 2022.

Jintao Zhu, Zhonghui Gu, Jianfeng Pei, and Luhua Lai. Diffbindfr: an se (3) equivariant network for flexible protein–ligand docking. *Chemical Science*, 15(21):7926–7942, 2024.

A DATASETS DETAILS

A.1 INTRODUCTION OF MISATO DATASET

The limited availability of protein-ligand interaction data has significantly hindered the progress of artificial intelligence in biological domains (Yang et al., 2020). Most of existing datasets either lack molecular dynamics information relevant to protein-ligand interactions (Wang et al., 2005; Liu et al., 2007). The absence of kinetic information for proteins-ligands complexes makes it challenging for AI to fully capture and model these biological processes. The development of the MISATO dataset has, to some extent, alleviated the shortage of kinetic data for protein-molecule complexes.

The MISATO dataset contains the largest molecular dynamics simulation data to date for protein-ligand complexes, along with recalculated QM properties of small molecules. Our work utilizes the complex structures and the associated MD simulation results as the primary data source, with further processing to tailor the data for in-depth modeling.

The development of MISATO dataset is based on the PDBbind database (Wang et al., 2005) which contains around 20,000 complexes structures and experimental binding affinities measurement. A total of 19,443 complexes are collected from PDBBind for further processing. Some important properties during the binding process, such as the binding affinity and the interaction energy are recalculated. Most importantly, the MISATO dataset performs 10ns MD simulations for 16,972 protein-ligand complexes, with 8 ns of MD trajectory recorded. These extensive MD results can provide additional kinetic information in the protein-ligand interaction process which is crucial for drug discovery and design research (Vajda et al., 2018).

A.2 HOLO POCKET CONSTRUCTION

Holo Pocket Definition. We exclude the complexes in MISATO where the ligands are oligopeptides, resulting in a total of 12,695 different complexes MD data. To capture different binding pocket conformations from the MD simulation trajectories, we locate residues within a cutoff distance of 7 Å around each ligand and extract them from the 100-frame MD results. We then define the pocket as the union set of all extracted residues from each frame. To select representative holo-state pocket conformations that appear with higher probability in the interaction process, we cluster the 100-frame complexes conformations from the 8 ns MD simulations using GROMACS (Van Der Spoel et al., 2005), with an RMSD threshold of less than 1 Å between the heavy atoms of both the proteins and the ligands. We then retain the top 10 clusters (or fewer if the total number of clusters are smaller than 10) as different holo conformations in our training dataset. The statistics of clustered conformations and pockets are shown in Fig. 9.

Additionally, we refer to the MD trajectory analysis results of the complexes, including the buried solvent-accessible surface area (SASA) (Lee & Richards, 1971), the center-of-mass distance between ligands and receptors, $RMSD_{Ligand}$ (the root-mean-square deviation of the ligand after protein alignment with the native structure), and the molecular mechanics generalized Born surface area (MMGBSA) (Wang et al., 2019). These labels provide a global description of the dynamic properties of the complexes and can be used as evaluation metrics for the binding process. We use the record of $RMSD_{Ligand}$ in the following processing.

Figure 9: The statistics on the number of conformations (left) and the number of pocket residues (right) in our clustered complexes.

Structural File Alignment. The PDB files in the MISATO dataset contain unusual three-letter-code representations for residues. This is due to the requirement of the force field calculation, where it needs to consider the special states of amino acid such as protonation and deprotonation for a better simulation accuracy (Case et al., 2021). However, for the training data points in our structure-based drug design model, it is necessary to uniform the representations of residues with the 20 types of three-letter codes for standard amino acids. Consequently, we correct the CYX (Cystine), which denotes the CYS (Cysteine) that forms a disulfide bond with another CYS, and the HIE, which represents the default protonation state of HIS (Histidine) in Amber's pre-processing (Case et al., 2021).

We also examine the atom names within residues and find that some atoms in ASP, GLU, PHE, TRP, TYR occasionally have inconsistent atom naming, which could lead to mismatch in atom-level alignment. Additionally, the Amber adds terminal cappings for the missing residues before MD simulations, affecting atom naming in N-terminus and C-terminus residues. These naming issues have been corrected in our processed holo-pocket data. Finally, the residues of all holo proteins are idealized with determined bond lengths and angles according to Engh & Huber (2012).

A.3 Apo Pocket Construction

Apo Protein Prediction. In order to obtain the apo-pocket structures as the input of our model, we consider the AlphaFold2-predicted (Jumper et al., 2021) structures as apo-like conformations and extract the corresponding pocket residues to generate apo-like pockets.

One challenge of folding structures directly from current sequences is the lack of chain annotations in the original MISATO files, which causes residues to be indexed continuously from start to finish. This can lead to incorrect folding structures during single-chain folding. Moreover, missing residues in PDB records can further decrease the prediction accuracy of folding models.

Instead, we retrieve AlphaFold2-predicted structures from the AlphaFold Protein Structure Database[1], where proteins are identified using UniProt IDs (Consortium, 2019). We perform ID mapping from Protein Data Bank (PDB)[2] to UniProt using the mapping tools provided by the UniProt API. In total, we successfully map 12,695 PDB IDs to 13,775 UniProt IDs, with 203 PDB IDs failing to find associated UniProt records. Among the successful mappings, 991 entries lack AlphaFold2-predicted structures in the database. Finally, we download AlphaFold2-predicted structures for 2,639 unique proteins and align these structures with the corresponding MISATO holo proteins.

Apo Pocket Alignment. To identify the pocket residue indices in apo proteins, we first extract sequences from both the MISATO PDB files and the AlphaFold2-predicted structures, then perform sequence alignment to establish residue index-mapping relationships. We use the Bio.pairwise2 module with the Smith–Waterman algorithm (Smith et al., 1981) for local sequence alignment (Cock et al., 2009). Using the residue index-mapping results, we extract the aligned residues from the apo-protein files to generate what we refer to as apo pockets. Through this workflow, we successfully obtain 7,528 atom-level aligned apo pockets. Alignment failures are primarily due to missing residues, mutations, and aligning sequences for multimers where the pocket consists of residues from different chains. In our curated dataset, the residues forming the pocket all originate from a single chain. Finally, the residues of all holo proteins are idealized with determined bond lengths and angles according to Engh & Huber (2012).

A.4 Ligand Data Processing

The $\text{RMSD}_{\text{Ligand}}$ is used to evaluate the conformational stability of complexes during MD simulations. To ensure the reliability of MD results for our training data, we filter the clustered holo structures based on the average $\text{RMSD}_{\text{Ligand}}$ over the 100-frame MD simulation results. A threshold of 3 Å is applied, resulting in a selection of 5,692 holo and apo structures for our training dataset. Additionally, we use RDKit (Landrum et al., 2020) to recalculate the bond connections and bond types in ligands to ensure that all ligands can be successfully loaded and featurized.

The protein-ligand complex conformations in our training dataset count for 46,235. The distribution of $\text{RMSD}_{\text{Ligand}}$ and the number of remaining complexes after each key processing step are illustrated in Fig. 10.

---

[1] https://alphafold.ebi.ac.uk
[2] https://www.rcsb.org/

Figure 10: Left: Statistics of $RMSD_{Ligand}$ for complexes in MISATO; Right: Statistics on dataset size after each processing step. (A-B) Filtering out complexes of where ligands are peptides; (B-C): Sequence alignment and apo-pocket extraction; (C-D): Filtering conformation ensembles with $RMSD_{Ligand}$ smaller than 3 Å.

A.5 VISUALIZATIONS OF DATASET

We provide visualizations of apo pockets and holo conformations from our processed dataset in Fig. 13. In each row, the left figure shows the apo pocket and the right two figures are different holo pockets with the same ligand. We also visualize the main chain and side chains of residues surrounding the ligand. Additionally, we evaluate the ligands in our dataset with QED, SA, logP, Lipinski and their binding affinity with apo and holo pockets using vina_score and vina_min. The results are presented in Fig. 11 and Fig. 12.

Figure 11: The distribution of molecular properties (QED, SA, logP, and Lipinski) for ligands in our dataset.

Figure 12: The distribution of vina_score_only and vina_min of apo/holo complexes in our dataset.

Figure 13: Examples of apo pockets and holo complexes from our processed dataset. The left yellow regions represent the apo pockets in the form of protein surfaces. The right two green regions show different holo conformations of the same proteins and ligands. The PDB IDs for these examples are 3FUP, 3DZ4, 3A3Y, 2E2B, 1PMU, 1FQ8, and 5TT7.

B ALL ATOM COORDINATES COMPUTING

We adopt a coordinates computing and updating method similar to those employed in previous works (Campbell et al., 2024; Jumper et al., 2021; Yim et al., 2023b). The residue-specific frames are first constructed to describe the idealized atom positions in every type of amino acid. Then we will predict the backbone and side chain frames update and map the updated frames back to atom coordinates. We will explain the details of this process in the following paragraphs.

Backbone Parameterization. To simplify the expressions, we specify that all subsequent expressions refer to the residue at index i. We begin by constructing the frame centered at C_α for every residue using their position of C_α, C and N, represented by bold letters. The residues are idealized with determined bond lengths and angles according to Engh & Huber (2012). Based on this setting, the rigid frame is built with the Gram-Schmidt process:

$$\mathbf{v}_1 = \mathbf{C} - \mathbf{C}_\alpha, \qquad \mathbf{v}_2 = \mathbf{N} - \mathbf{C}_\alpha, \qquad \mathbf{e}_1 = \mathbf{v}_1/\|\mathbf{v}_1\|,$$
$$\mathbf{u}_2 = \mathbf{v}_2 - \mathbf{e}_1(\mathbf{e}_1^\top \mathbf{v}_2), \qquad \mathbf{e}_2 = \mathbf{u}_2/\|\mathbf{u}_2\|, \qquad \mathbf{e}_3 = \mathbf{e}_1 \times \mathbf{e}_2. \tag{27}$$

Then we can generate backbone amino acid frame $T_0 = (\mathbf{t}_0, \mathbf{r}_0)$ with $\mathbf{t}_0 = \mathbf{C}_\alpha = \mathbf{0}$ and $\mathbf{r}_0 = \text{concat}(\mathbf{e}_1, \mathbf{e}_2, \mathbf{e}_3) = \mathbf{I}$.

Backbone Frame Update. According to Jumper et al. (2021), the rotation and translation of backbone are expressed using a predicted quaternion (a, b, c, d) and vector $\mathbf{t}$. The rotation matrix $\mathbf{r}$ is calculated from the predicted quaternion as follows:

$$\mathbf{r} = \begin{pmatrix} a^2 + b^2 - c^2 - d^2 & 2bc - 2ad & 2bd + 2ac \\ 2bc + 2ad & a^2 - b^2 + c^2 - d^2 & 2cd - 2ab \\ 2bd - 2ac & 2cd + 2ab & a^2 - b^2 - c^2 + d^2 \end{pmatrix}. \tag{28}$$

Note that the quaternion need normalization before the calculation of $\mathbf{r}$. The backbone frame update can thus be expressed as $T_{bb} = (\mathbf{t}, \mathbf{r})$.

The position of the O atom in the backbone is constrained to a circle that rotates around the x-axis (defined by C_α-C bond) with the C-O bond. We predict the torsion angle of the backbone $\chi_0 = [\chi_{01}, \chi_{02}] \in \text{SO}(2)$ that determines the position of the O atom and calculate the rotation with:

$$\mathbf{r}_x^{\chi_0} = \begin{pmatrix} 1 & 0 & 0 \\ 0 & \chi_{01} & -\chi_{02} \\ 0 & \chi_{02} & \chi_{01} \end{pmatrix}, \tag{29}$$

where $\|(\chi_{01})^2 + (\chi_{02})^2\| = 1$, the C-O bond length which defines the translation $\mathbf{t}_{\chi_0}$ is specified at 1.23 Å. Using $T_{\chi_0} = (\mathbf{t}_{\chi_0}, \mathbf{r}^{\chi_0})$ with backbone frame update, we can update the position of the O atom in backbone.

FrameToAtom Mapping. The updating of full atom positions involves the backbone rotation and translation with side-chain torsion $\alpha = (\chi_1, \chi_2, \chi_3, \chi_4)$. For each torsion angle, an additional side-chain frame is built to ensure that the torsion occurs around the x-axis within the current frame (Jumper et al., 2021). The definitions of the side-chain torsion angles for the 20 types of amino acids are shown in Table 3. The side-chain frames are updated hierarchically as follows:

$$T_1 = T_{bb} \circ T_{(\chi_1 \to bb)}^{\mathbf{a}} \circ \mathbf{r}_x^{\chi_1},$$
$$T_2 = T_1 \circ T_{(\chi_2 \to \chi_1)}^{\mathbf{a}} \circ \mathbf{r}_x^{\chi_2},$$
$$T_3 = T_2 \circ T_{(\chi_3 \to \chi_2)}^{\mathbf{a}} \circ \mathbf{r}_x^{\chi_3},$$
$$T_4 = T_3 \circ T_{(\chi_4 \to \chi_3)}^{\mathbf{a}} \circ \mathbf{r}_x^{\chi_4},$$
$$\mathbf{r}_x^{\alpha} = \begin{pmatrix} 1 & 0 & 0 \\ 0 & \alpha_1 & -\alpha_2 \\ 0 & \alpha_2 & \alpha_1 \end{pmatrix}. \tag{30}$$

Here, $T_{(\chi_1 \to bb)}^{\mathbf{a}}$ denotes the transformation from the χ_1 frame to the backbone frame for an idealized amino acid of type $\mathbf{a}$. The same hierarchical updating process is applied from χ_1 to χ_4. $\mathbf{r}_x^{\alpha}$ represents the rotation of the four types of torsion angles around x-axis where $\|(\alpha_1)^2 + (\alpha_2)^2\| = 1$. Using the

Table 3: Definition of the torsion angles (χ_1, χ_2, χ_3, χ_4) and their corresponding rigid groups for the 20 types of residues. We frame the torsion angles that are π-symmetric and list the required torsion angles to fix the side-chain atom positions.

Residue Type	χ_1	χ_2	χ_3	χ_4	Atom position fixed by
ALA (A)	-	-	-	-	-
ARG (R)	N, C$^\alpha$, C$^\beta$, C$^\gamma$	C$^\alpha$, C$^\beta$, C$^\gamma$, C$^\delta$	C$^\beta$, C$^\gamma$, C$^\delta$, N$^\epsilon$	C$^\gamma$, C$^\delta$, N$^\epsilon$, C$^\zeta$	$\chi_1, \chi_2, \chi_3, \chi_4$
ASN (N)	N, C$^\alpha$, C$^\beta$, C$^\gamma$	C$^\alpha$, C$^\beta$, C$^\gamma$, O$^{\delta1}$	-	-	χ_1, χ_2
ASP (D)	N, C$^\alpha$, C$^\beta$, C$^\gamma$	$\boxed{\text{C}^\alpha, \text{C}^\beta, \text{C}^\gamma, \text{O}^{\delta1}}$	-	-	χ_1, χ_2
CYS (C)	N, C$^\alpha$, C$^\beta$, S$^\gamma$	-	-	-	χ_1
GLN (Q)	N, C$^\alpha$, C$^\beta$, C$^\gamma$	C$^\alpha$, C$^\beta$, C$^\gamma$, C$^\delta$	C$^\beta$, C$^\gamma$, C$^\delta$, O$^{\epsilon1}$	-	χ_1, χ_2, χ_3
GLU (E)	N, C$^\alpha$, C$^\beta$, C$^\gamma$	C$^\alpha$, C$^\beta$, C$^\gamma$, C$^\delta$	$\boxed{\text{C}^\beta, \text{C}^\gamma, \text{C}^\delta, \text{O}^{\epsilon1}}$	-	χ_1, χ_2, χ_3
GLY (G)	-	-	-	-	-
HIS (H)	N, C$^\alpha$, C$^\beta$, C$^\gamma$	C$^\alpha$, C$^\beta$, C$^\gamma$, N$^{\delta1}$	-	-	χ_1, χ_2
ILE (I)	N, C$^\alpha$, C$^\beta$, C$^{\gamma1}$	C$^\alpha$, C$^\beta$, C$^{\gamma1}$, C$^{\delta1}$	-	-	χ_1, χ_2
LEU (L)	N, C$^\alpha$, C$^\beta$, C$^\gamma$	C$^\alpha$, C$^\beta$, C$^\gamma$, C$^{\delta1}$	-	-	χ_1, χ_2
LYS (K)	N, C$^\alpha$, C$^\beta$, C$^\gamma$	C$^\alpha$, C$^\beta$, C$^\gamma$, C$^\delta$	C$^\beta$, C$^\gamma$, C$^\delta$, C$^\epsilon$	C$^\gamma$, C$^\delta$, C$^\epsilon$, N$^\zeta$	$\chi_1, \chi_2, \chi_3, \chi_4$
MET (M)	N, C$^\alpha$, C$^\beta$, C$^\gamma$	C$^\alpha$, C$^\beta$, C$^\gamma$, S$^\delta$	C$^\beta$, C$^\gamma$, S$^\delta$, C$^\epsilon$	-	χ_1, χ_2, χ_3
PHE (F)	N, C$^\alpha$, C$^\beta$, C$^\gamma$	$\boxed{\text{C}^\alpha, \text{C}^\beta, \text{C}^\gamma, \text{C}^{\delta1}}$	-	-	χ_1, χ_2
PRO (P)	N, C$^\alpha$, C$^\beta$, C$^\gamma$	C$^\alpha$, C$^\beta$, C$^\gamma$, C$^\delta$	-	-	-
SER (S)	N, C$^\alpha$, C$^\beta$, O$^\gamma$	-	-	-	χ_1
THR (T)	N, C$^\alpha$, C$^\beta$, O$^{\gamma1}$	-	-	-	χ_1
TRP (W)	N, C$^\alpha$, C$^\beta$, C$^\gamma$	C$^\alpha$, C$^\beta$, C$^\gamma$, C$^{\delta1}$	-	-	χ_1, χ_2
TYR (Y)	N, C$^\alpha$, C$^\beta$, C$^\gamma$	$\boxed{\text{C}^\alpha, \text{C}^\beta, \text{C}^\gamma, \text{C}^{\delta1}}$	-	-	χ_1, χ_2
VAL (V)	N, C$^\alpha$, C$^\beta$, C$^{\gamma1}$	-	-	-	χ_1

above frame transformations and updating rules, we can mapping the idealized atom positions from the frames to coordinates, also referred to as FrameToAtom in the main paragraph:

$$\hat{x}_{\mathbf{v}}^{\mathbf{a}} = \text{concat}_{f,\mathbf{v}'} \left((T_f \circ x_{f,\mathbf{v}'}^{\mathbf{a}}) \right), \tag{31}$$

where $\hat{x}_{\mathbf{v}}^{\mathbf{a}}$ is the updated atom position, $x_{f,\mathbf{v}'}^{\mathbf{a}}$ represents the idealized position of atom $\mathbf{v}$ in residue with amino acid type $\mathbf{a}$ under frame f defined by different rotations and translations in Eqs. (28) to (30).

C DEFINITION OF TORSION ANGLES

In Table 3, we present the compositions of all the side chain torsion angles in the 20 types of amino acids that are used to compute atomic coordinates. The side-chain torsion angles that show π-symmetric are highlighted with black boxes.

D ABLATION STUDIES

We perform ablation studies to verify the effect of interaction loss that is introduced in Section 3.2. The related results are reported in Table 4. The results demonstrate that the proposed interaction loss can effectively improve the performance of both ODE and SDE versions of DYNAMICFLOW, especially the binding affinity.

Table 4: Summary of properties of reference molecules and molecules generated by our model and the variants without interaction loss. ($\uparrow$) / ($\downarrow$) denotes a larger / smaller number is better.

	Vina Score ($\downarrow$)	QED ($\uparrow$)	SA ($\uparrow$)	Linpiski ($\uparrow$)	logP	High Affi. ($\uparrow$)	Comp. Rate ($\uparrow$)
DYNAMICFLOW-ODE	-7.28±1.98	0.53±0.20	0.61±0.14	3.13±2.62	4.45±0.81	51.0%	70.2%
w/o interaction loss	-6.76±1.39	0.54±0.22	0.60±0.15	3.20±2.48	4.36±0.93	37.4%	72.2%
DYNAMICFLOW-SDE	-7.65±1.59	0.53±0.15	0.53±0.17	4.34±2.58	4.25±0.90	52.5%	73.6%
w/o interaction loss	-7.00±1.15	0.48±0.21	0.56±0.16	1.35±3.54	4.06±1.48	43.4%	78.0%

E VISUALIZATION OF GENERATED SAMPLES

Visualization of Generated Complexes. Here, we list more examples of generated ligands and holo-like pockets in Fig. 14. The ligands demonstrate promising binding affinity, as indicated by their Vina Scores.

Figure 14: Examples of our generated ligands and corresponding holo pockets. The green surfaces are the holo pockets and the white surfaces with transparency are the apo pockets.

Visualization of Sampling Trajectories. We sample from the generation trajectories and illustrate the ligand generation process along with the conformational changes of the pocket in Fig. 15. The reference apo pockets are from 6SZJ (top) and 6UL8 (bottom). From left to right, the ligands are reconstructed from random noise, represented by the nodes. The apo pockets also undergo conformational changes, transitioning from the apo state to the holo state in response to the generated ligands.

Figure 15: Examples of our generation flow. The ligand is initialized at the CoM of the apo pocket in terms of random noise. The white node corresponds to the mask token of atom type.

F   EVALUATION ON POCKET VOLUME

We use POVME3 (Wagner et al., 2017) to estimate the volumes of generated pockets and make comparison with the volumes of apo and holo pockets. POVME3 is a receptor-centric method for pocket analysis. It defines pocket volume by occupying the surrounding region of the receptor with equidistant points. Points that are near or outside of receptor atoms are removed and the volume is calculated based on the remaining points. Following this approach, we define the pocket region as the spherical area with a 15 Å radius centered at the pocket's geometric center, excluding points within the van der Waals radius (plus the hydrogen atom radius) of receptor atoms. Compared with the apo pockets, our (randomly selected) generated pockets are more similar to the reference holo states with smaller volume differences. The results are shown in Table 5. We also show an example of the volume occupation of our generated pocket and the corresponding apo/holo pocket in Fig. 16.

Table 5: Volume difference between apo/our pockets and holo pockets.

	Avg. ± Std.	Med.
Apo states	83.84 ± 61.20	71.20
Our Pocket (DYNAMICFLOW-ODE)	**50.08 ± 35.05**	**41.75**
Our Pocket (DYNAMICFLOW-SDE)	68.56 ± 55.51	59.20

Holo Pocket
Volume = 267 Å³

Generated Pocket
Volume = 204 Å³

Apo Pocket
Volume = 117 Å³

Figure 16: Example of volume calculation from POVME3 using a 6 Åradius. We select the apo (purple) and holo (red) pocket from PDB file 6UDI, alongside the generated pocket (cyan). Compared to the apo pocket, our generated pocket more resembles the real holo structure in terms of pocket volume.

G BINDING AFFINITY EVALUATION CONSIDERING PROTEIN DYNAMICS

Incorporating molecular dynamics in evaluation is also important. However, relying on MD trajectory-based methods such as MMGBSA or MMPBSA (Wang et al., 2019) can be highly cumbersome. These approaches employ different solvation models and require extensive computational resources, with MD simulations often taking months to complete for thousands of systems. Therefore, as an alternative, we opt for a deep-learning-based approach for flexible docking and scoring to achieve reliable and scalable evaluation.

Specifically, for each generated ligand designed by the baselines and our methods, we employ DynamicBind (Lu et al., 2024b), a geometric deep generative model tailored for "dynamic docking", to generate 10 protein-ligand complex structures. DynamicBind also includes a model that predicts an "affinity" score, which estimates the negative logarithm of the binding affinity (A) in concentration units. We then calculate the weighted average of these predicted binding affinities to derive the final "affinity" score, where a higher "affinity" score indicates better binding potential.

For each target, we assess the affinity of a randomly selected generated ligand, the highest affinity among 10 generated ligands, and the average affinity across all 100 generated ligands. We report the mean, standard deviation, and median of these affinities across 50 targets. The results are summarized in Table 6.

Table 6: Binding affinity evaluation based on DynamicBind.

	Single		Best over 10		All	
	Avg. ± Std.	Med.	Avg. ± Std.	Med.	Avg. ± Std.	Med.
Pocket2Mol	3.64 ± 1.26	3.31	4.90 ± 1.15	4.81	5.70 ± 1.22	5.68
TargetDiff	6.00 ± 1.14	6.19	7.30 ± 0.70	7.46	7.81 ± 0.71	7.91
TargetDiff*	6.19 ± 0.97	6.38	7.16 ± 0.94	7.54	7.64 ± 0.73	7.79
IPDiff	6.15 ± 1.14	6.45	7.05 ± 0.79	7.18	7.68 ± 0.90	7.82
IPDiff*	5.96 ± 1.31	5.83	7.10 ± 1.09	7.14	7.63 ± 0.97	7.72
DYNAMICFLOW-ODE	**6.46 ± 1.00**	**6.69**	7.40 ± 0.94	7.62	7.91 ± 0.90	8.07
DYNAMICFLOW-SDE	6.21 ± 1.19	6.09	**7.53 ± 0.86**	**7.67**	**7.95 ± 0.83**	**8.12**

H INFERENCE TIME

We benchmark the inference time of baselines and our methods for generating 10 ligand molecules given the same pocket on 1 Tesla V100-SXM2-32GB. The default number of function evaluations (NFE) is 1000 for TargetDiff and IPDiff and 100 for our method.

As Table 7 shows, our methods are capable of generating high-quality ligands while simultaneously modeling protein dynamics at a fast speed, demonstrating a significant advantage in computational efficiency.

Table 7: Inference time of baselines and our methods for generating 10 ligand molecules.

	Time (s)	Default NFE
Pocket2Mol	980	N/A
TargetDiff	156	1000
TargetDiff*	154	1000
IPDiff	334	1000
IPDiff*	343	1000
DYNAMICFLOW-ODE	35	100
DYNAMICFLOW-SDE	36	100