Precise Regret Bounds for Log-loss via a Truncated Bayesian Algorithm

Abstract

We study sequential general online regression, known also as sequential probability assignments, under logarithmic loss when compared against a broad class of experts. We obtain tight, often matching, lower and upper bounds for sequential minimax regret, which is defined as the excess loss incurred by the predictor over the best expert in the class. After proving a general upper bound we consider some specific classes of experts from Lipschitz class to bounded Hessian class and derive matching lower and upper bounds with provably optimal constants. Our bounds work for a wide range of values of the data dimension and the number of rounds. To derive lower bounds, we use tools from information theory (e.g., Shtarkov sum) and for upper bounds, we resort to new "smooth truncated covering" of the class of experts. This allows us to find constructive proofs by applying a simple and novel truncated Bayesian algorithm. Our proofs are substantially simpler than the existing ones and yet provide tighter (and often optimal) bounds.

1 Introduction

In online learning and sequential probability assignments arising in information theory, portfolio optimization, and machine learning, the training algorithm consumes d dimensional data in rounds $t \in \{1, 2, \ldots, T\}$ and predicts the label $\hat{y}_t$ based on data received and labels observed so far. After prediction, the true label y_t is revealed and the loss $\ell(y_t, \hat{y}_t)$ is incurred. The (pointwise) *regret* is defined as the (excess) loss incurred by the algorithm over a class of experts, also called the hypothesis class.

More precisely, in each round $t \geq 1$ the learner obtains a d dimensional input/ feature vector $\mathbf{x}_t \in \mathbb{R}^d$. In addition to $\mathbf{x}_t$, the learner may use the past observations $(\mathbf{x}_r, y_r)$, $r < t$ to make a prediction $\hat{y}_t$ of true label. Therefore, the prediction can be written as $\hat{y}_t = \phi_t(y^{t-1}, \mathbf{x}^t)$, where y^{t-1} represents the labels in the past $t - 1$ rounds, $\mathbf{x}^t$ represents the input vectors in t rounds, and ϕ_t represents the strategy of the learner to obtain its prediction based on the past and current observations. Once a prediction is made, nature reveals the true label y_t and the learner incurs loss $\ell : \hat{\mathcal{Y}} \times \mathcal{Y} \to \mathbb{R}$, where $\hat{\mathcal{Y}}$ and $\mathcal{Y}$ are the prediction and true label domains respectively. Hereafter, we assume throughout $\hat{\mathcal{Y}} = [0, 1]$, $\mathcal{Y} = \{0, 1\}$ with logarithmic loss

$$\ell(\hat{y}_t, y_t) = -y_t \log(\hat{y}_t) - (1 - y_t) \log(1 - \hat{y}_t). \tag{1}$$

In regret analysis, we are interested in comparing the accumulated loss of the learner with that of the best strategy within a predefined class of predictors (experts) denoted by $\mathcal{H}$. More precisely, $\mathcal{H}$ is

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

a collection of predicting functions $h : \mathbb{R}^d \mapsto \hat{\mathcal{Y}}$ with input being $\mathbf{x}_t$ at time t. Therefore, given a learner $\phi_t, t > 0$ and $(y_t, \mathbf{x}_t)_{t=1}^T$ after T rounds the *pointwise regret* is defined as

$$R(\hat{y}^T, y^T, \mathcal{H}|\mathbf{x}^T) = \sum_{t=1}^T \ell(\hat{y}_t, y_t) - \inf_{h \in \mathcal{H}} \sum_{t=1}^T \ell(h(\mathbf{x}_t), y_t),$$

where $\hat{y}_t = \phi_t(y^{t-1}, \mathbf{x}^t)$. Observe that the first term above represents the accumulated loss incurred by the learning algorithm, while the second summation deals with the best prediction within $\mathcal{H}$. We highlight two useful perspectives on analyzing the regret next.

Fixed Design: This point of view studies the minimal regret for the worst realization of the label with the feature vector $\mathbf{x}^T$ known in advance. Suppose that the learner has a fixed strategy $\phi_t, t > 0$. Then, the *fixed design minimax regret* for a given $\mathbf{x}^T$ is defined as

$$r_T^*(\mathcal{H}|\mathbf{x}^T) = \inf_{\phi^T} \sup_{y^T} R(\phi^T, y^T, \mathcal{H}|\mathbf{x}^T). \tag{2}$$

Further, the fixed design *maximal* minimax regret is given by:

$$r_T^*(\mathcal{H}) = \sup_{\mathbf{x}^T} \inf_{\phi^T} \sup_{y^T} R(\phi^T, y^T, \mathcal{H}|\mathbf{x}^T). \tag{3}$$

Sequential Design: In this paper we mostly focus on the *sequential* or *agnostic* regret in which the optimization on regret is performed at each time t without knowing in advance $\mathbf{x}^T$ or y^T. Then the *sequential (maximal) minimax regret* is given by [23]:

$$r_T^a(\mathcal{H}) = \sup_{\mathbf{x}_1} \inf_{\hat{y}_1} \sup_{y_1} \cdots \sup_{\mathbf{x}_T} \inf_{\hat{y}_T} \sup_{y_T} R(\hat{y}^T, y^T, \mathcal{H}|\mathbf{x}^T). \tag{4}$$

In [37] it is shown that $r_T^a(\mathcal{H}) \geq r_T^*(\mathcal{H})$ for all $\mathcal{H}$. We will use $r_T^*(\mathcal{H})$ as our tool to derive lower bounds for $r_T^a(\mathcal{H})$.

Our main goal is to gain insights into the growth of sequential regret $r_T^a(\mathcal{H})$ for various classes $\mathcal{H}$ and to show how the structure of $\mathcal{H}$, as well as the relationship between d and T impact the precise growth of the regret. To see this more clearly, we briefly review regret in universal source coding.

Regrets in Information Theory. In universal compression, the dependence between regret and the reference class was intensively studied [9, 20, 26, 27, 31, 38, 39]. Here, there is no feature vector $\mathbf{x}^t$, and the dimension $d = 1$. A sequence y^T is generated by a source P that belongs to a class of sources $\mathcal{S}$, which can be viewed as the reference class $\mathcal{H}$ in online learning. The minimax regret for the logarithmic loss is given by [8, 30, 9]: $r_T^*(\mathcal{S}) = \min_Q \max_{y^T}[-\log Q(y^T) + \log \sup_{P \in \mathcal{S}} P(y^T)]$, where Q is the universal probability assignment approximating the unknown P. The main question is how the structure of $\mathcal{S}$ impacts the growth of the minimax regret. Let m denote the alphabet size (in online learning, we only consider $m = 2$). It is known [9, 20, 26, 27, 31, 38, 39] that for Markov sources of order r, regret grows as $m^r(m-1)/2 \log T$ for fixed m [26, 20, 27, 33], while in [33] minimax regret was analyzed for all ranges of m and T. For non-Markovian sources, the growth is super logarithmic. For example, for renewal sources of order r the regret is $\Theta(T^{r/(r+1)})$ [6] and the precise constant in front of the leading term is know for $r = 1$ [10]. However, it should be pointed out that [5, 1] studied the general classes of densities smoothly parameterized by a d-dimensional data to obtain general results for minimax regret that can be phrased as an online regret.

Main Contributions. Our main results are summarized in Table 1. One of the main contributions of this paper is the concept of a global sequential covering used to prove *constructively* general upper bounds on regret (Theorem 1). We establish Theorem 1 via a novel smooth truncation approach enabling us to find tight upper bounds that subsume the state-of-the-art results (e.g., [22, 3]) obtained non-algorithmically. In fact, Algorithm 2 developed in this paper achieves these bounds. Moreover, Theorem 1 provides optimal constants that are crucial to derive the best bounds in special cases discussed next. For general Lipschitz parametric class $\mathcal{H}$, in Theorem 2, we derive the upper bound $d \log(T/d) + O(d)$ for $T > d$. In Theorem 3, we show that the leading constant 1 (in front of

70 $d \log(T/d))$ is optimal for $T \gg d \log(T)$. Furthermore, we obtain the best constant for the leading
71 term $\frac{d}{2} \log(T/d)$ when the Hessian of $\log f$ is bounded for any function $f \in \mathcal{H}$ (see Theorem 4).
72 Then, we show in Theorem 5 that the constant $\frac{1}{2}$ in our bound is optimal for functions of the form
73 $f(\langle \mathbf{w}, \mathbf{x} \rangle)$, where $\mathbf{w} \in \mathbb{R}^d$ is the parameter of the function, $\langle \mathbf{w}, \mathbf{x} \rangle$ is the inner product in $\mathbb{R}^d$, $\mathbf{w}$ and
74 $\mathbf{x}$ are in a general ℓ_s-norm unite ball, and $T \gg d^{(s+2)/s}$. This result recovers all the lower bounds
75 in [29] obtained for logistic regression (however, the technique of [29] works for other functions with
76 bounded second derivatives, like the probit function). Lastly, when $d \geq T$, for a linear function of
77 the form $|\langle \mathbf{w}, \mathbf{x} \rangle|$ we show that the growth is at least $\Omega(T^{s/(s+1)})$ under ℓ_s ball and at most $\tilde{O}(T^{2/3})$
78 for ℓ_2 ball (see Theorem 6 and Example 2).

79 The main technique used in our paper (smooth truncation) is novel with other potential applications
80 (e.g., average minimax regret). Instead of the conventional approach for truncating only the values
81 close to $\{0, 1\}$, we truncate all values in $[0, 1]$ in a smooth way (see Lemma 4). This allows us
82 to obtain an upper bound via a simple truncated Bayesian algorithm. Our proofs are substantially
83 simpler (cf. [3]) yet provide tighter and often optimal bounds.

84 In summary, our main contributions are: (i) constructive proofs through a new smooth truncated
85 Bayesian algorithm; (ii) the novel concept of global sequential covering; (iii) lower and upper bounds
86 with optimal leading constants; and (iv) novel information-theoretic techniques for the lower bounds.

Table 1: Summary of results

Constrains	d v.s T	**Bounds**	**Comment**
General α cover $\mathcal{G}_\alpha$	N.A.	$r_T^a(\mathcal{H}) \leq \inf\limits_{0 < \alpha < 1} \{2\alpha T + \log|\mathcal{G}_\alpha|\}$	Theorem 1
General Lipschitz f	Any	$r_T^a(\mathcal{H}_f) \leq d \log\left(\frac{T}{d} + 1\right) + O(d)$	Theorem 2
under ℓ_s ball	$T \gg d \log T$	$r_T^a(\mathcal{H}_f) \geq d \log\left(\frac{T}{d}\right) - O(d \log \log T)$	Theorem 3
Bounded Hessian of $\log f$ under ℓ_2 ball	Any	$r_T^a(\mathcal{H}_f) \leq \frac{d}{2} \log\left(\frac{T}{d} + 1\right) + O(d)$	Theorem 4
$f(\langle \mathbf{w}, \mathbf{x} \rangle)$ with $f'(0) \neq 0$ under ℓ_s ball	$T \gg d^{(s+2)/s}$	$r_T^a(\mathcal{H}_f) \geq \frac{d}{2} \log\left(\frac{T}{d^{(s+2)/s}}\right) - O(d)$	Theorem 5
$|\langle \mathbf{w}, \mathbf{x} \rangle|$ under ℓ_s ball	$d \geq T$	$r_T^a(\mathcal{H}_f) \geq \frac{s+1}{s \cdot e} T^{s/(s+1)}$	Theorem 6
$|\langle \mathbf{w}, \mathbf{x} \rangle|$ under ℓ_2 ball	$d \geq T$	$\Omega(T^{2/3}) \leq r_T^a(\mathcal{H}_f) \leq \tilde{O}(T^{2/3})$	Example 2

87 **Related Work**   In this paper we study sequential minimax regret for general online regression
88 with logarithmic loss using tools of information theory, in particular universal source coding (lower
89 bounds) [1, 9, 17, 20, 25, 26, 27, 38] and sequential covering (upper bounds).

90 Most of the existing works in online regression deals with logistic regression. We first mention
91 the work of [12], who studied pointwise regret of logistic regression for the *proper* setting. Unlike
92 *improper* learning, studied in this paper, where feature $\mathbf{x}_t$ at time t is also available to the learner,
93 [12] showed that pointwise regret is $\Theta(T^{1/3})$ for $d = 1$ and $O(\sqrt{T})$ for $d > 1$. Furthermore, [16]
94 demonstrates that regret for logistic regression grows as $O(d \log T/d)$. This was further generalized
95 in [11]. These results were strengthened in [29], which also provides matching lower bounds. Precise
96 asymptotics for the fixed design minimax regret were recently presented in [13, 14].

97 Regret bounds under logarithmic loss for general expert class $\mathcal{H}$ was first investigated by Vovk under
98 the framework of mixable losses [15, 34]. In particular, Vovk showed that for finite class $\mathcal{H}$, the regret
99 growth is $\log|\mathcal{H}|$ via the *aggregating algorithm* (i.e., the Bayesian algorithm that we will discuss
100 below). We refer the reader to [4, Chapter 3.5, 3.6] and the references therein for more results on
101 this topic. Cesa-Bianchi and Lugosi [4] were the first to investigate log-loss under general (infinite)
102 expert class $\mathcal{H}$ [4, Chapter 9.10, 9.11], where they derived a general upper bound using the concept of
103 covering number and a two-stage prediction scheme. In particular, Cesa-Bianchi and Lugosi showed

104 that for Lipschitz parametric classes with values bounded away from $\{0, 1\}$, one can achieve a regret
105 bound of the form $d/2 \log(T/d)$. When the values are close to $\{0, 1\}$, they used a *hard* truncation
106 approach, which gives a sub-optimal bound of the form $2d \log(T/d)$. Moreover, the approach of [4]
107 only works for fixed design regret (or *simulatable* in their context). In [22], the authors extended the
108 result of [4, Chapter 9.10] to the sequential case via the machinery of sequential covering that was
109 established in [21]. However, [22] also used the same *hard* truncation as in [4] resulting in suboptimal
110 upper bounds. In [3], the authors obtained an upper bound similar to the upper bound presented in
111 Theorem 1 via the observation that the $\log$ function is self-concordance. In particular, this allows
112 them to resolve the tight bounds for non-parametric Lipschitz functions that map $[0, 1]^s \to [0, 1]$.
113 However, their bounds are proved *non-constructively*, i.e., the proof does not provide an algorithm
114 that achieves such bounds.

2 Problem Formulation and Preliminaries

116 We denote $\mathcal{X}$ as the input feature space and $\mathcal{H}$ as the concept class, which is a set of functions mapping
117 $\mathcal{X} \to [0, 1]$. We use an auxiliary set $\mathcal{W}$ to index $\mathcal{H}$. We say that a function g is *sequential* if it maps
118 $\mathcal{X}^* \to [0, 1]$, where $\mathcal{X}^*$ is set of all finite sequences with elements in $\mathcal{X}$. We denote $\mathcal{G}$ as a class of
119 *sequential* functions. If T is a time horizon, then for any $t \in [T]$, we write $\mathbf{x}^t = \{\mathbf{x}_1, \cdots, \mathbf{x}_t\}$ and
120 $y^t = \{y_1, \cdots, y_t\}$. We use standard asymptotic notation $f(t) = O(g(t))$ or $f(t) \ll g(t)$ if there
121 exists a constant C such that $f(t) \leq C g(t)$ for all $t \geq 0$.

122 The main objective of this paper is to study the growth of the sequential minimax regret $r_T^a(\mathcal{H})$ for
123 a large class of experts $\mathcal{H}$. We accomplish this goal using two different techniques. For the lower
124 bound, we precisely estimate the fixed design minimax regret $r_T^*(\mathcal{H}|\mathbf{x}^T)$ using the Shtarkov sum
125 [30], discussed next. For the upper bound, we construct a novel global cover set $\mathcal{G}$ of $\mathcal{H}$ and design a
126 new (truncated) Bayesian algorithm to find precise bounds with constants that are provably optimal.

127 **Lower Bounds.**   We investigate the lower bound of adversarial regret $r_T^a(\mathcal{H})$ by considering its
128 corresponding fixed design minimax regret $r_T^*(\mathcal{H}|\mathbf{x}^T)$ and $r_T^*(\mathcal{H}) = \max_{\mathbf{x}^T} r_T^*(\mathcal{H}|\mathbf{x}^T)$. We are able
129 to do this due to the recent result [37], which we quote next.

Lemma 1 (Wu et al., 2022). *Let $\mathcal{H}$ be any general hypothesis class and ℓ be any loss function. Then*
$$r_T^a(\mathcal{H}) \geq r_T^*(\mathcal{H}),$$
130 *and the inequality is strict for certain $\mathcal{H}$, and loss function ℓ.*

We establish precise growth of $r_T^*(\mathcal{H})$ by estimating the Shtarkov sum that was intensively analyzed
in information theory [30, 9] and recently applied in online learning [28, 13]. For the logarithmic
loss, the Shtarkov sum (conditioned on $\mathbf{x}^T$) is defined as follows [1]
$$S_T(\mathcal{H}|\mathbf{x}^T) \stackrel{\text{def}}{=} \sum_{y^T \in \{0,1\}^T} \sup_{h \in \mathcal{H}} P_h(y^T \mid \mathbf{x}^T),$$
131 where $P_h(y^T \mid \mathbf{x}^T) = \prod_{t=1}^{T} h(\mathbf{x}_t)^{y_t}(1 - h(\mathbf{x}_t))^{1-y_t}$ and we *interpret* $h(\mathbf{x}_t) = P(y_t = 1|\mathbf{x}_t)$. The
132 regret can be expressed in terms of the Shtarkov sum (see [13, Equation (6)] or [4, Theorem 9.1]) as
$$r_T^*(\mathcal{H}) = \sup_{\mathbf{x}^T} \log S_T(\mathcal{H}|\mathbf{x}^T). \tag{5}$$
133 It is known that the leading term in the Shtarkov sum for a large class of $\mathcal{H}$ is often independent
134 of $\mathbf{x}^T$ [29, 11, 13, 14]. Therefore, the Shtarkov sum often gives the leading growth of $r_T^*(\mathcal{H}|\mathbf{x}^T)$
135 independent of $\mathbf{x}^T$, which also suggests the leading growth of the agnostic regret $r_T^a(\mathcal{H})$.

136 **Upper Bounds.**   We now discuss our constructive approach to upper bounds. In the next section,
137 we present our Smooth truncated Bayesian Algorithm (Algorithm 2) that provides a constructive and
138 often achievable upper bound. Here we focus on some, mostly known, preliminaries.

139 Let $\mathcal{G}$ be any reference class map $\mathcal{X}^* \to [0, 1]$. Let $\mathcal{W}$ be an index set of $\mathcal{G}$ and μ be an arbitrary
140 finite measure over $\mathcal{W}$. The standard Bayesian predictor with prior μ is presented in Algorithm 1.
141 Based on this algorithm, we have the following two lemmas [4, Chapter 3.3] that are used to establish
142 most of the upper bounds in this paper. For completeness, we provide simple proofs in Appendix A.

---

[1]Note that the Starkov sum can be defined for any class of measures, however, here we only use the form for product measures.

Algorithm 1 Bayesian predictor

Input: Reference class $\mathcal{G} := \{g_w : w \in \mathcal{W}\}$ with index set $\mathcal{W}$ and prior μ over $\mathcal{W}$
 1: Set $p_w(y^0 \mid \mathbf{x}^0) = 1$ for all $w \in \mathcal{W}$.
 2: **for** $t = 1, \cdots, T$ **do**
 3:     Receive feature vector $\mathbf{x}_t$
 4:     Make prediction using the following equation:

$$\hat{y}_t = \frac{\int_{\mathcal{W}} g_w(\mathbf{x}^t) p_w(y^{t-1} \mid \mathbf{x}^{t-1}) \mathrm{d}\mu}{\int_{\mathcal{W}} p_w(y^{t-1} \mid \mathbf{x}^{t-1}) \mathrm{d}\mu}.$$

 5:     Receive label y_t
 6:     For all $w \in \mathcal{W}$, update: $p_w(y^t \mid \mathbf{x}^t) = e^{-\ell(g_w(\mathbf{x}^t), y_t)} p_w(y^{t-1} \mid \mathbf{x}^{t-1})$.
 7: **end for**

Lemma 2. *Let $\mathcal{G}$ be a collection of functions $g_w : \mathcal{X}^* \to [0, 1], w \in \mathcal{W}$. Let $\hat{y}_t$ be the Bayesian prediction rule as in Step 4 of Algorithm 1 with prior μ. Then, for any $\mathbf{x}^T$ and y^T we have*

$$\sum_{t=1}^{T} \ell(\hat{y}_t, y_t) \leq -\log \frac{\int_{\mathcal{W}} p_w(y^T \mid \mathbf{x}^T) \mathrm{d}\mu}{\int_{\mathcal{W}} 1 \mathrm{d}\mu},$$

where $p_w(y^T \mid \mathbf{x}^T) = e^{-\sum_{t=1}^{T} \ell(g_w(\mathbf{x}^t), y_t)}$ and ℓ is the log-loss as in equation (1).

The following lemma bounds the regret under log-loss of finite classes, which is well known.

Lemma 3. *For any finite class of experts $\mathcal{G}$, we have $r_T^a(\mathcal{G}) \leq \log |\mathcal{G}|$.*

3   Main Results

We start with a novel covering set called the *global sequential cover* that is different than the one used in [3]:

Definition 1 (Global sequential covering). *For any $\mathcal{H} \subset [0, 1]^{\mathcal{X}}$, we say that class $\mathcal{G}$ of functions map $\mathcal{X}^* \to [0, 1]$ is a global sequential α-covering of $\mathcal{H}$ at scale T if for any $\mathbf{x}^T \in \mathcal{X}^T$ and $h \in \mathcal{H}$, there exists $g \in \mathcal{G}$ such that $\forall t \in [T]$,*

$$|h(\mathbf{x}_t) - g(\mathbf{x}^t)| \leq \alpha.$$

Throughout we assume that $0 < \alpha < 1$.

Note that the main difference between our *global* sequential covering and the sequential covering used in [3] is that our covering function *does not* depend on the underlying trees introduced in [23] [2]. This is crucial to apply our covering set directly in an algorithmic way (see Algorithm 2). Particularly, it enables us to establish our lower and upper bounds for Lipschitz classes of functions with the optimal constants on the leading term. We further improve these results for Lipschitz class with bounded Hessian. Finally, we study cases when the data dimension d grows faster than T by bounding the covering size through the sequential fat-shattering number. In particular, we prove matching (up to poly $\log T$ factor) upper and lower bounds for the generalized linear functions.

General Results.   We are now in the position to state our first main general finding.

Theorem 1. *If for any $\alpha > 0$ there exists a global sequential α-covering set $\mathcal{G}_\alpha$ of $\mathcal{H}$, then*

$$r_T^a(\mathcal{H}) \leq \inf_{0 < \alpha < 1} \{2\alpha T + \log |\mathcal{G}_\alpha|\}, \tag{6}$$

and this bound is achievable algorithmically.

We should point out that Theorem 1 also improves the results of [3] by obtaining better constants in front of both αT and $\log |\mathcal{G}_\alpha|$. The proof is based on the following key lemma that is established in Appendix B.

---
[2]Note that the covering functions in Definition 1 can be viewed as the experts constructed in [23, Section 6.1]

Algorithm 2 Smooth truncated Bayesian predictor

Input: Reference class $\mathcal{G}$ with index set $\mathcal{W}$ and prior μ over $\mathcal{W}$, and truncation parameter α

1: Let $p_w(y^0 \mid \mathbf{x}^0) = 1$ for all $w \in \mathcal{W}$
2: **for** $t = 1, \cdots, T$ **do**
3:     Receive feature $\mathbf{x}_t$
4:     For all $w \in \mathcal{W}$, set

$$\tilde{g}_w(\mathbf{x}^t) = \frac{g_w(\mathbf{x}^t) + \alpha}{1 + 2\alpha}$$

5:     Make prediction

$$\hat{y}_t = \frac{\int_{\mathcal{W}} \tilde{g}_w(\mathbf{x}^t) p_w(y^{t-1} \mid \mathbf{x}^{t-1}) \mathrm{d}\mu}{\int_{\mathcal{W}} p_w(y^{t-1} \mid \mathbf{x}^{t-1}) \mathrm{d}\mu}$$

6:     Receive label y_t
7:     For all $w \in \mathcal{W}$, update: $p_w(y^t \mid \mathbf{x}^t) = e^{-\ell(\tilde{g}_w(\mathbf{x}^t), y_t)} p_w(y^{t-1} \mid \mathbf{x}^{t-1})$.
8: **end for**

Lemma 4. *Suppose $\mathcal{H}$ has a global sequential α-covering set $\mathcal{G}$ for some $\alpha \in [0, 1]$. Then, there exists a truncated set $\tilde{\mathcal{G}}$ of $\mathcal{G}$ with $|\tilde{\mathcal{G}}| = |\mathcal{G}|$ such that for all $\mathbf{x}^T, y^T$ and $h \in \mathcal{H}$ there exists a $\tilde{g} \in \tilde{\mathcal{G}}$ satisfying*

$$\frac{p_h(y^T \mid \mathbf{x}^T)}{p_{\tilde{g}}(y^T \mid \mathbf{x}^T)} \leq (1 + 2\alpha)^T, \tag{7}$$

where

$$p_h(y^T \mid \mathbf{x}^T) = \prod_{t=1}^{T} h(\mathbf{x}_t)^{y_t} (1 - h(\mathbf{x}_t))^{1-y_t} \quad \text{and} \quad p_{\tilde{g}}(y^T \mid \mathbf{x}^T) = \prod_{t=1}^{T} \tilde{g}(\mathbf{x}^t)^{y_t} (1 - \tilde{g}(\mathbf{x}^t))^{1-y_t}.$$

Proof of Theorem 1. We show that for any $0 < \alpha < 1$ if an α-covering set $\mathcal{G}_\alpha$ exists, then one can achieve the claimed bound for such an α. To do so, we run the Smooth truncated Bayesian Algorithm (Algorithm 2) on $\mathcal{G}_\alpha$ with uniform prior and truncation parameter α. We denote by $\tilde{\mathcal{G}}_\alpha$ the truncated class of $\mathcal{G}_\alpha$ as in Lemma 4 (same as the step 4 of Algorithm 2). We now fix $\mathbf{x}^T, y^T$. By Lemma 3 (with $\mathcal{G}$ being $\tilde{\mathcal{G}}_\alpha$), we have

$$\sum_{t=1}^{T} \ell(\hat{y}_t, y_t) \leq \inf_{\tilde{g} \in \tilde{\mathcal{G}}_\alpha} \sum_{t=1}^{T} \ell(\tilde{g}(\mathbf{x}^t), y_t) + \log |\tilde{\mathcal{G}}_\alpha| = \inf_{\tilde{g} \in \tilde{\mathcal{G}}_\alpha} \sum_{t=1}^{T} \ell(\tilde{g}(\mathbf{x}^t), y_t) + \log |\mathcal{G}_\alpha|,$$

the last equality follows from $|\mathcal{G}_\alpha| = |\tilde{\mathcal{G}}_\alpha|$. Since $\sum_{t=1}^{T} \ell(f(\mathbf{x}^t), y_t) = -\log p_f(y^T \mid \mathbf{x}^T)$ for any function f, then by Lemma 4 we conclude that

$$\inf_{h \in \mathcal{H}} \sum_{t=1}^{T} \ell(h(\mathbf{x}_t), y_t) \geq \inf_{\tilde{g} \in \tilde{\mathcal{G}}_\alpha} \sum_{t=1}^{T} \ell(\tilde{g}(\mathbf{x}^t), y_t) - T \log (1 + 2\alpha).$$

The result follows by combining the inequalities and noticing that $\log(1+x) \leq x$ for all $x \geq -1$. $\quad\square$

We further note that for any constant c_1, c_2 for which the bound $r_T^a(\mathcal{H}) \leq c_1 \alpha T + c_2 \log |\mathcal{G}_\alpha|$ holds universally we must have $c_1 \geq 2$ and $c_2 \geq 1$. Therefore, our bounds are optimal on the constants[3]. To see this, we let $\mathcal{X} = [T]$ and define g to be the function that maps every $t \in [T]$ to $\frac{1}{2}$. Let $\mathcal{H}$ be the class of functions that maps to $[1/2 - \alpha, 1/2 + \alpha]$. Clearly, $\mathcal{H}$ is α-covered by g. By noting that the maximum probability is $(1/2 + \alpha)^T = (1 + 2\alpha)^T (1/2)^T$, we compute the Shtarkov sum (5) to get:

$$r_T^a(\mathcal{H}) \geq r_T^*(\mathcal{H}) \geq \log(1 + 2\alpha)^T \sim 2\alpha T,$$

where $\sim$ holds when α is sufficiently small. This implies that we must have $c_1 \geq 2$. The fact that $c_2 \geq 1$ is due to the fact that mixability constant of log-loss is 1, which also follows from Theorem 3 below.

---
[3] Note that Theorem 1 can be easily generalized to alphabet of size K by using truncation $\tilde{g}(y_t \mid \mathbf{x}^t) = \frac{g(y_t \mid \mathbf{x}^t) + \alpha}{1 + K\alpha}$. The derived bound will be of form $K\alpha T + \log |\mathcal{G}_\alpha|$. This is tight on the constant K as well.

Lipschitz Parametric Class. We now consider a Lipschitz parametric function class. Given a function $f : \mathcal{W} \times \mathcal{X} \to [0,1]$, define the following class

$$\mathcal{H}_f = \{f(\mathbf{w}, \cdot) \in [0,1]^{\mathcal{X}} \; : \; \mathbf{w} \in \mathcal{W}\},$$

where $\mathbf{w} \in \mathcal{W}$ is often a vector in $\mathbb{R}^d$.

We will assume that $f(\mathbf{w}, \mathbf{x})$ is L-Lipschitz on $\mathbf{w}$ for every $\mathbf{x}$, where $L \in \mathbb{R}^+$. More formally, $\forall \mathbf{w}_1, \mathbf{w}_2 \in \mathcal{W}$ and $\mathbf{x} \in \mathcal{X}$ we have

$$|f(\mathbf{w}_1, \mathbf{x}) - f(\mathbf{w}_2, \mathbf{x})| \leq L||\mathbf{w}_1 - \mathbf{w}_2||,$$

where $|| \cdot ||$ is some norm on $\mathcal{W}$. For example, if we take $\mathcal{W} \subset \mathbb{R}^d$ then the norm can be ℓ_1, ℓ_2 or ℓ_∞ norm. For any specific norm $|| \cdot ||$, we write $\mathcal{B}(R)$ for the ball under such norm with radius R in $\mathcal{W}$. In particular, we denote by $\mathcal{B}_s^d(R)$ the ball in $\mathbb{R}^d$ of radius R under ℓ_s norm centered at the origin.

Theorem 2. *Let $f : \mathcal{B}_s^d(R) \times \mathbb{R}^d \to [0,1]$ be a L-Lipschitz function under ℓ_s norm. Then*

$$r_T^a(\mathcal{H}_f) \leq \min\left\{ d\log\left(\frac{2RLT}{d} + 1\right) + 2d, T \right\}. \tag{8}$$

Proof. By L-Lipschitz condition, to find an α-covering in the sense of Definition 1, we only need to find a covering of $\mathcal{B}_s^d(R)$ with radius α/L. By standard result (see e.g. Lemma 5.7 and Example 5.8 of [35]) we know that the covering size is upper bounded by

$$\left(\frac{2RL}{\alpha} + 1\right)^d.$$

By Theorem 1, we find

$$r_T^a(\mathcal{H}_f) \leq \inf_{0 < \alpha < 1} \left\{ 2\alpha T + d\log\left(\frac{2RL}{\alpha} + 1\right) \right\}.$$

Taking $\alpha = d/T$, we conclude

$$r_T^a(\mathcal{H}_f) \leq d\log\left(\frac{2RLT}{d} + 1\right) + 2d.$$

This completes the proof for $T \geq d$. The upper bound T is achieved by predicting $\frac{1}{2}$ every time. $\square$

Example 1. For logistic function $f(\mathbf{w}, \mathbf{x}) = (1 + e^{-\langle \mathbf{w}, \mathbf{x} \rangle})^{-1}$, and $\mathbf{w} \in \mathcal{B}_2^d(R)$ with $\mathbf{x} \in \mathcal{B}_2^d(1)$ our result recovers those of [11], but with a better leading constant (the bound in [11] has a constant 5). Note that, the result in [3] also provides a sub-optimal constant $c \sim 4$. Moreover, our bounds have a logarithmic dependency on Lipschitz constant L.

The question arises whether the factor in front of $\log T$ can be improved to $d/2$ instead of d as discussed in some recent papers [29, 13, 14]. In Theorem 3 below, we show that, in general, it cannot unless we further strengthen our assumption (see Theorem 4). For the ease of presentation, we only consider the parameters restricted to ℓ_2 norm. The proof can be found in Appendix C.

Theorem 3. *For any d, T, R, L such that $T \gg d\log(RLT)$, there exists L-Lipschitz function $f : \mathcal{B}_2^d(R) \times \mathbb{R}^d \to [0,1]$ such that*

$$r_T^a(\mathcal{H}_f) \geq d\log\left(\frac{RLT}{d}\right) - d\log 64 - d\log\log(RLT). \tag{9}$$

Lipschitz Class with Bounded Hessian. As we have demonstrated in Theorem 3 the leading constant 1 of the regret for Lipschitz parametric classes can not be improved in general. We now show that for some special function f one can improve the constant to $\frac{1}{2}$, as already noticed in [29, 13, 14]. For any function $f : \mathbb{R}^d \times \mathbb{R}^d \to [0,1]$, we say the Hessian of $\log f$ is uniformly bounded on $\mathcal{X} \subset \mathbb{R}^d$, if there exists constant C such that for any $\mathbf{w} \in \mathbb{R}^d$ and $\mathbf{x} \in \mathcal{X}$ and $y \in \{0, 1\}$ we have

$$\sup_{||\mathbf{u}||_2 \leq 1} |\mathbf{u}^T \nabla_{\mathbf{w}}^2 \log f(\mathbf{w}, \mathbf{x})^y (1 - f(\mathbf{w}, \mathbf{x}))^{1-y} \mathbf{u}| \leq C,$$

where $\nabla_{\mathbf{w}}^2$ is the Hessian at $\mathbf{w}$. The proof of the next theorem can be found in Appendix D.

Theorem 4. *Let $f : \mathbb{R}^d \times \mathbb{R}^d \to [0,1]$ be a function such that the Hessian of $\log f$ is uniformly bounded by C on $\mathcal{X}$. Let*
$$\mathcal{H}_f = \{f(\mathbf{w},\mathbf{x}) : \mathbf{w} \in \mathcal{W}, \mathbf{x} \in \mathcal{X}\}$$
be such a class of f restricted to some compact set $\mathcal{W} \subset \mathbb{R}^d$. Then
$$r_T^a(\mathcal{H}_f) \leq \log \frac{Vol(\mathcal{W}^*)}{Vol(\mathcal{B}_2^d(\sqrt{d/CT}))} + d/2 + \log 2. \tag{10}$$

where $\mathcal{W}^* = \{\mathbf{w} + \boldsymbol{u} \mid \mathbf{w} \in \mathcal{W}, \boldsymbol{u} \in \mathcal{B}_2^d(\sqrt{d/CT})\}$, $Vol(\cdot)$ is volume under Lebesgue measure. In particular, for $\mathcal{W} = \mathcal{B}_2^d(R)$, we have
$$r_T^a(\mathcal{H}_f) \leq \frac{d}{2}\log\left(\frac{2CR^2T}{d} + 2\right) + d/2 + \log 2.$$

Note that, Theorem 4 subsumes the results of [16, 29][4], where the authors considered functions of form $f(\langle \mathbf{w}, \mathbf{x}\rangle)$ and requires that the second derivative of $\log f$ is bounded, see also [4, Chapter 11.10]. However, the KL-divergence-based argument of [16] can not be used directly in the setup of Theorem 4 since we *do not* assume the function f has a linear structure. Our main proof technique of Theorem 4 is a direct application of Lemma 2 and an estimation of the integrals via Taylor expansion; see Appendix D for more details on the proof.

Finally, we complete this part with the following lower bound for generalized linear functions under unit ℓ_s balls. See Appendix E for proof.

Theorem 5. *Let $f : \mathbb{R} \to [0,1]$ be an arbitrary function such that there exists $c_1, c_2 \in (0,1)$ and for all $r > 0$ we have $[c_1 - c_2 d^{-r}, c_1 + c_2 d^{-r}] \subset f([-d^{-r}, d^{-r}])$ for sufficiently large d. Let*
$$\mathcal{H}_f = \{f(\langle \mathbf{w}, \mathbf{x}\rangle) : \mathbf{w} \in \mathcal{B}_s^d(1), \mathbf{x} \in \mathcal{B}_s^d(1)\}$$
where $s > 0$. Then
$$r_T^a(\mathcal{H}_f) \geq \frac{d}{2}\log\left(\frac{T}{d^{(s+2)/s}}\right) - O(d) \tag{11}$$

where O hides some absolute constant that is independent of d, T.

Note that for the logistic function $f(x) = (1 + e^{-x})^{-1}$ Theorem 5 holds with $c_1 = \frac{1}{2}$ and $c_2 = \frac{1}{5}$. Therefore,
1. If $s = 1$, then
$$r_T^a(\mathcal{H}_f) \geq \frac{d}{2}\log\left(\frac{T}{d^3}\right) - O(d).$$

2. If $s = 2$, then
$$r_T^a(\mathcal{H}_f) \geq \frac{d}{2}\log\left(\frac{T}{d^2}\right) - O(d).$$

3. If $s = \infty$, then
$$r_T^a(\mathcal{H}_f) \geq \frac{d}{2}\log\left(\frac{T}{d}\right) - O(d).$$

This recovers all the lower bounds from [29]. We note that a simple sufficient condition for Theorem 5 to hold is to require $f'(0) \neq 0$ if $f(x)$ is differentiable.

Large Growth. We now present some results for large d growing even faster than T. We will show that the size of *global* sequential covering (Definition 1) of a class $\mathcal{H}$ can be bounded by the sequential fat-shattering number of $\mathcal{H}$ in a similar fashion as in [23]. We first introduce the notion of sequential fat-shattering number as in [23].

We denote $\{0,1\}_*^d$ to be the set of all binary sequences of length less than or equal to d. A binary tree of depth d with labels in $\mathcal{X}$ is defined to be a map $\tau : \{0,1\}_*^d \to \mathcal{X}$. For any function class $\mathcal{H} \subset [0,1]^{\mathcal{X}}$, we say $\mathcal{H}$ α-fat shatters tree τ if there exists $[0,1]$-value tree $\mathbf{s} : \{0,1\}_*^d \to [0,1]$ such that for any binary sequence $\epsilon_1^d \in \{0,1\}_*^d$ there exist $h \in \mathcal{H}$ such that for all $t \in [d]$:
1. If $\epsilon_t = 0$, then $h(\tau(\epsilon_1^{t-1})) \leq \mathbf{s}(\epsilon_1^{t-1}) - \alpha$;
2. If $\epsilon_t = 1$, then $h(\tau(\epsilon_1^{t-1})) \geq \mathbf{s}(\epsilon_1^{t-1}) + \alpha$.

---

[4]To get the upper bounds in [29] one only needs to estimate the volume of ℓ_s balls, which is well known [36].

Definition 2. *The sequential α-fat shattering number of $\mathcal{H}$ is defined to be the maximum number $d(\alpha)$ such that $\mathcal{H}$ α-fat shatters a tree τ of depth $d := d(\alpha)$.*

In the lemma below, we present an upper bound for the cardinally of the global covering set with algorithmically constructed cover set $\mathcal{G}_\alpha$ (see also [23, Section 6.1]). Appendix F presents the proof.

Lemma 5. *Let $\mathcal{H}$ be any class map $\mathcal{X} \to [0, 1]$ and $d(\alpha)$ be the sequential α-fat shattering number of $\mathcal{H}$. Then there exists a global sequential α-covering set $\mathcal{G}_\alpha$ of $\mathcal{H}$ as in Definition 1 such that*

$$|\mathcal{G}_\alpha| \leq \sum_{t=0}^{d(\alpha/3)} \binom{T}{t} \left\lceil \frac{3}{2\alpha} \right\rceil^t \leq \left\lceil \frac{3T}{2\alpha} \right\rceil^{d(\alpha/3)+1}. \tag{12}$$

Example 2. By [23] we know that the sequential α-fat shattering number of linear functions $f(\mathbf{w}, \mathbf{x}) = |\langle \mathbf{w}, \mathbf{x} \rangle|$ with $\mathbf{w}, \mathbf{x} \in \mathcal{B}_2^d(1)$ is of order $\tilde{O}(\alpha^{-2})$ where in $\tilde{O}$ we hide a polylog factor. Lemma 5 implies that the global sequential α-covering number is upper bounded by

$$\left\lceil \frac{(3T)}{(2\alpha)} \right\rceil^{d(\alpha/3)+1}.$$

By Theorem 1, we have

$$r_T^a(\mathcal{H}_f) \leq \inf_{0 < \alpha < 1} \left\{ 2\alpha T + \tilde{O}\left(\frac{1}{\alpha^2}\right) \right\} \leq \tilde{O}(T^{2/3}),$$

by taking $\alpha = T^{-1/3}$. This bound is *independent* of the data dimension d.

Remark 1. *Observe that for any class $\mathcal{H}$ with sequential fat-shattering number of order α^{-s} one can achieve a regret upper bound of order $\tilde{O}(T^{s/s+1})$ by Theorem 1. We refer to [23, 24] for the estimations of sequential fat-shattering number of a variety of classes.*

Finally, we present the following general lower bound. See Appendix G for proof.

Theorem 6. *For any $s \geq 1$, we define*

$$\mathcal{D}_s = \left\{ \boldsymbol{p} \in [0, 1]^T : \sum_{t=1}^{T} p_t^s \leq 1 \right\}.$$

We can view the vectors in $\mathcal{D}_s$ as functions mapping $[T] \to [0, 1]$. Then

$$r_T^a(\mathcal{D}_s) \geq r_T^*(\mathcal{D}_s) \geq \Omega(T^{s/s+1}). \tag{13}$$

To see why Theorem 6 implies a lower bound for $f(\mathbf{w}, \mathbf{x}) = |\langle \mathbf{w}, \mathbf{x} \rangle|$ with $d \geq T$, as in Example 2, we take $\mathbf{w}, \mathbf{x} \in \mathcal{B}_2^T(1)$ (i.e., with $d = T$) and define $\mathbf{x}_t = \mathbf{e}_t$ with $\mathbf{e}_t$ being the standard base of $\mathbb{R}^T$ that takes value 1 at position t and zeros otherwise. Note that the functions of $\mathcal{H}_f$ with $f(\mathbf{w}, \mathbf{x}) = |\langle \mathbf{w}, \mathbf{x} \rangle|$ restricted on $\mathbf{x}^T$ is exactly $\mathcal{D}_2$. Then

$$r_T^a(\mathcal{H}_f) \geq r_T^*(\mathcal{H}_f) \geq r_T^*(\mathcal{D}_2) \geq \Omega(T^{2/3})$$

and this is a matching lower bound of Example 2. Note that, it is proved in [22] that for function $f(\mathbf{w}, \mathbf{x}) = \frac{\langle \mathbf{w}, \mathbf{x} \rangle + 1}{2}$, one can achieve the regret of form $\tilde{O}(\sqrt{T})$[5]. Example 2 implies that the generalized linear functions of form $f(\langle \mathbf{w}, \mathbf{x} \rangle)$ can have different regrets with polynomial gap even with a simple shift on the value (though they have the same covering number). It is therefore an interesting open problem to investigate a tighter complexity measure (instead of a covering number as in Definition 1) that captures this phenomenon.

4 Conclusion

In this paper, we presented best known lower and upper bounds on sequential online regret for a large class of experts. We accomplish this by designing a new smooth truncated Bayesian algorithm, together with a new concept of global sequential covering, that achieves these upper bounds. For the lower bound, we use a novel information-theoretic approach based on the Shtarkov sum. We expect that these techniques can be generalized to a broader set of problems, e.g., when the covariant $\mathbf{x}^T$ is present stochastically. We leave these to the future investigations.

---

[5]A $\tilde{\Omega}(\sqrt{T})$ lower bound for $d \geq \sqrt{T}$ can be derived from Theorem 5, recovering [22, Lemma 8].

References

[1] A. Barron, J. Rissanen, and B. Yu. The minimum description length principle in coding and modeling. *IEEE Trans. Inf. Theory*, 44(6):2743–2760, Oct. 1998.

[2] Shai Ben-David, Dávid Pál, and Shai Shalev-Shwartz. Agnostic online learning. In *COLT*, volume 3, page 1, 2009.

[3] Blair Bilodeau, Dylan Foster, and Daniel Roy. Tight bounds on minimax regret under logarithmic loss via self-concordance. In *International Conference on Machine Learning*, pages 919–929. PMLR, 2020.

[4] N. Cesa-Bianchi and G. Lugosi. *Prediction, Learning and Games*. Cambridge University Press, 2006.

[5] B. Clarke and A. Barron. Jeffreys' prior is asymptotically least favorable under entropy of risk. *J. Statistical PLanning and Inference*, pages 453 – 471, 1994.

[6] I. Csiszar and P. Shields. Redundancy rates for renewal and other processes. *IEEE Trans. Inf. Theory*, 42:2065–2072, 1995.

[7] Amit Daniely, Sivan Sabato, Shai Ben-David, and Shai Shalev-Shwartz. Multiclass learnability and the erm principle. In *Proceedings of the 24th Annual Conference on Learning Theory*, pages 207–232. JMLR Workshop and Conference Proceedings, 2011.

[8] L. D. Davisson. Universal noiseless coding. *IEEE Trans. Inf. Theory*, IT-19(6):783–795, Nov. 1973.

[9] M. Drmota and W. Szpankowski. Precise minimax redundancy and regrets. *IEEE Trans. Inf. Theory*, IT-50:2686–2707, 2004.

[10] P. Flajolet and W. Szpankowski. Analytic variations on redundancy rates of renewal processes. *IEEE Trans. Information Theory*, 48:2911–2921, 2002.

[11] Dylan J Foster, Satyen Kale, Haipeng Luo andMehryar Mohri, and Karthik Sridharan. Logistic regression: The importance of being improper. In *COLT - Conference on Learning Theory*, 2018.

[12] E. Hazan, T. Koren, and K. Y. Levy. Logistic regression: Tight bounds for stochastic and online optimization. In *The 27th Conference on Learning Theory, COLT 2014*, pages 197–209. MIT press, 2014.

[13] P. Jacquet, G. I. Shamir, and W. Szpankowski. Precise minimax regret for logistic regression with categorical feature values. In *PRML: ALT'21*, volume 132, pages 755–771, 2021.

[14] Philippe Jacquet, Gil Shamir, and Wojciech Szpankowski. Precise minimax regret for logistic regression with categorical feature values. In *Algorithmic Learning Theory*, pages 755–771. PMLR, 2021.

[15] Rémi Jézéquel, Pierre Gaillard, and Alessandro Rudi. Mixability made efficient: Fast online multiclass logistic regression. *Advances in Neural Information Processing Systems*, 34, 2021.

[16] Sham M Kakade and Andrew Y. Ng. Online bounds for bayesian algorithms. In L. K. Saul, Y. Weiss, and L. Bottou, editors, *Advances in Neural Information Processing Systems 17*, pages 641–648. MIT Press, 2005.

[17] R. E. Krichevsky and V. K. Trofimov. The performance of universal encoding. *IEEE Trans. Inform. Theory*, IT-27(2):199–207, Mar. 1981.

[18] Jack J Mayo, Hédi Hadiji, and Tim van Erven. Scale-free unconstrained online learning for curved losses. *arXiv preprint arXiv:2202.05630*, 2022.

[19] Edward James McShane. Extension of range of functions. *Bulletin of the American Mathematical Society*, 40(12):837–842, 1934.

[20] A. Orlitsky and N. P. Santhanam. Speaking of infinity. *IEEE Trans. Inf. Theory*, 50(10):2215–2230, Oct. 2004.

[21] A. Rakhlin and K. Sridharan. Online nonparametric regression with general los function. In *COLT*, 2014.

[22] Alexander Rakhlin and Karthik Sridharan. Sequential probability assignment with binary alphabets and large classes of experts. *arXiv preprint arXiv:1501.07340*, 2015.

[23] Alexander Rakhlin, Karthik Sridharan, and Ambuj Tewari. Online learning: Random averages, combinatorial parameters, and learnability. *Advances in Neural Information Processing Systems*, 23, 2010.

[24] Alexander Rakhlin, Karthik Sridharan, and Ambuj Tewari. Sequential complexities and uniform martingale laws of large numbers. *Probability Theory and Related Fields*, 161(1):111–153, 2015.

[25] J. Rissanen. Universal coding, information, prediction, and estimation. *IEEE Trans. Inform. Theory*, IT-30(4):629–636, Jul. 1984.

[26] J. Rissanen. Fisher information and stochastic complexity. *IEEE Trans. Information Theory*, 42:40–47, 1996.

[27] G. I. Shamir. On the MDL principle for i.i.d. sources with large alphabets. *IEEE Trans. Inform. Theory*, 52(5):1939–1955, May 2006.

[28] G. I. Shamir and W. Szpankowski. Low complexity approximate bayesian logistic regression for sparse online learning. In *ArXiv: http://arxiv.org/abs/2101.12113*, 2021.

[29] Gil I Shamir. Logistic regression regret: What's the catch? In *Conference on Learning Theory*, pages 3296–3319. PMLR, 2020.

[30] Y. M. Shtarkov. Universal sequential coding of single messages. *Problems of Information Transmission*, 23(3):3–17, Jul.-Sep. 1987.

[31] W. Szpankowski. On asymptotics of certain recurrences arising in universal coding. *Problems of Information Transmission*, 34:55–61, 1998.

[32] W. Szpankowski. *Average Case Analysis of Algorithms on Sequences*. Wiley, New York, 2001.

[33] W. Szpankowski and M. Weinberger. Minimax pointwise redundancy for memoryless models over large alphabets. *IEEE Trans. Information Theory*, 58:4094–4104, 2012.

[34] Volodya Vovk. Competitive on-line statistics. *International Statistical Review*, 69(2):213–248, 2001.

[35] Martin J Wainwright. *High-dimensional statistics: A non-asymptotic viewpoint*, volume 48. Cambridge University Press, 2019.

[36] Xianfu Wang. Volumes of generalized unit balls. *Mathematics Magazine*, 78(5):390–395, 2005.

[37] C. Wu, M. Heidari, A. Grama, and W. Szpankowski. Sequential vs fixed design minimax regrets for learning. *preprint*, 2022.

[38] Q. Xie and A. Barron. Minimax redundancy for the class of memoryless sources. *IEEE Trans. Information Theory*, pages 647–657, 1997.

[39] Q. Xie and A. Barron. Asymptotic minimax regret for data compression, gambling, and prediction. *IEEE Trans. Information Theory*, 46:431–445, 2000.

[40] Kenji Yamanishi. Minimax relative loss analysis for sequential prediction algorithms using parametric hypotheses. In *Proceedings of the eleventh annual conference on Computational learning theory*, pages 32–43, 1998.