CLIPORT: What and Where Pathways
for Robotic Manipulation

Abstract: Humans have the ability to manipulate objects precisely but also to reason about them in terms of abstract concepts. How can we imbue robots with this ability? Recent works in manipulation have shown that end-to-end networks can learn dexterous skills that require precise spatial reasoning, but these methods often fail to generalize to new goals or quickly learn transferable concepts. In parallel, there has been great progress in learning generalizable semantic representations for vision and language by training on large-scale internet data, however these representations lack the spatial understanding necessary for fine-grained manipulation. To this end, we propose a framework that combines the best of both worlds: a two-stream architecture with semantic (*what*) and spatial (*where*) pathways for vision-based manipulation. Specifically, we present CLIPORT, a language-conditioned imitation-learning agent that combines the broad semantic understanding of CLIP [1] with the spatial precision of Transporter [2]. Our end-to-end framework is capable of solving a variety of language-specified tabletop tasks from packing unseen objects to folding cloths, all without any explicit representations of object poses, instance segmentations, history, symbolic states, or syntactic structures. Experiments in simulation and hardware show that our approach is data-efficient and generalizes effectively to seen and unseen semantic concepts. We even train one multi-task policy for 10 simulated and 6 real-world tasks that shows better or comparable performance to single-task models.

Keywords: Manipulation, Vision Language Grounding, CLIP

1 Introduction

Ask a person to "get a scoop of coffee beans" or "fold the cloth in half" and they can naturally take abstract concepts like *scoop* or *fold* and ground them in concrete physical actions within an accuracy of a few centimeters. We humans do this intuitively, without explicit geometric or kinematic models of coffee beans or cloths. Moreover, we can generalize to a broad range of tasks and concepts from a minimal set of examples on what needs to be achieved. How can we imbue robots with this ability to efficiently ground abstract semantic concepts in precise spatial reasoning?

Recently, a number of end-to-end frameworks have been proposed for vision-based manipulation [2, 3, 4, 5]. While these methods do not use any explicit representations of object poses, instance segmentations, or symbolic states, they can only replicate demonstrations with a narrow range of variability and have no notion of the semantics underlying the tasks. Switching from packing red pens to blue pens involves collecting a new training set [2], or if using goal-conditioned policies, involves the user providing a goal-image from the scene [5, 6]. In realistic human-robot interaction settings, collecting additional demonstrations or providing goal-images is often infeasible and unscalable. A natural solution to both these problems is to condition policies with natural language. Language provides an intuitive interface for specifying goals and also for implicitly transferring concepts across tasks. While language-grounding for manipulation has been explored in the past [7, 8, 9, 10], these pipelines are limited by object-centric representations that cannot handle granular or deformable objects and often do not reason about perception and action in an integrated manner. In parallel, there has been great progress in learning models for semantic understanding [11, 12] and aligning representations of vision and language [13, 14, 15] by training on large-scale internet data. However, these representations lack the spatial understanding necessary for fine-grained manipulation.

Submitted to the 5th Conference on Robot Learning (CoRL 2021). Do not distribute.

Figure 1. **Language-Conditioned Manipulation Tasks:** CLIPORT is a broad framework applicable to a wide range of language-conditioned manipulation tasks in tabletop settings. We conduct large-scale experiments in Ravens [2] on 10 simulated tasks (a-j) with 1000s of unique instances per task. See Appendix A for challenges pertaining to each task. CLIPORT can even learn one multi-task model for all 10 tasks that achieves better or comparable performance to single-task models. Similarly, we demonstrate our approach on a Franka Panda manipulator with one multi-task model trained on 6 real-world tasks (k-o; only 5 shown). See supplementary video for simulated and real-robot executions.

To this end, we propose the first framework that combines the best of both worlds: end-to-end learning for fine-grained manipulation with the broad generalization capability of vision-language grounding systems. We introduce a two-stream architecture for manipulation with **semantic** (*what*) and **spatial** (*where*) pathways broadly inspired by (or very vaguely analogous to) the two-stream hypothesis is biology [16, 17, 18]. Specifically, we present CLIPORT, an imitation agent that integrates the semantic understanding of CLIP [1] with the spatial precision of Transporter [2]. Transporter has been applied to a wide range of rearragement tasks from industrial packing [2] to manipulating deformable objects [6]. The key insight of the approach is formulating manipulation as a series of pick-and-place affordance predictions. However, Transporter is a tabula rasa system that learns all visual representations from scratch and so every new task or goal requires collecting a new set of demonstrations. To address this problem, we bake in a strong semantic prior while learning policies. We condition our **semantic** stream with visual and language-goal features from a pre-trained CLIP model [1]. Since CLIP was trained to align image and language features from large-amounts of image-caption pairs from the internet, it provides a powerful prior for grounding semantic concepts that are common across tasks like object categories, parts, shapes, colors, and other visual attributes, all without being restricted to a top-down pipeline that requires bounding boxes or instance segementations [13, 14, 15, 19]. This architecture effectively allows us to formulate tabletop manipulation as a series of language-conditioned affordance predictions, a predominantly vision-based inference problem, and thus benefit from the strengths of data-driven paradigms like scale and robustness.

To study these benefits, we conduct large-scale experiments in the Ravens [2] framework with a simulated suction-gripper robot. We propose 10 language-conditioned tasks with 1000s of unique instances per task that require both semantic and spatial reasoning (see Figure 1 a-j). CLIPORT is not only effective at solving these tasks, but surprisingly, it can even learn a multi-task model for all 10 tasks that achieves better or comparable performance to single-task models. Further, our evaluations indicate that our multi-task model can effectively transfer attributes like "pink block" across tasks, having never seen pink blocks or the word 'pink' in the context of the evaluation task. We also demonstrate our approach on a Franka Panda manipulator with one multi-task model trained on 6 real-world tasks including moving chess pieces and folding cloths (see Figure 1 k-i).

In summary, our contributions are as follows:

- An extended **benchmark of language-grounding tasks** for manipulation in Ravens [2].
- **Two-stream architecture** for using internet pre-trained vision-language models for conditioning precise manipulation policies with language goals.
- **Empirical results** on a broad range of manipulation tasks, including multi-task models, validated with real-robot experiments.

We will release our code, models, and language-grounding benchmark upon publication.

2   Related Work

Vision-based Manipulation. Traditionally, perception for manipulation has centered around object detectors, segmentors, and pose estimators [20, 21, 22, 23, 24, 25]. These methods cannot handle deformable objects, granular media, or generalize to unseen objects without object-specific training data. Alternatively, dense descriptors [26, 27, 28] and keypoint representations [29, 30, 31] forgo segmentation and pose representations, but do not reason about sequential actions and struggle to represent scenes with variable numbers of objects. On the other hand, end-to-end perception-to-action models can learn precise sequential policies [2, 4, 6, 32, 33], however, these methods have limited understanding of semantic concepts and rely on goal-images to condition the policies.

Semantic Models. With the advent of large-scale models [34, 35, 36], a number of methods for learning joint vision and language representations have been proposed [13, 14, 15, 19, 37]. However, these methods are restricted to bounding box or segmentation detections, which make them inapplicable for detecting things like piles of coffee beans or squares on a chessboard. Alternatively, recent works in contrastive learning forgo top-down object-detection and learn continuous representations by pre-training on unlabeled data [11, 12]. Recently, CLIP [1] applied this approach to align vision and language representations by training on image-caption pairs from the internet.

Language Grounding for Robotics. Several works have proposed systems for instructing robots with natural language [7, 8, 9, 10, 38, 39, 40, 41, 42, 43, 44]. However, these methods use disentangled pipelines for perception and action with the language primarily being used to guide the perception. As such, these pipelines lack the spatial precision necessary for tasks like folding cloths. Recently, Lynch et. al [45] proposed an end-to-end system for grounding language in continuous control, but it requires several hours of human teleoperation data for a single simulated desk setting.

Two-Stream Architectures are prevalent in action-recognition networks [46, 47, 48] and audio-recognition systems [49, 50]. In robotics, Zeng et. al [51] proposed a two-stream pipeline for pick-and-place affordance predictions of novel objects. However, this method still requires a goal-image of the object to be picked. In contrast, our framework provides an intuitive interface with language commands without compromising the precision of end-to-end manipulation polices.

3   CLIPORT

CLIPORT is an imitation-learning agent based on four key principles: (1) Manipulation through a two-step primitive where each action involves a start and final end-effector pose. (2) Spatially equivariant visual representations that are robust to camera and object pose changes. (3) Two separate pathways for semantic and spatial information. (4) Language-conditioned policies for specifying goals and also for transferring concepts across tasks. Combining (1) and (2) from Transporter with (3) and (4) allows us to achieve generalizable policies that go beyond just imitating demonstrations.

Section 3.1 describes the problem formulation, gives an overview of Transporter [2], and presents our language-conditioned model. Section 3.2 provides details on the training approach.

3.1   Language-Conditioned Manipulation

We consider the problem of learning a goal-conditioned policy π that generates actions $\mathbf{a}_t$ given input $\gamma_t = (\mathbf{o}_t, \mathbf{l}_t)$ consisting of a visual observation $\mathbf{o}_t$ and a language instruction $\mathbf{l}_t$:

$$\pi(\boldsymbol{\gamma}_t) = \pi(\mathbf{o}_t, \mathbf{l}_t) \rightarrow \mathbf{a}_t = (\mathcal{T}_{\text{pick}}, \mathcal{T}_{\text{place}}) \in \mathcal{A} \tag{1}$$

The actions $\mathbf{a} = (\mathcal{T}_{\text{pick}}, \mathcal{T}_{\text{place}})$ specify the end-effector pose for picking and placing an object, respectively. We consider tabletop tasks where $\mathcal{T}_{\text{pick}}, \mathcal{T}_{\text{place}} \in \mathbf{SE}(2)$. The visual observation $\mathbf{o}_t$ is a

Figure 2. **CLIPORT Two-Stream Architecture.** An overview of the **semantic** and **spatial** streams in the 3 Fully-Connected-Networks f_{pick}, Φ_{query}, and Φ_{key} where f_{pick} is used to predict pick actions, and Φ_{query} and Φ_{key} are used to predict place actions. The **semantic** stream uses a frozen CLIP ResNet50 [1] to encode RGB input, and its decoder layers are conditioned with tiled language features from the CLIP sentence encoder. The **spatial** stream encodes RGB-D input, and its decoder layers are laterally fused with the **semantic** stream. The final output is dense pixelwise features which are used for pick or place affordance predictions. See Appendix B for the exact architecture.

top-down orthographic RGB-D reconstruction of the scene, thus each pixel corresponds to a point in 3D space. The language instruction $\mathbf{l}_t$ either specifies step-by-step instructions e.g. *"pack the scissors"* → *"pack the purple tape"* → etc., or a single goal description for the whole task e.g *"pack all the blue and yellow boxes in the brown box"*. See Figure 4 for examples.

We assume access to a set $\mathcal{D} = \{\zeta_1, \zeta_2, \ldots, \zeta_n\}$ of n expert demonstrations with associated discrete-time input-action pairs $\zeta_i = \{(\mathbf{o}_1, \mathbf{l}_1, \mathbf{a}_1), (\mathbf{o}_2, \mathbf{l}_2, \mathbf{a}_2), \ldots\}$ where $\mathbf{a}_t = (\mathcal{T}_{\text{pick}}, \mathcal{T}_{\text{place}})$ corresponds to pick-and-place coordinates at timestep t. These expert demonstrations are used to supervise the policy π.

Transporter for Pick-and-Place. Transporter [2] is a model for performing spatial manipulation. The model first (i) attends to a local region to decide where to pick, then (ii) computes a placement location by finding the best match for the picked region by cross-correlating deep visual features.

Following Transporter [2, 6], our policy π is composed of two action-value modules (Q-functions): The pick module $\mathcal{Q}_{\text{pick}}$ decides where to pick, and conditioned on this pick action the place module $\mathcal{Q}_{\text{place}}$ decides where to place. Transporter consists of three Fully-Convolutional-Networks (FCNs) sharing the same architecture. As we will describe in more detail below, we extend these networks to two-stream architectures that handle language input. Our pick FCN f_{pick} takes input $\boldsymbol{\gamma}_t = (\mathbf{o}_t, \mathbf{l}_t)$ and outputs a dense pixelwise prediction $\mathcal{Q}_{\text{pick}} \in \mathbb{R}^{H \times W}$ of action-values used to predict a pick action:

$$\mathcal{T}_{\text{pick}} = \underset{(u,v)}{\operatorname{argmax}} \, \mathcal{Q}_{\text{pick}}((u,v)|\boldsymbol{\gamma}_t) \tag{2}$$

Since $\mathbf{o}_t$ is an orthographic heightmap, each pixel location (u, v) can be mapped to a 3D picking location using the known camera calibration. f_{pick} is trained in a supervised manner to predict the pick action $\mathcal{T}_{\text{pick}}$ that imitates the expert demonstration with the specified language instruction at timestep t.

The second FCN Φ_{query} takes in $\boldsymbol{\gamma}_t[\mathcal{T}_{\text{pick}}]$, which is a $c \times c$ crop of $\mathbf{o}_t$ centered at $\mathcal{T}_{\text{pick}}$ along with the language instruction $\mathbf{l}_t$, and outputs a dense feature embedding of shape $\mathbb{R}^{c \times c \times d}$. The third FCN Φ_{key} consumes the full input $\boldsymbol{\gamma}_t$ and outputs a dense feature embedding of shape $\mathbb{R}^{H \times W \times d}$. The place action-values $\mathcal{Q}_{\text{place}}$ are then computed by cross-correlating the query and key features:

$$\mathcal{Q}_{\text{place}}(\Delta\tau|\gamma_t, \mathcal{T}_{\text{pick}}) = \big(\Phi_{\text{query}}(\boldsymbol{\gamma}_t[\mathcal{T}_{\text{pick}}]) * \Phi_{\text{key}}(\boldsymbol{\gamma}_t)\big)[\Delta\tau] \tag{3}$$

where $\Delta\tau \in \boldsymbol{SE}(2)$ represents a potential placement pose. Since $\mathbf{o}_t$ is an orthographic heightmap, rotations in the placement pose $\Delta\tau$ can be captured by rotating the crop of $\mathbf{o}_t$ for k discrete angles

before passing it through the query network Φ_{query}. Then $\mathcal{T}_{\text{place}} = \text{argmax}_{\Delta\tau} \mathcal{Q}_{\text{place}}(\Delta\tau|\gamma_t, \mathcal{T}_{\text{pick}})$. The place module is trained to imitate the placements in the expert demonstrations. For all simulated models, we use $k = 36$ and $d = 3$. As in Transporter [2, 6], our framework can be extended to handle any motion primitive like pushing, sliding, etc. that can be parameterized by two end-effector poses at each timestep. For more details, we refer the reader to the original paper [2].

Two-Stream Architecture. In CLIPORT, we extend the network architecture of all three FCNs $f_{\text{pick}}, \Phi_{\text{query}}$ and Φ_{key} from Transporter [2] to allow for language input and for reasoning about high-level semantic concepts. Figure 2 provides an overview of our architecture (the green parts correspond to the original Transporter ResNet). We extend the FCNs to two-pathways: **semantic** (ventral) and **spatial** (dorsal). The **semantic** stream is conditioned with language features at the bottleneck and fused with intermediate features from the **spatial** stream. The **spatial** stream is identical to the ResNet architecture in Transporter, a tabula rasa network that takes in RGB-D input $\mathbf{o}_t$ and outputs dense features through an hourglass encoder-decoder model. The **semantic** stream uses a frozen pre-trained CLIP ResNet50 [1] to encode the RGB input[1] $\tilde{\mathbf{o}}_t$ up until the penultimate layer $\tilde{\mathbf{o}}_t \to \mathbf{v}_t^{(0)} : \mathbb{R}^{7 \times 7 \times 2048}$, and then introduces decoding layers that upsample the feature tensors to mimic the **spatial** stream $\mathbf{v}_t^{(l-1)} \to \mathbf{v}_t^{(l)} : \mathbb{R}^{h \times w \times C}$ at each layer l.

The language instruction $\mathbf{l}_t$ is encoded with CLIP's Transformer-based sentence encoder to produce a goal embedding $\mathbf{l}_t \to \mathbf{g}_t : \mathbb{R}^{1024}$. This goal embedding $\mathbf{g}_t$ is downsampled with fully-connected layers to match the channel dimension C and tiled to match the spatial dimensions of the decoder features such that $\mathbf{g}_t \to \mathbf{g}_t^{(l)} : \mathbb{R}^{h \times w \times C}$. The decoder features are then conditioned with the tiled goal features through an element-wise product $\mathbf{v}_t^{(l)} \odot \mathbf{g}_t^{(l)}$ (Hadamard product). Since CLIP was trained with contrastive loss on the dot-product alignment between pooled image features and language encodings, the element-wise product allows us to use this alignment while the tiling preserves the spatial dimensions of the visual features. This language conditioning is repeated for three subsequent layers after the bottleneck inspired by LingUNet [52]. We also add skip connections to these layers from the CLIP ResNet50 encoder to utilize different levels of semantic information from shapes to parts to object-level concepts [53]. Finally, following existing two-stream architectures in video-action recognition [48], we add lateral connections from the **spatial** stream to the **semantic** stream. These connections involve concatenating two feature tensors and applying 1×1 `conv` to reduce the channel dimension $[\mathbf{v}_t^{(l)} \odot \mathbf{g}_t^{(l)}; \mathbf{d}_t^{(l)}] : \mathbb{R}^{h \times w \times C_\mathbf{v} + C_\mathbf{d}} \to \mathbb{R}^{h \times w \times C_\mathbf{v}}$, where $\mathbf{v}_t^{(l)}$ and $\mathbf{d}_t^{(l)}$ are the **semantic** and **spatial** tensors at layer l, respectively. For the final fusion of dense features, `addition` for f_{pick} and 1×1 `conv` fusion for Φ_{query} and Φ_{key} worked the best empirically. See Appendix B for details on the exact architecture used.

3.2 Implementation Details

Training from demonstrations. Similar to Transporter [2] we train CLIPORT using imitation learning on a set of expert demonstrations $\mathcal{D} = \{\zeta_1, \zeta_2, \ldots, \zeta_n\}$ consisting of discrete-time input-action pairs $\zeta_i = \{(\mathbf{o}_1, \mathbf{l}_1, \mathbf{a}_1), (\mathbf{o}_2, \mathbf{l}_2, \mathbf{a}_2), \ldots\}$. During training, we randomly sample an input-action pair from the dataset and supervise the model end-to-end with one-hot pixel encodings of demonstration actions $Y_{\text{pick}} : \mathbb{R}^{H \times W \times k}$ and $Y_{\text{place}} : \mathbb{R}^{H \times W \times k}$ with k discrete rotations. In simulated experiments with the suction-gripper, we use $k = 1$ for pick actions and $k = 36$ for place actions. Following Transporter [2], the model is trained with cross-entropy loss: $\mathcal{L} = -\mathbb{E}_{Y_{\text{pick}}}[\log \mathcal{V}_{\text{pick}}] - \mathbb{E}_{Y_{\text{place}}}[\log \mathcal{V}_{\text{place}}]$ where $\mathcal{V}_{\text{pick}} = \text{softmax}(\mathcal{Q}_{\text{pick}}((u, v)|\gamma_t))$ and $\mathcal{V}_{\text{place}} = \text{softmax}(\mathcal{Q}_{\text{place}}((u', v', \omega')|\gamma_t, \mathcal{T}_{\text{pick}}))$. Compared to the original Transporter models that were trained for 40K iterations, we train our models for 200K iterations to account for additional semantic variation in tasks – randomized colors, shapes, objects. All models are trained on a single commodity GPU for 2 days with a batch size of 1.

Training multi-task models. Multi-task training is nearly identical to single-task training except for the sampling of the training data. First, we randomly sample a task, and then select a random input-action pair from that task in the dataset. Using this strategy, all tasks are equally likely to be sampled but longer horizon tasks are less likely to reach full coverage of input-action pairs available in the dataset. To compensate for this, we train all multi-task models $3\times$ longer for 600K iterations or 6 GPU days.

---

[1]We cannot use depth information with CLIP since it was trained with RGB-only image-caption pairs from the internet.

4 Results

We perform experiments both in simulation and hardware aimed at answering the following questions: 1) How effective is the language-conditioned two-stream architecture for fine-grained manipulation compared to simpler baselines? 2) Is it possible to train a multi-task model for all tasks, and how well does it perform and generalize? 3) How well do these models generalize to seen and unseen semantic attributes like colors, shapes, and object categories?

4.1 Simulation Setup

Environment. All simulated experiments are based on a Universal Robot UR5e with a suction gripper. The setup provides a systematic and controlled environment for evaluation, especially for benchmarking the ability to ground semantic concepts like color and object categories. The input observation is a top-down RGB-D reconstruction from 3 cameras positioned around a rectangular table: one in the front, one on the left shoulder, and one on the right shoulder, all pointing towards the center. Each camera has a resolution of 640×480 and is noiseless.

Language-Conditioned Manipulation Tasks. We extend the Ravens benchmark [2] set in Py-Bullet [54] with 10 language-conditioned manipulation tasks. See Figure 1 for examples and Table 3 for challenges associated with each task. Each task instance is constructed by sampling a set of objects and attributes: poses, colors, sizes, and object categories. 8 of the 10 tasks have two variants, denoted by seen and unseen, depending on whether the task has unseen attributes (e.g. color) at test time. For colors: $\mathbb{T}_{\text{seen colors}} = \{$yellow, brown, gray, cyan$\}$ and $\mathbb{T}_{\text{unseen colors}} = \{$orange, purple, pink, white$\}$ with 3 overlapping colors $\mathbb{T}_{\text{all}} = \{$red, green, blue$\}$ used in both the seen and unseen spilts. For packing objects, we use 56 tabletop objects from the Google Scanned Objects dataset [55] and split them into 37 seen and 19 unseen objects. The language instructions are constructed from templates for simulated experiments, and human-annotated for real-world experiments. For more details about individual tasks, see Appendix A.

Evaluation Metric. We adopt the 0 (fail) to 100 (success) scores proposed in the Ravens benchmark [2]. The score assigns partial credit based on the task, e.g. $3/5 \Rightarrow 60.0$ for packing 3 out of 5 objects specified in the instructions, or $30/56 \Rightarrow 53.6$ for pushing 30 out of 56 particles into the correct zone. See Appendix A for the specific evaluation metric used in each task. During an evaluation episode, an agent keeps interacting with the scene until an oracle indicates task-completion. We report scores on 100 evaluation runs for agents trained with $n = 1, 10, 100, 1000$ demonstrations.

4.2 Simulation Results

Table 1 presents results from our large-scale experiments in Ravens [2] and Figure 3 summarizes these results with average scores across seen and unseen splits.

Figure 3. Average scores across seen and unseen splits for all tasks in Table 1.

Baseline Methods. To study the effectiveness of our two-stream architecture, we broadly compare against two baselines: Transporter-only and CLIP-only. Transporter-only is the original Transporter [2], or equivalently, the **spatial** stream of CLIPORT with RGB-D input. Although Transporter-only does not receive any language goals, it shows what can be achieved through chance by exploiting the most likely actions seen during training. On the other hand, CLIP-only is just the **semantic** stream of CLIPORT with RGB and language input. CLIP-only shows what can be achieved by fine-tuning a pre-trained semantic model for manipulation without spatial information, particularly depth.

Two-Stream Performance. Figure 3 (seen) captures the essence of our main claims. The performance of Transporter-only saturates at 50% since it doesn't use the language instruction to ground the desired goal. CLIP-only does have a goal, but lacks the spatial precision to go the last mile and thus saturates at 75%. Only CLIPORT (single) achieves more than 90%, which indicates that both the semantic and spatial streams are crucial for fine-grained manipulation. Further, CLIPORT (single) achieves 90% on most tasks with just 100 demonstrations, showcasing its efficiency.

In addition to these baselines, we present various ablations and alternative one-stream and two-stream models in Appendix E. To briefly summarize these results, CLIP is essential for few-shot

	packing-box-pairs seen-colors				packing-box-pairs unseen-colors				packing-seen-google objects-seq				packing-unseen-google objects-seq				packing-seen-google objects-group				packing-unseen-google objects-group			
Method	1	10	100	1000	1	10	100	1000	1	10	100	1000	1	10	100	1000	1	10	100	1000	1	10	100	1000
Transporter-only [2]	48.9	57.2	59.4	60.6	37.8	52.3	54.5	60.7	29.0	39.1	39.5	41.5	25.9	35.1	41.7	37.9	53.9	52.0	54.4	52.9	29.9	53.5	52.7	54.7
CLIP-only	37.1	72.3	87.4	90.9	36.1	61.8	67.2	62.9	29.3	76.0	86.4	**97.0**	36.5	46.2	58.8	58.0	51.8	66.6	89.5	94.7	46.3	61.0	75.3	77.4
CLIPORT (single)	51.9	84.7	95.9	**98.0**	47.1	66.9	70.0	71.9	15.3	60.3	**92.9**	96.5	25.9	52.0	62.5	61.6	51.4	71.5	88.8	**95.6**	53.6	68.4	77.8	72.4
CLIPORT (multi)	**68.6**	**90.0**	**96.0**	96.3	**55.9**	**70.3**	**76.6**	**72.9**	**43.6**	**76.2**	85.1	82.2	**48.9**	**60.1**	**67.2**	**67.4**	**68.4**	**84.8**	**92.0**	93.2	**67.4**	**72.7**	**82.7**	**81.6**
CLIPORT (multi-attr)	–	–	–	–	*63.2*	*85.0*	*91.5*	*87.0*	–	–	–	–	*38.0*	*62.0*	*78.0*	*82.0*	–	–	–	–	*70.2*	*80.8*	*87.8*	*91.5*

	stack-block-pyramid seq-seen-colors				stack-block-pyramid seq-unseen-colors				separating-piles seen-colors				separating-piles unseen-colors				towers-of-hanoi seq-seen-colors				towers-of-hanoi seq-unseen-colors			
	1	10	100	1000	1	10	100	1000	1	10	100	1000	1	10	100	1000	1	10	100	1000	1	10	100	1000
Transporter-only [2]	4.8	4.0	6.8	5.7	4.8	5.3	5.0	5.0	42.8	52.9	54.7	55.6	47.8	53.4	52.6	54.8	25.1	74.4	**100**	**100**	25.6	46.4	77.0	81.7
CLIP-only	5.5	30.0	58.7	59.0	2.0	16.3	5.7	19.3	39.7	69.6	90.4	92.9	46.4	61.6	76.9	74.4	10.9	48.1	88.6	52.9	15.9	44.7	67.1	58.1
CLIPORT (single)	29.0	68.8	95.0	**99.3**	15.8	29.0	32.7	**41.8**	45.1	58.6	**96.8**	**99.9**	50.7	56.5	**83.8**	**83.0**	55.3	**94.1**	99.9	**100**	**66.6**	**91.9**	**96.4**	**100**
CLIPORT (multi)	**38.3**	**71.0**	**97.0**	97.3	**27.8**	**31.8**	**39.3**	33.3	**53.2**	**73.0**	92.7	89.2	**55.5**	**71.2**	79.5	76.7	**67.6**	94.0	99.1	**100**	55.6	68.6	79.1	67.0
CLIPORT (multi-attr)	–	–	–	–	*28.7*	*56.3*	*84.5*	*93.8*	–	–	–	–	*51.2*	*66.1*	*82.2*	*89.8*	–	–	–	–	*53.4*	*94.0*	*99.6*	*100*

	align-rope				packing-unseen-shapes				assembling-kits-seq seen-colors				assembling-kits-seq unseen-colors				put-blocks-in-bowls seen-colors				put-blocks-in-bowls unseen-colors			
	1	10	100	1000	1	10	100	1000	1	10	100	1000	1	10	100	1000	1	10	100	1000	1	10	100	1000
Transporter-only [2]	6.3	24.7	39.8	48.2	28.0	34.0	27.0	32.0	6.8	15.2	30.8	32.6	9.4	15.6	30.4	30.0	18.8	45.2	63.2	69.0	12.2	16.8	20.5	21.7
CLIP-only	15.4	47.6	76.7	74.3	26.0	36.0	40.0	**43.0**	1.4	6.4	19.0	27.0	4.2	5.6	12.0	16.2	22.3	62.2	94.7	98.5	15.8	29.7	38.3	24.7
CLIPORT (single)	14.8	**66.2**	**93.2**	**98.2**	22.0	**42.0**	35.0	40.0	11.0	28.8	**51.6**	**72.0**	**17.2**	23.2	33.0	**38.0**	21.7	73.0	98.2	**100**	17.2	32.5	40.2	**48.3**
CLIPORT (multi)	**19.2**	52.4	80.2	72.2	**29.0**	**42.0**	**47.0**	41.0	**17.4**	**37.2**	48.2	57.6	12.2	23.8	**36.4**	29.0	**59.7**	**94.0**	**100**	**100**	**33.8**	**42.7**	**55.3**	43.3
CLIPORT (multi-attr)	–	–	–	–	–	–	–	–	–	–	–	–	*3.6*	*35.6*	*49.0*	*48.2*	–	–	–	–	*29.5*	*61.7*	*76.8*	*73.0*

Table 1. **Language-Conditioned Task Evaluations.** Task success scores (mean %) from 100 evaluation instances vs. # of training demonstrations (1, 10, 100, or 1000). Single-task models are trained on seen splits, and evaluated on both seen and unseen splits. CLIPORT (multi) models are trained on seen splits of all 10 tasks with 1𝕋, 10𝕋, 100𝕋, and 1000𝕋 demonstrations where 𝕋 = 10. CLIPORT (multi-attr) indicate leave-one-out CLIPORT (multi) models trained on seen-and-unseen splits from all tasks *except* for that one particular heldout task, for which it is trained only the seen split. See Figure 3 for an overview with average scores.

learning in lieu of alternatives like ImageNet-trained ResNet50 [56] with BERT [35]. Image-goal models outperform CLIPORT (single) in packing Google objects, but this is only because they do not have to solve the language-grounding problem.

Multi-Task Performance. In realistic settings, we want the robot to be capable of any task, not just one task. We investigate this through CLIPORT (multi) in Table 1 with one multi-task model trained on all 10 tasks. CLIPORT (multi) models are trained only on seen-splits of tasks, so an unseen attribute like 'pink' is consistent throughout single and multi-task settings. Surprisingly, CLIPORT (multi) outperforms single-task CLIPORT (single) models in $44/72 = 61\%$ of the evaluations in Table 1. This trend is also evident in Figure 3, especially in instances with 100 demonstrations or less. Although CLIPORT (multi) is trained on more diverse data from other tasks, both CLIPORT (multi) and CLIPORT (single) have access to the same amount of data *per* task. This supports our premise that language is a strong conditioning mechanism for reusing concepts from other tasks without learning them from scratch. It also validates a trait of data-driven approaches where training on lots of diverse data leads to more robust and generalizable representations [1, 57]. However, CLIPORT (multi) performs worse on longer-horizon tasks like align-rope. We hypothesize that this is because longer-horizon tasks get less coverage of input-action pairs in the dataset. Future works could use better sampling methods that balance tasks according to their average time horizon.

Generalizing to Unseen Attributes. Tasks that require generalizing to novel colors, shapes, and objects are more difficult and all our agents achieve relatively lower performance on these tasks, as shown in Figure 3 (unseen). However, CLIPORT (single) models do substantially better than chance, i.e., Transporter-only. The lower performances are due to the difficulty of grounding unseen attributes such as 'pink' and 'orange' in the language instruction "put the pink block on the orange bowl", when the agent has never encountered words 'orange', 'pink' or their corresponding visual characteristics in the context of the physical environment. Although pre-trained CLIP has been exposed to the attribute 'pink', it could correspond to different concepts in the physical setting depending on factors like lighting condition, and thus requires at least few examples to condition the trainable **semantic** decoder layers. Additionally, we notice that CLIPORT (single) is also less prone to overfitting compared to Transporter-only. As evidenced in towers-of-hanoi-seq-unseen-colors task in Table 1, Transporter-only suffers from a performance drop because of rings with unseen colors despite the fact that Tower of Hanoi can be solved without attending to the colors and simply focusing on the ring size. We hypothesize that since CLIP was trained on diverse internet data, it enables our agent to focus on task-relevant concepts while ignoring irrelevant aspects of the task.

Figure 4. Affordance predictions from CLIPORT (multi) models in sim (left two) and real settings (right three). More examples in Appendix G.

Transferring Attributes across Tasks. One solution for dealing with unseen attributes is to explicitly learn these attributes from other tasks. We study this with CLIPORT (multi-attr) in Table 1 and Figure 3 (unseen). For these models, CLIPORT (multi) is trained on both seen-and-unseen splits from all tasks *except* for the task being evaluated on, for which it was only trained on the seen split. As such, this evaluation measures whether having seen pink blocks in put-blocks-in-bowl-unseen-colors helps solve "pack all the pink and cyan boxes" in packing-box-pairs-unseen-colors. Results indicate that such explicit transfers result in significant improvements. For instance, on the put-blocks-in-bowls-unseen-colors task for $n = 1000$, CLIPORT (multi)'s performance increases from 43.3 to 73.0.

4.3 Real-Robot Experiments

We validated our results in hardware with a Franka Panda manipulator. See Appendix C for setup details. Table 2 reports success rates for a multi-task model trained and evaluated on 6 real-world tasks. Due to COVID restrictions, we could not conduct large-scale user-studies, so we report performance on small train (5-10 demos) and test sets (5-10 runs) per task. Overall, CLIPORT (multi) is effective at few-shot learning and the performances roughly correspond to those in simulated experiments, with simple block manipulation tasks

Task	# Train (Samples)	# Test	Succ. %
Stack Blocks	5 (13)	10	70.0
Put Blocks in Bowl	5 (10)	10	65.0
Pack Objects	10 (31)	10	60.0
Move Rook	4 (29)	10	70.0
Fold Cloth	10 (10)	10	57.0
Sweep Beans	5 (23)	5	58.6

Table 2. Success rates (%) of a multi-task model trained an evaluated 6 real-world tasks (see Figure 1). Samples indicate total pick-and-place images, e.g 5 in Figure 4.

achieving ∼ 70%. We estimate that for more robust real-world performance at least 50 to 100 training demonstrations are necessary, as evident in Figure 3. Interestingly, we observed that the model sometimes exploits biases in the training data instead of learning to ground instructions. For instance, in Put Blocks in Bowl, the training set consisted of only one datapoint on "yellow blocks" being placed inside a "blue bowl". This made it difficult to condition the model to place "yellow blocks" in non-blue bowls. But instances with just one or two examples where a colored block went to different colored bowls was sufficient to make the model pay attention to the language. In summary, unbiased datasets containing both a good coverage of expected skills and invariances, and a decent number of training demonstrations, are crucial for good real-world performance.

5 Conclusion

We introduced CLIPORT, an end-to-end framework for language-conditioned fine-grained manipulation. Our experiments, specifically with multi-task models, indicate that data-driven approaches to generalization have yet to be fully-exploited in robotics. With the right action abstraction (pick-and-place) and semantic priors (vision-language models) end-to-end systems can learn new skills without top-down pipelines that require domain-specific engineering.

While CLIPORT can solve a range of tabletop tasks, extending it to dexterous 6-DOF manipulation that goes beyond the pick-and-place primitive remains a challenge. As such, CLIPORT shares some limitations with Transporter: it cannot handle complex partially-observable scenes, or output continuous control for multi-fingered hands, or predict task-completion. But overall, we are excited by the possibilities of data-driven approaches for building scalable and generalizable robotic systems.

References

[1] A. Radford, J. W. Kim, C. Hallacy, A. Ramesh, G. Goh, S. Agarwal, G. Sastry, A. Askell, P. Mishkin, J. Clark, G. Krueger, and I. Sutskever. Learning Transferable Visual Models From Natural Language Supervision. *arXiv:2103.00020 [cs]*, Feb. 2021.

[2] A. Zeng, P. Florence, J. Tompson, S. Welker, J. Chien, M. Attarian, T. Armstrong, I. Krasin, D. Duong, V. Sindhwani, and J. Lee. Transporter networks: Rearranging the visual world for robotic manipulation. *Conference on Robot Learning (CoRL)*, 2020.

[3] I. Akkaya, M. Andrychowicz, M. Chociej, M. Litwin, B. McGrew, A. Petron, A. Paino, M. Plappert, G. Powell, R. Ribas, et al. Solving rubik's cube with a robot hand. *arXiv preprint arXiv:1910.07113*, 2019.

[4] D. Kalashnikov, A. Irpan, P. Pastor, J. Ibarz, A. Herzog, E. Jang, D. Quillen, E. Holly, M. Kalakrishnan, V. Vanhoucke, et al. Qt-opt: Scalable deep reinforcement learning for vision-based robotic manipulation. *Conference on Robot Learning (CoRL)*, 2018.

[5] D. Kalashnikov, J. Varley, Y. Chebotar, B. Swanson, R. Jonschkowski, C. Finn, S. Levine, and K. Hausman. Mt-opt: Continuous multi-task robotic reinforcement learning at scale. *arXiv preprint arXiv:2104.08212*, 2021.

[6] D. Seita, P. Florence, J. Tompson, E. Coumans, V. Sindhwani, K. Goldberg, and A. Zeng. Learning to rearrange deformable cables, fabrics, and bags with goal-conditioned transporter networks. In *IEEE International Conference on Robotics and Automation (ICRA)*, 2021.

[7] M. Shridhar and D. Hsu. Interactive visual grounding of referring expressions for human-robot interaction. In *Proceedings of Robotics: Science and Systems (RSS)*, 2018.

[8] C. Matuszek, L. Bo, L. Zettlemoyer, and D. Fox. Learning from unscripted deictic gesture and language for human-robot interactions. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 28, 2014.

[9] M. Bollini, S. Tellex, T. Thompson, N. Roy, and D. Rus. Interpreting and executing recipes with a cooking robot. In *Experimental Robotics*, pages 481–495. Springer, 2013.

[10] D. K. Misra, J. Sung, K. Lee, and A. Saxena. Tell me dave: Context-sensitive grounding of natural language to manipulation instructions. *The International Journal of Robotics Research (IJRR)*, 35(1-3):281–300, 2016.

[11] T. Chen, S. Kornblith, M. Norouzi, and G. Hinton. A simple framework for contrastive learning of visual representations. In *International conference on machine learning*, pages 1597–1607. PMLR, 2020.

[12] K. He, H. Fan, Y. Wu, S. Xie, and R. Girshick. Momentum contrast for unsupervised visual representation learning. In *The IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 9729–9738, 2020.

[13] J. Lu, D. Batra, D. Parikh, and S. Lee. Vilbert: Pretraining task-agnostic visiolinguistic representations for vision-and-language tasks. In *Advances in Neural Information Processing Systems (NeuRIPS)*, 2019.

[14] Y. C. Chen, L. Li, L. Yu, A. El Kholy, F. Ahmed, Z. Gan, Y. Cheng, and J. Liu. Uniter: Universal image-text representation learning. In *European Conference on Computer Vision*, pages 104–120. Springer, 2020.

[15] H. Tan and M. Bansal. Lxmert: Learning cross-modality encoder representations from transformers. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2019.

[16] D. H. Hubel and T. N. Wiesel. Receptive fields and functional architecture in two nonstriate visual areas (18 and 19) of the cat. *Journal of neurophysiology*, 28(2):229–289, 1965.

[17] M. Livingstone and D. Hubel. Segregation of form, color, movement, and depth: anatomy, physiology, and perception. *Science*, 240(4853):740–749, 1988.

[18] A. Derrington and P. Lennie. Spatial and temporal contrast sensitivities of neurones in lateral geniculate nucleus of macaque. *The Journal of physiology*, 357(1):219–240, 1984.

[19] A. Kamath, M. Singh, Y. LeCun, I. Misra, G. Synnaeve, and N. Carion. Mdetr–modulated detection for end-to-end multi-modal understanding. *arXiv preprint arXiv:2104.12763*, 2021.

[20] K. He, G. Gkioxari, P. Dollár, and R. Girshick. Mask r-cnn. In *The IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2017.

[21] Y. Xiang, T. Schmidt, V. Narayanan, and D. Fox. Posecnn: A convolutional neural network for 6d object pose estimation in cluttered scenes. In *Proceedings of Robotics: Science and Systems (RSS)*, 2018.

[22] M. Zhu, K. G. Derpanis, Y. Yang, S. Brahmbhatt, M. Zhang, C. Phillips, M. Lecce, and K. Daniilidis. Single image 3d object detection and pose estimation for grasping. In *2014 IEEE International Conference on Robotics and Automation (ICRA)*, pages 3936–3943. IEEE, 2014.

[23] A. Zeng, K.-T. Yu, S. Song, D. Suo, E. Walker, A. Rodriguez, and J. Xiao. Multi-view self-supervised deep learning for 6d pose estimation in the amazon picking challenge. In *2017 IEEE international conference on robotics and automation (ICRA)*, pages 1386–1383. IEEE, 2017.

[24] X. Deng, Y. Xiang, A. Mousavian, C. Eppner, T. Bretl, and D. Fox. Self-supervised 6d object pose estimation for robot manipulation. In *2020 IEEE International Conference on Robotics and Automation (ICRA)*, pages 3665–3671. IEEE, 2020.

[25] C. Xie, Y. Xiang, A. Mousavian, and D. Fox. The best of both modes: Separately leveraging rgb and depth for unseen object instance segmentation. In *Conference on Robot Learning (CoRL)*, pages 1369–1378. PMLR, 2020.

[26] P. R. Florence, L. Manuelli, and R. Tedrake. Dense object nets: Learning dense visual object descriptors by and for robotic manipulation. In *Conference on Robot Learning (CoRL)*, 2018.

[27] P. Florence, L. Manuelli, and R. Tedrake. Self-supervised correspondence in visuomotor policy learning. *IEEE Robotics and Automation Letters*, 5(2):492–499, 2019.

[28] P. Sundaresan, J. Grannen, B. Thananjeyan, A. Balakrishna, M. Laskey, K. Stone, J. E. Gonzalez, and K. Goldberg. Learning rope manipulation policies using dense object descriptors trained on synthetic depth data. In *2020 IEEE International Conference on Robotics and Automation (ICRA)*, pages 9411–9418. IEEE, 2020.

[29] L. Manuelli, W. Gao, P. Florence, and R. Tedrake. kpam: Keypoint affordances for category-level robotic manipulation. In *International Symposium on Robotics Research (ISRR)*, 2019.

[30] T. D. Kulkarni, A. Gupta, C. Ionescu, S. Borgeaud, M. Reynolds, A. Zisserman, and V. Mnih. Unsupervised learning of object keypoints for perception and control. *Advances in neural information processing systems (NeuRIPS)*, 32:10724–10734, 2019.

[31] X. Liu, R. Jonschkowski, A. Angelova, and K. Konolige. Keypose: Multi-view 3d labeling and keypoint estimation for transparent objects. In *The IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 11602–11610, 2020.

[32] K. Zakka, A. Zeng, J. Lee, and S. Song. Form2fit: Learning shape priors for generalizable assembly from disassembly. In *2020 IEEE International Conference on Robotics and Automation (ICRA)*, pages 9404–9410. IEEE, 2020.

[33] S. Song, A. Zeng, J. Lee, and T. Funkhouser. Grasping in the wild: Learning 6dof closed-loop grasping from low-cost demonstrations. *IEEE Robotics and Automation Letters*, 5(3): 4978–4985, 2020.

[34] A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, L. Kaiser, and I. Polosukhin. Attention is all you need. In *Advances in Neural Information Processing Systems (NeuRIPS)*, 2017.

[35] J. Devlin, M. W. Chang, K. Lee, and K. Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the Conference of the North American Chapter of the Association for Computational Linguistics (NAACL)*, 2018.

[36] A. Dosovitskiy, L. Beyer, A. Kolesnikov, D. Weissenborn, X. Zhai, T. Unterthiner, M. Dehghani, M. Minderer, G. Heigold, S. Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. In *International Conference on Learning Representations*, 2020.

[37] F. Yu, J. Tang, W. Yin, Y. Sun, H. Tian, H. Wu, and H. Wang. Ernie-vil: Knowledge enhanced vision-language representations through scene graph. *arXiv preprint arXiv:2006.16934*, 2020.

[38] Y. Bisk, D. Yuret, and D. Marcu. Natural language communication with robots. In *Proceedings of the North American Chapter of the Association for Computational Linguistics (NAACL)*, pages 751–761, 2016.

[39] J. Thomason, S. Zhang, R. J. Mooney, and P. Stone. Learning to interpret natural language commands through human-robot dialog. In *Twenty-Fourth International Joint Conference on Artificial Intelligence (IJCAI)*, 2015.

[40] J. Hatori, Y. Kikuchi, S. Kobayashi, K. Takahashi, Y. Tsuboi, Y. Unno, W. Ko, and J. Tan. Interactively picking real-world objects with unconstrained spoken language instructions. In *Proceedings of International Conference on Robotics and Automation (ICRA)*, 2018.

[41] Y. Chen, R. Xu, Y. Lin, and P. A. Vela. A Joint Network for Grasp Detection Conditioned on Natural Language Commands. *arXiv:2104.00492 [cs]*, Apr. 2021.

[42] V. Blukis, R. A. Knepper, and Y. Artzi. Few-shot object grounding for mapping natural language instructions to robot control. In *Conference on Robot Learning (CoRL)*, 2020.

[43] C. Paxton, Y. Bisk, J. Thomason, A. Byravan, and D. Fox. Prospection: Interpretable plans from language by predicting the future. In *International Conference on Robotics and Automation (ICRA)*, pages 6942–6948. IEEE, 2019.

[44] S. Tellex, T. Kollar, S. Dickerson, M. Walter, A. Banerjee, S. Teller, and N. Roy. Understanding natural language commands for robotic navigation and mobile manipulation. In *Proceedings of the AAAI Conference on Artificial Intelligence (AAAI)*, 2011.

[45] C. Lynch and P. Sermanet. Grounding language in play. *arXiv preprint arXiv:2005.07648*, 2020.

[46] K. Simonyan and A. Zisserman. Two-stream convolutional networks for action recognition in videos. *arXiv preprint arXiv:1406.2199*, 2014.

[47] C. Feichtenhofer, A. Pinz, and A. Zisserman. Convolutional two-stream network fusion for video action recognition. In *The IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 1933–1941, 2016.

[48] C. Feichtenhofer, H. Fan, J. Malik, and K. He. Slowfast networks for video recognition. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (CVPR)*, pages 6202–6211, 2019.

[49] E. Kazakos, A. Nagrani, A. Zisserman, and D. Damen. Slow-fast auditory streams for audio recognition. In *ICASSP 2021-2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 855–859. IEEE, 2021.

[50] F. Xiao, Y. J. Lee, K. Grauman, J. Malik, and C. Feichtenhofer. Audiovisual slowfast networks for video recognition. *arXiv preprint arXiv:2001.08740*, 2020.

[51] A. Zeng, S. Song, K.-T. Yu, E. Donlon, F. R. Hogan, M. Bauza, D. Ma, O. Taylor, M. Liu, E. Romo, et al. Robotic pick-and-place of novel objects in clutter with multi-affordance grasping and cross-domain image matching. In *2018 IEEE international conference on robotics and automation (ICRA)*, pages 3750–3757. IEEE, 2018.

[52] D. Misra, A. Bennett, V. Blukis, E. Niklasson, M. Shatkhin, and Y. Artzi. Mapping instructions to actions in 3d environments with visual goal prediction. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2018.

[53] G. Goh, N. C. †, C. V. †, S. Carter, M. Petrov, L. Schubert, A. Radford, and C. Olah. Multimodal neurons in artificial neural networks. *Distill*, 2021. doi:10.23915/distill.00030. https://distill.pub/2021/multimodal-neurons.

[54] E. Coumans and Y. Bai. Pybullet, a python module for physics simulation for games, robotics and machine learning. 2016.

[55] Google scanned objects dataset, 2020. URL https://app.ignitionrobotics.org/GoogleResearch/fuel/collections/Google%20Scanned%20Objects.

[56] K. He, X. Zhang, S. Ren, and J. Sun. Deep residual learning for image recognition. In *The IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 770–778, 2016.

[57] J. Lu, V. Goswami, M. Rohrbach, D. Parikh, and S. Lee. 12-in-1: Multi-task vision and language representation learning. In *The IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2020.

[58] A. Paszke, S. Gross, F. Massa, A. Lerer, J. Bradbury, G. Chanan, T. Killeen, Z. Lin, N. Gimelshein, L. Antiga, et al. Pytorch: An imperative style, high-performance deep learning library. *arXiv preprint arXiv:1912.01703*, 2019.

[59] V. Sanh, L. Debut, J. Chaumond, and T. Wolf. Distilbert, a distilled version of bert: smaller, faster, cheaper and lighter. *arXiv preprint arXiv:1910.01108*, 2019.