GENERATIVE ADVERSARIAL TRAINING FOR NEURAL COMBINATORIAL OPTIMIZATION MODELS

ABSTRACT

Recent studies show that deep neural networks can be trained to learn good heuristics for various Combinatorial Optimization Problems (COPs). However, it remains a great challenge for the trained deep optimization models to generalize to distributions different from the training one. To address this issue, we propose a general framework, Generative Adversarial Neural Combinatorial Optimization (GANCO) which is equipped with another deep model to generate training instances for the optimization model, so as to improve its generalization ability. The two models are trained alternatively in an adversarial way, where the generation model is trained by reinforcement learning to find instance distributions hard for the optimization model. We apply the GANCO framework to two recent deep combinatorial optimization models, i.e., Attention Model (AM) and Policy Optimization with Multiple Optima (POMO). Extensive experiments on various problems such as Traveling Salesman Problem, Capacitated Vehicle Routing Problem, and 0-1 Knapsack Problem show that GANCO can significantly improve the generalization ability of optimization models on various instance distributions, with little sacrifice of performance on the original training distribution.

1 INTRODUCTION

Combinatorial Optimization Problems (COPs) are a family of problems with the goal of finding the best one(s) from a finite set of solutions. Due to the considerably large solution space, many important COPs are hard to solve, such as the vehicle routing problems (Toth & Vigo, 2002). Exact algorithms based on branch-and-bound (Lawler & Wood, 1966) or its variants can provide elegant theoretical guarantees but the worst-case computational complexity is exponential, hence impractical for problems of medium and large sizes. In contrast, heuristic methods can usually attain good solutions in reasonable running time, which are often preferred in practical applications.

Traditional heuristics are designed based on expert knowledge for specific problems, which usually requires a large amount of time and efforts to develop. These manually designed heuristics could suffer from relatively poor performance. Moreover, for less studied problems, sufficient expert knowledge may even be unavailable. Recent studies suggest that deep learning could greatly facilitate in automating the design of heuristics, and alleviating the heavy reliance on expert knowledge. With the prior that the instances may follow certain distribution (e.g., locations in a routing problem may uniformly scatter in an area), deep models can be trained to learn heuristics in an end-to-end way (Dai et al., 2017; Kool et al., 2019; Chen & Tian, 2019). It has been shown that these models perform well with relatively short running time on COP instances following the training distribution.

However, after the trained model is deployed, it could encounter many instances following unknown distributions different from the training one, especially for real-life applications. As shown in many existing works and our experiments, when applied to infer the instances following a different distribution, the generalization performance of deep models gets much inferior, which severely hinders the practical use of the learned heuristics. Such mismatch between the training and testing distributions is always an important issue for most learning based methods, but is particularly severe for neural combinatorial optimization (NCO) models because the solution quality intricately depends on the instance distributions. The generalization to instances with different distributions has been widely acknowledged for the importance (e.g., in Mazyavkina et al. (2021)) and remains a challenge.

To tackle this issue, we propose the Generative Adversarial Neural Combinatorial Optimization (GANCO) framework which is model agnostic and generally applicable to various neural combinatorial optimization models for solving different COPs. Instead of training an *optimization* model only on instances following the predefined distribution, another deep neural network is deployed as a *generation* model to produce training instances following the distributions on which the optimization model performs poorly. The generation model and optimization model are trained alternatively in an adversarial way. Specifically, the generation model is trained by reinforcement learning to maximize the performance gap of the current optimization model on the generated instances with respect to a traditional non-learning baseline algorithm. The optimization model is trained in the original way but using the training dataset augmented with the newly generated instances to improve the generalization performance, i.e., to reduce the performance gap. As we will show in the experiments, the non-learning baseline algorithms do not need to be very strong or fast.

To demonstrate the effectiveness of the proposed GANCO framework, we apply it to a representative neural combinatorial optimization model, the Attention Model (AM, Kool et al. (2019)) on various COPs including Traveling Salesman Problem (TSP), Capacitated Vehicle Routing Problem (CVRP), Orienteering Problem (OP), Prize Collecting TSP (PCTSP) and 0-1 Knapsack Problem (KP). In the extensive experiments, we show that the proposed GANCO framework improves the generalization performance of the original optimization model on various testing distributions with little sacrifice of performance on the original training distribution. Furthermore, we show that the proposed GANCO framework can be readily and effectively applied to other optimization models such as the Policy Optimization with Multiple Optima (POMO, Kwon et al. (2020)).

2 RELATED WORKS

Most deep learning models are trained to learn the construction heuristics where the model picks the actions sequentially to construct a solution (e.g., Bello et al. (2017); Nazari et al. (2018); Kool et al. (2019); Hottung et al. (2021); Kwon et al. (2020)), which perform well with fairly short running time. While some other models learn the improvement heuristics to locally refine existing solutions, which usually search over a large number of solutions and are relatively slow. Moreover, they often need to fit in frameworks specifically designed for different problems, such as 2-opt (d O Costa et al., 2020), large neighborhood search (Hottung & Tierney, 2020) and combinations of local operators (Lu et al., 2020). Most models are trained with reinforcement learning (RL) except for several ones with supervised learning, e.g., Vinyals et al. (2015) and Joshi et al. (2019). Though we use representative construction heuristic models with RL in the experiments, our proposed GANCO framework can also be applied to models of other types.

The most well-known models trained with adversary are the Generative Adversarial Networks (Goodfellow et al., 2014; Yang et al., 2018; Zhang et al., 2019), which serve to generate new data samples to imitate the training set. The generative network generates the sample candidates whereas the discriminative network classifies whether the sample is generated or genuine. In contrast, the goal of our proposed GANCO framework is to train the optimization model for better generalization ability where the generation model is used only to generate more informative training samples.

To the best of our knowledge, the most related work considering generating data samples for COPs is Liu et al. (2020) where the samples are generated by performing crossover and mutation to existing instances. The goal is to search better parameters configuration for given traditional solvers. Whereas our proposed framework is designed to generate instances with the guidance of deep reinforcement learning and improve the generalization performance for neural combinatorial optimization models. In our experiments, we also verify the necessity of our data generation method.

3 MODEL

For most learning based methods, the patterns are learned from the training data and usually applicable to similar testing samples. However, if the distributions of training and testing samples are considerably different, these learned patterns may not be general enough to guarantee desirable inference performance. As we will show in the experiments, this issue is particularly severe for COPs due to the intricate relationship between the solution and the instance distribution.

Figure 1: Generative Adversarial Neural Combinatorial Optimization (GANCO) framework. We use 2 adversarial iterations of generation training and optimization training for illustration purpose.

Instead of designing a network architecture to achieve better generalization performance for specific problems, we aim to propose a model agnostic framework which is generally applicable to different optimization models and training methods. The only requirement for the optimization models is that they are able to learn effective patterns from the training data and perform well on similar testing samples, which could be fulfilled by most of the recent learning based models.

To this end, we propose the Generative Adversarial Neural Combinatorial Optimization (GANCO) framework, as shown in Figure 1. Rather than training the optimization model solely on instances sampled from the predefined training distribution, we also deploy another deep learning model to generate instances on which the optimization model performs poorly. The generation model is trained by reinforcement learning to maximize the performance gap between the optimization model and a non-learning baseline algorithm on the generated instances. And the optimization model is trained with the generated samples to improve the performance on similar instances. In other words, the generation model and the optimization model are trained to maximize and minimize the performance gaps on the generated instances, respectively. In such an adversarial training way, the lower bound of the optimization model performance on the instance distributions generated by the generation model will be pushed up. We detail the generation model and the GANCO framework in the following subsections.

3.1 GENERATION MODEL

As suggested in existing works (Kool et al., 2019; Kwon et al., 2020), many important COPs can be viewed as a graph of n nodes with different attributes, like the city coordinates for TSP and the item information for KP. Therefore, we formulate the data generation task as determining the attribute values for each node of an instance. However, the proposed framework could be easily adapted to other types of COPs, such as by determining the presence of each edge for problems depending on the graph connectivity (e.g., the Boolean Satisfiability Problem).

The generation model Ω takes the noise sample h for each node as the input to output the distribution parameters for the node attributes. We format the noise input $h \in \mathbb{R}^{n \times 2}$ as 2-dimensional variables for each node $j = 1, .., n$ following the unit uniform distribution independently, i.e., $h \sim U(0, 1)$. Pertaining to the network architecture, we use the self-attention block proposed in the Attention Model (AM, Kool et al. (2019)), which consists of a multi-head self-attention layer (Vaswani et al., 2017), two node-wise feed-forward layers with Batch Normalization (Ioffe & Szegedy, 2015) and skip connection (He et al., 2016). The noise input is node-wise linearly projected to H-dimension and encoded by k self-attention blocks. And another node-wise linear layer with a sigmoid activation projects the hidden vectors to the output distribution parameters $\Omega(h) \in \mathbb{R}^{n \times d}$ where d is the number of attributes for each node. Then we draw the sample $\tilde{x}$ from the Gaussian distribution $\mathcal{N}(\mu, \sigma^2)$ with mean $\mu = \Omega(h)$ and fixed standard deviation σ. The network outputs are kept in the same range $[0, 1]$ to use the same variance for different attributes. The sample $\tilde{x}$ is scaled to the corresponding valid ranges (and discretized for discrete attributes) to attain the node attributes $x = A(\tilde{x})$.

The goal of the generation model is to generate instances on which the optimization model currently performs poorly. Since different instances have different optimal objective values, the attained objective values alone are not meaningful enough to evaluate the model performance. Although the optimality gap appears to be a good alternative metric in this case, it often requires expensive computation to attain the optimal solutions. On the other hand, while achieving approximate solutions, traditional non-learning algorithms tend to perform relatively stably on instances with different distributions, compared to the learning based methods. Therefore, the performance gaps of the optimization model with respect to a traditional non-learning baseline algorithm could be regarded as a favorable metric. Theoretically, the baseline algorithm performance can be arbitrarily inferior as long as it performs consistently (e.g., similar optimality gaps) on different instances. As we will show in our experiments, the baseline algorithms do not need to be very strong or fast as the training for generation models converges in a relatively small number of iterations.

The generation model is trained by the reinforcement learning (RL). Specifically, the *state* of RL environment is the noise input $h \in \mathbb{R}^{n \times 2}$. The *action* is to sample the attribute values for a node. An *episode* is to sample the attribute values $x = A(\tilde{x})$ with $\tilde{x} \sim \mathcal{N}(\Omega(h), \sigma^2)$ for all the nodes to form an instance. The *reward* for an episode is the performance gap between the optimization model Φ and baseline algorithm B on the sampled instance x. The loss function is formally defined as follow,

$$L(\Omega) = -E_{h \sim U(0,1), \tilde{x} \sim \mathcal{N}(\Omega(h), \sigma^2)} G(x, \Phi, B), \qquad (1)$$

where $G(x, \Phi, B) = (O_\Phi(x) - O_B(x))/O_B(x)$ is the performance (objective) gap; $O_\Phi(x)$ and $O_B(x)$ are the objective values of the solutions found by the optimization model Φ and the baseline algorithm B for the generated instance x, respectively. Different from the generator in GAN (Goodfellow et al., 2014) which deterministically infers the instance given the noise input, we sample the noise input to infer the distribution and sample the instance from the output distribution. The generation model is trained by the REINFORCE algorithm (Sutton et al., 2000) with reward baseline as the mean of the gaps in a batch. The gradient to train the generation model is expressed as follow,

$$\nabla_\Omega L(\Omega) \approx -\frac{1}{N} \sum_{i=1}^{N} \left(G(x_i, \Phi, B) - \frac{1}{N} \sum_{j=1}^{N} G(x_j, \Phi, B) \right) \nabla_\Omega log\mathcal{N} \left(\tilde{x}_i; \Omega(h_i), \sigma^2 \right), \qquad (2)$$

where i and j are the instance indices; N is the batch size; $\tilde{x}_i \in R^{n \times d} \sim \mathcal{N}(\Omega(h_i), \sigma^2)$; and $\mathcal{N}(\tilde{x}_i; \Omega(h_i), \sigma^2)$ is the probability of $\tilde{x}_i$ sampled from the Gaussian distribution $\mathcal{N}(\Omega(h_i), \sigma^2)$.

3.2 GANCO FRAMEWORK

The formal flow of the GANCO framework is summarized in Algorithm 1 and a simplified illustration of the alternative training process is displayed in Figure 2. The GANCO framework is compatible with different optimization models and training algorithms. In the framework, the optimization model is always trained by the same algorithm from its original work.

Pretraining Stage First, we train the optimization model on the instances sampled from the original training distribution. To make sure that the performance improvement in the experiments is brought by the proposed GANCO framework rather than more epochs of training, we train the model until fully converged. However, convergence is not necessary in practice.

Adversarial Training Stage After pretraining, the generation model and optimization model are trained alternatively during the adversarial iterations. In each iteration, the generation model is first trained to generate the instance distributions on which the current optimization model exhibits poor performances. And the training distribution will be augmented with the newly generated distribution. Then the optimization model is trained with instances sampled from the augmented distribution to improve the performance on new instances while preserving the performance on old ones.

Generation Training At the beginning of each adversarial iteration, the parameters of the generation model are re-initialized randomly. In doing so, it prevents the model from being stuck in the local optimum of previous adversarial iterations and also allows the model to learn diverse instance distributions. Specifically, the generation model is trained using the gradients in Eq. (2).

Optimization Training In each adversarial iteration, the optimization model is trained with the same algorithm from its original work but on different distributions. To achieve desirable performance on both the base training distributions and the adversarial generated distributions, we maintain a number of samples from the base distributions while adding the samples from the newly

generated ones. In the experiments, we find that good performance could be easily and effectively realized by a simple data composition rule. Specifically, we always keep half of the samples from the base training distribution and then equally sample the other half from the generated distribution in each adversarial iteration. For optimization models trained by RL, we sample new instances from these distributions for each epoch following the composition rule above.

Algorithm 1 Generative Adversarial Neural Combinatorial Optimization

---

Input: Optimization model Φ, generation model Ω, the non-learning baseline algorithm B, the base training distribution D_o, the number of adversarial iterations N_a, the number of training iterations N_Ω for Ω and the number of training epochs N_Φ for Φ in an adversarial iteration, the learning rate η and batch size N for Ω.
Output: Generative adversarial trained optimization model Φ
1: **while** Φ not converged **do**   ▷ Pretraining Stage
2:     Sample dataset X from D_o, train Φ on dataset X
3: **end while**
4: Initialize the training distribution D as D_o
5: **for** $k_a \leftarrow 1$ to N_a **do**   ▷ Adversarial Training Stage
6:     Randomly initialize the parameters for Ω
7:     **for** $k_\Omega \leftarrow 1$ to N_Ω **do**   ▷ k_ath Generation Training
8:         Sample the noise inputs $h \in \mathbb{R}^{N \times n \times 2}$, and infer the distribution parameters $\mu = \Omega(h)$
9:         **for** $i \leftarrow 1$ to N **do**
10:             Sample the instances x_i with $\tilde{x}_i \sim \mathcal{N}(\mu_i, \sigma^2)$, and use Φ and B to solve x_i
11:         **end for**
12:         $\Omega \leftarrow \Omega - \eta \nabla_\Omega L(\Omega)$
13:     **end for**
14:     Augment D with the distribution generated by Ω
15:     **for** $k_\Phi \leftarrow 1$ to N_Φ **do**   ▷ k_ath Optimization Training
16:         Sample dataset X from D following dataset composition rule, and train Φ on dataset X
17:     **end for**
18: **end for**

(a) Pretraining stage   (b) 1st generation   (c) 1st optimization   (d) 2nd generation   (e) 2nd optimization

Figure 2: The generation model and optimization model are trained alternatively in the GANCO framework. The green lines refer to the performance (objective gap) of optimization model on different instances x and the red arrows refer to the process of generating instances x based on the noise input h by the generation model. (a) The optimization model is pretrained with the base training distribution. (b) The generation model is trained to generate instances on which the current optimization model performs poorly. (c) The optimization model is trained to achieve better performance on these newly generated instances. (d) and (e) repeat another adversarial training iteration.

4 EXPERIMENTS AND ANALYSIS

We adopt the Attention Model (AM, Kool et al. (2019)) as the optimization model to verify the effectiveness of our proposed GANCO framework. AM is a widely used strong deep learning model for a series of routing problems and other COPs such as the Knapsack Problem. It is also used as the base model in many other recent works, e.g., Kwon et al. (2020); Xin et al. (2021); Hottung et al. (2021). As a heuristic model that learns to construct the solution sequentially, AM requires much less expert knowledge about the problems, especially compared with the region and rule design in Chen & Tian (2019) and the various perturbation operators in Lu et al. (2020). Typically, AM consists

Table 1: Results of AM and GANCO-AM for TSP on instances with different distributions.

Dist.	Method	$n = 20$			$n = 50$			$n = 100$		
		Obj.	Gap	Time	Obj.	Gap	Time	Obj.	Gap	Time
Base	Concorde	3.83	0.00%	4s	5.69	0.00%	39s	7.76	0.00%	142s
	AM	3.83	0.14%	0.3s	**5.73**	**0.73%**	0.8s	**7.93**	**2.16%**	2.1s
	GANCO-AM	**3.83**	**0.14%**		5.74	0.83%		7.94	2.28%	
Clustered	Concorde	3.19	0.00%	12s	4.01	0.00%	91s	5.15	0.00%	210s
	AM	3.21	0.39%	0.3s	4.14	3.07%	0.8s	5.60	8.85%	2.1s
	GANCO-AM	**3.20**	**0.27%**		**4.10**	**2.04%**		**5.46**	**6.06%**	
Uniform	Concorde	2.78	0.00%	15s	3.91	0.00%	78s	5.30	0.00%	183s
	AM	2.79	0.54%	0.3s	4.04	3.37%	0.8s	5.67	7.12%	2.1s
	GANCO-AM	**2.78**	**0.19%**		**3.97**	**1.45%**		**5.51**	**3.94%**	
Diagonal	Concorde	2.43	0.00%	21s	2.72	0.00%	152s	3.24	0.00%	196s
	AM	2.49	2.29%	0.3s	3.35	23.21%	0.8s	5.22	61.47%	2.1s
	GANCO-AM	**2.44**	**0.29%**		**2.78**	**2.37%**		**3.47**	**7.39%**	
Gaussian	Concorde	3.40	0.00%	12s	4.45	0.00%	51s	5.70	0.00%	167s
	AM	3.41	0.32%	0.3s	4.67	4.86%	0.8s	6.21	9.06%	2.1s
	GANCO-AM	**3.41**	**0.27%**		**4.54**	**1.96%**		**6.10**	**7.02%**	
TSPLIB-S	Concorde	3.40	0.00%	7s	4.50	0.00%	44s	5.76	0.00%	155s
	AM	3.41	0.21%	0.3s	4.58	1.77%	0.8s	6.06	5.27%	2.1s
	GANCO-AM	**3.41**	**0.17%**		**4.55**	**1.26%**		**5.99**	**4.12%**	

of an encoder and a decoder, which is trained by the REINFORCE algorithm with a deterministic rollout baseline. With three self-attention blocks, the encoder maps the nodes into embeddings. Based on the attention mechanism with glimpse, the decoder sequentially decides which node to visit at each step. We further improve AM in two ways, i.e., removing the Batch Normalization layers and training the model for more epochs until full convergence. Therefore, the performance of our base model is much better than the original ones reported in Kool et al. (2019). We discuss the reasons for the changes and the performance improvement with more details in Appendix H.

We use AM to solve TSP, CVRP, OP, PCTSP and KP in our experiments. The model is trained by the GANCO framework for 20 adversarial iterations, during each of which the generation model is trained for at most 2000 iterations (depending on problems) with batch size 100 and attribute standard deviation σ 0.05, and the optimization model is trained for 20 epochs with 256000 instances in each. The hyper-parameters for model architecture and optimizer are the same as those in Kool et al. (2019). For fast convergence and stable training, we fix the parameters in AM encoder and only train the decoder after the pretraining stage. We leverage Concorde, Hybrid Genetic Search (HGS, Vidal (2020)), Compass (Kobeaga et al., 2018), Iterated Local Search (ILS) and Dynamic Programming (DP) for TSP, CVRP, OP, PCTSP and KP, respectively, as the non-learning baseline algorithms for training the generation model. As our GANCO framework is relatively robust to the performance of (non-learning) baseline algorithms, we set the number of non-improvement iterations before termination for HGS as 100 instead of the default 20000 to save training time. Also, we exploit a faster version of ILS and round the item weights to two decimal places for DP. For a fair comparison, we consider the node attribute ranges of the original training distribution as the valid ones and show the results for the five problems on various distributions of instances within those ranges.

Besides, we apply the GANCO framework to another prevailing optimization model, i.e., POMO (Kwon et al., 2020) to solve TSP and CVRP, and also present more analysis about our GANCO framework. All our codes will be made available soon.

4.1 Traveling Salesman Problem

For TSP, the attributes learned by the generation model are the two coordinates for each node. The base training instances are generated uniformly in the unit square, following Kool et al. (2019). We adopt instances following five different distributions as the testing sets to evaluate the generalization performance. Specifically, (1) *Clustered*: the nodes are distributed in clusters following Uchoa et al. (2017); (2) *Uniform*: the nodes are uniformly sampled in a rectangle with random aspect ratios; (3) *Diagonal*: the nodes are distributed near the diagonal of rectangle; (4) *Gaussian*: the nodes follow

Table 2: Results of AM and GANCO-AM for CVRP on instances with different distributions.

Dist.	Method	$n = 20$			$n = 50$			$n = 100$		
		Obj.	Gap	Time	Obj.	Gap	Time	Obj.	Gap	Time
Base	HGS	6.11	0.00%	0.5h	10.34	0.00%	1.4h	15.57	0.00%	3.2h
	AM	**6.28**	**2.74%**	0.5s	**10.76**	**4.05%**	1.2s	16.38	5.22%	2.8s
	GANCO-AM	6.29	2.86%	0.5s	10.78	4.22%	1.2s	**16.37**	**5.16%**	2.8s
Original	HGS	5.77	0.00%	0.5h	9.43	0.00%	1.4h	14.03	0.00%	3.9h
	AM	**5.93**	**2.83%**	0.5s	9.90	5.03%	1.2s	15.05	7.25%	2.7s
	GANCO-AM	5.94	3.02%	0.5s	**9.89**	**4.82%**	1.2s	**14.90**	**6.18%**	2.8s
Small	HGS	3.55	0.00%	0.2h	5.11	0.00%	1.0h	7.21	0.00%	3.1h
	AM	4.08	14.86%	0.5s	5.82	13.87%	1.2s	8.79	21.80%	3.4s
	GANCO-AM	**3.85**	**8.55%**	0.4s	**5.63**	**10.05%**	1.1s	**8.27**	**14.65%**	2.6s
Large	HGS	8.84	0.00%	0.6h	15.00	0.00%	1.5h	21.93	0.00%	3.7h
	AM	9.11	2.99%	0.5s	15.95	6.34%	1.3s	23.47	7.02%	3.0s
	GANCO-AM	**9.04**	**2.17%**	0.5s	**15.89**	**5.95%**	1.2s	**23.29**	**6.20%**	3.0s
Identical	HGS	5.93	0.00%	0.4h	9.74	0.00%	1.2h	14.46	0.00%	2.9h
	AM	6.19	4.47%	0.5s	10.25	5.31%	1.1s	15.75	8.93%	3.4s
	GANCO-AM	**6.12**	**3.34%**	0.5s	**10.20**	**4.75%**	1.1s	**15.47**	**7.03%**	3.0s
Quadrant	HGS	5.83	0.00%	0.5h	9.56	0.00%	1.4h	14.05	0.00%	3.4h
	AM	6.05	3.72%	0.5s	10.24	7.11%	1.1s	15.37	9.40%	3.0s
	GANCO-AM	**6.04**	**3.59%**	0.5s	**10.18**	**6.52%**	1.2s	**15.14**	**7.76%**	3.0s
SL	HGS	4.40	0.00%	0.4h	6.69	0.00%	1.3h	9.52	0.00%	3.4h
	AM	4.59	4.18%	0.4s	7.17	7.21%	1.1s	10.67	12.06%	3.3s
	GANCO-AM	**4.58**	**4.05%**	0.4s	**7.13**	**6.59%**	1.1s	**10.43**	**9.51%**	2.8s

the bivariate Gaussian distribution with random correlation coefficients; (5) *TSPLIB-S*: the nodes are sampled without replacement from a random instance of the TSPLIB (Reinelt, 1991). We scale the instance coordinates to the valid range $[0, 1]$ with the aspect ratio fixed between horizontal and vertical axes so that the objective values of all solutions for an instance will only be scaled by the same constant. More details of data generation for each distribution are presented in Appendix A.

The results of Concorde, AM (with greedy decoding) and GANCO-AM are gathered in Table 1, where we report the average objective values and gaps, and the total time for solving the 10000 testing instances sampled from each distribution, respectively. For the traditional algorithm Concorde, we run 20 instances in parallel on a 28-core CPU (also applies to HGS, Compass, ILS and DP in the subsequent subsections). The AM and GANCO-AM are trained and tested on a RTX-2080Ti GPU. Generally, their run time is much shorter than the traditional algorithm as indicated in the table(s), which is a core strength of deep models. Clearly, GANCO-AM improves the performance on various generalization testing sets (i.e., the last five distributions in Table 1) by large margins. While the optimality gaps of AM could be up to 61.47% for TSP100 on certain distribution, its performance after GANCO training tends to be much desirable and stable. As the GANCO framework does not change the optimization model architecture or the total number of parameters, the slight drop of performance on the base training distribution is fairly acceptable.

A more complete comparison with other methods is presented in Appendix A, where we show the performance improvement of GANCO-AM over AM while sampling more solution trajectories (e.g., GANCO-AM reduces the average gaps of AM on generalization distributions from 16.52% and 14.55% to 4.47% and 3.48% for TSP100 with 10 and 100 trajectories, respectively). Although we follow the convention in existing works (Kool et al., 2019) to train and test the model on fixed-size instances ($n = 20, 50, 100$ for routing problems), we also demonstrate that GANCO-AM significantly improves the results of AM on larger-size instances of the TSPLIB benchmark in Appendix B, where the average gap is reduced from 11.95% to 7.05% for instances with 100-300 nodes.

4.2 CAPACITATED VEHICLE ROUTING PROBLEM

Following Kool et al. (2019), the base training distribution with respect to the customer and depot coordinates is the same as the one for TSP. The demands are uniformly sampled from $\{1, ..., 9\}$, and the capacities are fixed as 30, 40, 50 for CVRP with 20, 50, 100 customers, respectively. Therefore, apart from the coordinate attribute, the generation model also learns the demand attribute given the

Table 3: Results of POMO and GANCO-POMO for CVRP100.

Dist.	HGS		Method	Single trajectory			100 trajectories		
	Obj.	Time		Obj.	Gap	Time	Obj.	Gap	Time
Base	15.57	3.2h	POMO	**16.09**	**3.32%**	4.7s	**15.87**	**1.97%**	51.3s
			GANCO-POMO	16.12	3.56%	4.9s	15.89	2.09%	51.6s
Original	14.03	3.9h	POMO	15.14	7.89%	4.0s	14.69	4.68%	58.3s
			GANCO-POMO	**14.56**	**3.78%**	3.8s	**14.35**	**2.26%**	50.8s
Small	7.21	3.1h	POMO	10.15	40.74%	4.1s	8.84	22.47%	61.1s
			GANCO-POMO	**7.78**	**7.82%**	3.6s	**7.57**	**4.91%**	48.0s
Large	21.93	3.7h	POMO	24.22	10.43%	4.5s	23.40	6.68%	68.5s
			GANCO-POMO	**22.94**	**4.56%**	3.9s	**22.58**	**2.95%**	53.8s
Identical	14.46	2.9h	POMO	16.28	12.60%	4.5s	15.52	7.38%	67.3s
			GANCO-POMO	**14.93**	**3.28%**	4.1s	**14.75**	**2.01%**	54.4s
Quadrant	14.05	3.4h	POMO	15.92	13.32%	4.4s	15.15	7.81%	66.1s
			GANCO-POMO	**14.78**	**5.20%**	3.8s	**14.51**	**3.24%**	53.7s
SL	9.52	3.4h	POMO	10.79	13.28%	4.2s	10.25	7.67%	57.9s
			GANCO-POMO	**10.05**	**5.52%**	3.7s	**9.84**	**3.35%**	49.1s

fixed capacities. For the generalization testing sets, the customer nodes follow the six distributions used for TSP (including its base distribution). The depots are distributed uniformly, fixed at the center or a corner in the unit square, following CVRPLIB (Uchoa et al., 2017). For the customer demands, we adopt six distributions based on CVRPLIB. Particularly, they are sampled from $\{1, ..., 9\}$ (*Original*) or $\{1, 2\}$ (*Small*) or $\{8, 9\}$ (*Large*), random yet identical for all nodes within the same instance (*Identical*), small or large depending on the node quadrant (*Quadrant*), and most small with a few large ones (*SL*), respectively. More details for the testing sets are presented in Appendix C.

As shown in Table 2, the proposed GANCO framework ameliorates the AM performance by large margins on almost all generalization testing sets with greedy decoding. However, for CVRP20, the performance of AM and GANCO-AM are close on some testing sets (such as *Original*, *Quadrant* and *SL*), which indicates that the original AM is fairly robust to certain distributions as the problem size is small. In Appendix C, we also compare with another popular traditional algorithm LKH3 (Helsgaun, 2017) and demonstrate the significant improvement of GANCO-AM over AM with the sampling (rather than greedy) version (e.g., the average gaps are reduced from 9.06% and 7.62% to 6.93% and 5.75% for CVRP100 with 10 and 100 trajectories, respectively).

4.3 ORIENTEERING PROBLEM, PRIZE COLLECTING TSP AND 0-1 KNAPSACK PROBLEM

We also apply the GANCO framework on AM to solve OP, PCTSP and KP, respectively. The base training distributions for OP and PCTSP are the same as those in Kool et al. (2019). The prizes setting for OP uses the hardest one reported in its original work, where the customer prizes increase with the *distance* to the depot. The base distribution for KP follows the setting in Kwon et al. (2020). More details for problem settings, generalization testing distributions and results are presented in Appendix D, E and F for OP, PCTSP and KP, respectively. GANCO significantly boosts the performance on the three problems of different sizes, with greedy decoding and trajectories sampling for AM, respectively (e.g., with greedy decoding, the average gaps for OP100, PCTSP100 and KP200 are reduced from 13.68%, 14.75% and 0.25% to 7.67%, 7.33% and 0.17%, respectively).

4.4 POLICY OPTIMIZATION WITH MULTIPLE OPTIMA

To demonstrate that the GANCO framework is model agnostic, we further apply it to the Policy Optimization with Multiple Optima (POMO, Kwon et al. (2020)) for solving TSP and CVRP. We only consider 100 nodes since the results of the improved AM in our experiments are superior or close to those of POMO on other sizes as reported in Kwon et al. (2020). In Table 3, we record the results of POMO and GANCO-POMO by inferring a single trajectory and 100 trajectories (with the multi-starting-node strategy) for solving CVRP100. Clearly, the improvement of GANCO-POMO over POMO is salient for both decoding methods. In Appendix G, we present more discussion about CVRP and detailed results for TSP100 (the average gaps are reduced from 7.79% to 2.08% with single trajectory, and from 3.64% to 0.90% with 100 trajectories for TSP100, respectively).

| (a) GANCO-AM on TSP100 | (b) GANCO-AM on CVRP100 | (c) CANCO-POMO on CVRP100 |

Figure 3: Results of models trained with GANCO on testing sets along the adversarial iterations.

4.5 ANALYSIS ON THE GANCO FRAMEWORK

In Figure 3, we plot the objective gaps of GANCO models on various testing sets along adversarial iterations for TSP or CVRP, where iteration 0 refers to the original AM or POMO. To better demonstrate the learning process, we adopt the gaps with respect to the best objective values among all the iterations. Though fluctuating on some testing sets especially for the early iterations, the performance on those generalization testing sets becomes more desirable and stable quickly as the iteration increases.

Similarly, in Figure 4, we also plot the objective gaps of GANCO-AM for CVRP100 on 20 distributions, each of which is generated in the respective adversarial iteration. Clearly, the objective gaps of the worst-case instances found by the generation model are decreasing as the iteration increases, indicating that the lower bound of performance is pushed up with our GANCO. Furthermore, even before we train the model on a generated distribution (the

Figure 4: GANCO-AM results of CVRP100 on distributions generated by the generation model along the 20 adversarial iterations.

diagonal polyline), the performance on it also usually tends to become better, which verified the effectiveness of the learned patterns. Besides, we also compare our data generation method with the genetic based one in Liu et al. (2020) to justify the deep RL in our GANCO. The details are presented in Appendix A.

Though deep learning models still perform relatively inferior to strong traditional algorithms on well-studied COPs, GANCO framework effectively improves the generalization ability. With certain settings for the less studied problems, deep models performs favorably against the traditional ones (e.g., inferring 10 trajectories on PCTSP50, GANCO-AM improves the average gaps on testing sets from 2.32% to 1.31% with average run time 8s for 10000 instances, compared to the fast ILS 1.67% and 106s). Especially the adversarial training does not alter the model architecture and consumes fairly short time. The hardest training in our methods (GANCO-AM for CVRP100) costs less than 3 days compared to the 14 days for pretraining of AM. Furthermore, aiming at improving the generalization ability, GANCO could also be potentially applied to upcoming deep models, e.g., the one has stronger performance and could handle much larger sizes.

5 CONCLUSION AND FUTURE WORK

In this paper, we propose the GANCO framework to improve the generalization ability of Neural Combinatorial Optimization models. Trained by reinforcement learning, a generation model aims to find instances hard for an optimization model. With the two models trained alternatively in an adversarial way, the generalization ability of the optimization model is significantly boosted. We apply GANCO to two optimization models including AM and POMO on various COPs. Extensive experimental results show that our GANCO framework ameliorates the generalization performance by large margins with slight performance drops on the original training distribution. In future, we will investigate more optimization models and COPs, and study how to tackle much larger instances.

REFERENCES

Irwan Bello, Hieu Pham, Quoc V Le, Mohammad Norouzi, and Samy Bengio. Neural combinatorial optimization with reinforcement learning. In *International Conference on Learning Representations Workshop*, 2017.

Xinyun Chen and Yuandong Tian. Learning to perform local rewriting for combinatorial optimization. In *Proceedings of the 33rd International Conference on Neural Information Processing Systems*, pp. 6281–6292, 2019.

Paulo R d O Costa, Jason Rhuggenaath, Yingqian Zhang, and Alp Akcay. Learning 2-opt heuristics for the traveling salesman problem via deep reinforcement learning. In *Asian Conference on Machine Learning*, pp. 465–480. PMLR, 2020.

Hanjun Dai, Elias B Khalil, Yuyu Zhang, Bistra Dilkina, and Le Song. Learning combinatorial optimization algorithms over graphs. In *Proceedings of the 31st International Conference on Neural Information Processing Systems*, pp. 6351–6361, 2017.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. *Advances in neural information processing systems*, 27, 2014.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Keld Helsgaun. An effective implementation of the lin–kernighan traveling salesman heuristic. *European journal of operational research*, 126(1):106–130, 2000.

Keld Helsgaun. An extension of the lin-kernighan-helsgaun tsp solver for constrained traveling salesman and vehicle routing problems. *Roskilde: Roskilde University*, 2017.

André Hottung and Kevin Tierney. Neural large neighborhood search for the capacitated vehicle routing problem. In *ECAI 2020*, pp. 443–450. IOS Press, 2020.

André Hottung, Bhanu Bhandari, and Kevin Tierney. Learning a latent search space for routing problems using variational autoencoders. In *International Conference on Learning Representations*, 2021.

Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *International conference on machine learning*, pp. 448–456. PMLR, 2015.

Chaitanya K Joshi, Thomas Laurent, and Xavier Bresson. An efficient graph convolutional network technique for the travelling salesman problem. *arXiv preprint arXiv:1906.01227*, 2019.

Gorka Kobeaga, María Merino, and Jose A Lozano. An efficient evolutionary algorithm for the orienteering problem. *Computers & Operations Research*, 90:42–59, 2018.

Wouter Kool, Herke van Hoof, and Max Welling. Attention, learn to solve routing problems! In *International Conference on Learning Representations*, 2019.

Yeong-Dae Kwon, Jinho Choo, Byoungjip Kim, Iljoo Yoon, Youngjune Gwon, and Seungjai Min. Pomo: Policy optimization with multiple optima for reinforcement learning. *Advances in Neural Information Processing Systems*, 33, 2020.

Eugene L Lawler and David E Wood. Branch-and-bound methods: A survey. *Operations research*, 14(4):699–719, 1966.

Shengcai Liu, Ke Tang, and Xin Yao. Generative adversarial construction of parallel portfolios. *IEEE transactions on cybernetics*, 2020.

Hao Lu, Xingwen Zhang, and Shuang Yang. A learning-based iterative method for solving vehicle routing problems. In *International Conference on Learning Representations*, 2020.

Nina Mazyavkina, Sergey Sviridov, Sergei Ivanov, and Evgeny Burnaev. Reinforcement learning for combinatorial optimization: A survey. *Computers & Operations Research*, pp. 105400, 2021.

Mohammadreza Nazari, Afshin Oroojlooy, Martin Takáč, and Lawrence V Snyder. Reinforcement learning for solving the vehicle routing problem. In *Proceedings of the 32nd International Conference on Neural Information Processing Systems*, pp. 9861–9871, 2018.

Gerhard Reinelt. Tsplib—a traveling salesman problem library. *ORSA journal on computing*, 3(4): 376–384, 1991.

Richard S Sutton, David A McAllester, Satinder P Singh, and Yishay Mansour. Policy gradient methods for reinforcement learning with function approximation. In *Advances in neural information processing systems*, pp. 1057–1063, 2000.

Paolo Toth and Daniele Vigo. *The vehicle routing problem*. SIAM, 2002.

Eduardo Uchoa, Diego Pecin, Artur Pessoa, Marcus Poggi, Thibaut Vidal, and Anand Subramanian. New benchmark instances for the capacitated vehicle routing problem. *European Journal of Operational Research*, 257(3):845–858, 2017.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in neural information processing systems*, pp. 5998–6008, 2017.

Thibaut Vidal. Hybrid genetic search for the cvrp: Open-source implementation and swap* neighborhood. *arXiv preprint arXiv:2012.10384*, 2020.

Thibaut Vidal, Teodor Gabriel Crainic, Michel Gendreau, Nadia Lahrichi, and Walter Rei. A hybrid genetic algorithm for multidepot and periodic vehicle routing problems. *Operations Research*, 60 (3):611–624, 2012.

Oriol Vinyals, Meire Fortunato, and Navdeep Jaitly. Pointer networks. *Advances in Neural Information Processing Systems*, 28:2692–2700, 2015.

Liang Xin, Wen Song, Zhiguang Cao, and Jie Zhang. Multi-decoder attention model with embedding glimpse for solving vehicle routing problems. In *Proceedings of 35th AAAI Conference on Artificial Intelligence*, 2021.

Zhen Yang, Wei Chen, Feng Wang, and Bo Xu. Generative adversarial training for neural machine translation. *Neurocomputing*, 321:146–155, 2018.

Han Zhang, Ian Goodfellow, Dimitris Metaxas, and Augustus Odena. Self-attention generative adversarial networks. In *International conference on machine learning*, pp. 7354–7363. PMLR, 2019.

A   AM EXPERIMENTS ON TSP

For the Traveling Salesman Problem (TSP), the base training instances are generated uniformly in the unit square (Kool et al., 2019). We adopt instances following five different distributions as the testing sets to evaluate the generalization performance.

1. *Clustered*: Following Uchoa et al. (2017), the nodes are distributed in clusters where the number of clusters S is uniformly sampled from the integers $\{3, ..., 8\}$. With the unit square discretized to 1000×1000 grid, the cluster centers are uniformly and independently sampled. A node is located at location p with probability proportional to $\sum_{s=i}^{S} exp(-w(p, s)/0.04)$, where s is the cluster index and $w(p, s)$ is the distance between location p and cluster center s. All nodes in an instance are located at distinct points in the grid.

2. *Uniform*: For each instance, the nodes are distributed uniformly in a rectangle. The aspect ratio of the rectangle is sampled from the uniform distribution $U(0, 1)$ and the longer side is the horizontal or vertical axis with equal probabilities.

3. *Diagonal*: The nodes are distributed along the diagonal of a rectangle. For each instance, a rectangle is generated in the same way as in *Uniform* and a noise size t is sampled from the uniform distribution $U(0.05, 0.2)$. One of the two diagonals is selected with equal probabilities. For each node in this instance, one point is sampled uniformly from the selected diagonal. And two noises independently sampled from the uniform distribution $U(-t, t)$ are imposed for the horizontal and vertical axes, respectively, to attain the node coordinates.

4. *Gaussian*: For each instance, a correlation coefficient ρ is sampled from the uniform distribution $U(0, 1)$. The nodes follow the bivariate Gaussian distribution with the mean $(0.5, 0.5)$, the standard deviation 1 for both axes, and the correlation coefficient ρ. However, we will scale the instance coordinates to the valid coordinate range $[0, 1]$. Therefore, the mean and standard deviation will not affect the scaled instance.

5. *TSPLIB-S*: For each instance, a reference instance is sampled from the TSPLIB benchmark (Reinelt, 1991). The nodes are sampled from this reference instance without replacement to form a new instance. We sample the instances in this way to have fixed number of nodes for testing set. However, we further present the results on the TSPLIB benchmark with various sizes in Appendix B.

We do not include the Random-Clustered node distribution in Uchoa et al. (2017), where half of the nodes are distributed uniformly in the unit square and the other half are distributed in 3-8 clusters. It is similar to the base unit uniform distribution for problems with 100 nodes or less.

In Table 4, we show the results of Concorde, LKH, original AM and GANCO-AM on the testing sets with different instance distributions, which include the base training distribution and 5 generalization testing distributions. Concorde is a highly optimized exact solver for TSP, which finds the optimal solutions in a fairly short time. LKH (Helsgaun, 2000) uses the same hyper-parameters (10000 trails and 10 runs) as those in Kool et al. (2019). For all the traditional algorithms (Concorde and LKH for TSP, HGS and LKH3 for CVRP, Compass for OP, ILS for PCTSP, DP for KP), we run 20 instances in parallel on a 28-core CPU. And the run time of AM and GANCO-AM is measured on a single RTX2080Ti GPU. In addition to the greedy decoding version of AM and GANCO-AM which infer one solution trajectory, we further include another two versions, i.e., inferring 10 trajectories (10t) and 100 trajectories (100t). In the greedy version, the node to visit at each step is selected as the one with the highest probability. More solution trajectories could be achieved by sampling the node to visit at each step for multiple times according to the inferred probability. With one solution trajectory greedily inferred, we further sample another 9 and 99 solution trajectories which lead to versions of 10 trajectories (10t) and 100 trajectories (100t), respectively. Clearly, for most settings, GANCO-AM improves the performance of the original AM by large margins. For small problem sizes ($n = 20$), some distributions (*Gaussian* and *TSPLIB-S*) are not significantly different from the base one, where the performance of AM and GANCO-AM is similar. For the base training distribution, the performance of GANCO-AM is fairly close to the original AM. As the GANCO framework does not change the model architecture or the total number of parameters, the small performance drop on the original training distribution is acceptable considering the improvement of generalization ability on other testing distributions.

To demonstrate the necessity of deep generation model trained by reinforcement learning in GANCO, we adopt the genetic based (GB) generation method in Liu et al. (2020) to our framework, namely GB-AM. Instead of managing instance distributions in GANCO, GB applies crossover and mutation operators to given instances for generating new ones. After the pretraining stage, GB first samples a dataset from the base training distribution. During the adversarial training stage, GB generates each new instance with the crossover and mutation operators. Two reference instances are randomly selected from the dataset. The ith node attributes (coordinates) are taken from the corresponding node of either reference instance with equal probability. And then each coordinate is mutated with probability $1/\sqrt{n}$ to be replaced with a random number sampled from the unit uniform distribution (n is the number of nodes). And same as GANCO, the objective gaps of the optimization model with respect to the baseline algorithm (Concorde) are used as the score for the instances. Given the objective gap scores, a binary tournament is used to remove an instance with lower score (since we plan to reserve the hard instances) and keep the dataset size unchanged. The genetic based generation is performed at the beginning of each adversarial iteration and the optimization model is trained on the new dataset. For a fair comparison, we use the same hyperparameters (number of

Table 4: Results of AM and GANCO-AM for TSP on instances with different distributions.

Dist.	Method	n = 20 Obj.	Gap	Time	n = 50 Obj.	Gap	Time	n = 100 Obj.	Gap	Time
Base	Concorde	3.83	0.00%	4s	5.69	0.00%	39s	7.76	0.00%	142s
	LKH	3.83	0.00%	32s	5.69	0.00%	296s	7.76	0.00%	1241s
	AM greedy	3.83	0.14%		5.73	0.73%		7.93	2.16%	
	GANCO-AM greedy	3.83	0.14%	0.3s	5.74	0.83%	0.8s	7.94	2.28%	2.1s
	GB-AM greedy	**3.83**	**0.12%**		**5.73**	**0.71%**		**7.91**	**1.97%**	
	AM 10t	3.83	0.07%		5.71	0.43%		7.88	1.50%	
	GANCO-AM 10t	3.83	0.08%	2s	5.72	0.49%	7s	7.88	1.57%	20s
	GB-AM 10t	**3.83**	**0.07%**		**5.71**	**0.40%**		**7.86**	**1.34%**	
	AM 100t	3.83	0.04%		5.70	0.26%		7.84	1.08%	
	GANCO-AM 100t	3.83	0.05%	25s	5.71	0.32%	74s	7.85	1.13%	206s
	GB-AM 100t	**3.83**	**0.04%**		**5.70**	**0.25%**		**7.83**	**0.96%**	
Clustered	Concorde	3.19	0.00%	12s	4.01	0.00%	91s	5.15	0.00%	210s
	LKH	3.19	0.00%	110s	4.01	0.00%	655s	5.15	0.00%	2754s
	AM greedy	3.21	0.39%		4.14	3.07%		5.60	8.85%	
	GANCO-AM greedy	**3.20**	**0.27%**	0.3s	**4.10**	**2.04%**	0.8s	**5.46**	**6.06%**	2.1s
	GB-AM greedy	3.21	0.40%		4.14	3.22%		5.64	9.53%	
	AM 10t	3.20	0.20%		4.09	1.99%		5.53	7.43%	
	GANCO-AM 10t	**3.20**	**0.14%**	2s	**4.06**	**1.25%**	7s	**5.39**	**4.64%**	20s
	GB-AM 10t	3.20	0.22%		4.10	2.11%		5.57	8.24%	
	AM 100t	3.20	0.12%		4.07	1.31%		5.46	6.04%	
	GANCO-AM 100t	**3.20**	**0.09%**	25s	**4.05**	**0.81%**	77s	**5.33**	**3.58%**	208s
	GB-AM 100t	3.20	0.12%		4.07	1.42%		5.50	6.85%	
Uniform	Concorde	2.78	0.00%	15s	3.91	0.00%	78s	5.30	0.00%	183s
	LKH	2.78	0.00%	111s	3.91	0.00%	712s	5.30	0.00%	2051s
	AM greedy	2.79	0.54%		4.04	3.37%		5.67	7.12%	
	GANCO-AM greedy	**2.78**	**0.19%**	0.3s	**3.97**	**1.45%**	0.8s	**5.51**	**3.94%**	2.1s
	GB-AM greedy	2.79	0.53%		4.12	5.25%		5.67	7.06%	
	AM 10t	2.78	0.28%		4.00	2.13%		5.61	5.99%	
	GANCO-AM 10t	**2.78**	**0.10%**	2s	**3.95**	**0.83%**	7s	**5.45**	**2.97%**	21s
	GB-AM 10t	2.78	0.26%		4.05	3.54%		5.61	5.96%	
	AM 100t	2.78	0.15%		3.97	1.43%		5.56	4.97%	
	GANCO-AM 100t	**2.78**	**0.05%**	26s	**3.93**	**0.51%**	77s	**5.42**	**2.26%**	208s
	GB-AM 100t	2.78	0.14%		4.01	2.40%		5.56	4.96%	
Diagonal	Concorde	2.43	0.00%	21s	2.72	0.00%	152s	3.24	0.00%	196s
	LKH	2.43	0.00%	472s	2.72	0.00%	1775s	3.24	0.01%	3371s
	AM greedy	2.49	2.29%		3.35	23.21%		5.22	61.47%	
	GANCO-AM greedy	**2.44**	**0.29%**	0.3s	**2.78**	**2.37%**	0.8s	**3.47**	**7.39%**	2.1s
	GB-AM greedy	2.48	1.90%		3.66	34.72%		5.78	78.76%	
	AM 10t	2.46	1.10%		3.17	16.68%		5.08	56.92%	
	GANCO-AM 10t	**2.44**	**0.13%**	2s	**2.76**	**1.47%**	7s	**3.44**	**6.25%**	20s
	GB-AM 10t	2.46	0.96%		3.26	19.89%		5.61	73.51%	
	AM 100t	2.45	0.62%		3.04	11.95%		4.89	51.19%	
	GANCO-AM 100t	**2.43**	**0.06%**	26s	**2.74**	**0.88%**	77s	**3.40**	**5.05%**	209s
	GB-AM 100t	2.45	0.53%		3.06	12.65%		5.34	65.02%	
Gaussian	Concorde	3.40	0.00%	12s	4.45	0.00%	51s	5.70	0.00%	167s
	LKH	3.40	0.00%	75s	4.45	0.00%	421s	5.70	0.00%	1335s
	AM greedy	3.41	0.32%		4.67	4.86%		6.21	9.06%	
	GANCO-AM greedy	**3.41**	**0.27%**	0.3s	**4.54**	**1.96%**	0.8s	**6.10**	**7.02%**	2.1s
	GB-AM greedy	3.41	0.36%		4.65	4.30%		6.25	9.69%	
	AM 10t	3.41	0.16%		4.61	3.41%		6.15	7.92%	
	GANCO-AM 10t	**3.41**	**0.15%**	2s	**4.51**	**1.22%**	7s	**6.01**	**5.54%**	20s
	GB-AM 10t	3.41	0.19%		4.59	2.99%		6.20	8.73%	
	AM 100t	**3.40**	**0.08%**		4.56	2.34%		6.09	6.90%	
	GANCO-AM 100t	3.40	0.10%	26s	**4.49**	**0.79%**	77s	**5.95**	**4.33%**	209s
	GB-AM 100t	3.40	0.10%		4.55	2.09%		6.14	7.84%	
TSPLIB-S	Concorde	3.40	0.00%	7s	4.50	0.00%	44s	5.76	0.00%	155s
	LKH	3.40	0.00%	40s	4.50	0.01%	296s	5.76	0.01%	1386s
	AM greedy	3.41	0.21%		4.58	1.77%		6.06	5.27%	
	GANCO-AM greedy	**3.41**	**0.17%**	0.3s	**4.55**	**1.26%**	0.8s	**5.99**	**4.12%**	2.1s
	GB-AM greedy	3.41	0.21%		4.58	1.77%		6.09	5.79%	
	AM 10t	3.40	0.11%		4.55	1.23%		6.01	4.33%	
	GANCO-AM 10t	**3.40**	**0.10%**	2s	**4.53**	**0.77%**	7s	**5.93**	**2.94%**	21s
	GB-AM 10t	3.40	0.11%		4.55	1.24%		6.04	4.88%	
	AM 100t	**3.40**	**0.06%**		4.54	0.89%		5.97	3.63%	
	GANCO-AM 100t	3.40	0.06%	26s	**4.52**	**0.50%**	77s	**5.88**	**2.18%**	210s
	GB-AM 100t	3.40	0.06%		4.54	0.91%		6.00	4.16%	

adversarial iterations, number of running for the baseline algorithm, number of epochs for training the optimization model and number of instances in an epoch) for GB as those for GANCO.

As shown in Table 4, GB-AM does not improve the performance of AM on the generalization testing distributions. However, the performance on the base training distribution is slightly boosted. This

result is expected because the genetic based generation method tends to search locally within the field of base training distribution to find the hard instances. The resulting distribution still approximately follows the base training distribution. It would be extremely hard for the genetic operators to attain instances following a significantly different distribution. If we discretize the node attributes, the generation task for finding instances with large objective gaps is essentially a Combinatorial Optimization Problem. Therefore, to tackle such a relatively hard task, we exploit a deep model trained with reinforcement learning, which is fairly effective as we have demonstrated in the experiments.

B   AM EXPERIMENTS ON TSPLIB

In Table 5, we show the greedy decoding results of AM and GANCO-AM on TSPLIB instances with 100-1000 nodes. Both models are trained only with instances of 100 nodes. The instance coordinates are scaled to the valid range $[0, 1]$ with the fixed aspect ratio between the horizontal and vertical axes. Therefore, the objective values of the tours for an instance are scaled by the same constant. As the models are trained for 2-dimensional Euclidean TSP, we treat all the instances as in this distance space. Even though both models are trained with fixed-size graphs of 100 nodes, the performance on medium-size instances with 100-300 nodes are reasonably good. The average objective gaps for AM and GANCO-AM are 11.95% and 7.05% on instances with 100-300 nodes. Clearly, GANCO-AM effectively improves the generalization performance. However, both models start to deteriorate with lager sizes. The average gaps for AM and GANCO-AM are 27.44% and 23.37% on large instances with 300-1000 nodes. Nevertheless, the GANCO-AM still improves the generalization performance over AM.

Table 5: Results of AM and GANCO-AM for TSP on TSPLIB instances.

Instance	Opt.	AM Obj.	AM Gap	GANCO-AM Obj.	GANCO-AM Gap	Instance	Opt	AM Obj.	AM Gap	GANCO-AM Obj.	GANCO-AM Gap
KroA100	5.41	5.60	3.58%	**5.57**	**2.94%**	KroB100	5.63	5.88	4.45%	**5.83**	**3.68%**
KroC100	5.29	5.54	4.72%	**5.39**	**1.88%**	KroD100	5.46	**5.58**	**2.09%**	5.62	2.98%
KroE100	5.62	5.91	5.08%	**5.91**	**5.01%**	rd100	8.07	8.32	3.20%	**8.31**	**3.07%**
eil101	8.65	**8.87**	**2.58%**	8.94	3.31%	lin105	4.76	**4.94**	**3.95%**	5.12	7.64%
pr107	5.37	5.57	3.71%	**5.50**	**2.46%**	pr124	6.26	6.44	2.90%	**6.43**	**2.59%**
bier127	6.94	7.55	8.84%	**7.30**	**5.16%**	ch130	8.83	9.20	4.14%	**9.14**	**3.47%**
pr136	8.54	8.84	3.45%	**8.74**	**2.33%**	gr137*	5.68	6.19	8.97%	**6.00**	**5.57%**
pr144	5.36	**5.51**	**2.75%**	5.59	4.34%	kroB150	6.66	6.95	4.36%	**6.89**	**3.46%**
kroA150	6.71	6.96	3.71%	**6.93**	**3.23%**	ch150	9.34	9.72	4.08%	**9.59**	**2.70%**
pr152	5.37	6.02	12.05%	**5.73**	**6.73%**	u159	8.09	8.72	7.80%	**8.30**	**2.63%**
rat195	8.08	9.12	12.96%	**8.99**	**11.29%**	d198	3.92	6.12	56.04%	**5.04**	**28.51%**
kroA200	7.45	**7.91**	**6.09%**	8.05	8.08%	kroB200	7.47	**7.93**	**6.20%**	7.99	6.98%
gr202*	4.78	7.31	52.79%	**5.36**	**12.13%**	ts225	10.55	**10.98**	**4.05%**	11.21	6.23%
tsp225	8.22	9.09	10.62%	**9.06**	**10.28%**	pr226	5.54	**5.76**	**3.94%**	5.80	4.66%
gr229*	4.63	9.04	95.43%	**5.81**	**25.52%**	gil262	12.05	**12.58**	**4.42%**	12.66	5.08%
pr264	6.38	7.50	17.59%	**7.19**	**12.61%**	a280	9.24	10.61	14.84%	**10.42**	**12.78%**
pr299	7.22	**8.16**	**13.09%**	8.18	13.36%	linhp318	10.17	**11.09**	**9.09%**	11.14	9.54%
lin318	10.17	**11.09**	**9.09%**	11.14	9.54%	rd400	15.34	17.41	13.48%	**17.04**	**11.05%**
fl417	6.29	8.28	31.66%	**7.05**	**12.12%**	gr431*	5.45	9.39	72.38%	**7.45**	**36.83%**
pr439	8.99	**10.72**	**19.27%**	11.39	26.73%	pcb442	13.36	15.58	16.61%	**15.19**	**13.68%**
d493	9.35	12.51	33.75%	**11.48**	**22.80%**	att532	10.09	**12.61**	**24.98%**	12.62	25.06%
ali535*	6.00	8.33	38.87%	**8.02**	**33.57%**	u574	12.02	14.71	22.34%	**14.67**	**21.98%**
rat575	13.62	16.75	22.97%	**16.66**	**22.36%**	p654	7.20	**9.08**	**26.23%**	9.71	34.97%
d657	12.21	15.30	25.27%	**14.96**	**22.50%**	gr666*	8.74	11.65	33.32%	**11.65**	**33.26%**
u724	14.44	18.47	27.91%	**18.23**	**26.27%**	rat783	15.41	20.32	31.91%	**19.70**	**27.88%**
dsj1000	15.36	20.70	34.72%	**20.06**	**30.59%**						

* The gr and ali535 instances are treated as in 2-D Euclidean space with their latitude and longitude as coordinates.

C   AM EXPERIMENTS ON CVRP

We detail the instance distributions for CVRP. The base training distribution is acquired from Kool et al. (2019), where the coordinates of customers and depot follow the unit uniform distribution, and the demands are uniformly sampled from the integers $\{1, ..., 9\}$. The capacity is fixed as 30, 40 and 50 for CVRP with 20, 50 and 100 nodes, respectively. Existing benchmarks such as CVRPLIB (Uchoa et al., 2017) have ranges of node attributes (demands and capacity) different from those of the base training distribution (the valid attribute ranges). Therefore, we use the following testing distributions based on the CVRPLIB benchmark. For all the generalization testing sets, the coordinates

of customer nodes follow one of the 6 distributions for TSP (including the base training distribution and 5 generalization testing distributions) with equal probabilities. And the depot follows one of the 3 positioning with equal probabilities, 1) *Central*: at the center of unit square (0.5, 0.5), 2) *Eccentric*: at one of the four corners in the unit square, 3) *Random*: uniformly sampled from the unit square. The capacity is the same constant as the base training distribution. The demand distributions are adapted from the CVRPLIB, and presented as follows,

1. *Original*: The demands are uniformly sampled from $\{1, ..., 9\}$.
2. *Small*: The demands are sampled from the small integers $\{1, 2\}$.
3. *Large*: The demands are sampled from the large integers $\{8, 9\}$.
4. *Identical*: The demands for the nodes in the same instance are an identical integer uniformly sampled from $\{1, ..., 9\}$.
5. *Quadrant*: The demands depend on the quadrant of nodes. With the center of unit square (0.5, 0.5) as the origin, the demands of nodes in even quadrants are sampled from small integers $\{1, 2\}$ while the demands of nodes in odd quadrants are sampled from large integers $\{8, 9\}$.
6. *SL*: Most nodes have small demands while other nodes have large ones. For one instance, a random percentage p is sampled from the uniform distribution $U(70\%, 95\%)$. Thus, p of the total nodes have demands sampled from the small integers $\{1, 2\}$ and the others have demands sampled from the large integers $\{8, 9\}$.

In Table 6, we show the results of HGS, a faster version of HGS, LKH3, the original AM and GANCO-AM on the various instance distributions. Hybrid Genetic Search (HGS, Vidal et al. (2012); Vidal (2020)) combines genetic algorithm with local search, which is considered as the state-of-the-art algorithm for CVRP. The faster version of HGS (HGS fast) uses the number of non-improvement iterations before termination as 100 instead of the default 20000 for HGS. HGS fast is the non-learning baseline algorithm which we use to train the generation model. LKH3 (Helsgaun, 2017) is an extension of LKH (Helsgaun, 2000) to solve various routing problems including CVRP. We use the same hyper-parameters (SPECIAL parameters, 10000 trials, 1 run) as those used in Kool et al. (2019). For distributions with small demands (*Small*) where the number of nodes in a route is large, LKH3 excels at the tour optimization within the route and outperforms HGS. However, LKH3 is unfriendly to the instances with many large-demand nodes. For these distributions (*Large*, *Identical*, *Quadrant*), LKH3 cannot find feasible solutions for some instances within 10000 trails.

We report the results of AM and GANCO-AM with greedy inferring, 10 trajectories (10t) and 100 trajectories (100t), respectively. As shown in Table 6, the GANCO-AM framework significantly improves the generalization performance over AM on most generalization testing settings. For small size ($n = 20$), GANCO-AM and AM exhibit similar performance on some distributions (*Quadrant* and *SL*), suggesting that AM is relatively robust to these distributions. And the improvement of GANCO-AM on all the generalization testing settings with relatively larger sizes ($n = 50, 100$) is significant.

D AM EXPERIMENTS ON OP

In the Orienteering Problem (OP), the vehicle starts from the depot, visits some of the customers and returns to the depot. The goal is to maximize the total prize collected from the customers with the tour distance shorter than the maximum length. We use the hardest setting reported in Kool et al. (2019), where the prize of node increases with the *distance* to the depot. The base training distribution is the unit uniform distribution for the node coordinate. The maximum tour length is fixed as 2, 3 and 4 for OP with 20, 50 and 100 customers, respectively. The prize ρ_i of node i is determined by $\rho_i = \frac{1}{100} \lfloor 1 + 99 \times \frac{w_{0i}}{max_{j=1}^{n} w_{0j}} \rfloor$, where w_{0i} is the distance between depot and node i. Therefore, the generation model only learns the node coordinates. For the generalization testing distributions, we use the same coordinate distributions for TSP (*Clustered*, *Uniform*, *Diagonal*, *Gaussian* and *TSPLIB-S*) as the ones for the customers. In each generalization distribution, the depot coordinates follow the 3 depot positioning (*Central*, *Eccentric*, *Random*) with equal probabilities.

In Table 7, we report the results of Compass Kobeaga et al. (2018), AM and GANCO-AM on the testing distributions for OP. Different from most other routing problems, the objective value is the

Table 6: Results of AM and GANCO-AM for CVRP on instances with different distributions.

Dist.	Method	n = 20			n = 50			n = 100		
		Obj.	Gap	Time	Obj.	Gap	Time	Obj.	Gap	Time
Base	HGS	6.11	0.00%	1803s	10.34	0.00%	5043s	15.57	0.00%	11686s
	HGS fast	6.12	0.03%	14s	10.35	0.10%	52s	15.69	0.80%	153s
	LKH3	6.12	0.07%	3336s	10.35	0.10%	13223s	15.65	0.54%	24393s
	AM greedy	**6.28**	**2.74%**	0.5s	**10.76**	**4.05%**	1.2s	16.38	5.22%	2.8s
	GANCO-AM greedy	6.29	2.86%	0.5s	10.78	4.22%	1.2s	**16.37**	**5.16%**	2.8s
	AM 10t	**6.23**	**1.87%**	3s	**10.64**	**2.84%**	10s	16.18	3.92%	25s
	GANCO-AM 10t	6.23	1.92%	3s	10.64	2.90%	10s	**16.17**	**3.87%**	25s
	AM 100t	**6.20**	**1.36%**	40s	**10.57**	**2.18%**	107s	16.06	3.14%	265s
	GANCO-AM 109t	6.20	1.41%	40s	10.57	2.18%	109s	**16.05**	**3.11%**	268s
Original	HGS	5.77	0.00%	1775s	9.43	0.00%	4926s	14.03	0.00%	13921s
	HGS fast	5.77	0.05%	14s	9.44	0.11%	51s	14.12	0.65%	155s
	LKH3	5.77	0.07%	3498s	9.44	0.07%	14042s	14.08	0.33%	29169s
	AM greedy	**5.93**	**2.83%**	0.5s	9.90	5.03%	1.2s	15.05	7.25%	2.7s
	GANCO-AM greedy	5.94	3.02%	0.5s	**9.89**	**4.82%**	1.2s	**14.90**	**6.18%**	2.8s
	AM 10t	**5.87**	**1.81%**	3s	9.76	3.53%	10s	14.86	5.89%	26s
	GANCO-AM 10t	5.88	1.91%	3s	**9.74**	**3.30%**	10s	**14.71**	**4.84%**	26s
	AM 100t	**5.84**	**1.25%**	40s	9.68	2.66%	111s	14.72	4.89%	272s
	GANCO-AM 109t	5.85	1.34%	40s	**9.66**	**2.44%**	111s	**14.59**	**3.96%**	268s
Small	HGS	3.55	0.10%	823s	5.11	0.19%	3549s	7.21	0.01%	11073s
	HGS fast	3.55	0.10%	11s	5.12	0.31%	40s	7.25	0.53%	146s
	LKH3	3.55	0.00%	153s	5.10	0.00%	1632s	7.21	0.00%	4366s
	AM greedy	4.08	14.98%	0.5s	5.82	14.08%	1.2s	8.79	21.82%	3.4s
	GANCO-AM greedy	**3.85**	**8.67%**	0.4s	**5.63**	**10.26%**	1.1s	**8.27**	**14.66%**	2.6s
	AM 10t	3.91	10.23%	3s	5.62	10.21%	10s	8.48	17.52%	31s
	GANCO-AM 10t	**3.74**	**5.59%**	3s	**5.46**	**6.94%**	9s	**8.08**	**11.97%**	26s
	AM 100t	3.80	7.18%	38s	5.49	7.51%	114s	8.27	14.59%	312s
	GANCO-AM 109t	**3.69**	**3.96%**	36s	**5.36**	**4.94%**	102s	**7.93**	**9.97%**	261s
Large	HGS	8.84	0.00%	2031s	15.00	0.00%	5416s	21.93	0.00%	13298s
	HGS fast	8.84	0.00%	16s	15.02	0.12%	55s	22.03	0.43%	149s
	LKH3	-	-	-	-	-	-	-	-	-
	AM greedy	9.11	2.99%	0.5s	15.95	6.34%	1.3s	23.47	7.02%	3.0s
	GANCO-AM greedy	**9.04**	**2.17%**	0.5s	**15.89**	**5.95%**	1.2s	**23.29**	**6.20%**	3.0s
	AM 10t	8.98	1.56%	4s	15.74	4.97%	11s	23.23	5.91%	28s
	GANCO-AM 10t	**8.95**	**1.20%**	4s	**15.68**	**4.56%**	11s	**23.02**	**4.93%**	28s
	AM 100t	8.92	0.82%	44s	15.58	3.86%	119s	23.03	4.97%	284s
	GANCO-AM 109t	**8.91**	**0.71%**	43s	**15.52**	**3.49%**	120s	**22.81**	**4.01%**	281s
Identical	HGS	5.93	0.00%	1495s	9.74	0.00%	4341s	14.46	0.00%	10521s
	HGS fast	5.93	0.01%	13s	9.74	0.04%	43s	14.49	0.25%	136s
	LKH3	-	-	-	-	-	-	-	-	-
	AM greedy	6.19	4.47%	0.5s	10.25	5.31%	1.1s	15.75	8.93%	3.4s
	GANCO-AM greedy	**6.12**	**3.34%**	0.5s	**10.20**	**4.75%**	1.1s	**15.47**	**7.03%**	3.0s
	AM 10t	6.10	2.91%	4s	10.14	4.15%	11s	15.55	7.59%	30s
	GANCO-AM 10t	**6.06**	**2.29%**	4s	**10.09**	**3.60%**	11s	**15.32**	**5.98%**	29s
	AM 100t	6.05	2.10%	43s	10.06	3.36%	120s	15.41	6.63%	301s
	GANCO-AM 109t	**6.03**	**1.74%**	42s	**10.01**	**2.86%**	119s	**15.20**	**5.18%**	284s
Quadrant	HGS	5.83	0.00%	1708s	9.56	0.00%	5049s	14.05	0.00%	12235s
	HGS fast	5.83	0.04%	14s	9.57	0.10%	50s	14.12	0.48%	152s
	LKH3	-	-	-	-	-	-	-	-	-
	AM greedy	6.05	3.72%	0.5s	10.24	7.11%	1.1s	15.37	9.40%	3.0s
	GANCO-AM greedy	**6.04**	**3.59%**	0.5s	**10.18**	**6.52%**	1.2s	**15.14**	**7.76%**	3.0s
	AM 10t	5.97	2.40%	4s	10.08	5.46%	10s	15.13	7.71%	29s
	GANCO-AM 10t	**5.97**	**2.34%**	4s	**10.03**	**4.89%**	11s	**14.93**	**6.25%**	28s
	AM 100t	5.93	1.67%	42s	9.97	4.31%	117s	14.96	6.50%	284s
	GANCO-AM 109t	**5.93**	**1.66%**	42s	**9.92**	**3.79%**	117s	**14.77**	**5.12%**	280s
SL	HGS	4.40	0.05%	1386s	6.69	0.00%	4601s	9.52	0.00%	12151s
	HGS fast	4.40	0.09%	13s	6.69	0.09%	46s	9.56	0.36%	145s
	LKH3	4.40	0.00%	1069s	6.69	0.00%	5630s	9.54	0.18%	12595s
	AM greedy	4.59	4.24%	0.4s	7.17	7.21%	1.1s	10.67	12.06%	3.3s
	GANCO-AM greedy	**4.58**	**4.11%**	0.4s	**7.13**	**6.59%**	1.1s	**10.43**	**9.51%**	2.8s
	AM 10t	4.52	2.69%	3s	7.03	5.19%	10s	10.45	9.73%	28s
	GANCO-AM 10t	**4.52**	**2.68%**	3s	**6.98**	**4.49%**	9s	**10.25**	**7.60%**	26s
	AM 100t	**4.48**	**1.89%**	38s	6.95	3.93%	109s	10.30	8.13%	271s
	GANCO-AM 109t	4.48	1.90%	38s	**6.90**	**3.27%**	107s	**10.12**	**6.30%**	258s

total collected prize which is to be maximized instead of minimized. The results confirm that the GANCO framework significantly improves the performance on all the generalization settings with different testing distributions, graph sizes and numbers of solution trajectories.

Table 7: Results of AM and GANCO-AM for OP on instances with different distributions.

Dist.	Method	$n=20$			$n=50$			$n=100$		
		Obj.	Gap	Time	Obj.	Gap	Time	Obj.	Gap	Time
Base	Compass	5.38	0.00%	49s	16.19	0.00%	167s	33.18	0.00%	454s
	AM greedy	5.27	1.96%	0.3s	**15.82**	**2.27%**	0.8s	**32.40**	**2.34%**	1.7s
	GANCO-AM greedy	**5.28**	**1.89%**	0.3s	15.77	2.57%	0.8s	32.30	2.64%	1.7s
	AM 10t	5.31	1.25%	2s	**15.98**	**1.33%**	6s	**32.74**	**1.32%**	15s
	GANCO-AM 10t	**5.31**	**1.17%**	2s	15.95	1.48%	6s	32.69	1.48%	15s
	AM 100t	5.33	0.81%	27s	**16.06**	**0.81%**	67s	**32.92**	**0.77%**	165s
	GANCO-AM 100t	**5.34**	**0.71%**	27s	16.04	0.91%	67s	32.89	0.86%	166s
Clustered	Compass	6.57	0.00%	75s	23.14	0.00%	786s	51.23	0.00%	2173s
	AM greedy	6.40	2.50%	0.3s	21.48	7.17%	1.0s	44.19	13.74%	2.3s
	GANCO-AM greedy	**6.42**	**2.22%**	0.3s	**21.73**	**6.10%**	0.9s	**46.67**	**8.91%**	2.3s
	AM 10t	6.46	1.62%	3s	21.91	5.33%	8s	45.38	11.43%	21s
	GANCO-AM 10t	**6.47**	**1.40%**	3s	**22.15**	**4.29%**	8s	**47.48**	**7.32%**	22s
	AM 100t	6.49	1.10%	32s	22.18	4.14%	87s	46.16	9.90%	221s
	GANCO-AM 100t	**6.51**	**0.90%**	32s	**22.40**	**3.21%**	88s	**48.08**	**6.16%**	227s
Uniform	Compass	7.31	0.00%	90s	22.46	0.00%	304s	45.97	0.00%	559s
	AM greedy	7.06	3.41%	0.3s	21.40	4.72%	0.9s	41.72	9.26%	2.4s
	GANCO-AM greedy	**7.11**	**2.74%**	0.3s	**21.57**	**3.97%**	1.0s	**43.29**	**5.84%**	2.4s
	AM 10t	7.15	2.20%	3s	21.74	3.22%	8s	42.54	7.46%	23s
	GANCO-AM 10t	**7.19**	**1.66%**	3s	**21.89**	**2.57%**	8s	**43.94**	**4.43%**	23s
	AM 100t	7.20	1.54%	33s	21.95	2.30%	91s	43.07	6.32%	241s
	GANCO-AM 100t	**7.24**	**1.05%**	33s	**22.06**	**1.80%**	91s	**44.37**	**3.48%**	241s
Diagonal	Compass	7.57	0.00%	137s	26.52	0.00%	752s	55.33	0.00%	634s
	AM greedy	7.28	3.84%	0.3s	24.60	7.24%	1.0s	44.61	19.39%	2.5s
	GANCO-AM greedy	**7.36**	**2.75%**	0.3s	**25.26**	**4.78%**	1.0s	**51.37**	**7.17%**	2.4s
	AM 10t	7.37	2.64%	3s	25.15	5.17%	8s	46.35	16.24%	23s
	GANCO-AM 10t	**7.43**	**1.80%**	3s	**25.62**	**3.41%**	8s	**51.95**	**6.12%**	23s
	AM 100t	7.42	1.98%	33s	25.53	3.76%	91s	47.31	14.49%	239s
	GANCO-AM 100t	**7.48**	**1.24%**	33s	**25.87**	**2.47%**	91s	**52.49**	**5.15%**	240s
Gaussian	Compass	6.14	0.00%	64s	19.52	0.00%	346s	40.73	0.00%	927s
	AM greedy	5.99	2.51%	0.3s	18.48	5.35%	1.0s	35.16	13.68%	2.4s
	GANCO-AM greedy	**6.00**	**2.37%**	0.3s	**18.56**	**4.93%**	1.0s	**37.31**	**8.40%**	2.4s
	AM 10t	6.05	1.59%	3s	18.81	3.66%	8s	35.96	11.71%	22s
	GANCO-AM 10t	**6.06**	**1.43%**	3s	**18.88**	**3.31%**	8s	**37.97**	**6.80%**	23s
	AM 100t	6.08	1.09%	32s	19.00	2.69%	90s	36.57	10.22%	230s
	GANCO-AM 100t	**6.09**	**0.93%**	32s	**19.05**	**2.40%**	90s	**38.44**	**5.65%**	238s
TSPLIB-S	Compass	6.14	0.00%	63s	20.47	0.00%	323s	44.98	0.00%	857s
	AM greedy	6.01	2.10%	0.3s	19.37	5.37%	1.0s	39.44	12.32%	2.3s
	GANCO-AM greedy	**6.02**	**1.95%**	0.3s	**19.50**	**4.74%**	0.9s	**41.37**	**8.03%**	2.4s
	AM 10t	6.06	1.38%	3s	19.69	3.79%	8s	40.58	9.80%	23s
	GANCO-AM 10t	**6.07**	**1.22%**	3s	**19.80**	**3.29%**	9s	**42.29**	**5.99%**	23s
	AM 100t	6.09	0.89%	32s	19.88	2.90%	90s	41.24	8.32%	232s
	GANCO-AM 100t	**6.09**	**0.79%**	33s	**19.97**	**2.43%**	92s	**42.79**	**4.87%**	238s

E   AM EXPERIMENTS ON PCTSP

In Prize Collecting TSP (PCTSP), the vehicle starts from the depot, visits some of the customers to collect prize and returns to the depot. With the total collected prize no less than a minimum value, the goal is to minimize the tour distance plus the total penalties of unvisited nodes. In Kool et al. (2019), the base training distribution is that the coordinates of depot and customers follow the unit uniform distribution. The prizes are designed to force the vehicle to visit approximately half of the customer nodes, which follows the uniform distribution $U(0, 4/n)$. And the penalties are designed to balance the importance of minimizing the tour distance and the cost of unvisited nodes, which follows the uniform distribution $U(0, 3K/n)$. Particularly, K is fixed as 2, 3 and 4 for PCTSP with 20, 50 and 100 customers. The prizes and penalties are specifically designed to have meaningful instances. Therefore, for the generalization testing distributions, we keep the node prize and penalty distributions the same as the base training distribution. We only consider the generalization to different node coordinate distributions. The depot coordinates follow one of the three depot positioning (*Central*, *Eccentric*, *Random*) with equal probabilities. The customer coordinates follow the same generalization testing distributions as those for TSP.

In Table 8, we show the results of ILS, a faster version of ILS, AM and GANCO-AM on PCTSP with different instance distributions. A faster version of ILS (ILS fast) uses the number of non-improvement iterations, the maximum iterations and the maximum reboot times as 200, 400 and 201 instead of the default 20000, 40000 and 4001 for the original ILS. The ILS fast is the non-learning baseline algorithm to train the generation model. Similarly, the GANCO framework improves the

Table 8: Results of AM and GANCO-AM for PCTSP on instances with different distributions.

Dist.	Method	$n = 20$			$n = 50$			$n = 100$		
		Obj.	Gap	Time	Obj.	Gap	Time	Obj.	Gap	Time
Base	ILS	3.15	0.00%	862s	4.50	0.00%	6895s	5.98	0.00%	47404s
	ILS fast	3.19	1.10%	78s	4.57	1.56%	119s	6.10	2.12%	358s
	AM greedy	3.15	0.11%	0.3s	4.54	0.94%	0.7s	6.11	2.15%	1.7s
	GANCO-AM greedy	**3.15**	**0.09%**	0.3s	**4.54**	**0.90%**	0.7s	**6.10**	**2.09%**	1.7s
	AM 10t	3.15	-0.19%	3s	4.51	0.36%	7s	6.06	1.33%	16s
	GANCO-AM 10t	**3.14**	**-0.20%**	3s	4.51	0.38%	7s	**6.05**	**1.29%**	16s
	AM 100t	**3.14**	**-0.37%**	32s	**4.50**	**0.08%**	74s	6.03	0.85%	168s
	GANCO-AM 100t	3.14	-0.36%	33s	4.50	0.10%	75s	**6.03**	**0.83%**	174s
Clustered	ILS	2.90	0.00%	1018s	3.72	0.00%	9957s	4.65	0.00%	57305s
	ILS fast	2.93	1.04%	81s	3.79	1.94%	102s	4.77	2.74%	476s
	AM greedy	2.90	0.14%	0.3s	3.79	2.06%	0.9s	5.09	9.53%	2.2s
	GANCO-AM greedy	**2.90**	**0.01%**	0.3s	**3.76**	**1.21%**	0.8s	**4.89**	**5.14%**	2.1s
	AM 10t	2.89	-0.28%	3s	3.75	0.95%	8s	4.99	7.40%	21s
	GANCO-AM 10t	**2.89**	**-0.35%**	3s	**3.73**	**0.37%**	8s	**4.82**	**3.78%**	21s
	AM 100t	2.88	-0.50%	34s	3.73	0.29%	88s	4.92	5.95%	224s
	GANCO-AM 100t	**2.88**	**-0.54%**	34s	**3.71**	**-0.13%**	88s	**4.78**	**2.76%**	218s
Uniform	ILS	2.68	0.00%	1121s	3.63	0.00%	12893s	4.72	0.00%	63008s
	ILS fast	2.71	1.14%	76s	3.69	1.64%	101s	4.83	2.16%	523s
	AM greedy	2.69	0.43%	0.3s	3.75	3.33%	0.9s	5.23	10.70%	2.3s
	GANCO-AM greedy	**2.69**	**0.38%**	0.3s	**3.70**	**1.94%**	0.9s	**4.99**	**5.74%**	2.3s
	AM 10t	2.68	-0.03%	3s	3.70	2.00%	8s	5.13	8.65%	22s
	GANCO-AM 10t	**2.68**	**-0.04%**	3s	**3.67**	**1.13%**	8s	**4.94**	**4.51%**	22s
	AM 100t	2.67	-0.26%	34s	3.68	1.23%	92s	5.06	7.18%	235s
	GANCO-AM 100t	**2.67**	**-0.26%**	34s	**3.65**	**0.64%**	91s	**4.90**	**3.65%**	231s
Diagonal	ILS	2.49	0.00%	1242s	2.95	0.00%	17265s	3.44	0.00%	83044s
	ILS fast	2.52	1.24%	70s	3.01	2.11%	122s	3.51	2.13%	716s
	AM greedy	2.51	0.73%	0.3s	3.23	9.69%	0.9s	4.62	34.47%	2.3s
	GANCO-AM greedy	**2.50**	**0.37%**	0.3s	**3.09**	**4.73%**	0.9s	**3.97**	**15.53%**	2.3s
	AM 10t	2.49	0.04%	3s	3.12	6.06%	8s	4.46	29.68%	23s
	GANCO-AM 10t	**2.48**	**-0.16%**	3s	**3.04**	**3.09%**	8s	**3.89**	**13.32%**	22s
	AM 100t	2.48	-0.28%	35s	3.07	4.10%	92s	4.32	25.68%	234s
	GANCO-AM 100t	**2.48**	**-0.41%**	35s	**3.01**	**2.04%**	91s	**3.82**	**11.29%**	229s
Gaussian	ILS	2.80	0.00%	949s	3.59	0.00%	11168s	4.48	0.00%	36622s
	ILS fast	2.82	0.83%	71s	3.63	1.06%	99s	4.53	1.17%	505s
	AM greedy	2.81	0.31%	0.3s	3.68	2.69%	0.8s	4.94	10.21%	2.2s
	GANCO-AM greedy	**2.81**	**0.31%**	0.3s	**3.66**	**1.97%**	0.8s	**4.74**	**5.76%**	2.1s
	AM 10t	**2.80**	**-0.03%**	3s	3.65	1.60%	8s	4.84	8.06%	22s
	GANCO-AM 10t	2.80	-0.02%	3s	**3.63**	**1.19%**	8s	**4.68**	**4.37%**	21s
	AM 100t	**2.79**	**-0.21%**	34s	3.62	1.00%	88s	4.78	6.66%	223s
	GANCO-AM 100t	2.80	-0.19%	34s	**3.62**	**0.75%**	86s	**4.64**	**3.45%**	215s
TSPLIB-S	ILS	2.98	0.00%	952s	3.93	0.00%	11155s	4.96	0.00%	39783s
	ILS fast	3.01	0.99%	72s	3.99	1.62%	106s	5.07	2.25%	471s
	AM greedy	2.99	0.15%	0.3s	4.00	1.81%	0.9s	5.40	8.83%	2.4s
	GANCO-AM greedy	**2.99**	**0.08%**	0.3s	**3.98**	**1.43%**	0.9s	**5.18**	**4.51%**	2.2s
	AM 10t	2.98	-0.20%	3s	3.97	1.01%	8s	5.31	7.00%	23s
	GANCO-AM 10t	**2.98**	**-0.24%**	3s	**3.96**	**0.75%**	8s	**5.12**	**3.30%**	22s
	AM 100t	2.97	-0.39%	35s	3.95	0.56%	89s	5.24	5.68%	237s
	GANCO-AM 100t	**2.97**	**-0.40%**	35s	**3.94**	**0.37%**	90s	**5.09**	**2.51%**	221s

original AM by large margins on almost all the generalization testing settings. For the only exception (PCTSP20 with *Gaussian*), the performance of AM and GANCO-AM is almost identical. It is worth noting that for small size problem, AM and GANCO-AM can outperform the traditional non-learning methods that are highly optimized for the specific problems.

F AM EXPERIMENTS ON KP

Following Kwon et al. (2020), the item weights and values in KP are sampled from the unit uniform distribution $U(0, 1)$ as the base training distribution. The weight capacity is fixed as 12.5, 25, 25 for the instances with 50, 100, 200 items. Considering the weights and values as the x and y axis coordinates, we could leverage the same generalization testing distributions for TSP. The item weights are rounded to 2 decimal places for the Dynamic Programming (DP) algorithm to attain the optimal solutions.

As shown in Table 9, for the greedy inferring, the GANCO framework effectively improves the performance on all the generalization testing distributions for different problem sizes. With more trajectories inferred, the performance of AM and GANCO-AM become fairly close on some distri-

Table 9: Results of AM and GANCO-AM for KP on instances with different distributions.

| Dist. | Method | $n = 50$ | | | $n = 100$ | | | $n = 200$ | | |
		Obj.	Gap	Time	Obj.	Gap	Time	Obj.	Gap	Time
Base	DP	20.099	0.00%	23s	40.404	0.00%	91s	57.730	0.00%	186s
	AM greedy	**20.081**	**0.092%**	0.7s	**40.383**	**0.052%**	1.7s	**57.699**	**0.053%**	4.1s
	GANCO-AM greedy	20.080	0.096%	0.7s	40.381	0.056%	1.7s	57.697	0.058%	3.9s
	AM 10t	**20.088**	**0.053%**	6s	**40.393**	**0.028%**	16s	**57.714**	**0.028%**	37s
	GANCO-AM 10t	20.088	0.056%	6s	40.392	0.029%	16s	57.712	0.031%	38s
	AM 100t	**20.092**	**0.036%**	67s	40.397	0.018%	169s	**57.721**	**0.015%**	391s
	GANCO-AM 100t	20.091	0.039%	68s	**40.397**	**0.018%**	173s	57.719	0.019%	404s
Clustered	DP	18.915	0.00%	22s	38.084	0.00%	97s	53.754	0.00%	182s
	AM greedy	18.873	0.226%	0.8s	38.018	0.174%	2.1s	53.544	0.390%	6.4s
	GANCO-AM greedy	**18.880**	**0.186%**	0.8s	**38.029**	**0.144%**	2.1s	**53.654**	**0.184%**	6.4s
	AM 10t	18.891	0.127%	8s	38.048	0.094%	21s	53.601	0.283%	63s
	GANCO-AM 10t	**18.895**	**0.110%**	8s	**38.052**	**0.084%**	21s	**53.694**	**0.111%**	64s
	AM 100t	18.900	0.080%	81s	38.062	0.057%	241s	53.637	0.217%	677s
	GANCO-AM 100t	**18.901**	**0.074%**	81s	**38.064**	**0.053%**	239s	**53.716**	**0.071%**	717s
Uniform	DP	18.783	0.00%	22s	37.757	0.00%	95s	50.819	0.00%	200s
	AM greedy	18.741	0.223%	0.7s	37.695	0.163%	1.8s	50.731	0.174%	4.1s
	GANCO-AM greedy	**18.753**	**0.159%**	0.7s	**37.717**	**0.105%**	1.8s	**50.748**	**0.140%**	4.1s
	AM 10t	18.757	0.137%	6s	37.720	0.095%	18s	50.776	0.086%	41s
	GANCO-AM 10t	**18.764**	**0.097%**	6s	**37.732**	**0.065%**	18s	**50.783**	**0.073%**	41s
	AM 100t	18.765	0.094%	71s	37.733	0.061%	182s	50.795	0.048%	443s
	GANCO-AM 100t	**18.769**	**0.071%**	71s	**37.740**	**0.044%**	182s	**50.798**	**0.042%**	443s
Diagonal	DP	18.650	0.00%	25s	37.031	0.00%	90s	49.553	0.00%	194s
	AM greedy	18.586	0.344%	0.7s	36.956	0.202%	1.8s	49.419	0.271%	4.2s
	GANCO-AM greedy	**18.620**	**0.158%**	0.7s	**36.980**	**0.138%**	1.8s	**49.436**	**0.236%**	4.2s
	AM 10t	18.612	0.202%	6s	36.990	0.111%	18s	49.477	0.154%	42s
	GANCO-AM 10t	**18.634**	**0.084%**	6s	**37.002**	**0.078%**	18s	**49.481**	**0.145%**	42s
	AM 100t	18.625	0.135%	71s	37.006	0.068%	182s	**49.508**	**0.091%**	445s
	GANCO-AM 100t	**18.639**	**0.057%**	71s	**37.012**	**0.053%**	182s	49.506	0.096%	444s
Gaussian	DP	16.351	0.00%	22s	32.126	0.00%	97s	37.127	0.00%	193s
	AM greedy	16.319	0.196%	0.8s	32.088	0.120%	1.9s	37.057	0.191%	3.8s
	GANCO-AM greedy	**16.319**	**0.193%**	0.7s	**32.089**	**0.116%**	2.0s	**37.074**	**0.143%**	3.8s
	AM 10t	**16.334**	**0.103%**	7s	**32.108**	**0.057%**	19s	37.096	0.086%	38s
	GANCO-AM 10t	16.333	0.107%	7s	32.107	0.058%	19s	**37.100**	**0.074%**	38s
	AM 100t	**16.341**	**0.060%**	75s	**32.116**	**0.030%**	205s	37.109	0.049%	402s
	GANCO-AM 100t	16.339	0.070%	75s	32.116	0.032%	203s	**37.113**	**0.038%**	403s
TSPLIB-S	DP	18.917	0.00%	22s	37.850	0.00%	91s	51.699	0.00%	189s
	AM greedy	18.887	0.159%	0.8s	37.799	0.134%	2.0s	51.579	0.233%	4.9s
	GANCO-AM greedy	**18.889**	**0.148%**	0.8s	**37.810**	**0.105%**	2.0s	**51.621**	**0.151%**	5.0s
	AM 10t	**18.900**	**0.089%**	7s	37.821	0.075%	19s	51.626	0.142%	49s
	GANCO-AM 10t	18.899	0.092%	7s	**37.827**	**0.059%**	19s	**51.658**	**0.080%**	49s
	AM 100t	**18.906**	**0.058%**	75s	37.831	0.048%	203s	51.647	0.102%	493s
	GANCO-AM 100t	18.904	0.066%	75s	**37.834**	**0.040%**	211s	**51.674**	**0.049%**	498s

butions (such as *Gaussian* and *TSPLIB-S*) because KP is a relatively simple problem and the order of node (item) sequences will not affect the solution. Therefore, multiple trajectories by sampling introduce more randomness to the solution quality and the performance slightly fluctuates.

G POMO EXPERIMENTS

We leverage AM as the base model for most experiments given that it has been used in many other recent works including POMO, and exhibits good performance on a series of COPs. Here, we only consider TSP100 and CVRP100 since the results of the improved AM in our experiments are superior or close to those of POMO on the other sizes. Specifically, regarding TSP20 and TSP50, the gaps of AM are 0.14% and 0.73% compared to 0.12% and 0.64% for POMO. Regarding CVRP20 and CVRP50, the gaps of AM are 2.74% and 4.05% compared to 3.72% and 3.52% for POMO. Regarding KP50, KP100 and KP200, the gaps of AM are 0.092%, 0.052% and 0.053% compared to 0.130%, 0.125% and 0.260% for POMO. However, POMO significantly outperforms AM on TSP100 and CVRP100 (2.16% and 5.22% of AM for TSP100 and CVRP100 compared to 1.07% and 3.32%). Therefore, to further show that the proposed GANCO framework is model agnostic and general enough to other models, we conduct experiments on POMO to solve TSP100 and CVRP100.

The results of POMO and GANCO-POMO are shown in Table 10 and Table 3 for TSP100 and CVRP100, respectively. Both the results of single trajectory and 100 trajectories (the-multi-starting-node strategy) are presented. Clearly, the improvement of GANCO-POMO over POMO is salient for both decoding methods.

Table 10: Results of POMO and GANCO-POMO for TSP100.

Dist.	Concorde Obj.	Concorde Time	Method	single trajectory Obj.	single trajectory Gap	single trajectory Time	100 trajectories Obj.	100 trajectories Gap	100 trajectories Time
Base	7.76	142s	POMO	**7.84**	**1.07%**	2.2s	**7.79**	**0.45%**	34s
			GANCO-POMO	7.85	1.20%		7.80	0.54%	
Clustered	5.15	210s	POMO	5.42	5.26%	2.2s	5.26	2.29%	34s
			GANCO-POMO	**5.28**	**2.61%**		**5.21**	**1.15%**	
Uniform	5.30	183s	POMO	5.56	4.97%	2.2s	5.41	2.21%	34s
			GANCO-POMO	**5.39**	**1.82%**		**5.34**	**0.75%**	
Diagonal	3.24	196s	POMO	3.94	21.78%	2.2s	3.57	10.43%	34s
			GANCO-POMO	**3.30**	**2.12%**		**3.26**	**0.86%**	
Gaussian	5.70	167s	POMO	5.93	3.99%	2.2s	5.80	1.84%	34s
			GANCO-POMO	**5.82**	**2.07%**		**5.75**	**0.97%**	
TSPLIB-S	5.76	155s	POMO	5.93	2.97%	2.2s	5.84	1.42%	34s
			GANCO-POMO	**5.86**	**1.79%**		**5.80**	**0.74%**	

H   MODIFICATIONS TO IMPROVE AM

We modify the base AM to improve its performance in two ways. Firstly, we remove the Batch Normalization layers as we find that they only help the model converge slightly faster at the beginning but harm the generalization performance on other distributions. Secondly, we train the model until full convergence instead of the fixed 100 epochs used in Kool et al. (2019). Therefore, the performance of the base model is much better than the original one (e.g., 0.14%, 0.73%, 2.16% optimality gaps instead of the original 0.34%, 1.76%, 4.53% for TSP with 20, 50, 100 nodes).

In Table 11, we take TSP50 as an example and show the results of AM with and without the BN layers. As the results are reported for 100 epochs in Kool et al. (2019), we start from there and present the results every 300 epochs until convergence. Clearly, after convergence, the performance without BN is better than with on various instance distributions including the training one. And the performance on most generalization distributions gets better with more training epochs. Even though the performance on some distributions could fluctuate or deteriorate, the best results on these distributions among different number of epochs are still far inferior to the ones attained after GANCO training.

Table 11: Results of AM with and without the Batch Normalization (BN) layers trained for different number of epochs on TSP50.

Dist.	Models	100 epochs	400 epochs	700 epochs	1000 epochs	1300 epochs	GANCO-AM (without BN)
Base	AM with BN	5.806	5.753	5.740	5.735	5.731	5.735
	AM without BN	5.825	5.755	5.740	5.733	**5.729**	
Clustered	AM with BN	4.235	4.191	4.171	4.183	4.181	4.096
	AM without BN	4.295	4.153	4.142	4.142	**4.137**	
Uniform	AM with BN	4.214	4.080	4.219	4.159	4.226	3.970
	AM without BN	4.117	4.057	4.044	4.089	**4.045**	
Diagonal	AM with BN	3.292	3.205	3.886	4.288	4.411	2.784
	AM without BN	3.858	3.260	3.427	3.457	**3.351**	
Gaussian	AM with BN	4.671	4.621	4.667	4.685	4.687	4.542
	AM without BN	4.743	4.639	4.659	4.691	**4.671**	
TSPLIB-S	AM with BN	4.656	4.605	4.606	4.606	4.592	4.554
	AM without BN	4.656	4.600	4.582	4.578	**4.577**	