TRANSFER AMONG AGENTS: AN EFFICIENT MULTIAGENT TRANSFER LEARNING FRAMEWORK

ABSTRACT

Transfer Learning has shown great potential to enhance the single-agent Reinforcement Learning (RL) efficiency, by sharing learned policies of previous tasks. Similarly, in multiagent settings, the learning performance can also be promoted if agents can share knowledge between each other. However, it remains an open question of how an agent should learn from other agents' knowledge. In this paper, we propose a novel multiagent option-based policy transfer (MAOPT) framework to improve multiagent learning efficiency. Our framework learns what advice to give to each agent and when to terminate it by modeling multiagent policy transfer as the option learning problem. MAOPT provides different kinds of variants which can be classified into two types in terms of the experience used during training. One type is the MAOPT with the Global Option Advisor which has the access to the global information of the environment. However, in many realistic scenarios, we can only obtain each agent's local information due to the partial observation. The other type contains MAOPT with the Local Option Advisor and MAOPT with the Successor Representation Option (SRO) which are suitable for this setting and collect each agent's local experience for the update. In many cases, each agent's experience is inconsistent with each other which causes the option-value estimation to oscillate and to become inaccurate. SRO is used to handle the experience inconsistency by decoupling the dynamics of the environment from the rewards to learn the option-value function under each agent's preference. MAOPT can be easily combined with existing deep RL approaches. Experimental results show it significantly boosts the performance of existing deep RL methods in both discrete and continuous state spaces.

1 INTRODUCTION

Transfer Learning has shown great potential to accelerate single-agent RL via leveraging prior knowledge from past learned policies of relevant tasks (Yin & Pan, 2017; Yang et al., 2020). Inspired by this, transfer learning in multiagent reinforcement learning (MARL) (Claus & Boutilier, 1998; Hu & Wellman, 1998; Bu et al., 2008; Hernandez-Leal et al., 2019; da Silva & Costa, 2019) is also studied with two major directions: 1) transferring knowledge across different but similar MARL tasks and 2) transferring knowledge among multiple agents in the same MARL task. For the former, several works explicitly compute similarities between states or temporal abstractions (Hu et al., 2015; Boutsioukis et al., 2011; Didi & Nitschke, 2016) to transfer across similar tasks with the same number of agents, or design new network structures to transfer across tasks with different numbers of agents (Agarwal et al., 2019; Wang et al., 2020). In this paper, we focus on the latter direction due to the following intuition: in a multiagent system (MAS), the exploration strategy of each agent is different, so the states each agent encounters (i.e., the exploration spaces) are also different; if we figure out some principled ways to transfer knowledge across different agents, all agents could form a big picture about the MAS even without exploring the whole space of the environment, and this will definitely facilitate more efficient MARL (da Silva et al., 2020).

Transferring knowledge among multiple agents is still investigated at an initial stage, and the assumptions and designs of some recent methods are usually simple. For example, LeCTR (Omidshafiei et al., 2019) and HMAT (Kim et al., 2020) adopted the teacher-student framework to learn to teach by assigning each agent two roles (i.e., the teacher and the student), so the agent could learn when and what to advise other agents or receive advice from other agents. However, both LeCTR

and HMAT only consider two-agent scenarios. Liang & Li (2020) proposed a method under the teacher-student framework where each agent asks for advice from other agents through learning an attentional teacher selector. However, they simply used the difference of two unbounded value functions as the reward signal which may cause instability. DVM (Wadhwania et al., 2019) and LTCR Xue et al. (2020) are two proposed multiagent policy distillation methods to transfer knowledge among more than two agents. However, both methods decompose the solution into several stages in a coarse-grained manner. Moreover, they consider the distillation equally throughout the whole training process, which is counter-intuitive. A good transfer should be adaptive rather than being equally treated, e.g., the transfer should be more frequent at the beginning of the training since agents are less knowledgeable about the environment, while decay as the training process continues because agents are familiar with the environment gradually and should focus more on their own knowledge.

In this paper, we propose a novel MultiAgent Option-based Policy Transfer (MAOPT) framework which models the policy transfer among agents as an option learning problem. In contrast to the previous teacher-student framework and policy distillation framework, MAOPT is adaptive and applicable to scenarios consisting of more than two agents. Specifically, MAOPT adaptively selects a suitable policy for each agent as the advised policy, which is used as a complementary optimization objective of each agent. MAOPT also uses the termination probability as a performance indicator to determine whether the advice should be terminated to avoid negative transfer. Furthermore, to facilitate the scalability and robustness, MAOPT contains two types: one type is MAOPT with the global option advisor (MAOPT-GOA), the other type consists of MAOPT with the local option advisor (MAOPT-LOA) and MAOPT with the successor representation option advisor (MAOPT-SRO). Ideally, we can obtain the global information to estimate the option-value function, where MAOPT-GOA is used to select a joint policy set, in which each policy is advised to each agent. However, in many realistic scenarios, we can only obtain each agents' local experience, where we adopt MAOPT-LOA and MAOPT-SRO. Each agent's experience may be inconsistent due to partial observations, which may cause the inaccuracy in option-value's estimation. MAOPT-SRO is used to overcome the inconsistency in multiple agents' experience by decoupling the dynamics of the environment from the rewards to learn the option-value function under each agent's preference. MAOPT can be easily incorporated into existing DRL approaches and experimental results show that it significantly boosts the performance of existing DRL approaches both in discrete and continuous state spaces.

2 Preliminaries

Stochastic Games (Littman, 1994) are a natural multiagent extension of Markov Decision Processes (MDPs), which model the dynamic interactions among multiple agents. Considering the fact agents may not have access to the complete environmental information, we follow previous work's settings and model the multiagent learning problems as partially observable stochastic games (Hansen et al., 2004). A Partially Observable Stochastic Game (POSG) is defined as a tuple $\langle \mathcal{N}, \mathcal{S}, \mathcal{A}^1, \cdots, \mathcal{A}^n, \mathcal{T}, \mathcal{R}^1, \cdots, \mathcal{R}^n, \mathcal{O}^1, \cdots, \mathcal{O}^n \rangle$, where $\mathcal{N}$ is the set of agents; $\mathcal{S}$ is the set of states; $\mathcal{A}^i$ is the set of actions available to agent i (the joint action space $\mathcal{A} = \mathcal{A}^1 \times \mathcal{A}^2 \times \cdots \times \mathcal{A}^n$); $\mathcal{T}$ is the transition function that defines transition probabilities between global states: $\mathcal{S} \times \mathcal{A} \times \mathcal{S} \rightarrow [0, 1]$; $\mathcal{R}^i$ is the reward function for agent i: $\mathcal{S} \times \mathcal{A} \rightarrow \mathbb{R}$ and $\mathcal{O}^i$ is the set of observations for agent i. A policy π^i: $\mathcal{O}^i \times \mathcal{A}^i \rightarrow [0, 1]$ specifies the probability distribution over the action space of agent i. The goal of agent i is to learn a policy π^i that maximizes the expected return with a discount factor γ: $J = \mathbb{E}_{\pi^i} \left[\sum_{t=0}^{\infty} \gamma^t r_t^i \right]$.

The Options Framework. Sutton et al. (1999) firstly formalized the idea of temporally extended action as an option. An option $\omega \in \Omega$ is defined as a triple $\{\mathcal{I}_\omega, \pi_\omega, \beta_\omega\}$ in which $\mathcal{I}_\omega \subset \mathcal{S}$ is an initiation state set, π_ω is an intra-option policy and $\beta_\omega : \mathcal{I}_\omega \rightarrow [0, 1]$ is a termination function that specifies the probability an option ω terminates at state $s \in \mathcal{I}_\omega$. An MDP endowed with a set of options becomes a Semi-Markov Decision Process (Semi-MDP), which has a corresponding optimal option-value function over options learned using intra-option learning. The options framework considers the *call-and-return* option execution model, in which an agent picks an option o according to its option-value function $Q_\omega(s, \omega)$, and follows the intra-option policy π_ω until termination, then selects a next option and repeats the procedure.

Deep Successor Representation (DSR). The successor representation (SR) (Dayan, 1993) is a basic scheme that describes the state value function by a prediction about the future occurrence of all

states under a fixed policy. SR decouples the dynamics of the environment from the rewards. Given a transition (s, a, s', r), SR is defined as the expected discounted future state occupancy:

$$M(s, s', a) = \mathbb{E}\left[\sum_{t=0}^{\infty} \gamma^t \mathbb{1}[s_t = s']|s_0 = s, a_0 = a\right],\qquad(1)$$

where $\mathbb{1}[.]$ is an indicator function with value of one when the argument is true and zero otherwise. Given the SR, the Q-value for selecting action a at state s can be formulated as the inner product of the SR and the immediate reward: $Q^\pi(s, a) = \sum_{s' \in \mathcal{S}} M(s, s', a)\mathcal{R}(s')$.

DSR (Kulkarni et al., 2016) extends SR by approximating it using neural networks. Specifically, each state s is represented by a D-dimensional feature vector ϕ_s, which is the output of the network parameterized by θ. Given ϕ_s, SR is represented as $m_{sr}(\phi_s, a|\tau)$ parameterized by τ, a decoder $g_{\bar{\theta}}(\phi_s)$ parameterized by $\bar{\theta}$ outputs the input reconstruction $\hat{s}$, and the immediate reward at state s is approximated as a linear function of ϕ_s: $\mathcal{R}(s) \approx \phi_s \cdot \mathbf{w}$, where $\mathbf{w} \in \mathbb{R}^D$ is the weight vector. In this way, the Q-value function can be approximated by putting these two parts together as: $Q^\pi(s, a) \approx m_{sr}(\phi_s, a|\tau) \cdot \mathbf{w}$. The stochastic gradient descent is used to update parameters $(\theta, \tau, \mathbf{w}, \bar{\theta})$. Specifically, the loss function of τ is:

$$L(\tau, \theta) = \mathbb{E}\left[(\phi_s + \gamma m'_{sr}(\phi_{s'}, a'|\tau') - m_{sr}(\phi_s, a|\tau))^2\right],\qquad(2)$$

where $a' = \arg\max_a m_{sr}(\phi'_s, a) \cdot \mathbf{w}$, and m'_{sr} is the target SR network parameterized by τ' which follows DQN (Mnih et al., 2015) for stable training. The reward weight $\mathbf{w}$ is updated by minimizing the loss function: $L(\mathbf{w}, \theta) = (\mathcal{R}(s) - \phi_s \cdot \mathbf{w})^2$. The parameter $\bar{\theta}$ is updated using an L2 loss: $L(\bar{\theta}, \theta) = (\hat{s} - s)^2$. Thus, the loss function of DSR is the composition of the three loss functions: $L(\theta, \tau, \mathbf{w}, \bar{\theta}) = L(\tau, \theta) + L(\mathbf{w}, \theta) + L(\bar{\theta}, \theta)$.

3 APPROACH

3.1 FRAMEWORK OVERVIEW

In this section, we describe our MAOPT framework in detail. Figure 1 illustrates MAOPT framework which contains n agents interacting with the environment and corresponding option advisors. At each step, each agent i obtains its own observation o^i, selects an action a^i following its policy π^i, and receives its reward r^i. Each option advisor uses samples from all agents to update the option-value function and corresponding termination probabilities. Each agent is advised by an option advisor, and the advice is the intra-option policy of an option ω which is selected from $\{\omega^1, \cdots, \omega^{i-1}, \omega^{i+1}, \cdots, \omega^n\}$, since we do not consider to select the agent i's policy as the advice for itself. Then the agent exploits this advised policy through imitation, which serves as a complementary optimization objective. The exploitation of this advised policy is terminated as the selected option terminates and then another option is selected. In this way, each agent efficiently exploits useful information from

Figure 1: Framework overview.

other agents and as a result, the learning process of the whole system is accelerated and improved.

Our proposed MAOPT can be classified into two types in terms of the experience used during training. One type is MAOPT with the global option advisor (MAOPT-GOA) which has the access to the global information (i.e., $(s, \vec{a}, \mathbf{r}, s')$, where $\mathbf{r} = \sum_{i=1}^n r^i$) of the environment. Thus, MAOPT-GOA selects a joint option as the advice set given the global observation of the environment and then evaluates the performance of the selected joint option. Selecting a joint option means that each advice given to each agent begins and ends simultaneously. However, in many realistic scenarios, we can only obtain each agent's local information due to the partial observation. Therefore, a more flexible way to advise each agent is necessary. The other type contains MAOPT with the local option advisor (MAOPT-LOA), and MAOPT with the successor representation option advisor (MAOPT-SRO) which collect each agent's local experience for the update. In many cases, each agent's experience is inconsistent with each other, e.g., each agent has an individual goal to achieve or has different roles,

and the rewards assigned to each agent are different. If we simply use all experiences for the update, the option-value estimation would oscillate and become inaccurate. MAOPT-SRO is used to handle the experience inconsistency by decoupling the dynamics of the environment from the rewards to learn the option-value function under each agent's preference.

3.2 MAOPT-GOA

In cases where we have access to the global information of the environment, the global option advisor is used to advise each agent. The procedure of MAOPT-GOA is described as follows. First, MAOPT-GOA initializes the joint option set $\Omega^1 \times \Omega^2 \times \cdots \times \Omega^n$ (where $\Omega^i = \{\omega^1, \cdots, \omega^{i-1}, \omega^{i+1}, \cdots, \omega^n\}$). Each option ω^i contains an intra-option policy corresponding to an agent's policy π^i. The joint option-value function is defined as $Q_{\vec{\omega}}(s, \vec{\omega}|\psi)$ parameterized by ψ which evaluates the performance of each joint option $\vec{\omega}$. The termination network parameterized by ϖ outputs the termination probability $\beta(s', \vec{\omega}|\varpi)$ of the joint option $\vec{\omega}$.

The update of the joint option-value network update follows previous work (Sutton et al., 1999; Bacon et al., 2017). We first samples B transitions uniformly from the global replay buffer, for each sample $(s, \vec{a}, \mathbf{r}, s')$, we calculate the joint U function, the joint option-value function upon arrival:

$$U(s', \vec{\omega}|\psi) = (1 - \beta(s', \vec{\omega}|\varpi)) Q_{\vec{\omega}}(s', \vec{\omega}|\psi) + \beta(s', \vec{\omega}|\varpi) \max_{\vec{\omega}' \in \vec{\Omega}} Q_{\vec{\omega}}(s', \vec{\omega}'|\psi). \tag{3}$$

Then, the option-value network minimizes the following loss:

$$L_{\vec{\omega}} = \frac{1}{B} \sum_b \left(\mathbf{r_b} + \gamma U(s_{b+1}, \vec{\omega}|\psi) - Q_{\vec{\omega}}(s_b, \vec{\omega}|\psi) \right)^2. \tag{4}$$

According to the call-and-return option execution model, the termination probability $\beta_{\vec{\omega}}$ controls when to terminate the selected joint option and then to select another joint option accordingly, which is updated w.r.t ϖ as follows (Bacon et al., 2017):

$$\varpi = \varpi - \alpha_{\varpi} \frac{\partial \beta(s', \vec{\omega}|\varpi)}{\partial \varpi} A(s', \vec{\omega}|\psi) + \xi, \tag{5}$$

where, $A(s', \vec{\omega}|\psi)$ is the advantage function which can be approximated as $Q_{\vec{\omega}}(s', \vec{\omega}|\varpi) - \max_{\vec{\omega}' \in \vec{\Omega}} Q_{\vec{\omega}}(s', \vec{\omega}'|\varpi)$, and ξ is a regularization term to ensure explorations (Bacon et al., 2017). Then, given each state s, MAOPT-GOA selects a joint option $\vec{\omega}$ following the ϵ-greedy strategy over the joint option-value function. Then MAOPT-GOA calculates the cross-entropy $H(\pi_{\omega^i}|\pi^i)$ between each intra-option policy π_{ω^i} and each agent's policy π^i, and gives it to each agent respectively, serving as a complementary optimization objective of each agent, which means that apart from maximizing the cumulate reward, the agent also imitates the intra-option policy π_{ω^i} by minimizing the loss function L_{tr}^i. The imitation for the intra-option policy is terminated as the option terminated, and then another option is selected to provide advice for the agent. The formula of the loss function L_{tr}^i is given as follows:

$$L_{tr}^i = f(t) H(\pi_{\omega^i}|\pi^i), \tag{6}$$

where, $f(t) = 0.5 + \tanh(3 - \mu t)/2$ is the weighting factor of $H(\pi_{\omega^i}|\pi^i)$. μ is a hyper-parameter that controls the decrease degree of the weight. This means that at the beginning of learning, each agent exploits knowledge from other agents mostly. As learning continues, knowledge from other agents becomes less useful and each agent focuses more on the current self-learned policy. Note that we cannot calculate the cross-entropy between the discrete action policies directly. To remedy this, we apply the softmax function with some temperature to the discrete action vectors to transform the actions into discrete categorical distributions.

In MAOPT-GOA, each advice given to each agent begins and ends simultaneously. While for each agent, when to terminate the reusing of other agents' knowledge should be decided asynchronously since the degree of familiarity to the environment of each agent is probably not identical. Moreover, in many realistic scenarios, we can only obtain each agent's local information due to the partial observation. Therefore, a more flexible way to advise each agent is necessary. In the following section, we describe the second type of MAOPT in detail.

Figure 2: MAOPT-LOA.   Figure 3: The SRO architecture.

3.3 MAOPT-LOA

MAOPT-LOA equips each agent an option advisor, and each advisor uses local information from all agents for estimation. How MAOPT-LOA is applied in actor-critic methods is illustrated in Figure 2. Firstly, MAOPT-LOA initializes n options $\Omega = \{\omega^1, \omega^2, \cdots, \omega^n\}$. Each option ω^i contains an intra-option policy corresponding to an agent's policy π^i. The input of option network parameterized by ψ and termination network parameterized by ϖ is the local observation o^i of each agent i. The option-value function $Q_\omega(o^i, \omega | \psi)$ and termination probability $\beta(o^i, \omega | \varpi)$ are used to evaluate the performance of each option $\omega^i \in \Omega$.

The update of the option-value function and the termination probability is similar to that in MAOPA-GOA. For the update of each agent i, MAOPT-LOA first selects an option ω^i following ϵ-greedy strategy over the option-value function. Then MAOPT-LOA calculates the cross-entropy $H(\pi_{\omega^i} | \pi^i)$ between each intra-option policy π_{ω^i} and each agent's policy π^i, and gives it to each agent respectively, contributing to a complementary loss function L^i_{tr} for each agent.

Note that the option-value network and termination network collect experience from all agents for the update. What if the experience from one agent is inconsistent with others? In a POSG, each agent can only obtain the local observation and individual reward signal, which may be different for different agents even at the same state. If we use inconsistent experiences to update one shared option-value network and termination network, the estimation of the option-value function would oscillate and become inaccurate. We propose MAOPT-SRO to address this problem. MAOPT-SRO decouples the dynamics of the environment from the rewards to learn the option-value function under each agent's preference. In this way, MAOPT-SRO can address such sample inconsistency and learn the option-value and the corresponding termination probabilities under each agent's preference which is described in the next section.

3.4 MAOPT-SRO

MAOPT-SRO applies a novel option learning algorithm, Successor Representation Option (SRO) learning to learn the option-value function under each agent's preference. The SRO network architecture is shown in Figure 3, with each observation o^i from each agent i as input. o^i is input through two fully-connected layers to generate the state embedding ϕ_{o^i}, which is transmitted to three network sub-modules. The first sub-module contains the state reconstruction model which ensures ϕ_{o^i} well representing o^i, and the weights for the immediate reward approximation at local observation o^i. The immediate reward is approximated as a linear function of ϕ_{o^i}: $\mathcal{R}^i(\phi_{o^i}) \approx \phi_{o^i} \cdot \mathbf{w}$, where $\mathbf{w} \in \mathbb{R}^D$ is the weight vector. The second sub-module is used to approximate SR for options $m_{sr}(\phi_{o^i}, \omega | \tau)$ which describes the expected discounted future state occupancy of executing the option ω. The last sub-module is used to update the termination probability $\beta(\phi_{o^{i\prime}}, \omega | \varpi)$, which is similar to that in MAOPT-LOA described in Section 3.3.

Given $m_{sr}(\phi_{o^i}, \omega | \tau)$, the SRO-value function can be approximated as: $Q_\omega(\phi_{o^i}, \omega) \approx m_{sr}(\phi_{o^i}, \omega | \tau) \cdot \mathbf{w}$. Since options are temporal abstractions (Sutton et al., 1999), SRO also needs to calculate the $\tilde{U}$ function which is served as SR upon arrival, indicating the expected discounted future state occupancy of executing an option ω upon entering a state. Given the transition $(o^i, a^i, r^i, o^{i\prime})$, we firstly introduce the SR upon arrival $\tilde{U}$ as follows:

$$\tilde{U}(\phi_{o^{i\prime}}, \omega | \tau) = (1 - \beta(\phi_{o^{i\prime}}, \omega | \varpi)) m_{sr}(\phi_{o^{i\prime}}, \omega | \tau') + \beta(\phi_{o^{i\prime}}, \omega | \varpi) m_{sr}(\phi_{o^{i\prime}}, \omega' | \tau'), \quad (7)$$

where $\omega' = \arg\max_{\omega \in \Omega} m_{sr}(\phi_{o^{i'}}, \omega | \tau') \cdot \mathbf{w}$.

We consider MAOPT-SRO combing with PPO (Schulman et al., 2017), a popular single-agent policy-based RL (pseudo-code is included in the appendix). The way MAOPT-SRO combines with other policy-based RL algorithms is similar. For each episode, each agent i first obtains its local observation o^i and selects an action a^i following its policy π^i. Then each agent receives the individual reward r^i and new observation $o^{i'}$. The transition is stored to each agent's replay buffer $\mathcal{D}^i$. For each update step, each agent updates its critic network by minimizing the loss L_c^i:

$$L_c^i = -\sum_{t=1}^{T}(\sum_{t'>t} \gamma^{t'-t} r_t^i - V_{v^i}(o_t^i))^2 \tag{8}$$

where T is the length of the trajectory segment. Then each agent updates its actor network by minimizing the summation of the original loss and the transfer loss L_{tr}^i:

$$\bar{L}_a^i = \sum_{t=1}^{T} \frac{\pi^i(a_t^i|o_t^i)}{\pi_{old}^i(a_t^i|o_t^i)} \left(\sum_{t'>t} \gamma^{t'-t} r_t^i - V_{v^i}(o_t^i) \right) - \lambda KL[\pi_{old}^i|\pi^i] + L_{tr} \tag{9}$$

SRO loss is composed of three components which follows previous work (Kulkarni et al., 2016): the state reconstruction loss $L(\bar{\theta}, \theta)$, the loss for reward prediction $L(\mathbf{w}, \theta)$ and SR loss $L(\tau, \theta)$. The state reconstruction network is updated by minimizing two losses $L(\bar{\theta}, \theta)$ and $L(\mathbf{w}, \theta)$ as follows:

$$L(\bar{\theta}, \theta) = \left(g_{\bar{\theta}}(\phi_{o^i}) - o^i \right)^2$$
$$L(\mathbf{w}, \theta) = \left(r^i - \phi_{o^i} \cdot \mathbf{w} \right)^2 \tag{10}$$

At each step, SRO first samples a batch of B/N transitions from each agent's buffer $\mathcal{D}^i$, which means there are B transitions in total for the update. The SR network approximates SR for options and is updated by minimizing the standard L2 loss $L(\tau, \theta)$ as follows:

$$L(\tau, \theta) = \frac{1}{B} \sum_b \left(y_b - m_{sr}(\phi_{o^i}, \omega | \tau) \right)^2 \tag{11}$$

where $y = \phi_{o^i} + \gamma \tilde{U}(\phi_{o^{i'}}, \omega | \tau)$. At last, the termination probability of the selection option is updated as described in Section 3.3.

4 EXPERIMENTAL RESULTS

In this section, we evaluate the performance of MAOPT combined with the common single-agent RL algorithm (PPO (Schulman et al., 2017)) and MARL algorithm (MADDPG (Lowe et al., 2017)). The test domains include two representative multiagent games, Pac-Man and multiagent particle environment (MPE) (illustrated in the appendix). Specifically, we first combine MAOPT-LOA and MAOPT-SRO with PPO on Pac-Man to validate whether MAOPT-SRO successfully solves the sample inconsistency due to the partial observation. Then, we combine MAOPT-GOA, MAOPT-LOA, and MAOPT-SRO with two baselines (MADDPG and PPO) on MPE to further validate whether MAOPT-SRO is a more flexible way for knowledge transfer among agents and enhances the advantage of our framework. We also compare with DVM (Wadhwania et al., 2019), which is the most recent multiagent transfer method[*].

4.1 PAC-MAN

Pac-Man (van der Ouderaa, 2016) is a mixed cooperative-competitive maze game with one pac-man player and two ghost players. The goal of the pac-man player is to eat as many pills as possible and avoid the pursuit of ghost players. For ghost players, they aim to capture the pac-man player as soon as possible. In our settings, we aim to control the two ghost players and the pac-man player as the opponent is controlled by well pre-trained PPO policy. The game ends when one ghost catches the pac-man player or the episode exceeds 100 steps. Each player receives -0.01 penalty each step and $+5$ reward for catching the pac-man player.

---

[*]The details of neural network structures and parameter settings are in the appendix, and we share network parameters among all homogeneous agents (Gupta et al., 2017; Rashid et al., 2018).

We consider two Pac-Man scenarios (OpenClassic and Medium-Classic) with the game difficulties increasing. Figure 4 (a) presents the average rewards on the OpenClassic scenario. We can see that both MAOPT-LOA and MAOPT-SRO perform better than other methods and achieve the average discount rewards of $+3$ approximately with smaller variance. In contrast, PPO and DVM only achieve the average discount rewards of $+2.5$ approximately with larger variance. This phenomenon indicates that both MAOPT-LOA and MAOPT-SRO enable efficient knowledge transfer between two ghosts, thus facilitating better performance.

(a) OpenClassic

Next, we consider a more complex Pac-Man game scenario, where the layout size is larger than the former and it contains obstacles (walls). From Figure 4 (b) we can observe that the advantage of MAOPT-LOA and MAOPT-SRO is much more obvious compared with PPO and DVM. Furthermore, MAOPT-SRO performs best among all methods, which means that MAOPT-SRO effectively selects more suitable advice for each agent. The reason that MAOPT performs better than DVM is that MAOPT enables each agent to effectively exploit useful information from other agents through the option-based call-and-return mechanism, which successfully avoids negative transfer when other agents' policies are only partially useful. However, DVM just transfers all information from other agents through policy distillation. By comparing the results of the two s-

(b) MediumClassic

Figure 4: The performance on Pac-Man.

cenarios, we see that the superior advantage of MAOPT-SRO increases when faced with more challenging scenarios. Intuitively, as the environmental difficulties increase, agents are harder to explore the environment and to learn the optimal policy. In such a case, agents need to exploit knowledge of other agents more efficiently, which would greatly accelerate the learning process as demonstrated by MAOPT-LOA and MAOPT-SRO.

4.2 MPE

MPE (Lowe et al., 2017) is a simple multiagent particle world with continuous observation and discrete action space. We evaluate the performance of MAOPT on two scenarios: predator and prey, and cooperative navigation. The predator and prey contains three agents which are slower and want to catch one adversary (rewarded $+10$ by each hit). The adversary is faster and wants to avoid being hit by the other three agents. Obstacles block the way. The cooperative navigation contains four agents, and four corresponding landmarks. Agents are penalized with a reward of -1 if they collide with other agents. Thus, agents have to learn to cover all the landmarks while avoiding collisions. Both games end when exceeding 100 steps.

(a) PPO

Both domains contain the sample inconsistency problem since each agent's local observation contains the relative distance between other agents, obstacles, and landmarks. Moreover, in cooperative navigation, each agent is assigned a different task, i.e., approaching a different landmark from others, which means each agent may receive different rewards under the same observation. Therefore, we cannot directly use all experience to update one shared option-value network. In such a case, we design an individual option learning module for each agent in MAOPT-LOA, which only collects one agent's experience to update the option-value function.

(b) MADDPG

Figure 5: The performance on predator and prey.

Figure 5 (a) shows the average rewards on predator and prey. We can see that all our proposed MAOPT-GOA, MAOPT-LOA, and MAOPT-SRO (combined with PPO) achieve higher average rewards than PPO and DVM. Figure 5 (b) demonstrates a similar phenomenon that both MAOPT-GOA and MAOPT-SRO (combined with MADDPG) perform bet-

Table 1: Average of collisions and average distance from a landmark in cooperative navigation.

	PPO	DVM	MADDPG	MAOPT-GOA	MAOPT-LOA	MAOPT-SRO
Avg. dist.	1.802	1.685	1.767	1.446	1.476	**1.366**
Collisions	0.163	0.144	0.209	0.153	0.124	**0.122**

ter than vanilla MADDPG, and MAOPT-SRO performs best among all methods. This is because MAOPT-SRO uses all agents' experience for the update and efficiently distinguishes which part of the information is useful and provides positive advice for each agent. Furthermore, it uses the individual termination probability to determine when to terminate each agent's advice, which is a more flexible manner, thus facilitating more efficient and effective knowledge transfer among agents.

Table 1 shows the average collisions of agents and the average distance between each agent and its nearest landmark in cooperative navigation. We can see that MAOPT-GOA, MAOPT-LOA, and MAOPT-SRO achieve the less collisions and the shorter average distance from landmarks than other methods. Furthermore, MAOPT-SRO performs best among all methods. The superior advantage of MAOPT is due to the effectiveness in identifying the useful information from other agents' policies. Therefore, each agent exploits useful knowledge of other agents and as a result, thus leading to the least collisions and the minimum distance from landmarks.

Finally, we provide an ablation study to investigate whether MAOPT-SRO selects a suitable policy for each agent, thus efficiently enabling agents to exploit useful information from others. Figure 6 presents the action movement in the environment caused by an agent's policy and the policy of MAOPT-SRO at the same training period ($t_1 = 6 \times 10^5$ steps, $t_2 = 2 \times 10^6$ steps). We can see that at both periods, actions selected by the intra-option policy of MAOPT-SRO are more accurate than those selected from the agent's own policy, namely, more prone to pursue the adversary (blue). This indicates that the advised policy selected by MAOPT-SRO performs better than the agent itself, which means MAOPT-SRO successfully distinguishes useful knowledge from other agents. Therefore, the agent can learn faster and better after exploiting knowledge from this advised policy.

(a) PPO_{t_1} (b) MAOPT-SRO_{t_1}

(c) PPO_{t_2} (d) MAOPT-SRO_{t_2}

Figure 6: Analysis of agent 1's policy and MAOPT-SRO's policy.

5 CONCLUSION AND FUTURE WORK

In this paper, we propose a novel MultiAgent Option-based Policy Transfer (MAOPT) framework for efficient multiagent learning by taking advantage of option-based policy transfer. Our framework learns what advice to give to each agent and when to terminate it by modeling multiagent transfer as the option learning problem. Furthermore, to facilitate the robustness of our framework, we provide two types: one type is MAOPT-GOA, which is adopted in fully cooperative settings (with access to global state and reward). The other type contains MAOPT-LOA and MAOPT-SRO, which are proposed for mixed settings (only access to local state with inconsistency and also individual rewards). MAOPT-SRO is proposed to solve the sample inconsistency due to the partial observation, by decoupling the dynamics of the environment from the rewards to learn the option-value function under each agent's preference. MAOPT can be easily combined with existing DRL approaches. Experimental results show it significantly boosts the performance of existing DRL methods. As for future work, it is worth investigating how to achieve coordination among agents by designing MAOPT-GOA in a centralized training, decentralized execution manner. For example, it is worth investigating how to decompose the joint option-value function into individual option-value functions and update each termination probability separately.

REFERENCES

Akshat Agarwal, Sumit Kumar, and Katia P. Sycara. Learning transferable cooperative behavior in multi-agent teams. *CoRR*, abs/1906.01202, 2019.

Pierre-Luc Bacon, Jean Harb, and Doina Precup. The option-critic architecture. In *Proceedings of AAAI*, pp. 1726–1734, 2017.

Georgios Boutsioukis, Ioannis Partalas, and Ioannis P. Vlahavas. Transfer learning in multi-agent reinforcement learning domains. In *Recent Advances in Reinforcement Learning - 9th European Workshop*, pp. 249–260, 2011.

Lucian Bu, Robert Babu, Bart De Schutter, et al. A comprehensive survey of multiagent reinforcement learning. *IEEE Transactions on Systems, Man, and Cybernetics*, 38(2):156–172, 2008.

Caroline Claus and Craig Boutilier. The dynamics of reinforcement learning in cooperative multiagent systems. In *Proceedings of AAAI/IAAI*, pp. 746–752, 1998.

Felipe Leno da Silva and Anna Helena Reali Costa. A survey on transfer learning for multiagent reinforcement learning systems. *Journal of Artificial Intelligence Research*, 64:645–703, 2019.

Felipe Leno da Silva, Garrett Warnell, Anna Helena Reali Costa, and Peter Stone. Agents teaching agents: a survey on inter-agent transfer learning. *Auton. Agents Multi Agent Syst.*, 34(1):9, 2020.

Peter Dayan. Improving generalization for temporal difference learning: The successor representation. *Neural Computation*, 5(4):613–624, 1993.

Sabre Didi and Geoff Nitschke. Multi-agent behavior-based policy transfer. In *Proceedings of European Conference on the Applications of Evolutionary Computation*, pp. 181–197, 2016.

Jayesh K. Gupta, Maxim Egorov, and Mykel J. Kochenderfer. Cooperative multi-agent control using deep reinforcement learning. In *Autonomous Agents and Multiagent Systems - AAMAS 2017 Workshops*, pp. 66–83, 2017.

Eric A Hansen, Daniel S Bernstein, and Shlomo Zilberstein. Dynamic programming for partially observable stochastic games. In *Proceedings of AAAI*, volume 4, pp. 709–715, 2004.

Pablo Hernandez-Leal, Bilal Kartal, and Matthew E. Taylor. A survey and critique of multiagent deep reinforcement learning. *Autonomous Agents and Multi-Agent Systems*, 33(6):750–797, 2019.

Junling Hu and Michael P. Wellman. Multiagent reinforcement learning: Theoretical framework and an algorithm. In *Proceedings of ICML*, pp. 242–250, 1998.

Yujing Hu, Yang Gao, and Bo An. Accelerating multiagent reinforcement learning by equilibrium transfer. *IEEE Trans. Cybernetics*, 45(7):1289–1302, 2015.

Dong-Ki Kim, Miao Liu, Shayegan Omidshafiei, Sebastian Lopez-Cot, Matthew Riemer, Golnaz Habibi, Gerald Tesauro, Sami Mourad, Murray Campbell, and Jonathan P. How. Learning hierarchical teaching policies for cooperative agents. In *Proceedings of the 19th International Conference on Autonomous Agents and Multiagent Systems*, pp. 620–628, 2020.

Tejas D Kulkarni, Ardavan Saeedi, Simanta Gautam, and Samuel J Gershman. Deep successor reinforcement learning. *arXiv preprint arXiv:1606.02396*, 2016.

Yongyuan Liang and Bangwei Li. Parallel knowledge transfer in multi-agent reinforcement learning. *CoRR*, abs/2003.13085, 2020.

Michael L. Littman. Markov games as a framework for multi-agent reinforcement learning. In *Proceedings of ICML*, pp. 157–163, 1994.

Ryan Lowe, Yi Wu, Aviv Tamar, Jean Harb, Pieter Abbeel, and Igor Mordatch. Multi-agent actor-critic for mixed cooperative-competitive environments. In *Proceedings of NeurIPS*, pp. 6379–6390, 2017.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A. Rusu, Joel Veness, Marc G. Belle-mare, Alex Graves, Martin A. Riedmiller, Andreas Fidjeland, Georg Ostrovski, Stig Petersen, Charles Beattie, Amir Sadik, Ioannis Antonoglou, Helen King, Dharshan Kumaran, Daan Wierstra, Shane Legg, and Demis Hassabis. Human-level control through deep reinforcement learning. *Nature*, 518(7540):529, 2015.

Shayegan Omidshafiei, Dong-Ki Kim, Miao Liu, Gerald Tesauro, Matthew Riemer, Christopher Amato, Murray Campbell, and Jonathan P. How. Learning to teach in cooperative multiagent reinforcement learning. In *Proceedings of AAAI*, pp. 6128–6136, 2019.

Tabish Rashid, Mikayel Samvelyan, Christian Schröder de Witt, Gregory Farquhar, Jakob N. Foerster, and Shimon Whiteson. QMIX: monotonic value function factorisation for deep multi-agent reinforcement learning. In *Proceedings of the 35th International Conference on Machine Learning*, pp. 4292–4301, 2018.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Richard S. Sutton, Doina Precup, and Satinder Singh. Between MDPs and semi-MDPs: A framework for temporal abstraction in reinforcement learning. *Artificial Intelligence*, 112(1):181 – 211, 1999. ISSN 0004-3702.

Tycho van der Ouderaa. Deep reinforcement learning in pac-man. 2016.

Samir Wadhwania, Dong-Ki Kim, Shayegan Omidshafiei, and Jonathan P. How. Policy distillation and value matching in multiagent reinforcement learning. In *2019 IEEE/RSJ International Conference on Intelligent Robots and Systems, IROS 2019, Macau, SAR, China, November 3-8, 2019*, pp. 8193–8200, 2019.

Weixun Wang, Tianpei Yang, Yong Liu, Jianye Hao, Xiaotian Hao, Yujing Hu, Yingfeng Chen, Changjie Fan, and Yang Gao. From few to more: large-scale dynamic multiagent curriculum learning. In *Proceedings of AAAI*, 2020.

Zeyue Xue, Shuang Luo, Chao Wu, Pan Zhou, Kaigui Bian, and Wei Du. Transfer heterogeneous knowledge among peer-to-peer teammates: A model distillation approach. *CoRR*, abs/2002.02202, 2020.

Tianpei Yang, Jianye Hao, Zhaopeng Meng, Zongzhang Zhang, Yujing Hu, Yingfeng Chen, Changjie Fan, Weixun Wang, Wulong Liu, Zhaodong Wang, and Jiajie Peng. Efficient deep reinforcement learning via adaptive policy transfer. In *Proceedings of the Twenty-Ninth International Joint Conference on Artificial Intelligence, IJCAI 2020*, pp. 3094–3100, 2020.

Haiyan Yin and Sinno Jialin Pan. Knowledge transfer for deep reinforcement learning with hierarchical experience replay. In *Proceedings of AAAI*, pp. 1640–1646, 2017.

A   APPENDIX

I. Pseudo-code for MAOPT-SRO

Algorithm 1 MAOPT-SRO.

1: Initialize: state feature parameters θ, reward weights $\mathbf{w}$, state reconstruction network parameters $\bar{\theta}$, termination network parameters ϖ, SR network parameters τ, SR target network parameters τ', replay buffer $\mathcal{D}^i$ for each agent i, actor network parameters ρ^i for each agent i, critic network parameters υ^i for each agent i, batch size T for PPO
2: **for** each episode **do**
3:     Start from state s, $t = 0$
4:     Select an option ω^i for each agent i
5:     **repeat**
6:         Select an action $a^i \sim \pi^i(o^i)$ for each agent i
7:         Perform the joint action $\vec{a} = \{a^1, \cdots, a^n\}$
8:         Observe reward $\mathbf{r} = \{r^1, \cdots, r^n\}$ and new state s'
9:         $t = t + 1$
10:         Store transition $(o^i, a^i, r^i, o^{i'}, i)$ replay buffer $\mathcal{D}$
11:         Select another option if ω^i terminates for each agent i
12:         **if** t % T **then**
13:             Set $\pi^i_{old} = \pi^i$ for each agent i
14:             Calculate the advantage $A^i = \sum_{t'>t} \gamma^{t'-t} r^i_t - V_{\upsilon^i}(o^i_t)$ for each agent i
15:             Optimize the critic loss $L^i_c = -\sum_{t=1}^{T} (\sum_{t'>t} \gamma^{t'-t} r^i_t - V_{\upsilon^i}(o^i_t))^2$ for each agent i
16:             Optimize the actor loss $\bar{L}^i_a = \sum_{t=1}^{T} \frac{\pi^i(a^i_t|o^i_t)}{\pi^i_{old}(a^i_t|o^i_t)} A^i_t - \lambda KL[\pi^i_{old}|\pi^i] + L^i_{tr}$ w.r.t ρ^i for each agent i
17:         **end if**
18:         Sample a batch of B/N transitions from each D^i
19:         **for** each sample $(o^i, a^i, r^i, o^{i'}, i)$ **do**
20:             Optimize $L(\bar{\theta}, \theta) = (g_{\bar{\theta}}(\phi_{o^i}) - o^i)^2$ w.r.t $\bar{\theta}, \theta$
21:             Optimize $L(\mathbf{w}, \theta) = (r^i - \phi_{o^i} \cdot \mathbf{w})^2$ w.r.t $\mathbf{w}, \theta$
22:             **for** $\omega \in \Omega$ **do**
23:                 **if** π_ω selects action a^i at observation o^i **then**
24:                     Calculate $\tilde{U}(\phi_{o^i}, \omega|\tau)$
25:                     Set $y \leftarrow \phi_{o^i} + \gamma\tilde{U}(\phi_{o^i}, \omega|\tau)$
26:                     Optimize the following loss w.r.t τ:
                     $L(\tau, \theta) = \frac{1}{B} \sum_b (y_b - m_{sr}(\phi_{o^i}, \omega|\tau))^2$
27:                     Optimize the termination loss w.r.t ϖ
28:                 **end if**
29:             **end for**
30:             Copy τ to SR target network every k steps
31:         **end for**
32:     **until** s is terminal
33: **end for**

Algorithm 1 illustrates the whole procedure of MAOPT-SRO. First, we initialize the network parameters for the state embedding network, reward prediction network, state reconstruction network, termination network, SR network, SR target network, and the actor and critic networks of each agent. For each episode, each agent i first obtains its local observation o^i which corresponds to the current state s (Line 3). Then, MAOPT-SRO selects an option ω^i for each agent i (Line 4), which selects an action a^i following its policy π^i (Line 6). The joint action $\vec{a}$ is performed, then the reward $\mathbf{r}$ and new state s' is returned from the environment (Lines 7-9). The transition is stored in the replay buffer $\mathcal{D}$ (Line 10). For each update step, each agent updates its critic network by minimizing the loss L^i_c (Line 15), and updates its actor network by minimizing the summation of the original loss L^i_a and the transfer loss L^i_{tr} (Line 16).

For the update of SRO, it first samples a batch of B/N transitions from each agent's buffer $\mathcal{D}^i$ (Line 18). SRO loss is composed of three components: the state reconstruction loss $L(\bar{\theta}, \theta)$, the loss for reward weights $L(\mathbf{w}, \theta)$ and SR loss $L(\tau, \theta)$. The state reconstruction network is updated by minimizing two losses $L(\bar{\theta}, \theta)$ (Line 20) and $L(\mathbf{w}, \theta)$ (Line 21). The second sub-module which approximates SR for options is updated by minimizing the standard L2 loss $L(\tau, \theta)$ (Lines 22-26). At last, the termination probability of the selection option is updated (Line 27).

II. Environment illustrations and descriptions

Pac-Man (van der Ouderaa, 2016) is a mixed cooperative-competitive maze game with one pac-man player and two ghost players (Figure 7). The goal of the pac-man player is to eat as many pills (denoted as white circles in the grids) as possible and avoid the pursuit of ghost players. For ghost players, they aim to capture the pac-man player as soon as possible. In our settings, we aim to control the two ghost players and the pac-man player as the opponent is controlled by well pre-trained PPO policy. The game ends when one ghost catches the pac-man player or the episode exceeds 100 steps. Each player receives -0.01 penalty each step and $+5$ reward for catching the pac-man player.

MPE (Lowe et al., 2017) is a simple multiagent particle world with continuous observation and discrete action space. We evaluate the performance of MAOPT on two scenarios: predator and prey (Figure 8), and cooperative navigation (Figure 9). The predator and prey contains three agents (green) which are slower and want to catch one adversary (blue)(rewarded $+10$ by each hit). The adversary is faster and wants to avoid being hit by the other three agents. Obstacles (grey) block the way. The cooperative navigation contains four agents (green), and four corresponding landmarks (cross). Agents are penalized with a reward of -1 if they collide with other agents. Thus, agents have to learn to cover all the landmarks while avoiding collisions. At each step, each agent receives a reward of the negative value of the distance between the nearest landmark and itself. Both games end when exceeding 100 steps.

(a) Open Classic

(b) Medium Classic

Figure 7: Pac-Man.   Figure 8: Predator and prey.   Figure 9: Cooperative navigation.

III. Network structure and parameter settings

State Description

Pac-Man The layout size of two scenarios are 25×9 (OpenClassic) and 20×11 (MediumClassic) respectively. The observation of each ghost player contains its position, the position of its teammate, walls, pills, and the pac-man, which is encoded as a one-hot vector. The input of the network is a 68-dimension in OpenClassic, 62-dimension in MediumClassic.

MPE The observation of each agent contains its velocity, position, and the relative distance between landmarks, blocks, and other agents, which is composed of 18-dimension in predator and prey, 24-dimension in cooperative navigation as the network input.

Network Structure Here we provide the network structure for PPO and MAOPT-SRO shown in Figure 10 (a) and (b) respectively.

Parameter Settings

Here we provide the hyperparameters for MAOPT, DVM as well as two baselines, PPO and MAD-DPG shown in Table 2 and 3 respectively.

(a) PPO

(b) SRO

Figure 10: Network structures.

Table 2: Hyperparameters for all methods based on PPO.

Hyperparameter	Value
Learning rate	$3e-4$
Length of trajectory segment T	32
Gradient norm clip λ	0.2
Optimizer	Adam
Batch size B of the option advisor	32
Replay memory size	$1e5$
Learning rate	$1e-5$
Action-selector ϵ-start	ϵ-greedy 1.0
ϵ-finish	0.05
ϵ anneal time	$5e4$ step
target-update-interval	1000
distillation-interval for DVM	$2e5$ step
distillation-iteration for DVM	2048 step

Table 3: Hyperparameters for all methods based on MADDPG.

Hyperparameter	Value
Learning rate	$1e-2$
Batch size	1024
Optimizer	Adam
Batch size B of the option advisor	32
Replay memory size	$1e5$
Learning rate	$1e-5$
Action-selector ϵ-start	ϵ-greedy 1.0
ϵ-finish	0.05
ϵ anneal time	$5e4$ step
target-update-interval	1000