Fully-Asynchronous Decentralized SGD with Quantized and Local Updates

Abstract

Decentralized optimization is emerging as a viable alternative for scalable distributed machine learning, but also introduces new challenges in terms of synchronization costs. To this end, several communication-reduction techniques, such as non-blocking communication, quantization, and local steps, have been explored in the decentralized setting. Due to the complexity of analyzing optimization in such a relaxed setting, this line of work often assumes *global* communication rounds, which require additional synchronization. In this paper, we consider decentralized optimization in the simpler, but harder to analyze, *asynchronous gossip* model, in which communication occurs in discrete, randomly chosen pairings among nodes. Perhaps surprisingly, we show that a variant of SGD called *SwarmSGD* still converges in this setting, even if *non-blocking communication*, *quantization*, and *local steps* are all applied *in conjunction*, and even if the node data distributions and underlying graph topology are both *heterogenous*. Our analysis is based on a new connection with multi-dimensional load-balancing processes. We implement this algorithm and deploy it in a super-computing environment, showing that it can outperform previous decentralized methods in terms of end-to-end training time, and that it can even rival carefully-tuned large-batch SGD for certain tasks.

1 Introduction

Decentralized optimization has recently emerged as a promising approach for scaling the distributed training of machine learning models, in particular via stochastic gradient descent (SGD) [Lian et al., 2017, Tang et al., 2018, Koloskova et al., 2019a]. Its key advantage is that it removes the need for a central coordinator node in distributed training, and therefore it can allow for extremely high scaling.

The general decentralized optimization setting is the following: we are given n nodes, each with a subset of data from some distribution, which can communicate over some underlying graph topology. In each global round, each node samples some local data, performs a local gradient step, and it is paired with a neighbor, which may be chosen randomly. The nodes exchange model information pairwise, and then update their models, often via direct model averaging. Variants of this setting have been analyzed since pioneering work by Tsitsiklis [1984], for various estimation and optimization algorithms [Xiao and Boyd, 2004, Nedic and Ozdaglar, 2009, Johansson et al., 2009, Shamir and Srebro, 2014] and have seen renewed interest given its applicability to training deep neural networks (DNNs) at scale, e.g. [Lian et al., 2017, 2018, Assran et al., 2018].

Recently, there has been significant focus on reducing the *synchronization overheads* for decentralized training, usually employing three approaches: 1) implementing faster *non-blocking communication* between communication partners at a round [Lian et al., 2018, Assran et al., 2018], which may cause them to see stale versions of their models, 2) allowing nodes to take *local steps* in between their communication rounds [Wang and Joshi, 2018, Koloskova et al., 2020], and 3) applying *quantization* to the communication [Lu and De Sa, 2020, Tang et al., 2018, Koloskova et al., 2019a,b].

The above impressive line of work contributes a rich set of algorithmic and analytic ideas; however, one common limitation is that the algorithms are usually set in the *synchronous gossip* model, which requires all nodes to perform their communication in lock-step rounds, and share a common notion

of time, thus reducing their practicality. To mitigate this fact, some references, e.g. [Lian et al., 2018, Assran et al., 2018, Lu and De Sa, 2020] partially relax this requirement, although they do so at the cost of additional assumptions, or reduced guarantees, as we discuss in related work. Another relative limitation is that the analyses are usually customized to the bespoke communication-reduced methods being applied, and therefore are hard to generalize to other methods.

Our Contribution. In this paper, we consider decentralized SGD-based optimization in the simpler, but harder to analyze, *asynchronous gossip* model [Xiao and Boyd, 2004], in which communication occurs in discrete, randomly chosen pairings among nodes, and thus does not require a common notion of time. We prove that a new variant of SGD we call *SwarmSGD* still converges in this setting, even though it supports all three communication-reduction approaches mentioned above *in conjunction*. Specifically, supporting both *non-blocking communication and quantization* requires new insights. In addition, our analysis generalizes to heterogeneous data distributions and communication topologies. On the practical side, we implement *SwarmSGD* and deploy it in a super-computing environment, showing that it matches or even outperforms previous decentralized methods in terms of accuracy and end-to-end training time, and that it can even rival carefully-tuned large-batch SGD in settings with high synchronization cost.

At a high level, SwarmSGD works as follows. Each node i maintains a local model estimate X_i based on which gradients are generated, and a shared buffer where quantized models are stored for communication with other nodes. In each step, node i first computes a sequence of H local gradient steps, which it does not yet apply. Next, the node chooses communication partner j, uniformly at random among its neighbors. Then, node i reads from its own communication buffer and from the communication buffer of j, obtaining quantized models Q_i and Q_j (a subtlety here is that Q_i is not necessarily the quantized version of the model X_i, since other nodes can write concurrently to i's buffer). The node i then averages Q_i with Q_j, and updates the neighbor's remote buffer to the quantized average. Finally, it applies its local gradient steps to the resulting average, adopts this as its next model X_i, and a writes quantized version of it in its own shared buffer. This procedure can be implemented in a deadlock-free, non-blocking manner, by using either shared-memory or the remote direct-memory access (RDMA) calls supported by MPI [Woodall et al., 2006]. Importantly, the communication partner j does not need to block its computation during communication, and may be contacted by more than one interaction partner during a single local step.

A key component of this procedure is the *quantization scheme*: directly using an unbiased quantizer, e.g. [Alistarh et al., 2017] would destroy convergence guarantees, as the quantization error would be proportional to the model norm, which may not be bounded. Instead, we use a customized variant of the lattice-based quantization scheme of [Davies et al., 2021], which has the property that its error depends on the distance between the *point being quantized* (the model), and an arbitrary *reference point*, which is provided as a parameter to the quantization. One of our key technical insights is that each node can reliably use *its own model* as a *reference point* to quantize and de-quantize messages placed in its buffer by other nodes. In turn, this requires non-trivial care when analyzing the quantization.

Specifically, the key result behind our analysis is exactly in showing that the nodes' local models stay well-enough concentrated around their mean throughout optimization to allow for correct decoding of quantized models, which in turn implies joint convergence by the nodes towards a point of vanishing gradient. This concentration follows via a non-trivial super-martingale argument. If nodes take a constant number of local SGD steps on average between communication steps, then SwarmSGD has $\Theta(\sqrt{n})$ speedup to convergence for non-convex objectives. This matches results from previous work which considered decentralized dynamics but with global synchronization [Lian et al., 2017]. Our analysis also extends to heterogenenous graph topologies, and data distributions.

Experimental Validation. We apply SwarmSGD to train deep neural networks on image classification and machine translation (NMT) tasks, deployed on the Piz Daint supercomputer [Piz, 2019]. Experiments confirm the intuition that the average synchronization cost of SwarmSGD per iteration is low: it stays at less than 10% of the batch computation time, and remains constant as we increase the number of nodes. For example, using SwarmSGD, we are able to train a Transformer-XL [Vaswani et al., 2017] model on WMT17 (En-Ge) $1.5\times$ faster than a highly-optimized large-batch SGD baseline, and to *slightly higher accuracy*, without additional hyper-parameter tuning. At the same time, due to the reduced communication frequency, Swarm also improves upon the speed of the previous practical decentralized methods, e.g. [Lian et al., 2017, 2018, Assran et al., 2018]. Importantly, we also note that, in less overparametrized settings such as training residual CNNs [He et al., 2016] on ImageNet [Russakovsky et al., 2015], nodes do need to perform more iterations over

the dataset relative to the baseline in order to recover full accuracy. This is predicted by the analysis, and confirms similar findings in previous work [Assran et al., 2018]. Overall, our method does appear well-suited to training large modern models at node counts where global synchronization among all nodes is prohibitively expensive.

Related Work. Decentralized optimization has a long history [Tsitsiklis, 1984], and is related to the study of gossip algorithms, e.g. [Kempe et al., 2003, Xiao and Boyd, 2004, Boyd et al., 2006]. Gossip is usually studied in one of two models [Boyd et al., 2006]: *synchronous*, structured in global rounds, where each node interacts with a randomly chosen neighbor, forming a matching, and *asynchronous*, where each node wakes up at random times, e.g. given by a Poisson clock, and picks a random neighbor to interact with. Several classic optimization algorithms have been analyzed in the *asynchronous gossip model* [Nedic and Ozdaglar, 2009, Johansson et al., 2009, Shamir and Srebro, 2014]. In this paper, we focus on analyzing decentralized SGD in this model.

As mentioned, the growing line of work on decentralized optimization for machine learning has mostly focused on variants of the *synchronous* gossip model. Specifically, Lian et al. [2017] considered this setting in the context of DNN training, while and Tang et al. [2018] and Koloskova et al. [2019b] also analyzed decentralized optimization with quantization in the *synchronous* model. Wang and Joshi [2018] and Koloskova et al. [2020] provided analysis frameworks for synchronous decentralized SGD with local updates, and possibly changing topologies.

Lian et al. [2018] and Assran et al. [2018] focused specifically on reducing *synchronization* costs in this setting, and proposed algorithms with *partially non-blocking communication*, in which nodes may read a *stale* version of the interaction partner's information, modelling e.g. a communication buffer. However, the maximum staleness must be bounded by a global variable τ, which must be enforced throughout the execution. Enforcing this bound can cause *blocking* in the system [Assran et al., 2018], and therefore the authors of these works propose to implement a relaxed round-based model, in which nodes interact once per round in perfect matchings. Their algorithms provide $O(1/\sqrt{Tn})$ convergence rates, under analytical assumptions.

Upon careful examination, we find that their analysis approach can be extended to the asynchronous gossip model we consider, by defining the "contact matrices" to correspond to pairwise interactions. However, this introduces two significant limitations. First, the analysis will not support *local gradient updates to models* nor *quantized communication*. If we remove these practical relaxations, our technique yields better bounds, as our potential analysis is specifically-tailored to this dynamic interaction model. Second, some of their technical conditions become unrealistic. Specifically, the analysis of Lian et al. [2018] would require the algorithm to execute for $T \geq n^6$ steps for their bounds to apply, which exceeds the number of steps required by SGD for even moderate counts. For Assran et al. [2018], as we detail in the Appendix, their analysis would not guarantee any non-trivial speedup due to parallelization in the asynchronous gossip model. We describe these issues in detail and present a systematic comparison in Appendix 7.

More recently, Lu and De Sa [2020] provided a novel approach to analyze decentralized SGD with quantization and *limited asynchrony*: specifically, their algorithm requires *blocking* communication, i.e. nodes have to synchronize explicitly during interactions, but may see old versions of eachothers' models. More precisely, during each interaction, both parties are responsible for updating their local models, meaning that once node is woken up (we call it initiator node) and chooses interaction partner it has to block until the partner is woken up as well. In our case, initiator can update both its local model and the local model of its partner and proceed to the next step without blocking. Koloskova et al. [2019a] use a similar update rule, since they consider synchronous model and this means that all the nodes are woken up at the same time.

In sum, we are the first to explicitly consider the *asynchronous gossip model*, and the impact of local updates, asynchrony, and quantization used *in conjunction* together with decentralized SGD. Our technique is new, and relies on a fine-grained analysis of individual interactions, and can yield improved bounds even in the case where $H = 1$. Further, our algorithm is the first to allow for both communication-compression and non-blocking communication. From the implementation perspective, the performance of our algorithm matches or improves that of previous methods, notably D-PSGD [Lian et al., 2017], AD-PSGD [Lian et al., 2018] and SGP [Assran et al., 2018].

2   Preliminaries

The Distributed System Model. We consider a model which consists of $n \geq 2$ nodes, each of which is able to perform local computation. We assume that communication network of nodes is

a graph G with spectral gap λ_2, which denotes the second smallest eigenvalue of the Laplacian of G. Let ρ_{max}, ρ_{min} be the maximum and minimum degrees in G, respectively. We will focus on densely-connected topologies, which model supercomputing and cloud networks: for instance, the standard Dragonfly topology [Kim et al., 2008, Besta and Hoefler, 2014] is regular, densely connected and low-diameter, mimicking regular expanders.

The execution is modelled as occurring in discrete *steps*, where in each step a new node (the "initiator") is sampled, and can then contact one of its neighbors (the "responder") uniformly at random. (At the algorithm level, the initiator is "sampled" once it completes its current computational step, and seeks to interact with a neighbor.) We denote the number of steps for which we run by T. Globally, the communication steps can be seen as a sequence of sampled *directed* communication edges. Thus, the basic unit of time is a single pairwise interaction between two nodes. Notice however that in a real system $\Theta(n)$ of these interactions could occur in parallel. Thus, the standard global time measure is *parallel time*, defined as the total number of interactions divided by n, the number of nodes. Parallel time intuitively corresponds to the *average* number of interactions per node until convergence. This model is identical to the asynchronous gossip model [Xiao and Boyd, 2004], and to the population protocol model [Angluin et al., 2006].

Stochastic Optimization. We assume that the agents wish to jointly minimize a d-dimensional, differentiable function $f : \mathbb{R}^d \to \mathbb{R}$. Specifically, we will assume the empirical risk minimization setting, in which agents are given access to a set of m data samples $S = \{s_1, \ldots, s_m\}$ coming from some underlying distribution $\mathcal{D}$, and to functions $\ell_i : \mathbb{R}^d \to \mathbb{R}$ which encode the loss of the argument at the sample s_i. The goal of the agents is to converge on a model x^* which minimizes the empirical loss over the m samples, that is $x^* = \text{argmin}_x f(x) = \text{argmin}_x (1/m) \sum_{i=1}^m \ell_i(x)$. We assume that each agent i has a local function f_i associated to its fraction of the data, i.e $\forall x \in \mathbb{R}^d$: $f(x) = \sum_{i=1}^n f_i(x)/n$.

Agents employ these samples to run a decentralized variant of SGD, described in detail in the next section. For this, we will assume that each agent i has access to *unbiased stochastic gradients* $\widetilde{g}_i$ of the function f_i, which are functions such that $\mathbb{E}[\widetilde{g}_i(x)] = \nabla f_i(x)$. Stochastic gradients can be computed by each agent by sampling i.i.d. the distribution $\mathcal{D}$, and computing the gradient of f at θ with respect to that sample. Our analysis also extends to the case where each agent is sampling from its own partition of data. We assume the following conditions about the objective function, although not all our results require the second moment bound:

1. **Smooth Gradients**: The gradient $\nabla f_i(x)$ is L-Lipschitz continuous for some $L > 0$, i.e. for all $x, y \in \mathbb{R}^d$ and agent i:
$$\|\nabla f_i(x) - \nabla f_i(y)\| \le L\|x - y\|. \tag{1}$$

2. **Bounded Variance**: The variance of the stochastic gradients is bounded by some $\sigma^2 > 0$, i.e. for all $x \in \mathbb{R}^d$ and agent i:
$$\mathbb{E}\left\|\widetilde{g}_i(x) - \nabla f_i(x)\right\|^2 \le \sigma^2. \tag{2}$$

3. **Bounded Local Function Variance**: There exists $\varsigma^2 > 0$, such that for all $x \in \mathbb{R}^d$:
$$\sum_{i=1}^n \frac{\left\|\nabla f(x) - \nabla f_i(x)\right\|^2}{n} \le \varsigma^2. \tag{3}$$

4. **Bounded Second Moment**: The second moment of the stochastic gradients is bounded by some $M^2 > 0$, i.e. for all $x \in \mathbb{R}^d$ and agent i:
$$\mathbb{E}\left\|\widetilde{g}_i(x)\right\|^2 \le M^2. \tag{4}$$

Note that throughout this paper for any random variable X, by $\mathbb{E}\|X\|^2$ we mean $\mathbb{E}[\|X\|^2]$.

Quantization Procedure. We use a quantization function which follows from Lemma 23 in (the full version of) Davies et al. [2021].

Corollary 2.1. *(Quantization for Communication Buffers) Fix parameters R and $\epsilon > 0$. There exists a quantization procedure defined by an encoding function $Enc_{R,\epsilon} : \mathbb{R}^d \to \{0,1\}^*$ and a decoding function $Dec_{R,\epsilon} = \mathbb{R}^d \times \{0,1\}^* \to \mathbb{R}^d$ such that, for any vector $x \in \mathbb{R}^d$ which we are trying to quantize, and any vector y which is used by decoding, which we call the* decoding *key, if $\|x - y\| \le R^{R^d}$ then with probability at least $1 - \log\log(\frac{\|x-y\|}{\epsilon})O(R^{-d})$, the function $Q_{R,\epsilon}(x) = Dec_{R,\epsilon}(y, Enc_{R,\epsilon}(x))$ has the following properties:*

202 1. *(Unbiased decoding)* $\mathbb{E}[Q_{R,\epsilon}(x)] = \mathbb{E}[Dec_{R,\epsilon}(y, Enc_{R,\epsilon}(x))] = x;$

203 2. *(Error bound)* $\|Q_{R,\epsilon}(x) - x\| \leq (R^2 + 7)\epsilon;$

204 3. *(Communication bound)* *To compute $Dec_{R,\epsilon}(y, Enc_{R,\epsilon}(x))$, only the first B bits of $Enc_{R,\epsilon}(x)$*

205 *are needed, where B is a random variable with $\mathbb{E}[B] = O\left(d\log(\frac{R}{\epsilon}\|x - y\|)\right)$.*

206 The key useful property of this quantization procedure is that the error and the communication cost
207 depend on the *distance* between the input and the decoding key. While Corollary 2.1 does not
208 bound the length of the encoded vectors, we will show an upper bound $B_{max} = O(d\log T)$ on the
209 maximum length that will be needed throughout the entire algorithm with high probability; nodes
210 then need only compute and write B_{max} bits to their buffer per encoding. Furthermore, the amount
211 of bits that must be *communicated* for successful decoding is only B.

3   The SwarmSGD Algorithm

213 We now describe a decentralized variant of SGD, designed to be executed by a population of n
214 nodes, interacting over the edges of communication graph G. We assume that the largest degree
215 of a vertex in G is ρ_{max} and the smallest one is ρ_{min}, additionally we assume that the second
216 smallest eigenvalue of the Laplacian matrix of G, is λ_2. As noted above, the algorithm proceeds
217 in individual communication steps, where in each step a node completes its local computation, and
218 seeks a random neighbor to communicate with. We therefore describe the algorithm from the point
219 of view of a single node i. For simplicity, we will first describe the algorithm sequentially. Next,
220 we detail how this relates to the parallel execution, and describe the quantization function and its
221 parametrization.

222 **Parallel Description.** Each agent i maintains a local model estimate X_i. We will assume that this
223 initial model is 0^d at each agent, although its value may be arbitrary. Each node has a communication
224 buffer, which, for simplicity, we assume can be read and written atomically by each node; however,
225 as detailed below, our implementation is in message-passing via RDMA [Woodall et al., 2006].
226 Importantly, buffers can only hold *quantized* versions of models. We will use the quantization
227 function Q defined in Corollary 2.1, with its quantization function $Enc_{R,\epsilon}$ and de-compression
228 function $Dec_{R,\epsilon}$. (For convenience, we omit R and ϵ in the following, as they will be constant.)
229 Recall that these functions also need a second parameter, as a decoding key.

230 Given the local model X_i, agent i first computes H_i local gradients, where we assume that H_i is a
231 geometric random variable with mean H, as follows. Let $\widetilde{h}_i^0(X_i) = 0^d$; for indices $1 \leq q \leq H_i$, let
232 $\widetilde{h}_i^q(X_i) = \widetilde{g}_i(X_i - \sum_{s=0}^{q-1}\eta\widetilde{h}_i^s(X_i))$ be the q-th local gradient. Then, let $\widetilde{h}_i(X_i) = \sum_{q=1}^{H_i}\widetilde{h}_i^q(X_i)$ be
233 the sum of all computed local gradients.

234 The corresponding sequential pseudocode is provided in Algorithm 1. Once it finishes this compu-
235 tation, the initiator i chooses a neighbor j uniformly at random. Let $Enc(Y_i)$ and $Enc(Y_j)$ be the
236 (quantized) values written in the communication buffers of i and j, respectively, at the time when
237 they interact. Next, i decodes the buffer contents with respect to its current model X_i to obtain
238 $Q(Y_i)$ and $Q(Y_j)$. It then computes their mean, which it encrypts and writes as a remote update into
239 j's buffer. Finally, i updates its own local model to this value, but *including* the gradient step, i.e.
240 $X_t^i = Q(Y_i)/2 + Q(Y_j)/2 - \eta\widetilde{h}_i(X_i)$, and updates its own buffer to the quantized version of this
241 variable, $Enc(X_t^i)$. Crucially, the communication pattern is *one-sided*, as node j does not need to
242 participate in any way.

243 **Sequential Execution.** Next, we discuss how this sequential version relates to the parallel one. The
244 theory assumes that nodes get activated randomly, by independent Poisson clocks, which leads to
245 a uniform global sampling distribution. We approximate this in practice by having the number of
246 local gradient steps executed by each node be a geometric random variable of mean H.[1] Due to the
247 memoryless property, this leads to nodes being sampled uniformly at random. Thus, time t tracks
248 the interactions between agents, and each interaction corresponds to H local steps in expectation.

249 Let us now focus on the interaction between an initiator i and its neighbor j. For both i and j,
250 the values in their communication buffers after $t - 1$ steps are always equal to $Enc(X_{t-1}^i)$ and
251 $Enc(X_{t-1}^j)$, respectively. This is equivalent to reading $Enc(Y_i)$ and $Enc(Y_j)$ in the parallel case.
252 Notice that in the parallel case, the local model of agent i is X_i and it is not aware of what other
253 agents wrote in its communication buffer, for the simplicity in the sequential case we assume that if

---

[1]Experimentally, results are practically identical if the number of local steps is a small *constant* H.

Algorithm 1 Sequential SwarmSGD pseudocode for each interaction between nodes i and j.

1: % Let G be a communication graph.
2: % Initial models $X_0^1 = X_0^2 = ... = X_0^n$
3: **for** $t = 1$ **to** T **do**
4:     Sample the initiator node i uniformly at random.
5:     Node i samples a node j, adjacent to it in G, uniformly at random.
6:     Let $t - 1 - \tau_{t-1}^i$ be the last step at which node i was chosen as initiator.
7:     Let $\hat{X}_{t-1}^i = X_{t-1-\tau_{t-1}^i}^i$ be its model from that step.
8:     % The node i reads quantized values from the buffers of i and j, decoding them w.r.t. $\hat{X}_{t-1}^i$
9:     $Q(X_{t-1}^i) \leftarrow Dec(\hat{X}_{t-1}^i, Enc(X_{t-1}^i))$
10:     $Q(X_{t-1}^j) \leftarrow Dec(\hat{X}_{t-1}^i, Enc(X_{t-1}^j))$
11:     % It then computes the average of these values, and updates model estimates *locally*
12:     $X_t^i \leftarrow Q(X_{t-1}^i)/2 + Q(X_{t-1}^j)/2 - \eta \widetilde{h}_i(\hat{X}_{t-1}^i)$
13:     $X_t^j \leftarrow Q(X_{t-1}^i)/2 + Q(X_{t-1}^j)/2$
14:     % Write $Enc(X_t^i)$ and $Enc(X_t^j)$ to the communication buffers of i and j
15:     % For $k \neq i, j, X_t^k = X_{t-1}^k$.
16: **end for**

---

after t steps there is $Enc(X_t^i)$ written in the communication buffer of agent i, then X_t^i is its local model (even though i has no knowledge of X_t^i) and $X_{t-\tau_t^i}^i$ is its outdated model.

An interesting question is what happens when *multiple nodes* contact j concurrently. For conciseness, our pseudocode assumes that the sequence in lines 9–13 happens atomically, but this sequence can cause a data race. To mitigate this, we implement a bounded non-blocking queue [Michael and Scott, 1996] at each node instead of a single buffer. Thus, instead of overwriting the buffer value, each node simply appends the corresponding quantized model mean to j's communication queue. This causes some further intricacies in the use of quantization, which we describe in the Appendix. In practice, this queue is extremely unlikely to be contended, since communication collisions are rare. Critically, all the above operations are non-blocking, and so the algorithm is deadlock-free.

4 The Convergence of SwarmSGD

Let $\mu_t = \sum_{i=1}^n X_t^i / n$ be the mean over node models at time t. Our main result is the following:

Theorem 4.1. *For learning rate* $\eta = n/\sqrt{T}$, *and quantization parameters* $R = 2 + T^{\frac{3}{d}}$ *and* $\epsilon = \frac{\eta H M}{(R^2 + 7)}$, *with probability at least* $1 - O(\frac{1}{T})$ *we have that Algorithm 1 converges at rate*

$$\frac{1}{T}\sum_{t=0}^{T-1} \mathbb{E}\|\nabla f(\mu_t)\|^2 \leq \frac{2(f(\mu_0) - f(x^*))}{H\sqrt{T}} + \frac{6H(\sigma^2 + 6\varsigma^2)}{\sqrt{T}} + \frac{12HM^2}{\sqrt{T}} + C\frac{n^2 \rho_{max}^3 H^2 L^2 M^2}{T\rho_{min}\lambda_2^2},$$

for constant C, and uses $O\left(d\log\left(\frac{\rho_{max}^2}{\rho_{min}\lambda_2}\right) + \log T\right)$ *expected communication bits per step.*

Discussion. First, this notion of convergence is standard in the non-convex case [Lian et al., 2015, 2017, 2018], and each of the upper bound terms has an intuitive interpretation: *the first* represents the reduction in loss relative to the initialization, and gets divided by the number of local steps H, since progress is made in this term in every local step; *the second* represents the noise due to stochasticity, and is naturally linear in H, as H steps are taken in expectation between two interactions. (Recall that in our model T is the number of interactions, and TH is the expected number of gradient steps.) The *fourth* term encodes overheads caused by local steps, quantization, and graph structure; however, it is usually seen as *negligible* [Lu and De Sa, 2020], due to division by T. We will therefore also ignore this term.

The third term is the critical one, as it implies a dependence on the second-moment bound. Intuitively, this term appears because our algorithm combines both non-blocking communication, *and* quantization: first, unlike prior work, we do not assume an explicit delay upper bound τ on communication; in conjunction with quantization, the unbounded delay this implies that our estimate on the model average μ_t may become dependent on M for large delays, which causes this dependency. While this limitation appears inherent, we are able to remove it if we eliminate quantization: in this case, we get a negligible dependency on M. We formalize this in Corollary 4.2.

Second, if we focus on the total number of steps to reach some error bound, we notice an interesting trade-off between the linear reduction in H in the first term, due to local steps, and the linear increase in H in the other terms. Notice that, for dense and low-diameter graphs, such as the regular expanders popular in cluster networks, our convergence bound has no dependence in the graph parameters, and communication is linear in d. However, one limitation is that we could have a $\log n$ dependency in the communication for highly irregular and poorly-connected graphs. Please see the Appendix for the detailed analysis.

Finally, note that time T here counts *total interactions*. However, $\Theta(n)$ pairwise interactions occur independently in parallel, and so we can replace T by nT in the above formula, to obtain optimal $\Theta(\sqrt{n})$ speedup in terms of wall-clock time. Yet, this speedup is dampened by the variance due to noisy local gradient steps, a fact which we will revisit in the experimental section.

Proof Overview. At a high level, the argument rests on two technical ideas. The first is that, in spite of noise and local steps, the nodes' parameters remain concentrated around the mean μ_t. The second is to leverage this, and bound the impact of stochastic noise and model staleness on convergence. In particular, the main technical difficulty in the proof is to correctly "encode" the fact that parameters are well concentrated around the mean. A natural approach is to bound the model variance Γ_t after t interactions. Formally, we define $\Gamma_t = \sum_{i=1}^{n} \|X_t^i - \mu_t\|^2$, where $\mu_t = \sum_{i=1}^{n} X_t^i / n$, as before.

We bound the expected evolution of Γ_t over time, depending on the learning rate, number of local steps, quantization parameter and the bound provided by the assumption on the stochastic gradients (the bound M^2). The critical point is that the upper bound on the expectation of Γ_t *does not depend* on the number of interactions t. More precisely, if all the above hyper-parameters are constant, we get that $\mathbb{E}[\Gamma(t)] = O(n)$. Our approach brings over tools from classic load-balancing [Berenbrink et al., 2009], to the multi-dimensional case.

Three key elements of novelty in our case are that (1) for us the load balancing process is *dynamic*, in the sense that new loads, i.e. gradients, get continually added; (2) the load-balancing process we consider is multi-dimensional, whereas usually the literature considers simple scalar weights; (3) the models can be *outdated* and *quantized*, which leads to a complex, noisy load-balancing process. We resolve the this third and most challenging issue by using carefully-defined auxiliary potentials. We encourage the reader to examine the complete argument in the Appendix.

Removing the Second-Moment Bound. Upon reflection, we notice that can render the dependency on M^2 negligible if we do not use quantization, but otherwise keep the algorithm the same:

Corollary 4.2. *Given the previous assumptions and learning rate $\eta = n/\sqrt{T}$, for some constant C, we have that the Algorithm 1 where quantization is the identity converges at rate*

$$\frac{1}{T}\sum_{t=0}^{T-1}\mathbb{E}\|\nabla f(\mu_t)\|^2 \leq \frac{2(f(\mu_0) - f(x^*))}{H\sqrt{T}} + \frac{6H(\sigma^2 + 6\varsigma^2)}{\sqrt{T}} + \frac{Cn^2\rho_{max}^3 H^2 L^2 M^2}{T\rho_{min}\lambda_2^2}.$$

Notice that in this case all the term containing the second moment bound M^2 is dampened by a factor of $\frac{1}{T}$, hence we can assume that Algorithm 1 converges at close-to optimal rate $O\left(\frac{2(f(\mu_0) - f(x^*))}{H\sqrt{T}} + \frac{6H(\sigma^2 + 6\varsigma^2)}{\sqrt{T}}\right)$. This result still improves upon previous analyses [Lian et al., 2018, Assran et al., 2018, Lu and De Sa, 2020] in the sense that communication is completely non-blocking (there is no τ), and we allow for local steps.

5 Experimental Results

In this section, we validate our analysis, by applying the algorithm to training deep neural networks for image classification and machine translation. We map the algorithm onto a multi-node supercomputing setting, in which we have a large number of compute nodes, connected by fast communication links. The key overhead in this setting is *synchronization*: at large node counts, the cost of synchronizing all nodes so they execute in lock-step can be very high, see e.g. [Li et al., 2019] for numerical results on different workloads. Transmission cost also becomes significant at large node counts and large model sizes. Decentralized methods can mitigate this overhead, since nodes synchronize only sporadically and in pairs.

Target System and Implementation. We run SwarmSGD on the CSCS Piz Daint supercomputer, which is composed of Cray XC50 nodes, each with a Xeon E5-2690v3 CPU and an NVIDIA Tesla P100 GPU, using a state-of-the-art Aries interconnect over a Dragonfly network topology, which is *regular*. Please see Piz [2019] for more details. We implemented SwarmSGD in Pytorch and

(a) Convergence versus Time.

(b) Throughput comparison. Higher is better.

Figure 1: Convergence and Scalability on the Transformer/WMT Task with multiplier = 1.

(a) Convergence in time versus number of local steps for ResNet18 on ImageNet. All variants recover the target accuracy, but we note the lower convergence of variants with more local steps. The experiment is run on 32 nodes.

(b) Average time per batch for previous methods, compared to SwarmSGD, on ResNet18/ImageNet. The base value on the y axis (0.4) is the average computation time per batch, so values above represent average communication time per batch.

Figure 2: Convergence results and performance breakdown for ResNet18/ImageNet.

TensorFlow using MPI-based primitives, with non-blocking averaging. The Pytorch implementation is on top of SGP framework [Assran et al., 2018], and uses SwarmSGD to train ResNets on the CIFAR-10/100 Krizhevsky et al. [2014] and ImageNet Russakovsky et al. [2015] datasets, while we use the TensorFlow implementation to train a much larger Transformer-XL model Vaswani et al. [2017] on the WMT17 (En-Ge) dataset. All algorithms use the same topology overlay, which is *fully-connected*: according to their theory and experiments, this well-connected overlay should maximize their convergence speed. SGP was run with overlap factor 1, as suggested by Assran et al. [2018].

Training Process. Our training methodology follows data-parallel training, with some differences due to decentralization, and is identical to previous work on decentralized and local SGD, e.g. Lian et al. [2017], Assran et al. [2018], Lin et al. [2018]. Training proceeds in *epochs*, each of which corresponds to processes collectively performing a full pass over the dataset. At the beginning of each epoch, we re-shuffle the dataset and partition it among processes [Lin et al., 2018].

As noted in previous work [Lian et al., 2017, 2018, Assran et al., 2018] variants of decentralized SGD are not always able to recover sequential SGD accuracy within the same number of epochs as this baseline. This is justified theoretically, as the slower mixing can affect convergence. Thus, we will allow the decentralized schemes to execute for more epochs, by a constant *multiplier* factor between 1 and 3. To reduce multipliers, we experimented with SlowMo [Wang et al., 2019]; we found that it improved results across methods on CIFAR-10, but not at ImageNet scale; therefore, the provided results do not include it. Once we have fixed the number of epochs, *we do not alter the other training hyperparameters*: in particular, the learning rate schedule, momentum and weight decay terms are identical to sequential SGD, for each individual model.

Accuracy and Speed. We first examined whether SwarmSGD can in fact recover full accuracy versus the sequential or large-batch SGD baselines. In Table 1 we provide an overview of parameter values to recover large-batch SGD accuracy (following Goyal et al. [2017]) using SwarmSGD, on the ResNet, ImageNet and CIFAR tasks. We execute for 32 nodes on ImageNet, and 8 nodes on CIFAR-10. (Local batch sizes are 128 for ResNet20 and ResNet50, and 128 for ResNet18. Quantization is not applied in these experiments.) The results show that Swarm can recover or slightly exceed the accuracy of the large-batch baselines, and that it has lower practical communication cost relative to existing methods (see Figure 2(b), where we separate the average computation cost per

Model / Dataset	SGD Top-1	LB SGD Top-1	SwarmSGD	Parameters
ResNet20 / CIFAR-10	91.7% (200 epochs)	91.57% (200 epochs)	91.59% (300 epochs)	4 local steps
ResNet18 / ImageNet	69.76 % (90 epochs)	69.17% (90 epochs)	69.79% (240 epochs)	3 local steps
ResNet50 / ImageNet	76.14% (90 epochs)	76.01% (90 epochs)	76.08% (240 epochs)	2 local steps

Table 1: Parameters for approximate Top-1 validation accuracy recovery on CIFAR-10 and ImageNet running on 32 nodes. Swarm step count represents *local SGD steps per model* between two averaging steps, and epochs are counted in terms of total passes over the data by all nodes.

batch). However, Swarm requires significant additional passes over the data (up to $2.7\times$) to achieve full accuracy, which negates its performance benefits in this specific setting, relative to large-batch SGD. (Please see the Supplementary for end-to-end time comparisons.) This finding is in line with previous work on decentralized methods [Assran et al., 2018].

Next, we examine accuracy for the WMT17 task. The results are provided in Figure 1(a), in accuracy-vs-time format, for 16 and 32 nodes, executing for 10 global epochs. Here, the large-batch SGD (LB-SGD) baseline (BLEU score 26.1 at 16 nodes) is a poor alternative at high node counts due to model size: its throughput is low, and drops catastrophically at 64 nodes due to the network becoming severely bandwdith-bottlenecked (see Figure 1(b)). At 16 nodes, Swarm *slightly exceeds* the baseline accuracy at 26.17 BLEU, for an end-to-end speedup of $\sim 1.5\times$. In the same setting, Swarm outperforms all other decentralized methods (the fastest previous method, AD-PSGD, is 30% slower, and less accurate), both in terms of BLEU score, and in terms of end-to-end time.(The objective loss graph is similar, and is provided in the Appendix). At 32 nodes, all decentralized methods reach lower scores (~ 23.5) after 10 epochs. However, we observed experimentally that running Swarm for an additional 5 epochs (multiplier 1.5) at 32 nodes recovered a BLEU score of ~ 25.92, which is 30% faster than the 16-node version in terms of end-to-end time (omitted for visibility).

In addition, we investigated 1) the accuracy of the *real average* of all models throughout training: it is usually more accurate than an arbitrary model, but not significantly, corroborating the claim that individual models tend to stay close to the mean; 2) the influence of the number of local steps on accuracy: perhaps surprisingly, we were able to recover baseline accuracy on ResNet18/ImageNet for up to 4 local steps (see Figure 2(a)); 3) the impact of quantization on convergence, where we were able to recover accuracy when applying 8-bit model quantization to Swarm. We encourage the reader to examine the full experimental report in the Appendix, which contains data on these experiments, as well as additional ablation studies.

Discussion. Generally, the performance and accuracy of SwarmSGD appear to be superior to previous decentralized methods (see Figure 1 for an illustration, and Figure 2(b) for a performance breakdown). We investigated this advantage, and found that the per-step communication cost of Swarm, without quantization, is similar to AD-PSGD; however, our algorithm benefits from the *reduction in communication frequency*: nodes communicate at least 2x less often, and therefore incur lower *average* communication cost. In particular, a closer examination of the average batch times in Figure 2(b) shows that time per node per batch (including communication and computation) is largely *constant* as we increase the number of nodes, which suggests good scaling behaviour.

The main disadvantage of Swarm is that, similar to previous decentralized methods, it may need additional data passes in order to fully recover accuracy at high node counts. However, we also note that our method did not benefit from the high level of hyperparameter tuning applied to large-batch SGD, e.g. Goyal et al. [2017]. We find it interesting that this accuracy issue is less prevalent in the context of large, over-parameterized models, such as the Transformer, where Swarm can be a viable alternative to large-batch SGD within the same number of epochs.

6 Conclusions and Future Work

We analyzed the convergence of SGD in an extremely decoupled model of distributed computing, in which nodes mostly perform independent SGD updates, interspersed with intermittent pairwise averaging steps, which may be performed in an inconsistent and noisy manner. We showed that SGD still converges in this restrictive setting, even under consistency relaxations. Empirical results complement our analysis, showing that this method can outperform previous decentralized algorithms, and can even be competitive against large-batch SGD for very large models. A natural extension would be to generalize the bounds to arbitrary communication graphs. From the practical perspective, we plan to improve multipliers, and experiment on large-scale decentralized testbeds.

References

Xiangru Lian, Ce Zhang, Huan Zhang, Cho-Jio Hsieh, Wei Zhang, and Ji Liu. Can decentralized algorithms outperform centralized algorithms? a case study for decentralized parallel stochastic gradient descent. *arXiv preprint arXiv:1705.09056*, 2017.

Hanlin Tang, Ce Zhang, Shaoduo Gan, Tong Zhang, and Ji Liu. Decentralization meets quantization. *arXiv preprint arXiv:1803.06443*, 2018.

Anastasia Koloskova, Tao Lin, Sebastian U Stich, and Martin Jaggi. Decentralized deep learning with arbitrary communication compression. *arXiv preprint arXiv:1907.09356*, 2019a.

John Nikolas Tsitsiklis. Problems in decentralized decision making and computation. Technical report, Massachusetts Inst of Tech Cambridge Lab for Information and Decision Systems, 1984.

Lin Xiao and Stephen Boyd. Fast linear iterations for distributed averaging. *Systems & Control Letters*, 53(1):65–78, 2004.

Angelia Nedic and Asuman Ozdaglar. Distributed subgradient methods for multi-agent optimization. *IEEE Transactions on Automatic Control*, 54(1):48, 2009.

Björn Johansson, Maben Rabi, and Mikael Johansson. A randomized incremental subgradient method for distributed optimization in networked systems. *SIAM Journal on Optimization*, 20 (3):1157–1170, 2009.

Ohad Shamir and Nathan Srebro. Distributed stochastic optimization and learning. In *2014 52nd Annual Allerton Conference on Communication, Control, and Computing (Allerton)*, pages 850–857. IEEE, 2014.

Xiangru Lian, Wei Zhang, Ce Zhang, and Ji Liu. Asynchronous decentralized parallel stochastic gradient descent. In *International Conference on Machine Learning*, pages 3043–3052. PMLR, 2018.

Mahmoud Assran, Nicolas Loizou, Nicolas Ballas, and Michael Rabbat. Stochastic gradient push for distributed deep learning. *arXiv preprint arXiv:1811.10792*, 2018.

Jianyu Wang and Gauri Joshi. Cooperative sgd: A unified framework for the design and analysis of communication-efficient sgd algorithms. *arXiv preprint arXiv:1808.07576*, 2018.

Anastasia Koloskova, Nicolas Loizou, Sadra Boreiri, Martin Jaggi, and Sebastian U Stich. A unified theory of decentralized sgd with changing topology and local updates. *arXiv preprint arXiv:2003.10422*, 2020.

Yucheng Lu and Christopher De Sa. Moniqua: Modulo quantized communication in decentralized SGD. In *Proc. International Conference on Machine Learning (ICML)*, 2020.

Anastasia Koloskova, Tao Lin, Sebastian U Stich, and Martin Jaggi. Decentralized deep learning with arbitrary communication compression. *arXiv preprint arXiv:1907.09356*, 2019b.

Tim S Woodall, Galen M Shipman, George Bosilca, Richard L Graham, and Arthur B Maccabe. High performance rdma protocols in hpc. In *European Parallel Virtual Machine/Message Passing Interface Users' Group Meeting*, pages 76–85. Springer, 2006.

Dan Alistarh, Demjan Grubic, Jerry Li, Ryota Tomioka, and Milan Vojnovic. QSGD: Randomized quantization for communication-efficient stochastic gradient descent. In *Proceedings of NIPS 2017*, 2017.

Peter Davies, Vijaykrishna Gurunathan, Niusha Moshrefi, Saleh Ashkboos Ashkboos, and Dan Alistarh. Distributed variance reduction with optimal communication. In *Proceedings of the International Conference on Learning Representations, ICLR 2021. Full version available at arXiv:2002.09268*, 2021.

The CSCS Piz Daint supercomputer. http://www.cscs.ch/computers/piz_daint, 2019. Accessed: 2020-1-25.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in neural information processing systems*, pages 5998–6008, 2017.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, et al. Imagenet large scale visual recognition challenge. *International Journal of Computer Vision*, 115(3):211–252, 2015.

David Kempe, Alin Dobra, and Johannes Gehrke. Gossip-based computation of aggregate information. In *44th Annual IEEE Symposium on Foundations of Computer Science, 2003. Proceedings.*, pages 482–491. IEEE, 2003.

Stephen Boyd, Arpita Ghosh, Balaji Prabhakar, and Devavrat Shah. Randomized gossip algorithms. *IEEE/ACM Trans. Netw.*, 14(SI):2508–2530, June 2006. ISSN 1063-6692. doi:10.1109/TIT.2006.874516. URL https://doi.org/10.1109/TIT.2006.874516.

John Kim, Wiliam J Dally, Steve Scott, and Dennis Abts. Technology-driven, highly-scalable dragonfly topology. In *2008 International Symposium on Computer Architecture*, pages 77–88. IEEE, 2008.

Maciej Besta and Torsten Hoefler. Slim fly: A cost effective low-diameter network topology. In *SC'14: Proceedings of the International Conference for High Performance Computing, Networking, Storage and Analysis*, pages 348–359. IEEE, 2014.

Dana Angluin, James Aspnes, Zoë Diamadi, Michael J Fischer, and René Peralta. Computation in networks of passively mobile finite-state sensors. *Distributed computing*, 18(4):235–253, 2006.

Maged M. Michael and Michael L. Scott. Simple, fast, and practical non-blocking and blocking concurrent queue algorithms. In *Proceedings of the 15th Annual ACM Symposium on Principles of Distributed Computing (PODC)*, pages 267–275, 1996.

Xiangru Lian, Yijun Huang, Yuncheng Li, and Ji Liu. Asynchronous parallel stochastic gradient for nonconvex optimization. In *Advances in Neural Information Processing Systems*, pages 2737–2745, 2015.

Petra Berenbrink, Tom Friedetzky, and Zengjian Hu. A new analytical method for parallel, diffusion-type load balancing. *J. Parallel Distrib. Comput.*, 69(1):54–61, January 2009. ISSN 0743-7315. doi:10.1016/j.jpdc.2008.05.005. URL https://doi.org/10.1016/j.jpdc.2008.05.005.

Shigang Li, Tal Ben-Nun, Salvatore Di Girolamo, Dan Alistarh, and Torsten Hoefler. Taming unbalanced training workloads in deep learning with partial collective operations. *arXiv preprint arXiv:1908.04207*, 2019.

Alex Krizhevsky, Vinod Nair, and Geoffrey Hinton. The cifar-10 dataset. *online: http://www.cs.toronto. edu/kriz/cifar.html*, 55, 2014.

Tao Lin, Sebastian U Stich, Kumar Kshitij Patel, and Martin Jaggi. Don't use large mini-batches, use local sgd. *arXiv preprint arXiv:1808.07217*, 2018.

Jianyu Wang, Vinayak Tantia, Nicolas Ballas, and Michael Rabbat. Slowmo: Improving communication-efficient distributed sgd with slow momentum. *arXiv preprint arXiv:1910.00643*, 2019.

Priya Goyal, Piotr Dollár, Ross Girshick, Pieter Noordhuis, Lukasz Wesolowski, Aapo Kyrola, Andrew Tulloch, Yangqing Jia, and Kaiming He. Accurate, large minibatch sgd: Training imagenet in 1 hour. *arXiv preprint arXiv:1706.02677*, 2017.

Bhaskar Ghosh and S. Muthukrishnan. Dynamic load balancing by random matchings. *J. Comput. Syst. Sci.*, 53(3):357–370, December 1996. ISSN 0022-0000. doi:10.1006/jcss.1996.0075. URL https://doi.org/10.1006/jcss.1996.0075.