MetaNorm: Learning to Normalize Few-Shot Batches Across Domains

Abstract

Batch normalization plays a crucial role when training deep neural networks. However, batch statistics become unstable with small batch sizes and are unreliable in the presence of distribution shifts. We propose MetaNorm, a simple yet effective meta-learning normalization. It tackles the aforementioned issues in a unified way by leveraging the meta-learning setting and learns to infer adaptive statistics for batch normalization. MetaNorm is generic, flexible and model-agnostic, making it a simple plug-and-play module that is seamlessly embedded into existing meta-learning approaches. It can be efficiently implemented by lightweight hypernetworks with low computational cost. We verify its effectiveness by extensive evaluation on representative tasks suffering from the small batch and domain shift problems: few-shot learning and domain generalization. We further introduce an even more challenging setting: few-shot domain generalization. Results demonstrate that MetaNorm consistently achieves much better, or at least competitive, accuracy compared to existing batch normalization methods.

1 Introduction

Batch normalization (Ioffe & Szegedy, 2015) is crucial for training neural networks, and with its variants, e.g., layer normalization (Ba et al., 2016), group normalization (Wu & He, 2018) and instance normalization (Ulyanov et al., 2016), has thus become an essential part of the deep learning toolkit (Bjorck et al., 2018; Luo et al., 2018a; Yang et al., 2019; Jia et al., 2019; Luo et al., 2018b; Summers & Dinneen, 2020). Batch normalization helps stabilize the distribution of internal activations when a model is being trained. Given a mini-batch $\mathcal{B}$, the normalization is conducted along each individual feature channel. During training, the batch normalization moments are calculated as follows:

$$\mu_{\mathcal{B}} = \frac{1}{M} \sum_{i=1}^{M} a_i, \quad \sigma_{\mathcal{B}}^2 = \frac{1}{M} \sum_{i=1}^{M} (a_i - \mu_{\mathcal{B}})^2, \tag{1}$$

where a_i indicates the i-th element of the M activations in the batch, $M = |\mathcal{B}| \times H \times W$, in which H and W are the height and width of the feature map in each channel. We can now apply the normalization statistics to each activation:

$$a_i' \leftarrow \mathbf{BN}(a_i) \equiv \gamma \hat{a}_i + \beta, \quad \text{where,} \quad \hat{a}_i = \frac{a_i - \mu_{\mathcal{B}}}{\sqrt{\sigma_{\mathcal{B}}^2 + \epsilon}}, \tag{2}$$

where γ and β are parameters learned during training, ϵ is a small scalar to prevent division by 0, and operations between vectors are element-wise. At test time, the standard practice is to normalize activations using the moving average over mini-batch means $\mu_{\mathcal{B}}$ and variance $\sigma_{\mathcal{B}}^2$. Batch normalization relies on the implicit assumption that the dataset comprises i.i.d. samples from some underlying distribution. However, this assumption does not hold in challenging settings like few-shot learning and domain generalization. In this paper, we strive for batch normalization when batches are of small size *and* suffer from distributions shifts between source and target domains.

Batch normalization for few-shot learning and domain generalization problems have so far been considered separately, predominantly in a meta-learning setting. For few-shot meta-learning (Snell et al., 2017; Finn et al., 2017; Gordon et al., 2019), existing methods rely critically on transductive batch normalization (Bronskill et al., 2020; Nichol et al., 2018). However, the nature of transductive

learning restricts its application due to the requirement to sample from the test set. To address this issue, Bronskill et al. (2020) proposes TaskNorm, which leverages other statistics from both layer and instance normalization. As a non-transductive normalization approach, it achieves impressive performance and outperforms conventional batch normalization (Ioffe & Szegedy, 2015). However, its performance remains under-performing compared to transductive batch normalization. Meanwhile, domain generalization (Muandet et al., 2013; Balaji et al., 2018; Li et al., 2017a;b) suffers from distribution shifts from training to test, which makes it problematic to directly apply statistics calculated from a seen domain to test data from unseen domains (Wang et al., 2019; Seo et al., 2019). Recent works deal with this problem by learning a domain specific normalization (Chang et al., 2019; Seo et al., 2019) or a transferable normalization in place of existing normalization techniques (Wang et al., 2019). We address the batch normalization challenges for few-shot classification and domain generalization in a unified way by learning a new batch normalization under the meta-learning setting.

We propose MetaNorm, a simple but effective meta-learning normalization. We leverage the meta-learning setting and learn to infer normalization statistics from data, instead of applying direct calculations or blending various normalization statistics. MetaNorm is a general batch normalization approach, which is model-agnostic and serves as a plug-and-play module that can be seamlessly embedded into existing meta-learning approaches. We demonstrate its effectiveness for few-shot classification and domain generalization, where it *learns* task-specific statistics from limited data samples in the support set for each few-shot task; and it can also learn to generate domain-specific statistics from the seen source domains for unseen target domains. We verify the effectiveness of MetaNorm by extensive evaluation on few-shot classification and domain generalization tasks. For few-shot classification, we experiment with representative gradient, metric and model-based meta-learning approaches on fourteen benchmark datasets. For domain generalization, we evaluate the model on three widely-used benchmarks for cross-domain visual object classification. Last but not least, we introduce the challenging new task of *few-shot domain generalization*, which combines the challenges of both few-shot learning and domain generalization. The experimental results demonstrate the benefit of MetaNorm compared to existing batch normalizations.

2 METHODOLOGY

We view finding appropriate statistics for batch normalization as a density estimation problem. We need to infer the distribution parameters, such as, μ and σ when a Gaussian distribution is presumed, as in existing batch normalization approaches. The motivation behind MetaNorm is to leverage the meta-learning setting and learn from data to generate adaptive normalization statistics. MetaNorm is generic and model-agnostic, addressing batch normalization in a unified way for different settings by minimizing the KL divergence:

$$D_{\mathrm{KL}}\big[q(m)|p(m)\big], \tag{3}$$

where $q(m)$ and $p(m)$ are defined as Gaussian distributions with different implementations depending on the task of interest, e.g., few-shot classification or domain generalization. We leverage the amortized inference technique (Kingma & Welling, 2014) and implement this by inference networks. To be more specific, for each individual channel in each ℓ convolutional layer, we infer the moments μ and σ by $f_\mu^\ell(\cdot)$ and $f_\sigma^\ell(\cdot)$, respectively, which are realized as multi-layer perceptions and we call hypernetworks. They are three layer networks with one hidden layer of 128 units and the input size depends on the feature dimensions of the convolutional layers.

MetaNorm for Few-Shot Classification In the few-shot classification scenario, we define the $\mathcal{C}$-way K-shot problem using the episodic formulation from (Vinyals et al., 2016). Each task $\mathcal{T}_i$ is a classification problem sampled from a task distribution $p(\mathcal{T})$. The tasks are divided into a *training meta-set* $\mathcal{T}^{tr}$, *validation meta-set* $\mathcal{T}^{val}$, and *test meta-set* $\mathcal{T}^{test}$, each with a disjoint set of target classes (i.e., a class seen during testing is not seen during training). The validation meta-set is used for model selection, and the testing meta-set is used only for final evaluation. Each task instance $\mathcal{T}_i \sim p(\mathcal{T})$ is composed of a support set $\mathcal{S}$ and a query set $\mathcal{Q}$, and only contains N classes randomly selected from the appropriate meta-set.

We aim to infer statistics from the support set that better match the query set. Therefore, we adopt a straightforward criterion for the inference:

$$D_{\mathrm{KL}}\big[q(m|S)||p(m|Q)\big], \tag{4}$$

where we define $q(m|S) = \mathcal{N}(\mu_S, \sigma_S)$ and $p(m|Q) = \mathcal{N}(\mu_Q, \sigma_Q)$, which are the distributions inferred from the support and query sets in a few-shot learning task. By minimizing the KL term in conjunction with the prime objective of a meta-learning algorithm, we are able to find the appropriate statistics from limited data samples for batch normalization. The KL term adheres to a closed form, which makes it easy to implement and computationally efficient. The $p(m|Q)$ can be estimated by directly calculating statistics using the query set, which however performs inferior to inference by optimization. We would like to highlight that the inference from the query set only happens during meta-training time and we use the learned inference network to generate normalization statistics in meta-test time for a test task using its support set.

To infer μ_S, we deploy an inference function $f_\mu^\ell(\cdot)$ that takes activations of a sample as input, and the outputs from all samples are then averaged as the final μ_S:

$$\mu_S = \frac{1}{|\mathcal{S}|} \sum_{i=1}^{|\mathcal{S}|} f_\mu^\ell(\mathbf{a}_i), \tag{5}$$

where $\mathbf{a}_i \in \mathbb{R}^{w \times h}$ is the flattened vector of the activation map of the i-th sample in the support set, w is the width of activation, and h is the height of the activation map. To infer σ_S, we use the obtained μ_S and deploy a separate inference function $f_\sigma^\ell(\cdot)$:

$$\sigma_S = \frac{1}{|\mathcal{S}|} \sum_{i=1}^{|\mathcal{S}|} f_\sigma^\ell\big((\mathbf{a}_i - \mu_S)^2\big). \tag{6}$$

It is worth mentioning that we actually use each sample to infer the statistics and take the average of all inferred statistics as the final normalization statistics. This enables us to fully exploit the samples to generate more accurate statistics.

Note that the inference functions $f_\mu^\ell(\cdot)$ and $f_\sigma^\ell(\cdot)$ are shared by different channels in the same layer and we will learn L pairs of those functions if we have L convolutional layers in the meta-learning model. They are parameterized by feed-forward multiple layer perception networks, which we call hypernetworks. Using these hypernetworks, we generate support moments (μ_S, σ_S) and query moments (μ_Q, σ_Q) from the support and query sets, which are used for calculating the KL term in Eq. (4) for optimization during meta-training time. At meta-training time, we apply the statistics inferred from the support set for normalization of both support and query samples:

$$a' = \gamma \left(\frac{a - \mu_S}{\sqrt{\sigma_S^2 + \epsilon}} \right) + \beta, \tag{7}$$

where γ and β are jointly learned with parameters of the hypernetworks at meta-training time and directly applied at meta-test time, as in conventional batch normalization. At meta-test time, given a test task, we use hypernetworks that take the support set as input to generate normalization statistics directly used for the query set.

MetaNorm for Domain Generalization In the domain generalization scenario, we adopt the meta-learning setting from (Li et al., 2018a; Balaji et al., 2018; Li et al., 2019), and divide a dataset into the source domains used for training and the target domains held out for testing. At training time, data in the source domains is episodically divided into sets of meta-train $\mathcal{D}^s$ and meta-test $\mathcal{D}^t$ domains.

In a similar vein to few-shot classification, we would like to learn to acquire the ability to generate domain-specific statistics from a single example, which can then be applied to unseen domains. We use a single example and all the examples in the same domain to infer the domain-specific statistics and minimize the KL term:

$$D_{\mathrm{KL}}\big[q(m|\mathbf{a}_i)||p(m|\mathcal{D}^s\backslash\mathbf{a}_i)\big], \tag{8}$$

where we define $q(m|\mathbf{a}_i) = \mathcal{N}(\mu_a, \sigma_a)$, and $p(m|\mathcal{D}^s\backslash\mathbf{a}_i) = \mathcal{N}(\mu_D, \sigma_D)$, which are implemented in a similar way as Eqs. (5) and (6), and $\mathbf{a}_i$ is an example from its own domain $\mathcal{D}^s$. In both meta-train and meta-test domains, each example is normalized using the statistics generated by itself, like in Eq. (7), in which we make γ and β shared across all domains. The minimization of the KL term in Eq. (8) is to encourage the model to generate domain-specific statistics for normalization from only a single example. This enables us to generate domain-specific statistics on test domains that are never seen at meta-training time.

Figure 1: **Illustration of the novel few-shot domain generalization scenario** using the 5-way, 1-shot setting. The training set in the upper box contains the meta-train domains $\mathcal{D}^s$ and the meta-test domain $\mathcal{D}^t$, which are from different domains. Each training task contains meta-train domains with five different classes and one example of each meta-train domain, and more than four examples for evaluation in the meta-test domain. The test set is defined in the same way but with all source domains $\mathcal{S}$ covering classes not present in any of the datasets in the training set, and more than four examples are used for evaluation in the target domain $\mathcal{T}$.

In practice, we take the sum of all samples in all source domains as follows:

$$\sum_i^{|\mathcal{D}^s|} \sum_j^J D_{\mathrm{KL}}\big[q(m|\mathbf{a}_i)||p(m|\mathcal{D}_j^s \backslash \mathbf{a}_i)\big], \tag{9}$$

where $\mathcal{D}_j^s$ denotes the j-th of J meta-source domains. The inference networks are first at meta-training time learned and then directly used as examples from the target domain at meta-test time. Note that on the meta-target domain we do not apply the KL term; instead, we simply rely on each example to generate its statistics for normalization.

MetaNorm for Few-Shot Domain Generalization   We introduce an even more challenging setting, i.e., few-shot domain generalization, that combines the challenges of both few-shot classification and domain generalization. Specifically, we aim to learn a model from a set of classification tasks, each of which has only a few samples in a support set for training and test the model on tasks in a query set, which are in a different domain from the support set. Like few-shot classification, the label space is not shared between training and testing. An example for the few-shot domain generalization setting is given in Figure 1.

We divide a dataset into the source domains $\mathcal{S}$ used for training and the target domains $\mathcal{T}$ held out for testing. During training time, data in the source domains $\mathcal{S}$ is episodically divided into sets of meta-train D^s and meta-test $\mathcal{D}^t$ domains. We sample $\mathcal{C}$-way k-shot data as the support set from each meta-train domain $\mathcal{D}^s$, where k is the number of labelled examples for each of the $\mathcal{C}$ classes. We sample $\mathcal{C}$ classes from meta-test $\mathcal{D}^t$ domain as the query set. At test time, we sample $\mathcal{C}$-way k-shot data as the support set from each of the source domains $\mathcal{S}$. The model learned at meta-training time is then fine-tuned on few-shot tasks samples from the source domains and tested on the target domain $\mathcal{T}$. To learn the normalization statistics, we minimize the following KL term:

$$\sum_i^{|\mathcal{D}^s|} D_{\mathrm{KL}}[q(m|\mathbf{a}_i)||p(m|\mathcal{D}^s)], \tag{10}$$

where $\mathbf{a}_i$ is the activation associated with each sample from the meta-source domain $\mathcal{D}^s$. Likewise, $q(m|\mathbf{a}_i)$ and $p(m|\mathcal{D}^s)$ are also defined as factorized Gaussian distributions. We also adopt γ and β, which are shared across tasks and jointly learned. MetaNorm learns to acquire the ability to generate proper statistics for itself, and applies it to the samples in the meta-target domain.

3 RELATED WORKS

Transductive Batch Normalization For conventional batch normalization under supervised settings, i.i.d. assumptions about the data distribution imply that estimating moments from the training set will provide appropriate normalization statistics for test data. However, in the meta-learning scenario data points are only assumed to be i.i.d. within a specific task. Therefore, it is critical to select the moments when batch normalization is applied to support and query set data points during meta training and meta testing. Hence, in the recent meta-learning literature the running moments are no longer used for normalization at meta-test time, but instead replaced with support/query set statistics. These statistics are used for normalization, both at meta-train *and* meta-test time. This approach is referred to as *transductive batch normalization* (TBN) (Bronskill et al., 2020). Competitive meta-learning methods (e.g., Gordon et al., 2019; Finn et al., 2017; Snell et al., 2017) rely on TBN to achieve state-of-the-art performance. However, there are two critical problems with TBN. First, TBN is sensitive to the distribution over the query set used during meta-training, and as such is less generally applicable than non-transductive learning. Second, TBN uses extra information for multiple test samples, compared to non-transductive batch normalization at prediction time, which could be problematic as we are not guaranteed to have a set of test samples available during training in practical applications. In contrast, MetaNorm is a non-transductive normalization. It generates statistics from the support set only, without relying on query samples, making it more practical.

Meta Batch Normalization To address the problem of transductive batch normalization and improve conventional batch normalization, meta-batch normalization (MetaBN) was introduced (Triantafillou et al., 2019; Bronskill et al., 2020). In MetaBN, the support set alone is used to compute the normalization statistics for *both* the support and query sets at both meta-training and meta-test time. MetaBN is non-transductive since the normalization of a test input does not depend on other test inputs in the query set. However, Bronskill et al. (2020) observe that MetaBN performs less well for small-sized support sets. This leads to high variance in moment estimates, which is similar to the difficulty of using batch normalization with small-batch training (Wu & He, 2018). To address this issue, Bronskill et al. (2020) proposed TaskNorm, which learns to combine statistics from both layer normalization and instance normalization, with a lending parameter to be learned at meta-train time. As a non-transductive normalization, TaskNorm achieves impressive performance, outperforming conventional batch normalization. However, it remains under-performing compared to TBN. TaskNorm indicates that non-transductive batch normalization can estimate proper normalization statistics by involving learning in the normalization process. We also propose to learn batch normalization within the meta-learning framework, but instead of employing a learnable combination of existing normalization statistics, we directly learn to infer statistics from data. At meta-train time, the model learns to acquire the ability to generate statistics only from the support set and at meta-test time we directly apply the model to infer statistics for new tasks.

Batch Normalization for Domain Adaptation and Domain Generalization Domain adaption suffers from a distribution shift between source and target domains, which makes it sub-optimal to directly apply batch normalization (Bilen & Vedaldi, 2017). Learning domain-specific batch normalization has been explored (Chang et al., 2019; Wang et al., 2019). Wang et al. (2019) introduced transferable normalization, TransNorm, which normalizes the feature representations from source and target domain separately using domain-specific statistics. Along a similar vein, Chang et al. (2019) proposed a domain-specific batch normalization layer, which consists of two branches, each in charge of a single domain exclusively. The hope is that, through the normalization, the feature representation will become domain invariant. Nevertheless, these normalization methods are specifically designed for domain adaptation tasks, where data from target domains are available, though often unlabelled. This makes them inapplicable to domain generalization tasks where data from target domains are inaccessible at training time. Seo et al. (2019) proposed learning to optimize domain specific normalization for domain generalization tasks. Under the meta-learning settings, a mixture of different normalization techniques is optimized for each domain, where the mixture weights are learned specifically for different domains. Instead of combining different normalization statistics, MetaNorm learns from data to generate adaptive statistics specific to each domain. Moreover, we introduce an even more challenging setting, i.e., few-shot domain generalization, which combines the challenges of few-shot classification and domain generalization.

Table 1: **Effect of KL term** in MetaNorm for few-shot classification with MAML (Finn & Levine, 2018) on *mini*ImageNet and domain generalization on PACS with ResNet-18. More few-shot classification results with ProtoNets (Snell et al., 2017) and VERSA (Gordon et al., 2019), as well as domain generalization results on Office-Home are provided in the appendix. In all cases the KL term is crucial.

MetaNorm	**Few-shot classification**		**Domain generalization**				
	5-way, 1-shot	5-way, 5-shot	*Photo*	*Art*	*Cartoon*	*Sketch*	***Mean***
w/o KL	34.3 ± 1.5	50.7 ± 0.8	88.96	71.25	65.37	69.28	73.72
w/ KL	$\mathbf{46.8} \pm \mathbf{1.6}$	$\mathbf{60.1} \pm \mathbf{0.8}$	**95.99**	**85.01**	**78.63**	**83.17**	**85.70**

Figure 2: **Impact of target set size.** The performance increases for larger target sets and plateaus at around 125 for few-shot classification and around 256 for domain generalization. MetaNorm generates proper normalization statistics with a reasonable batch size.

4 EXPERIMENTAL RESULTS

We conduct an extensive set of experiments on a total of 17 datasets containing more than 15 million images. All details about dataset and implementation settings are provided in the appendix. The code will be publicly released.

Effect of KL Term We first conduct ablation studies that measure the effectiveness of MetaNorm. The key of MetaNorm is the introduced KL term for learning to learn statistics. We test the performance of MetaNorm without the KL term by directly using the statistics generated from data. In this case, we also use the hypernetworks to generate the moments, μ and σ by simply removing the KL term in the objective function. In Table 1 we present results for few-shot classification on *mini*ImageNet (Vinyals et al., 2016) and for domain generalization on PACS (Li et al., 2017a). The performance of MetaNorm without KL degrades significantly. This is expected, as without the KL term the generation process of normalization statistics lacks direct supervision from the target distribution, resulting in improper statistics.

Impact of Target Set Size The other key parameter in MetaNorm is the size of the target set; that is, the number $|\mathcal{Q}|$ of samples in the query set (in few-shot classification) and the number $|\mathcal{D}^s|$ of samples in each domain (in domain generalization). This parameter is important when learning normalization statistics because we use the statistics generated by the target set as the 'ground truth'. We evaluate its impact on the performance of MetaNorm in Fig. 2. The performance rises as the size of the target set increases and plateaus at a reasonable size. In the few-shot setting, the performance reaches its peak at a size of about 125, while in the domain generalization setting, the performance plateaus at a size of about 128. This demonstrates that we are able to generate proper statistics with the mini-batch gradient descent optimization.

Sensitivity to Algorithm We evaluate MetaNorm using the MAML (Finn et al., 2017), ProtoNets (Snell et al., 2017) and VERSA (Gordon et al., 2019) algorithms, which are representative gradient,

Table 2: **Sensitivity to Algorithm.** Few-shot results on *mini*ImageNet using different algorithms. Results on Omniglot are provided in the appendix. MetaNorm consistently outperforms both transductive and non-transductive normalization approaches, regardless of the meta-learning algorithm.

	ProtoNets		MAML		VERSA	
	5-way, 1-shot	5-way, 5-shot	5-way, 1-shot	5-way, 5-shot	5-way, 1-shot	5-way, 5-shot
TBN	45.9 ± 0.6	65.5 ± 0.9	45.5 ± 1.8	59.7 ± 0.9	53.4 ± 1.8	67.3 ± 0.9
example	43.9 ± 1.9	60.1 ± 0.8	26.9 ± 1.5	30.3 ± 0.7	44.1 ± 1.7	60.3 ± 0.7
class	43.1 ± 1.8	59.8 ± 0.8	26.9 ± 1.5	27.2 ± 0.6	43.8 ± 1.8	59.7 ± 0.6
w/o BN	44.1 ± 1.5	60.1 ± 0.6	34.7 ± 1.5	51.3 ± 0.8	48.1 ± 1.5	63.8 ± 0.6
CBN	47.8 ± 0.6	66.7 ± 0.5	20.1 ± 0.0	20.2 ± 0.2	45.7 ± 0.4	60.7 ± 0.5
RN	39.7 ± 0.5	63.1 ± 0.5	40.7 ± 1.7	57.6 ± 0.9	-	-
MetaBN	42.6 ± 0.6	64.6 ± 0.5	41.6 ± 1.6	58.6 ± 0.9	50.1 ± 1.7	65.8 ± 0.9
TaskNorm-L	47.5 ± 0.6	65.3 ± 0.5	42.0 ± 1.7	58.1 ± 0.9	52.1 ± 1.6	66.1 ± 0.7
TaskNorm-I	43.2 ± 0.6	63.9 ± 0.5	42.4 ± 1.7	58.7 ± 0.9	52.9 ± 1.7	66.5 ± 0.8
MetaNorm	$\mathbf{48.1} \pm \mathbf{1.6}$	$\mathbf{65.9} \pm \mathbf{0.9}$	$\mathbf{46.8} \pm \mathbf{1.6}$	$\mathbf{60.1} \pm \mathbf{0.8}$	$\mathbf{53.7} \pm \mathbf{1.6}$	$\mathbf{68.1} \pm \mathbf{0.8}$

metric and model based meta-learning approaches for few-shot classification. These experiments are conducted on the Omniglot and *mini*ImageNet datasets under different settings. The comparison results on *mini*ImageNet are summarized in Table 2 and the results on Omniglot are provided in the appendix. Compared to all three meta-learning approaches under all settings, MetaNorm consistently achieves the best performance and outperforms both transductive and non-transductive normalization methods. Being non-transductive, TaskNorm can achieve impressive performance on all the tasks, but under-performs compared to transductive batch normalization. MetaNorm outperforms the transductive batch normalization, especially under the 5-way-1-shot setting, which is challenging since only a few examples are available for generating statistics. This demonstrates the benefit of leveraging meta-learning by MetaNorm for batch normalization. We conclude that MetaNorm is general and serves as a plug-and-play module for existing meta-learning models to improve their performance.

Sensitivity to Dataset We evaluate MetaNorm on a demanding few-shot classification challenge called Meta-Dataset (Triantafillou et al., 2020), which is composed of thirteen image classification datasets (eight for training, five testing). To compare with previous work, we perform experiments with ProtoNets and report the results in Table 3. All thirteen per-dataset results can be found in the appendix. MetaNorm achieves the best overall performance in terms of average rank, with highest accuracy on eight of the thirteen datasets. MetaNorm outperforms the transductive batch normalization on all the 13 datasets. It achieves comparable performance with transductive batch normalization on Omniglot and MNIST, which are relatively less challenging. Moreover, MetaNorm performs better than TaskNorm on seven of the thirteen datasets. We conclude that MetaNorm is effective, outperforming alternative normalizations for most datasets.

Table 3: **Sensitivity to Dataset.** Few-shot classification on Meta-Dataset using ProtoNets. MetaNorm performs best overall.

	Wins	Rank
TBN	–	4.81
CBN	–	9.11
BRN	–	6.23
LN	2	8.19
IN	–	10.61
RN	–	4.73
MetaBN	–	4.88
TaskNorm-r	–	7.88
TaskNorm-L	–	4.19
TaskNorm-I	3	3.01
MetaNorm	**8**	**2.35**

Sensitivity to Domains For this experiment we adopt two widely-used benchmarks for domain generalization of visual object recognition, i.e., PACS (Li et al., 2017a) and Office-Home (Venkateswara et al., 2017). Detailed descriptions on the experimental settings and implementations are provided in the appendix. For fair comparison with prior methods (Balaji et al., 2018; Li et al., 2018b; Seo et al., 2019), we employ ResNet-18 as the backbone network in all experiments. As shown in Table 4, MetaNorm achieves the best performance on PACS and Office in terms of average accuracy. On PACS, MetaNorm consistently outperforms other normalization approaches including domain-specific normalization (Seo et al., 2019), on all four domains. It is worth mentioning that the baseline normalization uses the statistics from the source domains for the batch normalization of the target domain. As expected, the baseline method produces relatively poor performance on most domains,

Table 4: **Sensitivity to Domains.** Performance comparison on domain generalization. MetaNorm consistently achieves the best performance among all normalization methods.

	PACS					Office-Home				
	Photo	*Art*	*Cartoon*	*Sketch*	***Mean***	*Art*	*Clipart*	*Product*	*Real-World*	***Mean***
Baseline	95.87	78.47	70.41	70.68	78.86	58.71	44.20	71.75	73.19	61.96
IBN (Pan et al., 2018)	92.04	75.29	72.95	77.42	79.43	55.41	44.82	68.28	71.95	60.09
DSBN (Chang et al., 2019)	95.51	78.61	66.17	70.15	77.61	59.04	45.02	72.67	71.98	62.18
SN (Luo et al., 2018a)	93.47	82.50	76.80	80.77	83.38	54.10	44.97	64.54	71.40	58.75
DSON (Seo et al., 2019)	95.87	84.67	77.65	82.23	85.11	59.37	45.70	71.84	74.68	62.90
MetaNorm	**95.99**	**85.01**	**78.63**	**83.17**	**85.70**	**59.77**	**45.98**	**73.13**	**75.29**	**63.55**

since the source domains cannot provide proper statistics for target domains due to the distribution shift. We conclude that MetaNorm is effective for domain generalization.

Few-Shot Domain Generalization   In our final experiment, we adopt the DomainNet dataset (Peng et al., 2019) and introduce a new, more challenging setting to evaluate the performance for few-shot domain generalization. Detailed descriptions on the dataset and experimental settings are provided in the appendix. We conduct the experiments with the MAML and ProtoNets algorithms under both 5-way 1-shot and 5-way 5-shot settings, and the results are reported in Table 5. We implement transductive batch normalization, MetaBN and the variants of TaskNorm for direct comparison. Under both settings, our MetaNorm produces the best performance and surpasses the transductive batch normalization by large margins performances of up to 4.0% on the challenging 5-way 1-shot setting with MAML. MetaNorm also achieves better than the non-transductive TaskNorm approaches. At the same time, with ProtoNet our MetaNorm again consistently delievers the best performance and surpasses both transductive and non-transductive normalizations, The performance on the challenging few-shot domain generalization scenario with different meta-learning algorithms again demonstrates the effectiveness of MetaNorm in handling the challenges of batch normalization for small batches *and* across domains.

Table 5: **Few-Shot Domain Generalization.** Comparison with different normalizations using MAML and ProtoNets on the Few-shot DomainNet dataset (see appendix). Reported results use "*Painting*" as the target domain. MetaNorm consistently achieves the best performance.

	MAML		ProtoNets	
	5-way, 1-shot	5-way, 5-shot	5-way, 1-shot	5-way, 5-shot
TBN	28.7 ± 1.8	49.3 ± 0.8	27.9 ± 1.8	47.1 ± 0.8
w/o BN	23.5 ± 1.7	45.4 ± 0.7	23.8 ± 1.8	45.9 ± 0.7
CBN	20.0 ± 0.0	20.1 ± 0.2	28.4 ± 1.8	47.9 ± 0.7
MetaBN	24.7 ± 1.6	46.1 ± 0.8	25.1 ± 1.8	46.1 ± 0.8
TaskNorm-L	26.9 ± 1.7	47.4 ± 0.8	29.5 ± 1.6	48.3 ± 0.8
TaskNorm-I	27.5 ± 1.6	48.8 ± 0.6	26.8 ± 1.8	46.9 ± 0.7
MetaNorm	$\mathbf{32.7} \pm \mathbf{1.7}$	$\mathbf{51.9} \pm \mathbf{0.9}$	$\mathbf{30.7} \pm \mathbf{1.8}$	$\mathbf{49.1} \pm \mathbf{0.9}$

5 CONCLUSION

In this paper we present MetaNorm, a meta-learning based batch normalization. MetaNorm tackles the challenging scenarios where the batch size is too small to produce sufficient statistics or when training statistics are not directly applicable to test data due to a domain shift. MetaNorm learns to learn adaptive statistics that are specific to tasks or domains. It is generic and model-agnostic, which enables it to be used with various meta-learning algorithms for different applications. We evaluate MetaNorm on two well-known existing tasks, i.e., few-shot classification and domain generalization, and we also introduce the challenging evaluation scenario of few-shot domain generalization that combines small batch and distribution shift problems. An extensive evaluation on 17 datasets reveals that MetaNorm consistently achieves excellent performance compared to other normalization approaches, verifying its effectiveness as a new meta-learning based batch normalization approach.

REFERENCES

Jimmy Lei Ba, Jamie Ryan Kiros, and Geoffrey E Hinton. Layer normalization. *arXiv preprint arXiv:1607.06450*, 2016. 1

Yogesh Balaji, Swami Sankaranarayanan, and Rama Chellappa. Metareg: Towards domain generalization using meta-regularization. In *Advances in Neural Information Processing Systems*, pp. 998–1008, 2018. 2, 3, 7

Hakan Bilen and Andrea Vedaldi. Universal representations: The missing link between faces, text, planktons, and cat breeds. *arXiv preprint arXiv:1701.07275*, 2017. 5

Nils Bjorck, Carla P Gomes, Bart Selman, and Kilian Q Weinberger. Understanding batch normalization. In *Advances in Neural Information Processing Systems*, pp. 7694–7705, 2018. 1

John Bronskill, Jonathan Gordon, James Requeima, Sebastian Nowozin, and Richard Turner. Tasknorm: Rethinking batch normalization for meta-learning. In *International Conference on Machine Learning*, pp. 4683–4694. 2020. 1, 2, 5

Fabio Maria Carlucci, Antonio D'Innocente, Silvia Bucci, Barbara Caputo, and Tatiana Tommasi. Domain generalization by solving jigsaw puzzles. In *IEEE Conference on Computer Vision and Pattern Recognition*, 2019. 13

Woong-Gi Chang, Tackgeun You, Seonguk Seo, Suha Kwak, and Bohyung Han. Domain-specific batch normalization for unsupervised domain adaptation. In *IEEE Conference on Computer Vision and Pattern Recognition*, pp. 7354–7362, 2019. 2, 5, 8

M. Cimpoi, S. Maji, I. Kokkinos, S. Mohamed, , and A. Vedaldi. Describing textures in the wild. In *IEEE Conference on Computer Vision and Pattern Recognition*, 2014. 13

Chelsea Finn and Sergey Levine. Meta-learning and universality: Deep representations and gradient descent can approximate any learning algorithm. In *International Conference on Learning Representations*, 2018. 6

Chelsea Finn, Pieter Abbeel, and Sergey Levine. Model-agnostic meta-learning for fast adaptation of deep networks. In *International Conference on Machine Learning*, pp. 1126–1135, 2017. 1, 5, 6

Jonathan Gordon, John Bronskill, Matthias Bauer, Sebastian Nowozin, and Richard Turner. Meta-learning probabilistic inference for prediction. In *International Conference on Learning Representations*, 2019. 1, 5, 6, 15

Sebastian Houben, Johannes Stallkamp, Jan Salmen, Marc Schlipsing, and Christian Igel. Detection of traffic signs in real-world images: The german traffic sign detection benchmark. In *International joint conference on neural networks*, pp. 1–8, 2013. 13

Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *International Conference on Machine Learning*, pp. 448–456, 2015. 1, 2

Songhao Jia, Ding-Jie Chen, and Hwann-Tzong Chen. Instance-level meta normalization. In *IEEE Conference on Computer Vision and Pattern Recognition*, pp. 4865–4873, 2019. 1

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. In *International Conference on Learning Representations*, 2014. 2

Brenden M Lake, Ruslan Salakhutdinov, and Joshua B Tenenbaum. Human-level concept learning through probabilistic program induction. *Science*, 350(6266):1332–1338, 2015. 13

Da Li, Yongxin Yang, Yi-Zhe Song, and Timothy M Hospedales. Deeper, broader and artier domain generalization. In *IEEE International Conference on Computer Vision*, pp. 5542–5550, 2017a. 2, 6, 7, 13

Da Li, Yongxin Yang, Yi-Zhe Song, and Timothy M Hospedales. Learning to generalize: Meta-learning for domain generalization. *arXiv preprint arXiv:1710.03463*, 2017b. 2

Da Li, Yongxin Yang, Yi-Zhe Song, and Timothy M Hospedales. Learning to generalize: Meta-learning for domain generalization. In *Thirty-Second AAAI Conference on Artificial Intelligence*, 2018a. 3

Haoliang Li, Sinno Jialin Pan, Shiqi Wang, and Alex C Kot. Domain generalization with adversarial feature learning. In *IEEE Conference on Computer Vision and Pattern Recognition*, pp. 5400–5409, 2018b. 7, 13

Yiying Li, Yongxin Yang, Wei Zhou, and Timothy M Hospedales. Feature-critic networks for heterogeneous domain generalization. In *International Conference on Machine Learning*, 2019. 3

Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C Lawrence Zitnick. Microsoft coco: Common objects in context. In *European conference on computer vision*, pp. 740–755, 2014. 13

Ping Luo, Jiamin Ren, Zhanglin Peng, Ruimao Zhang, and Jingyu Li. Differentiable learning-to-normalize via switchable normalization. *arXiv preprint arXiv:1806.10779*, 2018a. 1, 8

Ping Luo, Xinjiang Wang, Wenqi Shao, and Zhanglin Peng. Towards understanding regularization in batch normalization. *arXiv preprint arXiv:1809.00846*, 2018b. 1

S. Maji, J. Kannala, E. Rahtu, M. Blaschko, and A. Vedaldi. Fine-grained visual classification of aircraft. Technical report, 2013. 13

Krikamol Muandet, David Balduzzi, and Bernhard Schölkopf. Domain generalization via invariant feature representation. In *International Conference on Machine Learning*, pp. 10–18, 2013. 2

Alex Nichol, Joshua Achiam, and John Schulman. On first-order meta-learning algorithms. *arXiv preprint arXiv:1803.02999*, 2018. 1

Maria-Elena Nilsback and Andrew Zisserman. Automated flower classification over a large number of classes. In *Indian Conference on Computer Vision, Graphics & Image Processing*, pp. 722–729, 2008. 13

Xingang Pan, Ping Luo, Jianping Shi, and Xiaoou Tang. Two at once: Enhancing learning and generalization capacities via ibn-net. In *European Conference on Computer Vision*, pp. 464–479, 2018. 8

Xingchao Peng, Qinxun Bai, Xide Xia, Zijun Huang, Kate Saenko, and Bo Wang. Moment matching for multi-source domain adaptation. In *IEEE International Conference on Computer Vision*, pp. 1406–1415, 2019. 8, 13

Sachin Ravi and Hugo Larochelle. Optimization as a model for few-shot learning. In *International Conference on Learning Representations*, 2017. 13

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, Alexander Berg, and Li Fei-Fei. Imagenet large scale visual recognition challenge. *International journal of computer vision*, 115(3):211–252, 2015. 13

Seonguk Seo, Yumin Suh, Dongwan Kim, Jongwoo Han, and Bohyung Han. Learning to optimize domain specific normalization for domain generalization. *arXiv preprint arXiv:1907.04275*, 2019. 2, 5, 7, 8

Jake Snell, Kevin Swersky, and Richard Zemel. Prototypical networks for few-shot learning. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, pp. 4077–4087. 2017. 1, 5, 6, 15

Cecilia Summers and Michael J Dinneen. Four things everyone should know to improve batch normalization. In *International Conference on Learning Representations*, 2020. 1

Eleni Triantafillou, Tyler Zhu, Vincent Dumoulin, Pascal Lamblin, Kelvin Xu, Ross Goroshin, Carles Gelada, Kevin Swersky, Pierre-Antoine Manzagol, and Hugo Larochelle. Code for "Meta-dataset: A dataset of datasets for learning to learn from few examples", 2019. 5

Eleni Triantafillou, Tyler Zhu, Vincent Dumoulin, Pascal Lamblin, Utku Evci, Kelvin Xu, Ross Goroshin, Carles Gelada, Kevin Swersky, Pierre-Antoine Manzagol, and Hugo Larochelle. Meta-dataset: A dataset of datasets for learning to learn from few examples. In *International Conference on Learning Representations*, 2020. 7, 13

Dmitry Ulyanov, Andrea Vedaldi, and Victor Lempitsky. Instance normalization: The missing ingredient for fast stylization. *arXiv preprint arXiv:1607.08022*, 2016. 1

Hemanth Venkateswara, Jose Eusebio, Shayok Chakraborty, and Sethuraman Panchanathan. Deep hashing network for unsupervised domain adaptation. In *IEEE Conference on Computer Vision and Pattern Recognition*, 2017. 7, 13

Oriol Vinyals, Charles Blundell, Timothy Lillicrap, koray kavukcuoglu, and Daan Wierstra. Matching networks for one shot learning. In *Advances in Neural Information Processing Systems*, pp. 3630–3638. 2016. 2, 6, 12, 13

C. Wah, S. Branson, P. Welinder, P. Perona, and S. Belongie. The Caltech-UCSD Birds-200-2011 Dataset. Technical report, 2011. 13

Ximei Wang, Ying Jin, Mingsheng Long, Jianmin Wang, and Michael I Jordan. Transferable normalization: Towards improving transferability of deep neural networks. In *Advances in Neural Information Processing Systems*, pp. 1953–1963, 2019. 2, 5

Yuxin Wu and Kaiming He. Group normalization. In *European conference on computer vision*, pp. 3–19, 2018. 1, 5

Greg Yang, Jeffrey Pennington, Vinay Rao, Jascha Sohl-Dickstein, and Samuel S Schoenholz. A mean field theory of batch normalization. *arXiv preprint arXiv:1902.08129*, 2019. 1

A   ALGORITHMS DESCRIPTIONS

In this Appendix we provide the detailed MetaNorm algorithm descriptions to conduct batch normalization for few-shot classification (Algorithm 1), domain generalization (Algorithm 2) and few-shot domain generalization (Algorithm 3).

Algorithm 1 MetaNorm for Few-Shot Classification

Meta-train: Input Values of a over support set $\mathbf{a}_{S,i}$ and query set $\mathbf{a}_{Q,i}$;
$\gamma, \beta \leftarrow$ Initialize parameters.
$\mu_S = \frac{1}{|\mathcal{S}|} \sum\limits_{i=1}^{|\mathcal{S}|} f_\mu^\ell(\mathbf{a}_{S,i}); \mu_Q = \frac{1}{|\mathcal{Q}|} \sum\limits_{i=1}^{|\mathcal{Q}|} f_\mu^\ell(\mathbf{a}_{Q,i});$
$\sigma_S = \frac{1}{|\mathcal{S}|} \sum\limits_{i=1}^{|\mathcal{S}|} f_\sigma^\ell\big((\mathbf{a}_{S,i} - \mu_S)^2\big); \sigma_Q = \frac{1}{|\mathcal{Q}|} \sum\limits_{i=1}^{|\mathcal{Q}|} f_\sigma^\ell\big((\mathbf{a}_{Q,i} - \mu_Q)^2\big);$
$a'_{S,i} = \gamma\left(\frac{a_{S,i}-\mu_S}{\sqrt{\sigma_S^2+\epsilon}}\right) + \beta; a'_{Q,i} = \gamma\left(\frac{a_{Q,i}-\mu_S}{\sqrt{\sigma_S^2+\epsilon}}\right) + \beta;$
$\mathcal{L}_{\mathrm{KL}} = D_{\mathrm{KL}}\big[\mathcal{N}(\mu_\mathcal{S}, \sigma_\mathcal{S})||\mathcal{N}(\mu_\mathcal{Q}, \sigma_\mathcal{Q})\big]$
return $a'_{S,i} = \textbf{MetaNorm}(\mathbf{a}_{S,i}); a'_{Q,i} = \textbf{MetaNorm}(\mathbf{a}_{Q,i}); \mathcal{L}_{KL}$

Meta-test: Input Values of a over support set $\mathbf{a}_{S,i}$ and query set $\mathbf{a}_{Q,i}$;
$\mu_S = \frac{1}{|\mathcal{S}|} \sum\limits_{i=1}^{|\mathcal{S}|} f_\mu^\ell(\mathbf{a}_{S,i});$
$\sigma_S = \frac{1}{|\mathcal{S}|} \sum\limits_{i=1}^{|\mathcal{S}|} f_\sigma^\ell\big((\mathbf{a}_{S,i} - \mu_S)^2\big);$
$a'_{Q,i} = \gamma\left(\frac{\mathbf{a}_{Q,i}-\mu_S}{\sqrt{\sigma_S^2+\epsilon}}\right) + \beta;$
return $a'_{Q,i} = \textbf{MetaNorm}(a_{Q,i})$

Algorithm 2 MetaNorm for Domain Generalization

Train: Input Values of a over meta-train domain $\mathbf{a}_{S,i}$ and meta-test domain $\mathbf{a}_{T,i}$;
$\gamma, \beta \leftarrow$ Initialize parameters.
$\mu_{S,i} = f_\mu^\ell(\mathbf{a}_{S,i}); \mu_S = \frac{1}{|\mathcal{S}|} \sum\limits_{i=1}^{|\mathcal{S}|} f_\mu^\ell(\mathbf{a}_{S,i});$
$\sigma_{S,i} = f_\sigma^\ell\big((\mathbf{a}_{S,i} - \mu_{S,i})^2\big); \sigma_S = \frac{1}{|\mathcal{S}|} \sum\limits_{i=1}^{|\mathcal{S}|} f_\sigma^\ell\big((\mathbf{a}_{S,i} - \mu_S)^2\big);$
$\mu_{T,i} = f_\mu^\ell(\mathbf{a}_{T,i}); \sigma_{T,i} = f_\sigma^\ell\big((\mathbf{a}_{T,i} - \mu_{T,i})^2\big);$
$a'_{T,i} = \gamma\left(\frac{\mathbf{a}_{T,i}-\mu_{T,i}}{\sqrt{\sigma_{T,i}^2+\epsilon}}\right) + \beta;$
$\mathcal{L}_{KL} = D_{\mathrm{KL}}\big[\mathcal{N}(\mu_{\mathcal{S},\rangle}, \sigma_{\mathcal{S},\rangle})||\mathcal{N}(\mu_\mathcal{S}, \sigma_\mathcal{S})\big]$
return $a'_{T,i} = \textbf{MetaNorm}(a_{T,i}); \mathcal{L}_{\mathrm{KL}}$

Test: Input values of a over test domain $\mathbf{a}_i$;
$\mu_i = f_\mu^\ell(\mathbf{a}_i);$
$\sigma_i = f_\sigma^\ell\big((\mathbf{a}_i - \mu_i)^2\big);$
$a'_i = \gamma\left(\frac{\mathbf{a}_i-\mu_i}{\sqrt{\sigma_i^2+\epsilon}}\right) + \beta;$
return $a'_i = \textbf{MetaNorm}(a_i)$

B   DATASETS

We conduct an extensive set of experiments on a total of 17 datasets containing more than 15 million images. All dataset details and settings are provided in this Appendix.

***mini*ImageNet**. The *mini*ImageNet is originally proposed in (Vinyals et al., 2016) and has been widely used for evaluating few-shot learning algorithms. It consists of 60,000 color images from 100

Algorithm 3 MetaNorm for Few-Shot Domain Generalization

Meta-train: Input Values of a over meta-train domain set $\mathbf{a}_{S,i}$ and meta-test domain set $\mathbf{a}_{Q,i}$; $\gamma, \beta \leftarrow$ Initialize parameters.

$\mu_S = \frac{1}{|\mathcal{S}|} \sum\limits_{i=1}^{|\mathcal{S}|} f^\ell_\mu(\mathbf{a}_{S,i})$; $\mu_Q = \frac{1}{|\mathcal{Q}|} \sum\limits_{i=1}^{|\mathcal{Q}|} f^\ell_\mu(\mathbf{a}_{Q,i})$;

$\sigma_S = \frac{1}{|\mathcal{S}|} \sum\limits_{i=1}^{|\mathcal{S}|} f^\ell_\sigma\big((\mathbf{a}_{S,i} - \mu_S)^2\big)$; $\sigma_Q = \frac{1}{|\mathcal{Q}|} \sum\limits_{i=1}^{|\mathcal{Q}|} f^\ell_\sigma\big((\mathbf{a}_{Q,i} - \mu_Q)^2\big)$;

$a'_{S,i} = \gamma \left(\frac{a_{S,i} - \mu_S}{\sqrt{\sigma_S^2 + \epsilon}} \right) + \beta$; $a'_{Q,i} = \gamma \left(\frac{a_{Q,i} - \mu_S}{\sqrt{\sigma_S^2 + \epsilon}} \right) + \beta$;

$\mathcal{L}_{\mathrm{KL}} = D_{\mathrm{KL}}\big[\mathcal{N}(\mu_{\mathcal{S}}, \sigma_{\mathcal{S}}) || \mathcal{N}(\mu_{\mathcal{Q}}, \sigma_{\mathcal{Q}})\big]$

return $a'_{S,i} = \textbf{MetaNorm}(\mathbf{a}_{S,i})$; $a'_{Q,i} = \textbf{MetaNorm}(\mathbf{a}_{Q,i})$; $\mathcal{L}_{KL}$

Meta-test: Input Values of a over support set $\mathbf{a}_{S,i}$ and query set $\mathbf{a}_{Q,i}$;

$\mu_S = \frac{1}{|\mathcal{S}|} \sum\limits_{i=1}^{|\mathcal{S}|} f^\ell_\mu(\mathbf{a}_{S,i})$;

$\sigma_S = \frac{1}{|\mathcal{S}|} \sum\limits_{i=1}^{|\mathcal{S}|} f^\ell_\sigma\big((\mathbf{a}_{S,i} - \mu_S)^2\big)$;

$a'_{Q,i} = \gamma \left(\frac{\mathbf{a}_{Q,i} - \mu_S}{\sqrt{\sigma_S^2 + \epsilon}} \right) + \beta$;

return $a'_{Q,i} = \textbf{MetaNorm}(a_{Q,i})$

---

classes with 600 examples per class. The images have dimensions of 84×84 pixels. We follow the train/val/ test split introduced in (Ravi & Larochelle, 2017), which uses 64 classes for meta-training, 16 classes for meta-validation, and the remaining 20 classes for meta-testing.

Omniglot. Omniglot (Lake et al., 2015) is a few-shot learning dataset consisting of 1,623 handwritten characters (each with 20 instances) derived from 50 alphabets. We follow the pre-processing and training procedure defined in (Vinyals et al., 2016). We resize images to 28×28. The training, validation and test sets consist of a random split of 1,100, 100, and 423 characters.

PACS (Li et al., 2017a) contains a total of 9,991 images of the size 224×224 from 4 domains, i.e., *photo*, *art-painting*, *cartoon* and *sketch*, which demonstrate huge domain gaps. Images are from 7 object classes, i.e., *dog*, *elephant*, *giraffe*, *guitar*, *horse*, *house*, and *person*. We follow the "leave-one-out" protocol in (Li et al., 2017a; 2018b; Carlucci et al., 2019), where the model is trained on any three of the four domains, which we call source domains, and tested on the last (target) domain. The train-val-test splits are the same as in (Li et al., 2017a).

Office-Home (Venkateswara et al., 2017) also has 4 domains: *art*, *product*, *clipart* and *real-world*. For each domain, the dataset contains images of 65 object categories found typically in Office and Home settings. We use the same experimental protocol as for PACS.

DomainNet (Peng et al., 2019) contains 6 distinct domains, i.e., *clipart*, *infograph*, *painting*, *quickdraw*, *real*, and *sketch* for 345 categories. The categories are from 24 divisions, which are:*Furniture*, *Mammal*, *Tool*, *Cloth*, *Electricity*, *Building*, *Office*, *Human Baby*, *Road Transportation*, *Food*, *Nature*, *Cold Blooded*, *Music*, *Fruit*, *Sport*, *Tree*, *Bird*, *Vegetable*, *Shape*, *Kitchen*, *Water Transportation*, *Sky Transportation*, *Insect*, *Others*.

Meta-Dataset (Triantafillou et al., 2020) is composed of ten (eight train, two test) existing image classification datasets. These are: *ILSVRC-2012* (ImageNet, (Russakovsky et al., 2015)), *Omniglot* (Lake et al., 2015), *Aircraft* (Maji et al., 2013), *CUB-200-2011* (Birds, (Wah et al., 2011)), *Describable Textures* (Cimpoi et al., 2014), *Quick Draw*, *Fungi*, *VGG Flowr* (Nilsback & Zisserman, 2008), *Traffic Signs* (Houben et al., 2013) and *MSCOCO* (Lin et al., 2014). Each episode generated in Meta-Dataset uses classes from a single dataset. Two of these datasets, *Traffic Signs* and *MSCOCO*, are fully reserved for evaluation, it means no classes from these sets participate in the training set. The remaining ones contribute some classes to each of training, validation and test splits of classes. There are about 14 million images in total in Meta-Dataset. The challenge constructs few-shot learning tasks by drawing from the following distribution. First, one of the datasets is sampled uniformly; second, the "way" and "shot" are sampled randomly according to a fixed procedure; third, the classes

and context / target instances are sampled. As a result, the context size D^τ will vary in the range between 5 and 500 for each task. In the meta-test phase, the identity of the original dataset is not revealed and tasks must be treated independently (i.e. no information can be transferred between them). The meta-training set comprises a disjoint and dissimilar set of classes from those used for meta-test.

C FEW-SHOT DOMAINNET

To construct Few-shot DomainNet, we chose 200 random classes from DomainNet and used 140 for training, 20 for validation and the last 40 for testing. Note that the last 40 class objects were never seen during training. It consisting of 200, 000 colour images of size 84×84 with 100 classes, each having 1,000 examples. Please see the Table 6, Table 7 and Table 8 for training, validation, and test classes.

Table 6: **Training classes of Few-shot DomainNet**

Furniture: bathtub, ceiling fan, couch, fence, hot tub, mailbox
Mammal: tiger, rhinoceros, bat, cat, lion, panda
Tool: anvil, basket, broom, sword, pliers
Cloth: belt, camouflage, eyeglasses, crown, bowtie
Electricity: calculator, computer, camera, cooler, dishwasher
Building: bridge, jail, pool, tent, castle
Office: alarm clock, binoculars, backpack, book, bandage
Human Body: arm, ear, face, beard, elbow, finger, brain, eye, foot, knee
Road Transportation: ambulance, bus motorbike, bicycle, train
Food: birthday cake, cookie, hot dog, peanut, sandwich, bread, donut, pizza, steak, lollipop
Nature: beach, lightning, ocean, river, sun, cloud, moon, rain, tornado
Cold Blooded: crab, frog, crocodile, lobster, fish, octopus, shark
Music: cello, guitar, saxophone, violin, clarinet, harp, trombone
Fruit: apple, banana, blackberry, blueberry, grapes, pear
Sport: baseball, baseball bat, basketball, snorkel, yoga, tennis racquet
Tree: bush, grass, cactus, tree, flower
Bird: bird, owl
Vegetable: asparagus, broccoli, carrot, mushroom, onion
Shape: circle, hexagon
Kitchen: fork, frying pan, hourglass, knife, lighter
Water Transportation: aircraft carrier, canoe, cruise ship, submarine
Sky Transportation: airplane, helicopter
Insect: ant, bee
Others: angel, cannon, dragon, mermaid, stop sign, snowman, feather

D IMPLEMENTATION DETAILS.

In the few-shot learning task, MAML and ProtoNets use a simple CNN containing 4 convolutional layers, each of which is a 3×3 convolution with 32 filters, followed by MetaNorm, a ReLU non-linearity, and finally a 2×2 max-pooling. VERSA uses a CNN containing 5 convolutional layers, each of which is a 3×3 convolution with 64 filters, followed by MetaNorm, a ReLU non-linearity, and finally a 2×2 max-pooling. In the domain generalization task, we rely on ResNet-18 as backbone

Table 7: **Validation classes of Few-shot DomainNet**

Furniture:stairs, ladder
Mammal:monkey
Tool: paint can
Cloth:purse, t-shirt
Electricity:radio
Building:pond
Office: nail
Human Body: skull, tooth
Road Transportation: firetruck
Food: -
Nature:star, hurricane
Cold Blooded:sea turtle
Music: -
Fruit: strawberry
Sport: hockey stick
Tree: -
Bird: penguin
Vegetable: -
Shape: -
Kitchen: wine bottle
Water Transportation: -
Sky Transportation: -
Insect: –
Others: teddy-bear

for fair comparison with previous work. Each convolutional layer is followed by MetaNorm. The hypernetwork is a 3-layer MLP with 128 units per layer and rectifier nonlinearities. All code will be released.

E   EXTRA RESULTS FOR EFFECT OF KL TERM

In this Appendix we consider extra results for the ablation on measuring the effect of the KL term. We report results for for few-shot classification on *mini*ImageNet with ProtoNets (Snell et al., 2017) and VERSA (Gordon et al., 2019) in Table 9. We also report domain generalization results on Office-Home in Table 10. In all cases the KL term is crucial.

F   SENSITIVITY TO ALGORITHM ON OMNIGLOT

The experiments on Omniglot for few-shot classification under the meta-learning settings of MAML, VERSA and ProtoNets are reported in Tables 11, 12 and 13. MetaNorm consistently outperforms both transductive and non-transductivenormalization approaches.

G   SENSITIVITY TO DATASET

The complete set of results for each of the thirteen datasets in Meta-Dataset are provided in Table 14.

Table 8: **Test classes of Few-shot DomainNet**

Furniture:teapot, toothpaste, stove, umbrella
Mammal:mouse,
Tool: bucket, paint can
Cloth:sweater, shoe, flip flops
Electricity:television, stereo, toaster, flashlight
Building:waterslide, garden
Office: map, clock, calendar, scissors
Human Body: finger, nose, toe
Road Transportation: bulldozer
Food: peanut
Nature: mountain, sun
Cold Blooded: lobster, scorpion
Music: harp
Fruit: pineapple
Sport: soccer ball, hockey stick
Tree: house plant, leaf
Bird: swan
Vegetable: string bean
Shape: squiggle
Kitchen: -
Water Transportation: -
Sky Transportation: -
Insect: --
Others: feather, snowman

Table 9: **Effect of KL term** in MetaNorm for few-shot classification on *mini*ImageNet with ProtoNets and VERSA.

	ProtoNets		VERSA	
MetaNorm	5-way, 1-shot	5-way, 5-shot	5-way, 1-shot	5-way, 5-shot
w/o KL	40.1 ± 1.6	58.7 ± 0.8	48.7 ± 1.6	64.3 ± 0.8
w/ KL	$\mathbf{48.1} \pm \mathbf{1.6}$	$\mathbf{65.9} \pm \mathbf{0.9}$	$\mathbf{53.7} \pm \mathbf{1.6}$	$\mathbf{68.1} \pm \mathbf{0.8}$

Table 10: **Effect of KL term** in MetaNorm for domain generalization on Office-Home.

	Office-Home				
MetaNorm	*Art*	*Clipart*	*Product*	*Real-World*	*Mean*
w/o KL	51.25	39.27	69.75	68.19	57.12
w/ KL	**59.77**	**45.98**	**73.13**	**75.29**	**63.55**

Table 11: **Sensitivity to Algorithm.** Few-shot results on Omniglot using MAML.

| | Omniglot | | | |
	5-way, 1-shot	5-way, 5-shot	20-way, 1-shot	20-way, 5-shot
TBN	98.4 ±0.7	99.2±0.2	90.9±0.5	96.6±0.2
example	21.6±1.3	22.0±0.5	3.7±0.2	5.5±0.2
class	21.6±1.3	23.2±0.5	3.7±0.2	14.5±0.3
w/o BN	92.6±0.9	90.7±0.1	84.3±0.4	91.7±0.2
CBN	20.1±0.0	20.0±0.0	5.0±0.0	5.0±0.0
RN	92.6±0.9	98.2±0.2	89.0±0.6	96.8±0.2
MetaBN	91.8±0.9	98.1±0.3	89.6±0.5	96.4±0.2
TaskNorm-L	94.0±0.8	98.0±0.3	89.6±0.5	96.4±0.2
TaskNorm-I	94.4±0.8	98.6±0.2	90.0±0.5	96.3±0.2
MetaNorm	**98.8±0.5**	**99.3±0.2**	**91.3±0.5**	**97.1±0.2**

Table 12: **Sensitivity to Algorithm.** Few-shot results on Omniglot using VERSA

| | Omniglot | | | |
	5-way, 1-shot	5-way, 5-shot	20-way, 1-shot	20-way, 5-shot
TBN	99.7±0.2	99.8±0.2	97.7±0.2	**98.8±0.1**
example	94.9±0.2	95.1±0.3	92.9±0.2	95.9±0.2
class	94.3±0.3	94.8±0.1	91.8±0.3	95.1±0.4
w/o BN	95.6±0.7	96.5±0.1	93.1±0.3	96.3±0.2
CBN	94.3±0.3	95.7±0.0	92.7±0.2	95.2±0.3
RN	-	-	-	-
MetaBN	96.7±0.3	98.1±0.3	95.8±0.2	97.1±0.2
TaskNorm-L	97.9±0.3	99.2±0.2	96.1±0.2	98.0±0.2
TaskNorm-I	98.3±0.2	99.5±0.2	96.7±0.2	98.1±0.1
MetaNorm	**99.8±0.1**	**99.9±0.1**	**97.9±0.5**	**98.8±0.2**

Table 13: **Sensitivity to Algorithm.** Few-shot results on Omniglot using ProtoNets

| | Omniglot | | | |
	5-way, 1-shot	5-way, 5-shot	20-way, 1-shot	20-way, 5-shot
TBN	98.4±0.2	99.6±0.2	94.5±0.2	98.6±0.1
example	98.4±0.2	99.5±0.2	94.3±0.2	98.5±0.1
class	98.4±0.2	99.3±0.2	94.2±0.2	98.4±0.1
w/o BN	94.6±0.7	95.5±0.1	91.7±0.3	94.3±0.2
CBN	98.5±0.2	99.6±0.1	94.5±0.2	98.6±0.1
RN	98.0±0.2	99.6±0.1	94.1±0.2	98.6±0.1
MetaBN	98.4±0.2	99.6±0.1	94.5±0.2	98.6±0.1
TaskNorm-L	98.6±0.2	99.6±0.1	95.0±0.2	98.7±0.1
TaskNorm-I	98.4±0.2	99.6±0.2	93.4±0.2	98.6±0.1
MetaNorm	**98.9±0.2**	**99.7±0.2**	**95.8±0.2**	**98.9±0.2**

Table 14: **Sensitivity to Dataset.** Few-shot classification results on Meta-Dataset using ProtoNets.

	ILSVRC	Omniglot	Aircraft	Birds	Textures	Quick Draw	Fungi	VGG Flower	Traffic Signs	MSCOCO	MNIST	CIFAR10	CIFAR100	Rank
TBN	**44.7±1.0**	**90.7±0.6**	83.3±0.6	69.6±0.9	61.2±0.7	75.0±0.8	46.4±1.0	83.1±0.6	64.0±0.8	38.2±1.0	93.4±0.4	64.7±0.8	48.0±1.1	4.81
CBN	43.6±1.0	77.5±1.1	77.0±0.7	67.5±0.9	57.7±0.7	62.1±1.0	43.6±1.0	82.3±0.6	59.5±0.8	36.6±1.0	86.5±0.6	57.3±0.8	43.1±1.0	9.11
BRN	43.0±1.0	89.1±0.7	**84.4±0.5**	69.0±0.9	58.0±0.7	74.3±0.8	46.5±1.0	84.5±0.6	65.7±0.8	38.4±1.0	91.9±0.4	60.1±0.8	43.9±1.0	6.23
LN	33.9±0.9	**90.8±0.6**	73.9±0.7	54.1±1.0	55.8±0.7	72.5±0.8	33.2±1.1	78.3±0.8	**69.1±0.7**	30.1±0.9	**94.0±0.4**	51.5±0.8	34.0±0.9	8.19
IN	32.5±0.9	83.4±0.8	75.0±0.6	50.2±1.0	45.3±0.7	70.8±0.8	29.8±1.0	69.4±0.8	60.7±0.8	27.7±0.9	87.4±0.5	50.5±0.8	32.1±1.0	10.61
RN	**45.1±1.0**	**90.8±0.6**	80.9±0.6	68.6±0.9	64.1±0.7	75.4±0.7	46.7±1.0	84.4±0.7	66.0±0.8	37.3±1.0	**93.9±0.4**	62.3±0.8	47.2±1.1	4.73
MetaBN	**44.2±1.0**	90.4±0.6	82.3±0.6	68.6±0.8	60.5±0.7	74.2±0.7	46.5±1.0	**86.0±0.6**	63.2±0.8	38.6±1.1	**93.9±0.4**	63.0±0.8	47.0±1.0	4.88
TaskNorm-r	42.7±1.0	88.6±0.7	79.6±0.6	64.2±0.9	60.8±0.7	73.2±0.8	42.3±1.1	81.1±0.7	64.9±0.8	35.4±1.0	92.5±0.4	61.4±0.8	45.2±1.0	7.88
TaskNorm-L	**45.1±1.1**	90.2±0.6	81.2±0.6	68.8±0.9	63.4±0.8	75.4±0.7	46.5±1.0	82.9±0.7	67.0±0.7	39.2±1.0	91.9±0.4	**66.9±0.8**	51.3±1.1	4.19
TaskNorm-I	**44.9±1.0**	90.6±0.6	**84.7±0.5**	71.0±0.9	65.9±0.7	77.5±0.7	49.6±1.1	83.2±0.6	65.8±0.7	38.5±1.0	93.3±0.4	**67.6±0.8**	50.0±1.0	3.07
MetaNorm	45.3±1.0	**90.8±0.5**	83.9±0.6	**70.6±0.8**	**66.7±0.6**	**77.6±0.6**	**51.1±0.6**	**86.3±0.7**	68.1±0.6	**39.7±0.9**	92.1±0.5	67.1±0.7	**52.7±0.9**	**2.35**