Rotation-Scale Equivariant Steerable Filters

Abstract

This is a great paper and it has a concise abstract.
Keywords: List of keywords, comma separated.

(a) Texture (b) CRAG (c) GlaS

Figure 1: **Model Size vs. Segmentation Performance vs. GPU Requirement.**
Our Rotation-Scale Equivariant Steerable Filter outperforms other filters. In
particular, RSESF achieves state-of-the-art mIoU but is much smaller and GPU
efficient. Details are in Table 2 and 4.

1. Introduction

This is where the content of your paper goes. Some random notes[1]:

- You should use LaTeX(Lamport, 1986).

- JMLR/PMLR uses natbib for references. For simplicity, here, \cite defaults to par-
  enthetical citations, i.e. \citep. You can of course also use \citet for textual
  citations.

- Eprints such as arXiv papers can of course be cited (Hinton et al., 2015), Hinton et al.
  (2015). We recomend using a @misc bibtex entry for these as shown in the sample
  bibliography.

- You should follow the guidelines provided by the conference.

---

1. Random footnote are discouraged

- Read through the JMLR template documentation for specific LaTeXusage questions.

- Note that the JMLR template provides many handy functionalities such as \figureref to refer to a figure, e.g. Figure **??**, \tableref to refer to a table, e.g. Table 3 and \equationref to refer to an equation, e.g. Equation (1).

Acknowledgments

Acknowledgments withheld.

References

Geoffrey Hinton, Oriol Vinyals, and Jeff Dean. Distilling the knowledge in a neural network. Eprint arXiv:1503.02531, 2015.

Leslie Lamport. *Latex: A Document Preparation System.* Addison-Wesley Longman Publishing Co., Inc., Boston, MA, USA, 1986. ISBN 0-201-15790-X.

(a) CNN (37.14) (b) SDCF (33.39) (c) SESN (31.66) (d) SEUNet (40.2)

(e) RDCF (30.78) (f) E2CNN (64.46) (g) RST-L (43.53) (h) RSESF (69.91)

(i)

Figure 2: Polar plots show model predictions as a function of the orientation and scale of the input.

Table 1: Segmentation performance for in distribution (ID) and out-of-distribution settings.

Filter Types	Year	In Distribution			Out-of-Distribution		
		GlaS	CRAG	Texture	GlaS	CRAG	Texture
CNN	2015	67.09	87.83	99.11	54.19	69.86	37.78
RDCF	2019	65.48	87.69	99.05	49.69	75.19	26.82
E(2)CNN [Dis]	2019	**68.31**	**89.73**	99.57	47.91	66.26	39.67
E(2)CNN [Con]	2019	65.90	82.87	**99.71**	59.16	55.07	54.37
SDCF	2022	66.87	88.63	99.16	47.41	**81.45**	28.03
SESN	2020	67.73	88.51	98.83	60.47	80.21	28.87
SEUNet	2022	67.15	87.63	98.55	59.87	78.73	32.82
RST	2022	65.88	83.41	95.92	50.63	72.52	30.19
RST-L	2022	67.82	87.94	99.25	56.33	71.90	40.87
ours	2022	66.53	88.16	98.00	**60.89**	79.69	**55.42**

Table 2: Segmentation performance for in distribution (ID) and out-of-distribution settings.

Channel Squeeze at the Last Layer	In Distribution			Out-of-Distribution		
	GlaS	CRAG	Texture	GlaS	CRAG	Texture
Pooling over R	**68.02**	**88.79**	75.58	60.81	**80.49**	30.89
Selecting R* over C	66.53	88.16	**98.00**	**60.89**	79.69	**55.42**
Selecting R^c & for each c	64.24	86.18	78.87	51.98	67.92	32.04

Table 3: Model comparison in terms of number of trainable parameters (Million), amount of GPU (GB) required during training, and the training time (seconds) per epoch (averaged over 70 epochs).

	CNN	RDCF	E2CNN [Dis]	E2CNN [Con]	SDCF	SESN	SEUNet	RST	RST-L	Ours
Params	28.95	2.42	7.03	13.98	9.66	9.66	1.22	0.15	1.36	1.22
GPU	4.68	5.07	7.65	7.65	5.09	5.06	5.05	5.06	15.12	5.05
Speed	93	383	182	45	427	406	372	365	895	372

Appendix A. Proof of Theorem 1

This is a boring technical proof of

$$\cos^2\theta + \sin^2\theta \equiv 1. \tag{1}$$

Appendix B. Proof of Theorem 2

This is a complete version of a proof sketched in the main text.