Learning in Observable POMDPs, without Computationally Intractable Oracles

Abstract

Much of reinforcement learning theory is built on top of oracles that are computationally hard to implement. Specifically for learning near-optimal policies in Partially Observable Markov Decision Processes (POMDPs), existing algorithms either need to make strong assumptions about the model dynamics (e.g. deterministic transitions) or assume access to an oracle for solving a hard optimistic planning or estimation problem as a subroutine. In this work we develop the first oracle-free learning algorithm for POMDPs under reasonable assumptions. Specifically, we give a quasipolynomial-time end-to-end algorithm for learning in "observable" POMDPs, where observability is the assumption that well-separated distributions over states induce well-separated distributions over observations. Our techniques circumvent the more traditional approach of using the principle of optimism under uncertainty to promote exploration, and instead give a novel application of barycentric spanners to constructing policy covers.

1 Introduction

Markov Decision Processes (MDPs) are a ubiquitous model in reinforcement learning that aim to capture sequential decision-making problems in a variety of applications spanning robotics to healthcare. However, modelling a problem with an MDP makes the often-unrealistic assumption that the agent has perfect knowledge about the state of the world. Partially Observable Markov Decision Processes (POMDPs) are a broad generalization of MDPs which capture an agent's inherent uncertainty about the state: while there is still an underlying state that updates according to the agent's actions, the agent never directly observes the state, but instead receives samples from a state-dependent observation distribution. The greater generality afforded by partial observability is crucial to applications in game theory [BS18], healthcare [Hau00, HF00b], market design [WME+22], and robotics [CKK96].

Unfortunately, this greater generality comes with steep statistical and computational costs. There are well-known statistical lower bounds [JKKL20, KAL16], which show that in the worst case, it is statistically intractable to find a near-optimal policy for a POMDP given the ability to play policies on it (the *learning* problem), even given unlimited computation. Furthermore, there are worst-case computational lower bounds [PT87, Lit94, BDRS96, LGM01, VLB12], which establish that it is computationally intractable to find a near-optimal policy even when given the exact parameters of the model (the substantially simpler *planning* problem).

Nevertheless there is a sizeable literature devoted to overcoming the *statistical* intractability of the learning problem by restricting to natural subclasses of POMDPs [KAL16, GDB16, ALA16, JKKL20, XCGZ21, KECM21a, KECM21b, LCSJ22]. There are far fewer works attempting to overcome *computational* intractability, and all make severe restrictions on either the model dynamics [JKKL20, KAL16] or the structure of the uncertainty [BDRS96, KECM21a]. The standard practice

is to simply sidestep computational issues by assuming access to strong oracles such as ones that solve *Optimistic Planning* (given a constrained, non-convex set of POMDPs, find the maximum value achievable by any policy on any POMDP in the set) [JKKL20] or *Optimistic Maximum Likelihood Estimation* (given a set of action/observation sample trajectories, find a POMDP which obtains maximum value conditioned on approximately maximizing the likelihood of seeing those trajectories) [LCSJ22]. Unsurprisingly, these oracles are computationally intractable to implement. Is there any hope for giving computationally efficient, oracle-free learning algorithms for POMDPs under reasonable assumptions? The naïve approach would require exponential time, and thus even a quasi-polynomial time algorithm would represent a dramatic improvement.

A necessary first step towards solving the learning problem is having a computationally efficient planning algorithm. Few such algorithms have provable guarantees under reasonable model assumptions, but recently it was shown [GMR22] that there is a quasipolynomial-time planning algorithm for POMDPs which satisfy an *observability* assumption. Let $H \in \mathbb{N}$ be the horizon length of the POMDP, and for each state s and step $h \in [H]$, let $\mathbb{O}_h(\cdot|s)$ denote the observation distribution at state s and step h. Then observability is defined as follows:

Assumption 1.1 ([EDKM07, GMR22])**.** *Let $\gamma > 0$. For $h \in [H]$, let $\mathbb{O}_h$ be the matrix with columns $\mathbb{O}_h(\cdot|s)$, indexed by states s. We say that the matrix $\mathbb{O}_h$ satisfies γ-observability if for each h, for any distributions b, b' over states, $\|\mathbb{O}_h b - \mathbb{O}_h b'\|_1 \geq \gamma \|b - b'\|_1$. A POMDP satisfies* (one-step) γ-observability *if all H of its observation matrices do.*

Compared to previous assumptions enabling computationally efficient planning, observability is much milder because it makes no assumptions about the dynamics of the POMDP, and it allows for natural observation models such as noisy or lossy sensors [GMR22]. It is known that statistically efficient learning is possible under somewhat weaker assumptions than observability [JKKL20], however these works rely on solving a planning problem that is computationally intractable. This raises the question: *Is observability enough to remedy both the computational and statistical woes of learning POMDPs?* In particular, can we get not only efficient planning but efficient learning too?

Overview of results. This work provides an affirmative answer to the questions above: we give an algorithm (BaSeCAMP, Algorithm 3) with quasi-polynomial time (and sample) complexity for learning near-optimal policies in observable POMDPs – see Theorem 3.1. While this falls just short of polynomial time, it turns out to be optimal in the sense that even for observable POMDPs there is a quasi-polynomial time lower bound for the (simpler) planning problem under standard complexity assumptions [GMR22]. A key innovation of our approach is an alternative technique to encourage exploration: whereas essentially all previous approaches for partially observable RL used the principle of *optimism under uncertainty* to encourage the algorithm to visit states [JKKL20, LCSJ22], we introduce a new framework based on the use of *barycentric spanners* [AK08] and *policy covers* [DKJ+19]. While each of these tools has previously been used in the broader RL literature to promote exploration (e.g. [LS17, FKQR21, DKJ+19, AHKS20, DGZ22, JKSY20, MHKL20]), they have not been used specifically in the study of POMDPs with imperfect observations,[1] and indeed our usage of them differs substantially from past instances.

The starting point for our approach is a result of [GMR22] (restated as Theorem 2.1) which implies that the dynamics of an observable POMDP $\mathcal{P}$ may be approximated by those of a *Markov decision process* $\mathcal{M}$ with a quasi-polynomial number of states. If we knew the transitions of $\mathcal{M}$, then we could simply use dynamic programming to find an optimal policy for $\mathcal{M}$, which would be guaranteed to be a near-optimal policy for $\mathcal{P}$. Instead, we must *learn* the transitions of $\mathcal{M}$, for which it is necessary to explore all (reachable) states of the underlying POMDP $\mathcal{P}$. A naïve approach to encourage exploration is to learn the transitions of $\mathcal{P}$ via forwards induction on the layer h, using, at each step h, our knowledge of the learned transitions at steps prior to h to find a policy which vists each reachable state at step h. Such an approach would lead to a *policy cover*, namely a collection of policies which visits all reachable latent states.

A major problem with this approach is that the latent states are not observed: instead, we only see observations. Hence a natural approach might be to choose policies which lead to all possible *observations* at each step h. This approach is clearly insufficient, since, e.g., a single state could emit a uniform distribution over observations. Thus we instead compute the following stronger concept:

---

[1] Policy covers have been used in the special case of *block MDPs* [DKJ+19, MHKL20], namely where different states produce disjoint observations.

for each step h, we consider the set $\mathcal{X}$ of all possible distributions over observations at step h under any general policy, and attempt to find a *barycentric spanner* of $\mathcal{X}$, namely a small subset $\mathcal{X}' \subset \mathcal{X}$ so that all other distributions in $\mathcal{X}$ can be expressed as a linear combination of elements of $\mathcal{X}'$ with bounded coefficients. By playing a policy which realizes each distribution in such a barycentric spanner $\mathcal{X}'$, we are able to explore all reachable latent states, despite having no knowledge about which states we are exploring. This discussion omits a key technical aspect of the proof, which is the fact that we can only compute a barycentric spanner for a set $\mathcal{X}$ corresponding to an empirical estimate $\widehat{\mathcal{M}}$ of $\mathcal{M}$. A key innovation in our proof is a technique to dynamically use such barycentric spanners, even when $\widehat{\mathcal{M}}$ is innacurate, to improve the quality of the estimate $\widehat{\mathcal{M}}$. We remark that a similar dynamic usage of barycentric spanners appeared in [FKQR21]; we discuss in the appendix why the approach of [FKQR21] cannot be applied here.

Taking a step back, few models in reinforcement learning (beyond tabular or linear MDPs) admit computationally efficient end-to-end learning algorithms – indeed, our main contribution is a way to circumvent the daunting task of implementing any of the various constrained optimistic planning oracles assumed in previous optimism-based approaches. We hope that our techniques may be useful in other contexts for avoiding computational intractability without resorting to oracles.

2 Preliminaries

For sets $\mathcal{T}, \mathcal{Q}$, let $\mathcal{Q}^{\mathcal{T}}$ denote the set of mappings from $\mathcal{T} \to \mathcal{Q}$. Accordingly, we will identify $\mathbb{R}^{\mathcal{T}}$ with $|\mathcal{T}|$-dimensional Euclidean space, and let $\Delta(\mathcal{T}) \subset \mathbb{R}^{\mathcal{T}}$ consist of distributions on $\mathcal{T}$. For $d \in \mathbb{N}$ and a vector $\mathbf{v} \in \mathbb{R}^d$, we denote its components by $\mathbf{v}(1), \ldots, \mathbf{v}(d)$. For integers $a \leq b$, we abbreviate a sequence $(x_a, x_{a+1}, \ldots, x_b)$ by $x_{a:b}$. If $a > b$, then we let $x_{a:b}$ denote the empty sequence. *Sometimes we refer to negative indices of a sequence $x_{1:n}$: in such cases the elements with negative indices may be taken to be aribtrary, as they will never affect the value of the expression. See Appendix B.1 for clarification.* For $x \in \mathbb{R}$, we write $[x]_+ = \max\{x, 0\}$, and $[x]_- = -\min\{x, 0\}$.

2.1 Background on POMDPs

In this paper we address the problem of learning finite-horizon *partially observable Markov decision processes (POMDPs)*. Formally, a POMDP $\mathcal{P}$ is a tuple $\mathcal{P} = (H, \mathcal{S}, \mathcal{A}, \mathcal{O}, b_1, R, \mathbb{T}, \mathbb{O})$, where: $H \in \mathbb{N}$ is a positive integer denoting the *horizon* length; $\mathcal{S}$ is a finite set of *states* of size $S := |\mathcal{S}|$; $\mathcal{A}$ is a finite set of *actions* of size $A := |\mathcal{A}|$; $\mathcal{O}$ is a finite set of *observations* of size $O := |\mathcal{O}|$; b_1 is the initial distribution over states; and $R, \mathbb{T}, \mathbb{O}$ are given as follows. First, $R = (R_1, \ldots, R_H)$ denotes a tuple of *reward functions*, where, for $h \in [H]$, $R_h : \mathcal{O} \to [0, 1]$ gives the reward received as a function of the observation at step h. Second, $\mathbb{T} = (\mathbb{T}_1, \ldots, \mathbb{T}_H)$ is a tuple of *transition kernels*, where, for $h \in [H], s, s' \in \mathcal{S}, a \in \mathcal{A}$, $\mathbb{T}_h(s'|s, a)$ denotes the probability of transitioning from s to s' at step h when action a is taken. For each $a \in \mathcal{A}$, we will write $\mathbb{T}_h(a) \in \mathbb{R}^{S \times S}$ to denote the matrix with $\mathbb{T}_h(a)_{s,s'} = \mathbb{T}_h(s|s', a)$. Third, $\mathbb{O} = (\mathbb{O}_1, \ldots, \mathbb{O}_H)$ is a tuple of *observation matrices*, where for $h \in [H], s \in \mathcal{S}, o \in \mathcal{O}$, $(\mathbb{O}_h)_{o,s}$, also written as $\mathbb{O}_h(o|s)$, denotes the probability observing o while in state s at step h. Thus $\mathbb{O}_h \in \mathbb{R}^{O \times S}$ for each h. Sometimes, for disambiguation, we will refer to the states $\mathcal{S}$ as the *latent states* of the POMDP $\mathcal{P}$.

The interaction (namely, a single *episode*) with $\mathcal{P}$ proceeds as follows: initially a state $s_1 \sim b_1$ is drawn from the initial state distribution. At each step $1 \leq h < H$, an action $a_h \in \mathcal{A}$ is chosen (as a function of previous observations and actions taken), $\mathcal{P}$ transitions to a new state $s_{h+1} \sim \mathbb{T}_h(\cdot|s_h, a_h)$, a new observation is observed, $o_{h+1} \sim \mathbb{O}_{h+1}(\cdot|s_{h+1})$, and a reward of $R_{h+1}(o_{h+1})$ is received (and observed). We emphasize that the underlying states $s_{1:H}$ are never observed directly. As a matter of convention, we assume that no observation is observed at step $h = 1$; thus the first observation is o_2.

2.2 Policies, value functions

A *deterministic policy* σ is a tuple $\sigma = (\sigma_1, \ldots, \sigma_H)$, where $\sigma_h : \mathcal{A}^{h-1} \times \mathcal{O}^{h-1} \to \mathcal{A}$ is a mapping from *histories* up to step h, namely tuples $(a_{1:h-1}, o_{2:h})$, to actions. We will denote the collection of histories up to step h by $\mathscr{H}_h := \mathcal{A}^{h-1} \times \mathcal{O}^{h-1}$ and the set of deterministic policies by Π^{det}, meaning that $\Pi^{\mathrm{det}} = \prod_{h=1}^H \mathcal{A}^{\mathscr{H}_h}$. A *general policy* π is a distribution over deterministic policies; the set of general policies is denoted by $\Pi^{\mathrm{gen}} := \Delta(\prod_{h=1}^H \mathcal{A}^{\mathscr{H}_h})$. Given a general policy $\pi \in \Pi^{\mathrm{gen}}$,

140 we denote by $\sigma \sim \pi$ the draw of a deterministic policy from the distribution π; to execute a general
141 policy π, a sample $\sigma \sim \pi$ is first drawn and then followed for an episode of the POMDP. For a
142 general policy π and some event $\mathcal{E}$, write $\mathbb{P}^{\mathcal{P}}_{a_{1:H-1},o_{2:H},s_{1:H}\sim\pi}(\mathcal{E})$ to denote the probability of $\mathcal{E}$ when
143 $s_{1:H}, a_{1:H-1}, o_{2:H}$ is drawn from a trajectory following policy π for the POMDP $\mathcal{P}$. At times we
144 will compress notation in the subscript, e.g., write $\mathbb{P}^{\mathcal{P}}_{\pi}(\mathcal{E})$ if the definition of $s_{1:H}, a_{1:H-1}, o_{2:H}$ is
145 evident. In similar spirit, we will write $\mathbb{E}^{\mathcal{P}}_{a_{1:H-1},o_{2:H},s_{1:H}\sim\pi}[\cdot]$ to denote expectations.

146 Given a general policy $\pi \in \Pi^{\mathrm{gen}}$, define the *value function* for π at step 1 by $V^{\pi,\mathcal{P}}_1(\emptyset) =$
147 $\mathbb{E}^{\mathcal{P}}_{o_{1:H}\sim\pi}\left[\sum_{h=2}^{H} R_h(o_h)\right]$, namely as the expected reward received by following π.

148 Our objective is to find a policy π which maximizes $V^{\pi,\mathcal{P}}_1(\emptyset)$, in the *PAC-RL model* [KS02]: in
149 particular, the algorithm does not have access to the transition kernel, reward function, or observation
150 matrices of $\mathcal{P}$, but can repeatedly choose a general policy π and observe the following data from a
151 single trajectory drawn according to π: $(a_1, o_2, R_2(o_2), a_2, \ldots, a_{H-1}, o_H, R_H(o_H))$. The challenge
152 is to choose such policies π which can sufficiently explore the environment.

153 Finally, we remark that *Markov decision processes* (MDPs) are a special case of POMDPs where
154 $\mathcal{O} = \mathcal{S}$ and $\mathbb{O}_h(o|s) = \mathbb{1}[o = s]$ for all $h \in [H], o, s \in \mathcal{S}$. For the MDPs we will consider, the initial
155 state distribution will be left unspecified (indeed, the optimal policy of an MDP does not depend on
156 the initial state distribution). Thus, we consider MDPs $\mathcal{M}$ described by a tuple $\mathcal{M} = (H, \mathcal{S}, \mathcal{A}, R, \mathbb{T})$.

2.3 Belief contraction

158 A prerequisite for a computationally efficient *learning* algorithm in observable POMDPs is a com-
159 putationally efficient *planning* algorithm, i.e. an algorithm to find an approximately optimal policy
160 when the POMDP is known. Recent work [GMR22] obtains such a planning algorithm taking
161 quasipolynomial time; we now introduce the key tools used in [GMR22], which are used in our
162 algorithm as well.

163 Consider a POMDP $\mathcal{P} = (H, \mathcal{S}, \mathcal{A}, \mathcal{O}, b_1, R, \mathbb{T}, \mathbb{O})$. Given some $h \in [H]$ and a history
164 $(a_{1:h-1}, o_{2:h}) \in \mathcal{H}_h$, the *belief state* $\mathbf{b}^{\mathcal{P}}_h(a_{1:h-1}, o_{2:h}) \in \Delta(\mathcal{S})$ is given by the distribution of the state
165 s_h conditioned on taking actions $a_{1:h-1}$ and observing $o_{2:h}$ in the first h steps. Formally, the belief
166 state is defined inductively as follows: $\mathbf{b}^{\mathcal{P}}_1(\emptyset) = b_1$, and for $2 \leq h \leq H$ and any $(a_{1:h-1}, o_{2:h}) \in \mathcal{H}_h$,

$$\mathbf{b}^{\mathcal{P}}_h(a_{1:h-1}, o_{2:h}) = U^{\mathcal{P}}_{h-1}(\mathbf{b}^{\mathcal{P}}_{h-1}(a_{1:h-2}, o_{2:h-1}); a_{h-1}, o_h),$$

167 where for $\mathbf{b} \in \Delta(\mathcal{S}), a \in \mathcal{A}, o \in \mathcal{O}, U^{\mathcal{P}}_h(\mathbf{b}; a, o) \in \Delta(\mathcal{S})$ is the distribution defined by

$$U^{\mathcal{P}}_h(\mathbf{b}; a, o)(s) := \frac{\mathbb{O}_{h+1}(o|s) \cdot \sum_{s'\in\mathcal{S}} \mathbf{b}(s') \cdot \mathbb{T}_h(s|s', a)}{\sum_{x\in\mathcal{S}} \mathbb{O}_{h+1}(o|x) \sum_{s'\in\mathcal{S}} \mathbf{b}(s') \cdot \mathbb{T}_h(x|s', a)}.$$

168 We call $U^{\mathcal{P}}_h$ the *belief update operator*. The belief state $\mathbf{b}^{\mathcal{P}}_h(a_{1:h-1}, o_{2:h})$ is a sufficient statistic for the
169 sequence of future actions and observations under any deterministic policy. In particular, the optimal
170 policy can be expressed as a function of the belief state, rather than the entire history. Thus, a natural
171 approach to plan a near-optimal policy is to find a small set $\mathscr{B} \subset \Delta(\mathcal{S})$ of distributions over states
172 such that each possible belief state $\mathbf{b}^{\mathcal{P}}_h(a_{1:h-1}, o_{2:h})$ is close to some element of $\mathscr{B}$. Unfortunately,
173 this is not possible, even in observable POMDPs [GMR22, Example D.2]. The main result of
174 [GMR22] circumvents this issue by showing that there is a subset $\mathscr{B} \subset \Delta(\mathcal{S})$ of quasipolynomial
175 size (depending on $\mathcal{P}$) so that $\mathbf{b}^{\mathcal{P}}_h(a_{1:h-1}, o_{2:h})$ is close to some element of $\mathscr{B}$ *in expectation* under
176 any given policy. To state the result of [GMR22], we need to introduce *approximate belief states*:

177 **Definition 2.1** (Approximate belief state). Fix a POMDP $\mathcal{P} = (H, \mathcal{S}, \mathcal{A}, \mathcal{O}, b_1, R, \mathbb{T}, \mathbb{O})$. For any
178 distribution $\mathscr{D} \in \Delta(\mathcal{S})$, as well as any choices of $1 \leq h \leq H$ and $L \geq 0$, the approximate belief state
179 $\mathbf{b}^{\mathrm{apx},\mathcal{P}}_h(a_{h-L:h-1}, o_{h-L+1:h}; \mathscr{D})$ is defined as follows, via induction on L: in the case that $L = 0$,
180 then we define

$$\mathbf{b}^{\mathrm{apx},\mathcal{P}}_h(\emptyset; \mathscr{D}) := \begin{cases} b_1 & : h = 1 \\ \mathscr{D} & : h > 1, \end{cases}$$

181 and for the case that $L > 0$, define, for $h > L$,

$$\mathbf{b}^{\mathrm{apx},\mathcal{P}}_h(a_{h-L:h-1}, o_{h-L+1:h}; \mathscr{D}) := U^{\mathcal{P}}_{h-1}(\mathbf{b}^{\mathrm{apx},\mathcal{P}}_{h-1}(a_{h-L:h-2}, o_{h-L+1:h-1}; \mathscr{D}); a_{h-1}, o_h).$$

182 We extend the above definition to the case that $h \leq L$ by defining
183 $\mathbf{b}_h^{\mathrm{apx},\mathcal{P}}(a_{h-L:h-1}, o_{h-L+1:h}; \mathscr{D}) := \mathbf{b}_h^{\mathrm{apx},\mathcal{P}}(a_{\max\{1,h-L\}:h-1}, o_{\max\{2,h-L+1\}:h}; \mathscr{D})$. In words, the
184 approximate belief state $\mathbf{b}_h^{\mathrm{apx},\mathcal{P}}(a_{h-L:h-1}, o_{h-L+1:h}; \mathscr{D})$ is obtained by applying the belief update
185 operator starting from the distribution $\mathscr{D}$ at step $h - L$, if $h - L > 1$ (and otherwise, starting from b_1,
186 at step 1). At times, we will drop the superscript $\mathcal{P}$ from the above definitions and write $\mathbf{b}_h, \mathbf{b}_h^{\mathrm{apx}}$.

187 The main technical result of [GMR22], stated as Theorem 2.1 below (with slight differences, see
188 Appendix B), proves that if the POMDP $\mathcal{P}$ is γ-observable for some $\gamma > 0$, then for a wide range of
189 distributions $\mathscr{D}$, for sufficiently large L, the approximate belief state $\mathbf{b}_h^{\mathrm{apx},\mathcal{P}}(a_{h-L:h-1}, o_{h-L+1:h}; \mathscr{D})$
190 will be close to (i.e., "contract to") the true belief state $\mathbf{b}_h^{\mathcal{P}}(a_{1:h-1}, o_{2:h})$.

191 **Theorem 2.1** (Belief contraction; Theorems 4.1 and 4.7 of [GMR22]). *Consider any γ-observable*
192 *POMDP $\mathcal{P}$, any $\epsilon > 0$ and $L \in \mathbb{N}$ so that $L \geq C \cdot \min\left\{ \frac{\log(1/(\epsilon\phi)) \log(\log(1/\phi)/\epsilon)}{\gamma^2}, \frac{\log(1/(\epsilon\phi))}{\gamma^4} \right\}$. Fix*
193 *any $\pi \in \Pi^{\mathrm{gen}}$, and suppose that $\mathscr{D} \in \Delta^{\mathcal{S}}$ satisfies $\frac{\mathbf{b}_h^{\mathcal{P}}(a_{1:h-L-1}, o_{2:h-L})(s)}{\mathscr{D}(s)} \leq \frac{1}{\phi}$ for all $(a_{h-1}, o_{2:h})$.*
194 *Then $\mathbb{E}_{(a_{1:h-1}, o_{2:h}) \sim \pi}^{\mathcal{P}} \left\| \mathbf{b}_h^{\mathcal{P}}(a_{1:h-1}, o_{2:h}) - \mathbf{b}_h^{\mathrm{apx},\mathcal{P}}(a_{h-L:h-1}, o_{h-L+1:h}; \mathscr{D}) \right\|_1 \leq \epsilon$.*

2.4 Visitation distributions

196 For a POMDP $\mathcal{P} = (H, \mathcal{S}, \mathcal{A}, \mathcal{O}, b_1, R, \mathbb{T}, \mathbb{O})$, policy $\pi \in \Pi^{\mathrm{gen}}$, and step $h \in [H]$, the (latent) *state*
197 *visitation distribution* at step h is $d_{\mathsf{S},h}^{\mathcal{P},\pi} \in \Delta(\mathcal{S})$ defined by $d_{\mathsf{S},h}^{\mathcal{P},\pi}(s) := \mathbb{P}_{s_{1:H} \sim \pi}^{\mathcal{P}}(s_h = s)$, and the
198 *observation visitation distribution* at step h is $d_{\mathsf{O},h}^{\mathcal{P},\pi} \in \Delta(\mathcal{O})$ defined by $d_{\mathsf{O},h}^{\mathcal{P},\pi} := \mathbb{P}_{o_{1:H} \sim \pi}^{\mathcal{P}}(o_h = \cdot) = $
199 $\mathbb{O}_h \cdot d_{\mathsf{S},h}^{\mathcal{P},\pi}$. We will often deal with MDPs $\mathcal{M} = (H, \mathcal{Z}, \mathcal{A}, R, \mathbb{T})$ where the set of states has a product
200 structure $\mathcal{Z} = \mathcal{A}^L \times \mathcal{O}^L$. We then define $\mathsf{o} : \mathcal{Z} \to \mathcal{O}$ by $\mathsf{o}(a_{1:L}, o_{1:L}) = o_L$. For such MDPs, we
201 define the observation visitation distributions by $d_{\mathsf{O},h}^{\mathcal{M},\pi}(o) := \mathbb{P}_{z_{1:H} \sim \pi}^{\mathcal{M}}(\mathsf{o}(z_h) = o)$.

3 Main result: learning observable POMDPs in quasipolynomial time

203 Theorem 3.1 below states our main guarantee for BaSeCAMP (Algorithm 3).

204 **Theorem 3.1.** *Given any $\alpha, \gamma > 0$ and γ-observable POMDP $\mathcal{P}$, BaSeCAMP with parameter settings*
205 *as described in Section C.1 outputs a policy which is α-suboptimal, using time and sample complexity*
206 *bounded by $(OA)^{CL}$, where $C > 1$ is a constant and $L = \min\left\{ \frac{\log(HSO/(\alpha\gamma))}{\gamma^4}, \frac{\log^2(HSO/(\alpha\gamma))}{\gamma^2} \right\}$.*

207 It is natural to ask whether the complexity guarantee of Theorem 3.1 can be improved further.
208 [GMR22, Theorem 6.4] shows that under the Exponential Time Hypothesis, there is no algorithm
209 for planning in γ-observable POMDPs which runs in time $(SAHO)^{o(\log(SAHO/\alpha)/\gamma)}$ and produces
210 α-suboptimal policies, *even if the POMDP is known*. Thus, up to polynomial factors in the exponent,
211 Theorem 3.1 is optimal. It is plausible, however, that there could be an algorithm which runs in
212 quasipolynomial time yet only needs *polynomially* many samples; we leave this question for future
213 work.

4 Algorithm description

4.1 Approximating $\mathcal{P}$ with an MDP.

216 A key consequence of observability is that, by the belief contraction result of Theorem 2.1, the
217 POMDP $\mathcal{P}$ is well-approximated by an MDP $\mathcal{M}$ of quasi-polynomial size. In more detail, we will
218 apply Theorem 2.1 with $\phi = 1/S$, $\mathscr{D} = \mathrm{Unif}(\mathcal{S})$, and some $L = \mathrm{poly}(\log(S/\epsilon)/\gamma)$ sufficiently
219 large so as to satisfy the requirement of the theorem statement. The MDP $\mathcal{M}$ has state space
220 $\mathcal{Z} := \mathcal{A}^L \times \mathcal{O}^L$, horizon H, action space $\mathcal{A}$, and transitions $\mathbb{P}_h^{\mathcal{M}}(\cdot | z_h, a_h)$ which are defined via
221 a belief update on the approximate belief state $\mathbf{b}_h^{\mathrm{apx},\mathcal{P}}(z_h; \mathrm{Unif}(\mathcal{S}))$[2]: in particular, for a state

---

[2]For simplicity, descriptions of the reward function of $\mathcal{M}$ are omitted; we refer the reader to the appendix for the full details of the proof

$z_h = (a_{h-L:h-1}, o_{h-L+1:h}) \in \mathcal{Z}$ of $\mathcal{M}$, action a_h, and subsequent observation $o_{h+1} \in \mathcal{O}$, define

$$\mathbb{P}_h^{\mathcal{M}}((a_{h-L+1:h}, o_{h-L+2:h+1})|z_h, a_h) := e_{o_{h+1}}^{\top} \cdot \mathbb{O}_{h+1}^{\mathcal{P}} \cdot \mathbb{T}_h^{\mathcal{P}}(a_h) \cdot \mathbf{b}_h^{\mathrm{apx}, \mathcal{P}}(z_h; \mathrm{Unif}(\mathcal{S})). \quad (1)$$

The above definition should be compared with the probability of observing o_{h+1} given history $(a_{1:h}, o_{2:h})$ and policy π when interacting with the POMDP $\mathcal{P}$, which is

$$\mathbb{P}_{o_{h+1} \sim \pi}^{\mathcal{P}}(o_{h+1}|a_{1:h}, o_{2:h}) = e_{o_{h+1}}^{\top} \cdot \mathbb{O}_{h+1}^{\mathcal{P}} \cdot \mathbb{T}_h^{\mathcal{P}}(a_h) \cdot \mathbf{b}_h^{\mathcal{P}}(a_{1:h-1}, o_{2:h}). \quad (2)$$

Theorem 2.1 gives that $\left\|\mathbf{b}_h^{\mathcal{P}}(a_{1:h-1}, o_{2:h}) - \mathbf{b}_h^{\mathrm{apx}, \mathcal{P}}(a_{h-L:h-1}, o_{h-L+1:h}; \mathrm{Unif}(\mathcal{S}))\right\|_1$ is small in expectation under any general policy π, which, using (1) and (2), gives that, for all $\pi \in \Pi^{\mathrm{gen}}$ and $h \in [H]$,

$$\mathbb{E}_{a_{1:h}, o_{2:h} \sim \pi} \sum_{o_{h+1} \in \mathcal{O}} \left|\mathbb{P}_h^{\mathcal{M}}(o_{h+1}|z_h, a_h) - \mathbb{P}_h^{\mathcal{P}}(o_{h+1}|a_{1:h}, o_{2:h})\right| \leq \epsilon. \quad (3)$$

(Above we have written $z_h = (a_{h-L:h-1}, o_{h-L+1:h})$ and, via abuse of notation, $\mathbb{P}_h^{\mathcal{M}}(o_{h+1}|z_h, a_h)$ in place of $\mathbb{P}_h^{\mathcal{M}}((a_{h-L+1:h}, o_{h-L+2:h+1})|z_h, a_h)$.) The inequality (3) establishes that the dynamics of $\mathcal{P}$ under any policy may be approximated by those of the MDP $\mathcal{M}$. Crucially, this implies that there exists a deterministic Markov policy for $\mathcal{M}$ which is near-optimal among general policies for $\mathcal{P}$; the set of such Markov policies for $\mathcal{M}$ is denoted by $\Pi_{\mathsf{Z}}^{\mathrm{markov}}$. Because of the Markovian structure of $\mathcal{M}$, such a policy can be found in time polynomial in the size of $\mathcal{M}$ (which is quasi-polynomial in the underlying problem parameters), if $\mathcal{M}$ is known. Of course, $\mathcal{M}$ is not known.

Approximately learning the MDP $\mathcal{M}$. These observations suggest the following model-based approach of trying to learn the transitions of $\mathcal{M}$. Suppose that we know a sequence of general policies $\pi^1, \ldots, \pi^H$ (abbreviated as $\pi^{1:H}$) so that for each h, π^h visits a uniformly random state of $\mathcal{P}$ at step $h - L$ (i.e. $d_{\mathsf{S}, h-L}^{\mathcal{P}, \pi^h} = \mathrm{Unif}(\mathcal{S})$). Then we can estimate the transitions of $\mathcal{M}$ as follows: play π^h for $h - L - 1$ steps and then play $L + 1$ random actions, generating a trajectory $(a_{1:h}, o_{2:h+1})$. Conditioned on $z_h = (a_{h-L:h-1}, o_{h-L+1:h})$ and final action a_h, the last observation of this sample trajectory, o_{h+1}, would give an unbiased draw from the transition distribution $\mathbb{P}_h^{\mathcal{M}}(\cdot|z_h, a_h)$. Repeating this procedure would allow estimation of $\mathbb{P}_h^{\mathcal{M}}$ (see Lemma E.1).

This idea is formalized in the procedure ConstructMDP (Algorithm 1): given a sequence of general policies $\pi^1, \ldots, \pi^H$ (abbreviated $\pi^{1:H}$), ConstructMDP constructs an MDP, denoted $\widehat{\mathcal{M}} = \widehat{\mathcal{M}}(\pi^{1:H})$, which empirically approximates $\mathcal{M}$ using the sampling procedure described above. For technical reasons, $\widehat{\mathcal{M}}$ actually has state space $\overline{\mathcal{Z}} := \mathcal{A}^L \cdot \overline{\mathcal{O}}^L$, where $\overline{\mathcal{O}} := \mathcal{O} \cup \{o^{\mathrm{sink}}\}$ and o^{sink} is a special "sink observation" so that, after o^{sink} is observed, all future observations are also o^{sink}. Furthermore, we remark that $d_{\mathsf{S}, h-L}^{\mathcal{P}, \pi^h}$ does not have to be exactly uniform – it suffices if π^h visits all states of $\mathcal{P}$ at step $h - L$ with non-negligible probability.

4.2 Exploration via barycentric spanners

The above procedure for approximating $\mathcal{M}$ with $\widehat{\mathcal{M}}$ omits a crucial detail: *how can we find the "exploratory policies" $\pi^{1:H}$?* Indeed a major obstacle to finding such policies is that *we never directly observe the states of $\mathcal{P}$.* By repeatedly playing a policy π on $\mathcal{P}$, we can estimate the induced observation visitation distribution $d_{\mathsf{O}, h-L}^{\mathcal{P}, \pi}$, which is related to the state visitation distribution via the equality $\mathbb{O}_{h-L}^{\dagger} \cdot d_{\mathsf{O}, h-L}^{\mathcal{P}, \pi} = d_{\mathsf{S}, h-L}^{\mathcal{P}, \pi}$. Unfortunately, the matrix $\mathbb{O}_{h-L}$ is still unknown, and in general *unidentifiable*.

On the positive side, we can attempt to learn $\mathcal{M}$ layer by layer – in particular, when learning the hth layer, we can assume that we have learned previous layers, i.e., $d_{\mathsf{O}, h-L}^{\widehat{\mathcal{M}}, \pi}$ approximates $d_{\mathsf{O}, h-L}^{\mathcal{M}, \pi}$, and therefore $d_{\mathsf{O}, h-L}^{\mathcal{P}, \pi}$. Even though $\widehat{\mathcal{M}}$ does not have underlying latent states, we can define "formal" latent state distributions on $\widehat{\mathcal{M}}$ in analogy with $\mathcal{P}$, i.e. $d_{\mathsf{S}, h-L}^{\widehat{\mathcal{M}}, \pi} := \mathbb{O}_{h-L}^{\dagger} \cdot d_{\mathsf{O}, h-L}^{\widehat{\mathcal{M}}, \pi}$. But this does not seem helpful, again because $\mathbb{O}_{h-L}$ is unknown. Our first key insight is that a policy π^h, for which $d_{\mathsf{S}, h-L}^{\widehat{\mathcal{M}}, \pi^h}$ puts non-negligible mass on all states, can be found (when it exists) via knowledge of $\widehat{\mathcal{M}}$ and the technique of *Barycentric Spanners* – all without ever explicitly computing $d_{\mathsf{S}, h-L}^{\widehat{\mathcal{M}}, \pi^h}$.

Barycentric spanners. Suppose we knew that the transitions of our empirical estimate $\widehat{\mathcal{M}}$ approximate those of $\mathcal{M}$ up to step h, and we want to find a policy π^h for which the (formal) latent state distribution $d_{\mathsf{S},h-L}^{\widehat{\mathcal{M}},\pi^h}$ is non-negligible on all states. Unfortunately, the set of achievable latent state distributions $\{\mathbb{O}_{h-L}^\dagger \cdot d_{\mathsf{O},h-L}^{\widehat{\mathcal{M}},\pi} : \pi \in \Pi^{\mathrm{gen}}\} \subseteq \mathbb{R}^S$ is defined implicitly, via the unknown observation matrix $\mathbb{O}_{h-L}$. But we do have access to $\mathcal{X}_{\widehat{\mathcal{M}},h-L} := \{d_{\mathsf{O},h-L}^{\widehat{\mathcal{M}},\pi} : \pi \in \Pi^{\mathrm{gen}}\} \subseteq \mathbb{R}^O$, the set of achievable distributions over the observation at step $h - L$. In particular, for any reward function on observations at step $h - L$, we can efficiently (by dynamic programming) find a policy π that maximizes reward on $\widehat{\mathcal{M}}$ over all policies. In other words, we can solve *linear optimization* problems over $\mathcal{X}$. By a classic result [AK08], we can thus efficiently find a *barycentric spanner* for $\mathcal{X}_{\widehat{\mathcal{M}},h-L}$:

Definition 4.1 (Barycentric spanner). Consider a subset $\mathcal{X} \subset \mathbb{R}^d$. For $B \geq 1$, a set $\mathcal{X}' \subset \mathcal{X}$ of size d is a *B-approximate barycentric spanner* of $\mathcal{X}$ if each $x \in \mathcal{X}$ can be expressed as a linear combination of elements in $\mathcal{X}'$ with coefficients in $[-B, B]$.

Using the guarantee of [AK08] (restated as Lemma D.1) applied to the set $\mathcal{X}_{\widehat{\mathcal{M}},h-L}$, we can find, in time polynomial in the size of $\widehat{\mathcal{M}}$, a 2-approximate barycentric spanner $\widetilde{\pi}^1, \ldots, \widetilde{\pi}^O$ of $\mathcal{X}_{\widehat{\mathcal{M}},h-L}$; this procedure is formalized in `BarySpannerPolicy` (Algorithm 2). Thus, for any policy π, the observation distribution $d_{\mathsf{O},h-L}^{\widehat{\mathcal{M}},\pi}$ induced by π is a linear combination of the distributions $\{d_{\mathsf{O},h-L}^{\widehat{\mathcal{M}},\widetilde{\pi}^i} : i \in [O]\}$ with coefficients in $[-2, 2]$; further, the formal latent state distribution $d_{\mathsf{S},h-L}^{\widehat{\mathcal{M}},\pi}$ induced by π is a linear combination of the formal latent state distributions $\{d_{\mathsf{S},h-L}^{\widehat{\mathcal{M}},\widetilde{\pi}^i} : i \in [O]\}$ with the same coefficients. Now, intuitively, the randomized mixture policy $\pi_{\mathrm{mix}} = \frac{1}{O}(\widetilde{\pi}^1 + \cdots + \widetilde{\pi}^O)$ should explore every reachable state; indeed, we show the following guarantee for `BarySpannerPolicy`:

Lemma 4.1 (Informal version & special case of Lemma D.2). *In the above setting, under some technical conditions, for all $s \in \mathcal{S}$ and $\pi \in \Pi^{\mathrm{gen}}$, it holds that $d_{\mathsf{S},h-L}^{\widehat{\mathcal{M}},\pi_{\mathrm{mix}}}(s) \geq \frac{1}{4O^2} \cdot d_{\mathsf{S},h-L}^{\widehat{\mathcal{M}},\pi}(s)$.*

But recall the original goal: a policy π^h which explores $\mathcal{P}$ – not $\widehat{\mathcal{M}}$. Unfortunately, those states in $\mathcal{P}$ which can only be reached with probability that is small compared to the distance between $\mathcal{P}$ and $\widehat{\mathcal{M}}$ may be missed by π_{mix}. When we use π_{mix} to compute the next-step transitions of $\widehat{\mathcal{M}}$, this will lead to additional error when applying belief contraction (Theorem 2.1), and therefore additional error between $\mathcal{P}$ and $\widehat{\mathcal{M}}$. If not handled carefully, this error will compound exponentially over layers.

4.3 The full algorithm via iterative discovery

The solution to the dilemma discussed above is to not try to construct our estimate $\widehat{\mathcal{M}}$ of $\mathcal{M}$ layer by layer, hoping that at each layer we can explore all reachable states of $\mathcal{P}$ despite making errors in earlier layers of $\widehat{\mathcal{M}}$. Instead, we have to be able to go back and "fix" errors in our empirical estimates at earlier layers. This task is performed in our main algorithm, `BaSeCAMP` (Algorithm 3). For some $K \in \mathbb{N}$, `BaSeCAMP` runs for a total of K iterations: at each iteration $k \in [K]$, `BaSeCAMP` defines H general policies, $\overline{\pi}^{k,1}, \ldots, \overline{\pi}^{k,H} \in \Pi^{\mathrm{gen}}$ (abbreviated $\overline{\pi}^{k,1:H}$; step 4). The algorithm's overall goal is that, for some k, for each $h \in [H]$, $\overline{\pi}^{k,h}$ explores all latent states at step $h - L$ that are reachable by any policy.

To ensure that this condition holds at some iteration, `BaSeCAMP` performs the following two main steps for each iteration k: first, it calls Algorithm 1 to construct an MDP, denoted $\widehat{\mathcal{M}}^{(k)}$, using the policies $\overline{\pi}^{k,1:H}$. Then, for each $h \in [H]$, it passes the tuple $(\widehat{\mathcal{M}}^{(k)}, h)$ to `BarySpannerPolicy`, which returns as output a general policy, $\pi^{k+1,h,0}$. Then, policies $\pi^{k+1,h}$ are produced (step 7) by averaging $\pi^{k+1,h',0}$, for all $h' \geq h$. The policies $\pi^{k+1,h}$ are then mixed into the policies $\overline{\pi}^{k+1,h}$ for the next iteration $k + 1$. It follows from properties of `BarySpannerPolicy` that, in the event that the policies $\overline{\pi}^{k,h}$ are not sufficiently exploratory, one of the new policies $\pi^{k+1,h}$ visits *some* latent state $(s, h') \in \mathcal{S} \times [H]$, which was not previously visited by $\overline{\pi}^{k,1:H}$ with significant probability. Thus, after a total of $K = O(SH)$ iterations k, it follows that we must have visited all (reachable) latent states of the POMDP. At the end of these K iterations, `BaSeCAMP` computes an optimal policy for each $\widehat{\mathcal{M}}^{(k)}$ and returns the best of them (as evaluated on fresh trajectories drawn from $\mathcal{P}$; step 12).

Algorithm 1 `ConstructMDP`

1: **procedure** CONSTRUCTMDP($L, N_0, N_1, \pi^1, \ldots, \pi^H$)
2:     **for** $1 \leq h \leq H$ **do**
3:         Let $\widehat{\pi}^h$ be the policy which follows π^h for the first $\max\{h - L - 1, 0\}$ steps and thereafter chooses uniformly random actions.
4:         Draw N_0 independent trajectories from the policy $\widehat{\pi}^h$:
5:         Denote the data from the ith trajectory by $a^i_{1:H-1}, o^i_{2:H}$, for $i \in [N_0]$.
6:         Set $z^i_h = (a^i_{h-L:h-1}, o^i_{h-L+1:h})$ for all $i \in [N_0], h \in [H]$.
7:         *// Construct the transitions $\mathbb{P}_h^{\widehat{\mathcal{M}}}(z_{h+1}|z_h, a_h)$ as follows:*
8:         **for** each $z_h = (a_{h-L:h-1}, o_{h-L+1:h}) \in \mathcal{Z}$, $a_h \in \mathcal{A}$ **do**
9:             *// Define $\mathbb{P}_h^{\widehat{\mathcal{M}}}(\cdot|z_h, a_h)$ to be the empirical distribution of $z^i_{h+1}|z^i_h, a^i_h$, as follows:*
10:            For $o_{h+1} \in \mathcal{O}$, define $\varphi(o_{h+1}) := |\{i : (a^i_{\max\{1,h-L\}:h}, o^i_{\max\{2,h-L+1\}:h+1}) = (a_{\max\{1,h-L\}:h}, o_{\max\{2,h-L+1\}:h+1})\}|$.
11:            **if** $\sum_{o_{h+1}} \varphi(o_{h+1}) \geq N_1$ **then**
12:                Set $\mathbb{P}_h^{\widehat{\mathcal{M}}}((a_{h-L+1:h}, o_{h-L+2:h+1})|z_h, a_h) := \frac{\varphi(o_{h+1})}{\sum_{o'_{h+1}} \varphi(o'_{h+1})}$ for all $o_{h+1} \in \mathcal{O}$.
13:                Set $R_h^{\widehat{\mathcal{M}}}(z_h, a_h) := R_h^{\mathcal{P}}(o^i_h)$ for some i with $o^i_h = o_h$.   ▷ $R_h^{\mathcal{P}}(o^i_h)$ *is observed.*
14:            **else**
15:                Let $\mathbb{P}_h^{\widehat{\mathcal{M}}}(\cdot|z_h, a_h)$ put all its mass on $(a_{h-L+1:h}, (o_{h-L+2:h}, o^{\text{sink}}))$.
16:         **for** each $z_h = (a_{h-L:h-1}, o_{h-L+1:h}) \in \overline{\mathcal{Z}}\backslash\mathcal{Z}$ and $a_h \in \mathcal{A}$ **do**
17:            Let $\mathbb{P}_h^{\widehat{\mathcal{M}}}(\cdot|z_h, a_h)$ put all its mass on $(a_{h-L+1:h}, (o_{h-L+2:h}, o^{\text{sink}}))$.
18:     Let $\widehat{\mathcal{M}}$ denote the MDP $(H, \overline{\mathcal{Z}}, \mathcal{A}, R^{\widehat{\mathcal{M}}}, \mathbb{P}^{\widehat{\mathcal{M}}})$.
19:     **return** the MDP $\widehat{\mathcal{M}}$, which we denote by $\widehat{\mathcal{M}}(\pi^{1:H})$.

Algorithm 2 `BarySpannerPolicy`

1: **procedure** BARYSPANNERPOLICY($\widehat{\mathcal{M}}, h$)   ▷ $\widehat{\mathcal{M}}$ *is an MDP on state space* $\overline{\mathcal{Z}} = \mathcal{A}^L \times \overline{\mathcal{O}}^L$ *with horizon length H, and $h \in [H]$*
2:     Let $\mathscr{O}$ be the linear optimization oracle which given $r \in \mathbb{R}^{\mathcal{O}}$, returns $\arg\max_{\pi \in \Pi_{\mathsf{Z}}^{\text{markov}}} \langle r, d^{\pi, \widehat{\mathcal{M}}}_{\mathsf{O}, h-L} \rangle$ and $\max_{\pi \in \Pi_{\mathsf{Z}}^{\text{markov}}} \langle r, d^{\pi, \widehat{\mathcal{M}}}_{\mathsf{O}, h-L} \rangle$ ▷ *Note that $\mathscr{O}$ can be implemented in time $O(|\overline{\mathcal{Z}}| \cdot HO)$ using dynamic programming*
3:     Using the algorithm of [AK08] with oracle $\mathscr{O}$, compute policies $\{\pi^1, \ldots, \pi^O\}$ so that $\{d^{\pi^i, \widehat{\mathcal{M}}}_{\mathsf{O}, h-K} : i \in [O]\}$ is a 2-approximate barycentric spanner of $\{d^{\pi, \widehat{\mathcal{M}}}_{\mathsf{O}, h-K} : \pi \in \Pi_{\mathsf{Z}}^{\text{markov}}\}$. ▷ *This algorithm requires only $O(O^2 \log O)$ calls to $\mathscr{O}$*
4:     **return** the general policy $\frac{1}{O} \cdot \sum_{i=1}^O \pi^i$.

Algorithm 3 `BaSeCAMP` (**Ba**rycentric **S**pann**e**r policy **C**over with **A**pproximate **M**D**P**)

1: **procedure** BASECAMP(L, N_0, N_1, α, K)
2:     Initialize $\pi^{1,1}, \ldots, \pi^{1,H}$ to be arbitrary policies.
3:     **for** $k \in [K]$ **do**
4:         For each $h \in [H]$, set $\overline{\pi}^{k,h} = \frac{1}{K} \sum_{k=1}^K \pi^{k,h}$.
5:         Run `ConstructMDP`($L, N_0, N_1, \overline{\pi}^{k,1:H}$) and let its output be $\widehat{\mathcal{M}}^{(k)}$.
6:         For each $h \in [H]$, let $\pi^{k+1,h,0}$ be the output of `BarySpannerPolicy`($\widehat{\mathcal{M}}^{(k)}, h$).
7:         For each $h \in [H]$, define $\pi^{k+1,h} := \frac{1}{H-h+1} \sum_{h'=h}^H \pi^{k+1,h',0}$.
8:     *// Choose the best optimal policy amongst all $\widehat{\mathcal{M}}^{(k)}$*
9:     **for** $k \in [K]$ **do**
10:         Let $\pi_\star^k$ denote an optimal policy of $\widehat{\mathcal{M}}^{(k)}$.
11:         Execute $\pi_\star^k$ for $\frac{C \log 1/p}{\alpha^2}$ trajectories and let the mean reward across the trajectories be $\widehat{r}^k$.
12:     Let $k^\star = \arg\max_{k \in [K]} \widehat{r}^k$.
13:     **return** $\pi_\star^{k^\star}$.

---

5 Proof Outline

We now briefly outline the proof of Theorem 3.1; further details may be found in the appendix. The high-level idea of the proof is to show that the algorithm `BaSeCAMP` makes a given amount of progress for each iteration k, as specified in the following lemma:

Lemma 5.1 ("Progress lemma": informal version of Lemma I.2). *Fix any iteration k in Algorithm 3, step 3. Then, for some parameters δ, ϕ with $\alpha \gg \delta \gg \phi > 0$, one of the following statements holds:*

    1. There is some $(h, s) \in [H] \times \mathcal{S}$ so that:

$$d_{\mathsf{S}, h-L}^{\mathcal{P}, \overline{\pi}^{k,h}}(s) < \phi \cdot H^2 S, \quad \text{yet, for all } k' > k: \quad d_{\mathsf{S}, h-L}^{\mathcal{P}, \overline{\pi}^{k',h}}(s) \geq \phi \cdot H^2 S.$$

    2. Any (s, h) with $d_{\mathsf{S}, h-L}^{\mathcal{P}, \overline{\pi}^{k,h}}(s) < \phi$ satisfies $d_{\mathsf{S}, h-L}^{\mathcal{P}, \pi}(s) \leq \delta$ for all general policies π.

Given Lemma 5.1, the proof of Theorem 3.1 is fairly straightforward. In particular, each $(h, s) \in [H] \times \mathcal{S}$ can only appear as the specified pair in item 1 of the lemma for a single iteration k. Thus, as long as $K > HS$, item 2 must hold for some value of k, say $k^\star \in [K]$. In turn, it is not difficult to show from this that the MDP $\widehat{\mathcal{M}}^{(k^\star)}$ is a good approximation of $\mathcal{P}$, in the sense that for any general policy π, the values of π in $\widehat{\mathcal{M}}^{(k^\star)}$ and in $\mathcal{P}$ are close (Lemma H.3). Thus, the optimal policy $\pi_\star^{k^\star}$ of $\widehat{\mathcal{M}}^{(k^\star)}$ will be a near-optimal policy of $\mathcal{P}$, and steps 9 through 12 of `BaSeCAMP` will identify either the policy $\pi_\star^{k^\star}$ or some other policy $\pi_\star^{k'}$ which has even higher reward on $\mathcal{P}$.

Proof of the progress lemma. The bulk of the proof of Theorem 3.1 consists of the proof of Lemma 5.1, which we proceed to outline. Suppose that item 2 of the lemma does not hold, meaning that there is some $\pi \in \Pi^{\mathrm{gen}}$ and some $(h, s) \in [H] \times \mathcal{S}$ so that $d_{\mathsf{S}, h-L}^{\mathcal{P}, \overline{\pi}^{k,h}}(s) < \phi$ yet $d_{\mathsf{S}, h-L}^{\mathcal{P}, \pi}(s) > \delta$; i.e., $\overline{\pi}^{k,h}$ does *not* explore $(s, h - L)$, but the policy π does. Roughly speaking, `BaSeCAMP` ensures that item 1 holds in this case, using the following two steps:

(A) First, we show that $\langle e_s, \mathbb{O}_{h-L}^\dagger \cdot d_{\mathsf{O}, h-L}^{\widehat{\mathcal{M}}^{(k)}, \pi} \rangle \geq \delta'$, where δ' is some parameter satisfying $\delta \gg \delta' \gg \phi$. In words, the estimate of the underlying state distribution provided by $\widehat{\mathcal{M}}^{(k)}$ *also* has the property that some policy π visits $(s, h - L)$ with non-negligible probability (namely, δ'). While this statement would be straightforward if $\widehat{\mathcal{M}}^{(k)}$ were a close approximation $\mathcal{P}$, this is *not* necessarily the case (indeed, if it were the case, then item 2 of Lemma 5.1 would hold). To circumvent this issue, we introduce a family of intermediate POMDPs indexed by $H' \in [H]$ and denoted $\overline{\mathcal{P}}_{\phi, H'}(\overline{\pi}^{k,1:H})$, which we call *truncated POMDPs*. Roughly speaking, the truncated POMDP $\overline{\mathcal{P}}_{\phi, H'}(\overline{\pi}^{k,1:H})$ diverts transitions away from all states at step $H' - L$ which $\overline{\pi}^{k,H'}$ does not visit with probability at least ϕ. This modification is made to allow Theorem 2.1 to be applied to $\overline{\mathcal{P}}_{\phi, H'}(\overline{\pi}^{k,1:H})$ and any general policy π. By doing so, we may show a *one-sided* error bound between $\overline{\mathcal{P}}_{\phi, H'}(\overline{\pi}^{k,1:H})$ and $\widehat{\mathcal{M}}^{(k)}$ (Lemma G.3) which, importantly, holds even when the policies $\overline{\pi}^{k,1:H}$ may fail to explore some states. It is this one-sided error bound which implies the lower bound on $\langle e_s, \mathbb{O}_{h-L}^\dagger \cdot d_{\mathsf{O}, h-L}^{\widehat{\mathcal{M}}^{(k)}, \pi} \rangle$.

(B) Second, we show that the policy $\pi^{k+1,h,0}$ produced by `BarySpannerPolicy` in step 6 explores $(s, h - L)$ with sufficient probability. To do so, we first use Lemma 4.1 to conclude that $\langle e_s, \mathbb{O}_{h-L}^\dagger \cdot d_{\mathsf{O}, h-L}^{\widehat{\mathcal{M}}^{(k)}, \pi^{k+1,h,0}} \rangle \geq \frac{\delta'}{4O^2}$. The more challenging step is to use this fact to conclude a lower bound on $d_{\mathsf{S}, h-L}^{\mathcal{P}, \pi^{k+1,h,0}}(s)$; unfortunately, the one-sided error bound between $\mathcal{P}$ and $\widehat{\mathcal{M}}^{(k)}$ that we used in the previous paragraph goes in the wrong direction here. The solution is to use Lemma H.3, which has the following consequence: either $d_{\mathsf{S}, h-L}^{\mathcal{P}, \pi^{k+1,h,0}}(s)$ is not too small, or else the policy $\pi^{k+1,h,0}$ visits some state at a step *prior to* $h - L$ which was not sufficiently explored by any of the policies $\overline{\pi}^{k,1:H}$. In either case $\pi^{k+1,h,0}$ visits a state that was not previously explored, and the fact that $\pi^{k+1,h,0}$ is mixed in to $\overline{\pi}^{k',h'}$ for $k' > k, h' \leq h$ (steps 4, 7 of `BaSeCAMP`) allows us to conclude item 1 of Lemma 5.1.

References

[AHKS20] Alekh Agarwal, Mikael Henaff, Sham Kakade, and Wen Sun. Pc-pg: Policy cover directed exploration for provable policy gradient learning. *Advances in Neural Information Processing Systems*, 33:13399–13412, 2020.

[AK08] Baruch Awerbuch and Robert Kleinberg. Online linear optimization and adaptive routing. *Journal of Computer and System Sciences*, 74(1):97–114, 2008.

[ALA16] Kamyar Azizzadenesheli, Alessandro Lazaric, and Animashree Anandkumar. Open problem: Approximate planning of pomdps in the class of memoryless policies. In *Conference on Learning Theory*, pages 1639–1642. PMLR, 2016.

[AYA18] Kamyar Azizzadenesheli, Yisong Yue, and Animashree Anandkumar. Policy gradient in partially observable environments: Approximation and convergence. *arXiv preprint arXiv:1810.07900*, 2018.

[BDRS96] Dima Burago, Michel De Rougemont, and Anatol Slissenko. On the complexity of partially observed markov decision processes. *Theoretical Computer Science*, 157(2):161–183, 1996.

[BS18] Noam Brown and Tuomas Sandholm. Superhuman ai for heads-up no-limit poker: Libratus beats top professionals. *Science*, 359(6374):418–424, 2018.

[Can20] Clément L Canonne. A short note on learning discrete distributions. *arXiv preprint arXiv:2002.11457*, 2020.

[CKK96] Anthony R Cassandra, Leslie Pack Kaelbling, and James A Kurien. Acting under uncertainty: Discrete bayesian models for mobile-robot navigation. In *Proceedings of IEEE/RSJ International Conference on Intelligent Robots and Systems. IROS'96*, volume 2, pages 963–972. IEEE, 1996.

[CLZ97] Anthony Cassandra, Michael L. Littman, and Nevin L. Zhang. Incremental pruning: A simple, fast, exact method for partially observable markov decision processes. In *Proceedings of the Thirteenth Conference on Uncertainty in Artificial Intelligence*, UAI'97, page 54–61, San Francisco, CA, USA, 1997. Morgan Kaufmann Publishers Inc.

[DGZ22] Constantinos Daskalakis, Noah Golowich, and Kaiqing Zhang. The complexity of markov equilibrium in stochastic games. *arXiv preprint arXiv:2204.03991*, 2022.

[DKJ+19] Simon Du, Akshay Krishnamurthy, Nan Jiang, Alekh Agarwal, Miroslav Dudik, and John Langford. Provably efficient rl with rich observations via latent state decoding. In *International Conference on Machine Learning*, pages 1665–1674. PMLR, 2019.

[EDKM05] Eyal Even-Dar, Sham M Kakade, and Yishay Mansour. Reinforcement learning in pomdps without resets. 2005.

[EDKM07] Eyal Even-Dar, Sham M Kakade, and Yishay Mansour. The value of observation for monitoring dynamic systems. In *IJCAI*, pages 2474–2479, 2007.

[EJKM22] Yonathan Efroni, Chi Jin, Akshay Krishnamurthy, and Sobhan Miryoosefi. Provable reinforcement learning with a short-term memory. *CoRR*, abs/2202.03983, 2022.

[FKQR21] Dylan J Foster, Sham M Kakade, Jian Qian, and Alexander Rakhlin. The statistical complexity of interactive decision making. *arXiv preprint arXiv:2112.13487*, 2021.

[GDB16] Zhaohan Daniel Guo, Shayan Doroudi, and Emma Brunskill. A pac rl algorithm for episodic pomdps. In *Artificial Intelligence and Statistics*, pages 510–518. PMLR, 2016.

[GHL19] Neha Priyadarshini Garg, David Hsu, and Wee Sun Lee. Despot-alpha: Online pomdp planning with large state and observation spaces. In *Robotics: Science and Systems*, 2019.

[GMR22] Noah Golowich, Ankur Moitra, and Dhruv Rohatgi. Planning in observable pomdps in quasipolynomial time. *arXiv preprint arXiv:2201.04735*, 2022.

[Han98] Eric A Hansen. Solving pomdps by searching in policy space. In *Proceedings of the Fourteenth conference on Uncertainty in artificial intelligence*, pages 211–219, 1998.

[Hau00] Milos Hauskrecht. Value-function approximations for partially observable markov decision processes. *Journal of artificial intelligence research*, 13:33–94, 2000.

[HF00a] Eric A. Hansen and Zhengzhu Feng. Dynamic programming for pomdps using a factored state representation. In *In Proceedings of the Fifth International Conference on AI Planning Systems*, pages 130–139, 2000.

[HF00b] Milos Hauskrecht and Hamish Fraser. Planning treatment of ischemic heart disease with partially observable markov decision processes. *Artificial intelligence in medicine*, 18(3):221–244, 2000.

[JJN21] Mehdi Jafarnia-Jahromi, Rahul Jain, and Ashutosh Nayyar. Online learning for unknown partially observable mdps. *CoRR*, abs/2102.12661, 2021.

[JKKL20] Chi Jin, Sham M Kakade, Akshay Krishnamurthy, and Qinghua Liu. Sample-efficient reinforcement learning of undercomplete pomdps. *arXiv preprint arXiv:2006.12484*, 2020.

[JKSY20] Chi Jin, Akshay Krishnamurthy, Max Simchowitz, and Tiancheng Yu. Reward-free exploration for reinforcement learning. In *International Conference on Machine Learning (ICML)*, pages 4870–4879. PMLR, 2020.

[KAL16] Akshay Krishnamurthy, Alekh Agarwal, and John Langford. Pac reinforcement learning with rich observations. *arXiv preprint arXiv:1602.02722*, 2016.

[KECM21a] Jeongyeol Kwon, Yonathan Efroni, Constantine Caramanis, and Shie Mannor. Reinforcement learning in reward-mixing mdps. *arXiv preprint arXiv:2110.03743*, 2021.

[KECM21b] Jeongyeol Kwon, Yonathan Efroni, Constantine Caramanis, and Shie Mannor. Rl for latent mdps: Regret guarantees and a lower bound. *arXiv preprint arXiv:2102.04939*, 2021.

[KLLM22] Daniel Kane, Sihan Liu, Shachar Lovett, and Gaurav Mahajan. Computational-statistical gaps in reinforcement learning. *arXiv preprint arXiv:2202.05444*, 2022.

[KMN99] Michael J Kearns, Yishay Mansour, and Andrew Y Ng. Approximate planning in large pomdps via reusable trajectories. In *NIPS*, pages 1001–1007. Citeseer, 1999.

[KS02] Michael Kearns and Satinder Singh. Near-optimal reinforcement learning in polynomial time. *Machine learning*, 49(2):209–232, 2002.

[LCSJ22] Qinghua Liu, Alan Chung, Csaba Szepesvári, and Chi Jin. When is partially observable reinforcement learning not scary? *arXiv preprint arXiv:2204.08967*, 2022.

[LGM01] Christopher Lusena, Judy Goldsmith, and Martin Mundhenk. Nonapproximability results for partially observable markov decision processes. *Journal of artificial intelligence research*, 14:83–103, 2001.

[Lit94] Michael L Littman. Memoryless policies: Theoretical limitations and practical results. *From animals to animats*, 3:238–245, 1994.

[LS17] Tor Lattimore and Csaba Szepesvari. The end of optimism? an asymptotic analysis of finite-armed linear bandits. In *Artificial Intelligence and Statistics*, pages 728–737. PMLR, 2017.

[LYX11] Yanjie Li, Baoqun Yin, and Hongsheng Xi. Finding optimal memoryless policies of pomdps under the expected average reward criterion. *European Journal of Operational Research*, 211(3):556–567, 2011.

[MHKL20] Dipendra Misra, Mikael Henaff, Akshay Krishnamurthy, and John Langford. Kinematic state abstraction and provably efficient rich-observation reinforcement learning. In Hal Daumé III and Aarti Singh, editors, *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pages 6961–6971. PMLR, 13–18 Jul 2020.

[MKKC99] Nicolas Meuleau, Kee-Eung Kim, Leslie Pack Kaelbling, and Anthony R. Cassandra. Solving pomdps by searching the space of finite policies. In *Proceedings of the Fifteenth Conference on Uncertainty in Artificial Intelligence*, UAI'99, page 417–426, San Francisco, CA, USA, 1999. Morgan Kaufmann Publishers Inc.

[Mon82] George E. Monahan. State of the art-a survey of partially observable markov decision processes: Theory, models, and algorithms. *Manage. Sci.*, 28(1):1–16, jan 1982.

[MR05] Elchanan Mossel and Sébastien Roch. Learning nonsingular phylogenies and hidden markov models. *CoRR*, abs/cs/0502076, 2005.

[PB04] Pascal Poupart and Craig Boutilier. Vdcbpi: an approximate scalable algorithm for large pomdps. In *NIPS*, pages 1081–1088. Citeseer, 2004.

[PGT06] Joelle Pineau, Geoffrey Gordon, and Sebastian Thrun. Anytime point-based approximations for large pomdps. *Journal of Artificial Intelligence Research*, 27:335–380, 2006.

[PT87] Christos H Papadimitriou and John N Tsitsiklis. The complexity of markov decision processes. *Mathematics of operations research*, 12(3):441–450, 1987.

[PV08] Pascal Poupart and Nikos Vlassis. Model-based bayesian reinforcement learning in partially observable domains. In *Proc Int. Symp. on Artificial Intelligence and Mathematics,*, pages 1–2, 2008.

[RCdP07] Stephane Ross, Brahim Chaib-draa, and Joelle Pineau. Bayes-adaptive pomdps. In J. Platt, D. Koller, Y. Singer, and S. Roweis, editors, *Advances in Neural Information Processing Systems*, volume 20. Curran Associates, Inc., 2007.

[RG02] Nicholas Roy and Geoffrey J Gordon. Exponential family pca for belief compression in pomdps. *Advances in Neural Information Processing Systems*, 15:1667–1674, 2002.

[RPPCD08] Stéphane Ross, Joelle Pineau, Sébastien Paquet, and Brahim Chaib-Draa. Online planning algorithms for pomdps. *Journal of Artificial Intelligence Research*, 32:663–704, 2008.

[SS12] Trey Smith and Reid Simmons. Heuristic search value iteration for pomdps. *arXiv preprint arXiv:1207.4166*, 2012.

[SV05] Matthijs TJ Spaan and Nikos Vlassis. Perseus: Randomized point-based value iteration for pomdps. *Journal of artificial intelligence research*, 24:195–220, 2005.

[SV10] David Silver and Joel Veness. Monte-carlo planning in large pomdps. Neural Information Processing Systems, 2010.

[SYHL13] Adhiraj Somani, Nan Ye, David Hsu, and Wee Sun Lee. Despot: Online pomdp planning with regularization. *Advances in neural information processing systems*, 26:1772–1780, 2013.

[TK03] Georgios Theocharous and Leslie Kaelbling. Approximate planning in pomdps with macro-actions. *Advances in Neural Information Processing Systems*, 16:775–782, 2003.

[VLB12] Nikos Vlassis, Michael L. Littman, and David Barber. On the computational complexity of stochastic controller optimization in pomdps. *ACM Trans. Comput. Theory*, 4(4), nov 2012.

[WAJ+21] Gellert Weisz, Philip Amortila, Barnabás Janzer, Yasin Abbasi-Yadkori, Nan Jiang, and Csaba Szepesvári. On query-efficient planning in mdps under linear realizability of the optimal state-value function. In *Conference on Learning Theory*, pages 4355–4385. PMLR, 2021.

[WME+22] Xintong Wang, Gary Qiurui Ma, Alon Eden, Clara Li, Alexander Trott, Stephan Zheng, and David C. Parkes. Using reinforcement learning to study platform economies under market shocks, 2022.

[XCGZ21] Yi Xiong, Ningyuan Chen, Xuefeng Gao, and Xiang Zhou. Sublinear regret for learning pomdps. *arXiv preprint arXiv:2107.03635*, 2021.