Ternary Momentum For Quantized Training

Abstract

Quantization enables efficient inference on resource-limited devices, yet training still depends on high-precision gradients and optimizer states. We address this gap by introducing stochastic ternary momentum, a fully quantized optimizer that operates with quantized parameters, ternary gradient information, and enables ternary momentum states for stable and memory efficient quantized optimization. Our method replaces deterministic and full-precision updates with integer-valued updates driven by stochastic sampling, ensuring that expected updates match standard momentum while maintaining strict memory constraints. It eliminates re-quantization overhead and preserves quantization consistency throughout training. We establish theoretical convergence guarantees of our ternary momentum method for convex objectives over bounded integer domains and for non-convex objectives over unbounded integer domains. Experiments on vision and language tasks demonstrate that our approach retains strong performance while reducing optimizer memory by 95% compared to full-precision, advancing the feasibility of fully quantized training.

1 Introduction

Quantization has emerged as a critical technique for deploying deep learning models on resource-constrained devices, as it reduces both memory footprint and computational cost during inference (Courbariaux et al., 2016; Han et al., 2016; Wang et al., 2019b; Jacob et al., 2018; Frantar et al., 2023; Li et al., 2016). However, quantization is typically applied only at deployment, while training still requires substantial memory and high-precision computations, particularly for large models where gradients and optimizer states must be stored (Rajbhandari et al., 2020). The gap between training and deployment requirements becomes more significant when using extremely low-bit-width quantized models, where the difference in resource demands is most pronounced. Successfully addressing the challenge of efficient training holds immense promise: it would unlock the ability to train larger models on devices with limited memory.

When training quantized models, there are three primary sources of memory usage: the *parameters*, which are used during both training and inference, and the *gradients* and *optimizer states*, which are required only during training. In this work, our focus is on memory efficiency during training, specifically low bit-width optimizer states with only ternary gradient information to allow low-resources quantized optimization.

The use of *quantized gradients* is a natural line of research toward memory-efficient training. In this scenario, rather than relying on full precision availability of the gradients, only partial information about them is available. We focus on the case of ternary or binary values that provide extremely coarse approximations of the true gradient. Such estimators have been studied mainly in the context of communication efficiency for distributed learning rather than memory reduction (Wen et al., 2017; Sun et al., 2023; Bernstein et al., 2018; Jiang et al., 2024; Karimireddy et al., 2019a). Those methods are designed for full-precision parameters and optimizer states which suffer from high memory consumption.

Another aspect of memory consumption during training is the use of *high-dimensional full-precision optimizer states* which are required for standard optimization algorithms such as Adam (Kingma & Ba, 2014) and momentum-based methods (e.g., heavy-ball momentum (Polyak, 1964) and Nesterov momentum (Nesterov, 1983; 2013)), leading to substantial memory overhead during training. While several approaches aim to reduce this cost by exploiting the tensorial structure of gradients to lower the dimensionality of optimizer

states (Zhao et al., 2024; Zmushko et al., 2025; Lialin et al., 2024; Luo et al., 2024; Zhang et al., 2025; He et al., 2025; Zhu et al., 2025), a more direct and general strategy is to quantize these states into low-bit representations, independent of their structure. Although previous works have explored 4-bit quantization of optimizer states (Li et al., 2023; Modoranu et al., 2024; Wang et al., 2024; Alistarh et al., 2017), achieving extremely low bit-width representations, such as ternary quantization, remains largely unresolved. The difficulty lies in the reliance of momentum-based methods on averaging techniques that inherently assume continuous-valued states, making them dependent on floating-point storage and computation. A naïve solution is to re-quantize the momentum states after each update, but this often causes severe precision loss under strict bit budgets. The problem becomes even more acute when optimizing quantized parameters: since each update is already coarse, degraded momentum estimates can lead to poor update decisions. In such cases, the accumulation of inaccuracies from both quantized parameters and quantized optimizer states can produce unstable trajectories. Consequently, repeated quantization (whether stochastic or deterministic) may yield updates that are either excessively large or negligibly small, destabilizing or harming the convergence of the optimization process. This fundamental mismatch between the continuous nature of conventional optimizers and the discrete structure of quantized training represents a key bottleneck to achieving truly memory-efficient optimization.

Additionally, when aiming to apply standard optimization methods which are designed for high-precision gradients, with only extremely limited gradient information, it is unclear how they should be adapted to the coarse gradients, how their convergence guarantees extend, and what information their auxiliary states can meaningfully capture. While sign-based optimization methods have recently attracted attention, their integration with conventional optimizers under strict memory constraints on the parameters and optimizer states remains unexplored.

In this work, we address the three memory sources of the optimization. First is the parameter domain, where we restrict the parameters to a small, predefined set of discrete values, $\theta \in \{r_{\min}, ..., r_{\max}\}^d$, where d is the model dimension, with particular emphasis on ternary parameters, $r_{\min} = -1, r_{\max=1}$. The second is the gradient information, which we assume that only ternary gradient information is available, i.e., $\tilde{g} \in \{-1, 0, 1\}^d$. The last is the optimizer states, where we focus specifically on the ternary states with $m \in \{-1, 0, 1\}^d$. This extreme regime poses new challenges for training quantized models. Despite the restrictions, the described setting is increasingly relevant for training under tight memory and computational budgets, where every bit of storage matters. To address this gap, we introduce a tailored optimization method that harnesses low-precision gradients to perform momentum-like updates, making quantized optimization viable even under such conditions.

The contributions of our work can be listed as follows:

Stochastic Ternary Momentum. We introduce stochastic ternary momentum, an optimization method which includes novel modification of first-order momentum methods that enables the optimizer state and updates to be represented entirely with ternary values. The key innovation is to replace deterministic momentum and parameter updates with a random update rule. At each iteration, we sample Bernoulli masks that determine which coordinates of the momentum and parameters are updated. Instead of applying full-precision magnitudes of the updates, they are realized through probabilistic masks that respect ternary constraints with updates that are limited to $+1$, -1 or 0. Our method builds on the availability of ternary gradient approximations, such as sparse zero-sign representations Zhang et al. (2024); Chen et al. (2024); Zhou et al. (2025), discrete non-backward approximations Di Castro et al. (2024), and the seminal TernGrad approach Wen et al. (2017).

Expected Updates Match Deterministic Momentum. Despite relying on discrete updates, our design is principled: we show that the expected updates of both momentum and parameters exactly match their deterministic counterparts when relying on ternary gradient information. This guarantees that the stochasticity introduced for quantization compatibility does not bias the optimization process, while still enabling convergence with low-memory and fully quantized updates.

Quantization-Preserving Optimization. Beyond extreme memory efficiency, a major advantage of our method is that it natively preserves quantization. Unlike conventional approaches, it does not require mixing full-precision and quantized variables, thereby eliminating the repeated overhead of re-quantizing parameters

or optimizer states. This property ensures both consistent quantization throughout training and robustness under tight bit budgets.

Theoretical Convergence Guarantees. To further motivate our ternary momentum optimization algorithm, we establish convergence guarantees for our method assuming deterministic gradient sign access in two different settings. (i) In the case of separable convex functions over a discrete and bounded domain, our algorithm converges to the global optimum. (ii) For minimizing more general smooth non-convex functions over the unbounded integer set, we provide a convergence guarantee to a local minimum, i.e., a critical point.

Experimental Results. We empirically validate our method across diverse architectures and tasks, including image classification on ImageNette and language model fine-tuning with LoRA. Our experiments span ternary parameters, various gradient approximation techniques, and datasets such as IMDB, SST2, COPA, and WinoGrande, using fully connected networks, ViTs, OPT-1.3b and Llama2-7b. Our results demonstrate a reduction in optimizer state memory consumption by a factor of $\log_2(3)/32$ which is equivalent to $\approx 5\%$ compared to the full-precision first-momentum counterpart. Our evaluation demonstrates that our algorithm is both effective and robust, even under extreme memory constraints. These findings highlight the practicality of our approach and open the door to fully quantized optimization in low-resource training environments.

2 Related Work

Quantization. Neural network quantization is primarily used for inference, where post-training quantization (PTQ) methods dominate. In these approaches, models are first trained in full precision using large computational resources and are then quantized and deployed on resource-limited devices (Jacob et al., 2018; Xiao et al., 2023; Frantar et al., 2023; Han et al., 2016; Liu et al., 2021; Wang et al., 2019b; Li et al., 2016). An alternative paradigm is quantization-aware-training (QAT), where parameters are repeatedly quantized during training to better simulate inference-time behavior. However, QAT methods typically assume access to full-precision gradients and rely on optimizers designed for full-precision updates, which therefore require maintaining high-precision optimizer states in memory (Esser et al., 2020; Zhou et al., 2016; Rastegari et al., 2016; Choi et al., 2018; Courbariaux et al., 2015; Dettmers et al., 2022; Wu et al., 2018).

Efficient-Memory Optimizers. Recent work has also explored reducing the memory footprint of optimization algorithms. One line of research designs *low-dimensional* optimizers, where gradients and optimizer states are stored or updated in a low-rank or sparse subspace while maintaining full-precision representations (Zhao et al., 2024; Zmushko et al., 2025; Lialin et al., 2024; Luo et al., 2024; Zhang et al., 2025; He et al., 2025; Zhu et al., 2025; Hao et al., 2024; Liang et al., 2024; Yao et al., 2022; Lin et al., 2018; Stich et al., 2018; Alistarh et al., 2018; Wangni et al., 2018). Another line of work focuses on reducing the number of trainable parameters rather than the optimizer states, a common strategy in fine-tuning. Parameter-Efficient Fine-Tuning (PEFT) methods (Han et al., 2024a; Houlsby et al., 2019; Ben-Zaken et al., 2022; Hu et al., 2022), among which LoRA (Hu et al., 2022) is particularly influential (see Han et al. (2024b) for a comprehensive survey), introduce lightweight low-rank adapters or other compact modules into pretrained models to minimize memory usage during fine-tuning. Although PEFT methods do not directly address optimizer quantization, they naturally result in lower memory usage for gradients and optimizer states due to the reduced number of trainable parameters.

Optimizer States Quantization. The works most relevant to ours are those that explicitly quantize the optimizer states, including methods designed for Adam (Zhang et al., 2025; Modoranu et al., 2024) and other optimizers (Wang et al., 2024; Li et al., 2023). However, these approaches typically assume access to full-precision gradients and often rely on relatively high bitwidths (e.g., 4 bits), which limits their applicability in highly resource-constrained training settings.

Sign- and Ternary-Based Optimization without Gradients. Another relevant line of research investigates sign-based or ternary gradient methods, which avoid storing or computing full-precision gradients (Di Castro et al., 2024; Bar & Giryes, 2025; Zhou et al., 2025). These approaches aim to reduce computational and memory costs, but they often employ simple update rules and do not incorporate more sophisticated optimizer dynamics that can stabilize or accelerate training.

Our work targets a highly constrained yet practical setting where only a ternary approximation of the gradients is available. We further maintain all optimizer states within small bitwidth representations (ternary states), enabling both memory and computational efficiency without relying on full-precision gradient access.

3 Background and Problem Setup

In the following section we list the relevant background for our ternary momentum algorithm.

Full-Precision Optimization with Momentum. We begin by recalling the standard optimization setup involving gradient access and momentum. The objective is to minimize a differentiable loss function $\mathcal{L} : \mathbb{R}^d \to \mathbb{R}$. Starting from initial parameters $\theta_0 \in \mathbb{R}^d$, at each iteration $t = 1, \ldots, T$, we obtain a noisy gradient estimate $g_t \in \mathbb{R}^d$ of the true gradient $\nabla \mathcal{L}(\theta_{t-1})$ and determine the next iterate θ_t based on the previously observed (noisy) gradients. Typically, this noisy estimate is computed using a randomly sampled mini-batch of training data.

To mitigate the stochastic noise in this process, the heavy-ball method (Polyak, 1964) maintains a running average of past gradients, $m_t = \beta m_{t-1} + (1 - \beta)g_t$, with $m_0 = 0$ and a momentum parameter $\beta \in (0, 1)$. These updates require high-dimensional real optimizer states that are stored in floating-point memory. The parameter update rule is then given by $\theta_t = \theta_{t-1} - \eta_t m_t$, where η_t denotes the learning rate at step t.

Quantized Setting. In the quantized optimization setting, the parameter space is restricted to discrete values. Specifically, we assume $\theta_t \in \mathbb{Z}^d$, with each coordinate bounded between some integers $r_{\min}$ and $r_{\max}$. Throughout this work, we mainly focus on the ternary case, where $r_{\min} = -1$ and $r_{\max} = 1$, so that $\theta_t \in \{-1, 0, 1\}^d$. In addition, we assume access to a quantized gradient information oracle, denoted by $\text{TernGrad}(\theta)$, which given the current parameters θ_t returns a ternary gradient approximation $\tilde{g} \in \{-1, 0, 1\}^d$. The optimization objective remains the same—to minimize the loss $\mathcal{L}(\theta)$—but under the strict constraint that the parameters must remain within the discrete and bounded range at all times.

In this work, we propose an optimization scheme that employs ternary momentum, offering high memory efficiency while preserving optimization effectiveness. We consider the setting where the momentum is restricted to discrete ternary values, $m_t \in \{-1, 0, 1\}^d$, and depends solely on ternary gradient information, $\tilde{g} \in \{-1, 0, 1\}^d$. Furthermore, our objective is to learn discrete model parameters, $\theta_t \in [r_{\min}, r_{\max}] \subset \mathbb{Z}$, that remain discrete throughout the optimization process.

3.1 Naive Quantized Optimization with Ternary Gradients

Optimization without momentum. A straightforward approach to quantized optimization with ternary gradient information is to update the parameters directly using only the ternary gradient, $\theta_t = \theta_{t-1} - \tilde{g}_t$. However, such updates can be overly aggressive, often causing instability in the optimization process. A natural remedy is to scale the update by a learning rate, $\theta_t = \theta_{t-1} - \eta_t \tilde{g}_t$ but this introduces a weakness: it requires mixed-precision operations between the quantized θ_t and the floating-point $\eta_t \tilde{g}_t \in \mathbb{R}^d$. Hence, the parameters θ_t must be repeatedly quantized after each step, reintroducing instability and computational overhead.

Optimization with momentum. Another natural attempt to stabilize training is to incorporate momentum into the ternary gradient approximation. In this case, the moving average produces real-valued momentum states, $m_t = \beta m_{t-1} + (1 - \beta)\tilde{g}_t \in \mathbb{R}^d$, which in turn yield real-valued parameter updates, $\theta_t = \theta_{t-1} - \eta_t m_t \in \mathbb{R}^d$. To enforce quantization, both the parameters and optimizer states must be re-quantized after every update. Yet, under the aggressive quantization regime considered in this work, repeated re-quantization amplifies the mismatch between the continuous dynamics and their quantized counterparts, leading to updates that are either vanishingly small or excessively large, depending on the hyperparameters. This ultimately undermines stability and prevents reliable convergence.

Algorithm 1 Ternary First Moment

Input: $\theta_0 \in \{r_{\min}, \ldots, r_{\max}\}^d$ with integers $r_{\min} < r_{\max}$, learning rate $\{\eta_t\}_{t=1}^T$, momentum coefficient β, TernGrad ternary gradient algorithm, and bounds $r_{\min}, r_{\max}$.
Initialize: $m_0 = 0$

for $t = 1, \ldots, T$ **do**
    Compute ternary gradient approximation: $\tilde{g}_t = \mathrm{TernGrad}(\theta_{t-1})$
    Update momentum:
        Sample vector $e_t^{(m)} \sim \mathrm{Bernoulli}(\beta)$ i.i.d. element-wise where $e_t^{(m)} \in \{0,1\}^d$.
        Momentum Update: $m_t = e_t^{(m)} \odot m_{t-1} + (1 - e_t^{(m)}) \odot \tilde{g}_t$
    Update parameters:
        Sample vector $e_t^{(\theta)} \sim \mathrm{Bernoulli}(\eta_t)$ i.i.d. element-wise where $e_t^{(\theta)} \in \{0,1\}^d$.
        Update rule: $\theta_t = \mathrm{clamp}_{[r_{\min}, r_{\max}]}\{\theta_{t-1} - e_t^{(\theta)} \odot m_t\}$
end for
Return optimized parameters θ_T

---

4 Optimization with Ternary Gradient and Momentum

In this section, we present our momentum-based optimization method designed specifically for the setting of quantized parameters, ternary gradients, and quantized first-order momentum. The method is detailed in Algorithm 1.

The required inputs to our algorithm are quantized initial parameters that are bounded by $r_{\min}$ and $r_{\max}$, learning rate η_t that can be adapted over time, a momentum coefficient, and a function for acquiring the ternary approximation of the gradient. At each iteration t, we get the ternary information of the gradient using the TernGrad function. Then, unlike standard momentum updates that involve floating-point arithmetic (e.g. $m_t = \beta m_{t-1} + (1 - \beta)g_t$), our approach employs a ternary Bernoulli approximation of the momentum. Specifically, for each entry, we sample a binary random variable $e_t^{(m)} \in \{0,1\}$ from a Bernoulli distribution with parameter β. This forms a vector $e_t^{(m)} \in \{0,1\}^d$, which then dictates element-wise the momentum update: if $e_{t,i}^{(m)} = 1$, the i-th component of the momentum $m_{t,i}$ retains its previous value $m_{t-1,i}$; otherwise, if $e_{t,i}^{(m)} = 0$, it is replaced by the corresponding component of the current ternary gradient $\tilde{g}_{t,i}$. This is formally expressed as:

$$m_t = e_t^{(m)} \odot m_{t-1} + (1 - e_t^{(m)}) \odot \tilde{g}_t, \quad e_t^{(m)} \sim \mathrm{Bernoulli}(\beta). \tag{1}$$

The β hyperparameter controls the probability of which we rely on past approximations that are stored in the momentum, for higher values of β the updates rely more heavily on the history. This stochastic design is critical because it intrinsically ensures that the momentum m_t remains confined to ternary values, thus avoiding the need for high-precision storage and mitigating memory demands.

Next, we describe the parameter update step. Instead of directly applying a floating-point learning rate (e.g., $\theta_t = \theta_{t-1} - \eta_t m_t$), we again leverage a Bernoulli approximation. For each parameter $\theta_{t,i}$, a binary random variable $e_{t,i}^{(\theta)} \in \{0,1\}$ is sampled from a Bernoulli distribution with parameter η_t (the learning rate). This generates a vector $e_t^{(\theta)} \in \{0,1\}^d$. The parameter update then becomes $\theta_t = \theta_{t-1} - e_t^{(\theta)} \odot m_t$. This effectively means that each parameter is updated by its corresponding momentum component only with a probability equal to the learning rate η_t.

Unbiased Updates Property. Our stochastic update rules of the momentum and parameters are motivate by their expected behavior. Despite the use of integer values, the stochastic nature of the updates maintains consistency with full-precision optimization. In expectation, the updates for both the momentum and the parameters precisely match their full-precision counterparts. Formally,

$$\mathbb{E}[m_t | m_{t-1}, \tilde{g}_t] = \beta m_{t-1} + (1 - \beta)\tilde{g}_t, \quad \text{and} \quad \mathbb{E}[\theta_t | \theta_{t-1}, m_t] = \theta_{t-1} - \eta_t m_t.$$

This theoretical equivalence is crucial as it suggests that the algorithm may achieve similar convergence properties to traditional methods with access to ternary gradients while operating under severe memory and precision constraints.

Our proposed ternary momentum algorithm enjoys several significant strengths, particularly for constrained environments. We summarize them below:

- **Significant Memory Reduction.** The main gain of using ternary momentum is a substantial memory reduction of the storage of the optimizer states compared to traditional full-precision first momentum. For instance, when compared to storing full-precision (32-bit float) momentum states, our ternary representation reduces the memory footprint by a factor of approximately $\frac{\log_2(3)}{32} \approx 0.048$ (or roughly 5%), which is highly advantageous for memory-limited edge devices.

- **Integer-Only Optimization without Mixed Precision.** Unlike conventional training and quantized-aware-training methods that require floating-point calculations for all parameters in each update step, our approach ensures that model parameters θ remain integers throughout the optimization process. This holds also for the momentum updates. Thus, we eliminate the computational overhead and potential precision loss associated with repeated quantization steps during training. As a result of integer preserving design of our algorithm, there is no need to use mixed-precision operations. Both parameter and momentum updates are performed using a randomized mask, $e^{(m)}$ and $e^{(\theta)}$, and integer arithmetic. Thus, with the use of our method, we avoid costly additions and multiplications operations between full-precision and floating-point variables.

- **Regulating the Expected Number of Changes.** In quantized optimization, the number of parameter changes is an indicator of training efficiency, as each change corresponds to flipping a discrete value in memory. Such flips cause energy consumption in low-precision hardware, making the change count a proxy for energy efficiency (Stutz et al., 2021). In our algorithm, this quantity can be controlled in a principled manner by different values of hyperparameters. A large momentum coefficient β reduces the variability of the momentum vector, leading to fewer expected updates, approximately $(1-\beta)d$ per iteration. Similarly, the learning rate η_t directly influences the probability of flipping a quantized parameter, with smaller values resulting in fewer changes. Together, these mechanisms allow explicit regulation over energy efficiency yielded from flipping parameters.

5 Theoretical Analysis

Next, we present a theoretical convergence analysis of our ternary first-moment algorithm (Algorithm 1) under different assumptions on the loss function and parameter domain. Throughout, we assume that the loss function satisfies the following element-wise smoothness assumption.

Definition 1 (Element-wise smoothness). *A differentiable function $f : \mathbb{R}^d \to \mathbb{R}$ is element-wise $\boldsymbol{L} = (L_1, \ldots, L_d)$-smooth for $L_1, \ldots, L_d \geq 0$, if for any $x, y \in \mathbb{R}^d$,*

$$|f(y) - (f(x) + \nabla f(x) \cdot (y - x))| \leq \frac{1}{2} \sum_{i=1}^{d} L_i (y_i - x_i)^2.$$

This assumption, previously used in the analysis of SignSGD (Bernstein et al., 2018), naturally captures heterogeneous curvature across coordinates and is well suited to sign-based methods, where each coordinate update has a fixed magnitude.

In addition to the smoothness assumption, we distinguish between two settings:

1. **Separable, convex, and smooth setting.** We assume that the objective is separable, i.e., of the form $\mathcal{L}(\theta) = \sum_{i=1}^{d} \mathcal{L}_i(\theta_i)$, where each $\mathcal{L}_i : \mathbb{R} \to \mathbb{R}$ is convex and L_i-smooth for $i = 1, \ldots, d$. This is equivalent to assuming that the separable function $\mathcal{L}(\theta)$ itself is convex and $\boldsymbol{L}$-smooth, where $\boldsymbol{L} = (L_1, \ldots, L_d)$. In this setting, convergence is measured in terms of loss suboptimality, $\mathcal{L}(\theta) - \min_{\theta'} \mathcal{L}(\theta')$.

2. **Non-convex and smooth setting.** Here we assume that $\mathcal{L} : \mathbb{R}^d \to \mathbb{R}$ is element-wise $\boldsymbol{L}$-smooth but not necessarily separable or convex. To accommodate this broader function class, we analyze Algorithm 1 in the case where $r_{\min} = -\infty$ and $r_{\max} = \infty$, i.e., no clipping is applied. As is standard in non-convex optimization, convergence is measured in terms of the gradient norm, which reflects convergence to a critical point.

We focus on these two settings, rather than a more general convex or non-convex formulation, due to the intrinsic limitations of sign-based methods with quantized updates of the form $\theta_t - \theta_{t-1} \in \{-1, 0, 1\}^d$. As demonstrated by Karimireddy et al. (2019b), even the simpler SignSGD method fails to converge in certain worst-case instances for more general classes of such problems.

Finally, for ternary gradient information, we use the element-wise deterministic sign operator over the deterministic gradient at time t,

$$\tilde{g}_t = \text{sign}(\nabla \mathcal{L}(\theta_t)) = \begin{cases} +1 & \text{if } \nabla \mathcal{L}(\theta_t) > 0; \\ 0 & \text{if } \nabla \mathcal{L}(\theta_t) = 0; \\ -1 & \text{if } \nabla \mathcal{L}(\theta_t) < 0. \end{cases}$$

We focus on the deterministic setting for simplicity. In stochastic settings, a common strategy to mitigate gradient noise is to employ a very large batch size (Bernstein et al., 2018), effectively reducing the problem to a (semi-)deterministic problem.

5.1 Separable, Convex and Smooth Objectives

Following, we formally detail the high-probability suboptimality guarantee for Algorithm 1 given a separable, convex and element-wise smooth objective.

Theorem 1. *Let $\delta \in (0, 1)$, $\beta \in (0, 1)$, integers $r_{\min} < r_{\max}$, a separable, convex, and element-wise $\boldsymbol{L}$-smooth function $\mathcal{L}(\theta) = \sum_{i=1}^d \mathcal{L}_i(\theta_i)$, and $\theta_0 \in \{r_{\min}, \dots, r_{\max}\}^d$. For any $T \geq r_{\max} - r_{\min} + \Delta_\beta$, where $\Delta_\beta \triangleq \lceil \log_\beta(\delta/(dT)) \rceil = \lceil \log(dT/\delta)/\log(1/\beta) \rceil$, consider the output θ_T produced by Algorithm 1 with parameters $\theta_0, r_{\min}, r_{\max}, \beta, \eta_t = 1$ for $t = 1, \dots, T$, and the deterministic signed gradient as* TernGrad. *Then with probability at least $1 - \delta$,*

$$\mathcal{L}(\theta_T) - \min_{\theta' \in [r_{\min}, r_{\max}]^d} \mathcal{L}(\theta') \leq \frac{1}{2} \|\boldsymbol{L}\|_1 \lceil \log(dT/\delta)/\log(1/\beta) \rceil^2,$$

where the probability is with respect to the random masks $e_t^{(m)}$ for $t = 1, \dots, T$.

For a sufficiently large number of steps, Theorem 1 establishes a convergence rate of $\widetilde{O}(\|\boldsymbol{L}\|_1)$. Up to logarithmic factors, this rate is essentially tight: in the worst case, the distance from the minimizer along each coordinate is lower bounded by half the update magnitude, resulting in a worst-case suboptimality of $\Omega(\|\boldsymbol{L}\|_1)$. For example, this lower bound is attained for a simple quadratic objective $\sum_{i=1}^d L_i(x_i - 0.5)^2$.

The proof of Theorem 1, provided in Appendix B.1, relies on two key observations. First, due to separability, the gradient with respect to each coordinate always points toward the minimizer. Second, with high probability, the momentum term cannot drive the iterate away from the minimizer for more than a logarithmic number of steps; afterward, the coordinate necessarily returns toward the minimizer.

While the objective studied in this section is simplified and may not capture all practical scenarios, it provides a controlled test bed that reveals the behavior of our method near a minimizer, offering essential theoretical insight into its properties.

5.2 Non-Convex Smooth Objectives

The result in Section 5.1 addresses a relatively restrictive family of objective functions. We now turn to a more general class of non-convex smooth functions. In this broader setting, we necessarily provide a weaker form of guarantee. Specifically: (1) we no longer assume bounded coordinates, that is, $r_{\min} = -\infty$ and

		IMDB	ImageNette Hybrid 1	ImageNette Hybrid 2
	# of parameters	19.9M	38.33M	38.33M
	# of Ternary	19.9M	25.1M	37.3M
FP		87.3	90.8	
Deterministic	No Momentum	86.75	83.6	78.32
	FP Momentum	86.19	86.78	**82.89**
	Ternary Momentum	**86.86**	**87.69**	81.44
Stochastic	No Momentum	85.27	89.58	85.46
	FP Momentum	82.9	89.58	85.29
	Ternary Momentum	**85.28**	**89.62**	**86.35**
No Backward	No Momentum	83.04	85.1	75.0
	FP Momentum	85.29	83.97	71.44
	Ternary Momentum	**85.57**	**88.23**	**79.4**

Table 1: Accuracy for training from scratch with multiple ternary gradient approximation methods.

	Theoretical	Fully Connected	Hybrid 1	Hybrid 2	OPT-1.3b LoRA	Llama2-7b LoRA
No Momentum	0	0	0	0	0	0
FP Momentum	d	79.6	95.75	142.2	6	16.78
Ternary Momentum	$d/\log_2(3)$	3.94	4.74	7.1	0.3	0.84

Table 2: Optimizer states memory in MB.

$r_{\max} = \infty$, resulting in optimization over $\mathbb{Z}^d$; and (2) the convergence guarantee concerns minimizing the average ℓ_1-norm of the gradients rather than the loss suboptimality.[1]

Theorem 2. *Let $\mathcal{L} : \mathbb{R}^d \to \mathbb{R}$ be an element-wise $\boldsymbol{L}$-smooth function lower bounded by some $\mathcal{L}^\star \in \mathbb{R}$. Let $\theta_0 \in \mathbb{Z}^d$ and consider the sequence $(\theta_t)_{t=0}^T$ generated by Algorithm 1 with parameters $\theta_0, r_{\min} = -\infty, r_{\max} = \infty, \beta \in (0,1), \eta_t = 1$ for $t = 1, \ldots, T$, and the deterministic signed gradient as* TernGrad. *Then it holds that*

$$\frac{1}{T} \sum_{t=1}^T \mathbb{E}[\|\nabla \mathcal{L}(\theta_{t-1})\|_1] \leq \frac{\mathcal{L}(\theta_0) - \mathcal{L}^\star}{(1-\beta)T} + \frac{(1+5\beta)\|\boldsymbol{L}\|_1}{2(1-\beta)^2}.$$

Similar to Theorem 1, the result above guarantees convergence to a neighborhood of size $O(\|\boldsymbol{L}\|_1)$, which is unavoidable due to the fixed magnitude of the updates. On the other hand, Theorem 2 complements Theorem 1 by showing that the algorithm converges, in terms of the average gradient norm, for a broader class of objectives. Note that while Theorem 2 fixes $\eta_t = 1$ for $t = 1, \ldots, T$, we prove a more general version that supports arbitrary $\eta_1, \ldots, \eta_T$, including the schedules $\eta_t = 1/t$ and $\eta_t = 1/\sqrt{t}$, although these schedules yield a slower convergence rate. See Appendix B.2 for full details.

Taken together, these results help explain the practical success of Algorithm 1 on favorable objectives–either when the optimization landscape exhibits separability, or when convergence to a critical point corresponds to strong empirical performance, as is often implicitly assumed when applying gradient-based methods to non-convex problems.

---

[1]Convergence in non-convex optimization is commonly expressed in terms of minimizing the gradient norm, which corresponds to finding an approximate critical point (Ghadimi & Lan, 2013; Arjevani et al., 2022).

6 Experiments

We evaluate our proposed method across both image and language domains using various models to demonstrate its effectiveness and versatility. We include various datasets, tasks, and ternary gradient approximation methods.

Datasets and Tasks

1. **Sentiment Analysis with IMDB:** We perform sentiment analysis using the IMDB dataset, leveraging BERT features (Devlin et al., 2019). The model architecture consists of a fully-connected network with three layers, each having a hidden width of 4096.

2. **Image Classification with ImageNette:** We utilize a subset of ImageNet, known as ImageNette (Howard, 2019), which consists of 10 classes. For this task, we employ the Vision Transformer (ViT) architecture (Dosovitskiy, 2020). We investigate two variants of our method: Hybrid 1 Variant: In this configuration, we replace the feed-forward network in each transformer layer with ternary weights. Hybrid 2 Variant: This variant further involves replacing the key (K), query (Q), and value (V) matrices in the attention block while retaining the prediction head in full-precision. The exact number of ternary parameters used in both variants is detailed in Table 1.

3. **Fine-Tuning of Language Models:** We fine-tune OPT-1.3b (Zhang et al., 2022) and Llama2-7b (Touvron et al., 2023) language models for with SST-2 (Socher et al., 2013), COPA (Wang et al., 2019a) and WinoGrande (Sakaguchi et al., 2021)datasets using LoRA. In this setup, all learned parameters are ternary, while the parameters that remain frozen are maintained in full precision. LoRA which lowers the dimension of learned parameters during fine-tuning is highly compatible with our method's aim to reduce memory during training. Importantly, since our method requires the initial parameters to be discrete fine-tuning all the parameters with our algorithm require some post training quantization. Hence, we use LoRA fine-tuning which introduces new parameters during fine-tuning so we initialize them in a quantized manner.

Ternary Gradient Approximations

Our method requires access to ternary approximation that is possible acquired in an efficient way. However, in our experiments we mostly simulate this approximation. We use different methods for ternarizing the gradient during optimization:

1. **Deterministic Ternarization:** In this approach, 10% of the full gradient entries with the smallest magnitude are set to 0, while the remaining entries are assigned values based on their sign.

2. **TernGrad (Wen et al., 2017):** A widely known approach samples the sparsity mask according to the gradient magnitudes, after which a sign operator is applied to the selected non-zero entries.

3. **No Backward (Di Castro et al., 2024):** This method does not involve a backward pass, providing an efficient alternative for gradient estimation.

4. **Sparse Zero-Order (ZO) (Zhang et al., 2024):** This method employs a zero-order optimization approach (Liu et al., 2019) to estimate the gradient sign. Specifically, it perturbs the parameters by adding and subtracting small noise and determines the gradient sign based on the corresponding increase or decrease in the loss value. The sparsity arises from zeroing a randomly selected subset of parameters, where 30% of them are non-zero.

Deterministic and TernGrad ternary gradient approximation methods require full access to the gradients and are therefore used primarily as simulations. In contrast, the latter two methods do not rely on gradient information, making them more suitable for the studied use case. Additionally, although the Sparse ZO approximation does not require full gradient access, the parameter perturbations it introduces still necessitate storing a full-precision copy of the model, which increases memory requirements.

Model		SST2 OPT-1.3b	COPA Llama2-7b	WinoGrande Llama2-7b
FP		96.66	85	69.5
Deterministic	No Momentum	93.01	73	68.6
	Ternary Momentum	**93.35**	**76**	**70.2**
Stochastic	No Momentum	93.58	84	**66.6**
	Ternary Momentum	**93.69**	**85**	66.1
No Backward	No Momentum	93.23	80	68.5
	Ternary Momentum	**93.46**	**83**	**68.9**
Sparse ZO	No Momentum	93.35	**84**	67.4
	Ternary Momentum	**93.39**	**84**	**68.3**

Table 3: Results of fine-tuning with LoRA with SST2, COPA, and WinoGrande.

Optimizer Baselines

We compare our method with two optimizers which are very relevant to the scenario we are focused on.

1. **Stochastic Updates without Momentum:** The update steps are chosen according to a randomly sampled masks, but no momentum is used. The update step is $\theta_t = \theta_{t-1} - e_t^{(\theta)} \tilde{g}_t$ where $e_t^{(\theta)} \sim$ Bernoulli(η_t) (as in the parameter update step in Algorithm 1). Note that this baseline is memory efficient since it does not require storing 1-bit optimizer states (see Table 2).

2. **Full-Precision Momentum:** The update steps are applied according to full-precision momentum. The momentum updates are $m_t = \beta m_{t-1} + (1 - \beta)\tilde{g}_t$ and the parameter updates are performed with stochastic rounding $\theta_t = SR(\theta_{t-1} - e_t^{(\theta)} \tilde{g}_t)$ where $e_t^{(\theta)} \sim$ Bernoulli(η_t). Note that the original optimizer relies on full-precision gradients, and its effectiveness under limited gradient information, such as in the case of ternary gradient approximation, remains unexplored. Most importantly, additional full-precision optimizer states are required to be stored.

We follow the experimental setup of Di Castro et al. (2024) for Table 1 and the Zero-Order Optimization Benchmarking framework (Zhang et al., 2024) for Table 3. In all experiments, we use a learning rate of $0.75/t$, which depends on the iteration number, following Di Castro et al. (2024). In Appendix A, we provide additional details on the hyperparameter used and hyperparameter search for the learning rate and momentum coefficient.

6.1 Results

Training from scratch. Our initial experiments on standard classification datasets (Table 1) demonstrate that the proposed ternary first momentum method effectively learns a model from scratch across diverse tasks. We observe that our method, employing all ternary approximation strategies, generally outperforms the quantized baselines, affirming the benefits of incorporating even an extremely low precision momentum for effective optimization.

As expected, all tested configurations exhibit some degradation in accuracy compared to their full-precision training (parameters and optimizer states) counterparts. However, these differences are often small, suggesting that models trained with ternary momentum can achieve competitive performance on standard classification tasks. Specifically, when both parameters and momentum are ternary, we observe an accuracy degradation of up to 2% for IMDB, 3.1% for ImageNette with Hybrid 1, and 9.5% for ImageNette with Hybrid 2. This pattern suggests that the degradation tends to increase as the number of ternary parameters being optimized grows.

Notably, in the ImageNette Hybrid 2 task with deterministic ternary approximation, our ternary momentum method showed some degradation compared to the full-precision baseline, likely due to higher sensitivity to gradient quantization noise in this larger and deeper model. Nevertheless, it still outperformed the no-momentum baseline, highlighting its robustness and strong memory–efficiency trade-off as detailed below.

Fine-Tuning LLMs with LoRA. The results for fine-tuning LLMs with LoRA (Table 3) further underscore the practical utility of our ternary momentum method. We observe that our approach generally achieves superior performance compared to optimizing ternary models with ternary gradients without momentum across various downstream tasks. This demonstrates that the stochastically approximated momentum effectively enhances optimization stability and performance, even when applied to large, pre-trained models.

Our method's inherent memory efficiency complements LoRA, which reduces the number of trainable parameters. By minimizing the optimizer state footprint, the ternary first-momentum method enables fine-tuning of larger models under tight memory constraints. Combined with ternary gradients, it achieves predominantly ternary memory usage for both gradients and momentum, yielding substantial overall memory savings during training.

Notably, we observed a minor performance degradation specifically for the WinoGrande dataset when using a stochastic ternary approximation. We hypothesize this particular instance of degradation may be attributed to the inherent noise and adversarial nature of the WinoGrande dataset interacting unfavorably with the stochastic momentum.

Memory of optimizer states. Table 2 comprehensively details the memory required for optimizer states across various models. The results clearly demonstrate the drastic reduction of memory footprint compared to full-precision momentum optimizers. Specifically, our method is using only $\log_2(3)/32 \approx 5\%$ for the first momentum buffer compared to a full-precision momentum. While naturally requiring more memory than an optimizer completely devoid of momentum, the ternary momentum memory cost is demonstrably minimal for the performance gains it provides, presenting an optimized trade-off. This magnitude of memory savings becomes particularly critical for very large models, where memory constraints are often the primary training bottleneck.

These findings demonstrate the ternary momentum method's position as a highly effective and memory-efficient optimization strategy for large-scale machine learning, particularly beneficial in resource-constrained environments.

7 Conclusion, Future Work and Limitations

In this work, we introduce a ternary first-momentum optimization algorithm, provide theoretical motivation for its design, and demonstrate its empirical potential. Our results show that optimizer states can retain meaningful information even under an extremely low bit-width setting with ternary quantization.

While the proposed method demonstrates promising results, its practical applicability is currently limited by the lack of efficient and accurate ternary gradient approximation mechanisms that operate in a fully quantized manner.

This work opens several directions for future research. One promising avenue is extending the approach to stochastic and quantized variants of second-momentum optimizers. Additionally, combining low bit-width quantization with low-dimensional optimization techniques could further enhance memory and computational efficiency. Another interesting direction is to explore adaptive masking strategies, where the update mask is sampled based on a dedicated saliency score rather than being uniformly applied across parameters.

References

Dan Alistarh, Demjan Grubic, Jerry Li, Ryota Tomioka, and Milan Vojnovic. Qsgd: Communication-efficient sgd via gradient quantization and encoding. *Advances in neural information processing systems*, 30, 2017.

Dan Alistarh, Torsten Hoefler, Mikael Johansson, Nikola Konstantinov, Sarit Khirirat, and Cédric Renggli. The convergence of sparsified gradient methods. *Advances in Neural Information Processing Systems*, 31,

2018.

Yossi Arjevani, Yair Carmon, John C Duchi, Dylan J Foster, Nathan Srebro, and Blake Woodworth. Lower bounds for non-convex stochastic optimization. *Mathematical Programming*, pp. 1–50, 2022.

Noga Bar and Raja Giryes. Zoqo: Zero-order quantized optimization. In *ICASSP 2025-2025 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 1–5. IEEE, 2025.

Elad Ben-Zaken, Shauli Ravfogel, and Yoav Goldberg. Bitfit: Simple parameter-efficient fine-tuning for transformer-based masked language-models. In *60th Annual Meeting of the Association for Computational Linguistics, ACL 2022*, pp. 1–9. Association for Computational Linguistics (ACL), 2022.

Jeremy Bernstein, Yu-Xiang Wang, Kamyar Azizzadenesheli, and Animashree Anandkumar. signsgd: Compressed optimisation for non-convex problems. In *International conference on machine learning*, pp. 560–569. PMLR, 2018.

Aochuan Chen, Yimeng Zhang, Jinghan Jia, James Diffenderfer, Konstantinos Parasyris, Jiancheng Liu, Yihua Zhang, Zheng Zhang, Bhavya Kailkhura, and Sijia Liu. Deepzero: Scaling up zeroth-order optimization for deep model training. In *The Twelfth International Conference on Learning Representations*, 2024.

Jungwook Choi, Zhuo Wang, Swagath Venkataramani, Pierce I-Jen Chuang, Vijayalakshmi Srinivasan, and Kailash Gopalakrishnan. Pact: Parameterized clipping activation for quantized neural networks. *arXiv preprint arXiv:1805.06085*, 2018.

Matthieu Courbariaux, Yoshua Bengio, and Jean-Pierre David. Binaryconnect: Training deep neural networks with binary weights during propagations. *Advances in neural information processing systems*, 28, 2015.

Matthieu Courbariaux, Itay Hubara, Daniel Soudry, Ran El-Yaniv, and Yoshua Bengio. Binarized neural networks: Training deep neural networks with weights and activations constrained to+ 1 or-1. *arXiv preprint arXiv:1602.02830*, 2016.

Tim Dettmers, Mike Lewis, Younes Belkada, and Luke Zettlemoyer. Gpt3. int8 (): 8-bit matrix multiplication for transformers at scale. *Advances in neural information processing systems*, 35:30318–30332, 2022.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 conference of the North American chapter of the association for computational linguistics: human language technologies, volume 1 (long and short papers)*, pp. 4171–4186, 2019.

Dotan Di Castro, Omkar Joglekar, Shir Kozlovsky, Vladimir Tchuiev, and Michal Moshkovitz. Gradient-free neural network training on the edge. *arXiv preprint arXiv:2410.09734*, 2024.

Alexey Dosovitskiy. An image is worth 16x16 words: Transformers for image recognition at scale. *arXiv preprint arXiv:2010.11929*, 2020.

Steven K. Esser, Jeffrey L. McKinstry, Deepika Bablani, Rathinakumar Appuswamy, and Dharmendra S. Modha. Learned step size quantization. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=rkgO66VKDS.

Elias Frantar, Saleh Ashkboos, Torsten Hoefler, and Dan-Adrian Alistarh. Optq: Accurate post-training quantization for generative pre-trained transformers. In *11th International Conference on Learning Representations*, 2023.

Saeed Ghadimi and Guanghui Lan. Stochastic first-and zeroth-order methods for nonconvex stochastic programming. *SIAM Journal on Optimization*, 23(4):2341–2368, 2013.

Andi Han, Jiaxiang Li, Wei Huang, Mingyi Hong, Akiko Takeda, Pratik Kumar Jawanpuria, and Bamdev Mishra. Sltrain: a sparse plus low rank approach for parameter and memory efficient pretraining. *Advances in Neural Information Processing Systems*, 37:118267–118295, 2024a.

Song Han, Huizi Mao, and William J Dally. Deep compression: Compressing deep neural network with pruning, trained quantization and huffman coding. In *ICLR*, 2016.

Zeyu Han, Chao Gao, Jinyang Liu, Jeff Zhang, and Sai Qian Zhang. Parameter-efficient fine-tuning for large models: A comprehensive survey. *arXiv preprint arXiv:2403.14608*, 2024b.

Yongchang Hao, Yanshuai Cao, and Lili Mou. Flora: Low-rank adapters are secretly gradient compressors. In *International Conference on Machine Learning*, pp. 17554–17571. PMLR, 2024.

Yutong He, Pengrui Li, Yipeng Hu, Chuyan Chen, and Kun Yuan. Subspace optimization for large language models with convergence guarantees. In *Proceedings of the 42nd International Conference on Machine Learning*, volume 267 of *Proceedings of Machine Learning Research*, pp. 22468–22522. PMLR, 2025.

Neil Houlsby, Andrei Giurgiu, Stanislaw Jastrzebski, Bruna Morrone, Quentin De Laroussilhe, Andrea Gesmundo, Mona Attariyan, and Sylvain Gelly. Parameter-efficient transfer learning for nlp. In *International conference on machine learning*, pp. 2790–2799. PMLR, 2019.

Jeremy Howard. Imagenette: A smaller subset of 10 easily classified classes from imagenet. *GitHub*, March 2019. URL https://github.com/fastai/imagenette.

Edward J Hu, yelong shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. LoRA: Low-rank adaptation of large language models. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=nZeVKeeFYf9.

Benoit Jacob, Skirmantas Kligys, Bo Chen, Menglong Zhu, Matthew Tang, Andrew Howard, Hartwig Adam, and Dmitry Kalenichenko. Quantization and training of neural networks for efficient integer-arithmetic-only inference. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 2704–2713, 2018.

Wei Jiang, Sifan Yang, Wenhao Yang, and Lijun Zhang. Efficient sign-based optimization: Accelerating convergence via variance reduction. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*, 2024. URL https://openreview.net/forum?id=uaNZvF1VFe.

Sai Praneeth Karimireddy, Quentin Rebjock, Sebastian Stich, and Martin Jaggi. Error feedback fixes signsgd and other gradient compression schemes. In *International conference on machine learning*, pp. 3252–3261. PMLR, 2019a.

Sai Praneeth Karimireddy, Quentin Rebjock, Sebastian Stich, and Martin Jaggi. Error feedback fixes SignSGD and other gradient compression schemes. In Kamalika Chaudhuri and Ruslan Salakhutdinov (eds.), *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pp. 3252–3261. PMLR, 09–15 Jun 2019b.

Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *CoRR*, abs/1412.6980, 2014. URL https://api.semanticscholar.org/CorpusID:6628106.

Bingrui Li, Jianfei Chen, and Jun Zhu. Memory efficient optimizers with 4-bit states. *Advances in Neural Information Processing Systems*, 36:15136–15171, 2023.

Fengfu Li, Bin Liu, Xiaoxing Wang, Bo Zhang, and Junchi Yan. Ternary weight networks. *arXiv preprint arXiv:1605.04711*, 2016.

Vladislav Lialin, Sherin Muckatira, Namrata Shivagunde, and Anna Rumshisky. ReloRA: High-rank training through low-rank updates. In *The Twelfth International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=DLJznSp6X3.

Kaizhao Liang, Bo Liu, Lizhang Chen, and Qiang Liu. Memory-efficient llm training with online subspace descent. *Advances in Neural Information Processing Systems*, 37:64412–64432, 2024.

Yujun Lin, Song Han, Huizi Mao, Yu Wang, and Bill Dally. Deep gradient compression: Reducing the communication bandwidth for distributed training. In *International Conference on Learning Representations*, 2018. URL `https://openreview.net/forum?id=SkhQHMWOW`.

Sijia Liu, Pin-Yu Chen, Xiangyi Chen, and Mingyi Hong. signsgd via zeroth-order oracle. In *International conference on learning representations*, 2019.

Zhenhua Liu, Yunhe Wang, Kai Han, Wei Zhang, Siwei Ma, and Wen Gao. Post-training quantization for vision transformer. *Advances in Neural Information Processing Systems*, 34:28092–28103, 2021.

Qijun Luo, Hengxu Yu, and Xiao Li. Badam: A memory efficient full parameter optimization method for large language models. *Advances in Neural Information Processing Systems*, 37:24926–24958, 2024.

Ionut-Vlad Modoranu, Mher Safaryan, Grigory Malinovsky, Eldar Kurtić, Thomas Robert, Peter Richtárik, and Dan Alistarh. Microadam: Accurate adaptive optimization with low space overhead and provable convergence. *Advances in Neural Information Processing Systems*, 37:1–43, 2024.

Yurii Nesterov. A method for solving the convex programming problem with convergence rate $o(1/k^2)$. *Proceedings of the USSR Academy of Sciences*, 269:543–547, 1983. URL `https://api.semanticscholar.org/CorpusID:145918791`.

Yurii Nesterov. *Introductory lectures on convex optimization: A basic course*, volume 87. Springer Science & Business Media, 2013.

Boris T Polyak. Some methods of speeding up the convergence of iteration methods. *Ussr computational mathematics and mathematical physics*, 4(5):1–17, 1964.

Samyam Rajbhandari, Jeff Rasley, Olatunji Ruwase, and Yuxiong He. Zero: Memory optimizations toward training trillion parameter models. In *SC20: International Conference for High Performance Computing, Networking, Storage and Analysis*, pp. 1–16. IEEE, 2020.

Mohammad Rastegari, Vicente Ordonez, Joseph Redmon, and Ali Farhadi. Xnor-net: Imagenet classification using binary convolutional neural networks. In *European conference on computer vision*, pp. 525–542. Springer, 2016.

Keisuke Sakaguchi, Ronan Le Bras, Chandra Bhagavatula, and Yejin Choi. Winogrande: An adversarial winograd schema challenge at scale. *Communications of the ACM*, 64(9):99–106, 2021.

Richard Socher, Alex Perelygin, Jean Wu, Jason Chuang, Christopher D Manning, Andrew Y Ng, and Christopher Potts. Recursive deep models for semantic compositionality over a sentiment treebank. In *Proceedings of the 2013 conference on empirical methods in natural language processing*, pp. 1631–1642, 2013.

Sebastian U Stich, Jean-Baptiste Cordonnier, and Martin Jaggi. Sparsified sgd with memory. *Advances in neural information processing systems*, 31, 2018.

David Stutz, Nandhini Chandramoorthy, Matthias Hein, and Bernt Schiele. Bit error robustness for energy-efficient dnn accelerators. *Proceedings of Machine Learning and Systems*, 3:569–598, 2021.

Tao Sun, Qingsong Wang, Dongsheng Li, and Bao Wang. Momentum ensures convergence of signsgd under weaker assumptions. In *International Conference on Machine Learning*, pp. 33077–33099. PMLR, 2023.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*, 2023.

Alex Wang, Yada Pruksachatkun, Nikita Nangia, Amanpreet Singh, Julian Michael, Felix Hill, Omer Levy, and Samuel Bowman. Superglue: A stickier benchmark for general-purpose language understanding systems. *Advances in neural information processing systems*, 32, 2019a.

Kuan Wang, Zhijian Liu, Yujun Lin, Ji Lin, and Song Han. Haq: Hardware-aware automated quantization with mixed precision. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 8612–8620, 2019b.

Sike Wang, Pan Zhou, Jia Li, and Hua Huang. 4-bit shampoo for memory-efficient network training. *Advances in Neural Information Processing Systems*, 37:126997–127029, 2024.

Jianqiao Wangni, Jialei Wang, Ji Liu, and Tong Zhang. Gradient sparsification for communication-efficient distributed optimization. *Advances in Neural Information Processing Systems*, 31, 2018.

Wei Wen, Cong Xu, Feng Yan, Chunpeng Wu, Yandan Wang, Yiran Chen, and Hai Li. Terngrad: Ternary gradients to reduce communication in distributed deep learning. *Advances in neural information processing systems*, 30, 2017.

Shuang Wu, Guoqi Li, Feng Chen, and Luping Shi. Training and inference with integers in deep neural networks. In *International Conference on Learning Representations*, 2018.

Guangxuan Xiao, Ji Lin, Mickael Seznec, Hao Wu, Julien Demouth, and Song Han. Smoothquant: Accurate and efficient post-training quantization for large language models. In *International conference on machine learning*, pp. 38087–38099. PMLR, 2023.

Zhewei Yao, Reza Yazdani Aminabadi, Minjia Zhang, Xiaoxia Wu, Conglong Li, and Yuxiong He. Zeroquant: Efficient and affordable post-training quantization for large-scale transformers. *Advances in neural information processing systems*, 35:27168–27183, 2022.

Susan Zhang, Stephen Roller, Naman Goyal, Mikel Artetxe, Moya Chen, Shuohui Chen, Christopher Dewan, Mona Diab, Xian Li, Xi Victoria Lin, et al. Opt: Open pre-trained transformer language models. *arXiv preprint arXiv:2205.01068*, 2022.

Yihua Zhang, Pingzhi Li, Junyuan Hong, Jiaxiang Li, Yimeng Zhang, Wenqing Zheng, Pin-Yu Chen, Jason D Lee, Wotao Yin, Mingyi Hong, et al. Revisiting zeroth-order optimization for memory-efficient llm fine-tuning: A benchmark. In *International Conference on Machine Learning*, pp. 59173–59190. PMLR, 2024.

Yushun Zhang, Congliang Chen, Ziniu Li, Tian Ding, Chenwei Wu, Diederik P Kingma, Yinyu Ye, Zhi-Quan Luo, and Ruoyu Sun. Adam-mini: Use fewer learning rates to gain more. In *The Thirteenth International Conference on Learning Representations*, 2025. URL https://openreview.net/forum?id=iBExhaU3Lc.

Jiawei Zhao, Zhenyu Zhang, Beidi Chen, Zhangyang Wang, Anima Anandkumar, and Yuandong Tian. Galore: Memory-efficient llm training by gradient low-rank projection. In *International Conference on Machine Learning*, pp. 61121–61143. PMLR, 2024.

Jiajun Zhou, Yifan Yang, Kai Zhen, Ziyue Liu, Yequan Zhao, Ershad Banijamali, Athanasios Mouchtaris, Ngai Wong, and Zheng Zhang. Quzo: Quantized zeroth-order fine-tuning for large language models. *arXiv preprint arXiv:2502.12346*, 2025.

Shuchang Zhou, Yuxin Wu, Zekun Ni, Xinyu Zhou, He Wen, and Yuheng Zou. Dorefa-net: Training low bitwidth convolutional neural networks with low bitwidth gradients. *arXiv preprint arXiv:1606.06160*, 2016.

Hanqing Zhu, Zhenyu Zhang, Wenyan Cong, Xi Liu, Sem Park, Vikas Chandra, Bo Long, David Z. Pan, Zhangyang Wang, and Jinwon Lee. APOLLO: SGD-like memory, adamw-level performance. In *Eighth Conference on Machine Learning and Systems*, 2025. URL https://openreview.net/forum?id=mJrPkdcZDj.

Philip Zmushko, Aleksandr Beznosikov, Martin Takáč, and Samuel Horváth. FRUGAL: Memory-efficient optimization by reducing state overhead for scalable training. In *Forty-second International Conference on Machine Learning*, 2025. URL https://openreview.net/forum?id=B4TyAILcE4.

A   Experiment Details

ImageNette ViT	
Batch Size	200
FP LR	6×10^{-4}
WD	0.05
Iterations	5000
Embed. dim	512
Layers	12
Heads	16
Init. density	0.9

IMDB Fully-Connected	
Batch Size	256
Epochs	50
Layers	3
Input dim	768
Hidden dim	4096
Init. density	0.9

LM Fine-Tuning w. LoRA	
Batch size	16
Iterations	20000
WD	0
LoRA α	16
LoRA r	8
Init. density	0.9

Figure 1: Hyperparameters used with different settings.

Hyperparameters Search. Results of grid search with multiple values of momentum coefficient β and initial learning rate η_0. The results show the benefits of the chosen hyperparameters.

Figure 2: Momentum coefficient, β, hyperparameter search.

Figure 3: Initial learning rate search.

B   Proofs of Section 5

B.1   Proof of Theorem 1

Note that for all $t \in [T]$, since $\eta_t = 1$, it holds that $e_t^{(\theta)} = \mathbf{1}$. Hence,

$$\theta_{t,i} = \theta_{t-1,i} - m_{t,i}, \quad \text{and} \quad |\theta_{t,i} - \theta_{t-1,i}| \leq 1.$$

Step (i): the good event. Fix $i \in [d]$. We define the following good event:

$$E_i \triangleq \left\{ \forall t \in [T - \Delta_\beta + 1], \exists d \in \{0, 1, \ldots, \Delta_\beta - 1\} \text{ s.t. } e_{t+d,i}^{(m)} = 0 \right\}.$$

Fixing some $t \in [T - \Delta_\beta + 1]$,

$$\Pr(e_t^{(m)} = e_{t+1}^{(m)} = \ldots = e_{t+\Delta_\beta-1}^{(m)} = 1) = \beta^{\Delta_\beta} \leq \delta/(dT),$$

where the last inequality follows from the definition of Δ_β. Performing a union bound over at most T windows, $\Pr(E_i) \geq 1 - \delta/d$. Defining $E_G = \cap_{i \in [d]} E_i$ and performing a union bound, $\Pr(E_G) \geq 1 - \delta$.

The rest of the proof will follow deterministically, conditioned on E_G.

Step (ii): distance from the minimizer. Let $\Theta = [r_{\min}, r_{\max}]$ and let $\Theta_i^\star \triangleq \arg\min_{\theta_i \in \Theta} \mathcal{L}_i(\theta_i)$. For any $t \in [T]$, let $D_i(\theta_t)$ be the distance of $\theta_{t,i}$ to the set of minimizers $\Theta_i^\star$. I.e.,

$$D_i(\theta_t) \triangleq \min_{\theta_i^\star \in \Theta_i^\star} |\theta_{t,i} - \theta_i^\star|.$$

Our goal is to bound $D_i(\theta_t) \leq \Delta_\beta$ for all $t \in [\Delta_\beta + r_{\max} - r_{\min}, T]$. Let $\tau \in [t]$ be the maximal iterate with $D_i(\theta_\tau) < 1$. To establish the existence of such τ, first, note that conditioned on E_i, there is some $s \leq \Delta_\beta$ with $\tilde{g}_{s,i} = m_{s,i}$. Second, since $\tilde{g}_{s,i} = \text{sign}(\theta_{s-1,i} - \theta_i^\star)$ (for all $\theta_i^\star$) from convexity in 1-d, $m_{s,i} = \text{sign}(\theta_{s-1,i} - \theta_i^\star)$, after which $D_i(\theta_s), D_i(\theta_{s+1}), \ldots$ must decrease by 1 in each step until reaching some s' with $D_i(\theta_{s'}) < 1$ (as all the gradients are aligned with the momentum until the iterates cross the set of minimizers). According to the domain size, it must happen after at most $\Delta_\beta + r_{\max} - r_{\min} < T$ steps.

Now, if $t - \tau < \Delta_\beta$, then $D_i(\theta_t) \leq D_i(\theta_\tau) + t - \tau \leq \Delta_\beta$. Otherwise, conditioned on E_i, there is some $s \in [\tau + 1, \tau + \Delta_\beta]$ with $m_{s,i} = \text{sign}(\theta_{s-1,i} - \theta_i^\star)$ (for any $\theta_i^\star \in \Theta_i^\star$), and $D_i(\theta_s), D_i(\theta_{s+1}), \ldots$ must decrease by 1 in each step until reaching below the 1 threshold, either contradicting the maximality of τ or enforcing $D_i(\theta_t) \leq D_i(\theta_{s-1}) \leq \Delta_\beta$. Hence, $D_i(\theta_t) \leq \Delta_\beta$.

Hence, we have established bounds for each $i \in [d]$ that hold with probability at least $1 - \delta$ (the probability of E_G), such that

$$\mathcal{L}(\theta_T) - \min_{\theta \in \Theta^d} \mathcal{L}(\theta) \leq \frac{1}{2} \|\boldsymbol{L}\|_1 \Delta_\beta^2. \qquad \square$$

B.2   Proof of Theorem 2

Here we prove a more general version of Theorem 2 that supports an arbitrary sequence $\eta_1, \ldots, \eta_T$. Theorem 2 then follows immediately by substituting $\eta_t = 1$ for $t = 1, \ldots, T$.

Theorem 3. *Let $\mathcal{L} : \mathbb{R}^d \to \mathbb{R}$ be an element-wise $\boldsymbol{L}$-smooth function lower bounded by some $\mathcal{L}^\star \in \mathbb{R}$. Let $\theta_0 \in \mathbb{Z}^d$ and consider the sequence $(\theta_t)_{t=0}^T$ generated by Algorithm 1 with parameters $\theta_0, r_{\min} = -\infty, r_{\max} = \infty, \beta \in (0,1)$, some $\eta_1, \ldots, \eta_T > 0$, and the deterministic signed gradient as* TernGrad. *Then it holds that*

$$\frac{1}{\sum_{t=1}^T \eta_t} \sum_{t=1}^T \eta_t \mathbb{E}[\|\nabla \mathcal{L}(\theta_{t-1})\|_1] \leq \frac{\mathcal{L}(\theta_0) - \mathcal{L}^\star}{(1-\beta)\sum_{t=1}^T \eta_t} + \frac{(1+5\beta)\|\boldsymbol{L}\|_1}{2(1-\beta)^2}.$$

In order to prove the theorem, we will use the following lemma. Its proof follows.

Lemma 1. *Let $\theta \in \mathbb{R}^d$, $\Delta \in \{-1, 0, 1\}^d$, $\boldsymbol{L} = (L_i)_{i=1}^d \in \mathbb{R}_+^d$, and let $\mathcal{L} : \mathbb{R}^d \to \mathbb{R}$ be a differentiable function satisfying*

$$\forall x, y \in \mathbb{R}^d \quad : \quad |\mathcal{L}(y) - (\mathcal{L}(x) + \nabla \mathcal{L}(x) \cdot (y - x))| \leq \frac{1}{2} \sum_{i=1}^d L_i (y_i - x_i)^2.$$

Then it holds that

$$\|\nabla \mathcal{L}(x + \Delta) - \nabla \mathcal{L}(x)\|_1 \leq 3\|L\|_1.$$

Proof. By the smoothness assumption,

$$\mathcal{L}(\theta_t) - \mathcal{L}(\theta_{t-1}) \leq \nabla \mathcal{L}(\theta_{t-1}) \cdot (\theta_t - \theta_{t-1}) + \frac{1}{2} \sum_{i=1}^{d} L_i (\theta_{t,i} - \theta_{t-1,i})^2$$

$$= -\nabla \mathcal{L}(\theta_{t-1}) \cdot (e_t^{(\theta)} \odot m_t) + \frac{1}{2} \sum_{i=1}^{d} L_i (e_{t,i}^{(\theta)} m_{t,i})^2.$$

Summing for $t = 1, \ldots, T$, replacing $\mathcal{L}(\theta_T) \geq \mathcal{L}^\star$, and rearranging,

$$\sum_{t=1}^{T} \mathbb{E}[\nabla \mathcal{L}(\theta_{t-1}) \cdot (e_t^{(\theta)} \odot m_t)] \leq \mathcal{L}(\theta_0) - \mathcal{L}^\star + \frac{1}{2} \sum_{t=1}^{T} \sum_{i=1}^{d} L_i \mathbb{E}[(e_{t,i}^{(\theta)} m_{t,i})^2].$$

By the law of total expectation, $\mathbb{E}[\nabla \mathcal{L}(\theta_{t-1}) \cdot (e_t^{(\theta)} \odot m_t)] = \eta_t \mathbb{E}[\nabla \mathcal{L}(\theta_{t-1}) \cdot m_t]$, and noting that $e_{t,i}^{(\theta)} m_{t,i} \in \{-1, 0, 1\}$, $\mathbb{E}[(e_{t,i}^{(\theta)} \odot m_{t,i})^2] \leq \eta_t$. Hence,

$$\sum_{t=1}^{T} \eta_t \mathbb{E}[\nabla \mathcal{L}(\theta_{t-1}) \cdot m_t] \leq \mathcal{L}(\theta_0) - \mathcal{L}^\star + \frac{\|\boldsymbol{L}\|_1}{2} \sum_{t=1}^{T} \eta_t.$$

Next we will focus on the $\mathbb{E}[\nabla \mathcal{L}(\theta_{t-1}) \cdot m_t]$.

$$\mathbb{E}[\nabla \mathcal{L}(\theta_{t-1}) \cdot m_t] = \mathbb{E}[\|\nabla \mathcal{L}(\theta_{t-1})\|_1 + \nabla \mathcal{L}(\theta_{t-1}) \cdot (m_t - \tilde{g}_t)] \qquad (\nabla \mathcal{L}(\theta_{t-1}) \cdot \tilde{g}_t = \|\nabla \mathcal{L}(\theta_{t-1})\|_1)$$

$$= \mathbb{E}[\|\nabla \mathcal{L}(\theta_{t-1})\|_1 + \nabla \mathcal{L}(\theta_{t-1}) \cdot (e_t^{(m)} \odot (m_{t-1} - \tilde{g}_t))]$$

$$= \mathbb{E}[\|\nabla \mathcal{L}(\theta_{t-1})\|_1 + \beta \nabla \mathcal{L}(\theta_{t-1}) \cdot (m_{t-1} - \tilde{g}_t)] \qquad (\theta_{t-1}, m_{t-1}, \tilde{g}_t \text{ independent from } e_t^{(m)})$$

$$= \mathbb{E}[(1 - \beta)\|\nabla \mathcal{L}(\theta_{t-1})\|_1 + \beta \nabla \mathcal{L}(\theta_{t-1}) \cdot m_{t-1}] \qquad (\nabla \mathcal{L}(\theta_{t-1}) \cdot \tilde{g}_t = \|\nabla \mathcal{L}(\theta_{t-1})\|_1)$$

$$= \mathbb{E}[(1 - \beta)\|\nabla \mathcal{L}(\theta_{t-1})\|_1 + \beta \nabla \mathcal{L}(\theta_{t-2}) \cdot m_{t-1} + \beta (\nabla \mathcal{L}(\theta_{t-1}) - \nabla \mathcal{L}(\theta_{t-2})) \cdot m_{t-1}]$$

$$\geq \mathbb{E}[(1 - \beta)\|\nabla \mathcal{L}(\theta_{t-1})\|_1 + \beta \nabla \mathcal{L}(\theta_{t-2}) \cdot m_{t-1} - 3\|L\|_1 \beta],$$

where the last inequality follows by Hölder's inequality and Lemma 1. Applying the inequality until $t = 1$ and using the initialization $m_0 = 0$,

$$\mathbb{E}[\nabla \mathcal{L}(\theta_{t-1}) \cdot m_t] \geq \mathbb{E}[\beta \nabla \mathcal{L}(\theta_{t-2}) \cdot m_{t-1} + (1 - \beta)\|\nabla \mathcal{L}(\theta_{t-1})\|_1 - 3\|L\|_1 \beta]$$

$$\geq \mathbb{E}[(1 - \beta) \sum_{k=1}^{t} (\beta)^{t-k} \|\nabla \mathcal{L}(\theta_{k-1})\|_1 - 3\|L\|_1 \sum_{k=1}^{t} \beta^{t-k+1}]$$

$$\geq \mathbb{E}[(1 - \beta) \sum_{k=1}^{t} (\beta)^{t-k} \|\nabla \mathcal{L}(\theta_{k-1})\|_1 - \frac{3\beta \|L\|_1}{1 - \beta}]$$

$$\geq \mathbb{E}[(1 - \beta)\|\nabla \mathcal{L}(\theta_{t-1})\|_1 - \frac{3\beta \|L\|_1}{1 - \beta}].$$

Thus,

$$\frac{1}{\sum_{t=1}^{T} \eta_t} \sum_{t=1}^{T} \eta_t \mathbb{E}[\|\nabla \mathcal{L}(\theta_{t-1})\|_1] \leq \frac{\mathcal{L}(\theta_0) - \mathcal{L}^\star}{(1 - \beta) \sum_{t=1}^{T} \eta_t} + \frac{(1 + 5\beta)\|L\|_1}{2(1 - \beta)^2}.$$

$\square$

B.3   Proof of Lemma 1

Proof. Let $s = \text{sign}(\nabla \mathcal{L}(x + \Delta) - \nabla \mathcal{L}(x))$. Hence, from the smoothness assumption,

$$\mathcal{L}(x + s) - \mathcal{L}(x) - \nabla \mathcal{L}(x) \cdot s \leq \frac{1}{2}\|\boldsymbol{L}\|_1,$$

$$-\mathcal{L}(x+s) + \mathcal{L}(x+\Delta) + \nabla\mathcal{L}(x+\Delta) \cdot (s-\Delta) \leq \frac{1}{2}\sum_{i=1}^{d} L_i(s_i - \Delta_i)^2 \leq 2\|\boldsymbol{L}\|_1,$$

and

$$\mathcal{L}(x) - \mathcal{L}(x+\Delta) - \nabla\mathcal{L}(x+\Delta) \cdot (-\Delta) \leq \frac{1}{2}\|\boldsymbol{L}\|_1.$$

Summing the inequalities,

$$(\nabla\mathcal{L}(x+\Delta) - \nabla\mathcal{L}(x)) \cdot s \leq 3\|\boldsymbol{L}\|_1.$$

$\square$