# HIERARCHICAL GAUSSIAN MIXTURE BASED TASK GENERATIVE MODEL FOR ROBUST META-LEARNING

## ABSTRACT

Meta-learning enables quick adaptation of machine learning models to new tasks with limited data. While tasks could come from varying distributions in reality, most of the existing meta-learning methods consider both training and testing tasks as from the same uni-component distribution, overlooking two critical needs of a practical solution: (1) the various sources of tasks may compose a multi-component mixture distribution, and (2) novel tasks may come from a distribution that is unseen during meta-training. In this paper, we demonstrate these two challenges can be solved jointly by modeling the density of task instances. We develop a meta-training framework underlain by a novel Hierarchical Gaussian Mixture based Task Generative Model (HTGM). HTGM extends the widely used empirical process of sampling tasks to a theoretical model, which learns task embeddings, fits mixture distribution of tasks, and enables density-based scoring of novel tasks. The framework is agnostic to the encoder and scales well with large backbone networks. The model parameters are learned end-to-end by maximum likelihood estimation via an Expectation-Maximization algorithm. Extensive experiments on benchmark datasets indicate the effectiveness of our method for both sample classification and novel task detection.

## 1 INTRODUCTION

Training models in small data regimes is of fundamental importance. It demands a model's ability to quickly adapt to new environments and tasks. To compensate for the lack of training data for each task, meta-learning (*a.k.a.* learning to learn) has become an essential paradigm for model training by generalizing meta-knowledge across tasks (Snell et al., 2017; Finn et al., 2017). While most existing meta-learning approaches were built upon an assumption that all training/testing tasks are sampled from the same distribution, a more realistic scenario should accommodate training tasks that lie in a mixture of distributions, and testing tasks that may belong to or deviate from the learned distributions. For example, in recent medical researches, a global model is typically trained on the historical medical records of a certain set of patients in the database (Shukla & Marlin, 2019; Wu et al., 2021). However, due to the uniqueness of individuals (*e.g.*, gender, age, genetics), patients' data have a substantial discrepancy, and the pre-trained model may demonstrate significant demographic or geographical biases when testing on a new patient (Purushotham et al., 2017). This issue can be mitigated by personalized medicine approaches (Chan & Ginsburg, 2011; Ni et al., 2022) where each patient is regarded as a task, and the pre-trained model is fine-tuned (*i.e.*, personalized) on a support set of a few records collected in a short period (*e.g.*, a few weeks) from every patient for adaptation. In this case, the training tasks (*i.e.,* patients) could be sampled from a mixture of distributions (*e.g.*, different age groups), and a testing task may or may not belong to any of the observed groups. As such, a meta-training strategy that is able to fit a mixture of task distributions and identify novel tasks is desirable for making meta-learning a practical solution.

One way to tackle the mixture distributions of tasks is to tailor the transferable knowledge to each task by learning a task-specific representation (Oreshkin et al., 2018; Vuorio et al., 2018; Lee & Choi, 2018), but as discussed in (Yao et al., 2019a), the over-customized knowledge prevents its generalization among closely related tasks (*e.g.*, tasks from the same distribution). The more recent methods try to balance the generalization and customization of the meta-knowledge by promoting *local generalization* either among a cluster of related tasks (Yao et al., 2019a), or within a neighborhood of a meta-knowledge graph of tasks (Yao et al., 2019b). Neither of them explicitly learns the

underlying distribution from which the tasks are generated, rendering them infeasible for detecting novel tasks that are out-of-distribution. However, detecting novel tasks is crucial in high-stake domains, such as medicine and finance, which provides users (*e.g.*, physicians) confidence on whether to trust the results of a testing task or not, and facilitates the downstream decision-making.

In (Lee et al., 2019a), a task-specific tuning variable was introduced to modulate the initial parameters learned by MAML (Finn et al., 2017), so that the impacts of the meta-knowledge on different tasks are adjusted differently, *e.g.*, novel tasks receive less impact than known tasks do. Whereas, this method focuses on improving model performance on different tasks (either known or novel), but neglects the critical mission of detecting which tasks are novel. In practice, providing an unreliable accuracy on a novel task, without differentiating it from other tasks may be meaningless and risky.

Since the aforementioned methods cannot simultaneously handle the mixture distribution of tasks and novel tasks, a practical solution is in demand. In this work, we consider tasks as instances, and demonstrate the dual problem of modeling the mixture of task distributions and detecting novel tasks are two sides of the same coin, *i.e.*, density estimation on task instances. To this end, we propose a new Hierarchical Gaussian Mixture based Task Generative Model (HTGM) to explicitly model the generative process of task instances. Our contributions are summarized as follows.

- For the first time, the widely used empirical process of generating a task is theoretically extended to and specified by a hierarchy of Gaussian mixture (GM) distributions. HTGM generates a *task embedding* from a *task-level* GM, and uses it to define the task-conditioned mixture probabilities for a *class-level* GM, from which samples are drawn, for instantiating the generated task. To allow realistic classes per task, a new Gibbs distribution is proposed to underlie the class-level GM.

- HTGM is an encoder-agnostic framework, thus is flexible to different domains. It inherits metric-based meta-learning methods, and only introduces a small overhead to an encoder for parameterizing its distributions, thus is efficient, and enables large-scale backbone networks. The model parameters are learned end-to-end by maximum likelihood estimation via a principled Expectation-Maximization (EM) algorithm. The bounds of our likelihood function is theoretically analyzed.

- In the experiments, we evaluated HTGM on benchmark image datasets for validating its ability to take advantage of large backbone networks, its effectiveness in modeling the mixture distribution of tasks, and its usefulness in identifying novel tasks. The results demonstrate HTGM outperforms the state-of-the-art (SOTA) baselines with significant improvements in most cases.

## 2 RELATED WORK

To the best of our knowledge, this is the first work to explicitly model the generative process of task instances from a mixture of distributions for meta-learning with novel task detection. Meta-learning has become a popular idea to handle the few-shot learning problem, which derives memory-based (Santoro et al., 2016; Mishra et al., 2018), optimization-based (Finn et al., 2017; Li et al., 2017), and metric-based methods (Vinyals et al., 2016; Snell et al., 2017). Most of these approaches consider an artificial scenario where training/test tasks are sampled from the same distribution. To enable dynamically changing tasks, task-adaptive meta-learning methods try to facilitate the customization of meta-knowledge by learning task-specific parameters (Rusu et al., 2018; Lee & Choi, 2018), temperature scaling parameters (Oreshkin et al., 2018), and task-specific modulation on model initialization (Vuorio et al., 2018; Yao et al., 2019a;b; Lee et al., 2019a). Among them, there are methods tackling the mixture distribution of tasks by either clustering tasks (Yao et al., 2019a) or learning task graphs (Yao et al., 2019b), and method that relocates the initial parameters for different tasks so that they use the meta-knowledge differently (Lee et al., 2019a). As discussed before, none of these methods simultaneously handle the mixture of task distributions and the detection of novel tasks.

Our model is built upon metric-based methods, and learns task embeddings for modeling task distributions. Achille et al. (2019) also proposed to learn embeddings for tasks and introduced a meta-learning method, but not for few-shot learning. Its embeddings are from a pre-specified set of tasks (rather than episode-wise sampling), and the meta-learning framework is for model selection. The model in (Yao et al., 2019a) has an augmented encoder for task embedding, but it does not explicitly model task generation, and is not designed for novel task detection (empirical comparison in 4.1).

Conventional novelty detection aims to identify and reject samples from unseen classes (Cheng & Vasconcelos, 2021). It relates to open-set recognition (Vaze et al., 2022), which aims to simulta-

neously identify unknown samples and classify samples from known classes. Out-of-distribution (OOD) detection (Liang et al., 2018; Liu et al., 2020) can be seen as a special case of novelty detection where novel samples are from other problem domains or datasets, thus are considered to be easier to detect than novelties (Cheng & Vasconcelos, 2021). These methods are for large scale training. In contrast, we want to detect novel tasks, which is a new problem in the small data regime.

Hierarchical Gaussian Mixture (GM) model has appeared in some traditional works (Goldberger & Roweis, 2005; Olech & Paradowski, 2016; Athey et al., 2019) for hierarchical clustering by applying GM agglomeratively or divisively, which is remarkably different from the topic in this paper.

## 3 HIERARCHICAL GAUSSIAN MIXTURE BASED TASK GENERATIVE MODEL

Meta-learning methods typically use an *episodic learning* strategy, where the meta-training set $\mathcal{D}^{\text{tr}}$ consists of a batch of episodes. Each episode samples a task $\tau$ from a distribution $p(\tau)$. Task $\tau$ has a support set $\mathcal{D}_\tau^s = \{(\mathbf{x}_i^s, y_i^s)\}_{i=1}^{n_s}$ for training, and a query set $\mathcal{D}_\tau^q = \{(\mathbf{x}_i^q, y_i^q)\}_{i=1}^{n_q}$ for testing, where $n_s$ is a small number to denote a few training samples. In particular, in a commonly used $N$-way $K$-shot $Q$-query task (Vinyals et al., 2016), $\mathcal{D}_\tau^s$ and $\mathcal{D}_\tau^q$ contain $N$ classes, with $K$ and $Q$ samples per class respectively, *i.e.*, $n_s = NK$ and $n_q = NQ$.

Let $f_{\boldsymbol{\theta}}(\mathbf{x}_i^*) \to y_i^*$ be a base model ($*$ denotes $s$ or $q$), and $f_{\boldsymbol{\theta}}(\cdot; \mathcal{D}_\tau^s)$ be the adapted model on $\mathcal{D}_\tau^s$. The training objective on $\tau$ is to minimize the average test error of the adapted model, *i.e.*, $\mathbb{E}_{(\mathbf{x}_i^q, y_i^q) \in \mathcal{D}_\tau^q} \ell(y_i^q, f_{\boldsymbol{\theta}}(\mathbf{x}_i^q; \mathcal{D}_\tau^s))$, where $\ell(\cdot, \cdot)$ is a loss function (*e.g.*, cross-entropy loss), and the meta-training process aims to find the parameter $\boldsymbol{\theta}$ that minimizes this error over all episodes in $\mathcal{D}^{\text{tr}}$. Then, $f_{\boldsymbol{\theta}}$ is evaluated on every episode of a meta-test set $\mathcal{D}^{\text{te}}$ that samples a task from the same distribution $p(\tau)$. Usually, $p(\tau)$ is a simple distribution (Finn et al., 2017; Lee et al., 2019a). In this work, $p(\tau)$ is generalized to a mixture distribution consists of multiple components $p_1(\tau), ..., p_r(\tau)$, and a test episode may sample a task either in or out of any component of $p(\tau)$. As such, given the training tasks in $\mathcal{D}^{\text{tr}}$, our goal is to estimate the underlying density of $p(\tau)$, so that once a test task is given, we can (1) identify if it is an novel task, and (2) adapt $f_{\boldsymbol{\theta}}$ to it with optimal accuracy.

Specifically, the base model $f_{\boldsymbol{\theta}}$ can be written as a combination of an encoder $g_{\boldsymbol{\theta}_e}$ and a predictor $h_{\boldsymbol{\theta}_d}$, *i.e.*, $f_{\boldsymbol{\theta}}(\mathbf{x}_i^*) = h_{\boldsymbol{\theta}_d}(g_{\boldsymbol{\theta}_e}(\mathbf{x}_i^*))$ (Tian et al., 2020). In this work, we focus on a metric-based non-parametric learner, *i.e.*, $\boldsymbol{\theta}_d = \varnothing$ (*e.g.*, prototypical networks (Snell et al., 2017)), not only because metric-based classifiers were confirmed as more effective than probabilistic classifiers for novelty detection (Jeong et al., 2021), but also for its better training efficiency that fits large-scale backbone networks than the costly nested-loop training of optimization-based methods (Tian et al., 2020).

Formally, our goal is to find the model parameter $\boldsymbol{\theta}$ that maximizes the likelihood of observing a task $\tau$. In other words, let $f_{\boldsymbol{\theta}}(\mathbf{x}_i^*) = \mathbf{e}_i^* \in \mathbb{R}^d$ be the sample embedding, we want to maximize the likelihood of the joint distribution $p_{\boldsymbol{\theta}}(\mathbf{e}_i^*, y_i^*)$ on the observed data in $\mathcal{D}_\tau = \{\mathcal{D}_\tau^s, \mathcal{D}_\tau^q\}$. We consider each task $\tau$ as an instance, with a representation $\mathbf{v}_\tau \in \mathbb{R}^d$ in the embedding space (the method to infer $\mathbf{v}_\tau$ is described in Sec. 3.2). To model the unobserved mixture component, we associate every task with a latent variable $z_\tau$ to indicate to which component it belongs. Suppose there are $r$ possible components, and let $n = n_s + n_q$ be the total number of samples in $\mathcal{D}_\tau$, the log-likelihood to maximize can be written by hierarchically marginalizing out $y_i^*$, $\mathbf{v}_\tau$ and $z_\tau$.

$$
\begin{aligned}
\ell(\mathcal{D}_\tau; \boldsymbol{\theta}) &= \frac{1}{n} \sum_{i=1}^n \log\left[p_{\boldsymbol{\theta}}(\mathbf{e}_i^*, y_i^*)\right] = \frac{1}{n} \sum_{i=1}^n \log\left[p_{\boldsymbol{\theta}}(\mathbf{e}_i^*|y_i^*) p(y_i^*)\right] \\
&= \frac{1}{n} \sum_{i=1}^n \log\left[p_{\boldsymbol{\theta}}(\mathbf{e}_i^*|y_i^*)\left[\int_{\mathbf{v}_\tau} p(y_i^*|\mathbf{v}_\tau) p(\mathbf{v}_\tau) d\mathbf{v}_\tau\right]\right] \\
&= \frac{1}{n} \sum_{i=1}^n \log\left[p_{\boldsymbol{\theta}}(\mathbf{e}_i^*|y_i^*)\left[\int_{\mathbf{v}_\tau} p(y_i^*|\mathbf{v}_\tau)\left[\sum_{z_\tau=1}^r p(\mathbf{v}_\tau|z_\tau) p(z_\tau)\right] d\mathbf{v}_\tau\right]\right]
\end{aligned}
\tag{1}
$$

where $p_{\boldsymbol{\theta}}(\mathbf{e}_i^*|y_i^*)$ specifies the probability of sampling $\mathbf{e}_i^*$ from the $y_i^*$-th class, $p(y_i^*|\mathbf{v}_\tau)$ is the probability of sampling the $y_i^*$-th class for task $\tau$, and $p(\mathbf{v}_\tau|z_\tau)$ indicates the probability of generating a task $\tau$ from the $z_\tau$-th mixture component. $p(z_\tau)$ is a prior on the $z_\tau$-th component. Hence, Eq. (1) implies a generative process of task $\tau$: $z_\tau \to \mathbf{v}_\tau \to y_i^* \to \mathbf{e}_i^*$. Next, we define each of the aforementioned distributions and propose our HTGM method.

### 3.1 MODEL SPECIFICATION AND PARAMETERIZATION

In Eq. (1), the *class-conditional distribution* $p_{\boldsymbol{\theta}}(\mathbf{e}_i^*|y_i^*)$, the *task-conditional distribution* $p(y_i^*|\mathbf{v}_\tau)$, and the *mixture distribution of tasks* defined by $\{p(\mathbf{v}_\tau|z_\tau), p(z_\tau)\}$ are not specified. To make Eq. (1) optimizable, we introduce our HTGM that models the generative process of tasks. Because $\mathcal{D}_\tau^s$ and $\mathcal{D}_\tau^q$ follow the same distribution, in the following, we ignore the superscript $*$ for simplicity.

**Class-Conditional Distribution.** First, similar to (Lee et al., 2018; 2019b), we use Gaussian distribution to model the embeddings $\mathbf{e}_i$'s in every class. Let $\boldsymbol{\mu}_{y_i}$ and $\sigma_{y_i}\boldsymbol{I}$ be the mean and variance of the distribution of the $y_i$-th class, then $p_{\boldsymbol{\theta}}(\mathbf{e}_i|y_i) = \mathcal{N}(\mathbf{e}_i|\boldsymbol{\mu}_{y_i}, \sigma_{y_i}\boldsymbol{I})$. In fact, the samples in all of the classes of task $\tau$ comprise a Gaussian mixture distribution, where $p(y_i)$ is the *mixture probability* of the $y_i$-th class. In Eq. (1), $p(y_i)$ is factorized to be task-specific, *i.e.*, $p(y_i|\mathbf{v}_\tau)$, which resorts to another mixture distribution $p(\mathbf{v}_\tau)$ of tasks, and establishes a structure of hierarchical mixture.

**Task-Conditional Distribution.** A straightforward definition of $p(y_i|\mathbf{v}_\tau)$ is the density at $\boldsymbol{\mu}_{y_i}$ in a Gaussian distribution with $\mathbf{v}_\tau$ as the mean, where $\boldsymbol{\mu}_{y_i}$ is the mean (or prototype) of the $y_i$-th class. However, doing so exposes two problems: (1) the density function of Gaussian distribution is log-concave with one global maximum. Given the mean and variance, maximizing its log-likelihood tends to collapse the prototypes $\boldsymbol{\mu}_{y_i}$'s of all classes in $\tau$, making them indistinguishable and impairing classification; (2) given $\mathbf{v}_\tau$, this method tends to sample classes with small $D_{\mathbf{v}_\tau}(\boldsymbol{\mu}_{y_i})$, where $D_{\mathbf{v}_\tau}(\cdot)$ measures the Mahalanobis distance between a data point and the Gaussian distribution centered at $\mathbf{v}_\tau$. However, in most of the existing works, classes are often uniformly sampled from a domain without any prior on distances (Finn et al., 2017). Fitting the distance function with such "uniform" classes naively leads to an ill-posed learning problem with degenerated solutions. In light of these issues, we seek to define $p(y_i|\mathbf{v}_\tau)$ as a (parameterized) density function with at least $N$ global optimums so that it can distinguish the $N$ different class prototypes of $N$-way tasks. The $N$ equal (global) optimums also allow it to fit $N$ classes that are uniformly sampled from a domain. To this end, we propose a Gibbs distribution $\pi(\mathbf{v}_\tau, \boldsymbol{\omega})$ defined by $\mathbf{v}_\tau$ and trainable parameters $\boldsymbol{\omega}$ with an energy function. Let $\boldsymbol{\mu}_{y_i}$ be the *surrogate embedding* of $y_i$, we write $p(y_i|\mathbf{v}_\tau)$ as follows

$$p_{\boldsymbol{\omega}}(y_i|\mathbf{v}_\tau) = \pi(\boldsymbol{\mu}_{y_i}|\mathbf{v}_\tau, \boldsymbol{\omega}) = \frac{\exp\left[-E_{\boldsymbol{\omega}}(\boldsymbol{\mu}_{y_i}; \mathbf{v}_\tau)\right]}{\int_{\boldsymbol{\mu}_{y_i}} \exp\left[-E_{\boldsymbol{\omega}}(\boldsymbol{\mu}_{y_i}; \mathbf{v}_\tau)\right]} \tag{2}$$

where $E_{\boldsymbol{\omega}}(\boldsymbol{\mu}_{y_i}; \mathbf{v}_\tau) = \min\left(\{||\boldsymbol{\mu}_{y_i} - \mathbf{W}_j\mathbf{v}_\tau||_2^2\}_{j=1}^N\right)$ is our energy function, and the denominator in Eq (2) is a normalizing constant (with respect to $\boldsymbol{\mu}_{y_i}$), *a.k.a.* the partition function in an energy-based model (EBM) (LeCun et al., 2006). $\boldsymbol{\omega} = \{\mathbf{W}_1, ..., \mathbf{W}_N\}$ are trainable parameters, with $\mathbf{W}_i \in \mathbb{R}^{d \times d}$. Given $\boldsymbol{\omega}$ and $\mathbf{v}_\tau$, Eq. (2) has $N$ global maximums at $\boldsymbol{\mu}_{y_i} = \mathbf{W}_1\mathbf{v}_\tau, ..., \boldsymbol{\mu}_{y_i} = \mathbf{W}_N\mathbf{v}_\tau$.

**Mixture Distribution of Tasks.** In Eq. (1), the task distribution $p(\mathbf{v}_\tau)$ is factorized as a mixture of $p(\mathbf{v}_\tau|z_\tau = 1), ..., p(\mathbf{v}_\tau|z_\tau = r)$, weighted by their respective mixture probability $p(z_\tau)$. We specify $p(\mathbf{v}_\tau)$ as a Gaussian mixture distribution, and introduce $\bar{\boldsymbol{\mu}}_{z_\tau}$ and $\bar{\boldsymbol{\Sigma}}_{z_\tau}$ as the mean and variance for each component, *i.e.*, $p(\mathbf{v}_\tau|z_\tau) = \mathcal{N}(\mathbf{v}_\tau|\bar{\boldsymbol{\mu}}_{z_\tau}, \bar{\boldsymbol{\Sigma}}_{z_\tau})$. Then the generation of $\mathbf{v}_\tau$ involves two steps: (1) draw a latent variable $z_\tau$ from a categorical distribution on $[p(z_\tau = 1), ..., p(z_\tau = r)]$, which can be Uniform$(r)$, and (2) draw $\mathbf{v}_\tau$ from $\mathcal{N}(\bar{\boldsymbol{\mu}}_{z_\tau}, \bar{\boldsymbol{\Sigma}}_{z_\tau})$ (Bishop, 2006).

With the aforementioned specification of the distributions, our HTGM generative process of an $N$-way $K$-shot $Q$-query task $\tau$ can be summarized as

1. Draw a latent task variable $z_\tau \sim \text{Categorical}([p(z_\tau = 1), ..., p(z_\tau = r)])$
2. Draw a task embedding $\mathbf{v}_\tau \sim \mathcal{N}(\bar{\boldsymbol{\mu}}_{z_\tau}, \bar{\boldsymbol{\Sigma}}_{z_\tau})$
3. For $c = 1, ..., N$:
    (a) Draw a class prototype $\boldsymbol{\mu}_c \sim \pi(\mathbf{v}_\tau, \boldsymbol{\omega})$ from the proposed Gibbs distribution in Eq. (2)
    (b) For $i = 1, ..., K + Q$:
        i. Draw a sample feature $\mathbf{e}_i \sim \mathcal{N}(\boldsymbol{\mu}_c, \boldsymbol{\Sigma}_c)$
    (c) Randomly distribute $K$ samples to the support set $\mathcal{D}_\tau^s$ and $Q$ samples to the query set $\mathcal{D}_\tau^q$

To reduce complexity, in this work, we investigate the feasibility of using isotropic Gaussian with tied variance, *i.e.*, $\boldsymbol{\Sigma}_c = \sigma^2\mathbf{I}$, for class distributions, which turned out to be efficient in our experiments. Here, $\mathbf{I}$ is the identity matrix, $\sigma$ is a hyperparameter. Tied variance is also a commonly used trick in Gaussian discriminate analysis (GDA) for generative classifiers (Lee et al., 2018). For task distributions, the variances $\{\bar{\boldsymbol{\Sigma}}_{j=1}\}_{j=1}^r$ can be automatically inferred by our algorithm in Sec. 3.2.

Figure 1: An illustration of HTGM on its (a) the training process, and (b) the testing process. In (a), ①②③ are the three parts of the training loss in Eq. (3). In (b), the training task embeddings contain the embeddings of all training tasks, *i.e.* the outputs of the task-pooling in (a).

Finally, substituting $p_{\boldsymbol{\theta}}(\mathbf{e}_i|y_i) = \mathcal{N}(\mathbf{e}_i|\boldsymbol{\mu}_{y_i}, \sigma^2\mathbf{I})$, $p_{\boldsymbol{\omega}}(y_i|\mathbf{v}_\tau) = \pi(\boldsymbol{\mu}_{y_i}|\mathbf{v}_\tau, \boldsymbol{\omega})$ (Eq. (2)), $p(\mathbf{v}_\tau|z_\tau) = \mathcal{N}(\mathbf{v}_\tau|\bar{\boldsymbol{\mu}}_{z_\tau}, \bar{\boldsymbol{\Sigma}}_{z_\tau})$ and $p(z_\tau) = \text{Uniform}(r)$ in Eq. (1), whose probabilities are specified and parameterized, we get our HTGM induced loss $\ell_{\text{HTGM}}(\mathcal{D}_\tau; \boldsymbol{\theta}, \boldsymbol{\phi})$, where $\boldsymbol{\phi} = \{\boldsymbol{\omega}, \{\bar{\boldsymbol{\mu}}_j\}_{j=1}^r\}$ are trainable parameters. The class means $\boldsymbol{\mu}_{y_i}$ and task variances $\bar{\boldsymbol{\Sigma}}_{z_\tau}$ will be inferred by our algorithm (see A.4).

## 3.2 MODEL OPTIMIZATION

It is hard to directly optimize $\ell_{\text{HTGM}}(\mathcal{D}_\tau; \boldsymbol{\theta}, \boldsymbol{\phi})$, because exact posterior inference is intractable (due to the integration over $\mathbf{v}_\tau$). To solve it, we resort to variational methods, and introduce an approximated posterior $q_{\boldsymbol{\psi}}(\mathbf{v}_\tau|\mathcal{D}_\tau^s)$, which implies we want to infer $\mathbf{v}_\tau$ from its observed support set $\mathcal{D}_\tau^s$. The query set $\mathcal{D}_\tau^q$ is not included because it is unavailable during model testing. Then we propose to maximize a lower-bound of Eq. (1), which is derived as (the details are in Appendix A.1)

$$\ell_{\text{HTGM}}(\mathcal{D}_\tau; \boldsymbol{\theta}, \boldsymbol{\phi}) \geq \ell_{\text{HTGM-ELBO}}(\mathcal{D}_\tau; \boldsymbol{\theta}, \boldsymbol{\phi}) = \frac{1}{n}\sum_{i=1}^{n}\log p_{\boldsymbol{\theta}, \boldsymbol{\phi}}(\mathbf{e}_i|y_i)$$
$$+ \frac{1}{n}\sum_{i=1}^{n}\mathbb{E}_{\mathbf{v}_\tau \sim q_{\boldsymbol{\psi}}(\mathbf{v}_\tau|\mathcal{D}_\tau^s)}\Big[\log p_{\boldsymbol{\phi}}(y_i|\mathbf{v}_\tau) + \log\Big(\sum_{z_\tau=1}^{r}p_{\boldsymbol{\phi}}(\mathbf{v}_\tau|z_\tau)p(z_\tau)\Big)\Big] + H\big(q_{\boldsymbol{\psi}}(\mathbf{v}_\tau|\mathcal{D}_\tau^s)\big) \tag{3}$$

where $H(q_{\boldsymbol{\psi}}(\mathbf{v}_\tau|\mathcal{D}_\tau^s)) = -\int_{\mathbf{v}_\tau}q_{\boldsymbol{\psi}}(\mathbf{v}_\tau|\mathcal{D}_\tau^s)\log q_{\boldsymbol{\psi}}(\mathbf{v}_\tau|\mathcal{D}_\tau^s)d\mathbf{v}_\tau$ is the entropy function. Similar to VAE (Kingma & Welling, 2013), Eq. (3) estimates the expectation (in the second term) by sampling $\mathbf{v}_\tau$ from $q_{\boldsymbol{\psi}}(\mathbf{v}_\tau|\mathcal{D}_\tau^s)$ defined by an inference network $\boldsymbol{\psi}$, instead of the integration in Eq. (1). Next, we elaborate on the inference network, the challenges of maximizing Eq. (3), and our workarounds.

**Inference Network.** Similar to VAE, $q_{\boldsymbol{\psi}}(\mathbf{v}_\tau|\mathcal{D}_\tau^s)$ is defined as a Gaussian distribution $\mathcal{N}(\hat{\boldsymbol{\mu}}_{z_\tau}, \bar{\sigma}^2\mathbf{I})$, where $\hat{\boldsymbol{\mu}}_{z_\tau}$ is the output of the inference network, which approximates $\bar{\boldsymbol{\mu}}_{z_\tau}$ in Step 2 of the generative process, and $\bar{\sigma}$ is a hyperparameter for the corresponding variance. As illustrated by Fig. 1(a), the inference network is built upon the base model $f_{\boldsymbol{\theta}}(\cdot)$ with two non-parametric aggregation (*i.e.*, mean pooling) functions, thus $\boldsymbol{\psi} = \boldsymbol{\theta}$. The first function aggregates class-wise embeddings to prototypes $\boldsymbol{\mu}_{y_i}$'s, similar to prototypical networks (Snell et al., 2017). Differently, the second aggregates all prototypes to $\hat{\boldsymbol{\mu}}_{z_\tau}$. During model training, we use the reparameterization trick (Kingma & Welling, 2013) to sample $\mathbf{v}_\tau$ from $\mathcal{N}(\hat{\boldsymbol{\mu}}_{z_\tau}, \bar{\sigma}^2\mathbf{I})$. It is noteworthy that $H(q_{\boldsymbol{\psi}}(\mathbf{v}_\tau|\mathcal{D}_\tau^s))$ in Eq. (3) becomes a constant now because $\bar{\sigma}^2$ is a constant.

**Challenge 1: Trivial Solution.** In Eq. (3), since the first term $\log p_{\boldsymbol{\theta},\boldsymbol{\phi}}(\mathbf{e}_i|y_i) = -\frac{1}{2\sigma_{y_i}^{2d}}\|\mathbf{e}_i - \boldsymbol{\mu}_{y_i}\|_2^2 +$ $const$ only penalizes the distance between a sample $\mathbf{e}_i$ and its own class mean $\boldsymbol{\mu}_{y_i}$ (*i.e.*, intra-class distances) without considering inter-class relationships, different class means $\boldsymbol{\mu}_1, ..., \boldsymbol{\mu}_N$ in task $\tau$ could collide, drawing all sample embeddings to the same spot. To avoid such trivial solution and improve the stability of optimization, we apply the negative sampling in (Mikolov et al., 2013)

$$\ell_{\text{neg}}(\mathcal{D}_\tau; y_i, \boldsymbol{\theta}, \boldsymbol{\phi}) = -\log \mathbb{E}_{\mathbf{e}_j \sim \mathcal{D}_\tau}\big[\exp\big(-\frac{1}{2\sigma_{y_i}^{2d}}\|\mathbf{e}_j - \boldsymbol{\mu}_{y_i}\|_2^2\big)\big] \tag{4}$$

where $\mathbf{e}_j$ is a negative sample embedding from any class in the support set, and $\boldsymbol{\mu}_{y_i}$ is the mean of the positive class. In practice, we found it is beneficial to integrate $\ell_{\text{neg}}$ with our likelihood $\ell_{\text{HTGM}}$ in Eq. (1) during training, *i.e.* $\ell_{\text{HTGM}} + \frac{1}{n}\sum_{i=1}^n \ell_{\text{neg}}$. Correspondingly, from Eq. (3) we have

$$\ell(\mathcal{D}_\tau; \boldsymbol{\theta}, \boldsymbol{\phi}) = \ell_{\text{HTGM-ELBO}}(\mathcal{D}_\tau; \boldsymbol{\theta}, \boldsymbol{\phi}) + \frac{1}{n}\sum_{i=1}^n \ell_{\text{neg}}(\mathcal{D}_\tau; y_i, \boldsymbol{\theta}, \boldsymbol{\phi}) \tag{5}$$

which does not only serve as a robust training loss, but also helps solve the next challenge.

**Challenge 2: The Partition Function in Eq. (2).** The second term $p_{\boldsymbol{\phi}}(y_i|\mathbf{v}_\tau)$ in Eq. (3) involves computing the partition function in Eq. (2) (*i.e.*, the denominator), which is intractable because of the integration over all possible $\boldsymbol{\mu}_{y_i}$'s. To solve it, we propose an upper bound of the partition function $\int_{\boldsymbol{\mu}_{y_i}} \exp\big[-E_{\boldsymbol{\omega}}(\boldsymbol{\mu}_{y_i}; \mathbf{v}_\tau)\big]d\boldsymbol{\mu}_{y_i} \leq N\sqrt{2^{d-1}\pi^d}$ (the derivation is in Appendix A.2), which is a constant with a specific $N$. By replacing the partition function in Eq. (2) with $N\sqrt{2^{d-1}\pi^d}$, we got a lower bound of $p_{\boldsymbol{\phi}}(y_i|\mathbf{v}_\tau)$, which in turn relaxes the lower bound in Eq. (3). The following theorem (the proof is in Appendix A.3) states the tightness of the relaxed bound is controllable.

**Theorem 1.** *Among the $N$ global maximums $\mathbf{W}_1\mathbf{v}_\tau, ..., \mathbf{W}_N\mathbf{v}_\tau$ of Eq. (2), let $\mathbf{W}_k\mathbf{v}_\tau$ and $\mathbf{W}_t\mathbf{v}_\tau$ ($1 \leq k, t \leq N$) be the pair with the smallest Euclidean distance $D(\mathbf{W}_k\mathbf{v}_\tau, \mathbf{W}_t\mathbf{v}_\tau)$, we have*

$$\lim_{D(\mathbf{W}_r\mathbf{v}_\tau, \mathbf{W}_t\mathbf{v}_\tau)\to\infty} \int_{\boldsymbol{\mu}_{y_i}} \exp\big[-E_{\boldsymbol{\omega}}(\boldsymbol{\mu}_{y_i}; \mathbf{v}_\tau)\big]d\boldsymbol{\mu}_{y_i} = N\sqrt{2^{d-1}\pi^d} \tag{6}$$

This theorem indicates the partition function approximates $N\sqrt{2^{d-1}\pi^d}$ when all pairs of the global maximums are far apart. It is noteworthy that during training (*i.e.*, maximizing the likelihood) we fit $\mathbf{W}_1\mathbf{v}_\tau, ..., \mathbf{W}_N\mathbf{v}_\tau$ to the different class prototypes $\boldsymbol{\mu}_1, ..., \boldsymbol{\mu}_N$ in $N$-way tasks. Because $\ell_{\text{neg}}$ in Eq. (4) tends to maximize the distances between different prototypes through the negative samples, maximizing the joint loss $\ell$ in Eq. (5) tends to separate $\mathbf{W}_1\mathbf{v}_\tau, ..., \mathbf{W}_N\mathbf{v}_\tau$, thus tighten the relaxed bound after using $N\sqrt{2^{d-1}\pi^d}$ according to Theorem 1. This is another benefit of negative sampling.

**Optimization via Expectation-Maximization.** In the third term of $\ell_{\text{HTGM-ELBO}}$ in Eq. (3), we need to estimate the mixture distribution $p(z_\tau)$. Similar to optimizing Gaussian mixture models, we alternately infer $p(z_\tau)$ and solving the model parameters $\{\boldsymbol{\theta}, \boldsymbol{\phi}\}$ through an Expectation-Maximization algorithm. In E-step, we infer $p(z_\tau)$ when fixing model parameters. In M-step, when fixing $p(z_\tau)$, $\{\boldsymbol{\theta}, \boldsymbol{\phi}\}$ can be efficiently solved by optimizing Eq. (5) with stochastic gradient descent (SGD). The formula to infer $p(z_\tau)$ and the detailed training algorithm for HTGM can be found in Appendix A.4.

## 3.3 MODEL ADAPTATION

Fig. 1(b) illustrates the adaptation process of HTGM. Given a new $N$-way task $\tau'$ from the meta-test set $\mathcal{D}^{\text{te}}$, its support set $\mathcal{D}_{\tau'}^s$ is fed to the inference network $\psi$ to generate (1) class prototypes $\boldsymbol{\mu}_1^s, ..., \boldsymbol{\mu}_N^s$ (similar to prototypical networks), and (2) distribution $q_{\boldsymbol{\psi}}(\mathbf{v}_{\tau'}|\mathcal{D}_{\tau'}^s)$, from which we sample a task embedding $\mathbf{v}_{\tau'}$. Then $\mathbf{v}_{\tau'}$ is projected to $\mathbf{W}_1\mathbf{v}_{\tau'}, ..., \mathbf{W}_N\mathbf{v}_{\tau'}$ which represent the $N$ optimal choices of class prototypes for task $\tau'$ as learned by the Gibbs distribution in Eq. (2) from the training tasks. They are used to adapt $\boldsymbol{\mu}_1^s, ..., \boldsymbol{\mu}_N^s$ so that the adapted prototypes are drawn towards the closest classes from the mixture component that task $\tau'$ belongs to. The adaptation is performed by selecting the closest optimum for each prototype, *i.e.*, $\hat{\boldsymbol{\mu}}_j' = \alpha\boldsymbol{\mu}_j^s + (1-\alpha)\mathbf{W}_k\mathbf{v}_{\tau'}$ where $k = \arg\min_{1 \leq k \leq N} D(\boldsymbol{\mu}_j^s, \mathbf{W}_k\mathbf{v}_{\tau'})$ using Euclidean distance $D(\cdot, \cdot)$ and $\alpha$ is a hyperparameter. Finally, we (1) assess if $\tau'$ is a novelty by computing the likelihood of $\mathbf{v}_{\tau'}$ in a pre-fitted GMM on the embeddings $\mathbf{v}_\tau$'s of the training tasks in $\mathcal{D}^{\text{tr}}$, and (2) perform classification on each sample $\mathbf{x}_i'$ in the query set $\mathcal{D}_{\tau'}^q$ using the adapted prototypes by $p(y_i' = c|\mathbf{x}_i') = \frac{\exp(-D(f_{\boldsymbol{\theta}}(\mathbf{x}_i'), \hat{\boldsymbol{\mu}}_c'))}{\sum_{j=1}^N \exp(-D(f_{\boldsymbol{\theta}}(\mathbf{x}_i'), \hat{\boldsymbol{\mu}}_j'))}$.

| Setting | Model | Bird | Texture | Aircraft | Fungi | Average |
|---------|-------|------|---------|----------|-------|---------|
| 5-way 1-shot | TAML | 55.77±1.43 | 31.78±1.30 | 48.56±1.37 | 41.00±1.50 | 44.28 |
| | MAML | 53.94±1.45 | 31.66±1.31 | 51.37±1.38 | 42.12±1.36 | 44.77 |
| | Meta-SGD | 55.58±1.43 | 32.38±1.32 | 52.99±1.36 | 41.74±1.34 | 45.67 |
| | MUMOMAML | 56.82±1.49 | 33.81±1.36 | 53.14±1.39 | 42.22±1.40 | 46.50 |
| | HSML | 60.98±1.50 | 35.01±1.36 | 57.38±1.40 | 44.02±1.39 | 49.35 |
| | ARML | 62.33±1.47 | 35.65±1.40 | 58.56±1.41 | 44.82±1.38 | 50.34 |
| | ProtoNet | 61.54±1.27 | 38.84±1.42 | 73.42±1.23 | 46.52±1.42 | 55.08 |
| | MetaOptNet | 62.80±1.29 | 44.30±1.45 | 68.64±1.29 | 47.04±1.38 | 55.70 |
| | ProtoNet-Aug | 65.04±1.29 | 44.68±1.43 | 70.44±1.32 | 49.30±1.40 | 57.37 |
| | NCA | 62.58±1.25 | 40.98±1.44 | 68.70±1.26 | 46.36±1.34 | 54.66 |
| | FEATS | 62.60±1.31 | 44.12±1.49 | 68.86±1.28 | 47.92±1.34 | 55.88 |
| | HTGM (ours) | **70.12±1.28** | **47.76±1.49** | **75.52±1.24** | **52.06±1.41** | **61.37** |
| 5-way 5-shot | TAML | 69.50±0.75 | 45.11±0.69 | 65.92±0.74 | 50.99±0.87 | 57.88 |
| | MAML | 68.52±0.79 | 44.56±0.68 | 66.18±0.71 | 51.85±0.85 | 57.78 |
| | Meta-SGD | 67.87±0.74 | 45.49±0.68 | 66.84±0.70 | 52.51±0.81 | 58.18 |
| | MUMOMAML | 70.49±0.76 | 45.89±0.69 | 67.31±0.68 | 53.96±0.82 | 59.41 |
| | HSML | 71.68±0.73 | 48.08±0.69 | 73.49±0.68 | 56.32±0.80 | 62.39 |
| | ARML | 73.34±0.70 | 49.67±0.67 | 74.88±0.64 | 57.55±0.82 | 63.86 |
| | ProtoNet | 78.88±0.72 | 57.93±0.75 | 86.42±0.57 | 62.52±0.79 | 71.44 |
| | MetaOptNet | 81.66±0.71 | **61.97±0.78** | 84.03±0.56 | 63.80±0.81 | 72.87 |
| | ProtoNet-Aug | 80.62±0.71 | 58.30±0.77 | 87.05±0.53 | 63.62±0.81 | 72.39 |
| | NCA | 79.16±0.75 | 58.69±0.76 | 85.27±0.53 | 61.68±0.80 | 71.20 |
| | FEATS | 78.37±0.72 | 57.02±0.73 | 85.55±0.54 | 61.56±0.80 | 70.63 |
| | HTGM (ours) | **82.27±0.74** | 60.67±0.78 | **88.48±0.52** | **65.70±0.79** | **74.28** |

Table 1: Results (accuracy±95% confidence) of the compared methods on Plain-Multi dataset.

## 4 EXPERIMENTS

In this section, we evaluate HTGM's effectiveness on few-shot classification and novel task detection on benchmark datasets, and compare it with SOTA methods.

**Datasets.** The first is the *Plain-Multi* benchmark proposed in (Yao et al., 2019a). It includes four fine-grained image classification datasets, *i.e.*, CUB-200-2011 (Bird), Describable Textures Dataset (Texture), FGVC of Aircraft (Aircraft), and FGVCx-Fungi (Fungi). In each episode, a task samples classes from one of the four datasets, so that different tasks are from a mixture of the four domains. The second is the *Art-Multi* benchmark from (Yao et al., 2019b), whose distribution is more complex than Plain-Multi. Similar to (Jerfel et al., 2019), each image in Plain-Multi was applied with two filters, *i.e.*, *blur* filter and *pencil* filter, respectively, to simulate a changing distribution of few-shot tasks. Afterwards, together with the original four datasets, a total of 12 datasets comprise Art-Multi, and each task is sampled from one of them. Both benchmarks were divided into the meta-training, meta-validation, and meta-test sets by following their corresponding papers.

**Baselines.** We compare HTGM with the most relevant SOTA methods on meta-learning, including (1) optimization-based methods: MAML (Finn et al., 2017) and Meta-SGD (Li et al., 2017) learn globally shared initialization among tasks. MUMOMAML (Vuorio et al., 2018) is a task-specific method. TAML (Lee et al., 2019a) handles imbalanced tasks. HSML (Yao et al., 2019a) and ARML (Yao et al., 2019b) learn locally shared initial parameters in clusters of tasks and neighborhoods of a meta-graph of tasks, respectively; and (2) Metric-based methods: ProtoNet (Snell et al., 2017) learns prototypes with distance-based classifier. MetaOptNet (Lee et al., 2019c) uses SVM classifier with kernel metrics. ProtoNet-Aug (Su et al., 2020), FEATS (Ye et al., 2020) and NCA (Laenen & Bertinetto, 2021) were built upon ProtoNet by augmenting images (*e.g.*, rotation, jigsaw), adding prototype aggregator (*e.g.*, Transformer), and using contrastive training loss, (instead of prototype-based loss), respectively. The detailed setup of these methods is deferred to Appendix D.

**Implementation.** Following (Tian et al., 2020), optimization-based baselines use the standard four-block convolutional layers the base learner, metric-based methods use ResNet-12 as the base learner. In our experiments, we observed optimization-based methods have out-of-memory issue when using ResNet-12, indicating their limitation in using large-scale backbone networks. The output of dimension of these networks is 640 (MetaOptNet uses 16000 as in its paper). For training, Adam

| Setting | Model | Original | Blur | Pencil | Average |
|---|---|---|---|---|---|
| 5-way,1-shot | TAML | 42.22±1.39 | 40.02±1.41 | 35.11±1.34 | 39.11 |
| | MAML | 42.70±1.35 | 40.53±1.38 | 36.71±1.37 | 39.98 |
| | Meta-SGD | 44.21±1.38 | 42.36±1.39 | 37.21±1.39 | 41.26 |
| | MUMOMAML | 45.63±1.39 | 41.59±1.38 | 39.24±1.36 | 42.15 |
| | HSML | 47.92±1.34 | 44.43±1.34 | 41.44±1.34 | 44.60 |
| | ARML | 45.68±1.34 | 42.62±1.34 | 39.78±1.34 | 42.69 |
| | ProtoNet | 55.23±1.31 | 51.70±1.42 | 49.22±1.44 | 52.05 |
| | MetaOptNet | 56.10±1.35 | 52.33±1.43 | 49.08±1.45 | 52.50 |
| | ProtoNet-Aug | 57.63±1.34 | 55.00±1.40 | 49.73±1.53 | 54.12 |
| | NCA | 56.12±1.35 | 50.80±1.49 | 47.99±1.45 | 51.64 |
| | FEATS | 54.33±1.33 | 50.90±1.48 | 47.96±1.48 | 51.07 |
| | HTGM (ours) | **61.18±1.34** | **58.80±1.42** | **53.23±1.48** | **57.74** |
| 5-way,1-shot | TAML | 58.54±0.73 | 55.23±0.75 | 49.23±0.75 | 54.33 |
| | MAML | 58.30±0.74 | 55.71±0.74 | 49.59±0.73 | 54.50 |
| | Meta-SGD | 57.82±0.72 | 55.54±0.73 | 50.24±0.72 | 54.53 |
| | MUMOMAML | 58.60±0.75 | 56.29±0.72 | 51.15±0.73 | 55.35 |
| | HSML | 60.63±0.73 | 57.91±0.72 | 53.93±0.72 | 57.49 |
| | ARML | 61.78±0.74 | 58.73±0.75 | 55.27±0.73 | 58.59 |
| | ProtoNet | 71.34±0.73 | 67.28±0.75 | 64.32±0.76 | 67.65 |
| | MetaOptNet | 72.33±0.72 | 68.90±0.78 | 63.89±0.71 | 68.37 |
| | ProtoNet-Aug | 72.87±0.71 | 70.50±0.72 | 63.98±0.73 | 68.78 |
| | NCA | 72.44±0.72 | 67.33±0.71 | 62.98±0.78 | 67.58 |
| | FEATS | 71.99±0.71 | 67.54±0.72 | 63.09±0.76 | 67.54 |
| | HTGM (ours) | **74.67±0.70** | **71.24±0.73** | **65.22±0.77** | **70.37** |

Table 2: Results (accuracy±95% confidence) of the compared methods on Art-Multi dataset.

optimizer was used. Each batch contains 4 tasks. Each model was trained with 20000 episodes. The learning rate of metric-based methods is $1e^{-3}$. The learning rates for inner- and outer-loops for optimization-based methods are $1e^{-3}$ and $1e^{-4}$. The weight decay was $1e^{-4}$. For HTGM, we set $\sigma = 1.0$, $\bar{\sigma} = 0.1$, $\alpha = 0.5$ (0.9) for 1-shot (5-shot) tasks. The number of mixture components $r$ varies w.r.t. different datasets, and was grid-searched within $[2, 4, 8, 16, 32]$. All hyperparameters were set according to the meta-validation sets.

## 4.1 EXPERIMENTAL RESULTS

**Few-shot classification.** Following (Tian et al., 2020), we report the mean accuracy and 95% confidence interval of 1000 random tasks with 5-way 1-shot/5-shot, 5/25-query tests. Following (Yao et al., 2019b), we report the accuracy of each domain (Bird, Texture, Aircraft and Fungi) and the overall average accuracy for Plain-Multi, and report the accuracy of each image filtering strategy and the overall average accuracy for Art-Multi.

Table 1 and 2 summarize the results. From the tables, we have several observations. First, metric-based methods generally outperform optimization-based methods. This is because of the efficiency of metric-based methods, enabling them to fit larger backbone network, which is consistent with the results in (Tian et al., 2020). Built upon metric-based method, HTGM only introduce few distribution-related parameters thus has the flexibility to scale with the encoder size. Second, baselines designed for dealing with mixture distributions of tasks, *i.e.*, HSML and ARML, outperform their counterparts without such design, demonstrating the importance to consider mixture task distribution in practice. Finally, HTGM outperform the SOTA baselines in most cases by large margins, suggesting its effectiveness of modeling the generative process of tasks.

**Novel task detection.** We also evaluate HTGM on the task of detecting novel N-way-K-shot tasks (N=5, K=1) that are drawn out of the training task distributions. To this end, we train each model in comparison on the Original domain in Art-Multi dataset, and test the model on tasks drawn from either Original domain (*i.e.*, known tasks), or {Blur, Pencil} domains (*i.e.*, novel tasks), and evaluate if the model can tell whether a testing task is known or novel.

For comparison, since none of the baselines detects novel tasks, we adapt them as follows. For metric-based methods, since they use a fixed encoder for all training/testing tasks, we averaged the

Figure 2: The frequency of tasks *w.r.t.* the normalized likelihood for (a) HSML (b) MetaOptNet (c) ProtoNet-Aug (d) HTGM. The x-axis ranges vary as only 95% tasks with top scores were preserved.

sample embeddings in each task to represent the task. Then a separate GMM model was built upon the training task embeddings, and its likelihood was adapted to score the novelty of testing tasks. However, optimization-based models perform gradient descent on the support set of each task, leading to varying encoders per task. As such, sample embeddings of different tasks are not comparable, and we cannot obtain task embeddings in the same way as before. Among them, only HSML has an augmented task-level encoder for task embedding, allowing us to include it for comparison. For fair comparison, our HTGM also trains a GMM on its task embeddings for detecting novel tasks. Moreover, two HTGM variants were included for ablation analysis to understand some design choices: (1) HTGM-Gaussian replaces the Gibbs distribution in Eq. (2) with a Gaussian distribution; (2) HTGM w/o GMM removes the task-level GM, *i.e.*, the third term in Eq. (3). The ablation variants' classification results are in Appendix C. Following (Cheng & Vasconcelos, 2021; Vaze et al., 2022; Sharma et al., 2021), we report Area Under ROC (AUROC), Average Precision (AP), and Max-F1 for performance evaluation.

Table 3 summarize the results, from which we observe HTGM outperforms all baselines over all evaluation metrics, indicating the superior quality of task embeddings learned by our model. The embeddings follow the specified mixture distribution of tasks $p(\mathbf{v}_\tau)$ as described in Sec. 3.1, which fit of the mixture data well hence allowing to detect novel tasks that are close to the boundary. Since the baselines learn embeddings without explicit constraint, they even don't fit the post-hoc GMM very well. Moreover, HTGM outperforms HTGM w/o GMM, which is even worse than some other baselines. This further validates the neces-

| Model | AUROC | AP | Max-F1 |
|---|---|---|---|
| HSML | 55.96 | 37.94 | 50.17 |
| ProtoNet | 65.17 | 41.51 | 56.07 |
| MetaOptNet | 72.71 | 63.77 | 58.33 |
| NCA | 66.28 | 51.45 | 52.74 |
| ProtoNet-Aug | 72.67 | 57.93 | 59.07 |
| FEATS | 59.35 | 42.57 | 49.31 |
| HTGM w/o GMM | 70.24 | 62.45 | 57.75 |
| HTGM-Gaussian | 74.06 | 66.18 | **60.62** |
| HTGM | **75.66** | **68.03** | 60.51 |

Table 3: Comparison between HTGM and its variants and the applicable baselines on novel task detection.

sity to introduce the regularization of task-level mixture distribution $p(\mathbf{v}_\tau)$. Also, the drops of AUROC and AP of HTGM-Gaussian demonstrate the importance of our unique design of the Gibbs distribution for the task-conditional distribution in Eq. (2). Similar to (Vaze et al., 2022), in Fig. 2, we visualized the normalized likelihood histogram of known and novel tasks for HSML, ProtoNet-Aug (the near-best metric-based baseline), MetaOptNet and HTGM. The figures indicate the likelihoods (*i.e.*, novelty scores) of HTGM are more distinguishable for known and novel tasks than the baselines. We also evaluated the impacts of hypaparameters, which is in Appendix B.

## 5 CONCLUSION

In this paper, we propose a new method named Hierarchical Gaussian Mixture based Task Generative Model (HTGM). HTGM models the generative process of task episode and conduct maximum likelihood estimation to learn task embeddings that can help us adjust prototypes acquired by feature extractor and acquire more competitive performance. Meanwhile, by explicitly modeling the distribution of tasks in embedding space, HTGM can effectively detect the tasks that are drawn from distributions unseen in the meta-training stage. The extensive experiment results indicate the advantage of the proposed method on both few-shot classification and out-of-distribution task detection.

REFERENCES

Alessandro Achille, Michael Lam, Rahul Tewari, Avinash Ravichandran, Subhransu Maji, Charless C Fowlkes, Stefano Soatto, and Pietro Perona. Task2vec: Task embedding for meta-learning. In *ICCV*, pp. 6430–6439, 2019.

Brandon Amos and J. Zico Kolter. OptNet: Differentiable optimization as a layer in neural networks. In *ICML*, volume 70 of *Proceedings of Machine Learning Research*, pp. 136–145. PMLR, 2017.

Thomas L Athey, Benjamin D Pedigo, Tingshan Liu, and Joshua T Vogelstein. Autogmm: Automatic and hierarchical gaussian mixture modeling in python. *arXiv preprint arXiv:1909.02688*, 2019.

M. Christopher Bishop. *Pattern recognition and machine learning*. Springer, 2006.

Isaac S Chan and Geoffrey S Ginsburg. Personalized medicine: progress and promise. *Annual review of genomics and human genetics*, 12:217–244, 2011.

Jiacheng Cheng and Nuno Vasconcelos. Learning deep classifiers consistent with fine-grained novelty detection. In *CVPR*, pp. 1664–1673, 2021.

Chelsea Finn, Pieter Abbeel, and Sergey Levine. Model-agnostic meta-learning for fast adaptation of deep networks. In *ICML*, pp. 1126–1135. PMLR, 2017.

Jacob Goldberger and Sam T Roweis. Hierarchical clustering of a mixture model. In *NeurIPS*, pp. 505–512, 2005.

Minki Jeong, Seokeon Choi, and Changick Kim. Few-shot open-set recognition by transformation consistency. In *CVPR*, pp. 12566–12575, 2021.

Ghassen Jerfel, Erin Grant, Tom Griffiths, and Katherine A Heller. Reconciling meta-learning and continual learning with online mixtures of tasks. *NeurIPS*, 32, 2019.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Steinar Laenen and Luca Bertinetto. On episodes, prototypical networks, and few-shot learning. *NeurIPS*, 34:24581–24592, 2021.

Yann LeCun, Sumit Chopra, Raia Hadsell, M Ranzato, and F Huang. A tutorial on energy-based learning. *Predicting structured data*, 1(0), 2006.

Hae Beom Lee, Hayeon Lee, Donghyun Na, Saehoon Kim, Minseop Park, Eunho Yang, and Sung Ju Hwang. Learning to balance: Bayesian meta-learning for imbalanced and out-of-distribution tasks. *arXiv preprint arXiv:1905.12917*, 2019a.

Kimin Lee, Kibok Lee, Honglak Lee, and Jinwoo Shin. A simple unified framework for detecting out-of-distribution samples and adversarial attacks. *NeurIPS*, 31, 2018.

Kimin Lee, Sukmin Yun, Kibok Lee, Honglak Lee, Bo Li, and Jinwoo Shin. Robust inference via generative classifiers for handling noisy labels. In *ICML*, pp. 3763–3772. PMLR, 2019b.

Kwonjoon Lee, Subhransu Maji, Avinash Ravichandran, and Stefano Soatto. Meta-learning with differentiable convex optimization. In *CVPR*, pp. 10657–10665, 2019c.

Yoonho Lee and Seungjin Choi. Gradient-based meta-learning with learned layerwise metric and subspace. In *ICML*, pp. 2927–2936. PMLR, 2018.

Zhenguo Li, Fengwei Zhou, Fei Chen, and Hang Li. Meta-sgd: Learning to learn quickly for few-shot learning. *arXiv preprint arXiv:1707.09835*, 2017.

Shiyu Liang, Yixuan Li, and R Srikant. Enhancing the reliability of out-of-distribution image detection in neural networks. In *ICLR*, 2018.

Weitang Liu, Xiaoyun Wang, John Owens, and Yixuan Li. Energy-based out-of-distribution detection. pp. 21464–21475, 2020.

Tomas Mikolov, Ilya Sutskever, Kai Chen, Greg S Corrado, and Jeff Dean. Distributed representations of words and phrases and their compositionality. In *NeurIPS*, 2013.

Nikhil Mishra, Mostafa Rohaninejad, Xi Chen, and Pieter Abbeel. A simple neural attentive meta-learner. In *ICLR*, 2018.

Jingchao Ni, Wei Cheng, Zhengzhang Chen, Takayoshi Asakura, Tomoya Soma, Sho Kato, and Haifeng Chen. Superclass-conditional gaussian mixture model for learning fine-grained embeddings. In *ICLR*, 2022.

Łukasz P Olech and Mariusz Paradowski. Hierarchical gaussian mixture model with objects attached to terminal and non-terminal dendrogram nodes. In *Proceedings of the 9th International Conference on Computer Recognition Systems CORES 2015*, pp. 191–201. Springer, 2016.

Boris Oreshkin, Pau Rodríguez López, and Alexandre Lacoste. Tadam: Task dependent adaptive metric for improved few-shot learning. In *NeurIPS*, 2018.

Sanjay Purushotham, Wilka Carvalho, Tanachat Nilanon, and Yan Liu. Variational recurrent adversarial deep domain adaptation. In *ICLR*, 2017.

Andrei A Rusu, Dushyant Rao, Jakub Sygnowski, Oriol Vinyals, Razvan Pascanu, Simon Osindero, and Raia Hadsell. Meta-learning with latent embedding optimization. In *ICLR*, 2018.

Adam Santoro, Sergey Bartunov, Matthew Botvinick, Daan Wierstra, and Timothy Lillicrap. Meta-learning with memory-augmented neural networks. In *ICML*, pp. 1842–1850. PMLR, 2016.

Karishma Sharma, Yizhou Zhang, Emilio Ferrara, and Yan Liu. Identifying coordinated accounts on social media through hidden influence and group behaviours. In *SIGKDD*, pp. 1441–1451, 2021.

Satya Narayan Shukla and Benjamin Marlin. Interpolation-prediction networks for irregularly sampled time series. In *ICLR*, 2019.

Jake Snell, Kevin Swersky, and Richard Zemel. Prototypical networks for few-shot learning. In *NeurIPS*, 2017.

Jong-Chyi Su, Subhransu Maji, and Bharath Hariharan. When does self-supervision improve few-shot learning? In *ECCV*, pp. 645–666. Springer, 2020.

Yonglong Tian, Yue Wang, Dilip Krishnan, Joshua B Tenenbaum, and Phillip Isola. Rethinking few-shot image classification: a good embedding is all you need? In *ECCV*, pp. 266–282. Springer, 2020.

Sagar Vaze, Kai Han, Andrea Vedaldi, and Andrew Zisserman. Open-set recognition: A good closed-set classifier is all you need. In *ICLR*, 2022.

Oriol Vinyals, Charles Blundell, Timothy Lillicrap, Daan Wierstra, et al. Matching networks for one shot learning. *NIPS*, 29, 2016.

Risto Vuorio, Shao-Hua Sun, Hexiang Hu, and Joseph J Lim. Toward multimodal model-agnostic meta-learning. *arXiv preprint arXiv:1812.07172*, 2018.

Yinjun Wu, Jingchao Ni, Wei Cheng, Bo Zong, Dongjin Song, Zhengzhang Chen, Yanchi Liu, Xuchao Zhang, Haifeng Chen, and Susan B Davidson. Dynamic gaussian mixture based deep generative model for robust forecasting on sparse multivariate time series. In *AAAI*, volume 35, pp. 651–659, 2021.

Huaxiu Yao, Ying Wei, Junzhou Huang, and Zhenhui Li. Hierarchically structured meta-learning. In *ICML*, pp. 7045–7054. PMLR, 2019a.

Huaxiu Yao, Xian Wu, Zhiqiang Tao, Yaliang Li, Bolin Ding, Ruirui Li, and Zhenhui Li. Automated relational meta-learning. In *ICLR*, 2019b.

Han-Jia Ye, Hexiang Hu, De-Chuan Zhan, and Fei Sha. Few-shot learning via embedding adaptation with set-to-set functions. In *CVPR*, pp. 8808–8817, 2020.

# A  APPENDIX FOR DETAILS OF DERIVING HTGM

## A.1  THE LOWER-BOUND OF THE LIKELIHOOD FUNCTION

In this section, we provide the details of the lower-bound in Eq. (3). By introducing the approximated posterior $q_{\psi}(\mathbf{v}_\tau|\mathcal{D}_\tau^s)$, the likelihood in Eq. (1) becomes (the superscript $*$ is neglected for clarity)

$$
\begin{aligned}
\ell(\mathcal{D}_\tau, \boldsymbol{\theta}) &= \frac{1}{n}\sum_{i=1}^{n}\log p_{\boldsymbol{\theta}}(\mathbf{e}_i|y_i) + \frac{1}{n}\sum_{i=1}^{n}\log\Big(\int_{\mathbf{v}_\tau} p(y_i|\mathbf{v}_\tau)p(\mathbf{v}_\tau)d\mathbf{v}_\tau\Big) \\
&= \frac{1}{n}\sum_{i=1}^{n}\log p_{\boldsymbol{\theta}}(\mathbf{e}_i|y_i) + \frac{1}{n}\sum_{i=1}^{n}\log\Big(\int_{\mathbf{v}_\tau} p(y_i|\mathbf{v}_\tau)p(\mathbf{v}_\tau)\frac{q_{\psi}(\mathbf{v}_\tau|\mathcal{D}_\tau^s)}{q_{\psi}(\mathbf{v}_\tau|\mathcal{D}_\tau^s)}d\mathbf{v}_\tau\Big) \\
&= \frac{1}{n}\sum_{i=1}^{n}\log p_{\boldsymbol{\theta}}(\mathbf{e}_i|y_i) + \frac{1}{n}\sum_{i=1}^{n}\log\Big(\int_{\mathbf{v}_\tau} q_{\psi}(\mathbf{v}_\tau|\mathcal{D}_\tau^s)\frac{p(y_i|\mathbf{v}_\tau)p(\mathbf{v}_\tau)}{q_{\psi}(\mathbf{v}_\tau|\mathcal{D}_\tau^s)}d\mathbf{v}_\tau\Big) \\
&\geq \frac{1}{n}\sum_{i=1}^{n}\log p_{\boldsymbol{\theta}}(\mathbf{e}_i|y_i) + \frac{1}{n}\sum_{i=1}^{n}\int_{\mathbf{v}_\tau} q_{\psi}(\mathbf{v}_\tau|\mathcal{D}_\tau^s)\Big[\log p(y_i|\mathbf{v}_\tau) + \log p(\mathbf{v}_\tau) - \log q_{\psi}(\mathbf{v}_\tau|\mathcal{D}_\tau^s)\Big]d\mathbf{v}_\tau \\
&= \frac{1}{n}\sum_{i=1}^{n}\log p_{\boldsymbol{\theta}}(\mathbf{e}_i|y_i) + \frac{1}{n}\sum_{i=1}^{n}\int_{\mathbf{v}_\tau} q_{\psi}(\mathbf{v}_\tau|\mathcal{D}_\tau^s)\Big[\log p(y_i|\mathbf{v}_\tau) + \log p(\mathbf{v}_\tau)\Big]d\mathbf{v}_\tau - \int_{\mathbf{v}_\tau} q_{\psi}(\mathbf{v}_\tau|\mathcal{D}_\tau^s)\log q_{\psi}(\mathbf{v}_\tau|\mathcal{D}_\tau^s)d\mathbf{v}_\tau \\
&= \frac{1}{n}\sum_{i=1}^{n}\log p_{\boldsymbol{\theta}}(\mathbf{e}_i|y_i) + \frac{1}{n}\sum_{i=1}^{n}\mathbb{E}_{\mathbf{v}_\tau \sim q_{\psi}(\mathbf{v}_\tau|\mathcal{D}_\tau^s)}\Big[\log p(y_i|\mathbf{v}_\tau) + \log p(\mathbf{v}_\tau)\Big] + H(q_{\psi}(\mathbf{v}_\tau|\mathcal{D}_\tau^s)) \\
&= \frac{1}{n}\sum_{i=1}^{n}\log p_{\boldsymbol{\theta}}(\mathbf{e}_i|y_i) + \frac{1}{n}\sum_{i=1}^{n}\mathbb{E}_{\mathbf{v}_\tau \sim q_{\psi}(\mathbf{v}_\tau|\mathcal{D}_\tau^s)}\Big[\log p(y_i|\mathbf{v}_\tau) + \log\Big(\sum_{z_\tau=1}^{r} p(\mathbf{v}_\tau|z_\tau)p(z_\tau)\Big)\Big] + H(q_{\psi}(\mathbf{v}_\tau|\mathcal{D}_\tau^s))
\end{aligned}
$$

(7)

where the fourth step uses Jensen's inequality. This completes the derivation of Eq. (3).

## A.2  THE UPPER-BOUND OF THE PARTITION FUNCTION

In Sec. 3.2, we apply an upper bound for the partition function for computational tractability, whose derivation is as follows:

$$
\begin{aligned}
\int_{\boldsymbol{\mu}_{y_i}} \exp\big[-E_{\boldsymbol{\omega}}(\boldsymbol{\mu}_{y_i};\mathbf{v}_\tau)\big]d\boldsymbol{\mu}_{y_i} &= \int_{\boldsymbol{\mu}_{y_i}} \exp\big[-\min\big(\{\|\boldsymbol{\mu}_{y_i}-\mathbf{W}_j\mathbf{v}_\tau\|_2^2\}_{j=1}^{N}\big)\big]d\boldsymbol{\mu}_{y_i} \\
&= \int_{\boldsymbol{\mu}_{y_i}} \max\big(\{\exp(-\|\boldsymbol{\mu}_{y_i}-\mathbf{W}_j\mathbf{v}_\tau\|_2^2)\}_{j=1}^{N}\big)d\boldsymbol{\mu}_{y_i} \\
&< \int_{\boldsymbol{\mu}_{y_i}} \sum_{j=1}^{N}\exp(-\|\boldsymbol{\mu}_{y_i}-\mathbf{W}_j\mathbf{v}_\tau\|_2^2)d\boldsymbol{\mu}_{y_i} \\
&= \sum_{j=1}^{N}\int_{\boldsymbol{\mu}_{y_i}} \exp(-\|\boldsymbol{\mu}_{y_i}-\mathbf{W}_j\mathbf{v}_\tau\|_2^2)d\boldsymbol{\mu}_{y_i}
\end{aligned}
$$

(8)

According to the multidimensional Gaussian integral, we know that:

$$
\int_{\boldsymbol{\mu}_{y_i}} \exp(-\|\boldsymbol{\mu}_{y_i}-\mathbf{W}_j\mathbf{v}_\tau\|_2^2)d\boldsymbol{\mu}_{y_i} = \sqrt{2^{d-1}\pi^d}
$$

(9)

Thus, we have:

$$
\int_{\boldsymbol{\mu}_{y_i}} \exp\big[-E_{\boldsymbol{\omega}}(\boldsymbol{\mu}_{y_i};\mathbf{v}_\tau)\big]d\boldsymbol{\mu}_{y_i} \leq N\sqrt{2^{d-1}\pi^d}
$$

(10)

## A.3  THE PROOF OF THEOREM 1

*Proof.* Let $B_j$ denote a ball in $\mathbb{R}^d$. Its center is at $\mathbf{W}_j\mathbf{v}_\tau$ and its radius is $D(\mathbf{W}_k\mathbf{v}_\tau, \mathbf{W}_t\mathbf{v}_\tau)/3$. Because $\mathbf{W}_k\mathbf{v}_\tau$ and $\mathbf{W}_t\mathbf{v}_\tau$ $(1 \leq k,t \leq N)$ is the pair with the smallest Euclidean distance $D(\mathbf{W}_k\mathbf{v}_\tau, \mathbf{W}_t\mathbf{v}_\tau)$, for any pair of balls $B_j$ and $B_m$ we have:

$$
B_j \cup B_m = \varnothing
$$

(11)

In other words, there is no overlap between any pair of balls. Therefore, if we compute the integral over the joint of all balls, we have:

$$\int_{\boldsymbol{\mu}_{y_i} \in \bigcup_{m=1}^{N} B_m} \exp\big[-E_{\boldsymbol{\omega}}(\boldsymbol{\mu}_{y_i}; \mathbf{v}_\tau)\big] d\boldsymbol{\mu}_{y_i} = \sum_{m=1}^{N} \int_{\boldsymbol{\mu}_{y_i} \in B_m} \exp\big[-E_{\boldsymbol{\omega}}(\boldsymbol{\mu}_{y_i}; \mathbf{v}_\tau)\big] d\boldsymbol{\mu}_{y_i} \tag{12}$$

Also, because there is no overlap between any pair of balls, for each point $\boldsymbol{\mu}_{y_i} \in B_m$, we have:

$$-\min\left(\{||\boldsymbol{\mu}_{y_i} - \mathbf{W}_j \mathbf{v}_\tau||_2^2\}_{j=1}^{N}\right) = -||\boldsymbol{\mu}_{y_i} - \mathbf{W}_m \mathbf{v}_\tau||_2^2 \tag{13}$$

Therefore, we can have the following derivation:

$$\begin{aligned} \int_{\boldsymbol{\mu}_{y_i} \in \bigcup_{m=1}^{N} B_m} \exp\big[-E_{\boldsymbol{\omega}}(\boldsymbol{\mu}_{y_i}; \mathbf{v}_\tau)\big] d\boldsymbol{\mu}_{y_i} &= \sum_{m=1}^{N} \int_{\boldsymbol{\mu}_{y_i} \in B_m} \exp\big[-E_{\boldsymbol{\omega}}(\boldsymbol{\mu}_{y_i}; \mathbf{v}_\tau)\big] d\boldsymbol{\mu}_{y_i} \\ &= \sum_{m=1}^{N} \int_{\boldsymbol{\mu}_{y_i} \in B_m} \exp\left(-||\boldsymbol{\mu}_{y_i} - \mathbf{W}_m \mathbf{v}_\tau||_2^2\right) d\boldsymbol{\mu}_{y_i} \\ &= N \int_{\boldsymbol{\mu}_{y_i} \in B_m} \exp\left(-||\boldsymbol{\mu}_{y_i} - \mathbf{W}_m \mathbf{v}_\tau||_2^2\right) d\boldsymbol{\mu}_{y_i} \end{aligned} \tag{14}$$

Meanwhile, since $\bigcup_{m=1}^{N} B_m$ is an sub-area of the whole $\mathbb{R}^d$ space, we have:

$$\int_{\boldsymbol{\mu}_{y_i} \in \bigcup_{m=1}^{N} B_m} \exp\big[-E_{\boldsymbol{\omega}}(\boldsymbol{\mu}_{y_i}; \mathbf{v}_\tau)\big] d\boldsymbol{\mu}_{y_i} \leq \int_{\boldsymbol{\mu}_{y_i}} \exp\big[-E_{\boldsymbol{\omega}}(\boldsymbol{\mu}_{y_i}; \mathbf{v}_\tau)\big] d\boldsymbol{\mu}_{y_i} \tag{15}$$

Based on multidimensional Gaussian integral, we know that:

$$\lim_{D(\mathbf{W}_r \mathbf{v}_\tau, \mathbf{W}_t \mathbf{v}_\tau) \to \infty} \int_{\boldsymbol{\mu}_{y_i} \in B_m} \exp\big[-E_{\boldsymbol{\omega}}(\boldsymbol{\mu}_{y_i}; \mathbf{v}_\tau)\big] d\boldsymbol{\mu}_{y_i} = \sqrt{2^{d-1}\pi^d} \tag{16}$$

Thus, we have

$$\lim_{D(\mathbf{W}_r \mathbf{v}_\tau, \mathbf{W}_t \mathbf{v}_\tau) \to \infty} \int_{\boldsymbol{\mu}_{y_i}} \exp\big[-E_{\boldsymbol{\omega}}(\boldsymbol{\mu}_{y_i}; \mathbf{v}_\tau)\big] d\boldsymbol{\mu}_{y_i} \geq N\sqrt{2^{d-1}\pi^d} \tag{17}$$

Meanwhile, since $N\sqrt{2^{d-1}\pi^d}$ is its upper bound, based on the squeeze theorem, we have:

$$\lim_{D(\mathbf{W}_r \mathbf{v}_\tau, \mathbf{W}_t \mathbf{v}_\tau) \to \infty} \int_{\boldsymbol{\mu}_{y_i}} \exp\big[-E_{\boldsymbol{\omega}}(\boldsymbol{\mu}_{y_i}; \mathbf{v}_\tau)\big] d\boldsymbol{\mu}_{y_i} = N\sqrt{2^{d-1}\pi^d} \tag{18}$$

$\square$

## A.4 THE TRAINING ALGORITHM OF HTGM

The training algorithm of HTGM is summarized in Algorithm 1.

## B HYPER PARAMETER ANALYSIS OF HTGM

In HTGM, three hyper-parameters are unique compared to common meta-learning models: $\sigma_{y_i}$ in $p_{\boldsymbol{\theta}}(\mathbf{e}_i|y_i)$, $\bar{\sigma}$ in $q_{\boldsymbol{\psi}}(\mathbf{v}_\tau|\mathcal{D}_\tau^s)$, and the component number of the GMM prior distribution. The following experiment results indicate that our model is robust to the setting of the two variances and validate our choice of the component number.

### B.1 ANALYSIS OF $\sigma_{y_i}$

Tabel 5 report the effect of different $\sigma_{y_i}$ on the classification performance (5-way-1-shot classification on Multi-Plain dataset). As shown in the table, although too low or too high setting of this hyper-parameter will hurt the performance, in general the model is robust toward the setting of $\sigma_{y_i}$.

---

**Algorithm 1:** Hierarchical Gaussian Mixture based Task Generative Model (HTGM)

---

**Input:** encoder $f_{\boldsymbol{\theta}}$, training dataset $\mathcal{D}_{\text{train}}$, hyperparameters $r$, $\sigma$
**Output:** model parameters $\{\boldsymbol{\theta}, \boldsymbol{\phi}\}$

---

1 Pre-train feature extractor via ProtoNet with augmentations.
2 Pre-train energy functions in Eq. 2 by maximizing $\frac{1}{n}\sum_{i=1}^{n}\log p_{\boldsymbol{\theta},\boldsymbol{\phi}}(\mathbf{e}_i|y_i) + \log p_{\boldsymbol{\phi}}(y_i|\mathbf{v}_\tau)$
3 **for** $i \leftarrow 1$ *to MaxEpoch* **do**
    `/* E-step */`
4     $V = \varnothing$
5     **for** $(\mathbf{x}^s, y^s, \mathbf{x}^q, y^q)$ *in Dataloader($\mathcal{D}_{train}$)* **do**
        `/* load a task episode` $(\mathbf{x}^s, y^s, \mathbf{x}^q, y^q)$ `*/`
6         $\mathbf{e}^s = f_{\boldsymbol{\theta}}(\mathbf{x}^s)$         `// get embeddings from support set`
7         $\hat{\boldsymbol{\mu}}_{z_\tau} = \text{Task-Pooling(Class-Pooling}(\mathbf{e}^s))$     `// get the mean of` $q_{\boldsymbol{\psi}}(\mathbf{v}_\tau|\mathcal{D}_\tau^s)$ `via`
        `pooling`
8         Sample a task embedding $\mathbf{v}_\tau$ from $q_{\boldsymbol{\psi}}(\mathbf{v}_\tau|\mathcal{D}_\tau^s) = \mathcal{N}(\hat{\boldsymbol{\mu}}_{z_\tau}, \bar{\sigma}^2\mathbf{I})$
9         $V = V \cup \{\mathbf{v}_\tau\}$
10     **end**
11     Fit the Gaussian Mixture Model's parameters $(\boldsymbol{\mu}_{y_i}, \bar{\boldsymbol{\Sigma}}_{z_\tau})$ with $V$. `// Update the GMM model`
12     Labeling $z_\tau$ for each task $(\mathbf{x}^s, y^s, \mathbf{x}^q, y^q)$ with the GMM.     `// Inferring posterior`
    `/* M-step */`
13     **for** $(\mathbf{x}^s, y^s, \mathbf{x}^q, y^q, z_\tau)$ *in Dataloader($\mathcal{D}_{train}$)* **do**
        `/* load a task episode` $(\mathbf{x}^s, y^s, \mathbf{x}^q, y^q)$ `with its predicted label` $z_\tau$ `*/`
14         $\mathbf{e}^s, \mathbf{e}^q = f_{\boldsymbol{\theta}}(\mathbf{x}^s), f_{\boldsymbol{\theta}}(\mathbf{x}^q)$         `// forward pass through the encoder`
15         $\boldsymbol{\mu}^s = \text{Class-Pooling}(\mathbf{e}^s)$
16         $\hat{\boldsymbol{\mu}}_{z_\tau} = \text{Task-Pooling}(\mathbf{v})$     `// get the mean of` $q_{\boldsymbol{\psi}}(\mathbf{v}_\tau|\mathcal{D}_\tau^s)$ `via task pooling`
17         Sample a task embedding $\mathbf{v}_\tau$ from $q_{\boldsymbol{\psi}}(\mathbf{v}_\tau|\mathcal{D}_\tau^s) = \mathcal{N}(\hat{\boldsymbol{\mu}}_{z_\tau}, \bar{\sigma}^2\mathbf{I})$
18         **for** *class $j$ in $y$* **do**
19             $\hat{\boldsymbol{\mu}}'_j = \alpha\boldsymbol{\mu}^s_j + (1-\alpha)\mathbf{W}_k\mathbf{v}_{\tau'}$ where $k = \arg\min_{1\leq k\leq N} D(\boldsymbol{\mu}^s_j, \mathbf{W}_k\mathbf{v}_{\tau'})$ using Euclidean
            distance $D(\cdot, \cdot)$
20         **end**
21         Compute $\log p_{\theta,\phi}(e_i|y_i)$ with $\hat{\boldsymbol{\mu}}'$ and $\mathbf{e}^q$
22         Compute objective function $\mathcal{L}(\theta) = \log p_{\theta,\phi}(e_i|y_i) + \log p_\phi(y_i|\mathbf{v}_\tau) + \log p_\phi(\mathbf{v}_\tau|z_\tau)$
23         Run a SGD step to optimize $\mathcal{L}(\theta)$
24     **end**
25 **end**

---

| Setting of $\sigma_{y_i}$ | Bird | Texture | Aircraft | Fungi |
|---|---|---|---|---|
| 0.1 | 69.33 | 46.92 | 75.20 | 50.78 |
| 0.5 | 70.00 | **47.98** | 75.38 | **52.38** |
| 1.0 (Ours) | **70.12** | 47.76 | **75.52** | 52.06 |
| 10.0 | 69.4 | 47.28 | 75.32 | 51.5 |

Table 4: Analysis of different $\sigma_{y_i}$

## B.2 ANALYSIS OF $\bar{\sigma}$

Tabel 5 summarize how different $\bar{\sigma}$ influence classification performance (5-way-1-shot classification on Multi-Plain dataset). In general, different settings of $\sigma_{y_i}$ will influence the model performance at a marginal level, indicating our model's robustness toward this hyper-parameter.

| Setting of $\bar{\sigma}$ | Bird | Texture | Aircraft | Fungi |
|---|---|---|---|---|
| 0.05 | 69.78 | **48.36** | 74.36 | 51.34 |
| 0.1(Ours) | **70.12** | 47.76 | **75.52** | **52.06** |
| 0.2 | 70.02 | 47.50 | 75.30 | 51.74 |
| 0.5 | 69.02 | 46.66 | 74.46 | 51.00 |

Table 5: Analysis of different $\bar{\sigma}$

| Component Number | 2 | 4 | 8 | 16 | 32 |
|---|---|---|---|---|---|
| silhouette score | 47.70 | 57.61 | 12.76 | 7.81 | 6.19 |

Table 6: Analysis of different component number

| Setting of $\bar{\sigma}$ | Bird | Texture | Aircraft | Fungi |
|---|---|---|---|---|
| HTGM w/o GMM | 68.86 | **48.00** | **75.74** | **52.28** |
| HTGM-Gaussian | 69.52 | 47.3 | 75.38 | 51.34 |
| HTGM | **70.12** | 47.76 | 75.52 | 52.06 |

Table 7: Analysis of different $\bar{\sigma}$

### B.3 IMPACT OF GMM COMPONENT NUMBER

Different choice of the GMM component number does not significantly influence the model classification performance. However, the clustering quality may varies due to the component number. Here, we report the silhouette score with different component number in Table 6. Based on this result, we can see that selecting a component number close to the ground-truth component number of the distribution can benefit the clustering quality.

## C CLASSIFICATION PERFORMANCE OF THE ABLATION VARIANTS

We summarize the classification performance of the two Ablation Variants HTGM w/o GMM and HTGM-Gaussian in Table 7. As we can see, our unique designs improve the novel task detection performance without significantly decreasing the classification performance.

## D DETAILED SETUP

In this section, we illustrate some detailed setup of our model and baselines.

**Feature Extractor of Metric-based Meta-Learning:** Following (Tian et al., 2020; Lee et al., 2019c), we apply a ResNet-12 as feature extractor for all Metric-based Meta-Learning. ResNet-12 contains 4 residual blocks. Each block has 3 convolutional layers with a kernel size of $3 \times 3$. Similar to (Tian et al., 2020; Lee et al., 2019c), we add Dropblock as regularizer and set the number of filters as (60,160,320,640). For MetaOptNet, following the original paper (Lee et al., 2019c) we flatten the output of the last convolutional layer to acquire a 16000-dimensional feature as image embedding. For other baselines, following (Tian et al., 2020) we use a global average-pooling layer on the top of the last residual block to acquire a 640-dimensional feature as image embedding.

**Optimization:** Following (Snell et al., 2017), all Prototypical Network based methods, including ProtoNet, ProtoNet-Aug, NCA use Adam optimizer with initial learning rate of 1e-3. For FEATS, when pretraining its encoder, we apply exact same setting as ProtoNet. When training its aggregation function, we decrease the learning rate to 1e-4 since larger learning rate leads to invalid result. For the optimization of MetaOptNet, following the original paper, we apply SGD with Nesterov mementum of 0.9, initial learning rate of 0.1 and a scheduler to optimize it.

**Other details:** For the SVM solving in MetaOptNet, following the original paper, we apply quadratic programming solver OptNet (Amos & Kolter, 2017). For the set-to-set function in FEATS, we choose transformer based on the results reported by Ye et al. (2020).