TOOLSMITH:
An Automatic Tool-Generation Framework for Multimodal Search Agents

Abstract

Recent multimodal search agents use reasoning, vision, and live web search across many turns to answer questions beyond parametric knowledge by orchestrating a small library of hand-crafted search and visual tools. However, the library is laborious to create and maintain, and frozen when new query types, evidence formats, and failure modes are encountered in the wild. Human practitioners, by contrast, cope with insufficient tools by fashioning new ones from familiar parts and reusing them across tasks. Inspired by this, we propose TOOLSMITH, an automatic tool-generation framework that grows and reuses modules on top of a lean base tool library. We evaluate TOOLSMITH on three in-domain multimodal search benchmarks and ten out-of-domain benchmarks under a VLM-as-a-Judge protocol. TOOLSMITH consistently improves over the base library across deployed agents of varying scales, with larger backbones reaping greater gains, demonstrating the scalability of the approach. Our code and data will be publicly available.

1 Introduction

Multimodal search agents (Geng et al., 2026; Huang et al., 2026; Yao et al., 2026; Chen et al., 2026a; Wu et al., 2025; Narayan et al., 2025) answer information-seeking questions beyond static knowledge inside the model, such as identifying the source of the rare knowledge, cross-checking a numerical claim against the live web, or assembling a multi-step provenance argument across images and retrieved pages. Contemporary systems handle such tasks by orchestrating reasoning, perception, and live web search across many turns over a fixed inventory of hand-crafted tools. It typically contains web search, webpage fetching, image grounding, OCR, depth estimation, and code execution. Throughout this paper, we use *tool* to mean a callable Python utility, exposed to the agent

Figure 1: We propose an automatic tool-generation framework for multimodal search agents. In the example shown, an agent restricted to a *fixed* tool library is bound to its pre-defined primitives and fails on queries that no original tool can directly resolve. Our framework instead *grows* the library: the agent operates over an extended tool library that includes newly generated tools and can invoke them freely when solving real queries. Here, the newly generated **Event In Image** tool resolves the query through finer-grained information verification and image search.

through a typed schema, that takes structured input (a text query, an image, a URL) and returns evidence the agent's reasoning loop consumes in a subsequent turn; *generating a new tool* means producing a new such callable schema, execution logic, and all, and admitting it to the catalog the agent draws from at inference.

Nevertheless, hand-crafted tools suffer from inherent limitations. First, tool inventories shipped with production systems and developer-curated skill banks (VoltAgent and Contributors, 2025) are expensive to maintain and frozen at the developer's anticipated coverage. When new query types, evi-

dence formats, and failure modes are encountered in the wild, human intervention will be needed to modify the tools. Second, complementary lines of work that learn memory *over* a fixed inventory (Xiao et al., 2025) or train an agent to use existing tools more efficiently (Gao et al., 2025; Wu et al., 2026a) sharpen *how* the agent uses its tools but do not expand *which* tools it has.

A natural alternative is letting the agent itself *generate* the missing tool. Tool generation has been studied across adjacent domains such as vision–language understanding, math and table QA, general NLP, and embodied / computer-use agents (Chen et al., 2024; Yuan et al., 2024; Wölflein et al., 2025; Wang et al., 2024, 2025), but has not been carried over to multimodal search, where the inventory remains hand-authored. The transfer is non-trivial: search-agent trajectories are long, and agent state mixes images, link references, and tool outputs across turns.

When exploring the world, human practitioners both use existing tools and fashion new ones when existing tools fall short (Goodall, 1964; Beck, 1980; Tomasello, 1999). We argue that a multimodal search agent should be equipped with the same capability. When existing tools fall short, the agent should organically *fashion new ones* from familiar parts, refining and reusing them across tasks. Currently, multimodal search agents only share the *using* half of this picture but conspicuously not the *fashioning* half. When their tool set fails, they 'let it go' rather than enlarge and revise the toolbox. Moreover, humans do not blindly adopt every novel implementation they sketch. They *verify* it on test cases before adding it to the working library (Schön, 1983). An agent equipped to grow its tools must also be equipped to verify them.

To this end, we introduce TOOLSMITH, an automatic tool-generation framework organized as four model-agnostic phases: 1) *Trajectory Mining*, 2) *Reuse-or-Grow Decision*, 3) *Tool Generation*, 4) *Two-Gate Verification*. We cluster the agent's failed trajectories into capability gaps (Shinn et al., 2023; Andrychowicz et al., 2017; Chen et al., 2025), check each gap against a lean library of eight primitives to decide reuse versus generation, prompt a generator VLM to author new tools as Python source under structural and anti-hardcode constraints, and admit candidates only after sandboxed sanity and LLM static code-review gates.

We evaluate TOOLSMITH across 3 in-domain multimodal search benchmarks (FVQA, InfoSeek, EncyclopedicVQA) and 10 out-of-domain benchmarks under a VLM-as-a-Judge manner. When using the Qwen3-VL-8B-Instruct model, admitted tools improve the base tool library by **+2.20pp** in-domain and **+1.33pp** out-of-domain tasks. Gains scale with backbone capacity, reaching **+2.98pp** out-of-domain on Qwen3-VL-32B-Instruct and a consistent uplift on GPT-5. We also utilize a comprehensive ablation study to demonstrate how different tool generation models and training samples affect the benchmark performance. Our code and data will be publicly available.

Contributions.

1. We propose TOOLSMITH, to the best of our knowledge, the first *automatic tool-generation* framework for multimodal search agents, with a model-agnostic four-phase pipeline over a base tool library of search, visual, and code-execution tools.

2. On 3 in-domain and 10 out-of-domain multimodal search benchmarks, admitted tools improve the base library across different models, with gains extending to larger backbones, which demonstrate the scalability and flexibility of our proposed TOOLSMITH.

3. We conduct ablation studies to analyze overhead, new-tool usage, tool-call distribution, tool-filtering, and failure modes, which provides an objective landscape of TOOLSMITH.

2 Related Work

Multimodal search agents. Our work targets multimodal search, where a query is resolved by orchestrating reasoning, perception, and live web retrieval across many turns. A growing collection of benchmarks frames this task: MMSearch (Jiang et al., 2025) couples a multimodal query with a curated search engine; MMSearch-Plus (Tao et al., 2026) adds provenance-aware verification; BrowseComp-VL (Geng et al., 2026) and MM-BrowseComp (Li et al., 2025) raise cross-modal information-seeking difficulty; VisBrowse-Bench (Zhang et al., 2026) targets visual-native search; and RealX-Bench (Hong et al., 2026) couples fine-grained perception with multi-hop retrieval. Beyond pure search, the landscape extends to embodied tasks that integrate web information with physical action (Hong et al., 2025). Recent browsing agents tackle these benchmarks via hand-engineered tool inventories (Geng et al., 2026; Huang et al., 2026; Yao et al., 2026; Chen et al., 2026a; Wu et al., 2025; Narayan et al., 2025),

supervised fine-tuning or reinforcement learning that teaches tool use, or memory learned over a fixed inventory (Xiao et al., 2025; Hasegawa et al., 2025). Our contribution is orthogonal: rather than freeze the inventory, we *generate* it.

Tool generation. Building on a lineage of LLM-orchestrated modular vision-language reasoning, our work is closely related to a recent line of methods in which the agent itself constructs new tools. GENOME (Chen et al., 2024) grows a library of vision-module wrappers proposed by an LLM and validated on few-shot examples. CRAFT (Yuan et al., 2024) creates and retrieves Python tools for math, table QA, and image classification. TOOLMAKER (Wölflein et al., 2025) turns code repositories into LLM-callable utilities for general NLP. Voyager (Wang et al., 2024) grows an executable skill library for an open-ended Minecraft agent, with a parallel line of work (Wang et al., 2025) carrying the idea to web agents via online programmatic skill induction. EvolveR (Wu et al., 2026b) distills past trajectories into textual principles that guide future behaviour, and WorldMind (Ren et al., 2026) builds a symbolic world-knowledge repository from agent experience for physically-grounded action. Compared with these, we introduce the tool generation framework into the multimodal search domain.

3 Method

TOOLSMITH is organized as a four-phase pipeline (Figure 2): Phase 1 mines *capability gaps* (query patterns the base tools cannot handle) from the baseline agent's failed trajectories. Phase 2 decides, per gap, whether to reuse an existing tool or escalate to generation. Phase 3 prompts a generator LLM to author the new tool as Python code. Phase 4 admits the candidate after verification gates. At inference time, a lightweight retrieval step selects relevant generated tools per query.

Notation. Let $\mathcal{A}_\theta$ be the baseline agent, $\mathcal{D}_{\text{train}}$ the training pool, and $\mathcal{T}_t$ the tool catalog at round t, initialized with the eight base tools, $\mathcal{T}_0 = \mathcal{T}_{\text{base}}$. A trajectory τ records the agent's full tool-call sequence on a single query. We write G_ϕ for the generator LLM, ψ for a sentence encoder, and $\cos(\cdot, \cdot)$ for cosine similarity.

3.1 Phase 1: Trajectory Mining

We roll out $\mathcal{A}_\theta$ on $\mathcal{D}_{\text{train}}$ and apply a two-layer trigger to each trajectory. **Layer A** (cheap signal) flags any trajectory whose final answer the LLM judge marks as incorrect. **Layer B** (LLM self-critique)

then reads each flagged trajectory and assigns a failure label from {NEW_TOOL_NEEDED, ARGU-MENT_MISTAKE, SEARCH_NOISE, AMBIGUOUS}. Only NEW_TOOL_NEEDED trajectories yield a capability gap, which we record as the tuple of (failing query, tools the agent already tried, the self-critique's failure reason, and an image reference when image-grounded).

Clustering. To ensure diversity in candidates, we embed each capability gap as the concatenation of its question, prediction, and gold answer using a sentence encoder ψ, then apply agglomerative clustering (average linkage) over cosine distance into C clusters. One representative per cluster enters Phases 2–4.

3.2 Phase 2: Reuse-or-Grow Decision

Phase 2 decides, for each capability gap, whether the current tool catalog already covers it or a new tool is needed. We compute the TF–IDF cosine similarity between the gap's text (its query and subtask) and every existing tool's description, and take the maximum:

$$\rho_{\text{pre}}(g, \mathcal{T}_t) = \max_{t \in \mathcal{T}_t} \cos\big(\text{tfidf}(\widetilde{g}), \text{tfidf}(d_t)\big), \quad (1)$$

where d_t is the description of tool t and $\widetilde{g} = q_g \oplus s_g$ concatenates the gap's query and subtask. If $\rho_{\text{pre}} > \tau_{\text{pre}}$, the gap is treated as covered by the best-matching tool and skipped; otherwise it is forwarded to Phase 3. TF–IDF suffices here because tool descriptions are short, the vocabulary is domain-specific (search, image, OCR, code), and we only need to detect obvious overlaps.

3.3 Phase 3: Tool Generation

Phase 3 takes each gap that Phase 2 forwards and writes a new tool for it. We prompt a generator LLM G_ϕ to produce Python source code conditioned on the gap, the current catalog, a system prompt that specifies the tool-class interface and forbids dynamic execution / unsanctioned I/O / hard-coded answers, and a handful of example tools the generator can imitate (full prompts and examples in Appendix E). The output is a candidate c comprising Python source, a typed schema, and a short natural-language description, which is then forwarded to Phase 4 for verification. Representative code listings of admitted, failed, and filtered candidates appear in Appendix F.

3.4 Phase 4: Verification and Inference

A candidate is admitted only if it passes both verification gates followed by a redundancy check

Figure 2: Overview of the TOOLSMITH pipeline: capability gaps mined from agent trajectories on a training pool are filtered through reuse-or-grow against the tool catalog, passed to an LLM that authors each new tool as Python source, and admitted only after verification gates with a feedback-driven retry on rejection.

against the existing catalog. We run the gates in order of increasing computational cost: Gate 1 is a cheap static check, so candidates that fail it are dropped before we pay for Gate 2's LLM critic.

Gate 1: Sandboxed sanity. The candidate's source is parsed and scanned for dynamic-execution and dangerous-I/O patterns, then executed once on a minimal dummy input under a ten-second wall-clock budget. Anything that violates the static checks or errors at runtime is rejected.

Gate 2: LLM static code review. An LLM critic scores the candidate on four 0–5 axes (parametric usage, description abstractness, edge-case handling, and task alignment) and admits it only when the mean score is at least $\mu_{\min}$ and the minimum across axes is at least $a_{\min}$. The critic may use a different model from the generator; tools with overly narrow descriptions or missing error handling are caught here.

Feedback-driven retry. When either gate rejects a candidate, we re-prompt G_ϕ with a short natural-language summary of which gate failed and why, up to a per-candidate budget A. Empirically, most retries either pass on the second attempt or remain wrong for the same reason, so A is capped at a small constant.

Tool catalog update. A candidate that survives both gates is then compared against every existing tool by TF–IDF cosine similarity over descriptions (the same construction as Eq. 1, with a stricter threshold τ_{post}). Only candidates whose closest match falls below τ_{post} are admitted to the next-round catalog $\mathcal{T}_{t+1}$; redundant duplicates are dropped.

Inference. Exposing the full generated catalog alongside the base primitives would inflate the per-turn schema and degrade tool selection. We instead retrieve a per-query subset: each tool description d_t is pre-embedded with ψ; given a test query q, the agent sees

$$\mathcal{T}_q = \mathcal{T}_{\mathrm{base}} \cup \text{top-K}\big(\cos(\psi(q),\, \psi(d_t))\,;\, t \in \mathcal{T}_{\mathrm{new}}\big), \quad (2)$$

yielding $|\mathcal{T}_{\mathrm{base}}| + K$ tools per sample. The base primitives are always visible (they are referenced by name in the agent's system prompt); the generated tools rotate per query based on relevance. Hyperparameter values are listed in Appendix D.

4 Experimental Setup

4.1 Base Tool Library

Our base library consists of eight primitive tools grouped into three capability categories: *Search*, *Vision*, and *Code Execution*. The search tools are

powered by the Serper API[1]; the visual tools wrap SAM3 (Carion et al., 2025), PaddleOCR-VL (PaddlePaddle Team, 2025), and Depth Anything 3 (Lin et al., 2025) as their underlying models. Table 1 lists the eight tools with a one-line description each. More details can be found at Appendix B.

Tool	Description
Search	
Text Search	Web search with automatic query-intent routing.
Image Search	Reverse image search (image → entities and URLs).
Webpage Visit	Fetch URL(s) and extract goal-relevant content.
Vision	
Zoom-in	Crop a region by normalized bounding box.
Visual Grounding	Locate regions matching a text query.
OCR	Extract printed text from an image.
Depth Estimation	Estimate a per-pixel depth map for an image.
Code execution	
Code Execution	Execute a Python snippet (agent-authored or LLM-authored from a goal in plain language) over prior tool outputs.

Table 1: Base library of eight primitive tools, grouped by capability. Detailed schemas and tool documentation appear in Appendix B.

These eight span the major primitive categories a multimodal search agent commonly relies on, providing a broad foundation on top of which our pipeline grows additional, task-specific tools.

4.2 Tool-Generation Training Pool

We collect trajectories from the *train* or *val* splits of three knowledge-intensive multimodal search datasets: FVQA (Wu et al., 2025), InfoSeek (Chen et al., 2023), and EncyclopedicVQA (Mensink et al., 2023). The held-out *test* splits of the same three datasets serve as our in-domain (ID) evaluation in Section 4.3, providing a within-distribution measure of whether the generated tools address the failure modes they were designed for. No example from any out-of-domain benchmark enters tool generation. We defer per-dataset sampling sizes and split choices to Appendix E.1.

4.3 Evaluation Benchmarks

We evaluate TOOLSMITH along two axes: *in-domain (ID)* performance on the held-out test splits of the three datasets we used to mine capability gaps during training, and *out-of-domain (OOD)* transfer to ten public multimodal search benchmarks unseen during tool generation. Per-

benchmark sample counts are summarized in Table 8, and full per-benchmark descriptions are deferred to Appendix A.1.

In-domain (ID). ID evaluation uses the held-out test splits of FVQA (Wu et al., 2025), InfoSeek (Chen et al., 2023), and EncyclopedicVQA (Mensink et al., 2023). Because the training pool from which we mine capability gaps comes from the *training* splits of these same datasets, the test splits provide a within-distribution measure of how well the generated tools address the failure modes they were designed for. We give full per-benchmark descriptions in Appendix A.1.1.

Out-of-domain (OOD). OOD evaluation uses ten public multimodal information-seeking benchmarks: MM-BrowseComp (Li et al., 2025), SimpleVQA (Cheng et al., 2025), MMSearch (Jiang et al., 2025), MMSearch-Plus (Tao et al., 2026), HLE-VL (Phan et al., 2026), LiveVQA (Fu et al., 2025), BrowseComp-VL (Geng et al., 2026), RealX-Bench (Hong et al., 2026), VDR-Bench (Huang et al., 2026), and VisBrowse-Bench (Zhang et al., 2026). None of these share data with the training pool. For benchmarks that mix text-only and image-grounded items we restrict evaluation to the multimodal subset (queries carrying at least one image), so the reported counts are smaller than the full-benchmark totals. Appendix A.1.2 provides per-benchmark descriptions.

Final-answer correctness is judged by a VLM-as-a-Judge prompted with GPT-4o (OpenAI, 2024), following (Huang et al., 2026; Chen et al., 2026a); the prompt and a discussion of retrieval-shortcut concerns are in Appendix A.2.

4.4 Models and Implementation

Models. We consider three open-sourced models, including Qwen3-VL-8B-Instruct (Qwen Team, 2025), Qwen3-VL-8B-Thinking, and Qwen3-VL-32B-Instruct, since all of them can cover different model sizes (8B vs 32B) and model variants (Instruct vs Thinking). For proprietary models, we consider GPT-5 (gpt-5-2025-08-07). We sample at temperature 0.3 with top-p 0.95, allow up to fifteen tool-calling iterations per query, and cap context at 120K tokens; full hyperparameters are in Appendix D.

Evaluation protocol. Because the search APIs, the agent's tool-routing decisions, and the LLM judge are all stochastic, every reported number is the mean of three independent runs.

---

[1] https://serper.dev/

5 Main Results

Tables 2 and 3 report headline accuracy on the in-domain (ID) and out-of-domain (OOD) benchmarks under three settings per inference backbone: *Direct Inference* (no tools), *Agent Workflow w/ Base Tools* (the eight-primitive base library), and *Agent Workflow w/ Base and* TOOLSMITH *(GPT-5)* (the base library plus tools admitted by TOOLSMITH when GPT-5 is fixed as the generator).[2]

The eight base primitives alone lift Qwen3-VL-8B-Instruct by roughly +25pp on ID and +10pp on OOD over *Direct Inference*, with 32B and GPT-5 showing comparably large jumps; multimodal search is clearly a tool-driven task. Adding the TOOLSMITH-generated tools on top of the base library yields further consistent gains of one to three points on both ID and OOD across all three inference backbones, and the gains are pervasive per-benchmark: 32B and GPT-5 improve on every OOD benchmark and 8B improves on eight of the ten, with the remaining two essentially flat.

The average gain peaks at 32B (+2.32pp across ID and OOD), with GPT-5 (+1.72pp) and 8B (+1.77pp) close behind for different reasons: GPT-5's smaller gain partly reflects its privacy-refusal floor (Appendix A.4); 8B's reflects the long-context tool-selection cost of an enlarged toolbox. The Qwen3-VL-8B-Thinking variant modestly outperforms Instruct under *Direct Inference* but takes more than $5\times$ the per-query latency inside the full agent workflow, so we standardize on Instruct as the default deployed agent for all subsequent results, ablations, and analyses.

6 Ablation Studies

The inference-backbone axis is already covered by the main results (Section 5), which sweep Qwen3-VL-8B-Instruct, 32B-Instruct, 8B-Thinking, and GPT-5 with a fixed GPT-5 tool generator. This section ablates the remaining design choices: which model *authors* new tools, whose trajectories the pipeline mines, and how the cluster-count knob shapes the resulting tool bank. Because each ablation requires re-running Phases 1–4 of the pipeline end-to-end on the full training pool, we restrict every sweep below to one representative ID benchmark (FVQA) and one representative OOD benchmark (MMSearch) to keep the compute budget tractable.

---

[2]Inference rows for GPT-5 here are systematically lower-bounded by privacy-driven refusals on identity-related queries; see Appendix A.4.

Model	FVQA	InfoSeek	Enc-VQA	*Avg*
Direct Inference				
Qwen3-VL-8B	28.39	29.20	10.61	22.62
Qwen3-VL-8B-T	25.67	27.25	18.06	23.63
Qwen3-VL-32B	32.67	33.20	32.76	32.88
GPT-5	54.67	53.67	43.33	50.46
Agent Workflow w/ Base Tools				
Qwen3-VL-8B	55.00	50.67	38.67	47.94
Qwen3-VL-32B	62.67	55.33	49.00	55.47
GPT-5	55.00	52.00	48.67	51.80
Agent Workflow w/ Base Tools and TOOLSMITH *(GPT-5)*				
Qwen3-VL-8B	58.00	53.00	40.00	50.14
Δ	+3.00	+2.33	+1.33	+2.20
Qwen3-VL-32B	64.55	56.99	50.47	57.14
Δ	+1.88	+1.66	+1.47	+1.67
GPT-5	56.10	53.04	49.64	52.84
Δ	+1.10	+1.04	+0.97	+1.04

Table 2: In-domain benchmark results. It contains per-benchmark accuracy on the held-out test splits of the three training datasets. New tools are generated by GPT-5 and utilized by the listed inference model. Qwen3-VL-8B refers to Qwen3-VL-8B-Instruct and Qwen3-VL-8B-T denotes the Qwen3-VL-8B-Thinking. Enc-VQA = EncyclopedicVQA. *Avg* is the mean across the three benchmarks (1800 / 2000 / 1960).

6.1 Tool-Generation Model

The main results (Section 5) sweep the inference backbone with a fixed GPT-5 generator; here we instead vary the tool-generation model over (GPT-5, Qwen3-VL-32B-Instruct, Qwen3-VL-8B-Instruct), and for each generator evaluate the resulting tool bank on the same three inference backbones. We restrict the sweep to one representative ID benchmark (FVQA) and one representative OOD benchmark (MMSearch) to keep the cost contained, and treat the resulting numbers as an illustrative finding rather than a statistical claim. Generation-process statistics (pass rates, dedup, cost) for the three generators are reported in Appendix E.2.

Reading the matrix by column (fix the consumer, vary the generator), accuracy rises monotonically with generator strength on both benchmarks, for every consumer, with no exceptions. A stronger generator simply produces better tools; the gain is largest when the consumer is weakest (the 8B-Instruct consumer picks up roughly six to seven points going from an 8B to a GPT-5 generator, versus only about two points for the GPT-5 consumer). Conversely, pairing the GPT-5 consumer with an 8B generator loses about two points relative to the all-GPT-5 cell. The take-away is that the choice of generator dominates the design: invest compute in the strongest available generator, and let the deployed agent scale separately.

Model	MM-BC	SVQA	MMS	MSP	HLE-VL	LVQA	BC-VL	RXB	VDR	VBB	*Avg*
				Direct Inference							
Qwen3-VL-8B	4.94	54.33	14.04	1.29	6.36	34.67	21.05	22.16	5.40	7.69	16.97
Qwen3-VL-8B-T	7.41	54.67	12.87	3.22	10.30	29.33	33.83	22.16	8.20	11.24	19.68
Qwen3-VL-32B	6.58	59.00	20.47	2.57	10.00	32.67	28.82	24.74	9.40	10.06	20.36
GPT-5	8.64	66.33	36.84	14.79	23.33	42.33	42.11	34.54	14.20	28.40	30.41
				Agent Workflow w/ Base Tools							
Qwen3-VL-8B	6.00	70.00	51.46	9.97	7.27	40.00	32.33	34.71	14.40	11.24	26.57
Qwen3-VL-32B	10.29	70.33	62.57	12.86	11.52	51.33	33.08	40.21	18.80	19.53	31.27
GPT-5	25.93	68.33	56.14	25.40	23.03	50.67	52.38	40.72	23.80	49.11	39.80
				Agent Workflow w/ Base Tools and TOOLSMITH *(GPT-5)*							
Qwen3-VL-8B	7.00	71.00	55.56	11.58	7.27	42.67	33.08	34.54	16.60	11.22	27.90
Δ	+1.00	+1.00	+4.10	+1.61	0.00	+2.67	+0.75	−0.17	+2.20	−0.02	+1.33
Qwen3-VL-32B	13.58	73.33	64.33	16.08	13.03	56.00	36.09	43.30	22.00	21.89	34.25
Δ	+3.29	+3.00	+1.76	+3.22	+1.51	+4.67	+3.01	+3.09	+3.20	+2.36	+2.98
GPT-5	29.22	71.00	57.31	27.65	24.55	56.67	53.88	42.27	25.80	50.89	42.20
Δ	+3.29	+2.67	+1.17	+2.25	+1.52	+6.00	+1.50	+1.55	+2.00	+1.78	+2.40

Table 3: Out-of-domain benchmark results. It has per-benchmark accuracy on the ten multimodal search benchmarks unseen during tool generation. Tools are generated by GPT-5 and used by the listed inference model. Qwen3-VL-8B refers to Qwen3-VL-8B-Instruct and Qwen3-VL-8B-T denotes the Qwen3-VL-8B-Thinking. Abbreviations: MM-BC = MM-BrowseComp; SVQA = SimpleVQA; MMS = MMSearch; MSP = MMSearch-Plus; LVQA = LiveVQA; BC-VL = BrowseComp-VL; RXB = RealX-Bench; VDR = VDR-Bench; VBB = VisBrowse-Bench. *Avg* is the average performance across the ten benchmarks (total 2917 instances; per-benchmark counts in Table 8).

		Inference model		
Benchmark	Generator	8B	32B	GPT-5
FVQA	*Base tools only*	55.00	62.67	55.00
	Qwen3-VL-8B	52.00	60.67	54.00
	Qwen3-VL-32B	56.00	63.17	55.20
	GPT-5	58.00	64.55	56.10
MMSearch	*Base tools only*	51.46	62.57	56.14
	Qwen3-VL-8B	48.54	60.82	54.97
	Qwen3-VL-32B	53.22	63.16	56.73
	GPT-5	55.56	64.33	57.31

Table 4: Tool-generation model ablation. Rows: the model that *authors* the new tool in Phase 3 (the tool-generation model). The *Base tools only* row is the no-ToolSmith reference (i.e., the agent runs with the eight base primitives alone; values reproduce the +Base rows of Tables 2 and 3 for the FVQA and MMSearch columns). Columns: the inference model that *consumes* the tools.

Trajectory source	$|\mathcal{T}_{new}|$	FVQA	MMSearch
Qwen3-VL-8B	264	58.00	55.56
Qwen3-VL-32B	218	57.11	54.97
GPT-5	173	56.50	54.39

Table 5: Trajectory-mining source ablation. The tool generator is fixed at GPT-5, and the inference model is Qwen3-VL-8B-Instruct. $|\mathcal{T}_{new}|$ is the number of tools admitted after both verification gates.

less, surfacing fewer raw gaps), and the 8B miner is best on both benchmarks; stronger miners cost roughly a point on FVQA and half that on MM-Search. The take-away is that miner strength should be matched to consumer strength: for an 8B deployed agent, self-mining gives the best alignment between the failure patterns the generator sees and the patterns the consumer hits at inference.

6.2 Trajectory-Mining Source Model

We additionally vary the model whose trajectories are mined in Phase 1, holding the tool generator at GPT-5 and the consumer at Qwen3-VL-8B-Instruct. A weak miner surfaces many simple, frequent gaps; a strong miner produces fewer but more specialized failures. The question is whether the 8B consumer prefers tools mined from its own failures or from a stronger model's.

The admitted tool count $|\mathcal{T}_{new}|$ decreases monotonically with miner strength (stronger miners fail

6.3 Cluster Count

We vary the Phase 1 cluster count C, which controls how many capability-gap representatives are forwarded to Phases 2–4 and is therefore the effective "training-sample" count for tool generation (the raw rollout pool of 9,174 queries is fixed, see Section 3.1). All other components are held fixed. The sweep is intentionally coarse: we want to confirm the shape of the curve, not aggressively tune C.

The expected Goldilocks pattern emerges: too

C	$|\mathcal{T}_{\text{new}}|$	FVQA	MMSearch
0	0	55.00	51.46
250	145	57.39	54.97
500	264	58.00	55.56
750	298	57.50	54.97

Table 6: Phase 1 cluster-count sweep. C is the number of clustered gap representatives passed to Phases 2–4, $|\mathcal{T}_{\text{new}}|$ the number of tools admitted to the tool catalog after both verification gates, and the last two columns are accuracy on a representative ID benchmark (FVQA) and a representative OOD benchmark (MMSearch), under Qwen3-VL-8B-Instruct with GPT-5 as tool generator. The $C{=}0$ row is the eight-primitive baseline. $C{=}500$ is the main-results default.

	New calls	Adoption
In-domain	27%	40.9%
Out-of-domain	15%	16.3%

Table 7: New-tool adoption. *New calls*: fraction of all tool calls to generated tools. *Adoption*: fraction of samples invoking ≥ 1 generated tool.

few clusters yield a small, broad tool bank that lifts accuracy only modestly, while too many spread the within-cluster support too thin and the admitted-tool count plateaus. The mid-range $C{=}500$ sits slightly above both $C{=}250$ and $C{=}750$ on the two benchmarks, indicating a flat plateau rather than a sharp optimum; we adopt 500 as the default and do not tune further.

7 Analysis

7.1 Overhead

Both the one-time tool-generation cost and the per-query inference overhead of TOOLSMITH are manageable in practice. Due to space, we defer the full token, dollar, wall-clock, and per-query breakdown to Appendix G.

7.2 New-Tool Adoption

Table 7 reports how often the agent invokes generated tools across in-domain and out-of-domain benchmarks.

On in-domain benchmarks, generated tools account for 27% of all tool calls, and 41% of samples invoke at least one, confirming that the agent actively selects generated tools when the query matches their capability. On out-of-domain benchmarks, adoption drops to 15% of calls and 16% of samples, which is expected since the tools were mined from in-domain failures. Nevertheless, the non-trivial OOD adoption indicates that some generated tools generalize beyond their training distribution.

7.3 Qualitative Analysis

We examine the patterns behind gained and lost samples; four illustrated case studies appear in Figures 3–6 (Appendix H), and code-level tool examples in Appendix F.

Why generated tools help. The dominant pattern is that generated tools enforce a *perceive-then-query* pipeline that the base agent skips. With only base primitives, the agent often jumps to text search without first identifying the visual entity. Generated tools chain reverse-image search with structured KB lookup in a single call, forcing the correct order. For example, on *"What year did he give $50M to create the Hastings Initiative?"* (Figure 3), the base agent searches without identifying Reed Hastings and mis-attributes the donation to Eric Schmidt; the generated tool resolves the person first, after which a single text search returns the correct year.

Why generated tools hurt. Among the lost samples, failures concentrate on a small number of tools that return incorrect information. Other losses stem from visual mis-identification or from the agent trusting a generated tool's output over a correct result it had already obtained from a base tool. Appendix F walks through one successful tool, one runtime-failing tool, and one tool filtered out by Gate 2 in code-level detail.

Adoption correlates with gain. The in-domain benchmarks, where adoption is highest (41%), show consistent accuracy improvements, while the lower-adoption OOD benchmarks show smaller or neutral changes, suggesting that the accuracy gains are driven by actual tool use rather than incidental prompt differences.

8 Conclusion

We introduced TOOLSMITH, an automatic, model-agnostic tool-generation framework for multimodal search agents. Starting from an eight-primitive base tool library, it mines trajectories on a training pool, generates new tools under our proposed TOOLSMITH framework. Across three in-domain and ten out-of-domain benchmarks, admitted tools improve on top of the base tool library on every benchmark, and gains persist across different inference models, and tool-generation models. Furthermore, we conduct more in-depth analysis on tool generation, tool use, and error samples. TOOLSMITH is a step toward multimodal search agents that extend their own capabilities with minimal human curation.

Limitations

TOOLSMITH does not include tools that themselves generate images, such as those introduced by Gen-Searcher (Feng et al., 2026) and Unify-Agent (Chen et al., 2026b); we plan to leave the generative part to future work. We have also not yet utilized a code-specialized LLM as the tool-generator backbone, and we believe a stronger code model would further improve the quality of admitted tools and downstream accuracy. Finally, since the live search APIs and proprietary models change with time, exact numerical reproduction may drift. We pin model snapshots and archive trajectories to partially mitigate this, but building a fully replicable environment for search agents remains worth pursuing in the future.

Ethical Considerations

All datasets we use are publicly released for research and we do not redistribute them. Generated code runs in a process-level sandbox with an AST allow-list and execution timeout, sufficient to block accidental misuse. We cannot control the commercial search APIs and proprietary models. But we have ensured that all of our uses are legal and appropriate. The potential risk comes from the external APIs, which may return harmful content. We have verified and tried our best to mitigate this risk.

References

Marcin Andrychowicz, Filip Wolski, Alex Ray, Jonas Schneider, Rachel Fong, Peter Welinder, Bob McGrew, Josh Tobin, Pieter Abbeel, and Wojciech Zaremba. 2017. Hindsight experience replay. In *Advances in Neural Information Processing Systems 30 (NIPS)*.

Benjamin B. Beck. 1980. *Animal Tool Behavior: The Use and Manufacture of Tools by Animals*. Garland STPM Press, New York.

Nicolas Carion, Laura Gustafson, Yuan-Ting Hu, Shoubhik Debnath, Ronghang Hu, Didac Suris, Chaitanya Ryali, Kalyan Vasudev Alwala, Haitham Khedr, Andrew Huang, Jie Lei, Tengyu Ma, Baishan Guo, and 1 others. 2025. SAM 3: Segment anything with concepts. *arXiv preprint arXiv:2511.16719*.

Shuang Chen, Kaituo Feng, Hangting Chen, Wenxuan Huang, Dasen Dai, Quanxin Shou, Yunlong Lin, Xiangyu Yue, Shenghua Gao, and Tianyu Pang. 2026a. OpenSearch-VL: An open recipe for frontier multimodal search agents. *arXiv preprint arXiv:2605.05185*.

Shuang Chen, Quanxin Shou, Hangting Chen, Yucheng Zhou, Kaituo Feng, Wenbo Hu, Yi-Fan Zhang, Yunlong Lin, Wenxuan Huang, Mingyang Song, Dasen Dai, Bolin Jiang, Manyuan Zhang, Shi-Xue Zhang, Zhengkai Jiang, Lucas Wang, Zhao Zhong, Yu Cheng, and Nanyun Peng. 2026b. Unify-Agent: A unified multimodal agent for world-grounded image synthesis. *arXiv preprint arXiv:2603.29620*.

Yang Chen, Hexiang Hu, Yi Luan, Haitian Sun, Soravit Changpinyo, Alan Ritter, and Ming-Wei Chang. 2023. Can pre-trained vision and language models answer visual information-seeking questions? In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing (EMNLP)*.

Zhenfang Chen, Delin Chen, Rui Sun, Wenjun Liu, and Chuang Gan. 2025. Scaling autonomous agents via automatic reward modeling and planning. In *The Thirteenth International Conference on Learning Representations (ICLR)*.

Zhenfang Chen, Rui Sun, Wenjun Liu, Yining Hong, and Chuang Gan. 2024. GENOME: Generative neuro-symbolic visual reasoning by growing and reusing modules. In *The Twelfth International Conference on Learning Representations (ICLR)*.

Xianfu Cheng, Wei Zhang, Shiwei Zhang, Jian Yang, Xiangyuan Guan, Xianjie Wu, Xiang Li, Ge Zhang, Jiaheng Liu, Yuying Mai, Yutao Zeng, Zhoufutu Wen, Ke Jin, Baorui Wang, Weixiao Zhou, Yunhong Lu, Tongliang Li, Wenhao Huang, and Zhoujun Li. 2025. SimpleVQA: Multimodal factuality evaluation for multimodal large language models. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 4637–4646. ArXiv:2502.13059.

Kaituo Feng, Manyuan Zhang, Shuang Chen, Yunlong Lin, Kaixuan Fan, Yilei Jiang, Hongyu Li, Dian Zheng, Chenyang Wang, and Xiangyu Yue. 2026. Gen-Searcher: Reinforcing agentic search for image generation. *arXiv preprint arXiv:2603.28767*.

Mingyang Fu, Yuyang Peng, Dongping Chen, Zetong Zhou, Benlin Liu, Yao Wan, Zhou Zhao, Philip S. Yu, and Ranjay Krishna. 2025. Seeking and updating with live visual knowledge. In *Advances in Neural Information Processing Systems 38 (NeurIPS)*. ArXiv:2504.05288.

Zhi Gao, Bofei Zhang, Pengxiang Li, Xiaojian Ma, Tao Yuan, Yue Fan, Yuwei Wu, Yunde Jia, Song-Chun Zhu, and Qing Li. 2025. Multi-modal agent tuning: Building a VLM-driven agent for efficient tool usage. In *The Thirteenth International Conference on Learning Representations (ICLR)*.

Xinyu Geng, Peng Xia, Zhen Zhang, Xinyu Wang, Qiuchen Wang, Ruixue Ding, Chenxi Wang, Jialong Wu, Yida Zhao, Kuan Li, Yong Jiang, Pengjun Xie, Fei Huang, and Jingren Zhou. 2026. WebWatcher: Breaking new frontier of vision-language deep research agent. In *The Fourteenth International Conference on Learning Representations (ICLR)*. ArXiv:2508.05748.

Jane Goodall. 1964. Tool-using and aimed throwing in a community of free-living chimpanzees. *Nature*, 201:1264–1266.

Kimihiro Hasegawa, Wiradee Imrattanatrai, Masaki Asada, Ken Fukuda, and Teruko Mitamura. 2025. TAMA: Tool-augmented multimodal agent for procedural activity understanding. *arXiv preprint arXiv:2510.00161*.

Jack Hong, Chenxiao Zhao, ChengLin Zhu, Weiheng Lu, Guohai Xu, and Xing Yu. 2026. DeepEyesV2: Toward agentic multimodal model. In *The Fourteenth International Conference on Learning Representations (ICLR)*. ArXiv:2511.05271.

Yining Hong, Rui Sun, Bingxuan Li, Xingcheng Yao, Maxine Wu, Alexander Chien, Da Yin, Ying Nian Wu, Zhecan James Wang, and Kai-Wei Chang. 2025. Embodied web agents: Bridging physical-digital realms for integrated agent intelligence. *arXiv preprint arXiv:2506.15677*.

Wenxuan Huang, Yu Zeng, Qiuchen Wang, Zhen Fang, Shaosheng Cao, Zheng Chu, Qingyu Yin, Shuang Chen, Zhenfei Yin, Lin Chen, Zehui Chen, Xu Tang, Yao Hu, Shaohui Lin, Philip Torr, Feng Zhao, and Wanli Ouyang. 2026. Vision-DeepResearch: Incentivizing DeepResearch capability in multimodal large language models. *arXiv preprint arXiv:2601.22060*.

Dongzhi Jiang, Renrui Zhang, Ziyu Guo, Yanmin Wu, Jiayi Lei, Pengshuo Qiu, Pan Lu, Zehui Chen, Chaoyou Fu, Guanglu Song, Peng Gao, Yu Liu, Chunyuan Li, and Hongsheng Li. 2025. MMSearch: Benchmarking the potential of large models as multimodal search engines. In *International Conference on Learning Representations (ICLR)*.

Shilong Li, Xingyuan Bu, Wenjie Wang, Jiaheng Liu, Jun Dong, Haoyang He, Hao Lu, Haozhe Zhang, Chenchen Jing, Zhen Li, Chuanhao Li, Jiayi Tian, Chenchen Zhang, Tianhao Peng, Yancheng He, Jihao Gu, Yuanxing Zhang, Jian Yang, Ge Zhang, and 5 others. 2025. MM-BrowseComp: A comprehensive benchmark for multimodal browsing agents. *arXiv preprint arXiv:2508.13186*.

Haotong Lin, Sili Chen, Junhao Liew, Donny Y. Chen, Zhenyu Li, Guang Shi, Jiashi Feng, and Bingyi Kang. 2025. Depth anything 3: Recovering the visual space from any views. *arXiv preprint arXiv:2511.10647*.

Thomas Mensink, Jasper Uijlings, Lluis Castrejon, Arushi Goel, Felipe Cadar, Howard Zhou, Fei Sha, Andre Araujo, and Vittorio Ferrari. 2023. Encyclopedic VQA: Visual questions about detailed properties of fine-grained categories. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*.

Kartik Narayan, Yang Xu, Tian Cao, Kavya Nerella, Vishal M. Patel, Navid Shiee, Peter Grasch, Chao Jia, Yinfei Yang, and Zhe Gan. 2025. DeepMMSearch-R1: Empowering multimodal LLMs in multimodal web search. *arXiv preprint arXiv:2510.12801*.

OpenAI. 2024. GPT-4o system card. *arXiv preprint arXiv:2410.21276*.

PaddlePaddle Team. 2025. PaddleOCR-VL: Boosting multilingual document parsing via a 0.9B ultra-compact vision-language model. *arXiv preprint arXiv:2510.14528*.

Long Phan, Alice Gatti, Ziwen Han, Nathaniel Li, Josephina Hu, Hugh Zhang, Chen Bo Calvin Zhang, Mohamed Shaaban, John Ling, Sean Shi, Michael Choi, Anish Agrawal, Arnav Chopra, Adam Khoja, Ryan Kim, Richard Ren, Jason Hausenloy, Oliver Zhang, Mantas Mazeika, and 2 others. 2026. Humanity's last exam. *Nature*. ArXiv:2501.14249.

Qwen Team. 2025. Qwen3-VL technical report. *arXiv preprint arXiv:2511.21631*.

Baochang Ren, Yunzhi Yao, Rui Sun, Shuofei Qiao, Ningyu Zhang, and Huajun Chen. 2026. Aligning agentic world models via knowledgeable experience learning. *arXiv preprint arXiv:2601.13247*.

Donald A. Schön. 1983. *The Reflective Practitioner: How Professionals Think in Action*. Basic Books, New York.

Noah Shinn, Federico Cassano, Edward Berman, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. 2023. Reflexion: Language agents with verbal reinforcement learning. In *Advances in Neural Information Processing Systems 36 (NeurIPS)*.

Xijia Tao, Yihua Teng, Xinxing Su, Xinyu Fu, Jihao Wu, Chaofan Tao, Ziru Liu, Haoli Bai, Rui Liu, and Lingpeng Kong. 2026. MMSearch-Plus: Benchmarking provenance-aware search for multimodal browsing agents. In *The Fourteenth International Conference on Learning Representations (ICLR)*. ArXiv:2508.21475.

Michael Tomasello. 1999. *The Cultural Origins of Human Cognition*. Harvard University Press, Cambridge, MA.

VoltAgent and Contributors. 2025. Awesome openclaw skills: A curated list of reusable agent skills. GitHub repository, https://github.com/VoltAgent/awesome-openclaw-skills.

Guanzhi Wang, Yuqi Xie, Yunfan Jiang, Ajay Mandlekar, Chaowei Xiao, Yuke Zhu, Linxi Fan, and Anima Anandkumar. 2024. Voyager: An open-ended embodied agent with large language models. *Transactions on Machine Learning Research (TMLR)*.

Zora Zhiruo Wang, Apurva Gandhi, Graham Neubig, and Daniel Fried. 2025. Inducing programmatic skills for agentic tasks. *arXiv preprint arXiv:2504.06821*.

Jason Wei, Zhiqing Sun, Spencer Papay, Scott McKinney, Jeffrey Han, Isa Fulford, Hyung Won Chung, Alex Tachard Passos, William Fedus, and Amelia Glaese. 2025. BrowseComp: A simple yet challenging benchmark for browsing agents. *arXiv preprint arXiv:2504.12516*.

Georg Wölflein, Dyke Ferber, Daniel Truhn, Ognjen Arandjelović, and Jakob Nikolas Kather. 2025. LLM agents making agent tools. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (ACL)*, pages 26092–26130, Vienna, Austria.

Jinming Wu, Zihao Deng, Wei Li, Yiding Liu, Bo You, Bo Li, Zejun Ma, and Ziwei Liu. 2025. MMSearch-R1: Incentivizing LMMs to search. *arXiv preprint arXiv:2506.20670*.

Mingyuan Wu, Jingcheng Yang, Jize Jiang, Meitang Li, Kaizhuo Yan, Hanchao Yu, Minjia Zhang, Chengxiang Zhai, and Klara Nahrstedt. 2026a. VTool-R1: VLMs learn to think with images via reinforcement learning on multimodal tool use. In *The Fourteenth International Conference on Learning Representations (ICLR)*. ArXiv:2505.19255.

Rong Wu, Xiaoman Wang, Jianbiao Mei, Pinlong Cai, Daocheng Fu, Cheng Yang, Licheng Wen, Xuemeng Yang, Yufan Shen, Yuxin Wang, and Botian Shi. 2026b. From interactions to principles: Experience-driven self-distillation for evolving LLM agents. In *Proceedings of the 43rd International Conference on Machine Learning (ICML)*. ArXiv:2510.16079.

Yunzhong Xiao, Yangmin Li, Hewei Wang, Yunlong Tang, and Zora Zhiruo Wang. 2025. ToolMem: Enhancing multimodal agents with learnable tool capability memory. *arXiv preprint arXiv:2510.06664*.

Huanjin Yao, Qixiang Yin, Min Yang, Ziwang Zhao, Yibo Wang, Haotian Luo, Jingyi Zhang, and Jiaxing Huang. 2026. MM-DeepResearch: A simple and effective multimodal agentic search baseline. *arXiv preprint arXiv:2603.01050*.

Lifan Yuan, Yangyi Chen, Xingyao Wang, Yi R. Fung, Hao Peng, and Heng Ji. 2024. CRAFT: Customizing LLMs by creating and retrieving from specialized toolsets. In *The Twelfth International Conference on Learning Representations (ICLR)*.

Zhengbo Zhang, Jinbo Su, Zhaowen Zhou, Changtao Miao, Yuhan Hong, Qimeng Wu, Yumeng Liu, Feier Wu, Yihe Tian, Yuhao Liang, Zitong Shan, Wanke Xia, Yi-Fan Zhang, Bo Zhang, Zhe Li, Shiming Xiang, and Ying Yan. 2026. VisBrowse-Bench: Benchmarking visual-native search for multimodal browsing agents. *arXiv preprint arXiv:2603.16289*.

Appendix

Outline. The appendix is organized as follows:

- Appendix A, **Evaluation**: per-benchmark sample counts and descriptions (in-domain and out-of-domain), the LLM judge prompt, performance variance, and a note on privacy-driven refusals.
- Appendix B, **Base Tools**: full schemas and at-inference prompts for the eight base tools.
- Appendix C, **System Prompt**: the agent system prompt used at inference.
- Appendix D, **More Implementation Details**: model setup, decoding settings, and pipeline hyperparameters.
- Appendix E, **More Tool Generation Details**: training samples, generator process statistics, and Phase 2/3 prompts.
- Appendix F, **More Tool Examples**: successful, failed, and filtered tool case studies.
- Appendix G, **Overhead Analysis**: end-to-end generation cost (tokens, dollars, wall-clock) and per-query inference overhead.
- Appendix H, **Qualitative Analysis**: recurring patterns behind gained and lost samples.

A Evaluation

A.1 Evaluation Benchmarks

We list per-benchmark details for the in-domain (ID) and out-of-domain (OOD) evaluation sets introduced in Section 4.3. Table 8 summarizes the per-benchmark sample counts. For OOD benchmarks that mix text-only and image-grounded items we restrict evaluation to the multimodal subset, so OOD counts are smaller than the corresponding full-benchmark totals.

A.1.1 In-Domain Benchmarks

FVQA. A fact-based VQA dataset (Wu et al., 2025) that pairs images with questions whose answers require commonsense or world-knowledge facts not directly observable in the image. We evaluate on the official test split of 1800 samples, and use the 3132 search-required samples from the train split for tool generation.

InfoSeek. A visual information-seeking benchmark (Chen et al., 2023) of fine-grained questions about entities depicted in images (e.g., species, models, landmarks). We use the val split for tool generation and test split for inference.

EncyclopedicVQA. A benchmark (Mensink et al., 2023) of questions about detailed properties of fine-grained categories. We evaluate on the test split and use val split for tool generation.

Benchmark	# Samples
In-domain (test splits of training-pool datasets)	
FVQA (Wu et al., 2025)	1800
InfoSeek (Chen et al., 2023)	2000
EncyclopedicVQA (Mensink et al., 2023)	1960
Out-of-domain (multimodal search benchmarks)	
MM-BrowseComp (Li et al., 2025)	243
SimpleVQA (Cheng et al., 2025)	300
MMSearch (Jiang et al., 2025)	171
MMSearch-Plus (Tao et al., 2026)	311
HLE-VL (Phan et al., 2026)	330
LiveVQA (Fu et al., 2025)	300
BrowseComp-VL (Geng et al., 2026)	399
RealX-Bench (Hong et al., 2026)	194
VDR-Bench (Huang et al., 2026)	500
VisBrowse-Bench (Zhang et al., 2026)	169

Table 8: Evaluation benchmarks. In-domain benchmarks are the held-out test splits of the three training datasets; out-of-domain benchmarks are ten multimodal search benchmarks unseen during tool generation, evaluated on their multimodal subsets.

A.1.2 Out-of-Domain Benchmarks

MMSearch. A multimodal search benchmark (Jiang et al., 2025) of 300 manually curated questions across 14 subfields, designed to assess large multimodal models as multimodal search engines. We evaluate on the End-to-End sub-task, which requires the agent to perform query understanding, retrieval, and answering in a single pipeline. To align with other works for fair comparison, we only use multimodal subset, which contains 171 samples.

MMSearch-Plus. A harder, provenance-aware extension (Tao et al., 2026) that emphasizes localized visual reasoning, verification under noisy or conflicting retrieval, and multi-step text–image search; each item provides 1–5 images and one or more valid answers. We use 311 full set for evaluation.

BrowseComp-VL. The vision–language extension of BrowseComp (Wei et al., 2025) introduced by WebWatcher (Geng et al., 2026), with cross-modal information-seeking questions spanning entertainment, humanities, technology, natural science, and other domains. We use all 399 samples for evaluation.

MM-BrowseComp. Hand-crafted multimodal browsing questions (Li et al., 2025) across several sub-tasks, where the answer-relevant content is hard to find. There are two versions of MM-BrowseComp. We use the newest version, which has 243 multimodal tasks.

SimpleVQA. A multimodal factuality benchmark (Cheng et al., 2025) of short, knowledge-bound questions with timeless reference answers.

Following WebWatcher's setting, we evaluate on the English subset containing 300 multimodal tasks.

VisBrowse-Bench. A benchmark of visual-native search instances (Zhang et al., 2026) that require cross-validation of multimodal evidence via interleaved text–image retrieval and joint reasoning, including cases where the answer is not present in any text snippet. We use the full 169 samples to evaluate.

HLE-VL. The multimodal subset of Humanity's Last Exam (Phan et al., 2026), drawn from frontier-knowledge questions across mathematics, the natural sciences, and the humanities.

LiveVQA. A live visual knowledge-seeking benchmark (Fu et al., 2025) drawing from recent news, video platforms, and academic publications, designed for the seeking-and-updating regime. We follow WebWatcher's setting and use 300 samples from LiveVQA to evaluate.

RealX-Bench. Introduced by DeepEyesV2 (Hong et al., 2026); expert-verified instances that require integrating fine-grained visual perception, dynamic multi-hop web retrieval, and multi-step logical reasoning. This benchmark contains perception and search types, which make it easy to check the performance improvement coming from visual tools and search tools.

VDR-Bench. The benchmark released alongside Vision-DeepResearch (Huang et al., 2026): long-horizon multimodal deep-research instances that interleave many reasoning turns with hundreds of search-engine interactions, designed to evaluate sustained multi-step browsing under heavy real-world noise.

A.2 LLM Judge Prompt and Retrieval-Shortcut Check

No retrieval shortcut. Across all ID and OOD benchmarks, we did not observe cases in which the search tools surface the gold answer verbatim from indexed pages. Accuracy therefore reflects the agent's multi-step reasoning over evidence rather than a retrieval shortcut.

Judge prompt. To align with recent multimodal deep-research work (Chen et al., 2026a), we adopt the same LLM judge as Vision-DeepResearch (Huang et al., 2026) and use GPT-4o as the judge model, applying the prompt below uniformly across all benchmarks.

LLM Judge Prompt

You are an impartial judge evaluating whether a deep research report contains the correct answer.
[Question] {question}
[Correct Answer] {correct_answer}
[Deep Research Report] {response}
Task: Determine if the deep research report contains the correct answer anywhere in its content.
Instructions:
1. Read through the entire research report carefully
2. Look for the correct answer anywhere in the report (it may be embedded in paragraphs, tables, or sections)
3. Check if the information in the report is consistent with the correct answer
4. The answer does NOT need to be in a specific format or labelled as "final answer"
5. Provide your reasoning
6. Answer with "yes" if the report contains the correct answer, "no" if it doesn't or contradicts it
Output format: correct: [yes/no] reasoning: [your explanation]

A.3 Performance Variance

Because the agent issues live search calls and the randomness exists in LLM generation, repeated evaluations of the same configuration show run-to-run variance. For the result numbers in Section 5, we report the average of three independent runs.

A.4 Refusals on Identity Queries

Some of our evaluation benchmarks contain queries that reference a real person, such as "who is the person in this photograph," "what is the affiliation of this researcher". Proprietary models are increasingly trained to decline such queries under their privacy and identification policies, even when the gold answer is a public-figure fact already widely indexed on the open web. We observe this from GPT-5 in our setting, which returns a refusal in place of an answer, and the judge will count the refusal as incorrect. Therefore, in some of the benchmarks, the GPT-5 performance is lower than the Qwen3-VL-32B model or Qwen3-VL-8B-Instruct model.

B   Base Tools

Below we give the detailed documentation for each of the eight base tools introduced in Section 4.1.

B.1   Search Tools

All three search tools route HTTP queries through the Serper API[3] and post-process the raw payload with a Qwen3-VL-8B-Instruct model as the VLM summarizer. The summarizer runs at decoding temperature 0 with a 4096-token output cap, and each call retrieves the top 10 raw results before reranking and summarization.

Text Search. Search the web with intelligent query routing and VLM summarization. Given a text query, the tool automatically classifies the query intent and routes it to the most appropriate Serper endpoint, which has general web, news, academic papers, images, maps, local places, shopping, or patents types, and returns a coherent summary of the top-10 raw results with inline citations [1], [2], . . . followed by a citations block of source titles and URLs. This format supports multi-round search: the agent can read the summary for quick understanding and then visit specific cited URLs through Webpage Visit. The summarizer prompt is shown in B.1.

Text Search summarizer prompt (abridged)

You are a research summarizer. Given raw web search results and a user query, do exactly three things:

1. RERANK the numbered organic results by how directly each helps answer the query.
2. KEEP at most K most useful results; emit their original 1-based ranks as `kept_indices`. If none help, emit `kept_indices: []`.
3. SUMMARIZE the query-relevant facts from the FULL set of raw results into a concise 3–5 sentence prose paragraph; include named entities, numbers, and dates verbatim.

Knowledge-graph, answer-box, and top-stories blocks are ineligible for `kept_indices` but their facts should still surface in `summary`. Output STRICT JSON with the schema {`kept_indices`, `summary`, `no_results_justification`,

---

`suggested_queries`, `suggested_next_actions`}; when no result is useful, populate the justification and propose alternative queries or downstream tool calls.

Image Search. Identify the objects, landmarks, artwork, text, products, plants, animals, and other entities depicted in an image, using Serper's reverse-image-search (Google Lens) endpoint. Returns a list of visual matches with titles, source URLs, links, and thumbnails. The agent invokes the tool by passing the runtime identifier of the target image. The tool performs reverse search (image → information) on a single image per call; finding images from a text description is instead handled by Text Search with an image-search intent. A separate multimodal summarizer prompt B.1 reranks the candidates against the query image and produces the same JSON envelope as Text Search.

Image Search summarizer prompt (abridged)

You are a visual-match summarizer. Given raw reverse-image-search results (and, in the multimodal variant, the query image plus each candidate's thumbnail), do exactly three things:

1. RERANK the numbered matches by how likely each identifies the same subject as the query image.
2. KEEP at most K most useful matches as `kept_indices`.
3. SUMMARIZE what the FULL set of raw matches indicates about the query image's likely subject in a concise 3–5 sentence prose paragraph; capture entity names, dates, attributes verbatim.

Output STRICT JSON with {`kept_indices`, `summary`, `no_results_justification`, `suggested_next_actions`}; when no match is useful, justify per-match and propose follow-up actions such as cropping with Visual Grounding before re-searching, or switching to Text Search.

Webpage Visit. Visit one or more webpages, convert them to plain text via Serper APIs, and extract goal-relevant content using a local Qwen3-VL-8B-

---

[3] https://serper.dev/

Instruct model. This tool returns per-URL evidence and a summary. The extraction prompt is shown in B.1.

Webpage Visit extraction prompt

Please process the following webpage content and user goal to extract relevant information:

Webpage Content: `{webpage_content}`
User Goal: `{goal}`
Task Guidelines

1. **Content scanning for rationale**: locate the specific sections directly related to the user's goal.
2. **Key extraction for evidence**: extract the most relevant information; preserve the full original context whenever possible.
3. **Summary output**: organize the result into a concise paragraph with logical flow that connects the evidence back to the goal.

Output: a single JSON object with keys `rational`, `evidence`, and `summary` (each a string; empty string if no content is available). No code fences, no Markdown, no extra keys.

B.2 Visual Tools

Zoom-in. Crop a region of an image given a normalized bounding box on the $[0, 1000]$ scale plus padding, and return the cropped image. Used for closer visual inspection after the agent has already localized a region of interest.

Visual Grounding. Locate and highlight regions of an image that match a text query, backed by SAM3 (Carion et al., 2025). It returns an annotated image with matched regions highlighted and numbered, along with bounding boxes.

OCR. Extract readable text from an image, backed by PaddleOCR-VL (PaddlePaddle Team, 2025). Returns the transcribed text as a single string. Used when the task is about words, numbers, or printed labels in the image; not for general object localization or segmentation.

Depth Estimation. Estimate a per-pixel depth map for an input image, backed by Depth Anything 3 (Lin et al., 2025). Returns a depth image (closer surfaces brighter, farther darker). Used when the task requires reasoning about relative distance, foreground–background separation, or 3D scene structure cues that flat 2D crops cannot resolve.

B.3 Code-Execution Tool

Code Execution. Run Python over the agent's local computation state and the outputs of previously called tools (bounding boxes, OCR strings, segmentation masks, and so on), returning both standard output and the resulting local variables. The agent may pass a snippet directly, or describe a computation goal in plain language and let a small coding LLM (Qwen3-VL-8B-Instruct) author the snippet using prior tool outputs as named variables. Used for aggregating numbers extracted by OCR, filtering detected regions by bounding-box area, or any cross-tool numerical reasoning the agent cannot complete in its own response.

C System Prompt

Here is the system prompt of the agent.

System Prompt

You are a visual reasoning agent that answers questions about images using a structured Perception-Reasoning-Action framework.

Your goal is to provide accurate, well-reasoned answers. You have access to various tools that compensate for known limitations of vision-language models.

Use native tool-calling for tools. Do not write textual Action/Action Input to call tools.

At most one native tool call is allowed per assistant message/turn.

Use the following format:

Question: the input question you must answer

Observation: your direct perception of the input or the result of the action you took

Thought: you should always think about what to do

Action: the action to take, should be one of the provided tools, or "Final Answer" if you have a final answer and do not need to call any more tools.

Action Input: the input to the action, or the final answer if Action is "Final Answer"

\# Image-input rule:

- Runtime image IDs are provided in Environment Update messages.

> - If a tool needs image input, use those IDs in *_image_path fields.
> - Do NOT invent image file names or paths.
> # Tool-Use Rules
> - Call exactly ONE tool per turn. Never include multiple <tool_call> blocks.
> - Full tool schemas with parameters and types are provided in the <tools> section below.
> - After each tool call, verify whether the result is actually informative for the task.
> - If a tool result is empty, missing key values, or non-informative, do NOT guess. Issue another tool call with corrected arguments or use a different tool.
> # Available Tools
> You may call ONE tool per turn to assist with the user query.
> You are provided with function signatures within <tools></tools> XML tags:
> <tools>
> {tools_directory}
> </tools>
> For each function call, return a json object with function name and arguments within <tool_call></tool_call> XML tags:
> <tool_call>
> {"name": <function-name>, "arguments": <args-json-object>}
> </tool_call>

D More Implementation Details

Model setup. For full reproducibility, all GPT-5 calls use the pinned snapshot `gpt-5-2025-08-07` via the OpenAI API. All Qwen3-VL-8B-Instruct, Qwen3-VL-32B-Instruct, and Qwen3-VL-8B-Thinking calls use the public Hugging Face weights served locally with vLLM. The LLM judge uses GPT-4o (Appendix A.2).

Decoding. Temperature 0.3, top-p 0.95, repetition penalty 1.1, per-turn maximum 2,048 generated tokens, at most fifteen tool-calling iterations per query, and an agent context capped at 120K tokens.

Pipeline hyperparameters. *Phase 1 (Trajectory Mining).* Sentence encoder $\psi =$ BAAI/bge-m3 for embedding capability gaps; agglomerative clustering with average linkage over cosine distance; default cluster count $C = 500$. *Phase 2 (Reuse-or-Grow).* Pre-generation TF–IDF reuse threshold $\tau_{\text{pre}} = 0.40$. *Phase 3 (Tool Generation).* Per-

candidate retry budget $A = 2$. *Phase 4 (Verification).* Gate 1 (sandboxed sanity) wall-clock budget 10 seconds; Gate 2 (LLM static code review) mean-score threshold $\mu_{\min} = 3.0$, minimum-axis threshold $a_{\min} = 1$; post-gate TF–IDF dedup threshold $\tau_{\text{post}} = 0.55$. *Inference.* Progressive-disclosure retrieval exposes the top-$K = 10$ generated tools per query alongside the base library.

E More Tool Generation Details

E.1 Training Samples

Trajectories are mined from the result of the agent on three knowledge-intensive multimodal QA datasets, all distinct from the evaluation benchmarks (Appendix A.1). We sample 3312, 3000, and 2862 queries per dataset.

Dataset	Split (size)
FVQA (Wu et al., 2025)	train (3312)
InfoSeek (Chen et al., 2023)	val (3000)
EncyclopedicVQA (Mensink et al., 2023)	val (2862)

Table 9: Tool-generation training samples and datasets.

E.2 Generator Process Statistics

We hold the inference model fixed at Qwen3-VL-8B-Instruct and vary the model that authors new tools during Phase 3, running each on the same 300-query FVQA training subset (search-required partition). Table 10 reports generation-process statistics; qualitative findings follow.

Generator	Trig.	Succ. (%)	Dedup	Cost
GPT-5	73	50 (68%)	23	$1.03
Qwen3-VL-32B	83	67 (81%)	6	$0.00
Qwen3-VL-8B	83	24 (29%)	17	$0.00

Table 10: Tool-generator model ablation on 300 FVQA training queries. *Trig.*: queries whose self-critique labels a capability gap. *Succ.*: candidates that pass both verification gates. *Dedup*: candidates skipped because a near-duplicate already exists in the catalog. Local models incur zero API cost.

GPT-5 produces structurally rich tools: modular helper functions, tiered authority ranking of knowledge sources, and multi-layer fallback chains. Qwen3-VL-32B passes 81% of candidates with clean but simpler code. Qwen3-VL-8B succeeds on only 29%; manual inspection reveals logic bugs that survive the gates but would fail at runtime (see Appendix F for code examples). We adopt GPT-5 as the default generator, accepting its API cost in exchange for the structurally richer code.

E.3 Tool Generation Prompts

We list all prompts used in the tool-generation pipeline in execution order.

1. Self-critique (Phase 1, Layer B).

Self-critique prompt (abridged)

```
System: You are an analyst deciding whether a
failed multimodal agent run requires a NEW tool
to be invented.

User:
Question: {question}
Final answer the agent gave: {prediction}
Ground-truth answer: {gold}

The agent invoked these tools: {tool_counts}
Last tool errors: {recent_errors}

Would a NEW tool have let the agent answer
correctly? Reply with one of:
- NEW_TOOL_NEEDED: capability X is missing
- ARGUMENT_MISTAKE: right tool, wrong usage
- SEARCH_NOISE: tools worked, bad results
- AMBIGUOUS: question itself unanswerable

If NEW_TOOL_NEEDED, describe:
   (a) input modality (text / image+text / image)
   (b) data source (website/API or web search)
   (c) which field of the gold answer to extract

Reply: LABEL: <label>  WHY: <one sentence>
```

2. Query classifier (Phase 3 pre-step).

Classifier prompt (abridged)

```
System: You classify a question by its expected
answer shape. Reply ONLY in 3-line format.

User:
Question: "{failed_query}"

Reply with EXACTLY this format (3 lines):
ANSWER_TYPE: <COUNT|DATE|BOOLEAN|ENTITY_NAME|
              FACTUAL_LOOKUP|OTHER>
ANSWER_LENGTH: <1-5_chars|short_phrase|
                full_sentence>
EXTRACTION_HINT: <what to extract from search>
```

3. Generator system prompt (Phase 3).

Generator system prompt (abridged)

```
You are a Python tool author for a multimodal
deep-research agent. Write a single new tool
class that solves the failed query.

The tool must:
1. Inherit from BaseTool
2. Call super().__init__() with: tool_name,
   tool_description, input_schema, ...
3. Implement execute(**kwargs) -> dict|str|list
4. Use only: requests, re, json, datetime
5. Chain-call base tools via HTTP POST to
   127.0.0.1:8104/execute -- do NOT call
   external APIs directly
6. Take entities as parameters; do not hardcode

Anti-hardcode rules:
   (a) No conditional-return lookup tables
   (b) No fake scores from string properties
   (c) No hardcoded reference constants
```

4. Seed examples (Phase 3, appended to system prompt). The system prompt includes six positive tool examples and one anti-pattern. Each example demonstrates a different tool archetype:

Seed example categories (code omitted)

```
# Example 1: text-only KB chain
#   (e.g. actress_by_character: query Wikipedia
#    for an actress given a character name)

# Example 2: image-then-KB chain
#   (e.g. fossil_identification: OCR image,
#    then search KB for fossil species)

# Example 3: narrow-domain HTML scrape
#   (e.g. esports_player_stats: scrape a
#    specific game wiki for player stats)

# Example 4: cross-modal lens+verify
#   (e.g. company_recognition: Lens to ID logo,
#    then verify via text search)

# Example 5: structured-KB chain-call
#   (e.g. entity_property_lookup: query
#    Wikidata for a specific property)

# Example 6: vision zero-shot classification
#   (e.g. best_label_by_image: CLIP similarity
#    over a label set)

# ANTI-PATTERN (what NOT to write):
#   - Hardcoded lookup tables
#   - Fake scores from string length
#   - Specific entity in tool_description
```

5. Generator user prompt (Phase 3, per-gap).

Generator user prompt (abridged)

```
Failed subtask:
  query: {failed_query}

Expected answer shape (from classifier):
  answer_type:   ENTITY_NAME
  answer_length: short_phrase
  extract_hint:  extract the person's name

Image: {image_url}
  (Declare image_url in input_schema and
   chain-call a vision tool)

Failure reason: {self_critique_reason}
Tools already tried: {tried_tools}

Design a single new tool that would have made
this subtask succeed, then return the JSON.
```

6. Feedback retry prompt (Phase 3, on gate failure).

Feedback retry prompt (abridged)

```
You previously wrote a tool for this subtask,
but it did not pass the quality gate.

Failed subtask:
  query: {failed_query}

Quality gate feedback:
  {feedback}
  (e.g. "L1: tool chain-calls wikidata_query
   but never checks confidence field")

Your previous code:
```python
{previous_code}
```

Fix the issues flagged above. Keep what worked.
Return the revised JSON.
```

7. LLM critic (Gate 2).

F More Tool Examples

We show more tool examples here, including successful and failed ones. Code is abridged for space.

F.1 Successful Tool: Medical Condition Identifier

Triggered by *"What skin condition is shown?"* The tool decomposes the problem into helper functions, ranks medical sources by authority, and chains five fallback stages. Key excerpts:

```
Medical Condition Identifier (abridged)

# Tiered medical-source authority ranking
def _authority_score(self, domain):
    tiers = [
        (100, ["wikipedia.org"]),
        (95, ["nih.gov", "cdc.gov", "who.int"]),
        (90, ["dermnetnz.org", "mayoclinic.org"]),
        (80, ["medscape.com", "webmd.com"]),
    ]
    for score, subs in tiers:
        if any(s in domain for s in subs):
            return score
    return 30

def execute(self, **kwargs):
    # Stage 1: reverse-image search
    cands = self._pick_candidates_from_lens(matches)
    # Stage 2: fallback to Image Search
    if not cands:
        cands = self.
    _pick_candidates_from_image_search(...)
    # Stage 3: rank by authority score
    ranked = sorted(cands, key=lambda x: -x["score"
      ])
    # Stage 4: extract from URL slug or title
    for c in ranked[:5]:
        cond = self._slug_to_condition(c["link"])
        if self._is_valid_condition(cond):
            return cond.lower()
    # Stage 5: last-resort -- visit the page
      directly
    _post("Webpage_Visit_Tool", {
        "urls": [best["link"]],
        "goal": "Extract the medical condition name"
    })
```

The tool embeds domain knowledge (medical authority tiers) and robust output normalization (1–5 word lowercase phrase, HTML/wiki markup stripped). The generated tool here also demonstrates the compositionality by composing base tools (Image Search, Test Search, and Webpage Visit) and then generate the new tool.

F.2 Failed Tool: Building Identifier

`tall_slender_building_identifier` passes the AST process, but still contains three defects:

```
Building Identifier (abridged)

# BUG 1: missing import -- module uses json.loads
# but `import json` is absent from the file header
infobox = json.loads(result)  # NameError

# BUG 2: returns a dict KEY, not the VALUE
return {"building_name":
    list(infobox["infobox"].keys())[0]}
#    ^^ returns "height" instead of "828 m"

# BUG 3: overly specific, non-reusable name
tool_name = "tall_slender_building_identifier"
#    ^^ only matches one visual archetype
```

F.3 Filtered Tool: Wrapper

The generator occasionally produces tools whose `tool_name` and docstring advertise a general capability, but whose body hardcodes the literal target entity from the originating forging-time query. The candidate below (with explanatory comments added) was triggered by a single training query about a named hurricane:

```
Wrapper (abridged)

class HurricaneWindSpeedLookupTool(BaseTool):
    """Look up the maximum sustained wind speed
    of a HURRICANE by name via web search. ..."""

    def __init__(self):
        super().__init__(
            tool_name="hurricane_wind_speed_lookup",
        ...)

    def execute(self, **kwargs):
        ...
        # Identify hurricane via Lens, then filter
      titles
        # by a hardcoded name regex:
        if image_url:
            titles = [m.get("title","")
                for m in matches[:5]]
            name_candidates = [t for t in titles
                if re.search(
                    r"\b(hurricane|storm|"
                    r"eresto|ernesto)\b",
                    t, re.I)]
        ...
```

The advertised scope is generic hurricane wind-speed lookup, but the title filter hardcodes the literal target entity (`ernesto`) together with an autoregressive misspelling (`eresto`). On every other hurricane, the filter returns the empty list and the tool errors out.

G Overhead Analysis

Table 11 breaks down the one-time cost of running TOOLSMITH with GPT-5 as the generator at

$C = 500$, yielding 264 verified tools. The cost is dominated by completion tokens ($\sim$\$34.80 of \$41.44 at the GPT-5 list price) because GPT-5's reasoning traces are charged as output.

Component	Calls	Prompt	Compl.	Cost
Generator (codegen)	455	5.19M	2.77M	\$34.18
Self-critique (trigger)	446	0.25M	0.70M	\$7.26
Classifier (local 8B)	—	0.05M	0.02M	\$0.00
Total		**5.49M**	**3.48M**	**\$41.44**

Table 11: Tool-generation cost breakdown. Token counts are from the API's reported usage field. GPT-5 pricing: \$1.25 / 1M input, \$10.00 / 1M output (reasoning tokens count as output). The classifier runs on a local Qwen3-VL-8B at zero API cost. Wall-clock time: 170 minutes with 4 concurrent workers.

At inference, the only added overhead is the per-query tool routing: a single forward pass through a sentence encoder ($\sim$10 ms on CPU) followed by a dot-product over the tool embedding matrix. The agent sees $|\mathcal{T}_{\text{base}}| + K = 18$ tools per query rather than the full catalog, so the per-turn context grows by only the top-$K{=}10$ generated tool schemas ($\sim$2K tokens), a modest increase relative to the 120K context budget.

H Qualitative Analysis

We present additional case studies. Three patterns account for the gains in these examples:

1. **Perceive-then-query.** The generated tool chains visual identification (Lens) with structured lookup (Wikidata, text search), forcing the agent to identify the entity before searching for facts. The base agent often skips identification and searches for the wrong entity.

2. **Specialized lookup.** The generated tool directly answers a specific attribute query (e.g. aircraft model year, building architect) via a targeted chain-call pipeline, replacing the base agent's generic multi-step search.

3. **Forced verification.** The generated tool prevents the agent from answering from internal knowledge alone (zero-tool hallucination) by requiring a lookup step.

Lost samples concentrate on a small number of tools returning incorrect information, and on visual mis-identification where Lens returns a similar but wrong entity.

Case studies. Figures 3–6 walk through four representative gained samples. The first three illustrate the perceive-then-query pattern at the entity (Figures 3 and 4) and region (Figure 5) levels; the fourth (Figure 6) shows how a generated tool can re-rank search results toward higher-authority sources even when both pipelines call similar primitives.

Figure 3: Entity-first identification (Reed Hastings, \$50M Hastings Initiative). The base agent searches without knowing who is in the image and misattributes the donation to Eric Schmidt; the generated Image Entity Canonical Name tool resolves the person first, after which a single text search returns the correct year.

Figure 4: Entity-first identification on a person whose visual context provides only vague cues. The base agent guesses "Mississippi" from incidental visual content and returns the wrong pageant; the generated Celebrated Person From Image tool produces the canonical identity (Beatrice Luigi Gomez), which makes the event lookup trivial.

Figure 5: Precise region identification on a US map. Without explicit map-region parsing the base agent confuses Oregon with neighboring Washington and returns the wrong governor; the generated State Context Lookup tool pins down the highlighted state first, after which the governor lookup succeeds.

Figure 6: Search-ranking steering. The base agent's generic image search returns multiple election maps and the agent latches onto a Reddit thread about the wrong year; the generated Event Name From Image tool primes the search for an event-name extraction and reorders the results so Wikipedia (1996) outranks Reddit (1968).