Structured Kernel Interpolation with Sparse Grids

Abstract

Structured kernel interpolation (SKI) accelerates Gaussian process (GP) inference by interpolating the kernel covariance function using a dense grid of inducing points, whose corresponding kernel matrix is highly structured and thus amenable to fast linear algebra. Unfortunately, SKI scales poorly in the dimension of the input points, since the dense grid size grows exponentially with the dimension. To mitigate this issue, we propose the use of *sparse grids* within the SKI framework. These grids enable accurate interpolation, but with a number of points growing more slowly with dimension. We contribute a novel nearly linear time matrix-vector multiplication algorithm for the sparse grid kernel matrix. We also describe how sparse grids can be combined with an efficient interpolation scheme based on simplices. With these modifications, we demonstrate that SKI can be scaled to higher dimensions while maintaining accuracy.

1 Introduction

Gaussian processes (GPs) are popular prior distributions over continuous functions for use in Bayesian inference [14]. Due to their simple mathematical structure, closed form expressions can be given for posterior inference [20]. Unfortunately, a well-established limitation of GPs is that they are difficult to scale to large datasets. Exact posterior inference and log-likelihood computation for hyperparameter learning require the inversion of a typically dense kernel covariance matrix $K \in \mathbb{R}^{n \times n}$, where n is the number of training points. Naively, this operation requires $\mathcal{O}(n^3)$ time and $\mathcal{O}(n^2)$ memory.

Structured Kernel Interpolation. Many techniques have been proposed to mitigate this scalability issue [24, 19, 25, 9]. Recently, structured kernel interpolation (SKI) has emerged as a promising approach [9]. In SKI, the kernel matrix is approximated via interpolation onto a dense rectilinear grid of m inducing points. In particular, K is approximated as $W K_G W^T$, where $K_G \in \mathbb{R}^{m \times m}$ is the kernel matrix on the inducing points and $W \in \mathbb{R}^{n \times m}$ is an interpolation weight matrix mapping training points to nearby grid points. Typically, W is sparse, and K_G is highly structured — e.g., for shift invariant kernels, K_G is multi-level Toeplitz. Thus, W, K_G, and in turn the approximate kernel matrix $W K_G W^T$ admit fast matrix-vector multiplication. This allows fast approximate inference and log-likelihood computation via the use of iterative methods, like the conjugate gradient and Lanczos algorithms.

SKI's Curse of Dimensionality. Unfortunately, SKI does not scale well to high-dimensional input data: the number of points in the dense grid, and hence the size of K_G, grows exponentially in the dimension d. Moreover, SKI typically employs local cubic interpolation, which leads to an interpolation weight matrix W with row sparsity that also scales ex-

37 ponentially in *d*. This *curse of dimensionality* is a well-known issue with the use of dense
38 grid interpolation. It has been studied extensively, e.g., in the context of high-dimensional
39 polynomial interpolation and numerical integration [17, 5].

40 In the computational mathematics community, an important technique for interpolating
41 functions in high dimensions is *sparse grids* [2]. Roughly a sparse grid is a union of
42 rectilinear grids with different resolutions in each dimension. In particular, it is a union of
43 all $2^{\ell_1} \times 2^{\ell_2} \times \ldots \times 2^{\ell_d}$ sized grids, where $\sum_{i=1}^{d} \ell_i \leq \ell$, for some maximum total resolution
44 ℓ. This upper bound on the total resolution limits the number of points in each grid —
45 while a grid can be dense in a few dimensions, no grid can be dense in all dimensions. See
46 Figure 1 for an illustration.

47 It is well-known that sparse grids have interpolation accuracy comparable to dense grids
48 under certain smoothness assumptions on the interpolated function [22], while using
49 significantly fewer points. Concretely, for any function $f : \mathbb{R}^d \to \mathbb{R}$ with bounded mixed
50 partial derivatives, a sparse grid containing $\mathcal{O}(2^\ell \ell^{d-1})$ points can interpolate as accurately
51 as a dense grid with $\mathcal{O}(2^{\ell d})$ points, where ℓ is the maximum grid resolution [21].

52 **Combining Sparse Grids with SKI.** Our main contribution is to demonstrate that sparse
53 grids can be used within the SKI framework to significantly improve scaling with dimension.
54 Doing so requires several algorithmic developments. When the inducing point grid is
55 sparse, the kernel matrix on the grid, K_G, no longer has simple structure. E.g., it is not
56 Toeplitz when the kernel is shift invariant. Thus, naive matrix-vector multiplications with
57 K_G require time that scales quadratically, rather than near-linearly in the grid size. This
58 would significantly limit the scope of performance improvement from using a sparse grid.

59 To handle this issue, we develop a near-linear time matrix-vector multiplication (MVM)
60 algorithm for any sparse grid kernel matrix. Our algorithm is recursive, and critically
61 leverages the fact that sparse grids can be constructed from smaller dense grids and that
62 they have tensor product structure across dimensions. For an illustration of our algorithm's
63 complexity versus that of naive quadratic time MVMs, see Figure 1 (c).

(a) (b) (c)

Figure 1: Illustration of sparse grid construction for $d = 2$ and maximum resolution $\ell = 2$. (a) A
dense grid with resolution (l_1, l_2) has 2^{l_1} and 2^{l_2} points in each dimension; the gray shaded grids
have total resolution $l_1 + l_2 \leq 2$. (b) The sparse grid $\mathcal{G}_{2,2}$ is the union of rectlinear grids with total
resolution at most 2. The 17 points with red squares belong to the sparse grid. The dense grid
includes the additional points with blue dots, for a total of 49 points. (c) MVM complexity of
performing a single kernel MVM operation for both grids with 2^8 unique points in each dimension.
For sparse grids, *Ours-MVM* (i.e., the proposed MVM algorithm) improves significantly over the
naive implementation (*Sparse-MVM*).

A second key challenge is that, while sparse grids allow for a grid size that grows as a much more mild exponential function of the dimension d, the bottleneck for applying SKI on large datasets can come in computing MVMs with the interpolation weight matrix $W \in \mathbb{R}^{n \times m}$. For classic high-dimensional interpolation schemes, like cubic interpolation, each row of W has $\mathcal{O}(2^d)$ non-zero entries, i.e., the kernel covariance for each training point is approximated by a weighted sum of the covariance at $\mathcal{O}(2^d)$ grid points. When the number of training points n is large, storing W in memory, and multiplying by it, can become prohibitively expensive. To handle this issue, we take an approach similar to that of Kapoor et al. [13] and employ simplicial basis functions for interpolation, whose support grows linearly with d. Combined with our fast MVM algorithm for sparse grid kernel matrices, this interpolation scheme lets us scale SKI to higher dimensions.

In summary, we propose the use of *sparse grids* to improve the scalability of kernel interpolation for GP inference relative to the number of dimensions. To this end, we develop an efficient nearly linear time matrix-vector multiplication algorithm for the sparse grid kernel matrix. Furthermore, we also propose the use of simplicial interpolation to improve scalability of SKI for both dense and sparse grids. We show empirically that these ideas allow SKI to scale to at least 10 dimensions and perform competitively with state-of-the art GP regression methods. We provide an efficient GPU implementation of the proposed algorithm compatible with GPyTorch [9], which is licensed under the MIT license.

2   Background

Notation. We let $\mathbb{N}$ and $\mathbb{N}_0$ denote the natural numbers and $\mathbb{N} \cup \{0\}$ respectively. Matrices are represented by capital letters, and vectors by bold letters. I denotes the identity matrix, with dimensions apparent from context. For a matrix M, $\mathrm{mvm}(M)$ denotes the number of operations required to multiply M by any admissible vector.

In Gaussian process (GP) regression, the training data are modeled as noisy measurements of a random function f drawn from a GP prior, denoted $f \sim \mathcal{N}(0, k(\cdot, \cdot))$, where $k : \mathbb{R}^d \times \mathbb{R}^d \to \mathbb{R}$ is a covariance kernel. For an input $\mathbf{x}_i$, the observed value is modeled as $\mathbf{y}_i = f(\mathbf{x}_i) + \epsilon_i$, with $\epsilon_i \sim \mathcal{N}(0, \sigma^2)$. Observed training pairs $(\mathbf{x}_i, y_i)$ are collected as $X = [\mathbf{x_1}, \dots, \mathbf{x_n}] \in \mathbb{R}^{n \times d}$ and $\mathbf{y} = [y_1, \dots, y_n] \in \mathbb{R}^n$. The kernel matrix (on training data) is $K_X = [k(\mathbf{x}_i, \mathbf{x}_j)]_{i,j=1}^n \in \mathbb{R}^{n \times n}$. The GP inference tasks are to compute the posterior distribution of f given $(X, \mathbf{y})$, which is itself a Gaussian process, and to compute the marginal log-likelihood $\log p(\mathbf{y})$. Naive approaches rely on the Cholesky decomposition of the matrix $\overline{K}_X = K_X + \sigma^2 I$, which takes $\Theta(n^3)$ time; see Rasmussen [20] for more details.

To avoid the $\Theta(n^3)$ running time of naive inference, many modern methods use iterative algorithms such as the conjugate gradient (CG) algorithm to perform GP inference in a way that accesses the kernel matrix only through matrix vector multiplication (MVM), i.e., the mapping $\mathbf{v} \mapsto \overline{K}_X \mathbf{v}$ [9]. These methods support highly accurate approximate solutions to GP posterior inference task as well as hyper-parameter optimization. The complexity of posterior inference and one step of hyper-parameter optimization is $\Theta(pn^2)$ for p CG iterations, as $\mathrm{mvm}(\overline{K}_X) = n^2$. Typically, $p \ll n$ suffices in practice [28, 9].

2.1   SKI: Structured Kernel Interpolation

SKI further accelerates iterative GP inference by approximating the kernel matrix in a way that makes matrix-vector multiplications faster [28]. Given a set of inducing points $U \subset \mathbb{R}^d$, SKI approximates the kernel function as $\tilde{k}(\mathbf{x}, \mathbf{x}') \triangleq \mathbf{w}_\mathbf{x}^T K_U \mathbf{w}_{\mathbf{x}'}$, where $K_U \in \mathbb{R}^{|U| \times |U|}$ is the kernel matrix for the set of inducing points U, and the vector $\mathbf{w_x} \in \mathbb{R}^{|U|}$ contains interpolation weights to interpolate from U to any $\mathbf{x}$. The SKI approximate kernel matrix is $\tilde{K}_X = W K_U W^T$, where $W \in \mathbb{R}^{n \times |U|}$ is the matrix with i^{th} row equal to $\mathbf{w}_{\mathbf{x}_i}$.

To accelerate matrix-vector multiplications with the approximate kernel matrix, SKI places inducing points on a regular grid and uses grid-based interpolation. This leads to a

sparse interpolation weight matrix W—for example, with cubic interpolation there are $O(4^d)$ entries per row, so that $\mathrm{mvm}(W) = O(n4^d)$—and to a kernel matrix K_U that is multi-level Toeplitz (if k is stationary) [28], so that $\mathrm{mvm}(K_U) = O(|U| \log |U|)$. Overall, $\mathrm{mvm}(\tilde{K}_X) = O(n4^d + |U| \log |U|)$, which is much faster than n^2 for small d. However, SKI quickly becomes infeasible in higher dimensions due to the 4^d entries per row of W and curse of dimensionality for the number of points in a high-dimensional grid: specifically, $|U| = m^d$ for a grid with m points in each dimension.

2.2 Sparse Grids

Rectilinear grids. We first give a formal construction of rectilinear grids, which will later be the foundation for sparse grids [7]. For a resolution index $l \in \mathbb{N}_0$, define the 1-d grid Ω_l as the centers of 2^l equal partitions of the interval $[0,1]$, which gives $\Omega_l := \{i/2^{l+1} \mid 1 \leq i \leq 2^{l+1} \text{ and } i \text{ is } \mathbf{odd}\}$. The fact that the position index i must be odd implies that grids for any two different resolutions are *disjoint*.[1] Moreover, resolution-position index pairs (l, i) uniquely specify grid points in the union $\bigcup_{l \in \mathbb{N}_0} \Omega_l$ of 1-d grids.

To extend rectilinear grids to d dimensions, let $\mathbf{l} \in \mathbb{N}_0^d$ denote a resolution vector. The corresponding rectilinear grid is given by $\Omega_{\mathbf{l}} := \otimes_{j=1}^d \Omega_{\mathbf{l}_j}$, where $\otimes$ denotes the Cartesian product. A grid point in $\Omega_{\mathbf{l}}$ is indexed by the pair $(\mathbf{l}, \mathbf{i})$ of a resolution vector $\mathbf{l}$ and *position vector* $\mathbf{i}$, where (l_j, i_j) gives the position in the 1-d grid Ω_j for dimension j. This construction of rectilinear grids yields three essential properties that will facilitate formalizing sparse grids: (1) a grid $\Omega_{\mathbf{l}}$ is uniquely determined by its resolution vector $\mathbf{l}$, (2) grids $\Omega_{\mathbf{l}}$ and $\Omega_{\mathbf{l}'}$ with different resolution vectors are disjoint, (3) the size $|\Omega_{\mathbf{l}}| = 2^{\|\mathbf{l}\|_1}$ of a grid is determined by the L_1 norm of its resolution vector.

Construction of Sparse Grids. Sparse grids use rectilinear grids as their fundamental building block [22] and exploit the fact that resolution vectors uniquely identify different rectilinear grids. Larger grids are formed as the union of rectilinear grids with different resolution vectors. *Sparse* grids use all rectilinear grids with resolution vector having L_1 norm below a specified threshold. Formally, for a resolution index $\ell \in \mathbb{N}_0$, the sparse grid $\mathcal{G}_{\ell,d}$ in d dimensions is $\mathcal{G}_{\ell,d} := \bigcup_{\mathbf{l}:\|\mathbf{l}\|_1 \leq \ell} \Omega_{\mathbf{l}}$.

Figure 1 illustrates the construction of the sparse grid $\mathcal{G}_{2,2}$ from smaller 2-d rectilinear grids with maximum resolution 2, i.e., $\{\Omega_{\mathbf{l}} \mid \|\mathbf{l}\|_1 \leq 2\}$. The figure also illustrates another important fact: the sparse grid $\mathcal{G}_{\ell,d}$ has a total of $\Theta(2^\ell)$ distinct and equally spaced coordinates in each dimension, but many fewer total points than a dense d-fold Cartesian product of such 1-d grids, which would have $\Theta(2^{\ell d})$ points.

Sparse grids have a number of formal properties that are useful in algorithms and applications [22, 7]. Proposition 1 below summarizes the most relevant ones for our work. For completeness, a proof appears in appendix A. For more details, see Valentin [26].

Proposition 1 (Properties of Sparse Grid). *Let $\mathcal{G}_{\ell,d} \subset [0,1]^d$ be a sparse grid with any resolution $\ell \in \mathbb{N}_0$ and dimension $d \in \mathbb{N}$. Then the following properties hold:*

(P1) $|\mathcal{G}_\ell^d| = \mathcal{O}(2^\ell \ell^{d-1})$,

(P2) $\forall \ell' \in \mathbb{N}, 0 \leq \ell' \leq \ell \implies \mathcal{G}_{\ell',d} \subseteq \mathcal{G}_{\ell,d}$,

(P3) $\mathcal{G}_{\ell,d} = \bigcup_{i=0}^\ell (\Omega_i \otimes \mathcal{G}_{\ell-i,d-1})$ and $\mathcal{G}_{\ell,1} = \bigcup_{i=0}^\ell \Omega_i$.

Property P1 shows that the size of sparse grid with $\Theta(2^\ell)$ points in each dimension grows more slowly than a dense grid with the same number of points in each dimension, since $\mathcal{O}(2^\ell \ell^{d-1}) \ll \mathcal{O}(2^{\ell d})$. Properties P2 and P3 are consequences of the structure of the set

---

[1] Suppose $i/2^{l+1} = j/2^{k+1}$ are both grid points and $k > l$. Then $i = j2^{k-l}$ is even, a contradiction.

152 $\{\|\mathbf{l}\|_1 \leq \ell\}$ and the sparse grid construction. Property P2 says that a sparse grid with
153 smaller resolution is contained in one with higher resolution. Property P3 is a crucial
154 property, and says that a d-dimensional sparse grid can be constructed recursively via
155 Cartesian products of 1-dimensional dense grids with sparse grids in $d-1$ dimensions.

3 Structured Kernel Interpolation on Sparse Grids

157 To scale kernel interpolation to higher dimensions, we propose to select inducing points
158 $U = \mathcal{G}_{\ell,d}$ on a sparse grid and approximate the kernel matrix as $W K_{\mathcal{G}_{\ell,d}} W^T$ for a suitable
159 interpolation matrix W adapted to sparse grids. This will require fast matrix-vector
160 multiplications with the sparse grid kernel matrix $K_{\mathcal{G}_{\ell,d}}$ and the interpolation matrix W.
161 We show how to accomplish these two tasks in Sections 3.1 and 3.2.

3.1 Fast Multiplication with the Sparse Grid Kernel Matrix

163 Algorithm 1 is an algorithm to compute $K_{\mathcal{G}_{\ell,d}}\mathbf{v}$ for any vector $\mathbf{v}$. The algorithm uses the
164 following definitions. For any finite set U, let $K_U = \left[k(\mathbf{x},\mathbf{x}')\right]_{\mathbf{x},\mathbf{x}'\in U}$. The rows and columns
165 of K_U are "U-indexed", meaning the entries correspond to elements of U under some
166 arbitrary fixed ordering. For $U \subseteq V$, we introduce a selection matrix $\mathcal{S}_{U,V}$ to map between
167 U-indexed and V-indexed vectors. It has entries $(\mathcal{S}_{U,V})_{ij}$ equal to one if the ith element of
168 U is equal to the jth element of V, and zero otherwise. We also define $\mathcal{S}_{V,U} = \mathcal{S}_{U,V}^T$. For a
169 V-indexed vector $\mathbf{z}_V$, the multiplication $\mathcal{S}_{U,V}\mathbf{z}_V$ produces a U-indexed vector by selecting
170 entries corresponding to elements in U, and for a U-indexed vector $\mathbf{z}_U$, the multiplication
171 $\mathcal{S}_{V,U}\mathbf{z}_U$ produces a V-indexed vector by inserting zeros for elements not in U.

Algorithm 1 Sparse Grid Kernel-MVM Algorithm

Input: $\mathbf{v} \in \mathbb{R}^{|\mathcal{G}_{\ell,d}|}$ and $K_{\mathcal{G}_{\ell,d}} \in \mathbb{R}^{|\mathcal{G}_{\ell,d}| \times |\mathcal{G}_{\ell,d}|}$

Output: $\mathbf{u} = K_{\mathcal{G}_{\ell,d}}\mathbf{v} \in \mathbb{R}^{|\mathcal{G}_{\ell,d}|}$

1: Let V_i be the result of reshaping $\mathcal{S}_{\Omega_i \otimes \mathcal{G}_{\ell-i,d-1}, \mathcal{G}_{\ell,d}}\mathbf{v}$ into a $|\Omega_i| \times |\mathcal{G}_{\ell-i,d-1}|$ matrix;
   this contains entries of $\mathbf{v}$ corresponding to the ith grid in the decomposition of P3.

2: **if** $d = 1$ **then**

3:     return $\mathbf{u} = K_{\mathcal{G}_{\ell,1}}\mathbf{v}$ ▷ Base case

4: **end if**

5: ▷ Pre-computation

6: **for** $i = 0$ to ℓ **do**

7:     $\bar{\mathbf{a}}_i = K_{\mathcal{G}_{i,1}}\mathcal{S}_{\mathcal{G}_{i,1},\Omega_i}V_i$

8:     $\bar{\mathbf{b}}_i = V_i K_{\mathcal{G}_{\ell-i,d-1}}$ ▷ Recurse with $d-1$ dimensions

9: **end for**

10: ▷ Main loop

11: **for** $i = 0$ to ℓ **do**

12:     $A_i = \left(\sum_{j>i}\mathcal{S}_{\Omega_i,\mathcal{G}_{j,1}}\bar{\mathbf{a}}_j \mathcal{S}_{\mathcal{G}_{\ell-j,d-1},\mathcal{G}_{\ell-i,d-1}}\right)K_{\mathcal{G}_{\ell-i,d-1}}$ ▷ Recurse with $d-1$ dimensions

13:     $B_i = \mathcal{S}_{\Omega_i,\mathcal{G}_{i,1}}K_{\mathcal{G}_{i,1}}\left(\sum_{j\leq i}\mathcal{S}_{\mathcal{G}_{i,1},\Omega_j}\bar{\mathbf{b}}_j \mathcal{S}_{\mathcal{G}_{\ell-j,d-1},\mathcal{G}_{\ell-i,d-1}}\right)$

14:     $\mathbf{u}_i = \text{vec}\left[A_i\right] + \text{vec}\left[B_i\right]$

15: **end for**

Theorem 1. *For any $\mathbf{v} \in \mathbb{R}^{|\mathcal{G}_{\ell,d}|}$, Algorithm 1 computes $K_{\mathcal{G}_{\ell,d}}\mathbf{v}$ in $\mathcal{O}(\ell^{d+1}2^\ell)$ time.*

The formal analysis and proof of Theorem 1 appears in Appendix B. The running time of $\mathcal{O}(\ell^{d+1}2^\ell)$ is nearly linear in $|\mathcal{G}_{\ell,d}|$ and much faster asymptotically than the naive MVM algorithm that materializes the full matrix and has running time quadratic in $|\mathcal{G}_{\ell,d}|$.

Algorithm 1 is built on two high-level observations. First, the decomposition of Property P3 from Proposition 1 is used to decompose the MVM into blocks, each of which is between subgrids which are the product of a 1-dimensional rectilinear grid and a sparse grid in $d-1$ dimensions. Therefore, the overall MVM computation can be recursively decomposed into MVMs with sparse grid kernel matrices in $d-1$ dimensions. This observation is in part inspired by Zeiser [29], which also decomposes computation with the matrix on sparse grids by the resolution of first dimension. Second, by Property P2, the kernel matrix multiplication for any grid of resolution ℓ also includes the result of the multiplication for grids of lower resolution and the same number of dimensions. Thus, the results of the multiplications for many individual blocks can be obtained by using the appropriate selection operators with the result of the multiplication with the kernel matrix $K_{\mathcal{G}_{\ell-i,d-1}}$ in Line 12 of the algorithm. Further explanation is provided in Appendix B.1.

Improving batching efficiency. The recursions in Lines 8 and 12 can be batched for efficiency, since both are multiplications with the same symmetric kernel matrix $K_{\mathcal{G}_{\ell,d}}$. Similarly, the recursion spawns many recursive multiplications with kernel matrices of the form $\mathcal{G}_{\ell',d'}$ for $0 \leq \ell' < \ell$ and $1 \leq d' < d$, and the calculation can be reorganized to batch all multiplications with each $K_{\mathcal{G}_{\ell',d'}}$. This is a significant savings, because there are only $d(\ell+1)$ distinct kernel matrices, but the recursion has a branching factor of $(\ell+1)$, so spawns many recursive calls with the same kernel matrices. We provide the pseudocode of this efficient implementation of Algorithm 1 in the Appendix B.1.

3.2 Sparse Interpolation For Sparse Grids

We now seek to construct the matrix W, which interpolates function values from the sparse grid $\mathcal{G}_{\ell,d}$ to training points $\mathbf{x}_i \in \mathbb{R}^d$, while ensuring that each row of W is sparse enough to preserve efficiency of matrix-vector multiplications with W. This requires a sparse interpolation rule for sparse grids.

To set up the problem, we consider interpolating a function f observed at points in a generic set U. Let $\mathbf{f}_U = (f(\mathbf{x}))_{u \in U}$. A linear interpolation rule for U is a mapping $\mathbf{x} \mapsto \mathbf{w_x} \in \mathbb{R}^{|U|}$ used to approximate $f(\mathbf{x})$ at an arbitrary point as $f(\mathbf{x}) \approx \mathbf{w_x}^T \mathbf{f}_U$. The density of an interpolation rule is the maximum number of nonzeros in $\mathbf{w_x}$ for any $\mathbf{x}$.

The *combination technique* for sparse grids constructs an interpolation rule by combining interpolation rules for the constituent rectilinear grids.

Proposition 2. *For each* $\mathbf{l}$, *let* $\mathbf{w_x^l}$ *be an interpolation rule for the rectilinear grid* $\Omega_\mathbf{l}$ *with maximum density* c. *The combination technique gives an interpolation rule* $\mathbf{w_x}$ *for the sparse grid* $\mathcal{G}_{\ell,d}$ *with density at most* $c \times \binom{\ell+d-1}{d-1}$. *The factor* $\binom{\ell+d-1}{d-1}$ *is the number of rectilinear grids included in* $\mathcal{G}_{\ell,d}$.

We use the combination technique to construct the sparse-grid interpolation coefficients $\mathbf{w_{x_i}}$ for each training point $\mathbf{x}_i$ and stack them in the rows of W, which can be done in time proportional to the number of nonzeros. Details are given in Appendix A. The combination technique can use any base interpolation rule for the rectilinear grids, such as multilinear, cubic, or simplicial interpolation.

3.3 Simplicial Interpolation

The density of the base interpolation rule is a critical consideration for kernel interpolation techniques—with or without sparse grids. Linear and cubic interpolation in d dimensions have density $\Theta(2^d)$ and $\Theta(4^d)$, respectively. This "second curse of dimensionality" makes computations with W intractable in higher dimensions independently of operations with the grid kernel matrix. For sparse grids, the density of W increases by an additional factor of $\binom{\ell+d-1}{d-1}$.

221 We propose to use simplicial interpolation [11] for the underlying interpolation rule to avoid
222 exponential growth of the density. Simplicial interpolation refers to a scheme where $\mathbb{R}^d$ is
223 partitioned into simplices and a point **x** is interpolated using only the $d + 1$ extreme points
224 of the enclosing simplex, so the density of the interpolation rule is exactly $d + 1$. Simplicial
225 interpolation was previously proposed for sparse grid classifiers in [8]. In work closely
226 related to ours, Kapoor et al. [13] used simplicial interpolation for GP kernel interpolation,
227 with the key difference that they use the *permutohedral lattice* as the underlying grid,
228 which has a number of nice properties but does not come equipped with fast specialized
229 routines for kernel matrix multiplication. In contrast, we maintain rectilinear and/or sparse
230 underlying grids, which preserve structure that enables fast kernel matrix multiplication.
231 For rectilinear grids, this requires partitioning each hyperrectangle into simplices, so the
232 entire space is partitioned by simplices whose extreme points belong to the rectilinear grid.
233 Then, within each simplex, the values at the extreme points are interpolated linearly. In
234 general, there are different ways to partition hypperrectangles into simplices—we use the
235 specific scheme detailed in [11]. For sparse grids, we then use the combination technique,
236 leading to overall density of $(d + 1)\binom{\ell+d-1}{d-1}$. More details on simplicial interpolation are
237 given in the Appendix B.2.

4   Experiments

239 In this section, we empirically evaluate the time and memory taken by Algorithm 1 for
240 matrix-vector multiplication with the sparse grid kernel matrix, the accuracy of sparse
241 grid interpolation and GP regression as the data dimension d increases, and the accuracy
242 of sparse grid kernel interpolation for GP regression on real higher-dimensional datasets
243 from UCI. Hyper-parameters, data processing steps, and optimization details are given in
244 Appendix C.1.

Figure 2: Matrix-vector multiplication (MVM) resource usage relative to sparse grid size for $d = 6$
and increasing resolution ℓ. From top-left to bottom-right: time for one MVM operation, build (pre-
processing) time for the kernel matrix, peak memory usage, and typical time to solve a linear system
using CG (time for build plus 50 MVMs). Each plot shows the naive quadratic MVM algorithm
(Sparse-MVM), the recursive implementation of Algorithm 1 (Ours-MVM-R), and the efficiently
batched iterative implementation of Algorithm 1 (Ours-MVM-I). All measurements are averaged
over 8 trials; errorbars represent twice the standard error. Figure best viewed with colors.

245 **Sparse grid kernel MVM complexity.**   First, we evaluate the efficiency of MVM algo-
246 rithms. We compare the basic and efficient implementations of Algorithm 1 to the naive
247 algorithm, which constructs the full kernel matrix and scales quadratically with the sparse
248 grid size. Algorithm 1 has a significant theoretical advantage in terms of both time and
249 memory requirements as the grid size grows. Figure 2 illustrates this for $d = 6$ by compar-
250 ing MVM time and memory requirements for sparse grids with resolutions $\ell \in \{2, \ldots, 9\}$
251 (roughly 100 to 1M grid points). The MVM time, preprocessing time, and memory con-
252 sumption of Algorithm 1 all grow more slowly than the naive algorithm, and the efficient
253 implementation of Algorithm 1 is faster for $|\mathcal{G}|$ larger than about 10^4, after which the naive
254 algorithm also exceeds the 10 GB memory limit. For comparison, at $\ell = 6$ (about 40K grid
255 points), Algorithm 1 uses only 0.05 GB of memory. These results indicate that the proposed
256 algorithm is crucial for enabling sparse grid kernel interpolation in higher dimensions.
257 Figure 2 also depicts the typical time to run GP inference (i.e., preprocessing time plus 50
258 MVM operations).

259 **Sparse grid interpolation and GP inference accuracy on synthetic data.**   A significant
260 advantage of sparse grids over dense rectilinear grids is their ability to perform accurate
261 interpolation in higher dimensions. We demonstrate this for $d = 6$ by interpolating
262 the function $f(\mathbf{x}) = \cos(\|\mathbf{x}\|_1)$ from observation locations on sparse grids of increasing
263 resolution onto 200 random points sampled uniformly from $[0, 1]^d$. Figure 3, left, shows the
264 interpolation error for dense and sparse grids with both cubic and simplicial interpolation.
265 *Sparse (cubic)* is significantly more accurate than *Dense (cubic)*, and *Sparse (simplicial)* is more
266 accurate than *Dense (simplicial)*.

267 We next evaluate the accuracy of GP inference in increasing dimensions. We keep the same
268 function $f(\mathbf{x})$ and generate observations as $y = f(\mathbf{x}) + \mathcal{N}(0, 0.05)$. For all d, we use $\ell = 4$
269 for the sparse grid and compare to the dense grid with the closest possible total number of
270 grid points (i.e., $\lceil \mathcal{G}_{4,d}^{1/d} \rceil$ points in each dimension). For $d \geq 8$, performance is better with
271 sparse grids than dense grids for both interpolation schemes. Remarkably, our proposal
272 to use simplicial interpolation with dense grids allows SKI to scale to $d = 10$, which is a
273 significant improvement over prior work, in which SKI is typically infeasible for $d \geq 4$.

Figure 3: Comparing dense and sparse grids with cubic and simplicial interpolation schemes on
synthetic data. Dense (cubic/simplicial) are dense grid methods with cubic/simplicial interpolation
schemes; similarly, sparse (cubic/simplicial) are for sparse grids. Left: Function interpolation error vs.
the grid size for $d = 6$. Right: Test root mean square error (RMSE) for GP regression for increasing
dimensions. For both tasks, sparse grid methods outperform dense grids. For $d = 10$, both methods
with cubic interpolation run out of GPU memory, which is 48 GB for this experiment.

274 **GP regression performance on UCI datasets.**   To evaluate the effectiveness of our pro-
275 posed methods for scaling GP kernel interpolation to higher dimensions, we consider
276 all UCI [4] data sets with dimension $8 \leq d \leq 10$. We compare our proposed methods,
277 Dense-grid (dense SKI with simplicial interpolation) and Sparse-grid (sparse-grid SKI with
278 simplicial interpolation) to SGPR [25], SKIP [10], and Simplex-GP [13]. For SGPR, we
279 report the best results using 256 or 512 inducing points. For SKIP, 100 points per dimension
280 are used. For Simplex-GP [13], the blur stencil order is set to 1. Table 2 shows the root
281 mean squared error (RMSE) for all methods. Our methods have performance comparable
282 to and often better than SGPR and prior methods for scaling kernel interpolation to higher

Table 1: Test root mean square error (RMSE) on UCI regression datasets with dimensions (i.e., $8 \leq d \leq 10$). See text for algorithm descriptions and settings. All mean and standard deviations are computed over 3 trials. Pendulum is abbreviated as *Pendu* to accommodate table horizontally.

Datasets (d)	SGPR	SKIP	Simplex-GP	Dense-grid	Sparse-grid
Energy (8)	1.509 ± 0.003	5.762 ± 0.000	3.076 ± 0.012	1.333 ± 0.009	$\mathbf{0.715} \pm 0.004$
Concrete (8)	12.727 ± 0.018	12.727 ± 0.001	12.727 ± 0.000	12.191 ± 0.001	$\mathbf{8.655} \pm 0.002$
Kin4ok (8)	$\mathbf{0.168} \pm 0.009$	0.174 ± 0.001	0.287 ± 0.003	0.205 ± 0.003	0.483 ± 0.000
Fertility (9)	0.197 ± 0.016	0.183 ± 0.000	0.187 ± 0.001	$\mathbf{0.182} \pm 0.000$	0.194 ± 0.002
Pendu (9)	$\mathbf{1.948} \pm 0.021$	2.947 ± 0.000	2.577 ± 0.009	2.053 ± 0.010	2.103 ± 0.015
Protein (9)	0.605 ± 0.001	0.778 ± 0.000	$\mathbf{0.582} \pm 0.018$	0.736 ± 0.002	0.595 ± 0.001
Solar (10)	0.790 ± 0.026	0.780 ± 0.002	0.792 ± 0.000	0.775 ± 0.002	$\mathbf{0.748} \pm 0.006$

dimensions. This shows that sparse grids and simplicial interpolation can effectively scale SKI to higher dimensions to give a GP regression framework that is competitive with state-of-the-art approaches. We report additional results and analysis in Appendix C.

5 Related Works

Beyond SKI and its variants, a number scalable GP approximations have been investigated. Most notable are the different variants of sparse GP approximations [27, 23, 18]. For m inducing points, these methods require either $\Omega(nm^2)$ time for direct solves or $\Omega(nm)$ time for approximate kernel MVMs in iterative solvers. While these methods generally do not leverage structured matrix algebra like the SKI framework, and thus have worse scaling in terms of the number of inducing points m, they may achieve comparable accuracy with smaller m, especially in higher dimensions. Some work utilizes the SKI framework to further boost the performance of sparse GP approximations [12].

A closely related work to ours is on improving the dimension scaling of SKI through the use of low-rank approximation and product structure [10]. In another very closely related work, Kapoor et al. [13] recently proposed to scale SKI to higher dimensions via interpolation on a permutohedral lattice. Like our work, they use simplicial interpolation. Unlike our work, the kernel matrix on the permutohedral lattice does not have special structure that admits fast exact multiplications; they instead use a locality-based approximation that takes into account the length scale of the kernel function by only considering pairs of grid points within a certain distance. Another related direction of research is the adaptation of sparse grid techniques for machine learning problems, e.g., classification and regression [16] and data mining [1]. These methods construct feature representations using sparse grid points [3], often by selecting a subset of grid points relevant for the dataset [6, 3].

6 Discussion

This work demonstrates that sparse grids and simplicial interpolation on a rectilinear grid, which are both old numerical techniques, can be used to scale GP kernel interpolation to higher dimensions. On several UCI benchmarking datasets with 8 to 10 dimensions, SKI with sparse grids and simplicial interpolation achieves better or competitive regression accuracy compared to state-of-the-art GP regression approaches.

Limitations and future work. Sparse grids and simplicial interpolation address two important bottlenecks when scaling kernel interpolation to higher dimensions. Sparse grids allow scalable matrix-vector multiplications with the grid kernel matrix, and simplicial interpolation allows scalable multiplications with the interpolation matrix W. The relatively large number of rectilinear grids used to form a sparse grid—i.e., the factor of $\binom{\ell+d-1}{d-1}$ in Proposition 2—is one limiting factor that makes multiplication by W more costly for sparse grids. Future research could investigate methods to mitigate this extra cost, and explore the limits of scaling to even higher dimensions with sparse grids.

References

[1] H-J Bungartz, Dirk Pflüger, and Stefan Zimmer. Adaptive sparse grid techniques for data mining. In *Modeling, simulation and optimization of complex processes*, pages 121–130. Springer, 2008.

[2] Hans-Joachim Bungartz and Michael Griebel. Sparse grids. *Acta Numerica*, 13:147–269, 2004.

[3] Tri Dao, Christopher De Sa, and Christopher Ré. Gaussian quadrature for kernel features. In *Advances in Neural Information Processing Systems 30 (NeurIPS)*, page 6109–6119, 2017.

[4] Dheeru Dua and Casey Graff. Uci machine learning repository, 2017. URL http://archive.ics.uci.edu/ml.

[5] A. Dutt, Miao Gu, and Vladimir Rokhlin. Fast algorithms for polynomial interpolation, integration, and differentiation. *SIAM Journal on Numerical Analysis*, 33:1689–1711, 1996.

[6] Jochen Garcke. A dimension adaptive sparse grid combination technique for machine learning. *Anziam Journal*, 48:C725–C740, 2006.

[7] Jochen Garcke. Sparse grids in a nutshell. In *Sparse grids and applications*, pages 57–80. Springer, 2012.

[8] Jochen Garcke and Michael Griebel. Classification with sparse grids using simplicial basis functions. *Intelligent data analysis*, 6(6):483–502, 2002.

[9] Jacob R. Gardner, Geoff Pleiss, David Bindel, Kilian Q. Weinberger, and Andrew Gordon Wilson. GPyTorch: Blackbox matrix-matrix Gaussian process inference with GPU acceleration. In *Advances in Neural Information Processing Systems 31 (NeurIPS)*, pages 7576–7586, 2018.

[10] Jacob R Gardner, Geoff Pleiss, Ruihan Wu, Kilian Q Weinberger, and Andrew Gordon Wilson. Product kernel interpolation for scalable Gaussian processes. *arXiv:1802.08903*, 2018.

[11] John H Halton. Simplicial multivariable linear interpolation. Tehcnical Report 91-002, University of North Carolina at Chapel Hill Department of Computer Science, 1991.

[12] Pavel Izmailov, Alexander Novikov, and Dmitry Kropotov. Scalable gaussian processes with billions of inducing inputs via tensor train decomposition. In *In Proceedings of the 21st International Conference on Artificial Intelligence and Statistics (AISTATS)*, volume 84 of *Proceedings of Machine Learning Research*, pages 726–735. PMLR, 2018.

[13] Sanyam Kapoor, Marc Finzi, Ke Alexander Wang, and Andrew Gordon Gordon Wilson. Skiing on simplices: Kernel interpolation on the permutohedral lattice for scalable gaussian processes. In *Proceedings of the 38th International Conference on Machine Learning (ICML)*, pages 5279–5289, 2021.

[14] Radford M. Neal. *Bayesian Learning for Neural Networks*. Springer-Verlag, 1996.

[15] Michael Obersteiner and Hans-Joachim Bungartz. A generalized spatially adaptive sparse grid combination technique with dimension-wise refinement. *SIAM Journal on Scientific Computing*, 43(4):A2381–A2403, 2021.

[16] Dirk Michael Pflüger. *Spatially adaptive sparse grids for high-dimensional problems*. PhD thesis, Technische Universität München, 2010.

[17] George M Phillips and Peter J Taylor. *Theory and applications of numerical analysis*. Elsevier, 1996.

[18] Joaquin Quiñonero-Candela and Carl Edward Rasmussen. A unifying view of sparse approximate Gaussian process regression. *Journal of Machine Learning Research*, 6(Dec): 1939–1959, 2005.

[19] Ali Rahimi and Benjamin Recht. Random features for large-scale kernel machines. In *Advances in Neural Information Processing Systems 20 (NeurIPS)*, pages 1177–1184, 2007.

[20] Carl Edward Rasmussen. *Gaussian Processes in Machine Learning*. Springer, 2004.

[21] Winfried Sickel and Tino Ullrich. Spline interpolation on sparse grids. *Applicable Analysis*, 90(3-4):337–383, 2011.

[22] Sergei Abramovich Smolyak. Quadrature and interpolation formulas for tensor products of certain classes of functions. In *Doklady Akademii Nauk*, volume 148, pages 1042–1045. Russian Academy of Sciences, 1963.

[23] Edward Snelson and Zoubin Ghahramani. Sparse Gaussian processes using pseudo-inputs. In *Advances in Neural Information Processing Systems 18 (NeurIPS)*, pages 1257–1264, 2005.

[24] Edward Snelson and Zoubin Ghahramani. Sparse Gaussian processes using pseudo-inputs. In *Advances in Neural Information Processing Systems 19 (NeurIPS)*, pages 1257–1264, 2006.

[25] Michalis Titsias. Variational learning of inducing variables in sparse gaussian processes. In *In Proceedings of the 12th International Conference on Artificial Intelligence and Statistics (AISTATS)*, pages 567–574. PMLR, 2009.

[26] Julian Valentin. B-splines for sparse grids: Algorithms and application to higher-dimensional optimization. *arXiv:1910.05379*, 2019.

[27] Christopher KI Williams and Matthias Seeger. Using the Nyström method to speed up kernel machines. In *Advances in Neural Information Processing Systems 14 (NeurIPS)*, pages 682–688, 2001.

[28] Andrew Wilson and Hannes Nickisch. Kernel interpolation for scalable structured Gaussian processes (KISS-GP). In *Proceedings of the 32nd International Conference on Machine Learning (ICML)*, pages 1775–1784, 2015.

[29] Andreas Zeiser. Fast matrix-vector multiplication in the sparse-grid galerkin method. *Journal of Scientific Computing*, 47(3):328–346, 2011.