Reverse-Complement Equivariant Networks for DNA Sequences

Abstract

As DNA sequencing technologies keep improving in scale and cost, there is a growing need to develop machine learning models to analyze DNA sequences, e.g., to decipher regulatory signals from DNA fragments bound by a particular protein of interest. As a double helix made of two complementary strands, a DNA fragment can be sequenced as two equivalent, so-called *reverse complement* (RC) sequences of nucleotides. To take into account this inherent symmetry of the data in machine learning models can facilitate learning. In this sense, several authors have recently proposed particular RC-equivariant convolutional neural networks (CNNs). However, it remains unknown whether other RC-equivariant architectures exist, which could potentially increase the set of basic models adapted to DNA sequences for practitioners. Here, we close this gap by characterizing the set of all linear RC-equivariant layers, and show in particular that new architectures exist beyond the ones already explored. We further discuss RC-equivariant pointwise nonlinearities adapted to different architectures, as well as RC-equivariant embeddings of k-mers as an alternative to one-hot encoding of nucleotides. We show experimentally that the new architectures can outperform existing ones.

1 Introduction

Incorporating prior knowledge about the structure of data in the architecture of neural networks is a promising approach to design expressive models with good generalization properties. In particular, exploiting natural symmetries in the data can lead to models with fewer parameters to estimate than agnostic approaches. This is especially beneficial when the amount of available data is limited. A famous example of such an architecture is the convolutional neural network (CNN) for 1D sequences or 2D images, which is well adapted to problems which are invariant to translations in the data, while exploiting multiscale and local information in the signals. Motivated by the success of CNNs, there has been a fast-growing body of research in recent years to build the theoretical underpinnings and design architectures and efficient algorithms to systematically exploit symmetries and structures in the data [3].

A central idea that has emerged is to formalize the symmetries in data by a particular *group action* (e.g., the group of translations or rotations on images), and to create multilayer neural networks which, by design, "behave well" under the action of the group. This is captured formally by the concept of *equivariance*, which states that each equivariant layer should be designed to be subject to the group action (e.g., we should be able to "translate" or "rotate" the signal in each layer), and that when an input data is transformed by a particular group element, then its representation in an equivariant layer should also be transformed according to the same group element. While it is easy to see that convolutional layers in CNNs are equivariant to translations, Cohen and Welling [7] formalized the concept of group equivariance CNN (G-CNN) for more general groups and showed in particular

how to design convolutional layers equivariant not only to translations but also to reflections and to a discrete set of rotations. Following this seminal work, the theoretical foundations of group equivariant neural networks were then expanded, going beyond regular representations [9], for more groups [2, 17, 36, 39], in less regular spaces [8, 10] or with more general results on their generality and universality [11, 12, 13, 21]. The main applications were developed with the groups of rotations in 2D and 3D, mostly to computer vision problems, but also in biology with histopathology [16, 22], medicine [40] and quantum chemistry [32].

In this paper, we explore and study the potential benefits of equivariant architectures for an important class of data, namely deoxyribonucleic acid (DNA) sequences. DNA is the major form of genetic material in most organisms, from bacteria to mammals, which encodes in particular all proteins that a cell can produce and which is transmitted from generation to generation. The study of DNA in humans and various organisms has led to tremendous progress in biology and medicine since the 1970s, when the first DNA sequencing technologies were invented, and the collapsing cost of sequencing in the last twenty years has accelerated the production of DNA sequences: there are for example about 2.8 billion sequences for a total length of $\sim 10^{13}$ nucleotides publicly available at the European Nucleotide Archive (ENA[1]). Unsurprisingly in such a data-rich field, machine learning-based approaches are increasingly used to analyze DNA sequences, e.g., in metagenomics to automatically predict the species present in an environment from randomly sequenced DNA fragments [25, 27, 35, 37] and to detect the presence of viral DNA in human samples [35], in functional genomics to predict the presence of protein binding sites or other regulatory elements in DNA sequences of interest [15, 23, 29, 34, 42, 43], to predict epigenetic modifications [24], or to predict the effect of variations in the DNA sequence on a phenotype of interest [1, 45].

Due to the sequential nature of DNA and the translation-equivariant nature of the questions addressed, many of these works are based on 1D CNN architectures, although recently transformer-based language models have also shown promising results on various tasks [6, 19, 41]. However, besides translation, DNA has an additional fundamental symmetry that has been largely ignored so far: the so-called reverse complement (RC) symmetry, due to the fact that DNA is made of two strands oriented in opposite direction and encoding complementary nucleotides. In other words, a given DNA segment can be sequenced as two RC DNA sequences, depending on which strand is sequenced; any predictive model for, e.g., DNA sequence classification should therefore be RC-invariant, which calls for RC-equivariant architectures. While strategies based on data augmentation and prediction averaging has been commonly used to handle the need for RC invariance [1, 31], one translation- and RC-equivariant CNN architecture has been proposed and led to promising results [4, 28, 33]. However, it remains unclear whether that architecture is the only one that can encode translation- and RC-equivariance, or if alternative models exist to complement the toolbox of users wishing to develop deep learning models for DNA sequences.

Using the general theory of equivariant representations, in particular steerable CNNs [9], we answer that question by characterizing the set of all linear translation- and RC-equivariant layers. We show in particular that new architectures exist beyond the ones already explored by [4, 28, 33], which in the language of equivariant CNNs only make use of the regular representation [7] while more general representations lead to different layers. We further discuss RC-equivariant pointwise nonlinearities adapted to different representations, as well as RC-equivariant embeddings of k-mers as an alternative to one-hot encoding of nucleotides. We test the new architecture on several protein binding prediction problems, and show experimentally that the new models can outperform existing ones, confirming the potential benefit of exploring the full set of RC-equivariant layers when manipulating DNA sequences with deep neural networks.

2   Methods

2.1   Group action of translation and reverse complementarity on DNA sequence

DNA is a long polymer made of two intertwined strands, forming the well-known double-helical structure. Each strand is a non-symmetric polymer that can be described as an oriented chain of four possible monomers called nucleotides and denoted respectively $\{A, C, G, T\}$. The two strands are oriented in opposite directions, and their nucleotides face each other to form hydrogen bonds.

---

[1]As of May, 2021: https://www.ebi.ac.uk/ena

Figure 1: Illustration of the reverse-complement symmetry. Both DNA strands get sequenced in opposite directions resulting in redundant information.

They interact at each position in a deterministic way because only two nucleotides pairings can happen: (A,T) and (G,C). Thus, given a nucleotide sequence on one strand, we can deduce the so-called RC sequence of its corresponding strand by complementing each nucleotide and reversing the order (**Figure 1**). When a double-stranded DNA fragment is sequenced, the two strands are first separated and, typically, only one of them is randomly selected and is decrypted by the machine. This implies that any given DNA fragment can be equivalently described by two RC sequences of nucleotides. Moreover, several genomic learning tasks amount to a sequence annotation that does not depend on the strand. For example, a protein can bind a double-stranded DNA fragment, and both strands of the bound part can get sequenced. This motivates the search for equivariance to this RC-action for the prediction functions. Moreover, the sequencing often results in long sequences where the relevant parts of the sequence do not correlate with their position. The task of prediction over genomic sequences is thus largely translation equivariant, which explains why the community settled on the use of CNNs to train and predict on arbitrary length segments.

To formalize mathematically the translation and RC operations on DNA sequences, we first encode the raw genetic sequence as a signal function in $F_0 = \left\{ f : \mathbb{Z} \to \{0,1\}^4 \right\}$, as the one hot encoding of the nucleotide content for each integer position. Because of the finite length of this polymer, we assume that beyond a compact support this function takes a constant value of zero. The group $(\mathbb{Z}, +)$ of translations acts naturally on this encoding by $T_u(f)(x) = f(x - u)$, for a translation $u \in \mathbb{Z}$, and the RC operations amounts to the following : $RC(f)(x) = \sigma(-1)[f(-x)]$, where $\sigma(-1)$ is the 4×4 permutation matrix that exchanges complementary bases A/T and C/G (while we denote by $\sigma(1)$ the 4×4 identity matrix). We notice that RC is a linear operation on F_0 that satisfies $RC^2 = I$, and thus that the RC operation is a group representation on F_0 for the group $\mathbb{Z}_2 = \{1, -1\}$ endowed with multiplication.

To jointly consider translations and RC actions, we naturally consider the semi-direct product group $G = \mathbb{Z} \rtimes \mathbb{Z}_2$. Elements $g \in G$ can be written as $g = ts$ with $t \in \mathbb{Z}, s \in \mathbb{Z}_2$ and the group G acts on F_0 by the action π_0 defined by:

$$\forall ts \in G, \quad \forall (f, x) \in F_0 \times \mathbb{Z}, \quad \big(\pi_0(ts)f\big)(x) = \sigma(s)[f(s(x - t))] \,.$$

In other words, π_0 is the representation of G on F_0 induced by the representation σ of RC on $\mathbb{R}^4$ [9].

2.2 Features spaces of equivariant layers

Let us now describe the structure of intermediate layers of a neural network equivariant to translations and RC. Following the theory of steerable CNNs [9], we consider successive representations of the input DNA sequence in the following way:

Definition 1. *Given ρ a representation of $\mathbb{Z}_2$ on $\mathbb{R}^D$ for some $D \in \mathbb{N}^*$, a ρ-feature space is the set of signals $F = \{f : \mathbb{Z} \to \mathbb{R}^D\}$ endowed with the G group action π, known as the representation induced by ρ :*

$$\forall ts \in G, \quad \forall (f, x) \in F \times \mathbb{Z}, \quad \big(\pi(ts)f\big)(x) = \rho(s)[f(s(x - t))] \,. \tag{1}$$

With this definition, we see in particular that the one-hot encoding input layer maps the input DNA sequence to a σ-feature space, and that the dimension (i.e., number of channels in the language of deep learning) and group action of ρ-feature space are fully characterized by the representation ρ. Interestingly, the theory of linear group representations allows us to characterize more precisely *all* such representations:

Theorem 1. *For any representation ρ of $\mathbb{Z}_2$ on $\mathbb{R}^D$, there exist $a, b \in \mathbb{N}$ such that $a + b = D$ and an invertible matrix $P \in GL(\mathbb{R}^D)$ such that*

$$\forall s \in \mathbb{Z}_2, \quad \rho(s) = P\, Diag(I_a, sI_b)P^{-1}\,.$$

In other words, combining Definition 1 and Theorem 1, we see that any ρ-feature space that we will use to build translation- and RC-equivariant layers is fully characterized by a triplet (P, a, b), which we call its *type*, and which characterizes both its dimension $D = a + b$ and the action of the group G by (1). By slight abuse of language, we also refer to (P, a, b) as the type of ρ.

Theorem 1 is a standard result of group theory, which explicits the decomposition of any representation ρ in terms of so-called irreducible representation, or *irreps*. In the case of $\mathbb{Z}_2$, there are exactly two irreps which act on $\mathbb{R}$, namely, $\rho_1(s) = 1$ and $\rho_{-1}(s) = s$. If ρ has type (P, a, b), then it means that it can be decomposed as a times $\rho_1(s)$ and b times $\rho_{-1}(s)$. In the particular case where P is the identity matrix, i.e., when we consider a type (I, a, b), then $\rho(s)$ is a diagonal matrix for any $s \in \mathbb{Z}_2$, and each channel of F is acted upon by a single irrep. In that case, we will call the channels of type "1" (resp. "-1") if they are acted upon by ρ_1 (resp. ρ_{-1}), and we will say that F is an "irrep feature space".

Now, let us introduce another special case. Since $\mathbb{Z}_2$ is finite of cardinality 2, let us consider the *regular representation* ρ_{reg} of $\mathbb{Z}_2$ on $\mathbb{R}^2$ defined by:

$$\rho_{reg}(1) = \begin{pmatrix} 1 & 0 \\ 0 & 1 \end{pmatrix}, \quad \rho_{reg}(-1) = \begin{pmatrix} 0 & 1 \\ 1 & 0 \end{pmatrix}.$$

One can easily check that ρ_{reg} is of type $(P_{reg}, 1, 1)$, where $P_{reg} = \begin{pmatrix} 1 & 1 \\ 1 & -1 \end{pmatrix}$. It corresponds to a ρ-feature space with two channels, where the RC operations flips the two channels (and of course the sequence coordinates).

Let us now consider feature spaces of interest. In the input layer, nucleotides are one-hot encoded in a certain order, let us say $(\texttt{A}, \texttt{T}, \texttt{G}, \texttt{C})$. As stated above, this input space is acted upon by σ, a $2-$cycle that swaps bases $\texttt{A}/\texttt{T}$ and $\texttt{C}/\texttt{G}$. We see that we can rewrite $\sigma = (\rho_{reg} \oplus \rho_{reg}) := (\rho_{reg}^{\oplus 2})$, where $\oplus$ is the bloc-diagonal operation. Because ρ_{reg} is of type $(P_{reg}, 1, 1)$, we can diagonalize σ with $(P_{reg}^{\oplus 2})$ and the diagonal would be alternated +1 and -1 values. Thus, there exists a permutation Π such that σ is of type $(P, 2, 2)$, with $P = \Pi(P_{reg}^{\oplus 2})\Pi^{-1}$

Interestingly, all RC-equivariant layers proposed so far in [4, 28, 33] follow a similar pattern: the channels go by pair, and the RC action amounts to flipping the channel values within a pair and reversing the sequence coordinates. In our formalism, this corresponds to channels of type (P, a, a), where $a \in \mathbb{N}^*$ is the number of pairs of channels, and where up to a permutation of channels the matrix P satisfies $P = \Pi(P_{reg}^{\oplus a})\Pi^{-1}$. Following [33], we will refer to these layers as *Reverse Complement Parameter Sharing* (RCPS) layers below.

This highlights the fact that translation- and RC-equivariant layers explored so far are equivariant according to Definition 1, but that there exists potentially many other equivariant layers, obtained in particular by allowing ρ-feature spaces of types (P, a, b) where $a \neq b$, on the one hand, and where P is not a direct sum of P_{reg}, on the other hand. We investigate such variants below.

2.3 Equivariant linear layers

While Definition 1 characterizes ρ-feature space in terms of structure and group action, an equivariant multilayer neural network is built by stacking ρ-feature spaces on top of each other and connecting them with equivariant layers. Cohen et al. [11, Theorem 2] gives us a general result about such equivariant mappings. Here, we apply this result to our specific data and group, and characterize the class of equivariant linear layers, i.e., the linear functions $\phi : F_n \to F_{n+1}$ that satisfy $\pi_{n+1}\phi = \phi\pi_n$, where π_n and π_{n+1} are respectively the group action on F_n and F_{n+1}.

Theorem 2. *Given two representations ρ_n and ρ_{n+1} of $\mathbb{Z}_2$, of respective types (P_n, a_n, b_n) and $(P_{n+1}, a_{n+1}, b_{n+1})$ with $a_n + b_n = D_n$ and $a_{n+1} + b_{n+1} = D_{n+1}$, and respective ρ_n- and ρ_{n+1}-feature spaces F_n and F_{n+1}, a linear map $\phi : F_n \to F_{n+1}$ is equivariant if and only if it can be written as a convolution:*

$$\forall (f, x) \in F_n \times \mathbb{Z}, \quad \phi(f)(x) = \sum_{y \in \mathbb{Z}} \kappa(y - x)f(y)\,, \tag{2}$$

where the kernel $\kappa : \mathbb{Z} \to \mathbb{R}^{D_{n+1} \times D_n}$ satisfies:

$$\forall x \in \mathbb{Z}, \quad \kappa(-x) = \rho_{n+1}(-1)\kappa(x)\rho_n(-1), \tag{3}$$

or equivalently:

$$\forall x \in \mathbb{Z}, \quad \kappa(x) = P_{n+1} \begin{pmatrix} \alpha(x) & \beta(x) \\ \gamma(x) & \delta(x) \end{pmatrix} P_n^{-1}, \tag{4}$$

where $\alpha : \mathbb{Z} \to \mathbb{R}^{a_{n+1} \times a_n}$ and $\delta : \mathbb{Z} \to \mathbb{R}^{b_{n+1} \times b_n}$ are even, while $\beta : \mathbb{Z} \to \mathbb{R}^{a_{n+1} \times b_n}$ and $\gamma : \mathbb{Z} \to \mathbb{R}^{b_{n+1} \times a_n}$ are odd functions.

As stated in Cohen et al. [11], "Convolution is all you need" to define linear layers which are equivariant to our group. In addition, Theorem 2 characterizes all the convolution kernels that ensure equivariance through the two equivalent constraints (3) and (4).

To illustrate this result, let us consider two RCPS feature spaces F_n and F_{n+1} of respective types $(\Pi_n(P_{reg}^{\oplus a_n})\Pi_n^{-1}, a_n, a_n)$ and $(\Pi_{n+1}(P_{reg}^{\oplus a_{n+1}})\Pi_{n+1}^{-1}, a_{n+1}, a_{n+1})$. Then, the channels in F_n and F_{n+1} go by pair, and if we consider a slice $\tilde{\kappa} : \mathbb{Z} \to \mathbb{R}^{2 \times 2}$ of the convolution kernel κ describing how a pair of channels in F_n maps to a pair of channels in F_{n+1}, (3) gives the constraint:

$$\tilde{\kappa}(-x) := \begin{pmatrix} \tilde{\kappa}_{11}(-x) & \tilde{\kappa}_{12}(-x) \\ \tilde{\kappa}_{21}(-x) & \tilde{\kappa}_{22}(-x) \end{pmatrix} = \begin{pmatrix} 0 & 1 \\ 1 & 0 \end{pmatrix} \tilde{\kappa}(x) \begin{pmatrix} 0 & 1 \\ 1 & 0 \end{pmatrix} = \begin{pmatrix} \tilde{\kappa}_{22}(x) & \tilde{\kappa}_{21}(x) \\ \tilde{\kappa}_{12}(x) & \tilde{\kappa}_{11}(x) \end{pmatrix}.$$

We recover exactly the constraints of the RCPS filters first proposed by [33], proving as a consequence of Theorem 2 that RCPS convolution filters describe exactly *all* equivariant linear mappings between RCPS feature spaces.

Moreover, if we now consider any two feature spaces F_n and F_{n+1} of respective types (P_n, a_n, b_n) and $(P_{n+1}, a_{n+1}, b_{n+1})$, then Equation (4) tells us that up to multiplications by matrices P_{n+1} and P_n^{-1}, the kernel is expressed in terms of even and odd functions, which can be trivially implemented with parameter sharing. For example, to represent the even function α, one just need to parameterize the values of $\alpha(x)$ for $x \geq 0$, and complete the negative values by parameter sharing $\alpha(-x) = \alpha(x)$. Hence, the parameter sharing idea used in RCPS [33] extends to any equivariant linear map.

Instead of using (4) to parameterize equivariant convolution kernels, one may also directly write the constraints (3) for specific representations, and potentially save the need of multiplication by P_{n+1} and P_n^{-1} in (4). This is for example the case in RCPS layers [33], and more generally for channels acted upon by the regular representation; for the sake of completeness, we derive in Appendix A.3 the constraints to go from and to the regular representation or the irreps, and use them in our implementation.

2.4 Equivariant nonlinear layers

Besides equivariant linear layers, a crucial component needed for multilayer neural networks is the possibility to have equivariant nonlinear layers, such as nonlinear pointwise activation functions or batch normalization [18]. In this section, we discuss particular nonlinearities that are adapted to various equivariant layers.

Pointwise activations. Let us begin with pointwise transformations, that encompass most activation functions used in deep learning. Pointwise transformations are formally defined as follows: given a function $\theta : \mathbb{R} \to \mathbb{R}$ and a vector space $V = \mathbb{R}^A$ for some index set A, the pointwise extension of θ to V is the mapping $\bar{\theta}_V : V \to V$ defined by $\bar{\theta}_V(f)(a) = \theta(f(a))$, for any $(f, a) \in V \times A$. For a D-dimensional representation ρ of $\mathbb{Z}_2$ and a ρ-feature space F with G-group action π, we say that a pointwise extension $\bar{\theta}_F : F \to F$ is equivariant if it commutes with π, i.e., $\pi\bar{\theta}_F = \bar{\theta}_F\pi$. By definition of the group action (1), this is equivalent to saying that the pointwise extension $\bar{\theta}_{\mathbb{R}^D}$ of θ to $\mathbb{R}^D$ commutes with ρ. The following theorem gives an exhaustive characterization of a large class of equivariant pointwise extensions for any ρ-feature space:

Theorem 3. *Let ρ be a representation of $\mathbb{Z}_2$ and $\theta : \mathbb{R} \to \mathbb{R}$ be a continuous function with left and right derivatives at 0. Let F be a ρ-layer and $\bar{\theta}_F : F \to F$ be the point-wise extension of θ on this layer. Then $\bar{\theta}_F$ is equivariant if and only if at least one of the following cases holds:*

    1. θ is a linear function.

2. θ is an affine function, and $\rho(-1)\mathbf{1} = \mathbf{1}$.

3. θ is not an affine function, and there exists a permutation matrix Π, integers $a, b, c, d \in \mathbb{N}$, and scalars $(\lambda_1, \ldots, \lambda_a) \in (\mathbb{R}_+^*)^a$, such that ρ decomposes as

$$\Pi^{-1}\rho(-1)\Pi = \bigoplus_{i=1}^{a} \begin{pmatrix} 0 & \lambda_i \\ \lambda_i^{-1} & 0 \end{pmatrix} \oplus \begin{pmatrix} 0 & -1 \\ -1 & 0 \end{pmatrix}^{\oplus b} \oplus (1)^{\oplus c} \oplus (-1)^{\oplus d}. \quad (5)$$

In that case,

- *Either $b = d = 0$ and $\forall i, \lambda_i = 1$ and θ is any function,*
- *Or $b = d = 0$ and $\exists i, \lambda_i \neq 1$ and θ is a leaky ReLu function.*[2]
- *Or $b + d > 0$ and $\forall i, \lambda_i = 1$ and θ is an odd function,*

The first case in Theorem 3 is of little interest, since pointwise linear functions are always equivariant to linear group actions. The second case essentially says that adding a constant to a pointwise linear function is only equivariant for representations ρ such that the sum of all rows of $\rho(-1)$ is equal to 1. This holds for example for the regular representation and the RCPS layers, but not for an irrep feature space of type (I, a, b) with $b > 0$, since in that case, some rows have a single "-1" entry. The most interesting case is the third one, since it describes what pointwise nonlinearities one can apply. The condition (5) on the decomposition of ρ essentially excludes all representations that have more than one nonzero value in at least one row of $\rho(-1)$. Among valid ρ's that decompose as (5), we see that the regular representation (corresponding to the first block in (5) with $\lambda_i = 1$), used in RCPS, stands out as the only that allows *any* nonlinearity, besides of course invariant channels of type "+1" (third block in (5)). Replacing a "1" in the regular representation by a scalar $\lambda_i \neq 1$ (in the first block of (5), with $b = d = 0$) creates a valid representation ρ, however only leaky ReLu pointwise nonlinearities can be applied in that case. Another case of practical interest is the irrep feature space of type (I, c, d) for some $c > 0$ and $d > 0$. By Theorem 3, only odd nonlinearities are allowed in that case, such as the hyperbolic tangent function. Finally, one should keep in mind that other representations, which do not satisfy the conditions listed in Theorem 3, do not allow any equivariant nonlinear pointwise transform; this is for example the case of $\rho(-1) = \begin{pmatrix} 0 & -1/2 \\ -2 & 0 \end{pmatrix}$, which is a valid representation of $\mathbb{Z}_2$ but does neither meet the condition to accept affine activations (case 2), nor to accept nonlinear activations (case 3) because $\rho(-1)$ does not decompose according to (5).

Other activation functions Besides pointwise transformations from a ρ-feature space to itself characterized in Theorem 3, the set of nonlinear equivariant layer is tremendous and the design choices are endless. A first extension is to keep pointwise activation, but to allow different nonlinearities on different channels, e.g., by using any function on the "+1" channels and an odd function on the "-1" channels of an irrep feature space. Another relaxation is to use different input and output representations. While odd functions will not affect the field type, even functions will turn a field of type "-1" into a "+1" type. It is well known that any function decomposes into a sum of an odd and even function. Therefore, given ρ, a representation decomposed as in (5), any point-wise non-linearity can be used in a ρ-feature space by first decomposing it into its odd and even components and applying each component separately for the second and fourth blocks.

Other possibilities exist and include creating new representations by tensorization, which amounts to taking pointwise products between different channels [12, 20, 36]. or using non point-wise activation layers, that act on several coupled dimensions, such as the ones used in [36]. For instance, we could apply the max function to paired channels. These possibilities are discussed in [38]

Batch normalization An equivariant batch normalization was introduced by [33]. It considers a feature map and its reverse complement as two instances, which is easy to do because the reverse complement feature map is already computed when using regular representation. We propose another batch normalization for irrep feature spaces that also gives the result we would have had if the batch contained all the reverse complement of its sequences. For the "+1" dimensions, it amounts to scaling as we would have the same values twice. For the "-1" dimensions, we enforce a zero mean and compute a variance estimate based on this constraint.

---

[2]A leaky ReLu function is $\theta(x) = \alpha_{sign(x)}x$ for some $(\alpha_+, \alpha_-) \in \mathbb{R}^2$.

K-mers. Instead of the standard one-hot encoding of individual nucleotides as input layer, we propose to one-hot encode k-mers for $k \geq 1$, i.e., overlapping blocks of k consecutive nucleotides. This technique is known to improve performance in several tasks [26, 27]. In order to implement it into an equivariant network, we need to know how the group acts on the k-mers space, made of 4^k elements. The simplest idea is to pair the index of the channels of two RC k-mers. Because some k-mers are their own reverse complement, the canonical way to do so is to have a representation that is a blend of "+1" irrep and regular representation. An alternative is to make the regular representation act on the k-mers instead by redundantly encoding these k-mers into paired dimensions. This is the strategy we follow in our implementation, to be more coherent with the usual input group action.

3 Experiments

We assess the performance of various equivariant architectures on a set of three binary prediction and four sequence prediction problems used by Zhou et al. [44] to assess the performance of RCPS networks. The binary classification problems aim to predict if a DNA sequence binds to three transcription factors (TFs), based on genome-wide binarized TF-ChIP-seq data for Max, Ctcf and Spi1 in the GM12878 lymphoblastoid cell-line [33]. The sequence prediction problems aim to predict TF binding at the base-pair resolution, using genome-wide ChIP-nexus profiles of four TFs-Oct4, Sox2, Nanog and Klf4 in mouse embryonic stem cells. For a more detailed explanation of the experimental setup, please refer to Zhou et al. [44]. We report "significant" differences in performance below when the P-value of a Wilcoxon signed rank test is smaller than 0.05.

Models. We build over the work of Zhou et al. [44] for both the binary and the sequence prediction problem. They benchmarked an equivariant RCPS architecture and a corresponding non-equivariant model, which we respectively refer to as "RCPS" and "Standard" models below. In addition, we extend the RCPS architecture with one-hot encoding of k-mers as input layers, which we refer to as "Regular" below. Finally, we add to the comparison a new equivariant network where each RCPS layer is replaced by an (I, a, b) layer with the same number of filters. We also use k-mers and vary the ratio $a/(a + b)$ in this model which we call "Irrep" below.

We combine the regular and "+1" dimensions with *ReLu* activations and the "-1" dimensions with a *tanh* activation.

Hyperparameters search To assess the impact of different hyperparameters (k-mer length for Irrep and Regular, $a/(a + b)$ ratio for Irrep), we measure the performance of each model with each hyperparameter on the three binary classification tasks, repeating each experiment ten times with different random seeds. We assess the performance of each run in terms of Area under the Receiver Operator Characteristic (AuROC), and show in Figure 2 the average performance reached by all runs with a given ratio $a/(a + b) \in \{0, 1/4, 1/2, 3/4, 1\}$ (left) and with a given $k \in \{1, 2, 3, 4\}$ (right). We see a clear asymmetry in the performance as a function of $a/(a+b)$, with poor performance when $a = 0$ and optimal performance for $a = 0.75$, which is significantly better than all other ratios tested except 0.5. This confirms that exploring different irreps may be valuable, and we fix the default value of $a/(a + b)$ for the Irrep model to 0.75 in what follows. As for the k-mer length, we see that $k = 2$ has the best performance, and significantly outperforms all other values of k tested. This confirms that going beyond one-hot encoding of nucleotides in equivariant architectures can be beneficial, and we set $k = 2$ by default for the Irrep and Regular model below.

Binary task. We then compare the performance of the four different models (Standard, RCPS, Regular with $k = 2$ and Irrep with $k = 2$ and $a/(a + b) = 0.75$) on the different binary classification tasks (Figure 3, left). On the overall performance, we see that, as already observed by [33], the RCPS architecture has a strong lead over a non-equivariant model. Interestingly, we also see that the two new architectures we explore, Regular and Irrep, significantly outperform RCPS. Moreover, breaking the results by task, we see that these results are overall consistent for all TF, except for 'Spi1' where RCPS matches the performance of Regular and Irrep. Interestingly, the 'Max' TF was coined a failure case for the equivariant network by [33] because of the relatively poor performance of RCPS, but using other equivariant networks we find it possible to have satisfactory performance. This indicates that enabling optimization over a larger family can indeed result in a boost of performance.

Figure 2: Average AuROC performance across four TFs and 10 random seeds for the Irrep model as a function of $a/(a+b)$ (*left*, also averaged over k values) and for the Irrep and Regular models as a function of k (*right*, also averaged over $a/(a+b)$ values for Irrep).

Since equivariant architectures are meant to be particularly beneficial in the low-data regime [14], we further assess the performance of the four models on the same binary classification problems but with only 1,000 sequences used to train the models, and show the results on Figure 3 (*right*). Overall, the performances are worse than in the full-data regime (Figure 3, *left*), which confirms that this is a regime where more data helps. The relative order of the four different methods remains overall the same, with both Regular and Irrep leading the way and significantly outperforming RCPS, while Standard is clearly worse than all equivariant architectures. Interestingly, the gaps between the best and worse models widens in the low-data regime. For example, there is a large gap of about 2% in performance between the best models (Irrep and Regular, AuROC=0.961) and the Standard model in the low-data regime (AuROC=0.942). Finally, we see that RCPS, which is the best model on Spi1 with the full dataset, is significantly worse than Regular and Irrep on the same TF in the low-data regime, suggesting again that different equivariant architectures may have different strengths and weaknesses in different regimes. We also investigated whether equivariant models converge faster to their solutions, but found not noticeable difference (Appendix A.5)

Profile task. We also compare the four models on the profile prediction tasks, and show in Figure 4 their performance in terms of Spearman correlation between the target profile and the predicted ones. To limit the carbon footprint of this study we only repeated 6 times each experiment with different random seed. As for the binary classification tasks, we assess the performance of each method on the

Figure 3: AuROC performance of the four different models on the three binary classification problems CTCF, MAX and SPI1, as well as their average. Error bars correspond to an estimate of the standard error on 10 repeats with different random seeds. The left plot is the performance on the full datasets, while the right plot shows the performance where models are trained on a subset of 1,000 sequences only (notice the differences of AuROC values on the vertical axis in both plots).

full dataset (Figure 4, *left*) as well as on a smaller experiment with only 1,000 training sequences (Figure 4, *right*).

Figure 4: Spearman Correlation between true and predicted profiles by different methods for four data sets, either trained on the full data sets (*left*) or on reduced data sets (*right*) of only 1,000 sequences.

First of all, we observe as before that in the low-data regime, the gap between standard and equivariant networks grows in favour of equivariant ones. We also observe, surprisingly, Regular and Irrep, which outperformed RCPS and Standard on the binary task, now perform on par with them with a non-significant difference of performance. In particular, since Regular only differs from RCPS by the length of k-mer used ($k = 2$ vs $k = 1$), a possible explanation for disappointing performance of Regular could be that since this task aims to annotate an individual nucleotide, encoding the nucleotide level information using k-mers makes the signal blurry and decreases performance.

Experiment settings and computational cost. All experiments were run on a single GPU (either a GTX1080 or a RTX6000), with 20 CPU cores. The binary classification experiments were shorter to train. To limit our carbon footprint, we chose to run more experiments on this task, e.g., for hyperparameter tuning and to reduce the number of replicates for the profile task. The total runtimes of each of those tasks were approximately of a week.

4 Discussion

In this paper, we addressed the problem of including the RC symmetry prior in neural networks. Leveraging the framework of equivariant networks, in particular steerable CNNs, we deepened existing methods by unraveling the whole space of linear layers and pointwise nonlinearities that are translation and RC-equivariant. We also investigated the links between the linear representations and the non-linear layers of neural networks, exposing the special role of the regular representation in equivariant networks. Finally, we implemented new linear and nonlinear equivariant layers and make all these equivariant layers available in Keras [5] and Pytorch [30]. We then explored empirically how this larger equivariant functional space behaves in terms of learning. Our best results improve the state of the art performance of equivariant networks, showing that new equivariant architectures can have practical benefits.

Other methods exist to make a network equivariant, such as group pooling. Zhou et al. [44] pointed out that despite not including the symmetry prior, such methods can result in better performances than equivariant models on some tasks. If the prior is true and the biological function is indeed equivariant, the best learning algorithm should lie in the space we explore, but Zhou et al. [44] suggest that optimization issues may arise when using constrained kernels. This motivates the exploration of dedicated optimization algorithms for equivariant constrained networks. This work on a small group and these optimization aspects should be of use for other equivariant methods that can also struggle to yield higher performance than group pooling.

References

[1] B. Alipanahi, A. Delong, M. T. Weirauch, and B. J. Frey. Predicting the sequence specificities of DNA-and RNA-binding proteins by deep learning. *Nature biotechnology*, 33(8):831–838, 2015.

[2] B. Anderson, T. S. Hy, and R. Kondor. Cormorant: Covariant molecular neural networks. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019.

[3] M. M. Bronstein, J. Bruna, T. Cohen, and P. Veličković. Geometric deep learning: Grids, groups, graphs, geodesics, and gauges. Technical Report 2104.13478, arXiv, 2021.

[4] R. C. Brown and G. Lunter. An equivariant Bayesian convolutional network predicts recombination hotspots and accurately resolves binding motifs. *Bioinformatics*, 35(13):2177–2184, 2019.

[5] F. Chollet. Keras. https://github.com/fchollet/keras, 2015.

[6] J. Clauwaert and W. Waegeman. Novel transformer networks for improved sequence labeling in genomics. *IEEE/ACM Trans. Comput. Biol. Bioinform.*, 2021.

[7] T. Cohen and M. Welling. Group equivariant convolutional networks. In M. F. Balcan and K. Q. Weinberger, editors, *Proceedings of The 33rd International Conference on Machine Learning*, volume 48 of *Proceedings of Machine Learning Research*, pages 2990–2999, New York, New York, USA, 20–22 Jun 2016. PMLR.

[8] T. Cohen, M. Weiler, B. Kicanaoglu, and M. Welling. Gauge equivariant convolutional networks and the icosahedral CNN. In *International Conference on Machine Learning*, pages 1321–1330. PMLR, 2019.

[9] T. S. Cohen and M. Welling. Steerable CNNs. In *International Conference on Learning Representations (ICLR)*, 2017.

[10] T. S. Cohen, M. Geiger, J. Köhler, and M. Welling. Spherical CNNs. In *Proceedings of the 6th International Conference on Learning Representations (ICLR)*, 2018.

[11] T. S. Cohen, M. Geiger, and M. Weiler. A General Theory of Equivariant CNNs on Homogeneous Spaces. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019.

[12] N. Dym and H. Maron. On the Universality of Rotation Equivariant Point Cloud Networks. *arXiv preprint arXiv:2010.02449*, 2020.

[13] C. Esteves. Theoretical aspects of group equivariant neural networks. *arXiv preprint arXiv:2004.05154*, 2020.

[14] F. Fuchs, D. Worrall, V. Fischer, and M. Welling. SE(3)-Transformers: 3D Roto-Translation Equivariant Attention Networks. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin, editors, *Advances in Neural Information Processing Systems*, volume 33, pages 1970–1981. Curran Associates, Inc., 2020.

[15] M. Ghandi, D. Lee, M. Mohammad-Noori, and M. A. Beer. Enhanced regulatory sequence prediction using gapped k-mer features. *PLoS Comput Biol*, 10(7):e1003711, 2014.

[16] S. Graham, D. Epstein, and N. Rajpoot. Dense steerable filter cnns for exploiting rotational symmetry in histology images. *IEEE Transactions on Medical Imaging*, 39(12):4124–4136, 2020.

[17] E. Hoogeboom, J. W. T. Peters, T. S. Cohen, and M. Welling. Hexaconv. In *6th International Conference on Learning Representations, ICLR 2018, Vancouver, BC, Canada, April 30 - May 3, 2018, Conference Track Proceedings*. OpenReview.net, 2018.

[18] S. Ioffe and C. Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *International conference on machine learning*, pages 448–456. PMLR, 2015.

[19] Y. Ji, Z. Zhou, H. Liu, and R. V. Davuluri. DNABERT: pre-trained bidirectional encoder representations from transformers model for DNA-language in genome. *Bioinformatics*, Feb. 2021.

[20] R. Kondor. N-body networks: a covariant hierarchical neural network architecture for learning atomic potentials. *arXiv preprint arXiv:1803.01588*, 2018.

[21] R. Kondor and S. Trivedi. On the generalization of equivariance and convolution in neural networks to the action of compact groups. In *International Conference on Machine Learning*, pages 2747–2755. PMLR, 2018.

[22] M. W. Lafarge, E. J. Bekkers, J. P. Pluim, R. Duits, and M. Veta. Roto-translation equivariant convolutional networks: Application to histopathology image analysis. *Medical Image Analysis*, 68:101849, 2021.

[23] D. Lee, D. U. Gorkin, M. Baker, B. J. Strober, A. L. Asoni, A. S. McCallion, and M. A. Beer. A method to predict the impact of regulatory variants from DNA sequence. *Nature genetics*, 47 (8):955, 2015.

[24] J. J. Levy, A. J. Titus, C. L. Petersen, Y. Chen, L. A. Salas, and B. C. Christensen. MethylNet: an automated and modular deep learning approach for DNA methylation analysis. *BMC bioinformatics*, 21:108, 2020.

[25] Q. Liang, P. W. Bible, Y. Liu, B. Zou, and L. Wei. DeepMicrobes: taxonomic classification for metagenomics with deep learning. *NAR genom. bioinform.*, 2:lqaa009, Mar. 2020.

[26] W. Liang. Segmenting DNA sequence into words based on statistical language model. *Nature Precedings*, pages 1–1, 2012.

[27] R. Menegaux and J.-P. Vert. Continuous embeddings of DNA sequencing reads and application to metagenomics. *Journal of Computational Biology*, 26(6):509–518, 2019.

[28] K. Onimaru, O. Nishimura, and S. Kuraku. Predicting gene regulatory regions with a convolutional neural network for processing double-strand genome sequence information. *PloS one*, 15 (7):e0235748, 2020.

[29] M. Oubounyt, Z. Louadi, H. Tayara, and K. T. Chong. DeePromoter: Robust promoter predictor using deep learning. *Frontiers in genetics*, 10:286, 2019.

[30] A. Paszke, S. Gross, F. Massa, A. Lerer, J. Bradbury, G. Chanan, T. Killeen, Z. Lin, N. Gimelshein, L. Antiga, A. Desmaison, A. Kopf, E. Yang, Z. DeVito, M. Raison, A. Tejani, S. Chilamkurthy, B. Steiner, L. Fang, J. Bai, and S. Chintala. Pytorch: An imperative style, high-performance deep learning library. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems 32*, pages 8024–8035. Curran Associates, Inc., 2019.

[31] D. Quang and X. Xie. Factornet: a deep learning framework for predicting cell type specific transcription factor binding from nucleotide-resolution sequential data. *Methods*, 166:40–47, 2019.

[32] K. T. Schütt, O. T. Unke, and M. Gastegger. Equivariant message passing for the prediction of tensorial properties and molecular spectra. *arXiv preprint arXiv:2102.03150*, 2021.

[33] A. Shrikumar, P. Greenside, and A. Kundaje. Reverse-complement parameter sharing improves deep learning models for genomics. *bioRxiv*, page 103663, 2017.

[34] G. D. Stormo. DNA binding sites: representation and discovery. *Bioinformatics*, 16(1):16–23, 2000.

[35] A. Tampuu, Z. Bzhalava, J. Dillner, and R. Vicente. ViraMiner: Deep learning on raw DNA sequences for identifying viral genomes in human samples. *PloS one*, 14:e0222271, 2019.

[36] N. Thomas, T. Smidt, S. Kearnes, L. Yang, L. Li, K. Kohlhoff, and P. Riley. Tensor field networks: Rotation-and translation-equivariant neural networks for 3d point clouds. *arXiv preprint arXiv:1802.08219*, 2018.

[37] K. Vervier, P. Mahé, M. Tournoud, J.-B. Veyrieras, and J.-P. Vert. Large-scale machine learning for metagenomics sequence classification. *Bioinformatics*, 32:1023–1032, 2016.

[38] M. Weiler and G. Cesa. General $e(2)$-equivariant steerable cnns. *arXiv preprint arXiv:1911.08251*, 2019.

[39] M. Weiler, M. Geiger, M. Welling, W. Boomsma, and T. S. Cohen. 3d steerable cnns: Learning rotationally equivariant features in volumetric data. In *Advances in Neural Information Processing Systems*, pages 10381–10392, 2018.

[40] M. Winkels and T. S. Cohen. 3d G-CNNs for pulmonary nodule detection. *arXiv preprint arXiv:1804.04656*, 2018.

[41] M. Zaheer, G. Guruganesh, K. A. Dubey, J. Ainslie, C. Alberti, S. Ontañón, P. Pham, A. Ravula, Q. Wang, L. Yang, and A. Ahmed. Big Bird: Transformers for Longer Sequences. In H. Larochelle, M. Ranzato, R. Hadsell, M. Balcan, and H. Lin, editors, *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020.

[42] H. Zeng, M. D. Edwards, G. Liu, and D. K. Gifford. Convolutional neural network architectures for predicting DNA–protein binding. *Bioinformatics*, 32(12):i121–i127, 2016.

[43] H. Zhang, C.-L. Hung, M. Liu, X. Hu, and Y.-Y. Lin. NCNet: Deep learning network models for predicting function of non-coding DNA. *Frontiers in genetics*, 10:432, 2019.

[44] H. Zhou, A. Shrikumar, and A. Kundaje. Towards a better understanding of reverse-complement equivariance for deep learning models in regulatory genomics. *bioRxiv*, 2020.11.04.368803, 2020.

[45] J. Zhou and O. G. Troyanskaya. Predicting effects of noncoding variants with deep learning–based sequence model. *Nature methods*, 12(10):931–934, 2015.