SEED: SELF-SUPERVISED DISTILLATION FOR VISUAL REPRESENTATION

ABSTRACT

This paper is concerned with self-supervised learning for small models. The problem is motivated by our empirical studies that while the widely used contrastive self-supervised learning method has shown great progress on large model training, it does not work well for small models. To address this problem, we propose a new learning paradigm, named **SE**lf-Sup**E**rvised **D**istillation (SEED), where we leverage a larger network (as Teacher) to transfer its representational knowledge into a smaller architecture (as Student) in a self-supervised fashion. Instead of directly learning from unlabeled data, we train a student encoder to mimic the similarity score distribution inferred by a teacher over a set of instances. We show that SEED dramatically boosts the performance of small networks on downstream tasks. Compared with self-supervised baselines, SEED improves the top-1 accuracy from 42.2% to 67.6% on EfficientNet-B0 and from 36.3% to 68.2% on MobileNet-V3-Large on the ImageNet-1k dataset.

1 INTRODUCTION

The burgeoning studies and success on self-supervised learning (*SSL*) for visual representation are mainly marked by its extraordinary potency of learning from unlabeled data at scale. Accompanying with the *SSL* is its phenomenal benefit of obtaining task-agnostic representations while allowing the training to dispense with prohibitively expensive data labeling. Major ramifications of visual *SSL* include pretext tasks (Noroozi & Favaro, 2016; Zhang et al., 2016; Gidaris et al., 2018; Zhang et al., 2019; Feng et al., 2019), contrastive representation learning (Wu et al., 2018; He et al., 2020; Chen et al., 2020a), online/offline clustering (Yang et al., 2016; Caron et al., 2018; Li et al., 2020; Caron et al., 2020; Grill et al., 2020), etc. Among them, several recent works (He et al., 2020; Chen et al., 2020a; Caron et al., 2020) have achieved comparable or even better accuracy than the supervised pre-training when transferring to downstream tasks, *e.g.* semi-supervised classification, object detection.

Figure 1: SEED vs. MoCo-V2 (Chen et al., 2020c)) on ImageNet-1K linear probe accuracy. The vertical axis is the top-1 accuracy and the horizontal axis is the number of learnable parameters for different network architectures. Directly applying self-supervised contrastive learning (MoCo-V2) does not work well for smaller architectures, while our method (SEED) leads to dramatic performance boost. Details of the setting can be found in Section 4.

The aforementioned top-performing *SSL* algorithms all involve large networks (*e.g.*, ResNet-50 (He et al., 2016) or larger), with, however, little attention on small networks. Empirically, we find that existing techniques like contrastive learning do not work well on small networks. For instance, the linear probe top-1 accuracy on ImageNet using MoCo-V2 (Chen et al., 2020c) is only 36.3% with MobileNet-V3-Large (see Figure 1), which is much lower compared with its supervised training accuracy 75.2% (Howard et al., 2019). For EfficientNet-B0, the accuracy is 42.2% compared with its supervised training accuracy 77.1% (Tan & Le, 2019). We conjecture that this is because smaller models with fewer parameters cannot effectively learn instance level discriminative representation with large amount of data.

To address this challenge, we inject knowledge distillation (KD) (Buciluǎ et al., 2006; Hinton et al., 2015) into self-supervised learning and propose self-supervised distillation (dubbed as SEED) as a new learning paradigm. That is, train the larger, and distill to the smaller both in self-supervised manner. Instead of directly conducting self-supervised training on a smaller model, SEED first trains a large model (as the teacher) in a self-supervised way, and then distills the knowledge to the smaller model (as the student). Note that the conventional distillation is for supervised learning, while the distillation here is in the self-supervised setting without any labeled data. Supervised distillation can be formulated as training a student to mimic the probability mass function over classes predicted by a teacher model. In unsupervised knowledge distillation setting, however, the distribution over classes is not directly attainable. Therefore, we propose a simple yet effective self-supervised distillation method. Similar to (He et al., 2020; Wu et al., 2018), we maintain a queue of data samples. Given an instance, we first use the teacher network to obtain its similarity scores with all the data samples in the queue as well as the instance itself. Then the student encoder is trained to mimic the similarity score distribution inferred by the teacher over these data samples.

The simplicity and flexibility that SEED brings are self-evident. 1) It does not require any clustering/prototypical computing procedure to retrieve the pseudo-labels or latent classes. 2) The teacher model can be pre-trained with any advanced *SSL* approach, *e.g.*, MoCo-V2 (Chen et al., 2020c), SimCLR (Chen et al., 2020a), SWAV (Caron et al., 2020). 3) The knowledge can be distilled to any target small networks (either shallower, thinner, or totally different architectures).

To demonstrate the effectiveness, we comprehensively evaluate the learned representations on series of downstream tasks, *e.g.*, fully/semi-supervised classification, object detection, and also assess the transferability to other domains. For example, on ImageNet-1k dataset, SEED improves the linear probe accuracy of EfficientNet-B0 from 42.2% to 67.6% (a gain over 25%), and MobileNet-V3 from 36.3% to 68.2% (a gain over 31%) compared to MoCo-V2 baselines, as shown in Figure 1 and Section 4.

Our contributions can be summarized as follows:

- We are the first to address the problem of self-supervised visual representation learning for small models.

- We propose a self-supervised distillation (SEED) technique to transfer knowledge from a large model to a small model without any labeled data.

- With the proposed distillation technique (SEED), we significantly improve the state-of-the-art *SSL* performance on small models.

- We exhaustively compare a variety of distillation strategies to show the validity of SEED under multiple settings.

2 RELATED WORK

Among the recent literature in self-supervised learning, contrastive based approaches show prominent results on downstream tasks. Majority of the techniques along this direction are stemming from noise-contrastive estimation (Gutmann & Hyvärinen, 2010) where the latent distribution is estimated by contrasting with randomly or artificially generated noises. Oord et al. (2018) first proposed Info-NCE to learn image representations by predicting the future using an auto-regressive model for unsupervised learning. Follow-up works include improving the efficiency (Hénaff et al., 2019), and using multi-view as positive samples (Tian et al., 2019b). As these approaches can only have the access to limited negative instances, Wu et al. (2018) designed a memory-bank to store the previously seen random representations as negative samples, and treat each of them as independent categories (instance discrimination). However, this approach also comes with a deficiency that the previously stored vectors are inconsistent with the recently computed representations during the earlier stage of pre-training. Chen et al. (2020a) mitigate this issue by sampling negative samples from a large batch. Concurrently, He et al. (2020) improve the memory-bank based method and propose to use the momentum updated encoder for the remission of representation inconsistency. Other techniques include Misra & Maaten (2020) that combines the pretext-invariant objective loss with contrastive learning, and Wang & Isola (2020) that decomposes contrastive loss into alignment and uniformity objectiveness.

Knowledge distillation (Hinton et al., 2015) aims to transfer knowledge from a cumbersome model to a smaller one without losing too much generalization power, which is also well investigated in model compression (Buciluǎ et al., 2006). Instead of mimicking the teacher's output logit, attention transfer (Zagoruyko & Komodakis, 2016) formulates knowledge distillation on attention maps. Similarly, works in (Ahn et al., 2019; Yim et al., 2017; Koratana et al., 2019; Huang & Wang, 2017) have utilized different learning objectives including consistency on feature maps, consistency on probability mass function, and maximizing the mutual information. CRD (Tian et al., 2019a), which is derived from CMC (Tian et al., 2019b), optimizes the student network by a similar objective to Oord et al. (2018) using a derived lower bound on mutual information. However, the aforementioned efforts all focus on task-specific distillation (*e.g.*, image classification) during the fine-tuning phase rather than a task-agnostic distillation in the pre-training phase for the representation learning. Several works on natural language pre-training proposed to leverage knowledge distillation for a smaller yet stronger small models. For instances, DistillBert (Sanh et al., 2019), TinyBert (Jiao et al., 2019), and MobileBert (Sun et al., 2020), have used knowledge distillation for model compression and shown their validity on multiple downstream tasks. Similar works also emphasize the value of smaller and faster models for language representation learning by leveraging knowledge distillation (Turc et al., 2019; Sun et al., 2019). These works all demonstrate the effectiveness of knowledge distillation for language representation learning in small models, while are not extended to the pre-training for visual representations. SEED closely relates to the above techniques but aims to facilitate **visual representation learning during pre-training phase for small models**, which as far as we know has not yet been investigated.

3 METHOD

3.1 PRELIMINARY ON KNOWLEDGE DISTILLATION

Knowledge distillation (Hinton et al., 2015; Buciluǎ et al., 2006) is an effective technique to transfer knowledge from a strong teacher network to a target student network. The training task can be generalized as the following formulation:

$$\hat{\theta}_S = \arg\min_{\theta_S} \sum_i^N \mathcal{L}_{\text{sup}}(\mathbf{x}_i, \theta_S, y_i) + \mathcal{L}_{\text{distill}}(\mathbf{x}_i, \theta_S, \theta_T), \tag{1}$$

where $\mathbf{x}_i$ is an image, y_i is the corresponding annotation, θ_S is the parameter set for the student network, and θ_T is the set for the teacher network. The loss $\mathcal{L}_{\text{sup}}$ is the alignment error between the network prediction and the annotation. For example in image classification task (Mishra & Marr, 2017; Shen & Savvides, 2020; Polino et al., 2018; Cho & Hariharan, 2019), it is normally a cross entropy loss. For object detection (Liu et al., 2019; Chen et al., 2017), it includes bounding box regression as well. The loss of $\mathcal{L}_{\text{distill}}$ is the mimic error of the student network towards a pre-trained teacher network. For example in (Hinton et al., 2015), the teacher signal comes from the softmax prediction of multiple large-scale networks and the loss is measured by the *Kullback–Leibler* divergence. In (Romero et al., 2014), the task is to align the intermediate feature map values and to minimize the squared $l2$ distance. The effectiveness has been well demonstrated in the supervised setting with labeled data, but remains unknown for the unsupervised setting, which is our focus.

3.2 SELF-SUPERVISED DISTILLATION FOR VISUAL REPRESENTATION

Different from supervised distillation, SEED aims to transfer knowledge from a large model to a small model without requiring labeled data, so that the learned representations in small model can be used for downstream tasks. Inspired by contrastive *SSL*, we formulate a simple approach for the distillation on the basis of instance similarity distribution over a contrastive instance queue. Similar to He et al. (2020), we maintain an instance queue for storing data samples' encoding output from the teacher. Given a new sample, we compute its similarity scores with all the samples in the queue using both the teacher and the student models. We require that the similarity score distribution computed by the student matches with that computed by the teacher, which is formulated as minimizing the cross entropy between the student and the teacher's similarity score distributions (as illustrated in Figure 2).

Figure 2: Illustration of our self-supervised distillation pipeline. The teacher encoder is pre-trained by *SSL* and kept frozen during the distillation. The student encoder is trained by minimizing the cross entropy of probabilities from teacher & student for an augmented view of an image, computed over a dynamically maintained queue.

Specifically, for a randomly augmented view $\mathbf{x}_i$ of an image, it is first mapped and normalized into feature vector representations $\mathbf{z}_i^T = f_\theta^T(\mathbf{x}_i)/||f_\theta^T(\mathbf{x}_i)||_2$, and $\mathbf{z}_i^S = f_\theta^S(\mathbf{x}_i)/||f_\theta^S(\mathbf{x}_i)||_2$, where $\mathbf{z}_i^T, \mathbf{z}_i^S \in \mathbb{R}^D$, and f_θ^T and f_θ^S denote the teacher and student encoders, respectively. Let $\mathbf{D} = [\mathbf{d}_1...\mathbf{d}_K]$ denote the instance queue where K is the queue length and $\mathbf{d}_j$ is the feature vector obtained from the teacher encoder. Similar to the contrastive learning framework, $\mathbf{D}$ is progressively updated under the "*first-in first-out*" strategy as distillation proceeds. That is, we en-queue the visual features of the current batch inferred by the teacher and de-queue the earliest seen samples at the end of iteration. Note that the maintained samples in queue $\mathbf{D}$ are mostly random and irrelevant to the target instance $\mathbf{x}_i$. Minimizing the cross entropy between the similarity score distribution computed by the student and teacher based on $\mathbf{D}$ softly contrasts $\mathbf{x}_i$ with randomly selected samples, without directly aligning with the teacher encoder. To address this problem, we add the teacher's embedding ($\mathbf{z}_i^T$) into the queue and form $\mathbf{D}^+ = [\mathbf{d}_1...\mathbf{d}_K, \mathbf{d}_{K+1}]$ with $\mathbf{d}_{K+1} = \mathbf{z}_i^T$.

Let $\mathbf{p}^T(\mathbf{x}_i; \theta_T; \mathbf{D}^+)$ denote the similarity score between $\mathbf{x}_i$ and $\mathbf{d}_j$'s ($j = 1, ..., K+1$) computed by the teacher model. $\mathbf{p}^T(\mathbf{x}_i; \theta_T; \mathbf{D}^+)$ is defined as

$$\mathbf{p}^T(\mathbf{x}_i; \theta_T, \mathbf{D}^+) = \left[p_1^T ... p_{K+1}^T \right], \qquad p_j^T = \frac{\exp(\mathbf{z}_i^T \cdot \mathbf{d}_j / \tau^T)}{\sum_{\mathbf{d} \sim \mathbf{D}^+} \exp(\mathbf{z}_i^T \cdot \mathbf{d} / \tau^T)}, \qquad (2)$$

and τ^T is a temperature parameter for the teacher. Note, we use $()^T$ to represent the feature from the teacher network and use $(\cdot)$ to represent the inner product between two features.

Similarly let $\mathbf{p}^S(x_i; \theta_S, \mathbf{D}^+)$ denote the similarity score computed by the student model, which is defined as

$$\mathbf{p}^S(\mathbf{x}_i; \theta_S, \mathbf{D}^+) = \left[p_1^S ... p_{K+1}^S \right], \qquad \text{where } p_j^S = \frac{\exp(\mathbf{z}_i^S \cdot \mathbf{d}_j / \tau^S)}{\sum_{\mathbf{d} \sim \mathbf{D}^+} \exp(\mathbf{z}_i^S \cdot \mathbf{d} / \tau^S)}, \qquad (3)$$

and τ^S is a temperature parameter for the student.

Our self-supervised distillation can be formulated as minimizing the cross entropy between the similarity scores of the teacher, $\mathbf{p}^T(\mathbf{x}_i; \theta_T, \mathbf{D}^+)$, and the student, $\mathbf{p}^S(\mathbf{x}_i; \theta_S, \mathbf{D}^+)$, over all the instances $\mathbf{x}_i$, that is,

$$\hat{\theta}_S = \arg\min_{\theta_S} \sum_i^N -\mathbf{p}^T(\mathbf{x}_i; \theta_T, \mathbf{D}^+) \cdot \log \mathbf{p}^S(\mathbf{x}_i; \theta_S, \mathbf{D}^+)$$

$$= \arg\min_{\theta_S} \sum_i^N \sum_j^{K+1} -\frac{\exp(\mathbf{z}_i^T \cdot \mathbf{d}_j / \tau^T)}{\sum_{\mathbf{d} \sim \mathbf{D}^+} \exp(\mathbf{z}_i^T \cdot \mathbf{d} / \tau^T)} \cdot \log \frac{\exp(\mathbf{z}_i^S \cdot \mathbf{d}_j / \tau^S)}{\sum_{\mathbf{d} \sim \mathbf{D}^+} \exp(\mathbf{z}_i^S \cdot \mathbf{d} / \tau^S)}. \qquad (4)$$

Since the teacher network is pre-trained and frozen, the queued features are consistent during training *w.r.t.* the student network. The higher the value of p_j^T is, the larger weight will be laid on p_j^S. Due to the $l2$ normalization, similarity score between $\mathbf{z}_i^T$ and $\mathbf{d}_{K+1}$ remains constant $\mathbb{1}$ before softmax normalization, which is the largest among p_j^T. Thus, the weight for p_{K+1}^S is the largest and can be adjusted solely by tuning the value of τ^T. By minimizing the loss, the feature of $\mathbf{z}_i^S$ can be aligned with $\mathbf{z}_i^T$ and meanwhile contrasts with other unrelated image features in $\mathbf{D}$. We further discuss the relation of these two goals with our learning objective in Appendix 1.5.

Relations with *Info-NCE* loss. When $\tau^T \to 0$, the softmax function for $\mathbf{p}^T$ smoothly approaches to a one-hot vector, where p_{K+1}^T equals 1 and all others 0. In this extreme case, the loss becomes

$$\mathcal{L}_{NCE} = \sum_i^N -\log \frac{\exp(\mathbf{z}_i^T \cdot \mathbf{z}_i^S/\tau)}{\sum_{\mathbf{d} \sim \mathbf{D}^+} \exp(\mathbf{z}_i^S \cdot \mathbf{d}/\tau)}, \tag{5}$$

which is similar to the widely-used *Info-NCE* loss (Oord et al., 2018) in contrastive-based *SSL* (see discussion in Appendix 1.6).

4 EXPERIMENT

4.1 PRE-TRAINING

Self-Supervised Pre-training of Teacher Network.   By default, we use MoCo-V2 (Chen et al., 2020c) to pre-train the teacher network. Following (Chen et al., 2020a), we use ResNet as the network backbone with different depths/widths and append a multi-layer-perceptron (MLP) layer (two linear layers and one *ReLU* (Nair & Hinton, 2010) activation layer in between) at the end of the encoder after average pooling. The dimension of the last feature dimension is 128. All teacher networks are pre-trained for 200 epochs due to the computational limitation unless explicitly specified. As our distillation is independent with the teacher pre-training algorithm, we also show results with other self-supervised pre-trained models for teacher network, *e.g.*, SWAV (Caron et al., 2020), SimCLR (Chen et al., 2020a).

Self-Supervised Distillation on Student Network.   We choose multiple smaller networks with fewer learnable parameters as the student network: MobileNet-v3-Large (Howard et al., 2017), EfficientNet-B0 (Tan & Le, 2019), and smaller ResNet with fewer layers (ResNet-18, 34). Similar to the pre-training for teacher network, we add one additional MLP layer on the basis of the student network. Our distillation is trained with a standard SGD optimizer with momentum 0.9 and a weight decay parameter of 1e-4 for 200 epochs. The initial learning rate is set as 0.03 and updated by a cosine decay scheduler (Nair & Hinton, 2010) with 5 warm-up epochs and batch size 256. In *Eq.* 4, the teacher temperature is set as $\tau^T = 0.01$ and the student temperature is $\tau^S = 0.2$. The queue size of K is 65,536. In the following subsections and appendix, we also show results with different hyper-parameter values, *e.g.*, for τ^T and K.

4.2 FINE-TUNING AND EVALUATION

In order to validate the effectiveness of self-supervised distillation, we choose to assess the performance of representations of the student encoder on several downstream tasks. We first report its performances of linear evaluation and semi-supervised linear evaluation on the ImageNet ILSVRC-2012 (Deng et al., 2009) dataset. To measure the feature transferability brought by distillation, we also conduct evaluations on other tasks, which include object detection and segmentation on the VOC07 (Everingham et al.) and MS-COCO (Lin et al., 2014) datasets. At the end, we compare the transferability of the features learned by distillation with ordinary self-supervised contrastive learning on the tasks of linear classification on datasets from different domains.

Linear and *K*NN Evaluation on ImageNet.   We conduct the supervised linear classification on ImageNet-1K, which contains $\sim$1.3M images for training, and 50,000 images for validation, spanning 1,000 categories. Following previous works in (He et al., 2020; Chen et al., 2020a), we train a single linear layer classifier on top of the frozen network encoder after self-supervised pre-training/distillation. SGD optimizer is used to train the linear classifier for 100 epochs with weight decay to be 0. The initial learning rate is set as 30 and is then reduced by a factor of 10 at 60 and 80 epochs (similar as in Tian et al. (2019a)). Notably, when training the linear classifier for MobileNet and EfficientNet, we reduce the initial learning rate to 3. The results are reported in terms of Top-1 and Top-5 accuracy. We also perform classification using *K*-Nearest Neighbors (*K*NN) based on the learned 128d vector from the last MLP layer. The sample is classified by taking the most frequent label of its K ($K = 10$) nearest neighbors.

Table 1 shows the results with various teacher networks and student networks. We list the baseline of contrastive self-supervised pre-training using MoCo-V2 (Chen et al., 2020c) in the first row for each student architecture. We can see clearly that smaller networks perform rather worse. For example,

S T	T-1	Eff-b0			Eff-b1			Mob-v3			R-18			R-34		
		K	T-1	T-5	K	T-1	T-5	K	T-1	T-5	K	T-1	T-5	K	T-1	T-5
✗	-	30.0	42.2	68.5	34.4	50.7	74.6	27.5	36.3	62.2	36.7	52.5	77.0	41.5	57.4	81.6
R-50	67.4	46.0	61.3	82.7	46.1	61.4	83.1	44.8	55.2	80.3	43.4	57.6	81.8	45.2	58.5	82.6
Δ		+16.0	+19.1	+14.2	+16.1	+10.7	+8.8	+17.3	+18.9	+18.1	+6.7	+5.1	+4.8	+3.7	+1.1	+1.0
R-101	70.3	50.1	63.0	83.8	50.3	63.4	84.6	48.8	59.9	83.5	48.6	58.9	82.5	50.5	61.6	84.9
Δ		+20.1	+20.8	+15.3	+15.9	+12.7	+10.0	+21.3	+23.6	+21.3	+11.9	+6.4	+5.5	+9.0	+4.2	+3.3
R-152	74.2	50.7	65.3	86.0	52.4	67.3	86.9	49.5	61.4	84.6	49.1	59.5	83.3	51.4	62.7	85.8
Δ		+20.7	+23.1	+17.5	+18.0	+16.6	+12.3	+22.0	+25.1	+22.4	+12.4	+7.0	+6.3	+9.9	+5.3	+4.2
R50×2*	77.3	57.4	67.6	87.4	60.3	68.0	87.6	55.9	68.2	88.2	55.3	63.0	84.9	58.2	65.7	86.8
Δ		+27.4	+25.4	+18.9	+25.9	+17.3	+13.0	+18.9	+31.9	+26.0	+18.6	+10.5	+7.9	+16.7	+8.3	+5.2

Table 1: ImageNet-1k test *accuracy* (%) using *K*NN and linear classification for multiple students and MoCo-v2 pre-trained *deeper* teacher architectures. ✗ denotes MoCo-V2 self-supervised learning baselines before distillation. * indicates using a deeper teacher encoder pre-trained by SWAV, where additional small-patches are also utilized during distillation and trained for 800 epochs. *K* denotes Top-1 accuracy using *K*NN. T-1 and T-5 denote Top-1 and Top-5 accuracy using linear evaluation. First column shows Top-1 Acc. of Teacher network.

Figure 3: ImageNet-1k Top-1 *accuracy* for semi-supervised evaluations using 1% 10% label fractions w/o distillation under different Teachers. MoCo-V2 baseline results are shown when teacher parameters are 0.

MobileNet-V3 can only reach 36.3%. This aligns well with previous conclusions from (Chen et al., 2020a;b) that bigger models are desired to perform better in contrastive-based self-supervised pre-training. We conjecture that this is mainly caused by the inability of smaller network to discriminate instances in a large-scale dataset. The results also clearly demonstrate that the distillation from a larger network helps boosting the performances of small networks, and show obvious improvement. For instance, with MoCo-V2 pre-trained ResNet-152 (for 400 epochs) as the teacher network, the Top-1 accuracy of MobileNet-V3-Large can be significantly improved from 36.3% to 61.4%. Furthermore, we use ResNet-50×2 (provided in Caron et al. (2020)) as the teacher network and adopt the multi-crop trick (see Appendix 1.3 for details). The accuracy can be further improved to 68.2% (last row of Table 1) for MobileNet-V3-Large with 800 epochs of distillation. We note that the gain benefited from distillation becomes more distinct on smaller architectures and we further study the effect of various teacher models in ablations.

Semi-Supervised Evaluation on ImageNet. Following (Oord et al., 2018; Kornblith et al., 2019; Kolesnikov et al., 2019), we evaluate the representation on the semi-supervised task, where a fixed 1% or 10% subsets of ImageNet training data (Chen et al., 2020a) are provided with the annotations. After the self-supervised learning with and without distillation, we also train a classifier on top of the representation. The results are shown in Figure 3, where the baseline without distillation is depicted when teacher parameters are 0. As we can see, the accuracy is also improved remarkably with SEED distillation, and a stronger teacher network with more parameters leads to a better performed student network.

Transferring to Classification. To further study whether the improvement of the learned representations by distillation is confined to ImageNet, we evaluate on additional classification datasets to study the generalization and transferability of the feature representation. We strictly follow the linear evaluation and fine-tuning settings from (Kornblith et al., 2019; Chen et al., 2020a; Grill et al., 2020), that a linear layer is trained on the basis of frozen features. We report Top-1 Accuracy of models before and after distillation from various architectures on CIFAR-10, CIFAR-100 (Krizhevsky et al., 2009), SUN-397 (Xiao et al., 2010) datasets (see Figure 4). More details regarding pre-processing and training can be found in Appendix 1.2. Notably, we observe that our distillation surpasses contrastive self-supervised pre-training consistently on all benchmarks, verifying the effectiveness of SEED.

Figure 4: ImageNet-1k *Accuracy* (%) of student network (EfficientNet-B0 and ResNet-18) transferred to other domains (CIFAR-10, CIFAR-100, SUN-397 datasets) with and without distillation from lager architectures (ResNet-50/101/152).

S	T	VOC Obj. Det.			COCO Obj. Det.			COCO Inst. Segm.		
		AP^{bb}	AP^{bb}_{50}	AP^{bb}_{75}	AP^{bb}	AP^{bb}_{50}	AP^{bb}_{75}	AP^{mk}	AP^{mk}_{50}	AP^{mk}_{75}
	✗	46.1	74.5	48.6	35.0	53.9	37.7	31.0	51.1	33.1
	R-50	46.1(0.0)	74.8(**+0.3**)	49.1(**+0.5**)	35.3(**+0.3**)	54.2(**+0.3**)	37.8(+0.1)	31.1(+0.1)	51.1(0.0)	33.2(+0.1)
R-18	**R-101**	46.8(**+0.7**)	75.8(**+1.3**)	49.3(**+0.7**)	35.3(**+0.3**)	54.3(**+0.4**)	37.9(+0.2)	31.3(**+0.3**)	51.3(+0.2)	33.4(**+0.3**)
	R-152	46.8(**+0.7**)	75.9(**+1.4**)	50.2(**+1.6**)	35.4(**+0.4**)	54.4(**+0.5**)	38.0(**+0.3**)	31.3(**+0.3**)	51.4(**+0.3**)	33.4(**+0.3**)

Table 2: Object detection and instance segmentation results using contrastive self-supervised learning and SEED distillation using ResNet-18 as backbone: bounding-box AP (AP^{bb}) and mask AP (AP^{mk}) evaluated on VOC07-val and COCO testing split. More results on different backbones can be found in the Appendix. Subscript in green represents improvement is larger than 0.3.

This also proves the generalization ability of the learned representations from distillation to a wide range of data domain and different classes.

Transferring to Detection and Segmentation. We conduct two downstream tasks here. The first is Faster R-CNN (Ren et al., 2015) model for object detection trained on VOC-07+12 train+val set and evaluated on VOC-07 test split. The second is Mask R-CNN (He et al., 2017) model for the object detection and instance segmentation on COCO 2017 dataset (Lin et al., 2014). The pre-trained model serves as the initial weight and following He et al. (2020), we fine-tune all the layers of the model. More experiment settings can be found in Appendix 1.2. The results are illustrated in Table 2. As we can see, on VOC, the distilled pre-trained model achieves a large improvement. With ResNet-152 as the teacher network, the Resnet18-based Faster R-CNN model shows +0.7 point improvement on AP, +1.4 improvement on AP_{50} and +1.6 on AP_{75}. On COCO, the improvement is relatively minor and the reason could be that COCO training set has ∼118k training images while VOC has only ∼16.5k training images. A larger training set with more fine-tuning iterations reduces the importance of the initial weights.

4.3 ABLATION STUDY

We now explore the effects of distillation using different Teacher architectures, Teacher Pre-training algorithms, various distillation strategies and hyper-parameters.

Different Teacher Networks. Figure 5 summarizes the accuracy of ResNet-18 and EfficientNet-B0 distilled from wider and deeper ResNet architectures. We see clear performance improvement as depth and width of teacher network increase: compared to ResNet-50, deeper (ResNet-101) and wider (ResNet-50×2) substantially improve the accuracy. However, further architectural enlargement has relatively limited effects, and we suspect the accuracy might be limited by the student network capacity in this case.

Different Teacher Pre-training Algorithms. In Table 3, we show the Top-1 accuracy of ResNet-18 distilled from ResNet-50 with different pre-training algorithms, *i.e.*, MoCo-V1 (He et al., 2020), MoCo-V2 (Chen et al., 2020c), SimCLR (Chen et al., 2020a), and SWAV (Caron et al., 2020)). Notably, the aforementioned methods all unanimously adopt contrastive-based pre-training except SWAV, which is based upon online clustering. We find that our SEED is agnostic to pre-training approaches, making it easy to use any self-supervised models (including clustering-based approach like SWAV) in self-supervised distillation. In addition, we observe that more training epochs for both teacher *SSL* and distillation epochs can bring beneficial gain.

Figure 5: *Accuracy* (%) of student networks (EfficientNet-b0 and ResNet-18) on ImageNet distilled from *wider* MoCo-v2 pre-trained ResNet (ResNet-50/101/152×2).

Teacher	P-E	D-E	T. Top-1	S. Top-1	S. Top-5
✗	✗	✗	✗	52.5	77.0
MoCo	200	200	60.6	52.1	77.0
SimCLR	200	200	65.6	57.5	81.7
MoCo-v2	200	200	67.4	57.6	81.8
	800	200	71.1	60.5	83.5
SWAV	800	100	75.3	61.1	83.8
	800	200	75.3	61.7	84.2
	800	400	75.3	62.0	84.4
SWAV*	800	200	75.3	**62.6**	**84.8**

Table 3: ImageNet-1k *Accuracy* (%) of student network (ResNet-18) distilled from variants of self-supervised ResNet-50. P-E/D-E represent the pre-training and distillation epochs. T./S.-Top represent testing accuracy of Teacher and Student. * represents distillation using additional small patches. First row is the ResNet-18 *SSL* baseline using MoCo-v2 trained for 200 epochs.

Method	Top-1 Acc.	Top-5 Acc.
l2-Distance	55.3	80.3
K-Means	51.0	75.8
Online Clustering	56.4	81.2
Binary Contr. Loss	57.4	81.5
SEED	**57.9**	**82.0**

Table 4: Top-1/5 accuracy of linear classification results on ImageNet using different distillation strategies on ResNet-18 (student) and ResNet-50 (teacher) architectures.

τ^T	ImageNet		CIFAR-10	CIFAR-100
	Top-1	Top-5	Top-1	Top-1
0.3	54.8	80.0	78.7	46.6
0.1	54.9	80.1	83.0	50.1
0.05	56.5	81.3	84.4	56.2
0.01	57.9	82.0	87.5	60.6
1e-3	57.6	81.8	86.9	**60.8**

Table 5: Effect of τ^T for the distillation of ResNet-18 (student), ResNet-50 (teacher) on multiple datasets.

Other Distillation Strategies. We explore several alternative distillation strategies. *l2-Distance*: where the *l2*-distance of teacher student's embeddings are minimized, motivated by (Romero et al., 2014). *K-Means*: we exploit *K*-Means clustering to assign a pseudo-label based on the teacher network's representation. *Online Clustering*: we continuously update the clustering centers during distillation for pseudo-label generation. *Binary Contrastive Loss*: we adopt an Info-NCE alike loss for contrastive distillation (Tian et al., 2019a). We provide details for other strategies in Appendix 1.4. Table 4 shows the results for each method on ResNet-18 (student) distilled from ResNet-50. From the results, the simple *l2*-distance minimizing approach can achieve a decent accuracy, which demonstrates the effectiveness of applying the distillation idea to the self-supervised learning. Meanwhile, our proposed SEED outperforms these alternatives with highest accuracy, which shows the superiority of aligning the student towards the teacher and contrasting with the irrelevant samples.

Other Hyper-Parameters. Table 5 summarizes the distillation performances on multiple datasets using different temperature τ^T. We observe a better performance when decreasing τ^T to 0.01 for ImageNet-1k and CIFAR-10 dataset, and to 1e-3 for CIFAR-100 datasets. When τ is large, the softmax-normalized similarity score of p_j^T between $\mathbf{z}_i^T$ and instance $\mathbf{d}_j$ in the queue $\mathbf{D}^+$ also becomes large, which means the student's feature should be less discrminative with the features of other images to some extent. When τ^T is 0, the teacher model will generate a one-hot vector, which only treats $\mathbf{z}_i^T$ as a positive instance and all others in the queue as negative. Thus, the best τ is a trade-off depending on the data distribution. We further compare effect of different hyper-parameters in Appendix 1.8.

5 CONCLUSIONS

Self-Supervised Learning is acknowledged for its remarkable ability in learning from unlabeled, and large scale data. However, a critical impedance for the *SSL* pre-training on smaller architecture comes from its low capacity of discriminating enormous number of instances. Instead of directly learning from unlabeled data, we proposed SEED as a novel self-supervised learning paradigm, which learns representation by self-supervised distillation from a bigger *SSL* pre-trained model. We show in extensive experiments that SEED effectively addresses the weakness of self-supervised learning for small models and achieves state-of-the-art results on various benchmarks of small architectures.

REFERENCES

Sungsoo Ahn, Shell Xu Hu, Andreas Damianou, Neil D Lawrence, and Zhenwen Dai. Variational information distillation for knowledge transfer. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 9163–9171, 2019.

Cristian Buciluǎ, Rich Caruana, and Alexandru Niculescu-Mizil. Model compression. In *Proceedings of the 12th ACM SIGKDD international conference on Knowledge discovery and data mining*, pp. 535–541, 2006.

Mathilde Caron, Piotr Bojanowski, Armand Joulin, and Matthijs Douze. Deep clustering for unsupervised learning of visual features. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pp. 132–149, 2018.

Mathilde Caron, Ishan Misra, Julien Mairal, Priya Goyal, Piotr Bojanowski, and Armand Joulin. Unsupervised learning of visual features by contrasting cluster assignments. *arXiv preprint arXiv:2006.09882*, 2020.

Guobin Chen, Wongun Choi, Xiang Yu, Tony Han, and Manmohan Chandraker. Learning efficient object detection models with knowledge distillation. In *Advances in Neural Information Processing Systems*, pp. 742–751, 2017.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. *arXiv preprint arXiv:2002.05709*, 2020a.

Ting Chen, Simon Kornblith, Kevin Swersky, Mohammad Norouzi, and Geoffrey Hinton. Big self-supervised models are strong semi-supervised learners. *arXiv preprint arXiv:2006.10029*, 2020b.

Xinlei Chen, Haoqi Fan, Ross Girshick, and Kaiming He. Improved baselines with momentum contrastive learning. *arXiv preprint arXiv:2003.04297*, 2020c.

Jang Hyun Cho and Bharath Hariharan. On the efficacy of knowledge distillation. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 4794–4802, 2019.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pp. 248–255. Ieee, 2009.

M. Everingham, L. Van Gool, C. K. I. Williams, J. Winn, and A. Zisserman. The PASCAL Visual Object Classes Challenge 2007 (VOC2007) Results. http://www.pascal-network.org/challenges/VOC/voc2007/workshop/index.html.

Zeyu Feng, Chang Xu, and Dacheng Tao. Self-supervised representation learning by rotation feature decoupling. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 10364–10374, 2019.

Spyros Gidaris, Praveer Singh, and Nikos Komodakis. Unsupervised representation learning by predicting image rotations. *arXiv preprint arXiv:1803.07728*, 2018.

Jean-Bastien Grill, Florian Strub, Florent Altché, Corentin Tallec, Pierre H Richemond, Elena Buchatskaya, Carl Doersch, Bernardo Avila Pires, Zhaohan Daniel Guo, Mohammad Gheshlaghi Azar, et al. Bootstrap your own latent: A new approach to self-supervised learning. *arXiv preprint arXiv:2006.07733*, 2020.

Michael Gutmann and Aapo Hyvärinen. Noise-contrastive estimation: A new estimation principle for unnormalized statistical models. In *Proceedings of the Thirteenth International Conference on Artificial Intelligence and Statistics*, pp. 297–304, 2010.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Kaiming He, Georgia Gkioxari, Piotr Dollár, and Ross Girshick. Mask r-cnn. In *Proceedings of the IEEE international conference on computer vision*, pp. 2961–2969, 2017.

Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 9729–9738, 2020.

Olivier J Hénaff, Aravind Srinivas, Jeffrey De Fauw, Ali Razavi, Carl Doersch, SM Eslami, and Aaron van den Oord. Data-efficient image recognition with contrastive predictive coding. *arXiv preprint arXiv:1905.09272*, 2019.

Geoffrey Hinton, Oriol Vinyals, and Jeff Dean. Distilling the knowledge in a neural network. *arXiv preprint arXiv:1503.02531*, 2015.

Andrew Howard, Mark Sandler, Grace Chu, Liang-Chieh Chen, Bo Chen, Mingxing Tan, Weijun Wang, Yukun Zhu, Ruoming Pang, Vijay Vasudevan, et al. Searching for mobilenetv3. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 1314–1324, 2019.

Andrew G Howard, Menglong Zhu, Bo Chen, Dmitry Kalenichenko, Weijun Wang, Tobias Weyand, Marco Andreetto, and Hartwig Adam. Mobilenets: Efficient convolutional neural networks for mobile vision applications. *arXiv preprint arXiv:1704.04861*, 2017.

Zehao Huang and Naiyan Wang. Like what you like: Knowledge distill via neuron selectivity transfer. *arXiv preprint arXiv:1707.01219*, 2017.

Xiaoqi Jiao, Yichun Yin, Lifeng Shang, Xin Jiang, Xiao Chen, Linlin Li, Fang Wang, and Qun Liu. Tinybert: Distilling bert for natural language understanding. *arXiv preprint arXiv:1909.10351*, 2019.

Alexander Kolesnikov, Xiaohua Zhai, and Lucas Beyer. Revisiting self-supervised visual representation learning. In *Proceedings of the IEEE conference on Computer Vision and Pattern Recognition*, pp. 1920–1929, 2019.

Animesh Koratana, Daniel Kang, Peter Bailis, and Matei Zaharia. Lit: Learned intermediate representation training for model compression. In *International Conference on Machine Learning*, pp. 3509–3518, 2019.

Simon Kornblith, Jonathon Shlens, and Quoc V Le. Do better imagenet models transfer better? In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 2661–2671, 2019.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Junnan Li, Pan Zhou, Caiming Xiong, Richard Socher, and Steven CH Hoi. Prototypical contrastive learning of unsupervised representations. *arXiv preprint arXiv:2005.04966*, 2020.

Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C Lawrence Zitnick. Microsoft coco: Common objects in context. In *European conference on computer vision*, pp. 740–755. Springer, 2014.

Yifan Liu, Ke Chen, Chris Liu, Zengchang Qin, Zhenbo Luo, and Jingdong Wang. Structured knowledge distillation for semantic segmentation. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 2604–2613, 2019.

Asit Mishra and Debbie Marr. Apprentice: Using knowledge distillation techniques to improve low-precision network accuracy. *arXiv preprint arXiv:1711.05852*, 2017.

Ishan Misra and Laurens van der Maaten. Self-supervised learning of pretext-invariant representations. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 6707–6717, 2020.

Vinod Nair and Geoffrey E Hinton. Rectified linear units improve restricted boltzmann machines. In *ICML*, 2010.

Mehdi Noroozi and Paolo Favaro. Unsupervised learning of visual representations by solving jigsaw puzzles. In *European Conference on Computer Vision*, pp. 69–84. Springer, 2016.

Aaron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*, 2018.

Antonio Polino, Razvan Pascanu, and Dan Alistarh. Model compression via distillation and quantization. *arXiv preprint arXiv:1802.05668*, 2018.

Shaoqing Ren, Kaiming He, Ross Girshick, and Jian Sun. Faster r-cnn: Towards real-time object detection with region proposal networks. In *Advances in neural information processing systems*, pp. 91–99, 2015.

Adriana Romero, Nicolas Ballas, Samira Ebrahimi Kahou, Antoine Chassang, Carlo Gatta, and Yoshua Bengio. Fitnets: Hints for thin deep nets. 2014.

Victor Sanh, Lysandre Debut, Julien Chaumond, and Thomas Wolf. Distilbert, a distilled version of bert: smaller, faster, cheaper and lighter. *arXiv preprint arXiv:1910.01108*, 2019.

Zhiqiang Shen and Marios Savvides. Meal v2: Boosting vanilla resnet-50 to 80%+ top-1 accuracy on imagenet without tricks. *arXiv preprint arXiv:2009.08453*, 2020.

Siqi Sun, Yu Cheng, Zhe Gan, and Jingjing Liu. Patient knowledge distillation for bert model compression. *arXiv preprint arXiv:1908.09355*, 2019.

Zhiqing Sun, Hongkun Yu, Xiaodan Song, Renjie Liu, Yiming Yang, and Denny Zhou. Mobilebert: a compact task-agnostic bert for resource-limited devices. *arXiv preprint arXiv:2004.02984*, 2020.

Mingxing Tan and Quoc V Le. Efficientnet: Rethinking model scaling for convolutional neural networks. *arXiv preprint arXiv:1905.11946*, 2019.

Yonglong Tian, Dilip Krishnan, and Phillip Isola. Contrastive representation distillation. In *International Conference on Learning Representations*, 2019a.

Yonglong Tian, Dilip Krishnan, and Phillip Isola. Contrastive multiview coding. *arXiv preprint arXiv:1906.05849*, 2019b.

Iulia Turc, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Well-read students learn better: On the importance of pre-training compact models. *arXiv preprint arXiv:1908.08962*, 2019.

Tongzhou Wang and Phillip Isola. Understanding contrastive representation learning through alignment and uniformity on the hypersphere. *arXiv preprint arXiv:2005.10242*, 2020.

Zhirong Wu, Yuanjun Xiong, Stella X Yu, and Dahua Lin. Unsupervised feature learning via nonparametric instance discrimination. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 3733–3742, 2018.

Jianxiong Xiao, James Hays, Krista A Ehinger, Aude Oliva, and Antonio Torralba. Sun database: Large-scale scene recognition from abbey to zoo. In *2010 IEEE computer society conference on computer vision and pattern recognition*, pp. 3485–3492. IEEE, 2010.

Jianwei Yang, Devi Parikh, and Dhruv Batra. Joint unsupervised learning of deep representations and image clusters. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 5147–5156, 2016.

Junho Yim, Donggyu Joo, Jihoon Bae, and Junmo Kim. A gift from knowledge distillation: Fast optimization, network minimization and transfer learning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 4133–4141, 2017.

Sergey Zagoruyko and Nikos Komodakis. Paying more attention to attention: Improving the performance of convolutional neural networks via attention transfer. *arXiv preprint arXiv:1612.03928*, 2016.

Liheng Zhang, Guo-Jun Qi, Liqiang Wang, and Jiebo Luo. Aet vs. aed: Unsupervised representation learning by auto-encoding transformations rather than data. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 2547–2555, 2019.

Richard Zhang, Phillip Isola, and Alexei A Efros. Colorful image colorization. In *European conference on computer vision*, pp. 649–666. Springer, 2016.