MULTI-CLASS UNCERTAINTY CALIBRATION VIA MUTUAL INFORMATION MAXIMIZATION-BASED BINNING

ABSTRACT

Post-hoc calibration is a common approach for providing high-quality confidence estimates of deep neural network predictions. Recent work has shown that widely used scaling methods underestimate their calibration error, while alternative Histogram Binning (HB) methods often fail to preserve classification accuracy. In the case of multi-class calibration with a large number of classes K, HB also faces the issue of severe sample-inefficiency due to a large class imbalance resulting from the conversion into K one-vs-rest class-wise calibration problems. The goal of this paper is to resolve the identified issues of HB in order to provide calibrated confidence estimates using only a small holdout calibration dataset for bin optimization while preserving multi-class ranking accuracy. From an information-theoretic perspective, we derive the *I-Max* concept for binning, which maximizes the mutual information between labels and quantized logits. This concept mitigates potential loss in ranking performance due to lossy quantization, and by disentangling the optimization of bin edges and representatives allows simultaneous improvement of ranking and calibration performance. To improve the sample efficiency and estimates from a small calibration set, we propose a *shared class-wise* (sCW) strategy that fits a single calibrator on the merged training sets of all K class-wise problems. The combination of sCW and I-Max binning outperforms the state of the art calibration methods on various evaluation metrics across different benchmark datasets and models, using a small calibration set (e.g. 1k samples for ImageNet).

1 INTRODUCTION

Despite great ability in learning discriminative features, deep neural network (DNN) classifiers often make over-confident predictions. This can lead to potentially catastrophic consequences in safety critical applications, e.g., medical diagnosis and perception tasks in autonomous driving. A multi-class classifier is perfectly calibrated if among the cases receiving the prediction distribution $\mathbf{q}$, the ground truth class distribution is also $\mathbf{q}$. The mismatch between the prediction and ground truth distribution can be measured through the Expected Calibration Error (ECE) (Guo et al., 2017).

Since the pioneering work of (Guo et al., 2017), scaling methods have been widely acknowledged as an efficient post-hoc calibration solution for modern DNNs. The common practice of evaluating their ECE resorts to histogram density estimation (HDE) for modeling the distribution of the predictions. However, Vaicenavicius et al. (2019) proved that with a fixed number of evaluation bins the ECE of scaling methods is underestimated even with an infinite number of samples. Widmann et al. (2019); Kumar et al. (2019); Wenger et al. (2020) also empirically showed this underestimation phenomena. This deems scaling methods as unreliable calibration solutions, as their true ECEs can be larger than evaluated, putting many applications at risk. Additionally, setting HDE also faces the bias/variance trade-off. Increasing its number of evaluation bins reduces the bias, as the evaluation quantization error is smaller, however, the estimation of the ground truth correctness begins to suffer from high variance. Fig. 1-a) shows that the empirical ECE estimates of both the raw network outputs and the temperature scaling method (TS) (Guo et al., 2017) are sensitive to the number of evaluation bins. It remains unclear how to optimally choose the number of evaluation bins so as to minimize the estimation error. Recent work (Zhang et al., 2020; Widmann et al., 2019) suggested kernel density estimation (KDE) instead of HDE. However, the choice of the kernel and bandwidth also remains unclear, and the smoothness of the ground truth distribution is hard to verify in practice.

(a) Top-1 prediction ECE (5k evaluation samples)   (b) ECE converging curve (based on 10^2 bootstraps)

Figure 1: (a) Temperature scaling (TS), equally sized-histogram binning (HB), and our proposal, i.e., sCW I-Max binning are compared for post-hoc calibrating a CIFAR100 (WRN) classifier. (b) Binning offers a reliable ECE measure as the number of evaluation samples increases.

An alternative technique for post-hoc calibration is Histogram Binning (HB) Guo et al. (2017). Note, here HB serves as a calibration method and is different to the HDE used for evaluating ECEs of scaling methods. HB produces discrete predictions, whose probability mass functions can be empirically estimated without using HDE/KDE. Therefore, its ECE estimate is constant and unaffected by the number of evaluation bins in Fig. 1-a) and it can converge to the true value with increasing evaluation samples (Vaicenavicius et al., 2019), see Fig. 1-b).

The most common variants of HB are Equal (Eq.) size (uniformly partitioning the probability interval $[0, 1]$), and Eq. mass (uniformly distributing samples over bins) binning. These simple methods for multi-class calibration are known to degrade accuracy, since quantization through binning may remove a considerable amount of label information contained by the classifier's outputs.

In this work we show that the key for HB to retain the accuracy of trained classifiers is choosing bin edges that minimize the amount of label information loss. Both Eq. size and mass binning are suboptimal. We present *I-Max*, a novel iterative method for optimizing bin edges with proved convergence. As the location of its bin edges inherently ensures sufficient calibration samples per bin, the bin representatives of I-Max can then be effectively optimized for calibration. Two design objectives, calibration and accuracy, are thus nicely disentangled under I-Max. For multi-class calibration, I-Max adopts the one-vs-rest (OvR) strategy to individually calibrate the prediction probability of each class. To cope with a limited number of calibration samples, we propose to fit one binning scheme for all per-class calibrations, which we call shared class-wise (sCW) I-Max binning. For large number of classes, sCW greatly improves the sample efficiency.

I-Max is evaluated according to multiple performance metrics, including accuracy, ECE, Brier and NLL, and compared against benchmark calibration methods across multiple datasets and trained classifiers. For ImageNet, I-Max obtains up to 66.11% reduction in ECE compared to the baseline and up to 38.14% reduction compared to the state-of-the-art GP-scaling method (Wenger et al., 2020).

2   RELATED WORK

For confidence calibration, Bayesian DNNs, e.g. (Blundell et al., 2015) and their approximations (Gal & Ghahramani, 2016) are resource-demanding methods to consider predictive model uncertainty. However, applications with limited complexity overhead and latency require sampling-free and single-model based calibration methods. Examples include modifying the training loss (Kumar et al., 2018), scalable Gaussian processes (Milios et al., 2018), sampling-free uncertainty estimation (Postels et al., 2019), data augmentation (Patel et al., 2019; Thulasidasan et al., 2019; Yun et al., 2019; Hendrycks et al., 2020) and ensemble distribution distillation (Malinin et al., 2020). In comparison, a simple approach that requires no retraining of the models is post-hoc calibration (Guo et al., 2017).

Prediction probabilities (logits) scaling and binning are the two main solutions for post-hoc calibration. Scaling methods use parametric or non-parametric models to adjust the raw logits. Guo et al. (2017) investigated linear models, ranging from the single-parameter based TS to more complicated vector/matrix scaling. To avoid overfitting, Kull et al. (2019) suggested to regularize matrix scaling with a L_2 loss on the model weights. Recently, Wenger et al. (2020) adopted a latent Gaussian process for multi-class calibration. Ji et al. (2019) extended TS to a bin-wise setting, by learning separate temperatures for various confidence subsets. To improve the expressive capacity of TS, an

ensemble of temperatures were adopted by Zhang et al. (2020). Owing to continuous outputs of scaling methods, one critical issue discovered in the recent work is: Their empirical ECE estimate is not only non-verifiable (Kumar et al., 2019), but also asymptotically smaller than the ground truth (Vaicenavicius et al., 2019). Recent work (Zhang et al., 2020; Widmann et al., 2019) exploited KDEs for an improved ECE evaluation, however, the parameter setting requires further investigation. Nixon et al. (2019) discussed potential issues of the ECE metric, and suggested to 1) use equal mass binning for ECE evaluation; 2) measure both top-1 and class-wise ECE to evaluate multi-class calibrators, 3) only include predictions with a confidence above some epsilon in the class-wise ECE score.

As an alternative to scaling, HB quantizes the raw confidences with either Eq. size or Eq. mass bins (Zadrozny & Elkan, 2001). It offers asymptotically convergent ECE estimation (Vaicenavicius et al., 2019), but is less sample efficient than scaling methods and also suffers from accuracy loss (Guo et al., 2017). Kumar et al. (2019) proposed to perform scaling before binning for an improved sample efficiency. Isotonic regression (Zadrozny & Elkan, 2002) and Bayesian binning into quantiles (BBQ) (Naeini et al., 2015) are often viewed as binning methods. However, their ECE estimates face the same issue as scaling methods: though isotonic regression fits a piecewise linear function, its predictions are continuous as they are interpolated for unseen data. BBQ considers multiple binning schemes with different numbers of bins, and combines them using a continuous Bayesian score, resulting in continuous predictions.

In this work, we improve the current HB design by casting bin optimization into a MI maximization problem. Furthermore, our findings can also be used to improve scaling methods.

3 METHOD

Here we introduce the I-Max binning scheme, which addresses the issues of HB in terms of preserving label-information in multi-class calibration. After the problem setup in Sec. 3.1, Sec. 3.2) presents a sample-efficient technique for one-vs-rest calibration. In Sec. 3.3 we formulate the training objective of binning as MI maximization and derive a simple algorithm for I-Max binning.

3.1 PROBLEM SETUP

We address supervised multi-class classification tasks, where each input $\mathbf{x} \in \mathcal{X}$ belongs to one of K classes, and the ground truth labels are one-hot encoded, i.e., $\mathbf{y} = [y_1, y_2, \ldots, y_K] \in \{0, 1\}^K$. Let $f : \mathcal{X} \mapsto [0, 1]^K$ be a DNN trained using cross-entropy loss. It maps each $\mathbf{x}$ onto a probability vector $\mathbf{q} = [q_1, \ldots, q_K] \in [0, 1]^K$, which is used to rank the K possible classes of the current instance, e.g., $\arg\max_k q_k$ being the top-1 ranked class. As the trained classifier tends to overfit to the cross-entropy loss rather than the accuracy (i.e., $0/1$ loss), $\mathbf{q}$ as the prediction distribution is typically poorly calibrated. A post-hoc calibrator h to revise $\mathbf{q}$ can deliver an improved performance. To evaluate the calibration performance of $h \circ f$, class-wise ECE averaged over the K classes is a common metric, measuring the expected deviation of the predicted per-class confidence after calibration, i.e., $h_k(\mathbf{q})$, from the ground truth probability $p(y_k = 1|h(\mathbf{q}))$:

$$_{\mathrm{cw}}\mathrm{ECE}(h \circ f) = \frac{1}{K} \sum_{k=1}^{K} E_{\mathbf{q}=f(\mathbf{x})} \left\{ \left| p(y_k = 1|h(\mathbf{q})) - h_k(\mathbf{q}) \right| \right\}. \tag{1}$$

When h is a binning scheme, $h_k(\mathbf{q})$ is discrete and thus repetitive. We can then empirically set $p(y_k = 1|h(\mathbf{q}))$ as the frequency of label-1 samples among those receiving the same $h_k(\mathbf{q})$. On the contrary, scaling methods are continuous. It is unlikely that two samples attain the same $h_k(\mathbf{q})$, thus requiring additional quantization, i.e., applying HDE for modeling the distribution of $h_k(\mathbf{q})$, or alternatively using KDE. It is noted that ideally we should compare the whole distribution $h(\mathbf{q})$ with the ground truth $p(\mathbf{y}|h(\mathbf{q}))$. However, neither HDE nor KDE scales well with the number of classes. Therefore, the multi-class ECE evaluation often boils down to the one-dimensional class-wise ECE as in (1) or the top-1 ECE, i.e., $E\left[|p(y_{k=\arg\max_k h_k(\mathbf{q})} = 1|h(\mathbf{q})) - \max_k h_k(\mathbf{q})| \right]$.

3.2 ONE-VS-REST (OVR) STRATEGY FOR MULTI-CLASS CALIBRATION

Histogram binning (HB) was initially developed for two-class calibration. When dealing with multi-class calibration, it separately calibrates each class in a *one-vs-rest* (OvR) fashion: For any class-k we

use y_k as the binary label for a two-class calibration task, in which the class-1 means $y_k = 1$ and class-0 collects all other $K - 1$ classes. HB then revises q_k by mapping its logit $\lambda_k \triangleq \log q_k - \log(1 - q_k)$ onto a given number of bins, and reproducing them with the empirical frequency of class-1 samples in each bin. The empirical frequencies are estimated from the class-k training set $S_k = \{(y_k, \lambda_k)\}$. We choose to bin the logit λ_k instead of q_k, as the former is unbounded, i.e., $\lambda_k \in \mathbb{R}$, which eases the bin edge optimization process. Nevertheless, as q_k and λ_k have monotonic bijective relation, binning q_k and λ_k are equivalent. It is further noted that after K class-wise calibrations we do not perform the extra normalization step as in (Guo et al., 2017). After OvR marginalizes the multi-class predictive distribution, each class shall then be treated independently (see Sec. A1).

Training HBs over the sets $S_1, \dots, S_K$, the two-class ratio in them is $1 : (K - 1)$, so when K is large we will need a large calibration set $C = \{(\mathbf{y}, \mathbf{x})\}$ to collect enough class-1 samples in S_k. For ImageNet with 1k classes, S_k constructed from the calibration set of size 10k contains only $10k/K = 10$ class-1 samples. To address this, we propose to merge $\{S_k\}$ across K classes, i.e., $S = \cup_k S_k = \{(y, \lambda)\}$; and then use S for HB training, yielding one binning scheme shareable to all two-class calibration tasks, i.e., *shared* class-wise (sCW) binning instead of CW binning respectively trained on S_k. Both S_k and S serve as empirical approximations to the inaccessible ground truth distribution $p(y_k, \lambda_k)$ for bin optimization. The former suffers from high variances, arising from insufficient samples (Fig. A1-a), while the latter is biased due to having samples drawn from the other classes (Fig. A1-b). As the calibration set size is usually small, the variance is expected to outweigh the approximation error over the bias (see an empirical analysis in Sec. A2).

3.3   Bin Optimization via Mutual Information (MI) Maximization

Binning can be viewed as a quantizer Q that maps the real-valued logit $\lambda \in \mathbb{R}$ to the bin interval $m \in \{1, \dots, M\}$ if $\lambda \in \mathcal{I}_m = [g_{m-1}, g_m)$, where M is the total number of bin intervals, and the bin edges g_m are sorted ($g_{m-1} < g_m$, and $g_0 = -\infty, g_M = \infty$). Any logit binned to $\mathcal{I}_m$ will be reproduced to the same bin representative r_m. In the context of calibration, the bin representative r_m assigned to the logit λ_k is used as the calibrated prediction probability of the class-k. As multiple classes can be assigned with the same bin representative, we will then encounter ties when making top-k predictions based on calibrated probabilities. Therefore, binning as lossy quantization generally does not preserve the raw logit-based ranking performance, being subject to potential accuracy loss.

Unfortunately, increasing M to reduce the quantization error is not a good solution here. For a given calibration set, the number of samples per bin generally reduces as M increases, and a reliable frequency estimation for setting the bin representatives $\{r_m\}$ demands sufficient samples per bin.

Considering that the top-k accuracy reflects how well the ground truth label can be recovered from the logits, we propose bin optimization via maximizing the MI between the quantized logits $Q(\lambda)$ and the label y

$$\{g_m^*\} = \arg \max_{Q:\{g_m\}} I(y; m = Q(\lambda)) \overset{(a)}{=} \arg \max_{Q:\{g_m\}} H(m) - H(m|y) \tag{2}$$

where the index m is viewed as a discrete random variable with $P(m|y) = \int_{g_{m-1}}^{g_m} p(\lambda|y) \mathrm{d}\lambda$ and $P(m) = \int_{g_{m-1}}^{g_m} p(\lambda) \mathrm{d}\lambda$, and the equality (a) is based the relation of MI to the entropy $H(m)$ and conditional entropy $H(m|y)$ of m. Such a formulation offers a quantizer Q^* optimal at preserving the label information for a given budget on the number of bins. Unlike designing distortion-based quantizers, the reproducer values of raw logits, i.e., the bin representatives $\{r_m\}$, are not a part of the optimization space, as it is sufficient to know the mapped bin index m of each logit. Once the bin edges $\{g_m^*\}$ are obtained, the bin representative r_m to achieve zero calibration error shall equal $P(y = 1|m)$, which can be empirically estimated from the samples within the bin interval $\mathcal{I}_m$.

It is interesting to analyze the objective function after the equality (a) in (2). The first term $H(m)$ is maximized if $P(m)$ is uniform, which is attained by Eq. mass binning. A uniform sample distribution over the bins is a sample-efficient strategy to optimize the bin representatives for the sake of calibration. However, it does not consider any label information, and thus can suffer from severe accuracy loss. Through MI maximization, we can view I-Max as revising Eq. mass by incorporating the label information into the optimization objective, i.e., having the second term $H(m|y)$. As a result, I-Max not only enjoys a well balanced sample distribution for calibration, but also maximally preserved label information for accuracy.

Figure 2: Histogram and KDE of CIFAR100 (WRN) logits in S constructed from 1k calibration samples. The bin edges of Eq. mass binning are located at the high mass region, mainly covering class-0 due to the imbalanced two class ratio $1:99$. Both Eq. size and I-Max binning cover the high uncertainty region, but here only I-Max yields reasonable bin widths ensuring enough mass per bin. Note, Eq. size binning uniformly partitions the interval $[0,1]$ in the probability domain. The observed dense and symmetric bin location around zero is the outcome of probability-to-logit translation.

In the example of Fig. 2, the bin edges of I-Max binning are densely located in an area where the uncertainty of y given the logit is high. This uncertainty results from small gaps between the top class predictions. With small bin widths, such nearby prediction logits are more likely located to different bins, and thus distinguishable after binning. On the other hand, Eq. mass binning has a single bin stretching across this high-uncertainty area due to the class imbalance. Eq. size binning follows a pattern closer to I-Max binning. However, its very narrow bin widths around zero may introduce large empirical frequency estimation errors when setting the bin representatives.

For solving the problem (2), we formulate an equivalent problem.

Theorem 1. *The MI maximization problem given in (2) is equivalent to*

$$\max_{Q:\{g_m\}} I(y; m = Q(\lambda)) \equiv \min_{\{g_m, \phi_m\}} \mathcal{L}(\{g_m, \phi_m\}) \tag{3}$$

where the loss $\mathcal{L}(\{g_m, \phi_m\})$ is defined as

$$\mathcal{L}(\{g_m, \phi_m\}) \triangleq \sum_{m=0}^{M-1} \int_{g_m}^{g_{m+1}} p(\lambda) \sum_{y' \in \{0,1\}} P(y = y'|\lambda) \log \frac{P(y = y')}{\sigma\left[(2y'-1)\phi_m\right]} \mathrm{d}\lambda \tag{4}$$

and $\{\phi_m\}$ as a set of real-valued auxiliary variables are introduced here to ease the optimization.

Proof. See A3 for the proof. $\square$

Next, we compute the derivatives of the loss $\mathcal{L}$ with respect to $\{g_m, \phi_m\}$. When the conditional distribution $P(y|\lambda)$ takes the sigmoid model, i.e., $P(y|\lambda) \approx \sigma[(2y-1)\lambda]$, the stationary points of $\mathcal{L}$, zeroing the gradients over $\{g_m, \phi_m\}$, have a closed-form expression

$$g_m = \log\left\{\frac{\log\left[\frac{1+e^{\phi_m}}{1+e^{\phi_{m-1}}}\right]}{\log\left[\frac{1+e^{-\phi_{m-1}}}{1+e^{-\phi_m}}\right]}\right\}, \quad \phi_m = \log\left\{\frac{\int_{g_m}^{g_{m+1}}\sigma(\lambda)p(\lambda)\mathrm{d}\lambda}{\int_{g_m}^{g_{m+1}}\sigma(-\lambda)p(\lambda)\mathrm{d}\lambda}\right\} \approx \log\left\{\frac{\sum_{\lambda_n \in \mathcal{S}_m}\sigma(\lambda_n)}{\sum_{\lambda_n \in \mathcal{S}_m}\sigma(-\lambda_n)}\right\}, \tag{5}$$

where the approximation for ϕ_m arises from using the logits in the training set S as an empirical approximation to $p(\lambda)$ and $S_m \triangleq S \cap [g_m, g_{m+1})$. So, we can solve the problem by iteratively and alternately updating $\{g_m\}$ and $\{\phi_m\}$ based on (A12). The convergence and initialization of such an iterative method as well as the sigmoid-model assumption are discussed along with the proof of Theorem 1 in A3.

As the iterative method operates under an approximation of the inaccessible ground truth distribution $p(y, \lambda)$, here we synthesize an example, see Fig. 3, to assess its effectiveness.[1] In Fig. 3-a, we show the monotonic increase in MI over the iterative steps. Furthermore, Fig. 3-b shows that I-Max approaches the theoretical limits and provides an information-theoretic perspective on the sub-optimal performance of the alternative binning schemes.

---

[1]The formulation (2) is a special case of IB, i.e., the Lagrange multiplier $\beta \to \infty$ and stochastic quantization degenerating to a deterministic one. If using stochastic binning for calibration, it outputs a weighted sum of all bin representatives, thereby being continuous and not ECE verifiable. Given that, we do not use it for calibration.

(a) Convergence behavior   (b) Label-information vs. compression rate

Figure 3: MI evaluation: The KDEs of $p(\lambda|y)$ for $y \in \{0, 1\}$ shown in Fig. 2 are used as the ground truth distribution to synthesize a dataset S_{kde} and evaluate the MI of Eq. mass, Eq. size, and I-Max binning trained over S_{kde}. (a) The developed iterative solution for I-Max bin optimization over S_{kde} successfully increases the MI over iterations, approaching the theoretical upper bound $I(y; \lambda)$. For comparison, I-Max is initialized with both Eq. size and Eq. mass bin edges, both of which are suboptimal at label information preservation. (b) We compare the three binning schemes with 2 to 16 quantization levels against the information bottleneck (IB) limit on the label-information $I(y; Q(\lambda))$ vs. the compression rate $R = I(\lambda; Q(\lambda))$. The information-rate pairs achieved by I-Max binning are very close to the limit. The information loss of Eq. mass binning is considerably larger, whereas Eq. size binning gets stuck in the low rate regime, failing to reach the upper bound even with more bins.

4 EXPERIMENTS

Datasets and Models We evaluate post-hoc calibration methods on three benchmark datasets, i.e., ImageNet (Deng et al., 2009) and both CIFARs (Krizhevsky, 2009), and across three modern DNNs per dataset. All trained models are publicly available and details are reported in Sec. A7.1.

Training and Evaluation Details We perform class-balanced random splits of the data test set: the calibration and evaluation set sizes are both 25k for ImageNet, and 5k for the CIFAR datasets. All reported numbers are the means across 5 random splits; stds can be found in the appendix. Note that some calibration methods only use a subset of the available calibration samples for training, showing their sample efficiency. Further calibrator training details are provided in Sec. A7.1.

We empirically evaluate MI, Accuracy (top-1 and 5 ACCs), ECE (class-wise and top-1), Brier and NLL; the latter are shown in the appendix. The ECEs of the scaling methods are evaluated by using HDE with 100 equal size evaluation bins, as in (Wenger et al., 2020). Sec. A6 also reports the results attained by HDE with additional binning schemes and KDE. For HDE-based ones, we notice that with 100 evaluation bins, the ECE estimate is insensitive to the choice of binning scheme.

4.1 EQ. SIZE, EQ. MASS VS. I-MAX BINNING

When comparing different calibration methods, it is important to jointly consider ECE and ACC. A naive classifier that always predicts all classes with confidence $1/K$ minimizes the ECE to zero, but its ACC is only at chance level. Additionally, only having a small $_{\text{CW}}$ECE may be an artifact. For instance, the $_{\text{CW}}$ECE of ImageNet will be dominated by cases where a properly trained classifier ranks the class-k as very unlikely, as the prior ensures the correctness in 99.9% cases. However, in practice, the relevance of the prediction probability being calibrated or not only matters when the event is likely to happen. Given that, we introduce a threshold into the $_{\text{CW}}$ECE evaluation as in (1) to only consider cases when the predicted probability of class-k exceeds its prior $1/K$.

In Tab. 1, we compare three binning schemes: Eq. size, Eq. mass and I-Max binning. The accuracy performances of the three binning schemes are proportional to their MI (in nats); Eq. mass binning is highly sub-optimal at label information preservation, and thus shows a severe accuracy drop. Eq. size binning accuracy is more similar to that of I-Max binning, but still lower, in particular at Acc$_{\text{top5}}$. Also note that I-Max can approach the MI theoretical limit of $I(y; \lambda)$=0.0068. Advantages of I-Max become even more prominent when comparing the NLLs of the binning schemes. For all three ECE evalution metrics, I-Max binning improves on the baseline calibration performance, and outperforms Eq. size binning. Eq. mass binning is out of this comparison scope due to its poor accuracy deeming

Table 1: ACCs and ECEs of Eq. mass, Eq. size and I-Max binning for the case of ImageNet (InceptionResNetV2). Due to the poor accuracy of Eq. mass binning, its ECEs are not considered for comparison. The MI is empirically evaluated based on KDE analogous to Fig. 3, where the MI upper bound is $I(y; \lambda)$=0.0068. For the other datasets and models, we refer to A8.

Binn.	sCW(?)	size	MI $\uparrow$	Acc$_{top1}$ $\uparrow$	Acc$_{top5}$ $\uparrow$	$_{CW}$ECE $\downarrow$	$_{CW}$ECE$_{\frac{1}{K}}$ $\downarrow$	$_{top1}$ECE $\downarrow$	NLL $\downarrow$
Baseline	✗	-	-	**80.33**	**95.10**	0.000442	0.0486	0.0357	0.8406
Eq. Mass	✗	25k	0.0026	7.78	27.92	0.000173	0.0016	0.0606	3.5960
	✓	1k	0.0026	5.02	26.75	0.000165	0.0022	0.0353	3.5272
Eq. Size	✗	25k	0.0053	78.52	89.06	0.000310	0.1344	0.0547	1.5159
	✓	1k	0.0062	80.14	88.99	0.000298	0.1525	0.0279	1.2671
I-Max	✗	25k	**0.0066**	80.27	95.01	0.000346	0.0342	0.0329	0.8499
	✓	1k	**0.0066**	80.20	94.86	**0.000296**	**0.0302**	**0.0200**	**0.7860**

the method impractical. Overall, I-Max successfully mitigates the negative impact of quantization on ACCs while still providing an improved and verifiable ECE performance. Additionally, I-Max achieves an even better calibration when using sCW with 1k calibration samples, instead of the standard CW binning with 25k calibration samples, highlighting the effectiveness of sCW binning.

In Sec. A5 we perform additional ablations on the number of bins and calibration samples. Accordingly, a post-hoc analysis investigates how the quantization error of the binning schemes change the ranking order. Observations are consistent with the intuition behind the problem formulation (see Sec. 3.3) and empirical results from Tab. 1 that MI maximization is a proper criterion for multi-class calibration and it maximally mitigates the potential accuracy loss.

4.2 SCALING VS. I-MAX BINNING

In Tab. 2, we compare I-Max binning to benchmark scaling methods. Namely, matrix scaling w. L_2 regularization (Kull et al., 2019) has a large model capacity compared to other parametric scaling methods, while TS (Guo et al., 2017) only uses a single parameter and MnM (Zhang et al., 2020) uses three temperatures as an ensemble of TS (ETS). As a non-parametric method, GP (Wenger et al., 2020) yields state of the art calibration performance. Additional 8 scaling methods can be found in Sec. A9. Benefiting from its model capacity, matrix scaling achieves the best accuracy. I-Max binning achieves the best calibration on CIFAR-100; on ImageNet, it has the best $_{CW}$ECE, and is similar to GP on $_{top1}$ECE. For a broader scope of comparison, we refer to Sec. A8.

To showcase the complementary nature of scaling and binning, we investigate combining binning with GP (a top performing non-parametric scaling method, though with the drawback of high complexity) and TS (a commonly used scaling method). Here, we propose to bin the raw logits and use the GP/TS scaled logits of the samples per bin for setting the bin representatives, replacing the empirical frequency estimates. As GP is then only needed at the calibration learning phase, complexity is no longer an issue. Being mutually beneficial, GP helps improving ACCs and ECEs of binning, i.e., marginal ACC drop 0.16% (0.01%) on Acc$_{top1}$ for ImageNet (CIFAR100) and 0.24% on Acc$_{top5}$ for ImageNet; and large ECE reduction 38.27% (49.78%) in $_{CW}$ECE$_{\frac{1}{K}}$ and 66.11% (76.07%) in $_{top1}$ECE of the baseline for ImageNet (CIFAR100).

4.3 SHARED CLASS WISE HELPS SCALING METHODS

Though without quantization loss, some scaling methods, i.e., Beta (Kull et al., 2017), Isotonic regression (Zadrozny & Elkan, 2002), and Platt scaling (Platt, 1999), even suffer from more severe accuracy degradation than I-Max binning. As they also use the one-vs-rest strategy for multi-class calibration, we find that the proposed shared CW binning strategy is beneficial for reducing their accuracy loss and improving their ECE performance, with only 1k calibration samples, see Tab. 3.

Table 2: ACCs and ECEs of I-Max binning (15 bins) and scaling methods. All methods use 1k calibration samples, except for Mtx. Scal. and ETS-MnM, which requires the complete calibration set, i.e., 25k/5k for ImageNet/CIFAR100. Additional 8 scaling methods can be found in A9.

Calibrator	CIFAR100 (WRN)			ImageNet (InceptionResNetV2)			
	$\text{Acc}_{top1} \uparrow$	$\text{CWECE}_{\frac{1}{K}} \downarrow$	$\text{top1ECE} \downarrow$	$\text{Acc}_{top1} \uparrow$	$\text{Acc}_{top5} \uparrow$	$\text{CWECE}_{\frac{1}{K}} \downarrow$	$\text{top1ECE} \downarrow$
Baseline	81.35	0.1113	0.0748	80.33	95.10	0.0486	0.0357
Mtx Scal. w. L_2	**81.44**	0.1085	0.0692	**80.78**	**95.38**	0.0508	0.0282
TS	81.35	0.0911	0.0511	80.33	95.10	0.0559	0.0439
GP	81.34	0.1074	0.0358	80.33	95.11	0.0485	*0.0186*
ETS-MnM	81.35	0.0976	0.0451	80.33	95.10	0.0479	0.0358
I-Max	81.30	*0.0518*	*0.0231*	80.20	94.86	*0.0302*	0.0200
I-Max w. TS	81.34	**0.0510**	0.0365	80.20	94.87	0.0354	0.0402
I-Max w. GP	81.34	0.0559	**0.0179**	80.20	94.87	**0.0300**	**0.0121**

Table 3: ACCs and ECEs of scaling methods using the one-vs-rest conversion for multi-class calibration. Here we compare using 1k samples for both CW and sCW scaling for ImageNet and CIFAR100. For each scheme and metric, we display the best variant of the scaling methods in bold.

Calibrator	sCW(?)	CIFAR100 (WRN)			ImageNet (InceptionResNetV2)			
		$\text{Acc}_{top1} \uparrow$	$\text{CWECE}_{\frac{1}{K}} \downarrow$	$\text{top1ECE} \downarrow$	Acc_{top1}	$\text{Acc}_{top5} \uparrow$	$\text{CWECE}_{\frac{1}{K}} \downarrow$	$\text{top1ECE} \downarrow$
Baseline	-	81.35	0.1113	0.0748	80.33	95.10	0.0489	0.0357
Beta	✗	81.02	0.1066	0.0638	77.80	86.83	0.1662	0.1586
Beta	✓	**81.35**	0.0942	0.0357	**80.33**	**95.10**	0.0625	0.0603
I-Max w. Beta	✓	81.34	**0.0508**	**0.0161**	80.20	94.87	**0.0381**	**0.0574**
Isotonic Reg.	✗	80.62	0.0989	0.0785	77.82	88.36	0.1640	0.1255
Isotonic Reg.	✓	81.30	0.0602	0.0257	**80.22**	**95.05**	0.0345	0.0209
I-Max w. Isotonic Reg.	✓	**81.34**	**0.0515**	**0.0212**	80.20	94.87	**0.0299**	**0.0170**
Platt Scal.	✗	81.31	0.0923	0.1035	**80.36**	94.91	0.0451	0.0961
Platt Scal.	✓	**81.35**	0.0816	0.0462	80.33	**95.10**	0.0565	0.0415
I-Max w. Platt Scal.	✓	81.34	**0.0511**	**0.0323**	80.20	94.87	**0.0293**	**0.0392**

5 CONCLUSION

We proposed I-Max binning for multi-class calibration, which maximally preserves the label-information under quantization, reducing potential accuracy losses. Using the shared class-wise (sCW) strategy, we also addressed the sample-inefficiency issue of binning and scaling methods that rely on one-vs-rest (OvR) for multi-class calibration. Our experiments showed that I-Max yields consistent class-wise and top-1 calibration improvements over multiple datasets and model architectures, outperforming HB and state-of-the-art scaling methods. Combining I-Max with scaling methods offers further calibration performance gains, and more importantly, ECE estimates that can converge to the ground truth in the large sample limit.

Future work will investigate extensions of I-Max that jointly calibrate multiple classes, and thereby directly model class correlations. Interestingly, even on datasets such as ImageNet which contain several closely related classes, there is no clear evidence that methods that do model class correlations, e.g. Mtrx. Scal. capture uncertainties better. In fact, I-Max empirically outperforms such methods, although all classes are calibrated independently under the OvR assumption. Non-OvR based methods may fail due to various reasons such as under-parameterized models (e.g. TS), limited data (e.g. Mtrx. Scal.) or complexity constraints (e.g. GP). Joint class calibration therefore strongly relies on new sample efficient evaluation measures that estimate how accurately class correlations are modeled, and which can be included as additional optimization criteria.

REFERENCES

David Arthur and Sergei Vassilvitskii. k-means++: the advantages of careful seeding. In *Proceedings of the ACM-SIAM symposium on Discrete algorithms*, pp. 1027–1035, Philadelphia, PA, USA, 2007.

Charles Blundell, Julien Cornebise, Koray Kavukcuoglu, and Daan Wierstra. Weight uncertainty in neural networks. In *International Conference on Machine Learning (ICML)*, pp. 1613–1622, Lille, France, July 2015.

J. Deng, W. Dong, R. Socher, L.-J. Li, K. Li, and L. Fei-Fei. ImageNet: A Large-Scale Hierarchical Image Database. In *Proc. of the IEEE/CVF Int. Conf. on Computer Vision and Pattern Recognition (CVPR)*, 2009.

Yarin Gal and Zoubin Ghahramani. Dropout as a bayesian approximation: Representing model uncertainty in deep learning. In *International Conference on Machine Learning (ICML)*, 2016.

Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q. Weinberger. On calibration of modern neural networks. In *International Conference on Machine Learning (ICML)*, pp. 1321–1330, Sydney, Australia, August 2017.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 770–778, 2016.

Dan Hendrycks, Norman Mu, Ekin Dogus Cubuk, Barret Zoph, Justin Gilmer, and Balaji Lakshminarayanan. Augmix: A simple method to improve robustness and uncertainty under data shift. In *International Conference on Learning Representations (ICLR)*, 2020.

G. Huang, Z. Liu, L. v. d. Maaten, and K. Q. Weinberger. Densely connected convolutional networks. In *Proc. of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2017.

B. Ji, H. Jung, J. Yoon, K. Kim, and y. Shin. Bin-wise temperature scaling (BTS): Improvement in confidence calibration performance through simple scaling techniques. In *2019 IEEE/CVF International Conference on Computer Vision Workshop (ICCVW)*, pp. 4190–4196, 2019.

Alex Krizhevsky. Learning multiple layers of features from tiny images. Technical report, 2009.

Meelis Kull, Telmo Silva Filho, and Peter Flach. Beta calibration: a well-founded and easily implemented improvement on logistic calibration for binary classifiers. In *International Conference on Artificial Intelligence and Statistics (AISTATS)*, pp. 623–631, Fort Lauderdale, FL, USA, April 2017.

Meelis Kull, Miquel Perello Nieto, Markus Kängsepp, Telmo Silva Filho, Hao Song, and Peter Flach. Beyond temperature scaling: Obtaining well-calibrated multi-class probabilities with dirichlet calibration. In *Advances in Neural Information Processing Systems (NeurIPs)*, pp. 12295–12305, 2019.

Ananya Kumar, Percy S Liang, and Tengyu Ma. Verified uncertainty calibration. In *Advances in Neural Information Processing Systems (NeurIPs)*, pp. 3787–3798, 2019.

Aviral Kumar, Sunita Sarawagi, and Ujjwal Jain. Trainable calibration measures for neural networks from kernel mean embeddings. In *International Conference on Machine Learning (ICML)*, pp. 2805–2814, July 2018.

Andrey Malinin, Bruno Mlodozeniec, and Mark Gales. Ensemble distribution distillation. In *International Conference on Learning Representations (ICLR)*, 2020.

Dimitrios Milios, Raffaello Camoriano, Pietro Michiardi, Lorenzo Rosasco, and Maurizio Filippone. Dirichlet-based gaussian processes for large-scale calibrated classification. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett (eds.), *Advances in Neural Information Processing Systems (NeurIPs)*, pp. 6005–6015, 2018.

Mahdi Pakdaman Naeini, Gregory F. Cooper, and Milos Hauskrecht. Obtaining well calibrated probabilities using Bayesian binning. In *Proc. of Conference on Artificial Intelligence (AAAI)*, pp. 2901–2907, 2015.

Jeremy Nixon, Michael W. Dusenberry, Linchuan Zhang, Ghassen Jerfel, and Dustin Tran. Measuring calibration in deep learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) Workshops*, June 2019.

Kanil Patel, William Beluch, Dan Zhang, Michael Pfeiffer, and Bin Yang. On-manifold adversarial data augmentation improves uncertainty calibration. *arXiv*, 2019.

John Platt. Probabilities for SV machines. In *Advances in Large Margin Classifiers*, pp. 61–74, 01 1999.

Janis Postels, Francesco Ferroni, Huseyin Coskun, Nassir Navab, and Federico Tombari. Sampling-free epistemic uncertainty estimation using approximated variance propagation. In *Proc. of the IEEE International Conference on Computer Vision (ICCV)*, October 2019.

Serim Ryou, Seong-Gyun Jeong, and Pietro Perona. Anchor loss: Modulating loss scale based on prediction difficulty. In *Proc. of the IEEE International Conference on Computer Vision (ICCV)*, October 2019.

Christian Szegedy, Sergey Ioffe, Vincent Vanhoucke, and Alexander A. Alemi. Inception-v4, Inception-ResNet and the impact of residual connections on learning. In *Proc. of the Conference on Artificial Intelligence*, pp. 4278–4284, San Francisco, U.S., February 2017.

Sunil Thulasidasan, Gopinath Chennupati, Jeff Bilmes, Tanmoy Bhattacharya, and Sarah Michalak. On mixup training: Improved calibration and predictive uncertainty for deep neural networks. *Advances in Neural Information Processing Systems (NeurIPs)*, 2019.

Juozas Vaicenavicius, David Widmann, Carl Andersson, Fredrik Lindsten, Jacob Roll, and Thomas Schön. Evaluating model calibration in classification. In *International Conference on Artificial Intelligence and Statistics (AISTATS)*, pp. 3459–3467, Okinawa, Japan, April 2019.

Jonathan Wenger, Hedvig Kjellström, and Rudolph Triebel. Non-parametric calibration for classification. In *International Conference on Artificial Intelligence and Statistics (AISTATS)*, 2020.

David Widmann, Fredrik Lindsten, and Dave Zachariah. Calibration tests in multi-class classification: A unifying framework. In *Advances in Neural Information Processing Systems (NeurIPs)*, pp. 12257–12267. 2019.

Saining Xie, Ross B. Girshick, Piotr Dollár, Zhuowen Tu, and Kaiming He. Aggregated residual transformations for deep neural networks. *Proc. of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2017.

Sangdoo Yun, Dongyoon Han, Seong Joon Oh, Sanghyuk Chun, Junsuk Choe, and Youngjoon Yoo. Cutmix: Regularization strategy to train strong classifiers with localizable features. In *Proc. of the IEEE International Conference on Computer Vision (ICCV)*, 2019.

Bianca Zadrozny and Charles Elkan. Obtaining calibrated probability estimates from decision trees and naive bayesian classifiers. In *International Conference on Machine Learning (ICML)*, pp. 609–616, 2001.

Bianca Zadrozny and Charles Elkan. Transforming classifier scores into accurate multiclass probability estimates. In *SIGKDD Conference on Knowledge Discovery and Data Mining*, pp. 694–699, January 2002.

Sergey Zagoruyko and Nikos Komodakis. Wide residual networks. In *Proceedings of the British Machine Vision Conference (BMVC)*, 2016.

Jize Zhang, Bhavya Kailkhura, and T Han. Mix-n-Match: Ensemble and compositional methods for uncertainty calibration in deep learning. In *International Conference on Machine Learning (ICML)*, Vienna, Austria, July 2020.

This document supplements the presentation of *Multi-Class Uncertainty Calibration via Mutual Information Maximization-based Binning* in the main paper with the following:

A1: No extra normalization after K class-wise calibrations;

A2: S vs. S_k as empirical approximations to $p(\lambda_k, y_k)$ for bin optimization in Sec. 3.2;

A3: Mathematical proof for Theorem 1 in Sec. 3.3;

A4: Post-hoc analysis on the experiment results in Sec. 4.1;

A5: Ablation on the number of bins and calibration set size;

A6: Empirical ECE estimation of scaling methods under multiple evaluation schemes;

A7: Training details;

A8: Extend Tab. 1 in Sec. 4.1 for more datasets and models;

A9: Extend Tab. 2 in Sec. 4.2 for more scaling methods, datasets and models.

A1 NO EXTRA NORMALIZATION AFTER K CLASS-WISE CALIBRATIONS

There is a group of calibration schemes that rely on one-vs-rest conversion to turn multi-class calibration into K class-wise calibrations, e.g., histogram binning (HB), Platt scaling and Isotonic regression. After per-class calibration, the calibrated prediction probabilities of all classes no longer fulfill the constraint, i.e., $\sum_{k=1}^{K} q_k \neq 1$. An extra normalization step was taken in Guo et al. (2017) to regain the normalization constraint. Here, we note that this extra normalization is unnecessary and partially undoes the per-class calibration effect. For HB, normalization will make its outputs continuous like any other scaling methods, thereby suffering from the same issue at ECE evaluation.

One-vs-rest strategy essentially marginalizes the multi-class predictive distribution over each class. After such marginalization, each class and its prediction probability shall be treated independently, thus no longer being constrained by the multi-class normalization constraint. This is analogous to train a CIFAR or ImageNet classifier with $\mathrm{sigmoid}$ rather than $\mathrm{softmax}$ cross entropy loss, e.g., Ryou et al. (2019). At training and test time, each class prediction probability is individually taken from the respective $\mathrm{sigmoid}$-response without normalization. The class with the largest response is then top-ranked, and normalization itself has no influence on the ranking performance.

A2 S VS. S_k AS EMPIRICAL APPROXIMATIONS TO $p(\lambda_k, y_k)$ FOR BIN OPTIMIZATION

In Sec. 3.2 of the main paper, we discussed the class imbalance issue, arising from one-vs-rest conversion.Fig. A1 shows the effect of the shared CW (sCW) strategy discussed in Sec. 3.2. Specifically, it can be seen that the sCW strategy greatly improves the sample efficiency compared to using the class-wise strategy.

(a) train set $S_{k=394}$ for CW binning.   (b) train. set S for *shared*-CW binning.

Figure A1: Histogram of ImageNet (InceptionResNetv2) logits for (a) CW and (b) sCW training. By means of the set merging strategy to handle the class imbalance $1 : 999$, S has $K{=}1000$ times more class-1 samples than S_k with the same 10k calibration samples from C.
To tackle it, we proposed to merge the class-wise (CW) bin training sets $\{S_k\}$ and use the merged one S to train a single binning scheme for all classes, i.e., shared CW (sCW) instead of CW binning. Tab. 3

showed that our proposal is also beneficial to scaling methods that use one-vs-rest for multi-class calibration.

As pointed out in Sec. 3.2, both S and S_k are empirical approximations to the inaccessible ground truth $p(\lambda_k, y_k)$ for bin optimization. In Fig. A2, we empirically analyze their approximation errors. From the CIFAR10 test set, we take 5k samples to approximate per-class logit distribution $p(\lambda_k | y_k = 1)$ by means of histogram density estimation[2], and then use it as the baseline for comparison, i.e., BS_k in Fig. A2. The rest of the 5k samples in the CIFAR10 test set are reserved for constructing S_k and S. For each class, we respectively evaluate the square root of the Jensen-Shannon divergence (JSD) from the baseline BS_k to the empirical distribution of S or S_k attained at different numbers of samples. Despite suffering from the bias induced by set merging, S achieves noticeably smaller JSDs than S_k in nearly all cases, and shows to be more sample efficient. Only after using all 5k samples, S_k has slightly smaller JSDs than S in the class-1, and 6 and 7. From CIFAR10 to CIFAR100 and ImageNet, the class imbalance issue becomes more severe. We expect the sample inefficiency issue of S_k becomes more critical, and therefore it is advisable to use S for bin optimization.

Figure A2: Empirical approximation error of S vs. S_k, where Jensen-Shannon divergence (JSD) is used to measure the difference between the empirical distributions underlying the training sets for class-wise bin optimization. Overall, the merged set S is a more sample efficient choice over S_k.

A3   PROOF OF THEOREM 1

Theorem 1. *The mutual information (MI) maximization problem given as follows:*

$$\{g_m^*\} = \arg \max_{Q:\{g_m\}} I(y; m = Q(\lambda)) \tag{A1}$$

is equivalent to

$$\max_{Q:\{g_m\}} I(y; m = Q(\lambda)) \equiv \min_{\{g_m, \phi_m\}} \mathcal{L}(\{g_m, \phi_m\}) \tag{A2}$$

where the loss $\mathcal{L}(\{g_m, \phi_m\})$ is defined as

$$\mathcal{L}(\{g_m, \phi_m\}) \triangleq \sum_{m=0}^{M-1} \int_{g_m}^{g_{m+1}} p(\lambda) \sum_{y' \in \{0,1\}} P(y = y'|\lambda) \log \frac{P(y = y')}{P_\sigma(y = y'; \phi_m)} d\lambda \tag{A3}$$

with $P_\sigma(y; \phi_m) \triangleq \sigma\left[(2y - 1)\phi_m\right].$ $\tag{A4}$

As a set of real-valued auxiliary variables, $\{\phi_m\}$ are introduced here to ease the optimization.

---

[2]Here, we focus on $p(\lambda_k | y_k = 1)$ as its empirical estimation suffers from the class imbalance, being much more challenging than $p(\lambda_k | y_k = 0)$ as illustrated in Fig. A1.

Proof . Before staring our proof, we note that the upper-case P indicates probability mass functions of discrete random variables, e.g., the label $y \in \{0, 1\}$ and the bin interval index $m \in \{1, \dots, M\}$; whereas the lower-case p is reserved for probability density functions of continuous random variables, e.g., the raw logit $\lambda \in \mathbb{R}$.

The key to prove the equivalence is to show the inequality

$$I(y; m = Q(\lambda)) \geq -\mathcal{L}(\{g_m, \phi_m\}), \tag{A5}$$

and the equality is attainable by minimizing $\mathcal{L}$ over $\{\phi_m\}$.

By the definition of MI, we firstly expand $I(y; m = Q(\lambda))$ as

$$I(y; m = Q(\lambda)) = \sum_{i=0}^{M-1} \int_{g_m}^{g_{m+1}} p(\lambda) \sum_{y' \in \{0,1\}} P(y = y'|\lambda) \log \frac{P(y = y'|m)}{P(y = y')} \mathrm{d}\lambda, \tag{A6}$$

where the conditional distribution $P(y|m)$ is given as

$$P(y|m) = P(y|\lambda \in [g_m, g_{m+1})) = \frac{P(y) \int_{g_m}^{g_{m+1}} p(\lambda|y)\mathrm{d}\lambda}{\int_{g_m}^{g_{m+1}} p(\lambda)\mathrm{d}\lambda} = \frac{\int_{g_m}^{g_{m+1}} p(y|\lambda)P(y)\mathrm{d}\lambda}{\int_{g_m}^{g_{m+1}} p(\lambda)\mathrm{d}\lambda}. \tag{A7}$$

From the above expression, we note that MI maximization effectively only accounts to the bin edges $\{g_m\}$. The bin representatives can be arbitrary as long as they can indicate the condition $\lambda \in [g_m, g_{m+1})$. So, the bin interval index m is sufficient to serve the role in conditioning the probability mass function of y, i.e., $P(y|m)$. After optimizing the bin edges, we have the freedom to set the bin representatives for the sake of post-hoc calibration.

Next, based on the MI expression, we compute its sum with $\mathcal{L}$

$$
\begin{aligned}
I(y; Q(\lambda)) + \mathcal{L}(\{g_m, \phi_m\}) &= \sum_{i=0}^{M-1} \int_{g_m}^{g_{m+1}} p(\lambda) \sum_{y' \in \{0,1\}} P(y = y'|\lambda)\mathrm{d}\lambda \log \frac{P(y = y'|m)}{P_\sigma(y = y'; \phi_m)} \\
&\overset{(a)}{=} \sum_{i=0}^{M-1} P(m) \left[\sum_{y' \in \{0,1\}} P(y = y'|m) \log \frac{P(y = y'|m)}{P_\sigma(y = y'; \phi_m)} \right] \\
&\overset{(b)}{=} \sum_{i=0}^{M-1} P(m)\mathrm{KLD}\left[P(y = y'|m) \| P_\sigma(y = y'; \phi_m) \right] \\
&\overset{(c)}{\geq} 0. \tag{A8}
\end{aligned}
$$

The equality (a) is based on

$$\int_{g_m}^{g_{m+1}} p(\lambda)P(y = y'|\lambda)\mathrm{d}\lambda = P(y = y', \lambda \in [g_m, g_{m+1})) = \underbrace{P(\lambda \in [g_m, g_{m+1}))}_{=P(m)} P(y = y'|m). \tag{A9}$$

From the equality (a) to (b), it is simply because of identifying the term in $[\cdot]$ of the equality (a) as the Kullback-Leibler divergence (KLD) between two probability mass functions of y. As the probability mass function $P(m)$ and the KLD both are non-negative, we reach to the inequality at (c), where the equality holds if $P_\sigma(y; \phi_m) = P(y|m)$. By further noting that $\mathcal{L}$ is convex over $\{\phi_m\}$ and $P_\sigma(y; \phi_m) = P(y|m)$ nulls out its gradient over $\{\phi_m\}$, we then reach to

$$I(y; Q(\lambda)) + \min_{\{\phi_m\}} \mathcal{L}(\{g_m, \phi_m\}) = 0. \tag{A10}$$

The obtained equality then concludes our proof

$$
\begin{aligned}
\max_{\{g_m\}} I(y; Q(\lambda)) = \max_{\{g_m\}} \left[- \min_{\{\phi_m\}} \mathcal{L}(\{g_m, \phi_m\}) \right] &= - \min_{\{g_m, \phi_m\}} \mathcal{L}(\{g_m, \phi_m\}) \\
&\equiv \min_{\{g_m, \phi_m\}} \mathcal{L}(\{g_m, \phi_m\}). \tag{A11}
\end{aligned}
$$

$\square$

Lastly, we note that $\mathcal{L}(\{g_m, \phi_m\})$ can reduce to a NLL loss (as $P(y)$ in the log probability ratio is omittable), which is a common loss for calibrators. However, only through this equivalence proof and the MI maximization formulation, can we clearly identify the great importance of bin edges in preserving label information. So even though $\{g_m, \phi_m\}$ are jointly optimized in the equivalent problem, only $\{g_m\}$ play the determinant role in maximizing the MI.

A3.1 Convergence of the Iterative Method

For convenience, we recall the update equations for $\{g_m, \phi_m\}$ in Sec. 3.3 of the main paper here

$$
\begin{cases}
g_m = \log \left\{ \dfrac{\log\left[\frac{1+e^{\phi_m}}{1+e^{\phi_{m-1}}}\right]}{\log\left[\frac{1+e^{-\phi_{m-1}}}{1+e^{-\phi_m}}\right]} \right\} \\
\phi_m = \log \left\{ \dfrac{\int_{g_m}^{g_{m+1}} \sigma(\lambda)p(\lambda)\mathrm{d}\lambda}{\int_{g_m}^{g_{m+1}} \sigma(-\lambda)p(\lambda)\mathrm{d}\lambda} \right\} \approx \log \left\{ \dfrac{\sum_{\lambda_n \in S_m} \sigma(\lambda_n)}{\sum_{\lambda_n \in S_m} \sigma(-\lambda_n)} \right\}
\end{cases} \quad \forall m. \tag{A12}
$$

In the following, we show that the updates on $\{g_m\}$ and $\{\phi_m\}$ according to (A12) continuously decrease the loss $\mathcal{L}$, i.e.,

$$
\mathcal{L}(\{g_m^l, \phi_m^l\}) \geq \mathcal{L}(\{g_m^{l+1}, \phi_m^l\}) \geq \mathcal{L}(\{g_m^{l+1}, \phi_m^{l+1}\}). \tag{A13}
$$

The second inequality is based on the explained property of $\mathcal{L}$. Namely, it is convex over $\{\phi_m\}$ and the minimum for any given $\{g_m\}$ is attained by $P_\sigma(y; \phi_m) = P(y|m)$. As ϕ_m is the log-probability ratio of $P_\sigma(y; \phi_m)$, we shall have

$$
\phi_m^{l+1} \leftarrow \log \frac{P(y=1|m)}{P(y=0|m)} \tag{A14}
$$

where $P(y=1|m)$ in this case is induced by $\{g_m^{l+1}\}$ and $P(y|\lambda) = \sigma[(2y-1)\lambda]$. Plugging $\{g_m^{l+1}\}$ and $P(y|\lambda) = \sigma[(2y-1)\lambda]$ into (A7), the resulting $P(y=y'|m)$ at the iteration $l+1$ yields the update equation of ϕ_m as given in (A12).

To prove the first inequality, we start from showing that $\{g_m^{l+1}\}$ is a local minimum of $\mathcal{L}(\{g_m, \phi_m^l\})$. The update equation on $\{g_m\}$ is an outcome of solving the stationary point equation of $\mathcal{L}(\{g_m, \phi_m^l\})$ over $\{g_m\}$ under the condition $p(\lambda = g_m) > 0$ for any m

$$
\frac{\partial \mathcal{L}(\{g_m, \phi_m^l\})}{\partial g_m} = p(\lambda = g_m) \sum_{y' \in \{0,1\}} P(y=y'|\lambda=g_m) \log \frac{P_\sigma(y=y'; \phi_m^l)}{P_\sigma(y=y'; \phi_{m-1}^l)} \overset{!}{=} 0 \quad \forall m \tag{A15}
$$

Being a stationary point is the necessary condition of local extremum when the function's first-order derivative exists at that point, i.e., first-derivative test. To further show that the local extremum is actually a local minimum, we resort to the second-derivative test, i.e., if the Hessian matrix of $\mathcal{L}(\{g_m, \phi_m^l\})$ is positive definite at the stationary point $\{g_m^{l+1}\}$. Due to $\phi_m > \phi_{m-1}$ with the monotonically increasing function sigmoid in its update equation, we have

$$
\frac{\partial^2 \mathcal{L}(\{g_m, \phi_m^l\})}{\partial g_m \partial g_{m'}} \bigg|_{g_m = g_m^{l+1} \forall m} = 0 \quad \text{and} \quad \frac{\partial^2 \mathcal{L}(\{g_m, \phi_m^l\})}{\partial^2 g_m} \bigg|_{g_m = g_m^{l+1} \forall m} > 0, \tag{A16}
$$

implying that all eigenvalues of the Hessian matrix are positive (equivalently, is positive definite). Therefore, $\{g_m^{l+1}\}$ as the stationary point of $\mathcal{L}(\{g_m, \phi_m^l\})$ is a local minimum.

It is important to note that from the stationary point equation (A15), $\{g_m^{l+1}\}$ as a local minimum is unique among $\{g_m\}$ with $p(\lambda = g_m) > 0$ for any m. In other words, the first inequality holds under the condition $p(\lambda = g_m^l) > 0$ for any m. Binning is a lossy data processing. In order to maximally preserve the label information, it is natural to exploit all bins in the optimization, not wasting any single bin in the area without mass, i.e., $p(\lambda = g_m) = 0$. Having said that, it is reasonable to constrain $\{g_m\}$ with $p(\lambda = g_m) > 0 \,\forall m$ over iterations, thereby concluding that the iterative method will converge to a local minimum based on the two inequalities (A13).

A3.2 INITIALIZATION OF THE ITERATIVE METHOD

We propose to initialize the iterative method by modifying the k-means++ algorithm Arthur & Vassilvitskii (2007) that was developed to initialize the cluster centers for k-means clustering algorithms. It is based on the following identification

$$\mathcal{L}(\{g_m, \phi_m\}) + I(y; \lambda) = \sum_{i=0}^{M-1} \int_{g_m}^{g_{m+1}} p(\lambda) \text{KDL} \left[P(y = y'|\lambda) \| P_\sigma(y = y'; \phi_m) \right] d\lambda \quad \text{(A17)}$$

$$\geq \int_{-\infty}^{\infty} p(\lambda) \min_m \text{KLD} \left[P(y = y'|\lambda) \| P_\sigma(y = y'; \phi_m) \right] d\lambda$$

$$\approx \frac{1}{|S|} \sum_{\lambda_n \in S} \min_m \text{KLD} \left[P(y = y'|\lambda_n) \| P_\sigma(y = y'; \phi_m) \right]. \quad \text{(A18)}$$

As $I(y; \lambda)$ is a constant with respect to $(\{g_m, \phi_m\})$, minimizing $\mathcal{L}$ is equivalent to minimizing the term on the RHS of (A17). The last approximation is reached by turning the binning problem into a clustering problem, i.e., grouping the logit samples in the training set S according to the KLD measure, where $\{\phi_m\}$ are effectively the centers of each cluster. k-means++ algorithm Arthur & Vassilvitskii (2007) initializes the cluster centers based on the Euclidean distance. In our case, we alternatively use the JSD as the distance measure to initialize $\{\phi_m\}$. Comparing with KLD, JSD is symmetric and bounded.

A3.3 A REMARK ON THE ITERATIVE METHOD DERIVATION

The closed-form update on $\{g_m\}$ in (A12) is based on the sigmoid-model approximation, which has been validated through our empirical experiments. It is expected to work with properly trained classifiers that are not overly overfitting to the cross-entropy loss, e.g., using data augmentation and other regularization techniques at training. Nevertheless, even in corner cases that classifiers are poorly trained, the iterative method can still be operated without the sigmoid-model approximation. Namely, as shown in Fig. 2 of the main paper, we can resort to KDE for an empirical estimation of the ground truth distribution $p(\lambda|y)$. Using the KDEs, we can compute the gradient of $\mathcal{L}$ over $\{g_m\}$ and perform iterative gradient based update on $\{g_m\}$, replacing the closed-form based update. Essentially, the sigmoid-model approximation is only necessary to find the stationary points of the gradient equations, speeding up the convergence of the method. If attempting to keep the closed-form update on $\{g_m\}$, an alternative solution could be to use the KDEs for adjusting the sigmoid-model, e.g., $p(y|\lambda) \approx \sigma \left[(2y - 1)(a\lambda + ab) \right]$, where a and b are chosen to match the KDE based approximation to $p(y|\lambda)$. After setting a and b, they will be used as a scaling and bias term in the original closed-form update equations

$$\begin{aligned} g_m &= \frac{1}{a} \log \left\{ \frac{\log \left[\frac{1 + e^{\phi_m}}{1 + e^{\phi_m - 1}} \right]}{\log \left[\frac{1 + e^{-\phi_m - 1}}{1 + e^{-\phi_m}} \right]} \right\} - b \\ \phi_m &= \log \left\{ \frac{\int_{g_m}^{g_{m+1}} \sigma(a\lambda + ab) p(\lambda) d\lambda}{\int_{g_m}^{g_{m+1}} \sigma(-a\lambda - ab) p(\lambda) d\lambda} \right\} \approx \log \left\{ \frac{\sum_{\lambda_n \in \mathcal{S}_m} \sigma(a\lambda_n + ab)}{\sum_{\lambda_n \in \mathcal{S}_m} \sigma(-a\lambda_n - ab)} \right\} \end{aligned} \quad \forall m. \quad \text{(A19)}$$

A4 POST-HOC ANALYSIS ON THE EXPERIMENT RESULTS IN SEC. 4.1

In Tab. 1 of Sec. 4.1, we compared three different binning schemes by measuring their ACCs and ECEs. The observation on their accuracy performance is aligned with our mutual information maximization viewpoint introduced in Sec. 3.3 and Fig. 2. Here, we re-present Fig. 2 and provide an alternative explanation to strengthen our understanding on how the location of bin edges affects the accuracy, e.g., why Eq. Size binning performed acceptable at the top-1 ACC, but failed at the top-5 ACC. Specifically, Fig. A3 shows the histograms of raw logits that are grouped based on their ranks instead of their labels as in Fig. 2. As expected, the logits with low ranks (i.e., rest below top-5 in Fig. A3) are small and thus take the left hand side of the plot, whereas the top-1 logits are mostly located on the right hand side. Besides sorting logits according to their ranks, we additionally estimate the density of the ground truth (GT) classes associated logits, i.e., GT in Fig. A3). With a properly trained classifier, the histogram of top-1 logits shall largerly overlap with the density curve GT, i.e., top-1 prediction being correct in most cases.

Figure A3: Histogram of CIFAR100 (WRN) logits in S constructed from 1k calibration samples, using the same setting as Fig. 2 in the main paper. Instead of categorizing the logits according to their two-class label $y_k \in \{0, 1\}$ as in Fig. 2, here we sort them according to their ranks given by the CIFAR100 WRN classifier. As a baseline, we also plot the KDE of logits associated to the ground truth classes, i.e., GT.

Table A1: Comparison of sCW binning methods in the case of ImageNet - InceptionResNetV2. As sCW binning creates ties at top predictions, the ACCs initially reported in Tab. 1 of Sec. 4.1 use the class index as the secondary sorting criterion. Here, we add Acc*$_{top1}$ and Acc*$_{top5}$ which are attained by using the raw logits as the secondary sorting criterion. As the CW ECEs are not affected by this change, here we only report the new $_{top1}$ECE*.

Binn.	Acc$_{top1}$ ↑	Acc*$_{top1}$ ↑	Acc$_{top5}$ ↑	Acc*$_{top5}$ ↑	$_{top1}$ECE ↓	$_{top1}$ECE* ↓	NLL ↓
Baseline	**80.33**	-	**95.10**	-	0.0357	-	0.8406
Eq. Mass	5.02	**80.33**	26.75	**95.10**	0.0353	0.7884	3.5272
Eq. Size	80.14	80.21	88.99	**95.10**	0.0279	0.0277	1.2671
I-Max	80.20	**80.33**	94.86	**95.10**	**0.0200**	**0.0202**	**0.7860**

From the bin edge location of Eq. Mass binning, it attempts to attain small quantization errors for logits of low ranks rather than top-5. This will certainly degrade the accuracy performance after binning. On contrary, Eq. Size binning aims at small quantization error for the top-1 logits, but ignores top-5 ones. As a result, we observed its poor top-5 ACCs. I-Max binning nicely distributes its bin edges in the area where the GT logits are likely to locate, and the bin width becomes smaller in the area where the top-5 logits are close by (i.e., the overlap region between the red and blue histograms). Note that, any logit larger than zero must be top-1 ranked, as there can exist at most one class with prediction probability larger than 0.5. Given that, the bins located above zero are no longer to maintain the ranking order, rather to reduce the precision loss of top-1 prediction probability after binning.

The second part of our post-hoc analysis is on the sCW binning strategy. When using the same binning scheme for all per-class calibration, the chance of creating ties in top-k predictions is much higher than CW binning, e.g., more than one class are top-1 ranked according to the calibrated prediction probabilities. Our reported ACCs in the main paper are attained by simply returning the first found class, i.e., using the class index as the secondary sorting criterion. This is certainly a suboptimal solution. Here, we investigate on how the ties affect ACCs of sCW binning. To this end, we use raw logits (before binning) as the secondary sorting criterion. The resulting ACC^*_{top1} and ACC^*_{top5} are shown in Tab.A1. Interestingly, such a simple change reduces the accuracy loss of Eq. Mass and I-Max binning to zero, indicating that they can preserve the top-5 ranking order of the raw logits but not in a strict monotonic sense, i.e., some $>$ are replaced by $=$. As opposed to I-Max binning, Eq. Mass binning has a poor performance at calibration, i.e., the really high NLL and ECE. This is because it trivially ranks many classes as top-1, but each of them has a very and same small confidence score. Given that, even though the accuracy loss is no longer an issue, it is still not a good solution for multi-class calibration. For Eq. Size binning, resolving ties only helps restore the baseline top-5 but not top-1 ACC. Its poor bin representative setting due to unreliable empirical frequency estimation over too narrow bins can result in a permutation among the top-5 predictions.

Concluding from the above, our post-hoc analysis confirms that I-Max binning outperforms the other two binning schemes at mitigating the accuracy loss and multi-class calibration. In particular, there

Table A2: Ablation on the number of bins and calibration samples for sCW I-Max binning, where the basic setting is identical to the Tab. 1 in Sec. 4.1 of the main paper.

Binn.	Bins	$Acc_{top1} \uparrow$	$Acc_{top5} \uparrow$	$_{CW}ECE_{\frac{1}{K}} \downarrow$	$_{top1}ECE \downarrow$	$Acc_{top1} \uparrow$	$Acc_{top5} \uparrow$	$_{CW}ECE_{\frac{1}{K}} \downarrow$	$_{top1}ECE \downarrow$
Baseline	-	**80.33**	95.10	0.0486	0.0357	**80.33**	95.10	0.0486	0.0357
		1k Calibration Samples				5k Calibration Samples			
GP		**80.33**	**95.11**	0.0485	0.0186	**80.33**	**95.11**	0.0445	0.0177
I-Max	10	80.09	94.59	0.0316	0.0156	80.14	94.59	0.0330	0.0107
	15	80.20	94.86	0.0302	0.0200	80.21	94.90	0.0257	0.0107
	20	80.10	94.94	**0.0266**	0.0234	80.25	94.98	**0.0220**	0.0133
	30	80.15	94.99	0.0343	0.0266	80.25	95.02	0.0310	0.0150
	40	80.11	95.05	0.0365	0.0289	80.24	95.08	0.0374	0.0171
	50	80.21	94.95	0.0411	0.0320	80.23	95.06	0.0378	0.0219
I-Max w. GP	10	80.09	94.59	0.0396	0.0122	80.14	94.59	0.0330	**0.0072**
	15	80.20	94.87	0.0300	**0.0121**	80.21	94.88	0.0256	0.0080
	20	80.23	94.95	0.0370	0.0133	80.25	95.00	0.0270	0.0091
	30	80.26	95.04	0.0383	0.0141	80.27	95.02	0.0389	0.0097
	40	80.27	**95.11**	0.0424	0.0145	80.26	95.08	0.0402	0.0108
	50	80.30	95.08	0.0427	0.0153	80.28	95.08	0.0405	0.0114

exists a simple solution to close the accuracy gap to the baseline, at the same time still retaining the desirable calibration gains.

A5   ABLATION ON THE NUMBER OF BINS AND CALIBRATION SET SIZE

In Tab. 1 of Sec. 4.1, sCW I-Max binning is the top performing one at the ACCs, ECEs and NLL measures. In this part, we further investigate on how the number of bins and calibration set size influences its performance. Tab. A2 shows that in order to benefit from more bins we shall accordingly increase the number of calibration samples. More bins help reduce the quantization loss, but increase the empirical frequency estimation error for setting the bin representatives. Given that, we observe a reduced ACCs and increased ECEs for having 50 bins with only 1k calibration samples. By increasing the calibration set size to 5k, then we start seeing the benefits of having more bins to reduce quantization error for better ACCs. Next, we further exploit scaling method, i.e., GP Wenger et al. (2020), for improving the sample efficiency of binning at setting the bin representatives. As a result, the combination is particularly beneficial to improve the ACCs and top-1 ECE. Overall, more bins are beneficial to ACCs, while ECEs favor less number of bins.

A6   EMPIRICAL ECE ESTIMATION OF SCALING METHODS UNDER MULTIPLE EVALUATION SCHEMES

As mentioned in the main paper, scaling methods suffer from not being able to provide verifiable ECEs, see Fig. 1. Here, we discuss alternatives to estimate their ECEs. The current literature can be split into two types of ECE evaluation: histogram density estimation (HDE) and kernel density estimation (KDE).

A6.1   HDE-BASED ECE EVALUATION

HDE bins the prediction probabilities (logits) for density modeling. The binning scheme has different variants, where changing the bin edges can give varying measures of the ECE. Two bin edges schemes have been discussed in the literature (Eq. size and Eq. mass) as well as a new scheme was introduced (I-Max). Alternatively, we also evaluate a binning scheme which is based on KMeans clustering to determine the bin edges.

(a) CIFAR100/WRN Top-1 (Prob. Space)

(b) CIFAR100/WRN Top-1 (Log Space)

(c) ImageNet/Inceptionresnetv2 Top-1 (Prob. Space)

(d) ImageNet/Inceptionresnetv2 Top-1 (Log Space)

Figure A4: Distribution of the top-1 predictions and its log-space counterparts, i.e., $\lambda = \log q - \log(1 - q)$.

A6.2 KDE-BASED ECE EVALUATION

Recent work (Zhang et al., 2020) presented an alternative ECE evaluation scheme which exploits KDEs to estimate the distribution of prediction probabilities $\{q_k\}$ from the test set samples. Using the code provided by Zhang et al. (2020), we observe that the KDE with the setting in their paper can have a sub-optimal fitting in the probability space. This can be observed from Fig. A4a and Fig. A4c, where the fitting is good for ImageNet/Inceptionresnetv2 though when the distribution is significantly skewed to the right (as in the case of CIFAR100/WRN) the mismatch becomes large. We expect that the case of CIFAR100/WRN is much more common in modern DNNs, due to their high capacities and prone to overfitting.

Equivalently, we can learn the distribution in its log space by the bijective transformation, i.e., $\lambda = \log q - \log(1 - q)$ and $q = \sigma(\lambda)$. As we can observe from Fig. A4b and Fig. A4d, the KDE fitting for both models is consistently good.

Zhang et al. (2020) empirically validated their KDE in a toy example, where the ground truth ECE can be analytically computed. By analogy, we reproduce the experiment and further compare it with the log-space KDE evaluation. Using the same settings as in (Zhang et al., 2020), we assess the ECE evaluation error by KDE, i.e., $|\text{ECE}_{\text{gt}} - \text{ECE}_{\text{kde}}|$, in both the log and probability space, achieving prob 0.0020 vs. log 0.0017 for the toy example setting $\beta_0 = 0.5; \beta_1 = -1.5$. For an even less calibrated setting, $\beta_0 = 0.2; \beta_1 = -1.9$, we obtain prob 0.0029 vs. log 0.0020. So the log-space KDE-based ECE evaluation ($\text{kdeECE}_{\text{log}}$) has lower estimation error than in the probability space.

A6.3 ALTERNATIVE ECE EVALUATION SCHEMES

Concluding from the above, Tab. A3 shows the ECE estimates attained by HDEs (from four different bin setting schemes) and KDE (from (Zhang et al., 2020), but in the log space). As we can see, the obtained results are evaluation scheme dependent. On contrary, I-Max binning with and without GP

Table A3: ECEs of scaling methods under various evaluation schemes for ImageNet InceptionRes-NetV2. Overall, we consider five evaluation schemes, namely (1) dECE: equal size binning; (2) mECE: equal mass binning, (3) kECE: MSE-based KMeans clustering; (4) iECE: I-Max binning; 5) kdeECE: KDE. The HDEs based schemes, i.e., (1)-(4), use 10^2 bins. Note that, the ECEs of I-Max binning (as a calibrator rather than evaluation scheme) are agnostic to the evaluation scheme. Furthermore, BBQ suffers from severe accuracy degradation.

Calibrator	ACC_{top_1}	$_{cw}dECE_{\frac{1}{K}}$ ↓	$_{cw}mECE_{\frac{1}{K}}$ ↓	$_{cw}kECE_{\frac{1}{K}}$ ↓	$_{cw}iECE_{\frac{1}{K}}$ ↓	$_{cw}kdeECE_{\frac{1}{K}}$ ↓	Mean ↓
Baseline	80.33	0.0486 ± 0.0003	0.0459 ± 0.0004	0.0484 ± 0.0004	0.0521 ± 0.0004	0.0749 ± 0.0014	0.0540
25k Calibration Samples							
BBQ	53.89	0.0287 ± 0.0009	0.0376 ± 0.0014	0.0372 ± 0.0014	0.0316 ± 0.0008	0.0412 ± 0.0010	0.0353
Beta	80.47	0.0706 ± 0.0003	0.0723 ± 0.0005	0.0742 ± 0.0005	0.0755 ± 0.0004	0.0828 ± 0.0003	0.0751
Isotonic Reg.	80.08	0.0644 ± 0.0015	0.0646 ± 0.0015	0.0652 ± 0.0016	0.0655 ± 0.0015	0.0704 ± 0.0014	0.0660
Platt	80.48	0.0597 ± 0.0007	0.0593 ± 0.0008	0.0613 ± 0.0008	0.0634 ± 0.0008	0.1372 ± 0.0028	0.0762
Vec Scal. w. L2 reg.	80.53	0.0494 ± 0.0002	0.0472 ± 0.0004	0.0498 ± 0.0003	0.0531 ± 0.0003	0.0805 ± 0.0010	0.0560
Mtx Scal. w. L2 reg.	**80.78**	0.0508 ± 0.0003	0.0488 ± 0.0004	0.0512 ± 0.0005	0.0544 ± 0.0004	0.0898 ± 0.0011	0.0590
1k Calibration Samples							
TS	80.33	0.0559 ± 0.0015	0.0548 ± 0.0018	0.0573 ± 0.0017	0.0598 ± 0.0015	0.1003 ± 0.0053	0.0656
GP	80.33	0.0485 ± 0.0037	0.0450 ± 0.0040	0.0475 ± 0.0039	0.0520 ± 0.0038	0.0580 ± 0.0052	0.0502
I-Max	80.20	0.0302 ± 0.0041					
I-Max w. GP	80.20	**0.0300** ± 0.0041					

Calibrator	ACC_{top_1}	$_{top1}dECE$ ↓	$_{top1}mECE$ ↓	$_{top1}kECE$ ↓	$_{top1}iECE$ ↓	$_{top1}kdeECE$ ↓	Mean ↓
Baseline	80.33	0.0357 ± 0.0010	0.0345 ± 0.0010	0.0348 ± 0.0012	0.0352 ± 0.0016	0.0480 ± 0.0016	0.0376
25k Calibration Samples							
BBQ	53.89	0.2689 ± 0.0033	0.2690 ± 0.0034	0.2690 ± 0.0034	0.2689 ± 0.0032	0.2756 ± 0.0145	0.2703
Beta	80.47	0.0346 ± 0.0022	0.0360 ± 0.0017	0.0360 ± 0.0022	0.0357 ± 0.0019	0.0292 ± 0.0023	0.0343
Isotonic Reg.	80.08	0.0468 ± 0.0020	0.0434 ± 0.0019	0.0436 ± 0.0020	0.0468 ± 0.0015	0.0437 ± 0.0057	0.0449
Platt	80.48	0.0775 ± 0.0015	0.0772 ± 0.0015	0.0771 ± 0.0016	0.0773 ± 0.0014	0.0772 ± 0.0018	0.0773
Vec Scal. w. L2 reg.	80.53	0.0300 ± 0.0010	0.0298 ± 0.0012	0.0300 ± 0.0016	0.0303 ± 0.0011	0.0365 ± 0.0023	0.0313
Mtx Scal. w. L2 reg.	**80.78**	0.0282 ± 0.0014	0.0287 ± 0.0011	0.0286 ± 0.0014	0.0289 ± 0.0014	0.0324 ± 0.0019	0.0293
1k Calibration Samples							
TS	80.33	0.0439 ± 0.0022	0.0452 ± 0.0022	0.0454 ± 0.0020	0.0443 ± 0.0020	0.0679 ± 0.0024	0.0493
GP	80.33	0.0186 ± 0.0034	0.0182 ± 0.0019	0.0186 ± 0.0026	0.0190 ± 0.0022	0.0164 ± 0.0029	0.0182
I-Max	80.20	0.0200 ± 0.0033					
I-Max w. GP	80.20	**0.0121** ± 0.0048					

are not affected, and more importantly, their ECEs are better than that of scaling methods, regardless of the evaluation scheme.

A7 TRAINING DETAILS

A7.1 PRE-TRAINED CLASSIFICATION NETWORKS

We evaluate post-hoc calibration methods on three benchmark datasets, i.e., ImageNet Deng et al. (2009), CIFAR-100 Krizhevsky (2009), and CIFAR-10 Krizhevsky (2009), and across three modern DNNs for each dataset, i.e., InceptionResNetV2 Szegedy et al. (2017), DenseNet161 Huang et al. (2017) and ResNet152 He et al. (2016) for ImageNet, and Wide ResNet (WRN) Zagoruyko & Komodakis (2016), DenseNet-BC ($L = 190, k = 40$) Huang et al. (2017) and ResNext8x64 Xie et al. (2017) for the two CIFAR datasets.

All these models are publicly available pre-trained networks and details are reported at the respective websites, i.e., ImageNet classifiers: `https://github.com/Cadene/pretrained-models.pytorch` and CIFAR classifiers: `https://github.com/bearpaw/pytorch-classification`

A7.2 TRAINING SCALING METHODS

The hyper-parameters were decided based on the original respective scaling methods publications with some exceptions. We found that the following parameters were the best for all the scaling methods. All scaling methods use the Adam optimizer with batch size 256 for CIFAR and 4096 for ImageNet. The learning rate was set to 10^{-3} for temperature scaling Guo et al. (2017) and Platt

Table A4: Tab. 1 Extension: ImageNet - InceptionResNetV2

Binn.	sCW(?)	size	Acc_{top1} ↑	Acc_{top5} ↑	$cwECE_{\frac{1}{K}}$ ↓	$top1ECE$ ↓	NLL
Baseline	✗	-	**80.33** ± 0.15	**95.10** ± 0.15	0.0486 ± 0.0003	0.0357 ± 0.0009	0.8406 ± 0.0095
Eq. Mass	✗	25k	7.78 ± 0.15	27.92 ± 0.71	0.0016 ± 0.0001	0.0606 ± 0.0013	3.5960 ± 0.0137
Eq. Mass	✓	1k	5.02 ± 0.13	26.75 ± 0.37	0.0022 ± 0.0001	0.0353 ± 0.0012	3.5272 ± 0.0142
Eq. Size	✗	25k	78.52 ± 0.15	89.06 ± 0.13	0.1344 ± 0.0005	0.0547 ± 0.0017	1.5159 ± 0.0136
Eq. Size	✓	1k	80.14 ± 0.23	88.99 ± 0.12	0.1525 ± 0.0023	0.0279 ± 0.0043	1.2671 ± 0.0130
I-Max	✗	25k	80.27 ± 0.17	95.01 ± 0.19	0.0342 ± 0.0006	0.0329 ± 0.0010	0.8499 ± 0.0105
I-Max	✓	1k	80.20 ± 0.18	94.86 ± 0.17	**0.0302** ± 0.0041	**0.0200** ± 0.0033	**0.7860** ± 0.0208

Table A5: Tab. 1 Extension: ImageNet - DenseNet

Binn.	sCW(?)	size	Acc_{top1} ↑	Acc_{top5} ↑	$cwECE_{\frac{1}{K}}$ ↓	$top1ECE$ ↓	NLL
Baseline	✗	-	**77.21** ± 0.12	**93.51** ± 0.14	0.0502 ± 0.0006	0.0571 ± 0.0014	0.9418 ± 0.0120
Eq. Mass	✗	25k	18.48 ± 0.19	45.12 ± 0.26	0.0017 ± 0.0000	0.1657 ± 0.0020	2.9437 ± 0.0162
Eq. Mass	✓	1k	17.21 ± 0.47	45.69 ± 1.22	0.0054 ± 0.0004	0.1572 ± 0.0047	2.9683 ± 0.0561
Eq. Size	✗	25k	74.34 ± 0.28	88.27 ± 0.11	0.1272 ± 0.0011	0.0660 ± 0.0018	1.6699 ± 0.0165
Eq. Size	✓	1k	77.06 ± 0.28	88.22 ± 0.10	0.1519 ± 0.0016	0.0230 ± 0.0050	1.3948 ± 0.0105
I-Max	✗	25k	77.07 ± 0.13	93.40 ± 0.17	0.0334 ± 0.0004	0.0577 ± 0.0008	0.9492 ± 0.0130
I-Max	✓	1k	77.13 ± 0.14	93.34 ± 0.17	**0.0263** ± 0.0119	**0.0201** ± 0.0088	**0.9229** ± 0.0103

scaling Platt (1999), 0.0001 for vector scaling Guo et al. (2017) and 10^{-5} for matrix scaling Guo et al. (2017). Matrix scaling was further regularized as suggested by Kull et al. (2019) with a L_2 loss on the bias vector and the off-diagonal elements of the weighting matrix. BBQ Naeini et al. (2015), isotonic regression Zadrozny & Elkan (2002) and Beta Kull et al. (2017) hyper-parameters were taken directly from Wenger et al. (2020).

A7.3 TRAINING I-MAX BINNING

The I-Max bin optimization started from k-means++ initialization, which uses JSD instead of Euclidean metric as the distance measure, see Sec. A3.2. Then, we iteratively and alternatively updated $\{g_m\}$ and $\{\phi_m\}$ according to (A12) until 200 iterations. With the attained bin edges $\{g_m\}$, we set the bin representatives $\{r_m\}$ based on the empirical frequency of class-1. If a scaling method is combined with binning, an alternative setting for $\{r_m\}$ is to take the averaged prediction probabilities based on the scaled logits of the samples per bin, e.g., in Tab. 2 in Sec. 4.2. Note that, for CW binning in 1, the number of samples from the minority class is too few, i.e., 25k/1k = 25. We only have about $25/15 \approx 2$ samples per bin, which are too few to use empirical frequency estimates. Alternatively, we set $\{r_m\}$ based on the raw prediction probabilities.

A8 EXTEND TAB. 1 FOR MORE DATASETS AND MODELS.

Tab. 1 in Sec. 4.1 of the main paper is replicated across datasets and models, where the basic setting remains the same. Specifically, three different ImageNet models can be found in Tab. A4, Tab. A5 and Tab. A6. Three models for CIFAR100 can be found in Tab. A7, Tab. A8 and Tab. A9. Similarly, CIFAR10 models can be found in Tab. A10, Tab. A11 and Tab. A12. The accuracy degradation of Eq. Mass reduces as the dataset has less number of classes, e.g., CIFAR10. This is because the class imbalance under one-vs-rest conversion becomes less critical in CIFAR10 than ImageNet. Nevertheless, its accuracy losses are still much larger than the other binning schemes, i.e., Eq. Size and I-Max binning. Therefore, its calibration performance is not considered for comparison. Overall, the observations of Tab. A4- A12 are similar to Tab. 1, showing the stable performance gains of I-Max binning across datasets and models.

Table A6: Tab. 1 Extension: ImageNet - ResNet152

Binn.	sCW(?)	size	Acc_{top1} ↑	Acc_{top5} ↑	$_{CW}ECE_{\frac{1}{K}}$ ↓	$_{top1}ECE$ ↓	NLL
Baseline	✗	-	**78.33** ± 0.17	**94.00** ± 0.14	0.0500 ± 0.0004	0.0512 ± 0.0018	0.8760 ± 0.0133
Eq. Mass	✗	25k	17.45 ± 0.10	44.87 ± 0.37	0.0017 ± 0.0000	0.1555 ± 0.0010	2.9526 ± 0.0168
Eq. Mass	✓	1k	16.25 ± 0.54	45.53 ± 0.81	0.0064 ± 0.0004	0.1476 ± 0.0054	2.9471 ± 0.0556
Eq. Size	✗	25k	75.50 ± 0.28	88.85 ± 0.19	0.1223 ± 0.0008	0.0604 ± 0.0017	1.6012 ± 0.0252
Eq. Size	✓	1k	78.24 ± 0.16	88.81 ± 0.19	0.1480 ± 0.0015	0.0286 ± 0.0053	1.3308 ± 0.0178
I-Max	✗	25k	78.24 ± 0.16	93.91 ± 0.17	0.0334 ± 0.0005	0.0521 ± 0.0015	0.8842 ± 0.0135
I-Max	✓	1k	78.19 ± 0.21	93.82 ± 0.17	**0.0295** ± 0.0030	**0.0196** ± 0.0049	**0.8638** ± 0.0135

Table A7: Tab. 1 Extension: CIFAR100 - WRN

Binn.	sCW(?)	size	Acc_{top1} ↑	$_{CW}ECE_{\frac{1}{K}}$ ↓	$_{top1}ECE$ ↓	NLL
Baseline	✗	-	**81.35** ± 0.13	0.1113 ± 0.0010	0.0748 ± 0.0018	0.7816 ± 0.0076
Eq. Mass	✗	5k	60.78 ± 0.62	0.0129 ± 0.0010	0.4538 ± 0.0074	1.1084 ± 0.0117
Eq. Mass	✓	1k	62.04 ± 0.53	0.0252 ± 0.0032	0.4744 ± 0.0049	1.1789 ± 0.0308
Eq. Size	✗	5k	80.39 ± 0.36	0.1143 ± 0.0013	0.0783 ± 0.0032	1.0772 ± 0.0184
Eq. Size	✓	1k	81.12 ± 0.15	0.1229 ± 0.0030	0.0273 ± 0.0055	1.0165 ± 0.0105
I-Max	✗	5k	81.22 ± 0.12	0.0692 ± 0.0020	0.0751 ± 0.0024	0.7878 ± 0.0090
I-Max	✓	1k	81.30 ± 0.22	**0.0518** ± 0.0036	**0.0231** ± 0.0067	**0.7593** ± 0.0085

Table A8: Tab. 1 Extension: CIFAR100 - ResNeXt8x64

Binn.	sCW(?)	size	Acc_{top1} ↑	$_{CW}ECE_{\frac{1}{K}}$ ↓	$_{top1}ECE$ ↓	NLL
Baseline	✗	-	81.93 ± 0.08	0.0979 ± 0.0015	0.0590 ± 0.0028	0.7271 ± 0.0026
Eq. Mass	✗	5k	63.02 ± 0.54	0.0131 ± 0.0012	0.4764 ± 0.0057	1.0535 ± 0.0191
Eq. Mass	✓	1k	64.48 ± 0.64	0.0265 ± 0.0011	0.4980 ± 0.0070	1.1232 ± 0.0277
Eq. Size	✗	5k	80.81 ± 0.26	0.1070 ± 0.0008	0.0700 ± 0.0030	1.0178 ± 0.0066
Eq. Size	✓	1k	81.99 ± 0.21	0.1195 ± 0.0013	0.0230 ± 0.0033	0.9556 ± 0.0071
I-Max	✗	5k	**81.99** ± 0.08	0.0601 ± 0.0027	0.0627 ± 0.0034	0.7318 ± 0.0026
I-Max	✓	1k	81.96 ± 0.14	**0.0549** ± 0.0081	**0.0205** ± 0.0074	**0.7127** ± 0.0040

Table A9: Tab. 1 Extension: CIFAR100 - DenseNet

Binn.	sCW(?)	size	Acc_{top1} ↑	$_{CW}ECE_{\frac{1}{K}}$ ↓	$_{top1}ECE$ ↓	NLL
Baseline	✗	-	**82.36** ± 0.26	0.1223 ± 0.0008	0.0762 ± 0.0015	0.7542 ± 0.0143
Eq. Mass	✗	5k	57.23 ± 0.50	0.0117 ± 0.0011	0.4173 ± 0.0051	1.1819 ± 0.0228
Eq. Mass	✓	1k	58.11 ± 0.21	0.0233 ± 0.0005	0.4339 ± 0.0024	1.2049 ± 0.0405
Eq. Size	✗	5k	81.35 ± 0.23	0.1108 ± 0.0017	0.0763 ± 0.0029	1.0207 ± 0.0183
Eq. Size	✓	1k	82.22 ± 0.30	0.1192 ± 0.0024	0.0219 ± 0.0021	0.9482 ± 0.0137
I-Max	✗	5k	82.35 ± 0.26	0.0740 ± 0.0007	0.0772 ± 0.0010	0.7618 ± 0.0145
I-Max	✓	1k	82.32 ± 0.22	**0.0546** ± 0.0122	**0.0189** ± 0.0071	**0.7022** ± 0.0124

Table A10: Tab. 1 Extension: CIFAR10 - WRN

Binn.	sCW(?)	size	Acc_{top1} ↑	$_{CW}ECE_{\frac{1}{K}}$ ↓	$_{top1}ECE$ ↓	NLL
Baseline	✗	-	**96.12** ± 0.14	0.0457 ± 0.0011	0.0288 ± 0.0007	0.1682 ± 0.0062
Eq. Mass	✗	5k	91.06 ± 0.54	0.0180 ± 0.0045	0.0794 ± 0.0066	0.2066 ± 0.0091
Eq. Mass	✓	1k	91.24 ± 0.27	0.0212 ± 0.0009	0.0836 ± 0.0091	0.2252 ± 0.0220
Eq. Size	✗	5k	96.04 ± 0.14	0.0344 ± 0.0008	0.0290 ± 0.0013	0.2231 ± 0.0074
Eq. Size	✓	1k	96.04 ± 0.15	0.0278 ± 0.0021	0.0105 ± 0.0028	0.2744 ± 0.0812
I-Max	✗	5k	96.10 ± 0.14	0.0329 ± 0.0011	0.0276 ± 0.0007	0.1704 ± 0.0067
I-Max	✓	1k	96.06 ± 0.13	**0.0304** ± 0.0012	**0.0113** ± 0.0039	**0.1595** ± 0.0604

Table A11: Tab. 1 Extension: CIFAR10 - ResNext8x64

Binn.	sCW(?)	size	Acc_{top1} ↑	$_{CW}ECE_{\frac{1}{K}}$ ↓	$_{top1}ECE$ ↓	NLL
Baseline	✗	-	**96.30** ± 0.18	0.0485 ± 0.0014	0.0201 ± 0.0021	**0.1247** ± 0.0058
Eq. Mass	✗	5k	89.40 ± 0.55	0.0168 ± 0.0037	0.0589 ± 0.0052	0.2011 ± 0.0085
Eq. Mass	✓	1k	89.85 ± 0.61	0.0269 ± 0.0051	0.0676 ± 0.0127	0.2208 ± 0.0172
Eq. Size	✗	5k	96.30 ± 0.20	0.0274 ± 0.0013	0.0174 ± 0.0013	0.1613 ± 0.0101
Eq. Size	✓	1k	96.17 ± 0.24	0.0288 ± 0.0039	0.0114 ± 0.0025	0.2495 ± 0.0571
I-Max	✗	5k	96.26 ± 0.20	**0.0240** ± 0.0020	0.0167 ± 0.0014	0.1264 ± 0.0066
I-Max	✓	1k	96.22 ± 0.21	0.0254 ± 0.0030	**0.0104** ± 0.0025	0.1397 ± 0.0276

Table A12: Tab. 1 Extension Dataset: CIFAR10 - DenseNet

Binn.	sCW(?)	size	Acc_{top1} ↑	$_{CW}ECE_{\frac{1}{K}}$ ↓	$_{top1}ECE$ ↓	NLL
Baseline	✗	-	96.65 ± 0.09	0.0404 ± 0.001	0.0253 ± 0.0009	0.1564 ± 0.0075
Eq. Mass	✓	1k	88.80 ± 0.47	0.0233 ± 0.0024	0.0637 ± 0.0023	0.2694 ± 0.0274
Eq. Mass	✗	5k	89.51 ± 0.36	0.0137 ± 0.0039	0.0657 ± 0.0041	0.2283 ± 0.0101
Eq. Size	✓	1k	96.64 ± 0.22	0.0262 ± 0.0035	0.0101 ± 0.0035	0.2465 ± 0.0543
Eq. Size	✗	5k	96.74 ± 0.07	0.0301 ± 0.0012	0.0242 ± 0.0013	0.1912 ± 0.0075
I-Max	✓	1k	96.59 ± 0.32	0.0261 ± 0.0025	0.0098 ± 0.0027	0.1208 ± 0.0044
I-Max	✗	5k	96.71 ± 0.09	0.0284 ± 0.0013	0.0233 ± 0.0009	0.1608 ± 0.0086

A9 EXTEND TAB. 2 FOR MORE SCALING METHODS, DATASETS AND MODELS

Tab. 2 in Sec. 4.2 of the main paper is replicated across datasets and models, and include more scaling methods for comparison. The three binning methods all use the shared CW strategy, therefore 1k calibration samples are sufficient. The basic setting remains the same as Tab. 2. Three different ImageNet models can be found in Tab. A13, Tab. A14 and Tab. A15. Three models for CIFAR100 can be found in Tab. A16, Tab. A17 and Tab. A18. Similarly, CIFAR10 models can be found in Tab. A19, Tab. A20 and Tab. A21.

Being analogous to Tab. 2, we observe that in most cases matrix scaling performs the best at the accuracy, but fail to provide satisfactory calibration performance measured by ECEs, Brier scores and NLLs. Among the scaling methods, GP Wenger et al. (2020) is the top performing one. Among the binning schemes, our proposal of I-Max binning outperforms Eq. Mass and Eq. Size at both calibration and accuracy. The combination of I-Max binning with GP excels at the ECE performance. It achieves slightly worse results than GP alone at Brier scores and NLLs. This relates to the reduced precision of prediction probabilities after binning. Note that, among all methods, Eq. Mass binning and VUC Kumar et al. (2019) suffer from severe accuracy degradation after multi-class calibration. The reason behind Eq. Mass binning was discussed in Sec. 3.3 of the main paper. As VUC Kumar et al. (2019) combined Eq. Mass binning with Platt scaling, its accuracy loss is due to the same reason. Given their poor accuracy, they are not in the scope of calibration performance comparison.

We also observe that GP performs better at NLL/Brier than the I-Max variants. The quantized nature of binning causes worse performance than GP at these metrics though improve with increasing the number of bins, e.g., reducing 0.7787 of I-Max w. GP in Tab. A13 to 0.7681 after using 100 bins. Note, that unlike ECE, NLL/Brier are not direct measures of calibration and care more about accuracy. For example, for N predictions assigned confidence 1 containing M mistakes, the *calibrated* confidence is $M/N < 1$. NLL/Brier is non-zero only for the M wrong predictions, despite all N predictions are miscalibrated.

Table A13: Tab. 2 Extension: ImageNet - InceptionResnetV2

Calibrator	Acc_{top1} ↑	Acc_{top5} ↑	$_{CW}ECE_{\frac{1}{K}}$ ↓	$_{top1}ECE$ ↓	NLL	Brier
Baseline	80.33 ± 0.15	95.10 ± 0.15	0.0486 ± 0.0003	0.0357 ± 0.0009	0.8406 ± 0.0095	0.1115 ± 0.0007
			25k Calibration Samples			
BBQ (Naeini et al., 2015)	53.89 ± 0.30	88.63 ± 0.22	0.0287 ± 0.0009	0.2689 ± 0.0033	1.7104 ± 0.0370	0.3273 ± 0.0016
Beta Kull et al. (2017)	80.47 ± 0.14	94.84 ± 0.15	0.0706 ± 0.0003	0.0346 ± 0.0022	0.9038 ± 0.0270	0.1174 ± 0.0010
Isotonic Reg. Zadrozny & Elkan (2002)	80.08 ± 0.19	93.46 ± 0.20	0.0644 ± 0.0014	0.0468 ± 0.0020	1.8375 ± 0.0587	0.1203 ± 0.0012
Platt Platt (1999)	80.48 ± 0.14	95.18 ± 0.12	0.0597 ± 0.0007	0.0775 ± 0.0015	0.8083 ± 0.0106	0.1205 ± 0.0010
VUC Kumar et al. (2019)	6.72 ± 0.21	27.36 ± 0.15	0.0012 ± 0.0001	0.0489 ± 0.0022	3.9514 ± 0.0186	0.0653 ± 0.0021
Vec Scal. Kull et al. (2019)	80.53 ± 0.19	95.18 ± 0.16	0.0494 ± 0.0002	0.0300 ± 0.0010	0.8269 ± 0.0097	0.1106 ± 0.0007
Mtx Scal. Kull et al. (2019)	**80.78** ± 0.18	**95.38** ± 0.15	0.0508 ± 0.0003	0.0282 ± 0.0014	0.8042 ± 0.0100	0.1090 ± 0.0006
BWS Ji et al. (2019)	80.33 ± 0.16	95.10 ± 0.16	0.0561 ± 0.0008	0.044 ± 0.0019	0.8273 ± 0.0105	0.1129 ± 0.0009
ETS-MnM Zhang et al. (2020)	80.33 ± 0.16	95.10 ± 0.16	0.0479 ± 0.0004	0.0358 ± 0.0009	0.8426 ± 0.0097	0.1115 ± 0.0008
			1k Calibration Samples			
TS Guo et al. (2017)	80.33 ± 0.16	95.10 ± 0.16	0.0559 ± 0.0015	0.0439 ± 0.0022	0.8293 ± 0.0107	0.1134 ± 0.0010
GP Wenger et al. (2020)	80.33 ± 0.15	95.11 ± 0.15	0.0485 ± 0.0035	0.0186 ± 0.0034	**0.7556** ± 0.0118	**0.1069** ± 0.0007
Eq. Mass	5.02 ± 0.13	26.75 ± 0.37	0.0022 ± 0.0001	0.0353 ± 0.0012	3.5272 ± 0.0142	0.0489 ± 0.0012
Eq. Size	80.14 ± 0.23	88.99 ± 0.12	0.1525 ± 0.0023	0.0279 ± 0.0043	1.2671 ± 0.0130	0.1115 ± 0.0011
I-Max	80.20 ± 0.18	94.86 ± 0.17	0.0302 ± 0.0041	0.0200 ± 0.0033	0.7860 ± 0.0208	0.1116 ± 0.0008
Eq. Mass w. TS	5.02 ± 0.13	26.87 ± 0.43	0.0023 ± 0.0001	0.0357 ± 0.0012	3.5454 ± 0.0222	0.0490 ± 0.0012
Eq. Mass w. GP	5.02 ± 0.13	26.87 ± 0.43	0.0022 ± 0.0001	0.0353 ± 0.0012	3.4778 ± 0.0217	0.0489 ± 0.0012
Eq. Size w. TS	80.26 ± 0.18	88.99 ± 0.12	0.1470 ± 0.0007	0.0391 ± 0.0038	1.2721 ± 0.0116	0.1136 ± 0.0012
Eq. Size w. GP	80.26 ± 0.18	88.99 ± 0.12	0.1508 ± 0.0021	0.0140 ± 0.0056	1.2661 ± 0.0121	0.1105 ± 0.0008
I-Max w. TS	80.20 ± 0.18	94.87 ± 0.19	0.0354 ± 0.0124	0.0402 ± 0.0019	0.8339 ± 0.0108	0.1142 ± 0.0009
I-Max w. GP	80.20 ± 0.18	94.87 ± 0.19	**0.0300** ± 0.0041	**0.0121** ± 0.0048	0.7787 ± 0.0102	0.1111 ± 0.0006

Table A14: Tab. 2 Extension: ImageNet - DenseNet

Calibrator	Acc_{top1} ↑	Acc_{top5} ↑	$_{CW}ECE_{\frac{1}{K}}$ ↓	$_{top1}ECE$ ↓	NLL	Brier
Baseline	77.21 ± 0.12	93.51 ± 0.14	0.0502 ± 0.0006	0.0571 ± 0.0014	0.9418 ± 0.0120	0.1228 ± 0.0009
			25k Calibration Samples			
BBQ (Naeini et al., 2015)	54.69 ± 0.42	86.55 ± 0.19	0.0274 ± 0.0007	0.2819 ± 0.0050	1.9805 ± 0.0500	0.3355 ± 0.0026
Beta Kull et al. (2017)	77.35 ± 0.22	93.34 ± 0.17	0.0494 ± 0.0008	0.0253 ± 0.0022	0.9768 ± 0.0254	0.1209 ± 0.0010
Isotonic Reg. Zadrozny & Elkan (2002)	76.81 ± 0.24	91.98 ± 0.17	0.0577 ± 0.0003	0.0490 ± 0.0021	1.9819 ± 0.0634	0.1281 ± 0.0012
Platt Platt (1999)	77.43 ± 0.21	93.64 ± 0.15	0.0448 ± 0.0010	0.0906 ± 0.0022	0.9168 ± 0.0139	0.1297 ± 0.0012
VUC Kumar et al. (2019)	17.98 ± 0.24	45.65 ± 0.33	0.0014 ± 0.0001	0.1607 ± 0.0026	2.9832 ± 0.0228	0.1742 ± 0.0023
Vec Scal. Kull et al. (2019)	77.44 ± 0.20	93.62 ± 0.17	0.0492 ± 0.0006	0.0516 ± 0.0018	0.9276 ± 0.0134	0.1208 ± 0.0011
Mtx Scal. Kull et al. (2019)	**77.56** ± 0.11	**93.81** ± 0.15	0.0498 ± 0.0006	0.0491 ± 0.0015	0.9159 ± 0.0158	0.1202 ± 0.0016
BWS Ji et al. (2019)	77.21 ± 0.12	93.51 ± 0.14	0.0395 ± 0.0007	0.0301 ± 0.0012	0.9106 ± 0.0116	0.1197 ± 0.0008
ETS-MnM Zhang et al. (2020)	77.21 ± 0.12	93.51 ± 0.14	0.0357 ± 0.0008	0.0234 ± 0.0015	0.9188 ± 0.0103	0.1194 ± 0.0006
			1k Calibration Samples			
TS Guo et al. (2017)	77.21 ± 0.12	93.51 ± 0.15	0.0375 ± 0.0007	0.0300 ± 0.0019	0.9116 ± 0.0110	0.1197 ± 0.0008
GP Wenger et al. (2020)	77.22 ± 0.12	93.51 ± 0.13	0.0394 ± 0.0037	0.0268 ± 0.0035	**0.8914** ± 0.0120	**0.1188** ± 0.0005
Eq. Mass	17.21 ± 0.47	45.69 ± 1.22	0.0054 ± 0.0004	0.1572 ± 0.0047	2.9683 ± 0.0561	0.1671 ± 0.0046
Eq. Size	77.06 ± 0.28	88.22 ± 0.10	0.1519 ± 0.0016	0.0230 ± 0.0050	1.3948 ± 0.0105	0.1206 ± 0.0013
I-Max	77.13 ± 0.14	93.34 ± 0.17	0.0263 ± 0.0119	0.0201 ± 0.0088	0.9229 ± 0.0103	0.1201 ± 0.0010
Eq. Mass w. TS	17.21 ± 0.47	45.73 ± 1.07	0.0054 ± 0.0004	0.1571 ± 0.0047	2.9104 ± 0.0482	0.1671 ± 0.0046
Eq. Mass w. GP	17.21 ± 0.47	45.71 ± 1.08	0.0054 ± 0.0004	0.1571 ± 0.0047	2.9090 ± 0.0485	0.1671 ± 0.0046
Eq. Size w. TS	77.19 ± 0.12	88.22 ± 0.10	0.1464 ± 0.0005	0.0241 ± 0.0032	1.3928 ± 0.0106	0.1201 ± 0.0008
Eq. Size w. GP	77.19 ± 0.12	88.22 ± 0.10	0.1527 ± 0.0007	0.0215 ± 0.0037	1.3944 ± 0.0094	0.1200 ± 0.0005
I-Max w. TS	77.13 ± 0.14	93.34 ± 0.17	0.0320 ± 0.0026	0.0245 ± 0.0024	0.9242 ± 0.0117	0.1201 ± 0.0007
I-Max w. GP	77.13 ± 0.14	93.34 ± 0.17	**0.0258** ± 0.0100	**0.0204** ± 0.0021	0.9200 ± 0.0124	0.1201 ± 0.0005

Table A15: Tab. 2 Extension: ImageNet - ResNet152

Calibrator	$\text{Acc}_{\text{top1}} \uparrow$	$\text{Acc}_{\text{top5}} \uparrow$	$\text{cwECE}_{\frac{1}{K}} \downarrow$	$\text{top1ECE} \downarrow$	NLL	Brier
Baseline	78.33 ± 0.17	94.00 ± 0.14	0.05 ± 0.0004	0.0512 ± 0.0018	0.8760 ± 0.0133	0.1174 ± 0.0013
				25k Calibration Samples		
BBQ (Naeini et al., 2015)	55.04 ± 0.26	87.15 ± 0.21	0.0278 ± 0.0004	0.2840 ± 0.0028	1.8490 ± 0.0474	0.3361 ± 0.0014
Beta Kull et al. (2017)	78.44 ± 0.16	93.71 ± 0.20	0.0507 ± 0.0012	0.0264 ± 0.0010	0.9365 ± 0.0249	0.1174 ± 0.0013
Isotonic Reg. Zadrozny & Elkan (2002)	77.97 ± 0.07	92.33 ± 0.32	0.0590 ± 0.0016	0.0486 ± 0.0027	1.9437 ± 0.1020	0.1248 ± 0.0015
Platt Platt (1999)	78.56 ± 0.15	94.06 ± 0.19	0.0458 ± 0.0009	0.0852 ± 0.0021	0.8557 ± 0.0159	0.1246 ± 0.0015
VUC Kumar et al. (2019)	16.50 ± 0.13	45.11 ± 0.42	0.0013 ± 0.0000	0.1463 ± 0.0012	2.9838 ± 0.0154	0.1599 ± 0.0012
Vec Scal. Kull et al. (2019)	$\mathbf{78.61} \pm 0.21$	94.12 ± 0.18	0.0490 ± 0.0003	0.0469 ± 0.0017	0.8625 ± 0.0143	0.1159 ± 0.0012
Mtx Scal. Kull et al. (2019)	78.54 ± 0.23	$\mathbf{94.14} \pm 0.22$	0.0496 ± 0.0004	0.0443 ± 0.0026	0.8583 ± 0.0180	0.1160 ± 0.0016
BWS Ji et al. (2019)	78.33 ± 0.18	94.00 ± 0.15	0.0402 ± 0.0005	0.0277 ± 0.0019	0.8488 ± 0.0127	0.1147 ± 0.0012
ETS-MnM Zhang et al. (2020)	78.33 ± 0.18	94.00 ± 0.15	0.0366 ± 0.0007	0.0198 ± 0.0006	0.8609 ± 0.0117	0.1145 ± 0.0011
				1k Calibration Samples		
TS Guo et al. (2017)	78.33 ± 0.18	94.00 ± 0.15	0.0378 ± 0.0007	0.0285 ± 0.0023	0.8505 ± 0.0126	0.1147 ± 0.0012
GP Wenger et al. (2020)	78.33 ± 0.17	94.00 ± 0.14	0.0403 ± 0.0021	0.0202 ± 0.0030	$\mathbf{0.8366} \pm 0.0118$	$\mathbf{0.1138} \pm 0.0012$
Eq. Mass	16.25 ± 0.54	45.53 ± 0.81	0.0064 ± 0.0004	0.1476 ± 0.0054	2.9471 ± 0.0556	0.1579 ± 0.0052
Eq. Size	78.24 ± 0.16	88.81 ± 0.19	0.1480 ± 0.0015	0.0286 ± 0.0053	1.3308 ± 0.0178	0.1167 ± 0.0011
I-Max	78.19 ± 0.21	93.82 ± 0.17	0.0295 ± 0.0030	0.0196 ± 0.0049	0.8638 ± 0.0135	0.1157 ± 0.0012
Eq. Mass w. TS	16.25 ± 0.54	45.54 ± 0.71	0.0064 ± 0.0004	0.1476 ± 0.0054	2.9024 ± 0.0401	0.1579 ± 0.0052
Eq. Mass w. GP	16.25 ± 0.54	45.52 ± 0.74	0.0064 ± 0.0004	0.1475 ± 0.0054	2.9021 ± 0.040	0.1579 ± 0.0052
Eq. Size w. TS	78.27 ± 0.17	88.81 ± 0.19	0.1428 ± 0.0007	0.0225 ± 0.0022	1.3286 ± 0.0171	0.1153 ± 0.0013
Eq. Size w. GP	78.27 ± 0.17	88.81 ± 0.19	0.1475 ± 0.0016	0.0138 ± 0.0049	1.330 ± 0.0171	0.1150 ± 0.0012
I-Max w. TS	78.19 ± 0.21	93.82 ± 0.17	$\mathbf{0.0281} \pm 0.0029$	0.0219 ± 0.0016	0.8637 ± 0.0125	0.1152 ± 0.0015
I-Max w. GP	78.19 ± 0.21	93.82 ± 0.17	0.0296 ± 0.0029	$\mathbf{0.0144} \pm 0.0050$	0.8602 ± 0.0127	0.1150 ± 0.0014

Table A16: Tab. 2 Extension: CIFAR100 - WRN

Calibrator	$\text{Acc}_{\text{top1}} \uparrow$	$\text{cwECE}_{\frac{1}{K}} \downarrow$	$\text{top1ECE} \downarrow$	NLL	Brier
Baseline	81.35 ± 0.13	0.1113 ± 0.0010	0.0748 ± 0.0018	0.7816 ± 0.0076	0.1082 ± 0.0021
			5k Calibration Samples		
BBQ (Naeini et al., 2015)	80.44 ± 0.19	0.0576 ± 0.0018	0.0672 ± 0.0044	1.7976 ± 0.0443	0.1297 ± 0.0019
Beta Kull et al. (2017)	81.44 ± 0.17	0.0952 ± 0.0006	0.0379 ± 0.0027	0.7624 ± 0.0148	0.1018 ± 0.0016
Isotonic Reg. Zadrozny & Elkan (2002)	81.25 ± 0.27	0.0597 ± 0.0029	0.0487 ± 0.0040	1.4015 ± 0.0748	0.1059 ± 0.0013
Platt Platt (1999)	81.35 ± 0.12	0.0827 ± 0.0014	0.0585 ± 0.0038	0.7491 ± 0.0073	0.1026 ± 0.0017
VUC Kumar et al. (2019)	61.92 ± 1.11	0.0104 ± 0.0008	0.4660 ± 0.0110	1.1901 ± 0.0231	0.4570 ± 0.0079
Vec Scal. Kull et al. (2019)	81.35 ± 0.21	0.1063 ± 0.0013	0.0687 ± 0.0029	0.7619 ± 0.0064	0.1055 ± 0.0017
Mtx Scal. Kull et al. (2019)	$\mathbf{81.44} \pm 0.20$	0.1085 ± 0.0008	0.0692 ± 0.0033	0.7531 ± 0.0078	0.1059 ± 0.0019
BWS Ji et al. (2019)	81.35 ± 0.14	0.1069 ± 0.0009	0.0451 ± 0.0028	0.737 ± 0.0057	0.1037 ± 0.0017
ETS-MnM Zhang et al. (2020)	81.35 ± 0.14	0.0976 ± 0.0019	0.0451 ± 0.0027	0.7695 ± 0.0052	0.1027 ± 0.0020
			1k Calibration Samples		
TS Guo et al. (2017)	81.35 ± 0.14	0.0911 ± 0.0036	0.0511 ± 0.0059	0.7527 ± 0.0074	0.1036 ± 0.0025
GP Wenger et al. (2020)	81.34 ± 0.12	0.1074 ± 0.0043	0.0358 ± 0.0039	$\mathbf{0.6943} \pm 0.0025$	$\mathbf{0.0996} \pm 0.0019$
Eq. Mass	62.04 ± 0.53	0.0252 ± 0.0032	0.4744 ± 0.0049	1.1789 ± 0.0308	0.4606 ± 0.0034
Eq. Size	81.12 ± 0.15	0.1229 ± 0.0030	0.0273 ± 0.0055	1.0165 ± 0.0105	0.1039 ± 0.0017
I-Max	81.30 ± 0.22	0.0518 ± 0.0036	0.0231 ± 0.0067	0.7593 ± 0.0085	0.1016 ± 0.0018
Eq. Mass w. TS	62.04 ± 0.53	0.0253 ± 0.0034	0.4764 ± 0.0052	1.0990 ± 0.0184	0.4624 ± 0.0037
Eq. Mass w. GP	62.04 ± 0.53	0.0252 ± 0.0032	0.4749 ± 0.0051	1.1110 ± 0.0226	0.4610 ± 0.0036
Eq. Size w. TS	81.31 ± 0.15	0.1197 ± 0.0029	0.0362 ± 0.0065	1.0106 ± 0.0113	0.1038 ± 0.0026
Eq. Size w. GP	81.31 ± 0.15	0.1205 ± 0.0025	0.0189 ± 0.0054	1.0161 ± 0.0115	0.1032 ± 0.0020
I-Max w. TS	81.34 ± 0.20	$\mathbf{0.051} \pm 0.0035$	0.0365 ± 0.0067	0.7716 ± 0.0066	0.1025 ± 0.0021
I-Max w. GP	81.34 ± 0.20	0.0559 ± 0.0089	$\mathbf{0.0179} \pm 0.0046$	0.7609 ± 0.0080	0.1014 ± 0.0014

Table A17: Tab. 2 Extension: CIFAR100 - ResNeXt

Calibrator	$Acc_{top1}\uparrow$	$cwECE_{\frac{1}{K}}\downarrow$	$_{top1}ECE\downarrow$	NLL	Brier
Baseline	81.93 ± 0.08	0.0979 ± 0.0015	0.0590 ± 0.0028	0.7271 ± 0.0026	0.0984 ± 0.0022
			5k Calibration Samples		
BBQ (Naeini et al., 2015)	81.06 ± 0.30	0.0564 ± 0.0013	0.0608 ± 0.0058	1.6878 ± 0.0546	0.1176 ± 0.0022
Beta Kull et al. (2017)	82.19 ± 0.31	0.0918 ± 0.0020	0.0368 ± 0.0047	0.7095 ± 0.0074	0.0947 ± 0.0024
Isotonic Reg. Zadrozny & Elkan (2002)	81.89 ± 0.19	0.0619 ± 0.0023	0.0503 ± 0.0036	1.3015 ± 0.0656	0.0995 ± 0.0018
Platt Platt (1999)	82.28 ± 0.21	0.0790 ± 0.0025	0.0534 ± 0.0047	0.7050 ± 0.0045	0.0961 ± 0.0026
VUC Kumar et al. (2019)	64.24 ± 0.62	0.0109 ± 0.0017	0.4896 ± 0.0059	1.1010 ± 0.0237	0.4729 ± 0.0046
Vec Scal. Kull et al. (2019)	82.24 ± 0.27	0.0963 ± 0.0013	0.0572 ± 0.0037	0.7129 ± 0.0053	0.0973 ± 0.0021
Mtx Scal. Kull et al. (2019)	$\mathbf{82.38}\pm0.17$	0.0970 ± 0.0014	0.0578 ± 0.0040	0.7042 ± 0.0046	0.0973 ± 0.0023
BWS Ji et al. (2019)	81.93 ± 0.08	0.1045 ± 0.0015	0.0448 ± 0.0044	0.6897 ± 0.0031	0.0969 ± 0.0017
ETS-MnM Zhang et al. (2020)	81.93 ± 0.08	0.0932 ± 0.0020	0.0460 ± 0.001	0.7284 ± 0.0029	0.0963 ± 0.0022
			1k Calibration Samples		
TS Guo et al. (2017)	81.93 ± 0.08	0.0864 ± 0.0036	0.0525 ± 0.0057	0.7163 ± 0.0037	0.0975 ± 0.0020
GP Wenger et al. (2020)	81.93 ± 0.09	0.1025 ± 0.0037	0.0345 ± 0.0038	$\mathbf{0.6456}\pm0.0071$	$\mathbf{0.0927}\pm0.0019$
Eq. Mass	64.48 ± 0.64	0.0265 ± 0.0011	0.4980 ± 0.0070	1.1232 ± 0.0277	0.4770 ± 0.0051
Eq. Size	81.99 ± 0.21	0.1195 ± 0.0013	0.0230 ± 0.0033	0.9556 ± 0.0071	0.0974 ± 0.0014
I-Max	81.96 ± 0.14	0.0549 ± 0.0081	0.0205 ± 0.0074	0.7127 ± 0.0040	0.0959 ± 0.0018
Eq. Mass w. TS	64.48 ± 0.64	0.0262 ± 0.0013	0.5003 ± 0.0066	1.0468 ± 0.0228	0.4793 ± 0.0048
Eq. Mass w. GP	64.48 ± 0.64	0.0264 ± 0.0012	0.4986 ± 0.0066	1.0555 ± 0.0227	0.4776 ± 0.0048
Eq. Size w. TS	81.94 ± 0.09	0.1179 ± 0.0015	0.0343 ± 0.0029	0.9498 ± 0.0058	0.0968 ± 0.0022
Eq. Size w. GP	81.94 ± 0.09	0.1177 ± 0.0009	0.0151 ± 0.0029	0.9561 ± 0.0056	0.0959 ± 0.0018
I-Max w. TS	81.96 ± 0.14	$\mathbf{0.053}\pm0.0073$	0.0333 ± 0.0023	0.7286 ± 0.0029	0.0964 ± 0.0019
I-Max w. GP	81.96 ± 0.14	0.0532 ± 0.0077	$\mathbf{0.0121}\pm0.0026$	0.7111 ± 0.0024	0.0950 ± 0.0017

Table A18: Tab. 2 Extension Dataset: CIFAR100 - DenseNet

Calibrator	$Acc_{top1}\uparrow$	$cwECE_{\frac{1}{K}}\downarrow$	$_{top1}ECE\downarrow$	NLL	Brier
Baseline	82.36 ± 0.26	0.1223 ± 0.0008	0.0762 ± 0.0015	0.7542 ± 0.0143	0.1041 ± 0.0008
			5k Calibration Samples		
BBQ (Naeini et al., 2015)	81.56 ± 0.22	0.0567 ± 0.0020	0.0635 ± 0.0052	1.5876 ± 0.0914	0.1216 ± 0.0026
Beta Kull et al. (2017)	82.39 ± 0.28	0.0953 ± 0.0013	0.0364 ± 0.0034	0.6935 ± 0.0185	0.0966 ± 0.0008
Isotonic Reg. Zadrozny & Elkan (2002)	82.05 ± 0.26	0.0591 ± 0.0016	0.0506 ± 0.0025	1.3030 ± 0.1107	0.1019 ± 0.0014
Platt Platt (1999)	82.34 ± 0.28	0.0866 ± 0.0012	0.0491 ± 0.0012	0.6835 ± 0.0138	0.0969 ± 0.0015
VUC Kumar et al. (2019)	58.32 ± 0.90	0.0099 ± 0.0008	0.4308 ± 0.0086	1.2175 ± 0.0117	0.4324 ± 0.0065
Vec Scal. Kull et al. (2019)	82.38 ± 0.32	0.1195 ± 0.0005	0.0711 ± 0.0015	0.7362 ± 0.0173	0.1028 ± 0.0015
Mtx Scal. Kull et al. (2019)	$\mathbf{82.53}\pm0.19$	0.1214 ± 0.0006	0.0733 ± 0.0013	0.7360 ± 0.0153	0.1025 ± 0.0015
BWS Ji et al. (2019)	82.36 ± 0.27	0.1028 ± 0.0013	0.0445 ± 0.0021	0.682 ± 0.0125	0.0975 ± 0.0008
ETS-MnM Zhang et al. (2020)	82.36 ± 0.27	0.1007 ± 0.0016	0.0387 ± 0.0012	0.6986 ± 0.0111	0.0969 ± 0.0008
			1k Calibration Samples		
TS Guo et al. (2017)	82.36 ± 0.27	0.0938 ± 0.0017	0.0447 ± 0.0023	0.6851 ± 0.0115	0.0976 ± 0.0008
GP Wenger et al. (2020)	82.35 ± 0.27	0.1021 ± 0.0032	0.0338 ± 0.0011	$\mathbf{0.6536}\pm0.0120$	$\mathbf{0.0943}\pm0.0007$
Eq. Mass	58.11 ± 0.21	0.0233 ± 0.0005	0.4339 ± 0.0024	1.2049 ± 0.0405	0.4317 ± 0.0017
Eq. Size	82.22 ± 0.30	0.1192 ± 0.0024	0.0219 ± 0.0021	0.9482 ± 0.0137	0.0997 ± 0.0014
I-Max	82.32 ± 0.22	0.0546 ± 0.0122	0.0189 ± 0.0071	0.7022 ± 0.0124	0.0967 ± 0.0019
Eq. Mass w. TS	58.11 ± 0.21	0.0233 ± 0.0006	0.4347 ± 0.0024	1.1483 ± 0.0102	0.4324 ± 0.0017
Eq. Mass w. GP	58.11 ± 0.21	0.0233 ± 0.0005	0.4342 ± 0.0024	1.1508 ± 0.0099	0.4319 ± 0.0018
Eq. Size w. TS	82.40 ± 0.24	0.1134 ± 0.0014	0.0245 ± 0.0025	0.9427 ± 0.0137	0.0986 ± 0.0013
Eq. Size w. GP	82.40 ± 0.24	0.1166 ± 0.0021	0.0126 ± 0.0012	0.9455 ± 0.0142	0.0985 ± 0.0013
I-Max w. TS	82.36 ± 0.21	$\mathbf{0.048}\pm0.0090$	0.0237 ± 0.0009	0.7040 ± 0.0104	0.0967 ± 0.0010
I-Max w. GP	82.36 ± 0.21	0.0535 ± 0.0121	$\mathbf{0.0114}\pm0.0025$	0.6988 ± 0.0104	0.0964 ± 0.0010

Table A19: Tab. 2 Extension: CIFAR10 - WRN

Calibrator	$\text{Acc}_{\text{top1}} \uparrow$	$\text{cwECE}_{\frac{1}{K}} \downarrow$	$_{\text{top1}}\text{ECE} \downarrow$	NLL	Brier
Baseline	96.12 ± 0.14	0.0457 ± 0.0011	0.0288 ± 0.0007	0.1682 ± 0.0062	0.0307 ± 0.0008
			5k Calibration Samples		
BBQ (Naeini et al., 2015)	95.98 ± 0.15	0.0290 ± 0.0047	0.0198 ± 0.0044	0.2054 ± 0.0156	0.0314 ± 0.0005
Beta Kull et al. (2017)	96.31 ± 0.06	0.0504 ± 0.0015	0.0208 ± 0.0023	0.1335 ± 0.0039	0.0271 ± 0.0007
Isotonic Reg. Zadrozny & Elkan (2002)	96.20 ± 0.12	0.0241 ± 0.0021	0.0138 ± 0.0017	0.1764 ± 0.0241	0.0273 ± 0.0005
Platt Platt (1999)	96.24 ± 0.09	0.0489 ± 0.0011	0.0177 ± 0.0015	0.1359 ± 0.0039	0.0270 ± 0.0006
VUC Kumar et al. (2019)	90.18 ± 0.48	0.0213 ± 0.0036	0.0817 ± 0.0052	0.2256 ± 0.0075	0.0867 ± 0.0026
Vec Scal. Kull et al. (2019)	$\textbf{96.27} \pm 0.11$	0.0449 ± 0.0008	0.0229 ± 0.0008	0.1437 ± 0.0050	0.0286 ± 0.0007
Mtx Scal. Kull et al. (2019)	96.20 ± 0.10	0.0444 ± 0.0005	0.0277 ± 0.0007	0.1625 ± 0.0062	0.0302 ± 0.0008
BWS Ji et al. (2019)	96.12 ± 0.14	0.0467 ± 0.0012	0.0195 ± 0.0014	0.1395 ± 0.0077	0.0279 ± 0.0007
ETS-MnM Zhang et al. (2020)	96.12 ± 0.14	0.0647 ± 0.0014	0.0329 ± 0.0012	0.1478 ± 0.0038	0.0270 ± 0.0006
			1k Calibration Samples		
TS Guo et al. (2017)	96.12 ± 0.14	0.0486 ± 0.0024	0.0205 ± 0.0009	0.1385 ± 0.0048	0.0278 ± 0.0007
GP Wenger et al. (2020)	96.10 ± 0.13	0.0549 ± 0.0021	0.0146 ± 0.0022	$\textbf{0.1281} \pm 0.0055$	0.0269 ± 0.0009
Eq. Mass	91.24 ± 0.27	0.0212 ± 0.0009	0.0836 ± 0.0091	0.2252 ± 0.0220	0.0858 ± 0.0055
Eq. Size	96.04 ± 0.15	0.0278 ± 0.0021	0.0105 ± 0.0028	0.2744 ± 0.0812	0.0305 ± 0.0015
I-Max	96.06 ± 0.13	0.0304 ± 0.0012	0.0113 ± 0.0039	0.1595 ± 0.0604	0.0274 ± 0.0013
Eq. Mass w. TS	91.24 ± 0.27	0.0219 ± 0.0005	0.0837 ± 0.0092	0.1944 ± 0.0093	0.0853 ± 0.0054
Eq. Mass w. GP	91.24 ± 0.27	0.0212 ± 0.0008	0.0821 ± 0.0088	0.1918 ± 0.0091	0.0851 ± 0.0054
Eq. Size w. TS	96.13 ± 0.12	0.0286 ± 0.0018	0.0125 ± 0.0024	0.1940 ± 0.0063	0.0296 ± 0.0009
Eq. Size w. GP	96.13 ± 0.11	$\textbf{0.0266} \pm 0.0016$	$\textbf{0.0066} \pm 0.0028$	0.1917 ± 0.0058	0.0292 ± 0.0009
I-Max w. TS	96.14 ± 0.13	0.0293 ± 0.0010	0.0163 ± 0.0012	0.1417 ± 0.0047	0.0280 ± 0.0008
I-Max w. GP	96.14 ± 0.13	0.0276 ± 0.0011	0.0074 ± 0.0035	0.1331 ± 0.0042	$\textbf{0.0268} \pm 0.0008$

Table A20: Tab. 2 Extension: CIFAR10 - ResNeXt

Calibrator	$\text{Acc}_{\text{top1}} \uparrow$	$\text{cwECE}_{\frac{1}{K}} \downarrow$	$_{\text{top1}}\text{ECE} \downarrow$	NLL	Brier
Baseline	96.30 ± 0.18	0.0485 ± 0.0014	0.0201 ± 0.0021	0.1247 ± 0.0058	0.0266 ± 0.0013
			5k Calibration Samples		
BBQ (Naeini et al., 2015)	96.18 ± 0.12	0.0256 ± 0.0027	0.0166 ± 0.0020	0.1951 ± 0.0134	0.0286 ± 0.0004
Beta Kull et al. (2017)	96.31 ± 0.22	0.0517 ± 0.0011	0.0148 ± 0.0016	0.1163 ± 0.0040	0.0256 ± 0.0011
Isotonic Reg. Zadrozny & Elkan (2002)	96.35 ± 0.20	0.0241 ± 0.0016	0.0129 ± 0.0008	0.1686 ± 0.0099	0.0264 ± 0.0011
Platt Platt (1999)	96.34 ± 0.19	0.0511 ± 0.0008	0.0143 ± 0.0017	0.1159 ± 0.0042	0.0256 ± 0.0011
VUC Kumar et al. (2019)	89.17 ± 0.40	0.0141 ± 0.0028	0.0589 ± 0.0042	0.1999 ± 0.0076	0.0837 ± 0.0011
Vec Scal. Kull et al. (2019)	$\textbf{96.37} \pm 0.19$	0.0495 ± 0.0017	0.0161 ± 0.0017	0.1189 ± 0.0053	0.0258 ± 0.0013
Mtx Scal. Kull et al. (2019)	96.34 ± 0.21	0.0492 ± 0.0020	0.0187 ± 0.0020	0.1225 ± 0.0060	0.0263 ± 0.0014
BWS Ji et al. (2019)	96.3 ± 0.19	0.0514 ± 0.0013	0.015 ± 0.0008	0.1199 ± 0.0048	0.0257 ± 0.0012
ETS-MnM Zhang et al. (2020)	96.3 ± 0.19	0.0547 ± 0.0013	0.0159 ± 0.0027	0.1193 ± 0.0043	0.0257 ± 0.0011
			1k Calibration Samples		
TS Guo et al. (2017)	96.30 ± 0.19	0.0524 ± 0.0028	0.0150 ± 0.0009	0.1182 ± 0.0051	0.0257 ± 0.0012
GP Wenger et al. (2020)	96.31 ± 0.17	0.0529 ± 0.0017	0.0125 ± 0.0021	$\textbf{0.1176} \pm 0.0051$	$\textbf{0.0258} \pm 0.0011$
Eq. Mass	89.85 ± 0.61	0.0269 ± 0.0051	0.0676 ± 0.0127	0.2208 ± 0.0172	0.0841 ± 0.0042
Eq. Size	96.17 ± 0.24	0.0288 ± 0.0039	0.0114 ± 0.0025	0.2495 ± 0.0571	0.0277 ± 0.0008
I-Max	96.22 ± 0.21	0.0254 ± 0.0030	0.0104 ± 0.0025	0.1397 ± 0.0276	0.0265 ± 0.0012
Eq. Mass w. TS	89.85 ± 0.61	0.0269 ± 0.0054	0.0676 ± 0.0128	0.1966 ± 0.0104	0.0844 ± 0.0043
Eq. Mass w. GP	89.85 ± 0.61	0.0266 ± 0.0049	0.0669 ± 0.0126	0.1962 ± 0.0106	0.0841 ± 0.0043
Eq. Size w. TS	96.29 ± 0.18	0.0270 ± 0.0022	0.0062 ± 0.0024	0.1574 ± 0.0091	0.0264 ± 0.0013
Eq. Size w. GP	96.29 ± 0.18	0.0271 ± 0.0020	0.0063 ± 0.0030	0.1576 ± 0.0093	0.0264 ± 0.0012
I-Max w. TS	96.28 ± 0.19	0.0224 ± 0.0016	0.0053 ± 0.0024	0.1208 ± 0.0058	0.0259 ± 0.0012
I-Max w. GP	96.28 ± 0.19	$\textbf{0.0223} \pm 0.0018$	$\textbf{0.0052} \pm 0.0029$	0.1206 ± 0.0061	0.0259 ± 0.0012

Table A21: Tab. 2 Extension: CIFAR10 - DenseNet

Calibrator	$\text{Acc}_{\text{top1}} \uparrow$	$_{\text{cw}}\text{ECE}_{\frac{1}{K}} \downarrow$	$_{\text{top1}}\text{ECE} \downarrow$	NLL	Brier
Baseline	96.65 ± 0.09	0.0404 ± 0.0010	0.0253 ± 0.0009	0.1564 ± 0.0075	0.0259 ± 0.0007
			5k Calibration Samples		
BBQ (Naeini et al., 2015)	96.75 ± 0.19	0.0245 ± 0.0030	0.0170 ± 0.0022	0.1806 ± 0.0105	0.0279 ± 0.0010
Beta Kull et al. (2017)	96.81 ± 0.10	0.0468 ± 0.0003	0.0154 ± 0.0013	0.1151 ± 0.0042	0.0234 ± 0.0007
Isotonic Reg. Zadrozny & Elkan (2002)	96.84 ± 0.08	0.0236 ± 0.0022	0.0140 ± 0.0024	0.1501 ± 0.0137	0.0241 ± 0.0007
Platt Platt (1999)	96.82 ± 0.11	0.0459 ± 0.0007	0.0141 ± 0.0010	0.1154 ± 0.0040	0.0233 ± 0.0007
VUC Kumar et al. (2019)	88.72 ± 0.05	0.0160 ± 0.0049	0.0643 ± 0.0059	0.2213 ± 0.0063	0.0868 ± 0.0017
Vec Scal. Kull et al. (2019)	$\mathbf{96.84} \pm 0.14$	0.0413 ± 0.0014	0.0223 ± 0.0010	0.1373 ± 0.0077	0.0249 ± 0.0007
Mtx Scal. Kull et al. (2019)	96.73 ± 0.09	0.0402 ± 0.0017	0.0245 ± 0.0008	0.1531 ± 0.0081	0.0257 ± 0.0007
BWS Ji et al. (2019)	96.65 ± 0.10	0.0423 ± 0.0010	0.0188 ± 0.0016	0.1239 ± 0.0065	0.0239 ± 0.0006
ETS-MnM Zhang et al. (2020)	96.65 ± 0.10	0.0527 ± 0.0012	0.0212 ± 0.0012	0.1196 ± 0.0038	0.0230 ± 0.0007
			1k Calibration Samples		
TS Guo et al. (2017)	96.65 ± 0.10	0.0425 ± 0.0005	0.0169 ± 0.0010	0.1186 ± 0.0051	0.0237 ± 0.0006
GP Wenger et al. (2020)	96.66 ± 0.09	0.0490 ± 0.0022	0.0135 ± 0.0025	$\mathbf{0.1143} \pm 0.0048$	$\mathbf{0.0228} \pm 0.0007$
Eq. Mass	88.80 ± 0.47	0.0233 ± 0.0024	0.0637 ± 0.0023	0.2694 ± 0.0274	0.0881 ± 0.0033
Eq. Size	96.64 ± 0.22	0.0262 ± 0.0035	0.0101 ± 0.0035	0.2465 ± 0.0543	0.0256 ± 0.0003
I-Max	96.59 ± 0.32	0.0261 ± 0.0025	0.0098 ± 0.0027	0.1208 ± 0.0044	0.0239 ± 0.0005
Eq. Mass w. TS	88.80 ± 0.47	0.0234 ± 0.0026	0.0626 ± 0.0023	0.2102 ± 0.0051	0.0877 ± 0.0030
Eq. Mass w. GP	88.80 ± 0.47	0.0233 ± 0.0026	0.0634 ± 0.0025	0.2098 ± 0.0053	0.0880 ± 0.0030
Eq. Size w. TS	96.75 ± 0.10	0.0250 ± 0.0011	0.0133 ± 0.0014	0.1657 ± 0.0056	0.0249 ± 0.0007
Eq. Size w. GP	96.77 ± 0.10	0.0242 ± 0.0022	0.0050 ± 0.0012	0.1612 ± 0.0048	0.0245 ± 0.0005
I-Max w. TS	96.81 ± 0.15	0.0229 ± 0.0016	0.0125 ± 0.0017	0.1224 ± 0.0056	0.0239 ± 0.0007
I-Max w. GP	96.81 ± 0.15	$\mathbf{0.0218} \pm 0.0012$	$\mathbf{0.0048} \pm 0.0009$	0.1173 ± 0.0054	0.0231 ± 0.0005