Stepwise Guided Policy Optimization:
Coloring Your Incorrect Reasoning in GRPO

Abstract

Reinforcement learning (RL) has proven effective in strengthening the reasoning capabilities of large language models (LLMs). A widely adopted method, Group Relative Policy Optimization (GRPO) (Shao et al., 2024), has shown strong empirical results in training DeepSeek-R1 (Guo et al., 2025a). However, GRPO fails to update the policy when all responses within a group are incorrect (i.e., *all-negative-sample* groups). This limitation underscores a key gap between artificial and human intelligence: unlike humans, who can learn from mistakes, GRPO discards these signals. Our first contribution is to introduce a simple framework that mitigates the all-negative-sample issue by incorporating response diversity within groups using a *step-wise* judge model, which can be either directly trained or adapted from existing LLMs. We prove that this diversification can accelerate GRPO's learning dynamics in a simplified setting. We also empirically validate the proposed stepwise guided policy optimization (SGPO) method, demonstrating consistent gains across model sizes (7B, 14B, 32B) in offline and online training on 9 benchmarks, including base and distilled variants. Our results highlight two advantages: (i) SGPO surpasses GRPO, especially in the early and mid-training stages where all-negative-sample groups are prevalent; and (ii) SGPO does not require judge models to generate correct answers, differentiating it from knowledge distillation methods.

1 Introduction

The rise of OpenAI-o1 (Jaech et al., 2024), DeepSeek-R1 (Guo et al., 2025a), and Kimi-1.5 (Team et al., 2025) has highlighted the emergence of *large AI reasoning models.* Unlike instruction-tuned models (Brown et al., 2020; Chowdhery et al., 2023; Touvron et al., 2023; Achiam et al., 2023), which produce quick responses by statistically inferring the next token, these new reasoning models deliberately decompose complex prompts (e.g., mathematical problems) into intermediate steps and work through chain-of-thought reasoning (Wei et al., 2022; Yao et al., 2023; Besta et al., 2024; Xiang et al., 2025). This slower yet more rigorous process yields greater accuracy and makes them more human-like, enabling success on more complex and challenging tasks (Yang et al., 2018; Shi et al., 2024; Jain et al., 2025). As generative AI applications move beyond single-turn chat and question-answering, these reasoning models are poised to become more powerful and widely adopted, positioning them as a foundational component of modern AI systems.

At the heart of this revolution lies post-training with outcome-based and verifiable rewards (Cobbe et al., 2021; Uesato et al., 2022; Zelikman et al., 2022; Singh et al., 2023; Hosseini et al., 2024; Lightman et al., 2024; Wang et al., 2024; Setlur et al., 2025; Zhang et al., 2025b), together with reinforcement learning (RL) methods (Schulman et al., 2015; 2017; Li et al., 2024b; Ahmadian et al., 2024; Shao et al., 2024; Xiong et al., 2025a), appreciated for their simplicity, intuitiveness, and practicality. A leading approach is proximal policy optimization (PPO) (Schulman et al., 2017), which relies on a critic (or value) model to estimate advantages. While essential in general RL tasks, this critic is often unnecessary in large language models (LLMs) due to their deterministic transition dynamics (Li et al., 2024b). This observation has inspired alternatives such as group relative policy optimization (GRPO) (Shao et al., 2024) and its extensions (Yu et al., 2025b; Liu et al., 2025b; Chu et al., 2025; Zhang et al., 2025a), which estimate advantages directly in a group-relative fashion (normalizing rewards across multiple samples for the same prompt).

A major limitation of these methods arises when all sampled responses in a group are incorrect (i.e., *all-negative-sample* groups), which eliminates the learning signal and halts policy updates. In GRPO, given a prompt $\mathbf{x}$, responses $\{\mathbf{y}_i\}_{i=1}^{G}$ are drawn from the old policy π_{old} and assigned rewards $\{r_i\}_{i=1}^{G}$, where $r_i = 1$ if $\mathbf{y}_i$ is correct and 0 otherwise. Advantages are obtained by normalizing r_i within the group. If $r_i = 0$ for all i, the advantage vanishes, yielding no update. Such groups are frequent in early and mid-stages of training, when reasoning ability is weak[1]. This shortcoming highlights a gap between artificial and human intelligence: humans effectively learn from mistakes, which act as essential signals during cognitive development (Chialvo & Bak, 1999). In mathematical reasoning, all-negative-sample groups prompt a child to revise rules and strengthen reasoning ability.

Recent studies suggest that negative samples in RL-based large reasoning model training carry more nuanced value than previously assumed (Xiong et al., 2025a). Instead of treating negative samples uniformly, they advocate for principled mechanisms to distinguish negative samples. One prominent direction is process reward models (PRMs) (Lightman et al., 2024; Wang et al., 2024; Luo et al., 2024; Setlur et al., 2025; Zhang et al., 2025b), which estimate either the probability of final success or its change after each reasoning step. However, their reliance on speculative value functions makes them prone to reward hacking (Skalse et al., 2022).

A common observation is that many reasoning tasks possess a structure where step-level correctness can be explicitly defined. This motivates the use of a step-wise judge model that evaluates trajectories by labeling each step as correct (1) or incorrect (0). Such a model can be trained directly (Xiong et al., 2025b) or adapted from existing LLMs (Zha et al., 2025; He et al., 2025)[2]. By grounding rewards in step-level correctness rather than speculative value estimates, our method mitigates reward hacking and yields clearer signals. Intuitively, this allows negative samples to be differentiated through their trajectories: while early-stage reasoning trajectories are of low-quality, these remain informative – much like partial credit in education, where intermediate steps still guide learning.

Our approach enables a holistic evaluation of multi-step reasoning by transforming negative samples from binary outcome rewards into graded, step-level rewards. Consider a negative sample with five reasoning steps $(a_1, a_2, a_3, a_4, a_5)$. If the first error occurs at a_3, then a_1 and a_2 are correct, yielding a correctness proportion of $\frac{2}{5}$. To improve reliability, we adopt a Grok4-Heavy -inspired strategy where multiple independent judgments are obtained from the judge model, and the error position is determined by the majority vote. We further introduce two scaling parameters β and γ to downweight noisy or unreliable signals (see Eq. (2)). Unlike PRMs, our approach avoids memory overhead and does not require costly step-level human annotations, thereby accelerating training. In this work, we focus on outcome-based post-training with group-relative updates (GRPO-style) for structured reasoning tasks; extending our approach to arbitrary reward settings is beyond the scope of this paper and left to future work.

Contribution. We propose and analyze a simple and efficient framework that introduces response diversity within all-negative-sample groups. It is both theoretically grounded in the simplified setting and empirically effective on various models, distinguishing our approach from existing heuristics. Our contributions can be summarized as follows:

1. We propose a *Stepwise Guided Policy Optimization* (SGPO) framework that leverages a step-wise judge model that identifies the first incorrect step that causes the trajectory to deviate from correctness. This makes evaluation computationally tractable and reliable. *It is important to emphasize that our contribution lies not in designing effective judge models, but in introducing a framework that leverages step-wise judges to effectively distinguish negative samples.* We also prove that SGPO outperforms GRPO in a simplified setting.

2. We conduct experiments demonstrating the effectiveness of our approach in improving LLM reasoning. Evaluations are undertaken across various model sizes (7B, 14B, 32B) in both offline and online settings with nine benchmarks, including base and distilled variants. Our results reveal two

---

[1]To reduce computational cost, training often uses small group sizes and short rollouts, further increasing the likelihood of all-negative-sample groups.

[2]We do not have access to their judge models as it's not publicly released, so we adapt our own from existing LLMs.

key benefits: (i) SGPO delivers improvements beyond the reach of GRPO, especially in the early and mid-stages of training where all-negative-sample groups are common; (ii) SGPO does not rely on more powerful judge models generating correct answers, allowing it to be distinguished from knowledge distillation methods.

The additional overhead from all-negative-sample groups remains modest, since the correctness can be efficiently verified against reference solutions, enabling rapid assessment of reasoning steps. As the computational and financial costs of closed-source judge models (`o4-mini`, `Claude3.7`) rise, SGPO accelerates learning dynamics, making the trade-off worthwhile. SGPO also outperforms GRPO with less powerful and more affordable open-source judge models (`DeepSeek-V3-0324`, `Qwen3-235B-A22B`, `QwQ-32B`), confirming that SGPO remains effective even without cutting-edge LLMs and underscoring its practicality in lower-resource settings.

2 Preliminaries and Technical Background

LLM finetuning. LLM finetuning typically consists of *pre-training* and *post-training*. Pre-training equips the model with broad language understanding and generation capabilities, while post-training adapts the model to specific downstream objectives (e.g., improving mathematical problem solving via reasoning). In post-training, a model usually first undergoes *imitation learning* (e.g., supervised finetuning on human or expert trajectories, or direct distillation from stronger models), and then further improves by training on self-generated responses paired with feedback indicating whether the responses are good or bad. Two common feedback-driven paradigms are *reinforcement learning from human feedback* (RLHF), where a learned reward model (trained from human preferences) assigns rewards to model outputs, and *reinforcement learning from verifiable rewards* (RLVR), where rewards are computed by an automatic verifier (often used for math problems with checkable answers). We introduce GRPO, a representative RLVR method, below.

Policy optimization. Modern LLMs are built based on the Transformer architecture (Vaswani et al., 2017) and generate responses $\mathbf{y} = (a_1, \ldots, a_H)$ to user prompts $\mathbf{x}$, where each token $a_h \in \mathcal{V}^\star$, with $\mathcal{V}$ denoting the vocabulary and $\mathcal{V}^\star$ the set of all possible token sequences. We view the LLM as a policy $\pi_\theta(\mathbf{y}|\mathbf{x})$ parameterized by θ, assigning probabilities to responses $\mathbf{y}$ given $\mathbf{x}$. The policy operates in an auto-regressive way as follows (Agarwal et al., 2020; Mei et al., 2021; Li et al., 2024b):

$$\pi_\theta(\mathbf{y}|\mathbf{x}) = \prod_{h=1}^{H} \pi_\theta(a_h \mid \mathbf{x}, a_1, \ldots, a_{h-1}).$$

For a prompt $\mathbf{x}$ with ground-truth response $\mathbf{y}_\mathbf{x}^\star$, performance is evaluated using a regular-expression match on the final answer: $r(\mathbf{x}, \mathbf{y}) = 1$ if $\mathbf{y}$ matches $\mathbf{y}_\mathbf{x}^\star$ and $r(\mathbf{x}, \mathbf{y}) = 0$ otherwise (Hendrycks et al., 2021). We consider the reasoning tasks defined over a dataset $\mathcal{D} = (\mathbf{x}, \mathbf{y}_\mathbf{x}^\star)$, where each $\mathbf{x}$ is a problem and $\mathbf{y}_\mathbf{x}^\star$ its ground-truth solution.

The policy gradient methods (Williams, 1992; Sutton & Barto, 1998) aim to maximize the objective $J(\theta) = \mathbb{E}_{\mathbf{x} \sim \rho, \mathbf{y} \sim \pi_\theta(\cdot|\mathbf{x})}[r(\mathbf{x}, \mathbf{y})]$ where ρ is the prompt distribution and π_θ is an LLM policy. Parameters are updated via $\theta \leftarrow \theta + \eta \nabla_\theta J(\theta)$. In practice, trajectories are sampled from an old policy $\pi_{\theta_{\text{old}}}$, which is different from π_θ, motivating the use of importance sampling as follows:

$$J(\theta) = \mathbb{E}_{\mathbf{x} \sim \rho, \mathbf{y} \sim \pi_{\theta_{\text{old}}}(\cdot|\mathbf{x})} \left[\frac{\pi_\theta(\mathbf{y}|\mathbf{x})}{\pi_{\theta_{\text{old}}}(\mathbf{y}|\mathbf{x})} r(\mathbf{x}, \mathbf{y}) \right].$$

However, this estimator suffers from high variance when π_θ deviates from $\pi_{\theta_{\text{old}}}$. To stabilize training, clipped surrogate objectives are used as follows:

$$J(\theta) = \mathbb{E}_{\mathbf{x} \sim \rho, \mathbf{y} \sim \pi_{\theta_{\text{old}}}(\cdot|\mathbf{x})} \left[\min \left\{ \frac{\pi_\theta(\mathbf{y}|\mathbf{x})}{\pi_{\theta_{\text{old}}}(\mathbf{y}|\mathbf{x})} r(\mathbf{x}, \mathbf{y}), \texttt{clip} \left(\frac{\pi_\theta(\mathbf{y}|\mathbf{x})}{\pi_{\theta_{\text{old}}}(\mathbf{y}|\mathbf{x})}, 1 - \epsilon, 1 + \epsilon \right) r(\mathbf{x}, \mathbf{y}) \right\} \right],$$

where $\texttt{clip}(x, 1 - \varepsilon, 1 + \varepsilon) := \max\{\min\{x, 1 + \varepsilon\}, 1 - \varepsilon\}$. The group relative policy optimization (GRPO) and its variants (Yu et al., 2025b; Liu et al., 2025b; Chu et al., 2025; Zhang et al., 2025a) adopt this framework

but estimate gradients using groups of samples. For each prompt $\mathbf{x}$, GRPO samples responses $\mathbf{y}_1, \ldots, \mathbf{y}_G$ from $\pi_{\theta_{\text{old}}}$. We aim at maximizing the objective function in the form of

$$J(\theta) = \mathbb{E}_{\mathbf{x} \sim \rho, \{\mathbf{y}_i\}_{i=1}^{G} \sim \pi_{\theta_{\text{old}}}(\cdot|\mathbf{x})} \left[\frac{1}{G} \sum_{i=1}^{G} \min \left\{ \frac{\pi_\theta(\mathbf{y}_i|\mathbf{x})}{\pi_{\theta_{\text{old}}}(\mathbf{y}_i|\mathbf{x})} A_i, \mathtt{clip} \left(\frac{\pi_\theta(\mathbf{y}_i|\mathbf{x})}{\pi_{\theta_{\text{old}}}(\mathbf{y}_i|\mathbf{x})}, 1 - \epsilon, 1 + \epsilon \right) A_i \right\} \right],$$

where $\epsilon \in (0, 1)$ and the advantage A_i is computed as

$$A_i = \frac{r(\mathbf{x}, \mathbf{y}_i) - \mathtt{mean}(\{r(\mathbf{x}, \mathbf{y}_1), \ldots, r(\mathbf{x}, \mathbf{y}_G)\})}{\mathtt{std}(\{r(\mathbf{x}, \mathbf{y}_1), \ldots, r(\mathbf{x}, \mathbf{y}_G)\})}, \tag{1}$$

where $r(\mathbf{x}, \mathbf{y}_i) = 1$ if $\mathbf{y}_i$ matches the ground-truth answer and 0 otherwise.

Remark 2.1. *When rewards are identical across all samples within a group, $A_i = 0$ and no update occurs. This is appropriate for all-positive groups but constitutes a critical limitation for all-negative groups, where GRPO fails to exploit mistakes as learning signals.*

3 Main Results

We propose the Stepwise Guided Policy Optimization (SGPO) framework, which employs the step-wise judge model to detect the first incorrect step that leads a trajectory away from correctness. In a simplified setting, we prove that SGPO consistently accelerates GRPO's learning dynamics.

3.1 A Step-wise Judge Model

We propose a principled reward mechanism for negative samples, wherein the step-wise judge model differentiates between structurally sound but partially incorrect reasoning and entirely erroneous responses. This design is motivated by the intuition that an incorrect final answer does not invalidate the entire reasoning process. For instance, a model may follow a logically coherent sequence of steps yet make a minor error – such as an arithmetic slip – that leads to an incorrect conclusion. Treating such cases the same as fundamentally flawed or incoherent reasoning does not make sense. This refinement remains effective under constraints such as reduced output length, where a model may be unable to complete the full solution but still demonstrates a valid reasoning trajectory.

Our step-wise judge model can be either trained directly or adapted from existing LLMs. It evaluates responses sequentially, identifying the first substantive error – such as a computational slip or a logical fallacy – that causes the trajectory to deviate from correctness. To formalize this, we define the *Reasoning Trajectory Score* (RTS) for an incorrect response $\mathbf{y}$, denoted as $\mathtt{RTS}(\mathbf{y}) \in [0, 1]$. The judge model checks each step in order, pinpoints the first error, and treats all preceding steps as the valid reasoning segment. $\mathtt{RTS}(\mathbf{y})$ is then computed as the ratio of the valid segment length to the total trajectory length. For example, if $\mathbf{y}$ consists of five steps $(a_1, a_2, a_3, a_4, a_5)$ and the first error occurs at a_4, then $\mathtt{RTS}(\mathbf{y}) = \frac{3}{5}$, indicating that three steps of reasoning are correct before erroneous.

In our experiment, we adapt the judge model from existing LLMs, either closed-source (`o4-mini`, `Claude3.7`) or open-source (`DeepSeek-V3-0324`, `Qwen3-235B-A22B`, `QwQ-32B`). To enhance reliability and further reduce variance in the reward signal, we employ the following protocol: (i) alongside the candidate response, we provide the judge with a reference solution (e.g., a gold final answer, a brief solution outline, or a full reasoning trace when available); in our experiments, we draw this solution from a supervised fine-tuning dataset with correct answers and reasoning trajectories, which anchors the intended solution path and enables error localization; and (ii) we elicit step-wise evaluation rather than holistic evaluation. The judge model justifies correctness or flags an error sentence by sentence, identifies the first clear mistake, and then traces how this error propagates to the final incorrect conclusion.

Based on the reasoning trajectory score, we introduce a new outcome reward function:

$$r_{\mathtt{SGPO}}(\mathbf{y}) = \begin{cases} 1, & \text{if the final answer of } \mathbf{y} \text{ is correct,} \\ \frac{1}{1 + \exp(-\beta(\mathtt{RTS}(\mathbf{y}) - \gamma))}, & \text{otherwise.} \end{cases} \tag{2}$$

where $\gamma > 0$ and $\beta > 0$ (taken as 10 and 0.5 in the actual implementation) are two parameters to decide scale threshold and scale intensity, respectively. This design ensures that the model receives a more informative gradient signal during training, thereby encouraging refinement of partially correct reasoning rather than indiscriminate penalization of all incorrect outputs. This specification of $r_{\texttt{SGPO}}$ can be directly incorporated into the advantage calculation in Eq. (1). As a consequence, SGPO keeps the same rollout pipeline as GRPO and the same outcome-based supervision, and only replaces the reward used in within-group advantage computation from $r(x, y)$ to $r_{\texttt{SGPO}}(y)$ in Eq. (2).

Remark 3.1. *Our approach differs from process reward models (PRMs) (e.g. Lightman et al., 2024). For a prompt $\mathbf{x}$ and a prefix of reasoning steps $(a_1, \ldots, a_t)$, a PRM typically predicts either (i) a prefix-level value $V(\mathbf{x}, a_{1:t}) = \mathbb{P}(\text{final answer correct} \mid \mathbf{x}, a_{1:t})$, or (ii) a step-level progress signal such as $\Delta_t = V(\mathbf{x}, a_{1:t}) - V(\mathbf{x}, a_{1:t-1})$. In practice, PRMs are trained by supervised ranking of intermediate steps and are used to re-rank trajectories or shape training at the* prefix *level, acting as approximate value (or Q-value) functions over prefixes. In contrast, SGPO introduces a different way of producing and using feedback signals: (i) Policy-guided rollouts without search. All trajectories are sampled from the current policy, without PRM-guided exploration or trajectory alteration; (ii) Post-hoc first-error identification. A step-wise judge inspects the entire trajectory, pinpoints the earliest error relative to a reference solution, and converts this into a calibrated scalar reward $r_{\texttt{SGPO}}(\mathbf{y})$ via the reasoning trajectory score; (iii) Stable credit assignment in all-negative-sample groups. By locating the first definitive mistake only after observing the full trace, SGPO eliminates the look-ahead ambiguity and feedback loops inherent to PRM-guided search (Zhang et al., 2024a), while avoiding the need for the judge to solve the problem or approximate a value function. We note that SGPO alleviates but does not fully eliminate degeneracy: if all trajectories in a group receive identical $r_{\texttt{SGPO}}$ (e.g., they fail at the same first-error position), the group-normalized advantages can still vanish, though this phenomenon is rarely observed in our experiments.*

Remark 3.2. *Our approach differs from knowledge distillation (e.g. Kang et al., 2023; Gu et al., 2024). The student model trained via knowledge distillation inherits the judge model's failure, since it only imitates the judge model's outputs. In contrast, SGPO leverages the judge model to identify mistakes in the student's reasoning, providing learning signals that go beyond imitation and enabling improvements unattainable by knowledge distillation.*

3.2 Accelerating Learning Dynamics

We present a theoretical analysis to explain why SGPO outperforms GRPO. We study an idealized setting in which the step-wise judge provides accurate first-error localization. Even in this regime, establishing a general separation is technically subtle, so we focus on a stylized example. To this end, we consider the case when $H = 2$, where each step admits two possible actions $a_h \in 1, 2$ for $h = 1, 2$. Extending the analysis to general horizons or action spaces and imperfect (noisy or biased) judges is left to future work. This configuration follows prior works (Dayan, 1991; Li et al., 2024b), where analogous examples were employed to validate theoretical insights. Without loss of generality, we assume a unique ground-truth response $\mathbf{y}_{\mathbf{x}}^{\star} = (2, 2)$ for the prompt $\mathbf{x}$. For clarity, we restrict the sample space to $(1, 1), (2, 1), (2, 2)$, excluding $(1, 2)$ since a correct reasoning step is unlikely to, and should not, follow an incorrect precursor.

To illustrate the effect of SGPO, we analyze the learning dynamics of SGPO and GRPO in this simplified setting. Under GRPO, the rewards are assigned as $r((2, 2)) = 1$ and $r((2, 1)) = r((1, 1)) = 0$, meaning that only selecting the "good" action 2 at both steps yields a positive reward. In contrast, SGPO assigns $r_{\texttt{SGPO}}((2, 2)) = 1$, $r_{\texttt{SGPO}}((2, 1)) = \frac{1}{2}$ and $r_{\texttt{SGPO}}((1, 1)) = 0$. The difference is that partial progress – choosing the "good" action 2 in the first step but failing at the second – receives no credit in GRPO yet proportional credit in SGPO. Here, $\frac{1}{2}$ is chosen for illustrative purposes to convey the qualitative behavior of the reward mechanism, while the exact values used in experiments are determined by Eq. (2).

The algorithm iteratively updates the policy parameter θ using samples drawn from the current policy π_θ. We rewrite the generic GRPO update with a step size $\eta > 0$ as follows,

$$\theta^{(k+1)} = \theta^{(k)} + \eta \cdot g(\theta), \quad \text{where } g(\theta) = \frac{1}{NGH} \left(\sum_{i=1}^{N} \sum_{k=1}^{G} \sum_{h=1}^{H} s_\theta(\mathbf{x}^i, a_{1:h-1}^{i,k}) A_{i,k} \right),$$

where N is the number of prompts, G is the number of groups, H is the number of reasoning steps in each response, $s_\theta(\mathbf{x}^i, a_{1:h-1}^{i,k}) := \nabla \theta \log \pi_\theta(a_t | \mathbf{x}, a_{1:h-1})$ is the score function, and the advantage $A_{i,k}$ is defined by Eq. (1) for each question $\mathbf{x}^i$. To distinguish, we denote $g_{\mathsf{GRPO}}(\cdot)$ as the gradient estimator using classical outcome reward model r, and $g_{\mathsf{SGPO}}(\cdot)$ as the gradient estimator using the reward r_{SGPO} as proposed in Section 3.1.

In our analysis, we examine the population-level learning dynamics with $G = 2$, omitting clipping and importance sampling. In practice, importance sampling and clipping are important for training stability; we omit them here to simplify the analysis and leave their theoretical treatment to future work. For simplicity, we perform our analysis in the likelihood space rather than in the parameter space directly. Indeed, we define the key quantities as follows,

$$p \doteq \pi_{\theta_1}(a_1 = 2, |, \mathbf{x}) = \frac{e^{\theta_1^{\mathbf{x},2}}}{e^{\theta_1^{\mathbf{x},1}} + e^{\theta_1^{\mathbf{x},2}}}, \qquad q \doteq \pi_{\theta_2}(a_2 = 2, |, \mathbf{x}, a_1 = 2) = \frac{e^{\theta_2^{\mathbf{x},2,2}}}{e^{\theta_2^{\mathbf{x},2,1}} + e^{\theta_2^{\mathbf{x},2,2}}}.$$

Note that the original 4-dimensional parameter space defined by $\theta_1^{\mathbf{x},1}$, $\theta_1^{\mathbf{x},2}$, $\theta_2^{\mathbf{x},2,1}$ and $\theta_2^{\mathbf{x},2,2}$ in $\mathbb{R}$ is reduced to a 2-dimensional likelihood space defined by $p, q \in [0, 1]$.

For our simple stylized model, we compute the score functions in terms of likelihood parameters p, q as follows,

$$s(a_1 = 1 \,|\, \mathbf{x}) = \begin{bmatrix} p \\ -p \\ 0 \\ 0 \end{bmatrix}, \quad s(a_1 = 2 \,|\, \mathbf{x}) = \begin{bmatrix} p - 1 \\ 1 - p \\ 0 \\ 0 \end{bmatrix},$$

and

$$s(a_2 = 1 \,|\, \mathbf{x}, a_1 = 2) = \begin{bmatrix} 0 \\ 0 \\ q \\ -q \end{bmatrix}, \quad s(a_2 = 2 \,|\, \mathbf{x}, a_1 = 2) = \begin{bmatrix} 0 \\ 0 \\ q - 1 \\ 1 - q \end{bmatrix}.$$

The responses can be drawn i.i.d. from the distribution as follows,

$$(a_1, a_2) = \begin{cases} (1, 1), & \text{w.p. } 1 - p, \\ (2, 1), & \text{w.p. } p(1 - q), \\ (2, 2), & \text{w.p. } pq. \end{cases}$$

The SGPO and GRPO training dynamics with population-level policy gradient can be computed exactly for the stylized model as follows,

$$\bar{g}_{\mathsf{SGPO}}(\theta) = \mathbb{E}[g_{\mathsf{SGPO}}(\theta)] = \frac{1}{2}\begin{bmatrix} p(p-1) \\ p(1-p) \\ p^2 q(q-1) \\ p^2 q(1-q) \end{bmatrix}, \quad \bar{g}_{\mathsf{GRPO}}(\theta) = \mathbb{E}[g_{\mathsf{GRPO}}(\theta)] = \frac{1}{2}\begin{bmatrix} p(p-1)q \\ p(1-p)q \\ pq(q-1) \\ pq(1-q) \end{bmatrix}.$$

Since $g_{\mathsf{GRPO}}(\theta)$ and $g_{\mathsf{SGPO}}(\theta)$ concentrate around $\bar{g}_{\mathsf{GRPO}}(\theta)$ and $\bar{g}_{\mathsf{SGPO}}(\theta)$ when the number of samples in each group is sufficiently large, it is reasonable to analyze the population-level dynamics for illustration. Note that the high-probability guarantees for the sample-level dynamics can be derived using concentration inequalities under certain conditions.

Denote $p_{\mathsf{GRPO}}^{(k)}$ and $q_{\mathsf{GRPO}}^{(k)}$ as the value of quantity p and q at iteration k under GRPO. Analogously, $p_{\mathsf{SGPO}}^{(k)}$ and $q_{\mathsf{SGPO}}^{(k)}$ are the corresponding probabilities p and q at iteration k under SGPO. We can explicitly write down the SGPO and GRPO update rules with $\eta = 1$ as follows,

$$\begin{cases} p_{\mathsf{SGPO}}^{(k+1)} = \exp(f_{11}(p_{\mathsf{SGPO}}^{(k)})), \\ q_{\mathsf{SGPO}}^{(k+1)} = \exp(f_{12}(p_{\mathsf{SGPO}}^{(k)}, q_{\mathsf{SGPO}}^{(k)})), \end{cases} \text{and} \quad \begin{cases} p_{\mathsf{GRPO}}^{(k+1)} = \exp(f_{21}(p_{\mathsf{GRPO}}^{(k)}, q_{\mathsf{GRPO}}^{(k)})), \\ q_{\mathsf{GRPO}}^{(k+1)} = \exp(f_{22}(p_{\mathsf{GRPO}}^{(k)}, q_{\mathsf{GRPO}}^{(k)})), \end{cases} \tag{3}$$

where the functions f_{ij} are defined by

$$
\begin{aligned}
f_{11}(p) &= \log(p) + p(1-p) - \log(1 - p + pe^{p(1-p)}), \\
f_{21}(p, q) &= \log(p) + p(1-p)q - \log(1 - p + pe^{p(1-p)q}), \\
f_{12}(p, q) &= \log(q) + p^2 q(1-q) - \log(1 - q + qe^{p^2 q(1-q)}), \\
f_{22}(p, q) &= \log(q) + pq(1-q) - \log(1 - q + qe^{pq(1-q)}).
\end{aligned}
\tag{4}
$$

Our theoretical findings are summarized in the following theorem.

Theorem 3.3. *Suppose that $p_{GRPO}^{(0)} = q_{GRPO}^{(0)} = p_{SGPO}^{(0)} = q_{SGPO}^{(0)} = \frac{1}{2}$ and $\eta = 1$[3] for GRPO and SGPO. Then, we have that (i) GRPO and SGPO achieve successful learning: $p_{GRPO}^{(k)}, q_{GRPO}^{(k)}, p_{SGPO}^{(k)}, q_{SGPO}^{(k)} \to 1$ as $k \to +\infty$; (ii) SGPO outperforms GRPO in learning the "good" action in the first step: $p_{SGPO}^{(k)} > p_{GRPO}^{(k)}$ for all $k \geq 1$; (iii) SGPO outperforms GRPO in learning the optimal policy: $p_{SGPO}^{(k)} q_{SGPO}^{(k)} > p_{GRPO}^{(k)} q_{GRPO}^{(k)}$ for all $k \geq 1$.*

Proof. To show (i), recall that the sequence $(p_{SGPO}^{(k)})_{k \in \mathbb{N}}$ is strictly increasing and bounded in $(0, 1)$ from Lemmas B.4(i) and B.4(ii), so it converge to some value $c \in (0, 1]$. Take limit as $k \to \infty$:

$$
1 = \lim_{k \to \infty} \frac{p_{SGPO}^{(k+1)}}{p_{SGPO}^{(k)}} = \lim_{k \to \infty} \frac{1}{(1 - p_{SGPO}^{(k)}) e^{-\Delta_{SGPO, p}^{(k)}} + p_{SGPO}^{(k)}} = \frac{1}{(1-c)e^{-c(1-c)} + c}.
$$

Using the simple Taylor lower bound $e^{-x} \geq 1 - x$, we have

$$
1 = \frac{1}{(1-c)e^{-c(1-c)} + c} \geq \frac{1}{(1-c)(1 - c(1-c)) + c} \implies (c-1)^2 \leq 0 \implies c = 1.
$$

This shows $p_{SGPO}^{(k)} \to 1$ as $k \to \infty$. Similarly, we can show $q_{GRPO}^{(k)}, p_{SGPO}^{(k)}, q_{SGPO}^{(k)} \to 1$ as $k \to \infty$.

To show (ii), consider the base case:

$$
\begin{aligned}
p_{SGPO}^{(1)} &= \exp(f_{11}(p_{SGPO}^{(0)})) = \exp(\log p_{SGPO}^{(0)} + h_{p_{SGPO}^{(0)}}(p_{SGPO}^{(0)}(1 - p_{SGPO}^{(0)}))) \\
&= \exp(\log p_{GRPO}^{(0)} + h_{p_{GRPO}^{(0)}}(p_{GRPO}^{(0)}(1 - p_{GRPO}^{(0)}))) \\
&> \exp(\log p_{GRPO}^{(0)} + h_{p_{GRPO}^{(0)}}(p_{GRPO}^{(0)}(1 - p_{GRPO}^{(0)})q_{GRPO}^{(0)})) = \exp(f_{21}(p_{GRPO}^{(0)}, q_{GRPO}^{(0)})) = p_{GRPO}^{(1)},
\end{aligned}
$$

where the inequality follows from Lemma B.1(ii). Thus, we use induction and assume $p_{SGPO}^{(k)} > p_{GRPO}^{(k)}$ for some $k \geq 1$. Then we have,

$$
\begin{aligned}
p_{SGPO}^{(k+1)} &= \exp(f_{11}(p_{SGPO}^{(k)})) > \exp(f_{11}(p_{GRPO}^{(k)})) = \exp(\log p_{GRPO}^{(k)} + h_{p_{GRPO}^{(k)}}(p_{GRPO}^{(k)}(1 - p_{GRPO}^{(k)}))) \\
&> \exp(\log p_{GRPO}^{(k)} + h_{p_{GRPO}^{(k)}}(p_{GRPO}^{(k)}(1 - p_{GRPO}^{(k)})q_{GRPO}^{(k)})) = \exp(f_{21}(p_{GRPO}^{(k)}, q_{GRPO}^{(k)})) = p_{GRPO}^{(k+1)},
\end{aligned}
$$

where the first inequality uses Lemma B.1(i) and the second one uses Lemma B.1(ii). Thus, $p_{SGPO}^{(k+1)} > p_{GRPO}^{(k+1)}$ and induction completes. We have proved that $p_{SGPO}^{(k)} > p_{GRPO}^{(k)}$ for all $k \geq 1$.

To show (iii), first notice that we can show $p_{GRPO}^{(k)} = q_{GRPO}^{(k)}$ for all $k \geq 0$ by induction. The base case is trivial by initialization. Suppose $p_{GRPO}^{(k)} = q_{GRPO}^{(k)}$ for some $k \geq 0$, then by noticing that $f_{21}(p, p) = f_{22}(p, p)$, we have

$$
\begin{aligned}
p_{GRPO}^{(k+1)} &= \exp(f_{21}(p_{GRPO}^{(k)}, q_{GRPO}^{(k)})) = \exp(f_{21}(p_{GRPO}^{(k)}, p_{GRPO}^{(k)})) \\
&= \exp(f_{22}(p_{GRPO}^{(k)}, p_{GRPO}^{(k)})) = \exp(f_{22}(p_{GRPO}^{(k)}, q_{GRPO}^{(k)})) = q_{GRPO}^{(k+1)}.
\end{aligned}
$$

Thus, by induction, $p_{GRPO}^{(k)} = q_{GRPO}^{(k)}$ for all $k \geq 0$. Now, we can reduce the update rule of $p_{GRPO}^{(k)}$ as

$$
p_{GRPO}^{(k+1)} = \frac{1}{(1/p_{GRPO}^{(k)} - 1) \exp(-(p_{GRPO}^{(k)})^2 (1 - p_{GRPO}^{(k)})) + 1}.
$$

---

[3]We use the unit stepsize for simplicity. Our results are valid for any sufficiently small step size.

Table 1: Evaluation results on offline RL training. For each model, we report the baseline performance before RL training. We then report RL training results that uses only negative samples and positive samples, respectively. Performance across validation and training dataset (`LIMO`) is shown.

	AMC23 avg@16	AIME24 avg@16	MATH500 pass@1	Olympiads pass@1	LIMO pass@1
Qwen2.5-14B-Instruct					
Baseline	58.59	14.58	**80.40**	41.78	31.70
Negative Samples only	**61.88**	**15.21**	**80.40**	**42.37**	30.11
Positive Samples only	61.72	14.58	79.80	42.07	**38.68**
Qwen2.5-32B-Instruct					
Baseline	64.22	17.08	**83.60**	45.93	34.64
Negative Samples only	**69.53**	**20.42**	83.00	46.37	36.47
Positive Samples only	66.87	18.75	**83.60**	**47.41**	**41.86**

Also recall the update rule of $p_{\text{SGPO}}^{(k)}$ and $q_{\text{SGPO}}^{(k)}$:

$$
\begin{aligned}
p_{\text{SGPO}}^{(k+1)} &= \frac{1}{(1/p_{\text{SGPO}}^{(k)}-1)\exp(-p_{\text{SGPO}}^{(k)}(1-p_{\text{SGPO}}^{(k)}))+1} \\
q_{\text{SGPO}}^{(k+1)} &= \frac{1}{(1/q_{\text{SGPO}}^{(k)}-1)\exp(-(p_{\text{SGPO}}^{(k)})^2 q_{\text{SGPO}}^{(k)}(1-q_{\text{SGPO}}^{(k)}))+1}
\end{aligned},
$$

and it suffices to show $p_{\text{SGPO}}^{(k)} q_{\text{SGPO}}^{(k)} > (p_{\text{GRPO}}^{(k)})^2$ for all $k \geq 1$. We prove by induction. For the base case,

$$
\sqrt{p_{\text{SGPO}}^{(1)} q_{\text{SGPO}}^{(1)}} = \sqrt{\frac{1}{1+(1/2)e^{-1/4}} \cdot \frac{1}{1+(1/2)e^{-1/16}}} > \frac{1}{1+(1/2)e^{-1/8}} = p_{\text{GRPO}}^{(1)}.
$$

The above inequality holds true since Lemma B.1(iv) implies

$$
2\log(1+(1/2)e^{-1/8}) > \log(1+(1/2)e^{-1/4}) + \log(1+(1/2)e^{-1/16}),
$$

It remains to show that $p_{\text{SGPO}}^{(k)} q_{\text{SGPO}}^{(k)} > (p_{\text{GRPO}}^{(k)})^2$ implies $p_{\text{SGPO}}^{(k+1)} q_{\text{SGPO}}^{(k+1)} > (p_{\text{GRPO}}^{(k+1)})^2$ for $k \geq 1$. By Lemma B.4(iii), we know $p_{\text{SGPO}}^{(k)} > q_{\text{SGPO}}^{(k)}$ for all $k \geq 1$. Thus, Lemma B.2 implies that

$$
p_{\text{SGPO}}^{(k+1)} q_{\text{SGPO}}^{(k+1)} = \frac{1}{A(p_{\text{SGPO}}^{(k)})B(p_{\text{SGPO}}^{(k)}, q_{\text{SGPO}}^{(k)})} > \frac{1}{C\left(\sqrt{p_{\text{SGPO}}^{(k)} q_{\text{SGPO}}^{(k)}}\right)^2}.
$$

Using Lemma B.1(iii), we complete the induction by applying our induction hypothesis:

$$
\frac{1}{C\left(\sqrt{p_{\text{SGPO}}^{(k)} q_{\text{SGPO}}^{(k)}}\right)^2} = \exp\left(f_{21}\left(\sqrt{p_{\text{SGPO}}^{(k)} q_{\text{SGPO}}^{(k)}}, \sqrt{p_{\text{SGPO}}^{(k)} q_{\text{SGPO}}^{(k)}}\right)\right) > \exp(f_{21}(p_{\text{GRPO}}^{(k)}, p_{\text{GRPO}}^{(k)})) = (p_{\text{GRPO}}^{(k+1)})^2.
$$

This completes the proof. □

Remark 3.4. *Theorem 3.3 presents one of the first theoretical analyses of GRPO with multiple samples and multi-step reasoning in the context of LLM reasoning. The first part establishes that SGPO converges to the optimal policy. The second and third parts demonstrate that SGPO both accelerates the acquisition of partially correct reasoning steps and preserves partial reasoning ability even when the final answer is incorrect. Importantly, the theorem provides a **per-iteration** comparison of learning under different reward mechanisms – an aspect rarely examined in previous works. The provable improvement in learning the optimal policy is also consistent with our numerical findings. We plot the resulting learning curves of our numerical simulation in Figure 1. The left panel shows the probability of selecting the "good" action in the first step at iteration k (i.e., $p_{SGPO}^{(k)}$ vs. $p_{GRPO}^{(k)}$), while the right panel shows the probability of learning the optimal policy (i.e., $p_{SGPO}^{(k)} q_{SGPO}^{(k)}$ vs. $p_{GRPO}^{(k)} q_{GRPO}^{(k)}$). The results align with the predictions of Theorem 3.3, demonstrating that the likelihood of learning the optimal policy under SGPO consistently exceeds that of GRPO across training.*

Figure 1: Learning dynamics of GRPO and SGPO in the simplified setting.

4 Experiments

We demonstrate the benefits of differentiating negative samples through experiments in both offline and online settings. Offline RL is more computationally efficient, offering faster training, reduced memory consumption, and improved stability. In contrast, online RL provides greater flexibility and learning capacity, and has become the standard approach in large-scale reasoning models such as DeepSeek-R1 (Guo et al., 2025a).

4.1 Offline Training

For baselines, we consider strong models without further fine-tuned on math-specific SFT datasets, namely `Qwen2.5-14B-Instruct` and `Qwen2.5-32B-Instruct`. Prior work showed that a small set of carefully curated prompts significantly enhance the reasoning capability. Accordingly, we adopt the `GAIR/LIMO` dataset (Ye et al., 2025) as the training set, which has demonstrated strong potential for improving the reasoning performance of large-scale (32B) models in offline SFT. Evaluation is conducted on four standard math reasoning benchmarks: `AIME24`, `AMC23`, `MATH500` (Hendrycks et al., 2021), and `OlympiadBench` (He et al., 2024). Our aim is to highlight the rich learning signal contained in all-negative-sample groups, showing that training exclusively on them can still yield performance gains. For benchmarks with fewer than 100 questions (`AMC23`, `AIME24`), we report `avg@16` results with a decoding temperature of 0.6 and `Top_P` = 0.95. For benchmarks with more than 100 questions, we report `pass@1` results using greedy decoding. Here, pass@k is the percentage of prompts solved by at least one sample, while avg@k is the average percentage of corrected samples among the k samples. Across all experiments, the maximum decoding length is set to 32768 tokens.

We conduct all response generation and model updates using offline RL (Peters & Schaal, 2007) with the standard GRPO mechanism. Specifically, the model is updated with advantages estimated from the offline dataset (see, e.g., Peng et al., 2019; Li et al., 2024b). For each prompt, we sample six responses per group and identify all-negative-sample groups in which all responses yield incorrect answers. Within these groups, we apply the step-wise judge model to assign differentiated rewards to negative samples, which are then used for offline RL updates. The model is trained for three epochs with a learning rate of 2×10^{-6}. As a contrastive baseline, we also perform offline RL using only positive rollouts with correct answers. This parallel setup enables a direct comparison between learning from exclusively negative reasoning trajectories and from exclusively positive ones.

We conduct offline RL training to demonstrate that utilizing all-negative-sample groups can enhance the reasoning abilities of LLMs. For comparison, we also include positive-only offline RL training. As shown in Table 1, SGPO with negative samples consistently improve performance across most of benchmarks, in

Table 2: Evaluation results on online RL training. We refer to BASELINE as the performance of the original model without RL finetuning. **Overall** is average performance across all the benchmarks. Note that the training dataset is `AIME1997-2023`. For `DeepSeek-R1-Distill-Qwen-7B`, we report additional results, including (i) compatibility with more judge models and (ii) ablation on the stability parameters β and γ.

	Kaoyan pass@1	GradeMath pass@1	MATH500 pass@1	Olympiads pass@1	CHMath24 avg@16	AIME25 avg@16	AIME24 avg@16	GaoKao avg@16	AMC23 avg@16	Overall avg
DeepSeek-R1-Distill-Qwen-7B										
BASELINE	50.25	41.43	87.00	49.93	73.75	**40.62**	52.92	80.22	89.53	62.85
GRPO	55.78	43.33	89.40	**56.00**	71.04	36.68	52.08	80.30	88.91	63.72
SGPO+o4-MINI-0416	57.79	46.19	90.80	54.67	75.00	38.33	54.58	81.33	90.00	65.41
SGPO+DEEPSEEK-V3-0324	54.77	**47.17**	91.00	55.11	**77.29**	40.42	**56.87**	82.28	90.83	**66.19**
SGPO+QWEN3-235B-A22B	56.78	46.67	**92.00**	54.67	73.33	37.92	55.63	81.17	90.63	65.42
SGPO+QwQ-32B	52.26	45.24	**92.00**	53.78	75.00	35.21	56.46	**82.28**	91.88	64.91
SGPO+QwQ-32B w/o $\{\beta,\gamma\}$	**58.29**	42.38	90.20	55.11	74.58	38.69	53.63	81.24	88.75	65.08
DeepSeek-R1-Distill-Llama-8B										
BASELINE	29.15	23.81	77.40	41.48	**61.46**	27.92	**42.29**	**72.78**	87.97	51.58
GRPO	35.68	28.33	**84.00**	46.32	57.08	**28.33**	42.08	68.99	86.72	53.06
SGPO+CLAUDE-3.7	**39.70**	**29.05**	83.60	**48.44**	58.96	24.58	39.37	71.52	**89.06**	**53.81**
Qwen2.5-14B-Instruct										
BASELINE	37.69	49.52	80.40	41.78	21.88	13.13	**14.58**	**41.14**	58.59	39.85
GRPO	**43.22**	47.14	80.20	43.11	21.88	13.13	13.33	39.16	**59.84**	40.11
SGPO+o4-MINI-0416	38.69	**53.33**	**81.00**	**44.00**	**22.92**	**16.67**	14.17	39.00	59.22	**41.00**
Qwen2.5-32B-Instruct										
BASELINE	45.73	**53.81**	**83.60**	45.93	26.87	12.29	17.08	44.15	64.22	43.74
GRPO	**48.24**	52.86	83.20	45.93	22.50	12.08	**21.67**	**45.73**	67.34	44.39
SGPO+o4-MINI-0416	**48.24**	**53.81**	83.00	**46.81**	**29.79**	**14.58**	19.58	45.09	**69.53**	**45.06**
QwQ-32B										
BASELINE	64.32	62.38	94.60	68.74	**89.39**	**68.54**	77.71	86.88	97.03	78.84
GRPO	71.36	63.81	94.60	69.48	88.75	64.38	75.83	**87.11**	97.03	79.15
SGPO+DEEPSEEK-V3-0324	**73.37**	**64.76**	**95.00**	**70.22**	88.33	66.46	**78.33**	**87.11**	**97.97**	**80.17**

some cases even surpassing models trained solely on positive samples. Notably, in the 14B model experiment, training on negative samples yields improvements on four benchmarks relative to the positive-sample baseline. These findings underscore the utility of negative samples, which should not be discarded in online GRPO training; see more discussions in Section 4.4.

4.2 Online Training

For baselines, we consider applying `Qwen2.5-14B-Instruct`, `Qwen2.5-32B-Instruct`, `QwQ-32B`, `DeepSeek-R1-Distill-Qwen-7B` and `DeepSeek-R1-Distill-Llama-8B`. Online GRPO training is implemented using the `verl` framework (Sheng et al., 2025). For the step-wise judge model, we adopt a diverse set of LLMs, ranging from closed-source models with strong reasoning capabilities (`o4-mini`, `Claude3.7`) to open-source models that are more accessible to the community, including `DeepSeek-V3-0324`, `Qwen3-235B-A22B`, and `QwQ-32B`.

Compared to offline RL, online RL yields larger improvements in a model's reasoning capabilities. Since our baselines already include strong distillation models, some benchmarks used in offline evaluation are nearing saturation. To provide a better assessment, we expand our evaluation suite beyond `AMC23`, `AIME24`, `MATH500`, and `OlympiadBench` by including `AIME25`, `GradeSchool` (Ye et al., 2025), `CHMath24`, `Kaoyan`, and `Gaokao`. Specifically, `CHMath24` is the benchmark from the 2024 Chinese High School Mathematics League Competition, `Gaokao` from China's 2024 National College Entrance Examination, `Kaoyan` from the Chinese Graduate School Entrance Examinations, and `GradeSchool` targets elementary-level mathematical reasoning. Among these, `CHMath24` and `Gaokao` each contain fewer than 100 questions, for which we apply the temperature-based decoding for evaluation.

For GRPO training, we use the `AIME` collections from 1997 to 2023 provided in DeepScaler (Luo et al., 2025b), training for 12 epochs. All training questions are in English, while evaluation benchmarks include multilingual questions. Notably, negative samples learned during training generalize well to out-of-domain

Table 3: Evaluation results are reported for `DeepSeek-R1-Distill-Qwen-7B` across four independent runs. First column indicates judge models and its corresponding reward stability setup.

| | Kaoyan
pass@1 | GradeMath
pass@1 | MATH500
pass@1 | Olympiads
pass@1 | CHMath24
avg@16 | AIME25
avg@16 | AIME24
avg@16 | GaoKao
avg@16 | AMC23
avg@16 | Overall
avg |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | **DeepSeek-R1-Distill-Qwen-7B-SGPO** | | | | | |
| +Qwen3-235B-A22B | 53.90 ± 2.10 | 46.55 ± 0.24 | 91.30 ± 0.87 | 53.45 ± 1.35 | 74.48 ± 1.10 | 37.40 ± 1.05 | 55.73 ± 1.39 | 81.33 ± 0.18 | 90.19 ± 0.48 | 64.92 ± 0.37 |
| +QwQ-32B | 53.89 ± 1.66 | 44.88 ± 1.36 | 91.15 ± 0.84 | 53.71 ± 0.74 | 74.33 ± 1.29 | 37.03 ± 1.23 | 54.76 ± 1.87 | 81.91 ± 0.53 | 90.08 ± 1.23 | 64.64 ± 0.41 |
| +QwQ-32B w/o $\{\beta,\gamma\}$ | 56.14 ± 2.76 | 44.53 ± 2.41 | 90.10 ± 0.66 | 53.64 ± 1.08 | 73.89 ± 1.13 | 38.70 ± 1.80 | 53.63 ± 2.15 | 81.24 ± 0.50 | 88.83 ± 0.81 | 64.52 ± 0.57 |

Table 4: Evaluation results are reported for `DeepSeek-R1-Distill-Qwen-7B` as base model and `QwQ-32B` as judge model with and without majority voting.

| | Kaoyan
pass@1 | GradeMath
pass@1 | MATH500
pass@1 | Olympiads
pass@1 | CHMath24
avg@16 | AIME25
avg@16 | AIME24
avg@16 | GaoKao
avg@16 | AMC23
avg@16 | Overall
avg |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | **DeepSeek-R1-Distill-Qwen-7B-SGPO** | | | | | |
| +QwQ-32B | 53.89 ± 1.66 | 44.88 ± 1.36 | 91.15 ± 0.84 | 53.71 ± 0.74 | 74.33 ± 1.29 | 37.03 ± 1.23 | 54.76 ± 1.87 | 81.91 ± 0.53 | 90.08 ± 1.23 | 64.64 ± 0.41 |
| +QwQ-32B with voting | 56.66 ± 1.66 | 45.24 ± 2.16 | 91.35 ± 0.50 | 53.82 ± 0.94 | 74.19 ± 0.92 | 37.35 ± 2.25 | 55.81 ± 0.99 | 82.12 ± 0.43 | 90.53 ± 1.07 | 65.23 ± 0.18 |

Table 5: Evaluation results are reported in terms of `pass@16` across benchmarks. The first two columns show the total number of questions and the number solved within 16 attempts, while the last two columns report the number of questions solved by SGPO but not by GRPO (SGPO\GRPO), and vice versa (GRPO\SGPO).

	SGPO - `pass@16`	GRPO - `pass@16`	SGPO \ GRPO	GRPO \ SGPO
AIME24	23/30	19/30	4	0
AIME25	21/30	21/30	1	1
Gaokao	70/79	68/79	2	0
AMC23	39/40	38/40	1	0
CHMath24	27/30	25/30	2	0

mathematical reasoning tasks. SGPO training follows the same setup. With batch-simultaneous processing, judge model calls take 90 seconds per batch of negatives, adding 10% wall-clock time relative to rollout and update. Step-wise supervision is applied only to all-negative-sample groups during the first three epochs, as we expect this duration to suffice for the model to internalize corrective signals; beyond this point, unresolved examples are more indicative of model capacity limits than learnability. Accordingly, the end-to-end wall-clock overhead is upper bounded by approximately $10\% \times 3/12 = 2.5\%$, and in practice this overhead can be offset by a small reduction of time needed to reach a target performance. For all models, rollout length is fixed at 8192 tokens and group size at 8. Models less than 8B are trained on 8 H100, 14B models on 16 H100, and 32B models on 32 H200. We adopt the default KL coefficient and learning rate from the `verl` training script (Sheng et al., 2025), and use the LIMO evaluation script (Ye et al., 2025), both of which are standard practices in the community.

A key insight from Table 2 is that stronger models generate higher-quality negative samples, which substantially aid learning. As model capability improves, so does the informativeness of its mistakes. Negative samples broadly fall into two categories: (i) correct reasoning trajectories truncated by output length limits, and (ii) trajectories containing logical errors. The first type remains highly valuable – yet discarded in GRPO – since it preserves meaningful reasoning steps, motivating our step-wise judge model. The second type, though incorrect, still provides informative signals, especially when all samples fail on genuinely challenging problems. Notably, stronger distilled models average 6K tokens per response, compared to only 1K tokens for weaker base models, making truncated but informative negative samples more common in the stronger case. Likewise, their erroneous responses also tend to be richer and more useful for step-level judgment.

Figure 2: Mean performance and its standard deviation over multiple runs across different judge model setups.

4.3 Other Ablation Studies

To assess reliability of judge models, we evaluate our approach not only with strong closed-source reasoning models but also with publicly available models of weaker capacity: `DeepSeek-V3`, `Qwen3-235B` and `QwQ-32B`. As shown in Table 2 (best-tuned results) and Table 3 (multiple runs with weaker judges), performance remains stable, indicating that weaker judges do not significantly degrade outcomes. We attribute this reliability to two design choices: (i) first-step error identification with the reference answer. SGPO requires the judge only to verify each step against the reference, not to solve the problem, thereby reducing task difficulty and avoiding the pitfalls of generic PRMs; (ii) reward stability parameters β and γ, which filter and smooth noisy signals. As confirmed by ablations, removing β and γ increases variance and weakens performance. To improve verification, we incorporate a Grok4−Heavy-inspired strategy: multiple independent evaluations by the judge model, with the error position selected by majority voting. Using `QwQ-32B` as the judge model, `DeepSeek-R1-Distill-Qwen-7B` as the base model, and four rollouts per judgment, we have observed noticeable gains in consistency and stability (see Table 4).

While `avg@16` measures average performance across rollouts, `pass@16` reflects the ability to solve new questions with multiple attempts. As shown in Table 5, SGPO's gains in `pass@16` stem directly from leveraging negative samples. Learning only from solvable problems reinforces existing ability, whereas all-negative-sample groups correspond to genuinely difficult questions where GRPO consistently fails. These are precisely the cases where additional feedback can be most valuable. By providing step-level signals, SGPO rewards near-misses by reinforcing correct reasoning up to the first error, penalizes early failures by discouraging persistent error modes, and exposes blind spots by turning hard cases into informative training signals. In this regard, SGPO can provide additional benefits over GRPO, covering more hard problems and providing sharper credit assignment, which translates to faster and more reliable learning under realistic compute budgets.

Figure 3: Evaluation results on GRPO and SGPO. SGPO rewards end at epoch 3.

By leveraging richer early-stage signals from negative samples, SGPO can achieve competitive performance with GRPO, and in some cases better performance or improved coverage on hard problems. As shown in Figure 3, SGPO continues improving beyond epoch 5 by solving several additional hard training problems, whereas GRPO plateaus. This improvement stems from informative negative samples that help resolve previously unsolved problems as also shown in Table 5. In line with our theoretical finding that SGPO converges faster than GRPO, empirical metrics offer supporting evidence. Prior work on RLVR entropy highlights its link to performance: Cui et al. (2025) showed that lower policy entropy under correct signals

Figure 4: Policy entropy levels during training for GRPO and SGPO across different base models.

correlates with stronger policies, while Agarwal et al. (2025) demonstrated that directly minimizing entropy can improve performance. As shown in Figure 4, SGPO reduces policy entropy more rapidly than GRPO, indicating faster convergence toward deterministic RLVR behavior with higher rollout confidence. This matches our theoretical results, confirming that step-wise signals accelerate convergence.

4.4 Discussions

We highlight the motivation for evaluating both offline and online RL. In the offline setup, training uses **only** negative samples, allowing us to directly test whether incorrect or incomplete reasoning trajectories can improve performance. In the online setup, we simulate realistic GRPO training, where batches contain a random mix of positive and negative samples. This demonstrates that negative samples are not only effective in isolation but also remain valuable in practical settings with noisier, mixed data. While mixing positives and negatives introduces noise, simply discarding negative samples does not stabilize training; in several cases, the performance of GRPO even drops below baseline, as the model overfits to problems it can already solve.

This instability arises from limited out-of-domain generalization and catastrophic forgetting. Without exposure to challenging or partially correct reasoning, the model risks overfitting to easy cases, reinforcing shallow heuristics instead of developing robust problem-solving skills. The absence of diverse failure cases can also cause catastrophic forgetting, degrading performance on previously solvable tasks. Incorporating negative samples mitigates these issues, as SGPO consistently outperforms GRPO on Chinese OOD math benchmarks. We emphasize that SGPO does not guarantee uniform improvements on every benchmark: its gains depend on the structure of negative samples. SGPO is most beneficial when failures are due to truncated but largely correct trajectories or localized mistakes, whereas when negative samples fail very early or lack meaningful structure, the step-wise signal can be less informative and gains may diminish. These observations motivate further work on more stable training frameworks, including richer reward diversification mechanisms for handling negative samples and efficient RL methods beyond GRPO.

5 Conclusion

We propose a simple and efficient framework that introduces response diversity within all-negative-sample groups and prove, in a simplified setting, that such diversification can accelerate the learning dynamic of GRPO. Empirically, our approach can yield consistent improvements across model sizes in both offline and online training over nine benchmarks, including base and distilled variants. Future works include extending theoretical results to broader multi-step reasoning tasks, applying response diversity to accelerate other RL methods, and designing lightweight, task-specific reward models that evaluate reasoning steps correctly even if they cannot solve the full problem.

References

J. Achiam, S. Adler, S. Agarwal, L. Ahmad, I. Akkaya, F. L. Aleman, D. Almeida, J. Altenschmidt, S. Altman, S. Anadkat, et al. GPT-4 technical report. *ArXiv Preprint: 2303.08774*, 2023. (Not cited.)

A. Agarwal, S. M. Kakade, J. D. Lee, and G. Mahajan. Optimality and approximation with policy gradient methods in markov decision processes. In *COLT*, pp. 64–66, 2020. (Not cited.)

S. Agarwal, Z. Zhang, L. Yuan, J. Han, and H. Peng. The unreasonable effectiveness of entropy minimization in LLM reasoning. *ArXiv Preprint: 2505.15134*, 2025. (Not cited.)

A. Ahmadian, C. Cremer, M. Gallé, M. Fadaee, J. Kreutzer, O. Pietquin, A. Üstün, and S. Hooker. Back to basics: Revisiting REINFORCE-style optimization for learning from human feedback in LLMs. In *ACL*, pp. 12248–12267, 2024. (Not cited.)

D. Arora and A. Zanette. Training language models to reason efficiently. *ArXiv Preprint: 2502.04463*, 2025. (Not cited.)

M. G. Azar, Z. Guo, B. Piot, R. Munos, M. Rowland, M. Valko, and D. Calandriello. A general theoretical paradigm to understand learning from human preferences. In *AISTATS*, pp. 4447–4455, 2024. (Not cited.)

Y. Bai, S. Kadavath, S. Kundu, A. Askell, J. Kernion, A. Jones, A. Chen, A. Goldie, A. Mirhoseini, C. McKinnon, et al. Constitutional AI: Harmlessness from AI feedback. *ArXiv Preprint: 2212.08073*, 2022. (Not cited.)

M. Besta, N. Blach, A. Kubicek, R. Gerstenberger, M. Podstawski, L. Gianinazzi, J. Gajda, T. Lehmann, H. Niewiadomski, P. Nyczyk, et al. Graph of thoughts: Solving elaborate problems with large language models. In *AAAI*, pp. 17682–17690, 2024. (Not cited.)

X. Bi, D. Chen, G. Chen, S. Chen, D. Dai, C. Deng, H. Ding, K. Dong, Q. Du, Z. Fu, et al. Deepseek LLM: Scaling open-source language models with longtermism. *ArXiv Preprint: 2401.02954*, 2024. (Not cited.)

T. B. Brown, B. Mann, N. Ryder, M. Subbiah, J. Kaplan, P. Dhariwal, A. Neelakantan, P. Shyam, G. Sastry, A. Askell, et al. Language models are few-shot learners. In *NeurIPS*, pp. 1877–1901, 2020. (Not cited.)

H. Chen, G. He, L. Yuan, G. Cui, H. Su, and J. Zhu. Noise contrastive alignment of language models with explicit rewards. In *NeurIPS*, pp. 117784–117812, 2024a. (Not cited.)

H. Chen, H. Zhao, H. Lam, D. Yao, and W. Tang. MallowsPO: Fine-tune your LLM with preference dispersions. In *ICLR*, 2025a. URL https://openreview.net/forum?id=d8cnezVcaW. (Not cited.)

P. Chen, X. Chen, W. Yin, and T. Lin. ComPO: Preference alignment via comparison oracles. *ArXiv Preprint: 2505.05465*, 2025b. (Not cited.)

Q. Chen, L. Qin, J. Liu, D. Peng, J. Guan, P. Wang, M. Hu, Y. Zhou, T. Gao, and W. Che. Towards reasoning era: A survey of long chain-of-thought for reasoning large language models. *ArXiv Preprint: 2503.09567*, 2025c. (Not cited.)

X. Chen, J. Xu, T. Liang, Z. He, J. Pang, D. Yu, L. Song, Q. Liu, M. Zhou, Z. Zhang, et al. Do not think that much for 2+3 = ? on the overthinking of o1-like LLMs. *ArXiv Preprint: 2412.21187*, 2024b. (Not cited.)

J. Cheng and B. Van Durme. Compressed chain of thought: Efficient reasoning through dense representations. *ArXiv Preprint: 2412.13171*, 2024. (Not cited.)

D. R. Chialvo and P. Bak. Learning from mistakes. *Neuroscience*, 90(4):1137–1148, 1999. (Not cited.)

A. Chowdhery, S. Narang, J. Devlin, M. Bosma, G. Mishra, A. Roberts, P. Barham, H. W. Chung, C. Sutton, S. Gehrmann, et al. Palm: Scaling language modeling with pathways. *Journal of Machine Learning Research*, 24(240):1–113, 2023. (Not cited.)

P. F. Christiano, J. Leike, T. B. Brown, M. Martic, S. Legg, and D. Amodei. Deep reinforcement learning from human preferences. In *NeurIPS*, pp. 4302–4310, 2017. (Not cited.)

X. Chu, H. Huang, X. Zhang, F. Wei, and Y. Wang. GPG: A simple and strong reinforcement learning baseline for model reasoning. *ArXiv Preprint: 2504.02546*, 2025. (Not cited.)

K. Cobbe, V. Kosaraju, M. Bavarian, M. Chen, H. Jun, L. Kaiser, M. Plappert, J. Tworek, J. Hilton, R. Nakano, et al. Training verifiers to solve math word problems. *ArXiv Preprint: 2110.14168*, 2021. (Not cited.)

G. Cui, Y. Zhang, J. Chen, L. Yuan, Z. Wang, Y. Zuo, H. Li, Y. Fan, H. Chen, W. Chen, et al. The entropy mechanism of reinforcement learning for reasoning language models. *ArXiv Preprint: 2505.22617*, 2025. (Not cited.)

P. Dayan. Reinforcement comparison. In *Connectionist Models*, pp. 45–51. Elsevier, 1991. (Not cited.)

B. Ding, C. Qin, L. Liu, Y. K. Chia, B. Li, S. Joty, and L. Bing. Is GPT-3 a good data annotator? In *ACL*, pp. 11173–11195, 2023. (Not cited.)

H. Dong, W. Xiong, D. Goyal, Y. Zhang, W. Chow, R. Pan, S. Diao, J. Zhang, K. Shum, and T. Zhang. RAFT: Reward ranked fine-tuning for generative foundation model alignment. *Transactions on Machine Learning Research*, 2023. URL https://openreview.net/forum?id=m7p5O7zblY. (Not cited.)

H. Dong, W. Xiong, B. Pang, H. Wang, H. Zhao, Y. Zhou, N. Jiang, D. Sahoo, C. Xiong, and T. Zhang. RLHF workflow: From reward modeling to online RLHF. *Transactions on Machine Learning Research*, 2024. URL https://openreview.net/forum?id=a13aYUU9eU. (Not cited.)

K. Ethayarajh, W. Xu, N. Muennighoff, D. Jurafsky, and D. Kiela. Model alignment as prospect theoretic optimization. In *ICML*, pp. 12634–12651, 2024. (Not cited.)

G. Feng, B. Zhang, Y. Gu, H. Ye, D. He, and L. Wang. Towards revealing the mystery behind chain of thought: A theoretical perspective. In *NeurIPS*, pp. 70757–70798, 2023. (Not cited.)

K. Gandhi, D. Lee, G. Grand, M. Liu, W. Cheng, A. Sharma, and N. D. Goodman. Stream of search (SOS): Learning to search in language. *ArXiv Preprint: 2404.03683*, 2024. (Not cited.)

L. Gao, J. Schulman, and J. Hilton. Scaling laws for reward model overoptimization. In *ICML*, pp. 10835–10866, 2023. (Not cited.)

F. Gilardi, M. Alizadeh, and M. Kubli. ChatGPT outperforms crowd workers for text-annotation tasks. *Proceedings of the National Academy of Sciences*, 120(30):e2305016120, 2023. (Not cited.)

Z. Gou, Z. Shao, Y. Gong, Y. Shen, Y. Yang, M. Huang, N. Duan, and W. Chen. ToRA: A tool-integrated reasoning agent for mathematical problem solving. In *ICLR*, 2024. URL https://openreview.net/forum?id=Ep0TtjVoap. (Not cited.)

Y. Gu, L. Dong, F. Wei, and M. Huang. MiniLLM: Knowledge distillation of large language models. In *ICLR*, 2024. URL https://openreview.net/forum?id=5h0qf7IBZZ. (Not cited.)

D. Guo, D. Yang, H. Zhang, J. Song, R. Zhang, R. Xu, Q. Zhu, S. Ma, P. Wang, X. Bi, et al. DeepSeek-R1: Incentivizing reasoning capability in LLMs via reinforcement learning. *ArXiv Preprint: 2501.12948*, 2025a. (Not cited.)

J. Guo, Y. Wu, J. Qiu, K. Huang, X. Juan, L. Yang, and M. Wang. Temporal consistency for LLM reasoning process error identification. *ArXiv Preprint: 2503.14495*, 2025b. (Not cited.)

S. Hao, Y. Gu, H. Ma, J. Hong, Z. Wang, D. Wang, and Z. Hu. Reasoning with language model is planning with world model. In *EMNLP*, pp. 8154–8173, 2023. (Not cited.)

S. Hao, Y. Gu, H. Luo, T. Liu, X. Shao, X. Wang, S. Xie, H. Ma, A. Samavedhi, Q. Gao, Z. Wang, and Z. Hu. LLM reasoners: New evaluation, library, and analysis of step-by-step reasoning with large language models. In *COLM*, 2024a. URL https://openreview.net/forum?id=b0y6fbSUG0. (Not cited.)

S. Hao, S. Sukhbaatar, D. Su, X. Li, Z. Hu, J. Weston, and Y. Tian. Training large language models to reason in a continuous latent space. *ArXiv Preprint: 2412.06769*, 2024b. (Not cited.)

A. Havrilla, Y. Du, S. C. Raparthy, C. Nalmpantis, J. Dwivedi-Yu, M. Zhuravinskyi, E. Hambro, S. Sukhbaatar, and R. Raileanu. Teaching large language models to reason with reinforcement learning. *ArXiv Preprint: 2403.04642*, 2024. (Not cited.)

C. He, R. Luo, Y. Bai, S. Hu, Z. Thai, J. Shen, J. Hu, X. Han, Y. Huang, Y. Zhang, et al. OlympiadBench: A challenging benchmark for promoting AGI with Olympiad-level bilingual multimodal scientific problems. In *ACL*, pp. 3828–3850, 2024. (Not cited.)

T. He, R. Mu, L. Liao, Y. Cao, M. Liu, and B. Qin. Good learners think their thinking: Generative PRM makes large reasoning model more efficient math learner. *ArXiv Preprint: 2507.23317*, 2025. (Not cited.)

D. Hendrycks, C. Burns, S. Kadavath, A. Arora, S. Basart, E. Tang, D. Song, and J. Steinhardt. Measuring mathematical problem solving with the MATH dataset. In *NeurIPS Datasets and Benchmarks Track*, 2021. URL https://openreview.net/forum?id=7Bywt2mQsCe. (Not cited.)

J. Hong, N. Lee, and J. Thorne. ORPO: Monolithic preference optimization without reference model. In *EMNLP*, pp. 11170–11189, 2024. (Not cited.)

A. Hosseini, X. Yuan, N. Malkin, A. Courville, A. Sordoni, and R. Agarwal. V-STar: Training verifiers for self-taught reasoners. In *COLM*, 2024. URL https://openreview.net/forum?id=stmqBSW2dV. (Not cited.)

J. Huang and K. C-C. Chang. Towards reasoning in large language models: A survey. In *ACL*, pp. 1049–1065, 2023. (Not cited.)

K. Huang, J. Guo, Z. Li, X. Ji, J. Ge, W. Li, Y. Guo, T. Cai, H. Yuan, R. Wang, Y. Wu, M. Yin, S. Tang, Y. Huang, C. Jin, X. Chen, C. Zhang, and M. Wang. MATH-Perturb: Benchmarking LLMs' math reasoning abilities against hard perturbations. *ArXiv Preprint: 2502.06453*, 2025. (Not cited.)

S. Huang, Z. Ma, J. Du, C. Meng, W. Wang, and Z. Lin. Mirror-consistency: Harnessing inconsistency in majority voting. In *EMNLP*, pp. 2408–2420, 2024. (Not cited.)

H. Hwang, D. Kim, S. Kim, S. Ye, and M. Seo. Self-explore: Enhancing mathematical reasoning in language models with fine-grained rewards. In *EMNLP*, pp. 1444–1466, 2024. (Not cited.)

A. Jaech, A. Kalai, A. Lerer, A. Richardson, A. El-Kishky, A. Low, A. Helyar, A. Madry, A. Beutel, A. Carney, et al. OpenAI o1 system card. *ArXiv Preprint: 2412.16720*, 2024. (Not cited.)

N. Jain, K. Han, A. Gu, W-D. Li, F. Yan, T. Zhang, S. Wang, A. Solar-Lezama, K. Sen, and I. Stoica. LiveCodeBench: Holistic and contamination free evaluation of large language models for code. In *ICLR*, 2025. URL https://openreview.net/forum?id=chfJJYC3iL. (Not cited.)

M. Kang, S. Lee, J. Baek, K. Kawaguchi, and S. J. Hwang. Knowledge-augmented reasoning distillation for small language models in knowledge-intensive tasks. In *NeurIPS*, pp. 48573–48602, 2023. (Not cited.)

Amirhossein Kazemnejad, Milad Aghajohari, Eva Portelance, Alessandro Sordoni, Siva Reddy, Aaron Courville, and Nicolas Le Roux. VinePPO: Accurate credit assignment in RL for LLM mathematical reasoning. In *The 4th Workshop on Mathematical Reasoning and AI at NeurIPS'24*, 2024. URL https://openreview.net/forum?id=KqALqWJSbF. (Not cited.)

T. Khot, H. Trivedi, M. Finlayson, Y. Fu, K. Richardson, P. Clark, and A. Sabharwal. Decomposed prompting: A modular approach for solving complex tasks. In *ICLR*, 2023. URL https://openreview.net/forum?id=_nGgzQjzaRy. (Not cited.)

M. Kwon, S. M. Xie, K. Bullard, and D. Sadigh. Reward design with language models. In *ICLR*, 2023. URL https://openreview.net/forum?id=10uNUgI5Kl. (Not cited.)

A. K. Lampinen, I. Dasgupta, S. C. Y. Chan, H. R. Sheahan, A. Creswell, D. Kumaran, J. L. McClelland, and F. Hill. Language models, like humans, show content effects on reasoning tasks. *PNAS Nexus*, 3(7): pgae233, 2024. (Not cited.)

Y. LeCun. A path towards autonomous machine intelligence version 0.9. 2, 2022-06-27. *Open Review*, 62(1): 1–62, 2022. (Not cited.)

H. Lee, S. Phatale, H. Mansoor, T. Mesnard, J. Ferret, K. Lu, C. Bishop, E. Hall, V. Carbune, A. Rastogi, et al. RLAIF vs. RLHF: Scaling reinforcement learning from human feedback with AI feedback. In *ICML*, pp. 26874–26901, 2024. (Not cited.)

L. Lehnert, S. Sukhbaatar, D. Su, Q. Zheng, P. McVay, M. Rabbat, and Y. Tian. Beyond $A^\star$: Better planning with transformers via search dynamics bootstrapping. In *COLM*, 2024. URL https://openreview.net/forum?id=SGoVIC0uOf. (Not cited.)

Z. Li, H. Liu, D. Zhou, and T. Ma. Chain of thought empowers transformers to solve inherently serial problems. In *ICLR*, 2024a. URL https://openreview.net/forum?id=3EWTEy9MTM. (Not cited.)

Z. Li, T. Xu, Y. Zhang, Z. Lin, Y. Yu, R. Sun, and Z-Q. Luo. ReMax: A simple, effective, and efficient reinforcement learning method for aligning large language models. In *ICML*, pp. 29128–29163, 2024b. (Not cited.)

Z. Li, C. Chen, T. Xu, Z. Qin, J. Xiao, Z-Q. Luo, and R. Sun. Preserving diversity in supervised fine-tuning of large language models. In *ICLR*, 2025. URL https://openreview.net/forum?id=NQEe7B7bSw. (Not cited.)

H. Lightman, V. Kosaraju, Y. Burda, H. Edwards, B. Baker, T. Lee, J. Leike, J. Schulman, I. Sutskever, and K. Cobbe. Let's verify step by step. In *ICLR*, 2024. URL https://openreview.net/forum?id=v8L0pN6EOi. (Not cited.)

T. Liu, Y. Zhao, R. Joshi, M. Khalman, M. Saleh, P. J. Liu, and J. Liu. Statistical rejection sampling improves preference optimization. In *ICLR*, 2024a. URL https://openreview.net/forum?id=xbjSwwrQOe. (Not cited.)

T. Liu, Z. Qin, J. Wu, J. Shen, M. Khalman, R. Joshi, Y. Zhao, M. Saleh, S. Baumgartner, J. Liu, et al. LiPO: Listwise preference optimization through learning-to-rank. In *NAACL*, pp. To appear, 2025a. (Not cited.)

Z. Liu, M. Lu, S. Zhang, B. Liu, H. Guo, Y. Yang, J. Blanchet, and Z. Wang. Provably mitigating overoptimization in RLHF: Your SFT loss is implicitly an adversarial regularizer. In *NeurIPS*, pp. 138663–138697, 2024b. (Not cited.)

Z. Liu, C. Chen, W. Li, P. Qi, T. Pang, C. Du, W. S. Lee, and M. Lin. Understanding R1-zero-like training: A critical perspective. *ArXiv Preprint: 2503.20783*, 2025b. (Not cited.)

H. Luo, L. Shen, H. He, Y. Wang, S. Liu, W. Li, N. Tan, X. Cao, and D. Tao. o1-pruner: Length-harmonizing fine-tuning for o1-like reasoning pruning. *ArXiv Preprint: 2501.12570*, 2025a. (Not cited.)

L. Luo, Y. Liu, R. Liu, S. Phatale, M. Guo, H. Lara, Y. Li, L. Shu, Y. Zhu, L. Meng, et al. Improve mathematical reasoning in language models by automated process supervision. *ArXiv Preprint: 2406.06592*, 2024. (Not cited.)

M. Luo, S. Tan, J. Wong, X. Shi, W. Y. Tang, M. Roongta, C. Cai, J. Luo, L. E. Li, R. A. Popa, and I. Stoica. DeepScaleR: Surpassing o1-preview with a 1.5B model by scaling RL. https://pretty-radio-b75.notion.site/DeepScaleR-Surpassing-O1-Preview-with-a-1-5B-Model-by-Scaling-RL-19681902c1468005bed8ca303013a4e2, 2025b. Notion Blog. (Not cited.)

A. Madaan, K. Hermann, and A. Yazdanbakhsh. What makes chain-of-thought prompting effective? a counterfactual study. In *EMNLP*, pp. 1448–1535, 2023. (Not cited.)

J. Mei, Y. Gao, B. Dai, C. Szepesvari, and D. Schuurmans. Leveraging non-uniformity in first-order non-convex optimization. In *ICML*, pp. 7555–7564, 2021. (Not cited.)

Y. Meng, M. Xia, and D. Chen. SimPO: Simple preference optimization with a reference-free reward. In *NeurIPS*, pp. 124198–124235, 2024. (Not cited.)

W. Merrill and A. Sabharwal. The expressive power of transformers with chain of thought. In *ICLR*, 2024. URL https://openreview.net/forum?id=NjNGlPh8Wh. (Not cited.)

L. Ouyang, J. Wu, X. Jiang, D. Almeida, C. L. Wainwright, P. Mishkin, C. Zhang, S. Agarwal, K. Slama, A. Ray, et al. Training language models to follow instructions with human feedback. In *NeurIPS*, pp. 27730–27744, 2022. (Not cited.)

A. Pal, D. Karkhanis, S. Dooley, M. Roberts, S. Naidu, and C. White. Smaug: Fixing failure modes of preference optimisation with DPO-positive. *ArXiv Preprint: 2402.13228*, 2024. (Not cited.)

R. Y. Pang, W. Yuan, H. He, K. Cho, S. Sukhbaatar, and J. Weston. Iterative reasoning preference optimization. In *NeurIPS*, pp. 116617–116637, 2024. (Not cited.)

R. Park, R. Rafailov, S. Ermon, and C. Finn. Disentangling length from quality in direct preference optimization. In *ACL*, pp. 4998–5017, 2024. (Not cited.)

X. Peng, A. Kumar, G. Zhang, and S. Levine. Advantage-weighted regression: Simple and scalable off-policy reinforcement learning. *ArXiv Preprint: 1910.00177*, 2019. (Not cited.)

J. Peters and S. Schaal. Reinforcement learning by reward-weighted regression for operational space control. In *ICML*, pp. 745–750, 2007. (Not cited.)

R. Rafailov, A. Sharma, E. Mitchell, S. Ermon, C. D. Manning, and C. Finn. Direct preference optimization: Your language model is secretly a reward model. In *NeurIPS*, pp. 53728–53741, 2023. (Not cited.)

R. Rafailov, J. Hejna, R. Park, and C. Finn. From r to q^*: Your language model is secretly a Q-function. In *COLM*, 2024. URL https://openreview.net/forum?id=kEVcNxtqXk. (Not cited.)

N. Razin, S. Malladi, A. Bhaskar, D. Chen, S. Arora, and B. Hanin. Unintentional unalignment: Likelihood displacement in direct preference optimization. In *ICLR*, 2025. URL https://openreview.net/forum?id=uaMSBJDnRv. (Not cited.)

P. Roit, J. Ferret, L. Shani, R. Aharoni, G. Cideron, R. Dadashi, M. Geist, S. Girgin, L. Hussenot, O. Keller, et al. Factually consistent summarization via reinforcement learning with textual entailment feedback. In *ACL*, pp. 6252–6272, 2023. (Not cited.)

J. Schulman, S. Levine, P. Moritz, M. I. Jordan, and P. Abbeel. Trust region policy optimization. In *ICML*, pp. 1889–1897, 2015. (Not cited.)

J. Schulman, F. Wolski, P. Dhariwal, A. Radford, and O. Klimov. Proximal policy optimization algorithms. *ArXiv Preprint: 1707.06347*, 2017. (Not cited.)

A. Setlur, C. Nagpal, A. Fisch, X. Geng, J. Eisenstein, R. Agarwal, A. Agarwal, J. Berant, and A. Kumar. Rewarding progress: Scaling automated process verifiers for LLM reasoning. In *ICLR*, 2025. URL https://openreview.net/forum?id=A6Y7AqlzLW. (Not cited.)

Amrith Setlur, Saurabh Garg, Xinyang Geng, Naman Garg, Virginia Smith, and Aviral Kumar. RL on incorrect synthetic data scales the efficiency of LLM math reasoning by eight-fold. In *NeurIPS*, pp. 43000–43031, 2024. (Not cited.)

Z. Shao, P. Wang, Q. Zhu, R. Xu, J. Song, X. Bi, H. Zhang, M. Zhang, Y. K. Li, Y. Wu, et al. DeepSeekMath: Pushing the limits of mathematical reasoning in open language models. *ArXiv Preprint: 2402.03300*, 2024. (Not cited.)

G. Sheng, C. Zhang, Z. Ye, X. Wu, W. Zhang, R. Zhang, Y. Peng, H. Lin, and C. Wu. HybridFlow: A flexible and efficient RLHF framework. In *EuroSys*, pp. 1279–1297. ACM, 2025. (Not cited.)

B. Shi, M. Tang, K. R. Narasimhan, and S. Yao. Can language models solve Olympiad programming? In *COLM*, 2024. URL https://openreview.net/forum?id=kGa4fMtP9l. (Not cited.)

D. Silver, A. Huang, C. J. Maddison, A. Guez, L. Sifre, G. Van Den Driessche, J. Schrittwieser, I. Antonoglou, V. Panneershelvam, M. Lanctot, et al. Mastering the game of Go with deep neural networks and tree search. *Nature*, 529(7587):484–489, 2016. (Not cited.)

A. Singh, J. D. Co-Reyes, R. Agarwal, A. Anand, P. Patil, X. Garcia, P. J. Liu, J. Harrison, J. Lee, K. Xu, A. T. Parisi, A. Kumar, A. A. Alemi, A. Rizkowsky, A. Nova, B. Adlam, B. Bohnet, G. F. Elsayed, H. Sedghi, I. Mordatch, I. Simpson, I. Gur, J. Snoek, J. Pennington, J. Hron, K. Kenealy, K. Swersky, K. Mahajan, L. A. Culp, L. Xiao, M. Bileschi, N. Constant, R. Novak, R. Liu, T. Warkentin, Y. Bansal, E. Dyer, B. Neyshabur, J. Sohl-Dickstein, and N. Fiedel. Beyond human data: Scaling self-training for problem-solving with language models. *Transactions on Machine Learning Research*, 2024. ISSN 2835-8856. URL https://openreview.net/forum?id=lNAyUngGFK. Expert Certification. (Not cited.)

I. Singh, V. Blukis, A. Mousavian, A. Goyal, D. Xu, J. Tremblay, D. Fox, J. Thomason, and A. Garg. ProgPrompt: Generating situated robot task plans using large language models. In *ICRA*, pp. 11523–11530. IEEE, 2023. (Not cited.)

J. Skalse, N. H. R. Howe, D. Krasheninnikov, and D. Krueger. Defining and characterizing reward hacking. In *NeurIPS*, pp. 9460–9471, 2022. (Not cited.)

C. V. Snell, J. Lee, K. Xu, and A. Kumar. Scaling LLM test-time compute optimally can be more effective than scaling parameters for reasoning. In *ICLR*, 2025. URL https://openreview.net/forum?id=4FWAwZtd2n. (Not cited.)

F. Song, B. Yu, M. Li, H. Yu, F. Huang, Y. Li, and H. Wang. Preference ranking optimization for human alignment. In *AAAI*, pp. 18990–18998, 2024. (Not cited.)

S. Srivastava, A. PV, S. Menon, A. Sukumar, A. Philipose, S. Prince, S. Thomas, et al. Functional benchmarks for robust evaluation of reasoning performance, and the reasoning gap. *ArXiv Preprint: 2402.19450*, 2024. (Not cited.)

N. Stiennon, L. Ouyang, J. Wu, D. Ziegler, R. Lowe, C. Voss, A. Radford, D. Amodei, and P. F. Christiano. Learning to summarize with human feedback. In *NeurIPS*, pp. 3008–3021, 2020. (Not cited.)

D. Su, S. Sukhbaatar, M. Rabbat, Y. Tian, and Q. Zheng. Dualformer: Controllable fast and slow thinking by learning with randomized reasoning traces. In *ICLR*, 2025. URL https://openreview.net/forum?id=bmbRCRiNDu. (Not cited.)

R. S. Sutton and A. G. Barto. *Reinforcement Learning: An Introduction*, volume 1. MIT Press, 1998. (Not cited.)

F. Tajwar, A. Singh, A. Sharma, R. Rafailov, J. Schneider, T. Xie, S. Ermon, C. Finn, and A. Kumar. Preference fine-tuning of LLMs should leverage suboptimal, on-policy data. In *ICML*, pp. 47441–47474, 2024. (Not cited.)

Y. Tang, Z. Guo, Z. Zheng, D. Calandriello, R. Munos, M. Rowland, P. H. Richemond, M. Valko, B. Pires, and B. Piot. Generalized preference optimization: A unified approach to offline alignment. In *ICML*, pp. 47725–47742, 2024. (Not cited.)

K. Team, A. Du, B. Gao, B. Xing, C. Jiang, C. Chen, C. Li, C. Xiao, C. Du, C. Liao, et al. Kimi k1.5: Scaling reinforcement learning with LLMs. *ArXiv Preprint: 2501.12599*, 2025. (Not cited.)

H. Touvron, T. Lavril, G. Izacard, X. Martinet, M-A. Lachaux, T. Lacroix, B. Rozière, N. Goyal, E. Hambro, F. Azhar, et al. Llama: Open and efficient foundation language models. *ArXiv Preprint: 2302.13971*, 2023. (Not cited.)

J. Uesato, N. Kushman, R. Kumar, F. Song, N. Siegel, L. Wang, A. Creswell, G. Irving, and I. Higgins. Solving math word problems with process-and outcome-based feedback. *ArXiv Preprint: 2211.14275*, 2022. (Not cited.)

A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, Ł. Kaiser, and I. Polosukhin. Attention is all you need. In *NeurIPS*, pp. 6000–6010, 2017. (Not cited.)

H. Wang, C. Qian, W. Zhong, X. Chen, J. Qiu, S. Huang, B. Jin, M. Wang, K-F. Wong, and H. Ji. OTC: Optimal tool calls via reinforcement learning. *ArXiv Preprint: 2504.14870*, 2025. (Not cited.)

P. Wang, L. Li, Z. Shao, R. Xu, D. Dai, Y. Li, D. Chen, Y. Wu, and Z. Sui. Math-Shepherd: Verify and reinforce LLMs step-by-step without human annotations. In *ACL*, pp. 9426–9439, 2024. (Not cited.)

X. Wang, J. Wei, D. Schuurmans, Q. V. Le, E. H. Chi, S. Narang, A. Chowdhery, and D. Zhou. Self-consistency improves chain of thought reasoning in language models. In *ICLR*, 2023. URL https://openreview.net/forum?id=1PL1NIMMrw. (Not cited.)

J. Wei, X. Wang, D. Schuurmans, M. Bosma, B. Ichter, F. Xia, E. H. Chi, Q. V. Le, and D. Zhou. Chain-of-thought prompting elicits reasoning in large language models. In *NeurIPS*, pp. 24824–24837, 2022. (Not cited.)

R. J. Williams. Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Machine Learning*, 8:229–256, 1992. (Not cited.)

Y. Wu, Z. Sun, S. Li, S. Welleck, and Y. Yang. Inference scaling laws: An empirical analysis of compute-optimal inference for LLM problem-solving. In *ICLR*, 2025. URL https://openreview.net/forum?id=VNckp7JEHn. (Not cited.)

V. Xiang, C. Snell, K. Gandhi, A. Albalak, A. Singh, C. Blagden, D. Phung, R. Rafailov, N. Lile, D. Mahan, et al. Towards system 2 reasoning in LLMs: Learning how to think with meta chain-of-though. *ArXiv Preprint: 2501.04682*, 2025. (Not cited.)

J. Xiao, Z. Li, X. Xie, E. Getzen, C. Fang, Q. Long, and W. J. Su. On the algorithmic bias of aligning large language models with RLHF: Preference collapse and matching regularization. *ArXiv Preprint: 2405.16455*, 2024. (Not cited.)

Y. Xie, K. Kawaguchi, Y. Zhao, J. X. Zhao, M-Y. Kan, J. He, and M. Q. Xie. Self-evaluation guided beam search for reasoning. In *NeurIPS*, pp. 41618–41650, 2023. (Not cited.)

W. Xiong, H. Dong, C. Ye, Z. Wang, H. Zhong, H. Ji, N. Jiang, and T. Zhang. Iterative preference learning from human feedback: Bridging theory and practice for RLHF under KL-constraint. In *ICML*, pp. 54715–54754, 2024. (Not cited.)

W. Xiong, J. Yao, Y. Xu, B. Pang, L. Wang, D. Sahoo, J. Li, N. Jiang, T. Zhang, C. Xiong, and H. Dong. A minimalist approach to LLM reasoning: From rejection sampling to reinforce. *ArXiv Preprint: 2504.11343*, 2025a. (Not cited.)

W. Xiong, W. Zhao, W. Yuan, O. Golovneva, T. Zhang, J. Weston, and S. Sukhbaatar. StepWiser: Stepwise generative judges for wiser reasoning. *ArXiv Preprint: 2508.19229*, 2025b. (Not cited.)

H. Xu, A. Sharaf, Y. Chen, W. Tan, L. Shen, B. Van Durme, K. Murray, and Y. J. Kim. Contrastive preference optimization: Pushing the boundaries of LLM performance in machine translation. In *ICML*, pp. 55204–55224, 2024. (Not cited.)

Y. Yang, D. Campbell, K. Huang, M. Wang, J. Cohen, and T. Webb. Emergent symbolic mechanisms support abstract reasoning in large language models. *ArXiv Preprint: 2502.20332*, 2025. (Not cited.)

Z. Yang, P. Qi, S. Zhang, Y. Bengio, W. Cohen, R. Salakhutdinov, and C. D. Manning. HotpotQA: A dataset for diverse, explainable multi-hop question answering. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pp. 2369–2380, 2018. (Not cited.)

S. Yao, D. Yu, J. Zhao, I. Shafran, T. L. Griffiths, Y. Cao, and K. Narasimhan. Tree of thoughts: Deliberate problem solving with large language models. In *NeurIPS*, pp. 11809–11822, 2023. (Not cited.)

Y. Ye, Z. Huang, Y. Xiao, E. Chern, S. Xia, and P. Liu. LIMO: Less is more for reasoning. *ArXiv Preprint: 2502.03387*, 2025. (Not cited.)

F. Yu, A. Gao, and B. Wang. OVM, Outcome-supervised value models for planning in mathematical reasoning. In *NAACL*, pp. 858–875, 2024a. (Not cited.)

F. Yu, L. Jiang, H. Kang, S. Hao, and L. Qin. Flow of reasoning: Efficient training of LLM policy with divergent thinking. In *ICML*, pp. To appear, 2025a. (Not cited.)

L. Yu, W. Jiang, H. Shi, J. Yu, Z. Liu, Y. Zhang, J. Kwok, Z. Li, A. Weller, and W. Liu. MetaMath: Bootstrap your own mathematical questions for large language models. In *ICLR*, 2024b. URL https://openreview.net/forum?id=N8N0hgNDRt. (Not cited.)

Q. Yu, Z. Zhang, R. Zhu, Y. Yuan, X. Zuo, Y. Yue, T. Fan, G. Liu, L. Liu, X. Liu, et al. DAPO: An open-source LLM reinforcement learning system at scale. *ArXiv Preprint: 2503.14476*, 2025b. (Not cited.)

H. Yuan, Z. Yuan, C. Tan, W. Wang, S. Huang, and F. Huang. RRHF: Rank responses to align language models with human feedback. In *NeurIPS*, pp. 10935–10950, 2023a. (Not cited.)

L. Yuan, G. Cui, H. Wang, N. Ding, X. Wang, B. Shan, Z. Liu, J. Deng, H. Chen, R. Xie, Y. Lin, Z. Liu, B. Zhou, H. Peng, Z. Liu, and M. Sun. Advancing LLM reasoning generalists with preference trees. In *ICLR*, 2025. URL https://openreview.net/forum?id=2ea5TNVR0c. (Not cited.)

Z. Yuan, H. Yuan, C. Li, G. Dong, K. Lu, C. Tan, C. Zhou, and J. Zhou. Scaling relationship on learning mathematical reasoning with large language models. *ArXiv Preprint: 2308.01825*, 2023b. (Not cited.)

X. Yue, X. Qu, G. Zhang, Y. Fu, W. Huang, H. Sun, Y. Su, and W. Chen. MAmmoTH: Building math generalist models through hybrid instruction tuning. In *ICLR*, 2024. URL https://openreview.net/forum?id=yLClGs770I. (Not cited.)

E. Zelikman, Y. Wu, J. Mu, and N. D. Goodman. STaR: self-taught reasoner bootstrapping reasoning with reasoning. In *NeurIPS*, pp. 15476–15488, 2022. (Not cited.)

K. Zha, Z. Gao, M. Shen, Z-W. Hong, D. S. Boning, and D. Katabi. RL Tango: Reinforcing generator and verifier together for language reasoning. *ArXiv Preprint: 2505.15034*, 2025. (Not cited.)

D. Zhang, S. Zhoubian, Z. Hu, Y. Yue, Y. Dong, and J. Tang. ReST-MCTS*: LLM self-training via process reward guided tree search. In *NeurIPS*, pp. 64735–64772, 2024a. (Not cited.)

K. Zhang, Y. Hong, J. Bao, H. Jiang, Y. Song, D. Hong, and H. Xiong. GVPO: Group variance policy optimization for large language model post-training. *ArXiv Preprint: 2504.19599*, 2025a. (Not cited.)

L. Zhang, A. Hosseini, H. Bansal, M. Kazemi, A. Kumar, and R. Agarwal. Generative verifiers: Reward modeling as next-token prediction. In *The NeurIPS Workshop on System-2 Reasoning at Scale*, 2024b. URL https://openreview.net/forum?id=aLgXy8A7k7. (Not cited.)

Z. Zhang, C. Zheng, Y. Wu, B. Zhang, R. Lin, B. Yu, D. Liu, J. Zhou, and J. Lin. The lessons of developing process reward models in mathematical reasoning. *ArXiv Preprint: 2501.07301*, 2025b. (Not cited.)

H. Zhao, G. I. Winata, A. Das, S-X. Zhang, D. Yao, W. Tang, and S. Sahu. RainbowPO: A unified framework for combining improvements in preference optimization. In *ICLR*, 2025. URL https://openreview.net/forum?id=trKee5pIFv. (Not cited.)

Y. Zhao, R. Joshi, T. Liu, M. Khalman, M. Saleh, and P. J. Liu. SLiC-HF: Sequence likelihood calibration with human feedback. *ArXiv Preprint: 2305.10425*, 2023. (Not cited.)

D. Zhou, N. Schärli, L. Hou, J. Wei, N. Scales, X. Wang, D. Schuurmans, C. Cui, O. Bousquet, Q. V. Le, and E. H. Chi. Least-to-most prompting enables complex reasoning in large language models. In *ICLR*, 2023. URL https://openreview.net/forum?id=WZH7099tgfM. (Not cited.)

D. M. Ziegler, N. Stiennon, J. Wu, T. B. Brown, A. Radford, D. Amodei, P. Christiano, and G. Irving. Fine-tuning language models from human preferences. *ArXiv Preprint: 1909.08593*, 2019. (Not cited.)

Broader Impacts

While large reasoning models can enable substantial societal and economic benefits, a growing literature also highlights potential negative impacts, including environmental costs from training and inference, concentration of power and access, labor displacement, and downstream misuse (e.g., for manipulation or disinformation). Our work improves the post-training procedure for such models; as a result, it may contribute to both beneficial applications and accelerated adoption, which can amplify these broader concerns. We emphasize that SGPO is a technical contribution and does not address these systemic risks directly. Responsible deployment should consider energy and compute reporting, access and governance practices, and safeguards against misuse. More broadly, we view rigorous assessment of societal impacts alongside technical progress as essential.

A Related Works

We comment on all related topics, including reasoning through chain-of-thought and its variants, test-time compute, direct preference alignment methods, reward models and reinforcement learning from AI feedback. For an overview of more reasoning models and methods, we refer to two recent surveys (Huang & Chang, 2023; Chen et al., 2025c).

Chain-of-Thought and its variants. Chain-of-thought (CoT) refers to as a broad class of methods that generate an intermediate reasoning process before arriving at a final answer. These approaches either prompt LLMs (Wei et al., 2022; Khot et al., 2023; Zhou et al., 2023) or train LLMs to generate reasoning chains through supervised fine-tuning (SFT) (Yue et al., 2024; Yu et al., 2024b; Li et al., 2025) and/or RL (Wang et al., 2024; Shao et al., 2024; Havrilla et al., 2024; Yu et al., 2025a). While CoT has proven effective for certain tasks, its auto-regressive generation nature makes it challenging to mimic human reasoning on more complex problems (LeCun, 2022; Hao et al., 2023), which require planning and search. Recent efforts were devoted to equipping LLMs with tree search methods (Xie et al., 2023; Yao et al., 2023; Hao et al., 2024a) or training LLMs on search trajectories (Lehnert et al., 2024; Gandhi et al., 2024; Su et al., 2025). Several other works have investigated why CoT is effective. For example, (Madaan et al., 2023) used a counterfactual prompting approach to examine the relative contributions of prompt elements, including symbols (digits, entities) and patterns (equations). (Feng et al., 2023; Merrill & Sabharwal, 2024; Li et al., 2024a) analyzed CoT from the perspective of model expressivity, and (Feng et al., 2023) showed that employing CoT increases the effective depth of a transformer since the generated outputs are looped back to the input. This insight motivated the chain-of-continuous-thought paradigm (Hao et al., 2024b), and a related approach has been proposed in (Cheng & Van Durme, 2024).

Reasoning through test-time compute. OpenAI-o1 (Jaech et al., 2024) is among the first large-scale applications of RL to reasoning, and achieved state-of-the-art performance upon release. Following this trend, DeepSeek-R1 (Guo et al., 2025a) is the first open-weight model to match or exceed OpenAI-o1. Their real-world success stories have involved several simple yet novel techniques that enhance LLM reasoning through more test-time compute, including chain-of-thought (Wei et al., 2022), self-consistency (Wang et al., 2023), best-of-N sampling (Snell et al., 2025), process reward models (Lightman et al., 2024), Monte Carlo tree search (Silver et al., 2016; Hao et al., 2023), tree-of-thought (Yao et al., 2023), and recent works on preventing overthinking (Chen et al., 2024b; Team et al., 2025; Luo et al., 2025a; Arora & Zanette, 2025) and compressing chain-of-thought (Hao et al., 2024b; Cheng & Van Durme, 2024). More specifically, *chain-of-thought* is a reasoning approach where intermediate steps are explicitly written to make complex problem-solving processes more transparent and logical. *Self-consistency* suggests generating multiple final answers and returning the mode of an empirical distribution, enhancing test-time performance when test-time verifiers are unavailable. Unfortunately, it is computationally expensive and effective only when answers can be clustered. *Best-of-N sampling* resolves this issue by sampling answers from the model and selecting the best at test time according to the scoring function; however, it is sensitive to the accuracy of test-time scoring functions (Gao et al., 2023). *Process reward models* offer fine-grained supervision of chain-of-thought reasoning, but they might be vulnerable to reward hacking and introduce computation overhead. *Monte Carlo tree search* is a generic technique that allocates computational resources toward the most promising regions of the search space, and *tree-of-thought* and its extension (Besta et al., 2024; Gandhi et al., 2024)

simplified this idea by exploring multiple reasoning paths in a specific structure, allowing language models to select the most promising line of thought for complex problem-solving. Both *length regularization* and *compressed chain-of-thought* are developed to reduce inference costs for reasoning, which is crucial for the economic feasibility, user experience and environmental sustainability of LLMs. In addition, several works have focused on specific reasoning tasks (Lampinen et al., 2024; Yang et al., 2025; Srivastava et al., 2024; Huang et al., 2025; 2024; Guo et al., 2025b; Gou et al., 2024; Wang et al., 2025), demonstrating promising performance. The recent findings Xiong et al. (2025a) have shown that the REINFORCE-type methods (including GRPO (Shao et al., 2024)) can not effectively learn from all-negative-sample groups. Our work alleviates this issue by leveraging AI feedback to differentiate negative samples. We also provide a theoretical analysis through a stylized model, explaining why such diversification improves GRPO's learning dynamics.

Direct preference alignment methods. These methods (e.g., DPO (Rafailov et al., 2023)) are simple and stable offline alternatives to online RLHF. Various DPO variants with other objectives have been proposed, including ranking ones beyond pairwise preference data (Dong et al., 2023; Yuan et al., 2023a; Song et al., 2024; Chen et al., 2024a; Liu et al., 2025a) and simple ones that do not rely on a reference model (Hong et al., 2024; Meng et al., 2024). Since DPO does not train a reward model, the limited size of human labels becomes a bottleneck. To alleviate this limitation, subsequent works proposed to augment preference data using a trained SFT policy (Zhao et al., 2023) or a refined SFT policy with rejection sampling (Liu et al., 2024a). The DPO loss was recently rederived and extended to a token-level MDP view (Rafailov et al., 2024), where the state is the token prefix and the transition is deterministic – which has covered the fine-tuning of LLMs – and more general RL problems (Azar et al., 2024). There are other DPO variants (Ethayarajh et al., 2024; Park et al., 2024; Xu et al., 2024; Tang et al., 2024; Meng et al., 2024; Chen et al., 2025a; Zhao et al., 2025). For example, (Ethayarajh et al., 2024) designed a DPO-style loss variant using a prospect theory, (Tang et al., 2024) optimized a general preference loss instead of the log-likelihood loss, and (Meng et al., 2024) aligned the reward function in the preference optimization objective with the generation metric. Dong et al. (2024) and (Xiong et al., 2024) proposed to generate human feedback in an online fashion to mitigate the distribution-shift and over-parameterization phenomenon. This improves DPO for complex reasoning tasks (Pang et al., 2024). Several other works focus on *unintentional alignment* of DPO and developing new methods (Pal et al., 2024; Tajwar et al., 2024; Liu et al., 2024b; Xiao et al., 2024; Yuan et al., 2025; Razin et al., 2025; Chen et al., 2025b). Among these works, (Razin et al., 2025) proposed to measure the similarity between preferred and dispreferred responses using the centered hidden embedding similarity (CHES) score and showed that filtering out preference pairs with small CHES score improves DPO, while (Chen et al., 2025b) proposed to use comparison oracles, and showed that combining it with DPO effectively alleviated the issue of unintentional alignment.

Reward models. For the prompt $\mathbf{x}$ with a ground-truth response $\mathbf{y}_\mathbf{x}^\star$, we evaluate by implementing a regular expression match on the final answer (Hendrycks et al., 2021): $r(\mathbf{x}, \mathbf{y}) = 1$ if $\mathbf{y}$ matches $\mathbf{y}_\mathbf{x}^\star$ on the *final answer* and $r(\mathbf{x}, \mathbf{y}) = 0$ otherwise. An *outcome reward* model (ORM) (Cobbe et al., 2021; Uesato et al., 2022) is trained for estimating $r(\mathbf{x}, \mathbf{y})$. In particular, we first choose $\mathbf{x} \in \mathcal{D}$ and collect training samples $(\mathbf{x}, \mathbf{y} \sim \pi_\theta(\cdot|\mathbf{x}), r(\mathbf{x}, \mathbf{y}))$. Then, we take $(\mathbf{x}, \mathbf{y})$ as input and train an ORM to predict $r(\mathbf{x}, \mathbf{y})$. This can be done using binary classification (Cobbe et al., 2021; Yu et al., 2024a), direct preference optimization (Hosseini et al., 2024) or next-token prediction (Zhang et al., 2024b). Previous works also train LLMs on self-generated data using the ground-truth outcome reward model with either supervised fine-tuning (Singh et al., 2024; Yuan et al., 2023b; Zelikman et al., 2022) or online RL (Bi et al., 2024; Guo et al., 2025a). A *process reward* model (PRM) is trained to score a_h at $\mathbf{s}_h = (\mathbf{x}, a_1, \ldots, a_{h-1})$ either using human annotations (Lightman et al., 2024) or the value functions based on LLM-generated data (Wang et al., 2024; Luo et al., 2024; Setlur et al., 2025); indeed, PRMs estimate either the likelihood of future success or the change in the likelihood of future success before and after taking a_h. In addition, PRMs were also developed to improve search methods (Snell et al., 2025; Wu et al., 2025), and to identify the "first pit" in an incorrect reasoning trajectory to construct preference pairs for direct preference alignment (Hwang et al., 2024; Setlur et al., 2024). Related work such as VinePPO (Kazemnejad et al., 2024) refines process-level credit assignment in PPO without explicitly training a PRM and avoids a learned value network by using Monte Carlo rollouts from intermediate prefixes; this is complementary to our GRPO-oriented setting.

Reinforcement learning from AI feedback. Reinforcement learning from human feedback (RLHF) uses human-preference-aligned reward models to evaluate response quality (Christiano et al., 2017; Ziegler et al., 2019; Stiennon et al., 2020; Ouyang et al., 2022). A key barrier to scale RLHF is the need for high-quality human labels. Previous studies (Gilardi et al., 2023; Ding et al., 2023) have shown that modern LLMs exhibit strong alignment with human judgments, suggesting that AI-generated labels can serve as a viable alternative. In this context, (Bai et al., 2022) was the first to explore RLAIF, jointly optimizing helpfulness and harmlessness using both human and AI-generated labels, and (Roit et al., 2023; Kwon et al., 2023; Lee et al., 2024) showed that LLMs can produce informative reward signals for RL post-training. Our approach can leverage AI feedback to introduce response diversity within all-negative-sample groups by assigning intermediate binary rewards to reasoning steps. Indeed, one identifies the proportion of correct steps in the reasoning trajectory and use it to compute a reward $r_i \in [0, 1)$.

B   Missing Proofs

In this section, we present the derivations underlying the update rules in Section 3.2. In particular, we derive $g_{\text{GRPO}}(\theta)$ and $g_{\text{SGPO}}(\theta)$, and obtain the corresponding update forms in Eqs. (3) and (4).

To derive $g_{\text{GRPO}}(\theta)$ and $g_{\text{SGPO}}(\theta)$, we start by restating the score functions:

$$s(a_1 = 1 \mid x) = \begin{bmatrix} p \\ -p \\ 0 \\ 0 \end{bmatrix}, \quad s(a_1 = 2 \mid x) = \begin{bmatrix} p - 1 \\ 1 - p \\ 0 \\ 0 \end{bmatrix},$$

$$s(a_2 = 1 \mid x, a_1 = 2) = \begin{bmatrix} 0 \\ 0 \\ q \\ -q \end{bmatrix}, \quad s(a_2 = 2 \mid x, a_1 = 2) = \begin{bmatrix} 0 \\ 0 \\ q - 1 \\ 1 - q \end{bmatrix}.$$

Let $S(y) := \sum_{h=1}^{H} s(a_h \mid x, a_{1:h-1})$ denote the score-sum for trajectory $y = (a_1, a_2)$. Under the restricted trajectory space $\{(1, 1), (2, 1), (2, 2)\}$, we have

$$S(1, 1) = \begin{bmatrix} p \\ -p \\ 0 \\ 0 \end{bmatrix}, \quad S(2, 1) = \begin{bmatrix} p - 1 \\ 1 - p \\ q \\ -q \end{bmatrix}, \quad S(2, 2) = \begin{bmatrix} p - 1 \\ 1 - p \\ q - 1 \\ 1 - q \end{bmatrix},$$

and the trajectory probabilities are

$$\mathbb{P}(1, 1) = 1 - p, \quad \mathbb{P}(2, 1) = p(1 - q), \quad \mathbb{P}(2, 2) = pq.$$

Recall $G = 2$ and $H = 2$. For a single prompt, our estimator averages over both samples and steps:

$$g(\theta) = \frac{1}{GH} \sum_{k=1}^{G} \sum_{h=1}^{H} s\left(a_h^{(k)} \mid x, a_{1:h-1}^{(k)}\right) A_k = \frac{1}{GH} \sum_{k=1}^{G} S(y^{(k)}) A_k,$$

where A_k is the within-group standardized advantage computed from the two rewards. For $G = 2$, whenever the two rewards are distinct, standardization yields $A_{\text{high}} = +1$ and $A_{\text{low}} = -1$; if the rewards are equal we set $A_1 = A_2 = 0$. Hence, for any ordered pair $(y^{(1)}, y^{(2)})$ with distinct rewards,

$$g(\theta) = \frac{1}{GH}(S(y^{(1)}) - S(y^{(2)})) \cdot \text{sign}(r(y^{(1)}) - r(y^{(2)})).$$

GRPO.   In GRPO, $r(2, 2) = 1$ and $r(1, 1) = r(2, 1) = 0$. Thus, the only nonzero contributions come from mixed pairs $\{(2, 2), (1, 1)\}$ and $\{(2, 2), (2, 1)\}$. Using independence of the two samples and summing both orderings,

$$\bar{g}_{\text{GRPO}}(\theta) = \mathbb{E}[g(\theta)] = \frac{2}{GH}(\mathbb{P}(2, 2)\mathbb{P}(1, 1)(S(2, 2) - S(1, 1)) + \mathbb{P}(2, 2)\mathbb{P}(2, 1)(S(2, 2) - S(2, 1))).$$

With $G = H = 2$, $\frac{2}{GH} = \frac{1}{2}$. Substituting the probabilities and $S(\cdot)$ yields

$$\bar{g}_{\text{GRPO}}(\theta) = \frac{1}{2} \begin{bmatrix} p(p-1)q \\ p(1-p)q \\ pq(q-1) \\ pq(1-q) \end{bmatrix}.$$

SGPO. In SGPO, $r_{\text{SGPO}}(2,2) = 1$, $r_{\text{SGPO}}(2,1) = \frac{1}{2}$, and $r_{\text{SGPO}}(1,1) = 0$. Therefore, all three unordered mixed pairs contribute: $\{(2,2),(2,1)\}$, $\{(2,2),(1,1)\}$, and $\{(2,1),(1,1)\}$. Summing both orderings,

$$\bar{g}_{\text{SGPO}}(\theta) = \frac{2}{GH}(\mathbb{P}(2,2)\mathbb{P}(2,1)(S(2,2) - S(2,1))$$
$$+ \mathbb{P}(2,2)\mathbb{P}(1,1)(S(2,2) - S(1,1)) + \mathbb{P}(2,1)\mathbb{P}(1,1)(S(2,1) - S(1,1))).$$

Again $\frac{2}{GH} = \frac{1}{2}$ for $G = H = 2$, and substituting gives

$$\bar{g}_{\text{SGPO}}(\theta) = \frac{1}{2} \begin{bmatrix} p(p-1) \\ p(1-p) \\ p^2 q(q-1) \\ p^2 q(1-q) \end{bmatrix}.$$

Now we derive the update rules in Eq. (3) and the functions in Eq. (4) from the population gradients. Let $\theta^{(k+1)} = \theta^{(k)} + \eta\, \bar{g}(\theta^{(k)})$, where $\bar{g}$ is either $\bar{g}_{\text{SGPO}}$ or $\bar{g}_{\text{GRPO}}$. For notational brevity, define the step-1 logits $(\theta_1, \theta_2) = (\theta_{x,1}^1, \theta_{x,2}^1)$ and step-2 logits $(\theta_3, \theta_4) = (\theta_{x,2,1}^2, \theta_{x,2,2}^2)$. Recall

$$p = \frac{e^{\theta_2}}{e^{\theta_1} + e^{\theta_2}}, \quad q = \frac{e^{\theta_4}}{e^{\theta_3} + e^{\theta_4}}.$$

Update of p. Let g_1, g_2 denote the first two coordinates of $\bar{g}(\theta)$. Then

$$p^{(k+1)} = \frac{e^{\theta_2^{(k)} + \eta g_2}}{e^{\theta_1^{(k)} + \eta g_1} + e^{\theta_2^{(k)} + \eta g_2}} = \frac{e^{\theta_2^{(k)}} e^{\eta g_2}}{e^{\theta_1^{(k)}} e^{\eta g_1} + e^{\theta_2^{(k)}} e^{\eta g_2}}.$$

Using $p^{(k)} = \frac{e^{\theta_2^{(k)}}}{e^{\theta_1^{(k)}} + e^{\theta_2^{(k)}}}$ and $1 - p^{(k)} = \frac{e^{\theta_1^{(k)}}}{e^{\theta_1^{(k)}} + e^{\theta_2^{(k)}}}$, we can factor out $e^{\theta_1^{(k)}} + e^{\theta_2^{(k)}}$ to obtain

$$p^{(k+1)} = \frac{p^{(k)} e^{\eta(g_2 - g_1)}}{(1 - p^{(k)}) + p^{(k)} e^{\eta(g_2 - g_1)}}.$$

For SGPO, from $\bar{g}_{\text{SGPO}}(\theta)$ we have $g_1 = \frac{1}{2}p(p-1)$ and $g_2 = \frac{1}{2}p(1-p)$, hence $g_2 - g_1 = p(1-p)$. For GRPO, from $\bar{g}_{\text{GRPO}}(\theta)$ we have $g_1 = \frac{1}{2}p(p-1)q$ and $g_2 = \frac{1}{2}p(1-p)q$, hence $g_2 - g_1 = p(1-p)q$. Setting $\eta = 1$ gives the claimed update

$$p_{\text{SGPO}}^{(k+1)} = \frac{p_{\text{SGPO}}^{(k)} e^{p_{\text{SGPO}}^{(k)}(1 - p_{\text{SGPO}}^{(k)})}}{1 - p_{\text{SGPO}}^{(k)} + p_{\text{SGPO}}^{(k)} e^{p_{\text{SGPO}}^{(k)}(1 - p_{\text{SGPO}}^{(k)})}} = \exp(f_{11}(p_{\text{SGPO}}^{(k)})),$$

$$p_{\text{GRPO}}^{(k+1)} = \frac{p_{\text{GRPO}}^{(k)} e^{p_{\text{GRPO}}^{(k)}(1 - p_{\text{GRPO}}^{(k)}) q_{\text{GRPO}}^{(k)}}}{1 - p_{\text{GRPO}}^{(k)} + p_{\text{GRPO}}^{(k)} e^{p_{\text{GRPO}}^{(k)}(1 - p_{\text{GRPO}}^{(k)}) q_{\text{GRPO}}^{(k)}}} = \exp(f_{21}(p_{\text{GRPO}}^{(k)}, q_{\text{GRPO}}^{(k)})).$$

Taking log on both sides yields

$$f_{11}(p) = \log p + p(1-p) - \log\left(1 - p + p e^{p(1-p)}\right),$$
$$f_{21}(p,q) = \log p + p(1-p)q - \log\left(1 - p + p e^{p(1-p)q}\right).$$

Update of q. An identical argument applies to q using the last two coordinates g_3, g_4 of $\bar{g}(\theta)$:

$$q^{(k+1)} = \frac{q^{(k)} e^{\eta(g_4-g_3)}}{(1-q^{(k)}) + q^{(k)} e^{\eta(g_4-g_3)}}.$$

For SGPO, $g_3 = \frac{1}{2}p^2 q(q-1)$ and $g_4 = \frac{1}{2}p^2 q(1-q)$, so $g_4 - g_3 = p^2 q(1-q)$. For GRPO, $g_3 = \frac{1}{2}pq(q-1)$ and $g_4 = \frac{1}{2}pq(1-q)$, so $g_4 - g_3 = pq(1-q)$. With $\eta = 1$ this gives

$$q_{\text{SGPO}}^{(k+1)} = \exp(f_{12}(p_{\text{SGPO}}^{(k)}, q_{\text{SGPO}}^{(k)})), \quad q_{\text{GRPO}}^{(k+1)} = \exp(f_{22}(p_{\text{GRPO}}^{(k)}, q_{\text{GRPO}}^{(k)})),$$

where by taking log on both sides, we have

$$f_{12}(p, q) = \log q + p^2 q(1-q) - \log\left(1 - q + q e^{p^2 q(1-q)}\right),$$

$$f_{22}(p, q) = \log q + pq(1-q) - \log\left(1 - q + q e^{pq(1-q)}\right).$$

We then provide several technical lemmas that are important to the proof of Theorem 3.3. Indeed, the first lemma summarizes the properties of particular functions related to the aforementioned functions f_{11}, f_{21}, f_{12} and f_{22} from Eq. (4).

Lemma B.1. *The following statements hold true,*

(i) The function f_{11} is strictly increasing on $(0, 1)$.
(ii) The function $h_p(x) := x - \log(1 - p + pe^x)$ is strictly increasing for any fixed $p \in (0, 1)$.
(iii) The function f_{21} is strictly increasing in either p for any fixed q or q for any fixed p on $(0, 1)$.
(iv) The function $\varphi(x) := \log(1 + (1/2)e^{-e^x})$ is strictly concave on $(-\infty, 0)$.

Proof. First of all, we have

$$f_{11}'(p_1) = \frac{1 + (1-2p_1)p_1(1-p_1)}{p_1(1+p_1+p_1 e^{p_1(1-p_1)})} > \frac{3}{4p_1(1+p_1+p_1 e^{p_1(1-p_1)})} > 0.$$

Thus, the function f_{11} is strictly increasing on $(0, 1)$.

Furthermore, we have

$$h_p'(x) = 1 - \frac{pe^x}{1-p+pe^x} = \frac{1-p}{1-p+pe^x} \overset{0<p<1}{>} 0.$$

Thus, the function $h_p(x)$ is strictly increasing.

Moreover, we have

$$\frac{\partial f_{21}(p_1, p_2)}{p_1} = \frac{1 + p_2(1-2p_1)p_1(1-p_1)}{p_1(1+p_1+p_1 e^{p_2 p_1(1-p_1)})} > \frac{3}{4p_1(1+p_1+p_1 e^{p_1(1-p_1)})} > 0,$$

$$\frac{\partial f_{21}(p_1, p_2)}{p_2} = \frac{p_1(1-p_1)^2}{1+p_1+p_1 e^{p_2 p_1(1-p_1)}} > 0.$$

Thus, the function f_{21} is strictly increasing in either p for any fixed q or q for any fixed p on $(0, 1)$.

Finally, we have

$$\varphi''(x) = \frac{(e^{x+e^x}/2 - e^{e^x}/2 - 1/4)e^x}{e^{2e^x} + e^{e^x} + 1/4}.$$

Since $u = e^x \in (0, 1)$ for $x < 0$, we have

$$(ue^u/2 - e^u/2 - 1/4)u = (e^u(u-1)/2 - 1/4)u < -(1/4)u < 0.$$

Thus, $\varphi''(x) < 0$ for all $x < 0$ which shows that f is strictly concave on $(-\infty, 0)$. $\square$

The second lemma presents an inequality which plays a key role in the proof of Theorem 3.3.

Lemma B.2. *We define the auxiliary functions as follows,*

$$A(x) = 1 + \left(\tfrac{1}{x} - 1\right) e^{-x(1-x)}, \;\; B(x,y) = 1 + \left(\tfrac{1}{y} - 1\right) e^{-x^2 y(1-y)},$$

$$C(z) = 1 + \left(\tfrac{1}{z} - 1\right) e^{-z^2(1-z)}.$$

Then, we have $C(\sqrt{xy})^2 > A(x)B(x,y)$ *for all* x *and* y *satisfying* $1/2 < y < x < 1$.

Proof. We consider the lower and upper bound of e^{-u} when $u > 0$:

$$1 - u + \tfrac{u^2}{2} - \tfrac{u^3}{6} < e^{-u} < 1 - u + \tfrac{u^2}{2}.$$

Since $1/x - 1$, $1/y - 1$ and $1/\sqrt{xy} - 1$ are all positive, we have

$$A(x) \le 1 + \tfrac{1-x}{x}\left(1 - x(1-x) + \tfrac{x^2(1-x)^2}{2}\right) = \tfrac{1}{x} - (1-x)^2 + \tfrac{x(1-x)^3}{2}.$$

$$B(x,y) \le 1 + \tfrac{1-y}{y}\left(1 - x^2 y(1-y) + \tfrac{x^4 y^2(1-y)^2}{2}\right) = \tfrac{1}{y} - x^2(1-y)^2 + \tfrac{x^4 y(1-y)^3}{2}.$$

$$
\begin{aligned}
C(z) &\ge 1 + \tfrac{1-z}{z}\left(1 - z^2(1-z) + \tfrac{z^4(1-z)^2}{2} - \tfrac{z^6(1-z)^3}{6}\right)\\
&= \tfrac{1}{z} - z(1-z)^2 + \tfrac{z^3(1-z)^3}{2} - \tfrac{z^5(1-z)^4}{6}.
\end{aligned}
$$

Set $z^2 = xy$, the original statement is equivalent to $(zC(z))^2 > (xA(x))(yB(x,y))$. Using the above upper and lower bound, it suffices to show $C_1(\sqrt{xy})^2 > A_1(x)B_1(x,y)$ where

$$A_1(x) = 1 - x(1-x)^2 + x^2(1-x)^3/2, \;\; B_1(x,y) = 1 - x^2 y(1-y)^2 + x^4 y^2(1-y)^3/2,$$

$$C_1(z) = 1 - z^2(1-z)^2 + z^4(1-z)^3/2 - z^6(1-z)^4/6.$$

By Lemma B.3, this is indeed true. This completes the proof. □

Lemma B.3. *Define functions*

$$A_1(x) = 1 - x(1-x)^2 + x^2(1-x)^3/2, \;\; B_1(x,y) = 1 - x^2 y(1-y)^2 + x^4 y^2(1-y)^3/2,$$

$$C_1(z) = 1 - z^2(1-z)^2 + z^4(1-z)^3/2 - z^6(1-z)^4/6.$$

Then, $C_1(\sqrt{xy})^2 > A_1(x)B_1(x,y)$ *for all* $1/2 < y < x < 1$.

Proof. Let $x = u^2$ and $y = v^2$, then $1 > u > v > 1/\sqrt{2}$ and $z = uv$. We next show the desired inequality holds on a larger region, i.e., $1 > u > v > 2/3$. On this larger region, we have the reparameterization as follows:

$$u = \tfrac{2s+3}{3s+3}, \quad v = \tfrac{2r+2s+3}{3r+3s+3}, \quad s, r \in (0, +\infty),$$

or equivalently,

$$s = \tfrac{3(1-u)}{3u-2}, \quad r = \tfrac{3(u-v)}{(3u-2)(3v-2)}, \quad 1 > u > v > \tfrac{2}{3}.$$

It is easy to see this defines a one-to-one correspondence from (u,v)-space to (s,r)-space. Thus, we aim to prove the following function f is positive:

$$F(s,r) := C_1\left(\tfrac{2s+3}{3s+3} \cdot \tfrac{2r+2s+3}{3r+3s+3}\right)^2 - A_1\left(\left(\tfrac{2s+3}{3s+3}\right)^2\right) B_1\left(\left(\tfrac{2s+3}{3s+3}\right)^2, \left(\tfrac{2r+2s+3}{3r+3s+3}\right)^2\right).$$

By leveraging Sympy's symbolic engine, the function expands and simplifies to:

$$F(s,r) = \tfrac{f(s,r)}{c(s+1)^{20}(r+s+1)^{20}}, \text{ where } f(s,r) := \sum_{k=0}^{20} c_{20-k}(s)\, r^{20-k},$$

where $c > 0$ is a universal constant, and single-variable polynomials $c_{20}(s), \ldots, c_2(s), c_0(s) > 0$ and $\Delta_2 := c_1(s)^2 - 4c_2(s)c_0(s) < 0$, for all $s > 0$ (see Table 6 for details). Notice that from the table, we can see the

only nontrivial parts are $c_3(s) > 0$ and $c_2(s) > 0$ because only these two contain negative coefficients. The positivity of $c_3(s)$ is simple because there is only one term (s^9) with negative coefficient and for all $s > 0$,

$$19471456710454363005152664s^{10} + 9684588377731643071927236s^8 > 14413823109350224541499726s^9.$$

To see this, simple estimation and AM-GM inequality yield

$$\text{LHS} > 1.9 \times 10^{25} s^{10} + 9.6 \times 10^{24} s^8 > 2\sqrt{182.4} \times 10^{24} s^9 > 2.7 \times 10^{25} s^9 > \text{RHS}.$$

The positivity of $c_2(s)$ is more complicated because it has 4 negative terms s^{10}, s^9, s^8, s^7. However, we can use similar idea, i.e., choosing a pair of positive terms to bound a negative term:

$$95791062786555508724088742320s^{15} + 571809550541807937530952s^5 > 7027359523643236832970716s^{10};$$
$$43785862330162499052209529768s^{14} + 18478934378953446115053s^4 > 99854072704322871537392604s^9;$$
$$1632673685352712299171515582s^{13} + 35488375569622472169240s^3 > 357260313779697920881889 25s^8;$$
$$46082190500843267907489331 53s^{12} + 4362950858813170449228s^2 > 60990378953076670142287608s^7.$$

To see this, simple estimation and AM-GM inequality yield

$$\text{LHS} > 9.5 \times 10^{28} s^{15} + 5.7 \times 10^{23} s^5 > 2\sqrt{541.5} \times 10^{25} s^{10} > 4.6 \times 10^{26} s^{10} > \text{RHS};$$
$$\text{LHS} > 4.3 \times 10^{28} s^{14} + 1.8 \times 10^{23} s^4 > 2\sqrt{77.4} \times 10^{25} s^9 > 1.7 \times 10^{26} s^{10} > \text{RHS};$$
$$\text{LHS} > 1.6 \times 10^{28} s^{13} + 3.5 \times 10^{22} s^3 > 2\sqrt{5.6} \times 10^{25} s^9 > 4.7 \times 10^{25} s^8 > \text{RHS};$$
$$\text{LHS} > 4.6 \times 10^{27} s^{12} + 4.3 \times 10^{21} s^2 > 2\sqrt{19.7} \times 10^{24} s^7 > 8.8 \times 10^{24} s^7 > \text{RHS}.$$

In conclusion, we have all coefficient $c_i(s)$ positive except $c_1(s)$, but it doesn't affect the positivity of f because $\Delta_2 < 0$. This completes the proof. $\qquad\square$

Table 6: Coefficient Lists of $F(s, r)$

Notation	Value
c	437675956526049436836
c_{20}	$2(2s+3)^2(1714774320744848750s^{18} + 26610409260691576200s^{17} + 191778746468802317181s^{16} + 850194149855082319224s^{15} + 2587082434290045806049s^{14} + 5704415906039160731874s^{13} + 9366197581963232054460s^{12} + 11563054951307567026248s^{11} + 10670965452123886149660s^{10} + 7187176769582075261292s^9 + 3372972168996579430017s^8 + 1072082836158220703952s^7 + 370302094042890771285s^6 + 32990167737690242581s^5 + 2827999868056162678s62^4 + 15116827017089336500s^3 + 49139849518345513368s^2 + 9090603727935062976s + 742484948385838248)$
c_{19}	$8(2s+3)^2(8573871603724243750s^{19} + 141183751848798840450s^{18} + 1085065457535611084097s^{17} + 5159905424662678527663s^{16} + 16962017821014041355285s^{15} + 40761515892906930261393s^{14} + 73777358861762677983126s^{13} + 101968163476291942277643s^{12} + 107719550183279202945336s^{11} + 8595187100533224794234s7^{10} + 5047714242076387274703s9^9 + 2122846171048422727081s2^8 + 7175576253360286202193s^7 + 3821642119447908810138s^6 + 3343140602539615070982s^5 + 2308058741380310946144s^4 + 1046528691565621471344s^3 + 300769285860744146028s^2 + 50403014643440592936s + 3785769852305984190)$
c_{18}	$2(2s + 3)^2(32580712094152126250\allowbreak0s^{20} + 5673987380977312396200s^{19} + 4632014361420018357535\allowbreak8s^{18} + 235164624868455434314740s^{17} + 830330782346499878631402s^{16} + 2159105892766696625508432s^{15} + 4268066364777710628878112s^{14} + 6521177726276586191628264s^{13} + 7742933419720025335966013\allowbreak1s^{12} + 71109113618735821090519\allowbreak92s^{11} + 49764748763830706631955\allowbreak17s^{10} + 2600230719135591148269222s^9 + 1035307928116150386109695s^8 + 4204952201581657836723\allowbreak00s^7 + 287436345862168026209421s^6 + 225749912117527047120354s^5 + 1322055539247657570232\allowbreak86s^4 + 52546262098747895532864s^3 + 13596497258861930544108s^2 + 2087305777245729888936s + 145293329180967197454)$
c_{17}	$12(2s + 3)^2(325807120941521262500s^{21} + 5982992191700268855300s^{20} + 51700930512613327403406s^{19} + 279079780777259477944590s^{18} + 1053187317945045364767966s^{17} + 294545890280984958687681\allowbreak0s^{16} + 6310900331865363012743844s^{15} + 10554182290179327214273482s^{14} + 13894164004300292404029789s^{13} + 14397511755502695216399777s^{12} + 11648187532971253859583195s^{11} + 7253672843249894875203621s^{10} + 3463934076062711984148183s^9 + 14013118711246369225106\allowbreak79s^8 + 7096350734538033843306\allowbreak63s^7 + 526601300781722718969621s^6 + 366411462920903557014120s^5 + 18779093836691745063360\allowbreak6s^4 + 66828265788979238418684s^3 + 15774993964318985462592s^2 + 2238177282159012945966s + 145311275743961970078)$
c_{16}	$3(2s + 3)^2(553872105600586146250\allowbreak0s^{22} + 10696394904119483034480\allowbreak0s^{21} + 97537241738707509555711\allowbreak0s^{20} + 5577701869567635624516312s^{19} + 224010701388547845626716\allowbreak02s^{18} + 670347255618093214622572\allowbreak20s^{17} + 154689592660061775780683034s^{16} + 280889539801332767094091608s^{15} + 40566432899300593609815822\allowbreak0s^{14} + 467432234597450323377654624s^{13} + 428162911701836470453488816s^{12} + 308851193177419859648120664s^{11} + 173923711507624595412555792s^{10} + 78611043902295277305014364s^9 + 345027239321086599680681\allowbreak91s^8 + 20784869678087847011350512s^7 + 1521107049127527089926047\allowbreak9s^6 + 9439795169478817720557390s^5 + 432364277729921086746684\allowbreak0s^4 + 1398336255225225668686176s^3 + 304165103383419145366680s^2 + 40170170984468888396880s + 2445688799534592091926)$

c_{15}	$12(2s + 3)^2(4430976844804689170000s^{23} + 89773624658788072119600s^{22} + 861449789967478967902968s^{21} + 5202052340570363961799272s^{20} + 22150958674722147636887880s^{19} + 70610768977431597138502416s^{18} + 174547747719038741579249148s^{17} + 341846798830220759744006802s^{16} + 537017897494050473220887475s^{15} + 680386317088643909072652357s^{14} + 694900917445527709102606203s^{13} + 568854294351452352559155357s^{12} + 370162500862325208186949407s^{11} + 192089934615274810143113637s^{10} + 85560000374404871078044743s^{9} + 42188979069325595690484894s^{8} + 27986482983635448916149477s^{7} + 19349473000527948423160098s^{6} + 10826549522417650582347903s^{5} + 4499119009419911850147903s^{4} + 1337268081929646109116429s^{3} + 270188727447397870150299s^{2} + 33412191448722202871793s + 1916481339467789227047)$
c_{14}	$3(2s + 3)^2(4430976844804689170000s^{24} + 939760900846202799633600s^{23} + 9465882231449979270581616s^{22} + 60189415644287265430240224s^{21} + 270831851136366961169859120s^{20} + 916082243422713193340650464s^{19} + 2414605718335618880853970032s^{18} + 5071784805050410035823167576s^{17} + 8606003351786628019139811024s^{16} + 11882072721559268002578594336s^{15} + 13373135736066588915267225192s^{14} + 12233789753017327381398656592s^{13} + 9038087243602138768195078704s^{12} + 5369286552690873446276117328s^{11} + 2623535852573549267091555300s^{10} + 1196071780982939651865144096s^{9} + 660078244623496780263588075s^{8} + 451393195997666208667458852s^{7} + 290343677073268941864046305s^{6} + 148042042832629803967321050s^{5} + 56464193331043404116741784s^{4} + 15559478430192850829818824s^{3} + 2939179015494775847121192s^{2} + 342046929585497061253176s + 18557914646800278459054)$
c_{13}	$6(2s + 3)^2(4430976844804689170000s^{25} + 981785555104524878071200s^{24} + 10357132334422169539112688s^{23} + 69166131783384274997062320s^{22} + 327906609514495942625889552s^{21} + 1172872936442019296825004672s^{20} + 3283063721629310545911589320s^{19} + 7360333239220785966714322212s^{18} + 13411238091959519801173855314s^{17} + 20030874331258639447616405430s^{16} + 24612632066584435063045693896s^{15} + 24861807943243247848564702728s^{14} + 20554616309938676564088193632s^{13} + 13828701774644445607198489296s^{12} + 75933070180197776947591316692s^{11} + 3573164437682539651140298914s^{10} + 1711205400898634741432588709s^{9} + 1026436201325482873227731181s^{8} + 693346698158130213351442587s^{7} + 413729468327452341092783823s^{6} + 194077643830831926535960674s^{5} + 68561905220231775619051080s^{4} + 17640970508803332546397944s^{3} + 3132633769453198732801032s^{2} + 344560424227000935565860s + 17745096925489168423620)$
c_{12}	$3(2s + 3)^2(144006747456152398025000s^{26} + 3327383318042925260865360s^{25} + 36686806677921921575024412s^{24} + 256712663785782687868607040s^{23} + 12788784884439188869718977532s^{22} + 4822501965635852078399708760s^{21} + 14284937167605407625123613032s^{20} + 34039675734020531218713639960s^{19} + 66269194087347804842641890936s^{18} + 106420251181999059483739591464s^{17} + 141673718347886548611527896944s^{16} + 156512253734744849831503592064s^{15} + 143119458698672790284020359156s^{14} + 107772919457957006535562903236s^{13} + 66583563316818931905117287625s^{12} + 34208027977787101480006575072s^{11} + 15821430510294339891416781741s^{10} + 8030913522092664743057080482s^{9} + 5050521785734143734257145460s^{8} + 3292374301511579644939102872s^{7} + 1827212365211212115171329068s^{6} + 795146625577647417589837740s^{5} + 262142182103903879108812389s^{4} + 63354427214296180937779584s^{3} + 10625610419721898094320272s^{2} + 1108770079900593722922360s + 54371622599418650521707)$

c_{11}	$2(2s + 3)^2(28801349491230479605000s^{27} + 69279266135375987271516000s^{26} + 79684994050724088696229560s^{25} + 58301357534867002173271898 4s^{24} + 3044719667796555717818159544s^{23} + 12071152881690852686028406920s^{22} + 37719751802283064561860228312s^{21} + 95186570754684978954315680724s^{20} + 197141443250509137121100298018s^{19} + 338621398294617306936300888486s^{18} + 485320394172125494078362290142s^{17} + 581787906451611153835763035926s^{16} + 582802786083324408675746802192s^{15} + 485993832849417808677870096480s^{14} + 335594444689992516446373541470s^{13} + 191818678234951313275318187166s^{12} + 93215508141687941579846043591s^{11} + 42995488556619072965421127845s^{10} + 22993334205445704498638551659s^{9} + 14702002876383491619167125293s^{8} + 91518024781573504854707806 38s^{7} + 4746495171599998113140409294s^{6} + 1930238883493800552821467836s^{5} + 597661705826550277052178582s^{4} + 1363694210951181524092878 75s^{3} + 216900514076785168241730 15s^{2} + 21544004474439075954871 83s + 100873131758694046028745)$
c_{10}	$(2s + 3)^2(63362968880707055131000 0s^{28} + 158423911056767229213912 00s^{27} + 18976210496844664501410429 6s^{26} + 144889923341990586569623070 4s^{25} + 791501774903763181229698927 2s^{24} + 329113740929638811711288518 08s^{23} + 10818411368041983695706257112 0s^{22} + 288181457405913203915560147656s^{21} + 632563077547125768289724175852s^{20} + 1156966248842167228077853758672s^{19} + 1775610230389152091840398326292s^{18} + 2294661769917892997575576903488s^{17} + 2498192965867701162268688835924s^{16} + 2285659112305489254434518711416s^{15} + 1748991971403770816761602941934s^{14} + 1113797684163785842646 4967323376s^{13} + 59249139515974357439009674211 1s^{12} + 274477660071554156565150112 13796s^{11} + 127044619585271350650188845452s^{10} + 70538582326147723865407765680s^{9} + 44889681102540017067072498465s^{8} + 26602898887160759567836334520s^{7} + 12967769746561749479001701280s^{6} + 4960789745148078555411299844s^{5} + 14507320987315900495954 23084s^{4} + 313930894468329082145284956s^{3} + 475256706206126110586180 19s^{2} + 45067951954440982167499 62s + 20198106643892008807412 1)$
c_{9}	$2(2s + 3)^2(28801349491230479605000s^{29} + 7474247118895785746840400s^{28} + 9308513797882609298968418 4s^{27} + 7404022441838906136102386 16s^{26} + 42224920164363414473174228 40s^{25} + 183734745877377571435765979 76s^{24} + 63374311264983526695777429384s^{23} + 177689296198984770408646605492s^{22} + 411992129847683864453855977890s^{21} + 799270570087512158479167778014s^{20} + 1307454563265970530661662310488s^{19} + 1811440906673507850196226957292s^{18} + 2129008833631551803404401966618s^{17} + 212031890299746512147055 2812398s^{16} + 1782752578142774040882126045846s^{15} + 1258348636755929955587480574282s^{14} + 742222950605778500648135120808s^{13} + 368759532677177603238716204 48s^{12} + 16329234017761666534529787 8034s^{11} + 756281355442081652542803 71040s^{10} + 42858735954613893102489442569s^{9} + 2681560986049355543901710 6967s^{8} + 15154066307595953401565854680s^{7} + 6986502898234763627448498006s^{6} + 25297749386947476621523 77363s^{5} + 70233050181067477048786 2723s^{4} + 14473265502786394882786 2261s^{3} + 209245472083712624855602 95s^{2} + 18995297776087151145213 99s + 816678653884039535181 75)$

c_8	$3(2s + 3)^2(144006747456152398025000s^{30} + 38737036857874396283424400s^{29} + 500869506060239258684790368s^{28} + 4143472934310331141335720008s^{27} + 2462455716417895553466814404s^{26} + 11190311839066344259536714024s^{25} + 40409295972773177050104566556s^{24} + 118947134811306669490272616200s^{23} + 290460448001449937986609641984s^{22} + 595650982876961700444247916136s^{21} + 1034394503332837044832871973660s^{20} + 1529122522398341452237748264328s^{19} + 1929170112144408531295247240352s^{18} + 2077275729835779898627972452564s^{17} + 1904400092584849147398803257857s^{16} + 1479295019246765244421617960408s^{15} + 967232587581523134128767690737s^{14} + 529827149456294513579866857762s^{13} + 245850149371151220247602350838s^{12} + 103586181981415962365079350136s^{11} + 47441969831005210765856651490s^{10} + 27017370328613731242988726116s^9 + 16543604074621342316534833896s^8 + 8959808104815503968120901160s^7 + 3934148480503417587877177653s^6 + 1356708501926603220744080694s^5 + 359356010050812330787473279s^4 + 70800398025365428901919252s^3 + 9805705639441860010993074s^2 + 854294427989006197205052s + 35306186075611540243056)$
c_7	$12(2s + 3)^2(2215488422402344585 0000s^{31} + 61696674032722867434 8400s^{30} + 827090707369616268343 0488s^{29} + 7105488837495844741933 1400s^{28} + 4393191571105468038118 96968s^{27} + 20811530357045666581306 24800s^{26} + 78516994084586808022426 34484s^{25} + 24207516760625423072207 073414s^{24} + 62092517428805875866794 674881s^{23} + 13419134915902123968841 4857431s^{22} + 24651837873231177502946 4265197s^{21} + 38722904880065353173811 4739999s^{20} + 52184907756189465763639 8449655s^{19} + 60401049965902695146089 7607741s^{18} + 59970619395213696432112 7694249s^{17} + 50893260009270036230801 4694866s^{16} + 36692384583010673508719 9088303s^{15} + 22297067887827188553515 9028828s^{14} + 11351075140481669158976 1355815s^{13} + 48959621580159733845289 884633s^{12} + 19343819733170955544319 552163s^{11} + 85709676482434192986603 77211s^{10} + 48422817052135271084165 13279s^9 + 29091383745623179903600 31394s^8 + 15229213035961739961385 75905s^7 + 64221296552864057231043 6879s^6 + 21234740879260983664481 5359s^5 + 53940504869138165983355 556s^4 + 10200981421548866272272 021s^3 + 13576094237482264271577 78s^2 + 11378258779245747678886 5s + 4528476210896135134182)$
c_6	$3(2s + 3)^2(44309768448046891700000s^{32} + 127595813491277942713440 0s^{31} + 17712124648743520374246000s^{30} + 1578007833031923424848077 76s^{29} + 10134760020968226539342475 36s^{28} + 49963468114719944382409704 00s^{27} + 19656891049003759997738219 664s^{26} + 63343018585986823082619729 288s^{25} + 17025853704363277922947372 3584s^{24} + 38671925597018899391722457 4336s^{23} + 74919597303712220212720213 5768s^{22} + 12459527898651638421599255 00256s^{21} + 17859909693607150460000117 363568s^{20} + 22109118970851524307378223 15488s^{19} + 23633256569498336318699304 74232s^{18} + 21763865344758685432501784 52024s^{17} + 17185192695977307690462199 31925s^{16} + 11548989976568146170383094 24924s^{15} + 65399379968237071658504097 6045s^{14} + 30909781238758984299404908 8882s^{13} + 12264998651480592797581101 3678s^{12} + 44139321593386486437541304 232s^{11} + 18194600512073131179652474 218s^{10} + 10080729455247177149466360 108s^9 + 60121544950098328631438607 03s^8 + 30867139019044853020774239 12s^7 + 12645365130026448915535735 32s^6 + 40426900431353599770906418 8s^5 + 99085318554137395893467265s^4 + 18066869592965845573731768s^3 + 23180375592196844545338 93s^2 + 18733587778495957729897 8s + 7192069815364796066229)$

c_5	$6(2s + 3)^2(8861953689609378340000s^{33} + 263596557834220301114400s^{32} + 3784460184258343211722032s^{31} + 34920466929143934879808368s^{30} + 232642130166877120425752976s^{29} + 1191697800945367086458055072s^{28} + 4880694751880441559218476632s^{27} + 16406950824469547680560778764s^{26} + 46112865280418851489322074134s^{25} + 109812274944960351155991786018s^{24} + 223725856433516713998849805632s^{23} + 392660140917098227883941019880s^{22} + 596450332899276085006754000436s^{21} + 786241559139425306167747437324s^{20} + 900162472445706270827205735408s^{19} + 894118456198813762374744874842s^{18} + 768019765700356821541048064211s^{17} + 567188919515029404795124639815s^{16} + 356892849173690588784279865923s^{15} + 188887726440058090918123569807s^{14} + 82758519677573937797801658678s^{13} + 297558419682951551809383377160s^{12} + 9265655123985315388229427762s^{11} + 3269804705124270960946179492s^{10} + 1745378750437674672254525343s^{9} + 1067124171571276165079329161s^{8} + 553192327447935426146669544s^{7} + 224471881547232310097558892s^{6} + 70271287113829333092849234s^{5} + 16759856517295120894936656s^{4} + 2963427571961631174417201s^{3} + 367988093962382467875321s^{2} + 28750493973686584294998s + 1066338997876680421860)$
c_4	$3(2s + 3)^2(5538721056005861462500s^{34} + 17000093042867794800120​0s^{33} + 25215428706296140524941​82s^{32} + 24069033861073900393194288s^{31} + 166112140239471730224127950s^{30} + 88286198474324819522022706​8s^{29} + 3758135559481861075860190560s^{28} + 13155787658258741235890755800s^{27} + 38587134973448786366330248032s^{26} + 96129109345583765886638321232s^{25} + 205447147746380335664768754954s^{24} + 379449453375926778871028692368s^{23} + 608776780980435381145177931646s^{22} + 851251839731897497067600541072s^{21} + 1039128387112340409627618422211s^{20} + 1107338907683241287910817574616s^{19} + 1028236425910911889110211542327s^{18} + 828653388719550997841334599814s^{17} + 575679860099214460991336767122s^{16} + 341113980250874385715195498752s^{15} + 169602112160966873244672554562s^{14} + 69019121880524178108395152092s^{13} + 22192275965509681657763172138s^{12} + 5513039324469607430622101184s^{11} + 1308552733582056616685717799s^{10} + 6228224269682729355610750562s^{9} + 441208218615564366021478680s^{8} + 25108662674499791880622183​2s^{7} + 105542726343197962447668330s^{6} + 33182712041751038192684904s^{5} + 7819078036046387444720541s^{4} + 135337293941263748900038​8s^{3} + 16359337223317228187320​2s^{2} + 12396727299661082512092s + 444813790293506728368)$
c_3	$6(2s + 3)^2(651614241883042525000s^{35} + 206181119083643318565400s^{34} + 315621334999692786151116s^{33} + 3113065178572047666007860s^{32} + 22229797545183952680520284s^{31} + 122422561739941481599835484s^{30} + 540840514528742111761776912s^{29} + 1968384017248063183323104976s^{28} + 6014334916396782599305697730s^{27} + 15642733509059107994947830402s^{26} + 34991063427920339849664070098s^{25} + 67834512242456744868412053510s^{24} + 114610735641635823232680558264s^{23} + 169420289219412443682245006436s^{22} + 219630129457905943676457475806s^{21} + 249914888458917575863280485878s^{20} + 249458032509437740525240777731s^{19} + 217920380868106493481515756421s^{18} + 165868299839291545410161133771s^{17} + 109196804131621756456248426789s^{16} + 61455743971044438451107683232s^{15} + 29010820857450160933812140136s^{14} + 11111724769820435809112639700s^{13} + 3230978841571830756780993930s^{12} + 597734071316630030096071452s^{11} + 19471456710454363005152664s^{10} - 14413823109350224541499726s^{9} + 968458837731643071927236s^{8} + 1256019583039185504039910s^{7} + 6629813221106696409536742s^{6} + 2267528918316638233964400s^{5} + 549510851612447197946100s^{4} + 95169593716835317546698s^{3} + 11333379076369208961606s^{2} + 8377615455010504271​46s + 29118359247617829474)$

c_2	$(2s + 3)^2(65161424188304252500 0 s^{36} + 212361287050892314836 00 s^{35} + 3351768289135045172584 92 s^{34} + 341248027234906031459076 0 s^{33} + 25184187621847674304218612 s^{32} + 14353247791263320410711104 0 s^{31} + 6571995334134877377460058 40 s^{30} + 24830578027621419813726048 72 s^{29} + 78904442564142212049840971 82 s^{28} + 213867066262644389974992575 04 s^{27} + 49968626600986503205494353 2722 s^{26} + 1014439442075341249520382 83748 s^{25} + 1800227084981344254247742 57358 s^{24} + 2804733165486533307037649 39232 s^{23} + 3847701887175612902111068 82724 s^{22} + 4655658061409025346140795 055268 s^{21} + 4970705288178906475764968 74221 s^{20} + 4678534555507223380165602 91068 s^{19} + 3872550916392453613427525 51670 s^{18} + 2806584924377792155024177 61676 s^{17} + 1768405807430274222159766 20477 s^{16} + 957910627865555087240887 42320 s^{15} + 43785862330162499052209529 768 s^{14} + 16326736853527122991715155 824 s^{13} + 460821905008432679074893 3153 s^{12} + 763090880285610579007863 108 s^{11} - 7027359523643236832970771 6 s^{10} - 998540727043228715373926 04 s^{9} - 35726031377969792088188925 s^{8} - 6099037895307670142287608 s^{7} + 38599700071122383235616 8 s^{6} + 5718095505418079375309 52 s^{5} + 184789343789534461150530 s^{4} + 35488375569622472169240 s^{3} + 4362950858813170449228 s^{2} + 3206021409943901224 56 s + 10806813741383936712)$
c_1	$2s^2(2s + 3)^2(5s + 6)^2(1371819456595879000 s^{33} + 4271634557055966808 8 s^{32} + 643544475178313701908 s^{31} + 624756655570258038906 0 s^{30} + 43916765565269249016660 s^{29} + 238129437052493452170540 s^{28} + 1036074226442125183419168 s^{27} + 3714930106381256786671824 s^{26} + 11187728687072575053763704 s^{25} + 28696708254175557235886484 s^{24} + 63352891406570842442956878 s^{23} + 121330161626918848657558398 s^{22} + 202765255131175811905486752 s^{21} + 296952156159684842999476188 s^{20} + 382193906007924533060066196 s^{19} + 432977106373155008061033636 s^{18} + 431882942555537334945182376 s^{17} + 378922778321739951076319160 s^{16} + 291693785851369028780662644 s^{15} + 196147224158011892839433394 s^{14} + 114410349624644626423212729 s^{13} + 57248884332430976396451627 s^{12} + 24130617950503756984051008 s^{11} + 8287189086050003227856022 s^{10} + 2152391916458370195915867 s^{9} + 325184614597411140314601 s^{8} - 33007972351878903475404 s^{7} - 41792510938686638897304 s^{6} - 15831185972996449730358 s^{5} - 3877006197061115690130 s^{4} - 665506024092175855680 s^{3} - 78419814392209911120 s^{2} - 5759186746951521828 s - 200126180395998828)$
c_0	$s^4(2s+3)^2(5s+6)^4(5487277826383516 s^{30} + 162900207047936448 s^{29} + 2337377142714373098 s^{28} + 21588165729897598296 s^{27} + 144210704373637237422 s^{26} + 742206852421449807276 s^{25} + 3061285798160471289822 s^{24} + 10391895636644586020112 s^{23} + 29588363727735612069036 s^{22} + 71651404108146138897096 s^{21} + 149117620073027461547436 s^{20} + 268806705178958727187248 s^{19} + 422185992215286625454736 s^{18} + 580191752386498986323712 s^{17} + 699694724310231624064272 s^{16} + 741757261801656111225984 s^{15} + 691666247103583662351612 s^{14} + 567033087779716710023352 s^{13} + 408047131644656580559296 s^{12} + 257036644794565634383008 s^{11} + 141145264141826804073576 s^{10} + 67178460532288884909516 s^{9} + 27499663057942951141041 s^{8} + 9582491278489242855672 s^{7} + 2803365139419823150782 s^{6} + 675682953313836552876 s^{5} + 130659498671205647052 s^{4} + 19489563056909654496 s^{3} + 2105305456045150908 s^{2} + 146594486051390088 s + 4941387170271576)$

Δ_2

$-36s^4(2s+3)^4(5s+6)^4(188188862149501274759871978264100000s^{66}$
$+1171982279367338935485204891772187040000s^{65}$
$+35903405951584376491517240494662740899​2s^{64}$
$+7212088571266452516322419090023965301952s^{63}$
$+10683913202536878409344821445611408008989​6s^{62}$
$+124465393074534346240061234112336643055611​2s^{61}$
$+1187453127258675915704887142527377641964648​0s^{60}$
$+9539717463978084911740021792529086079754307​2s^{59}$
$+65860142119616239467500609240927065578338709​6s^{58}$
$+39680223557336960917652631305424892564932972​96s^{57}$
$+211171821578745369801696554651560917442769203​80s^{56}$
$+1002346955322263064366492155231201633504320407​84s^{55}$
$+4277235454084557392774406702392019604985274451​68s^{54}$
$+16516932048985831100019838316753837038388031112​80s^{53}$
$+58038813051285159280644727598895039061348407197​88s^{52}$
$+18645262399111732404927179918528703191829668776​944s^{51}$
$+54982160923970862907155853987157692828051002129​468s^{50}$
$+14934032713121190950602119161930327947606930700​1480s^{49}$
$+374738908504925756556865067810806785110272348870​998s^{48}$
$+870959171363388767125455183938474548684433032733​976s^{47}$
$+187912542310567752353269511359111865325103054321​9650s^{46}$
$+377089342550260449521902917707765852079857151669​8604s^{45}$
$+705001522178417449079410838825181307325964366309​1008s^{44}$
$+122975169781454008873774301254059723913095352364​04816s^{43}$
$+200381644841642366592891584643332233229798614563​69558s^{42}$
$+305322049306583019221799603078979868509609731104​01060s^{41}$
$+435397401656423077474493767161522747389979719523​81288s^{40}$
$+581479427223404746884552844635854669268294471246​90864s^{39}$
$+727656098196702459816422262294213335428161653007​86478s^{38}$
$+853522262719441174035220544722749906159874120776​58020s^{37}$
$+938611851235801809865288322413950541241252103327​87978s^{36}$
$+967736762287074547941859498362807700222007026377​89136s^{35}$
$+935355053405668298352809695924619024798748697370​70324s^{34}$
$+847265730703312222401048138408764617479499951727​5720s^{33}$
$+718929230253964672423855671352042964593676069311​71072s^{32}$
$+571075053858216707658610944211693582963991262226​38720s^{31}$
$+424294755793692002949803968153228398398650217114​81712s^{30}$
$+294534022486713113709189755863719504001008758859​184424s^{29}$
$+190768874188154755913912253448286733319854339498​59745s^{28}$
$+115096309026137424300567101130259799463689293635​91560s^{27}$
$+645531457058926293542594799535539821984108361946​0275s^{26}$
$+335743256106102060358038278592258590053639639391​0862s^{25}$
$+161448358156969110843497412701892936220315302236​5980s^{24}$
$+715184392123946764432274154396140356129136774278​152s^{23}$
$+290561593707882411154971270303899134550457836920​080s^{22}$
$+107686614725038641896140906093508540897806554334​884s^{21}$
$+361751237678278765712871685717720960666418421897​15s^{20}$
$+109362954136214178401472446585845791272071743893​52s^{19}$
$+295623144695194588545245317760065022236003150785​3s^{18}$
$+714328315495087334767452511829810830341704532294​s^{17}$
$+157862256397341201315796262528952028945210160178​s^{16}$
$+346691848154089322434842906884986846229160005​52s^{15}$
$+879220885968824907033894237443409495692996843​4s^{14}$
$+272895891349790467960562930434828306766214915​6s^{13}$
$+908514477310679518991239534084776498569549130​s^{12}$
$+281997384651571824431416925444015840101696600s^{11}$
$+765957125613299444411389424541888723849699​2s^{10}$

$+1782323536880591650543354401619541599668158 4s^9$
$+3522507407940359387775769801382214828420516s^8$
$+586782005064608000832043474107919395519552s^7$
$+814845231527632291884775584680364066167 2s^6$
$+927568999324388705389946382849892996334 4s^5$
$+843808167321923057379954129881612634096s^4$
$+589880875894121296236334664761372978 56s^3$
$+297258128743307156811811585077963307 2s^2$
$+95923391203691628771401672158154016s$
$+14833514103663653933721908065693 92)$

The last lemma presents some properties for the population-level SGPO and GRPO dynamics.

Lemma B.4. *Under the assumptions from Theorem [3.3], the following statements hold true,*

(i) $p_{SGPO}^{(k)}, q_{SGPO}^{(k)}, p_{GRPO}^{(k)}, q_{GRPO}^{(k)} \in (0,1)$ *for all* $k \geq 0$.
(ii) $p_{SGPO}^{(k)}, q_{SGPO}^{(k)}, p_{GRPO}^{(k)}, q_{GRPO}^{(k)}$ *are strictly increasing in* k *and lie in* $(\frac{1}{2}, 1)$ *for all* $k \geq 1$.
(iii) $p_{SGPO}^{(k)} > q_{SGPO}^{(k)}$ *for all* $k \geq 1$.

Proof. We first rewrite the update rule in Eq. [(3)] as follows,

$$p_{\mathsf{SGPO}}^{(k+1)} = p_{\mathsf{SGPO}}^{(k)} \frac{e^{\Delta_{\mathsf{SGPO},p}^{(k)}}}{1-p_{\mathsf{SGPO}}^{(k)}+p_{\mathsf{SGPO}}^{(k)}e^{\Delta_{\mathsf{SGPO},p}^{(k)}}}, \quad \text{where} \quad \Delta_{\mathsf{SGPO},p}^{(k)} = p_{\mathsf{SGPO}}^{(k)}(1-p_{\mathsf{SGPO}}^{(k)}),$$

$$q_{\mathsf{SGPO}}^{(k+1)} = q_{\mathsf{SGPO}}^{(k)} \frac{e^{\Delta_{\mathsf{SGPO},q}^{(k)}}}{1-q_{\mathsf{SGPO}}^{(k)}+q_{\mathsf{SGPO}}^{(k)}e^{\Delta_{\mathsf{SGPO},q}^{(k)}}}, \quad \text{where} \quad \Delta_{\mathsf{SGPO},q}^{(k)} = (p_{\mathsf{SGPO}}^{(k)})^2 q_{\mathsf{SGPO}}^{(k)}(1-q_{\mathsf{SGPO}}^{(k)}),$$

$$p_{\mathsf{GRPO}}^{(k+1)} = p_{\mathsf{GRPO}}^{(k)} \frac{e^{\Delta_{\mathsf{GRPO},p}^{(k)}}}{1-p_{\mathsf{GRPO}}^{(k)}+p_{\mathsf{GRPO}}^{(k)}e^{\Delta_{\mathsf{GRPO},p}^{(k)}}}, \quad \text{where} \quad \Delta_{\mathsf{GRPO},p}^{(k)} = p_{\mathsf{GRPO}}^{(k)}(1-p_{\mathsf{GRPO}}^{(k)})q_{\mathsf{GRPO}}^{(k)},$$

$$q_{\mathsf{GRPO}}^{(k+1)} = q_{\mathsf{GRPO}}^{(k)} \frac{e^{\Delta_{\mathsf{GRPO},q}^{(k)}}}{1-q_{\mathsf{GRPO}}^{(k)}+q_{\mathsf{GRPO}}^{(k)}e^{\Delta_{\mathsf{GRPO},q}^{(k)}}}, \quad \text{where} \quad \Delta_{\mathsf{GRPO},q}^{(k)} = p_{\mathsf{GRPO}}^{(k)}q_{\mathsf{GRPO}}^{(k)}(1-q_{\mathsf{GRPO}}^{(k)}).$$

First of all, the uniform initialization yields the desired result for $k = 0$. Suppose $p_{\mathsf{SGPO}}^{(k)} \in (0,1)$ for some $k \geq 0$. Then, we have

$$1 - p_{\mathsf{SGPO}}^{(k)} + p_{\mathsf{SGPO}}^{(k)}e^{\Delta_{\mathsf{SGPO},p}^{(k)}} > p_{\mathsf{SGPO}}^{(k)}e^{\Delta_{\mathsf{SGPO},p}^{(k)}} > 0,$$

which implies $p_{\mathsf{SGPO}}^{(k+1)} \in (0,1)$. By induction, we have $p_{\mathsf{SGPO}}^{(k)} \in (0,1)$ for all $k \geq 0$. Similarly, we can show that $q_{\mathsf{SGPO}}^{(k)}, p_{\mathsf{GRPO}}^{(k)}, q_{\mathsf{GRPO}}^{(k)} \in (0,1)$ for all $k \geq 0$.

Furthermore, we have $\Delta_{\mathsf{SGPO},p}^{(k)} > 0$ since $p_{\mathsf{SGPO}}^{(k)} \in (0,1)$. This implies

$$\frac{p_{\mathsf{SGPO}}^{(k+1)}}{p_{\mathsf{SGPO}}^{(k)}} = \frac{1}{(1-p_{\mathsf{SGPO}}^{(k)})e^{-\Delta_{\mathsf{SGPO},p}^{(k)}}+p_{\mathsf{SGPO}}^{(k)}} > \frac{1}{1-p_{\mathsf{SGPO}}^{(k)}+p_{\mathsf{SGPO}}^{(k)}} = 1.$$

Since $p_{\mathsf{SGPO}}^{(0)} = \frac{1}{2}$, we have $p_{\mathsf{SGPO}}^{(k)} \in (\frac{1}{2}, 1)$ for all $k \geq 1$. Similarly, we can show that $q_{\mathsf{SGPO}}^{(k)}, p_{\mathsf{GRPO}}^{(k)}, q_{\mathsf{GRPO}}^{(k)}$ are strictly increasing and lie in $(\frac{1}{2}, 1)$.

Finally, we have $p_{\mathsf{SGPO}}^{(0)} \geq q_{\mathsf{SGPO}}^{(0)}$. Thus, it suffices to show that $p_{\mathsf{SGPO}}^{(k)} \geq q_{\mathsf{SGPO}}^{(k)}$ implies $p_{\mathsf{SGPO}}^{(k+1)} > q_{\mathsf{SGPO}}^{(k+1)}$ for all $k \geq 0$. Indeed, Lemma [B.1(i)] and $p_{\mathsf{SGPO}}^{(k)} \geq q_{\mathsf{SGPO}}^{(k)}$ yield

$$p_{\mathsf{SGPO}}^{(k+1)} = \exp(f_{11}(p_{\mathsf{SGPO}}^{(k)})) \geq \exp(f_{11}(q_{\mathsf{SGPO}}^{(k)})) = \exp(\log(q_{\mathsf{SGPO}}^{(k)}) + h_{q_{\mathsf{SGPO}}^{(k)}}(q_{\mathsf{SGPO}}^{(k)}(1-q_{\mathsf{SGPO}}^{(k)}))).$$

Then, Lemma [B.1(ii)] and $p_{\mathsf{SGPO}}^{(k)} \in (0,1)$ yield

$$\exp(\log(q_{\mathsf{SGPO}}^{(k)}) + h_{q_{\mathsf{SGPO}}^{(k)}}(q_{\mathsf{SGPO}}^{(k)}(1-q_{\mathsf{SGPO}}^{(k)}))) > \exp(\log q_{\mathsf{SGPO}}^{(k)} + h_{q_{\mathsf{SGPO}}^{(k)}}((p_{\mathsf{SGPO}}^{(k)})^2 q_{\mathsf{SGPO}}^{(k)}(1-q_{\mathsf{SGPO}}^{(k)}))).$$

In addition, we have

$$q_{\text{SGPO}}^{(k+1)} = \exp(f_{12}(p_{\text{SGPO}}^{(k)}, q_{\text{SGPO}}^{(k)})) = \exp(\log q_{\text{SGPO}}^{(k)} + h_{q_{\text{SGPO}}^{(k)}}((p_{\text{SGPO}}^{(k)})^2 q_{\text{SGPO}}^{(k)}(1 - q_{\text{SGPO}}^{(k)}))).$$

Putting these pieces together yields $p_{\text{SGPO}}^{(k+1)} > q_{\text{SGPO}}^{(k+1)}$. □