Overcoming Catastrophic Forgetting in Incremental Few-Shot Learning by Finding Flat Minima

Guangyuan Shi,* **Jiaxin Chen,*** **Wenlong Zhang, Li-Ming Zhan, Xiao-Ming Wu**[†]
Department of Computing
The Hong Kong Polytechnic University
{guang-yuan.shi, jiax.chen, wenlong.zhang, lmzhan.zhan}@connect.polyu.hk
xiao-ming.wu@polyu.edu.hk

Abstract

This paper considers incremental few-shot learning, which requires a model to continually recognize new categories with only a few examples provided. Our study shows that existing methods severely suffer from catastrophic forgetting, a well-known problem in incremental learning, which is aggravated due to data scarcity and imbalance in the few-shot setting. Our analysis further suggests that to prevent catastrophic forgetting, actions need to be taken in the primitive stage – the training of base classes instead of later few-shot learning sessions. Therefore, we propose to search for flat local minima of the base training objective function and then fine-tune the model parameters within the flat region on new tasks. In this way, the model can efficiently learn new classes while preserving the old ones. Comprehensive experimental results demonstrate that our approach outperforms all prior state-of-the-art methods and is very close to the approximate upper bound. The source code is available at `https://github.com/moukamisama/F2M`.

1 Introduction

Why study incremental few-shot learning? Incremental learning enables a model to continually learn new concepts from new data without forgetting previously learned knowledge. Rooted from real-world applications, this topic has attracted a significant amount of interest in recent years [5, 30, 31, 40, 26]. Incremental learning assumes sufficient training data is provided for new classes, which is impractical in many application scenarios, especially when the new classes are rare categories which are costly or difficult to collect. This motivates the study of incremental few-shot learning, a more difficult paradigm that aims to continually learn new tasks with only a few examples.

Challenges. The major challenge for incremental learning is *catastrophic forgetting* [14, 28, 35], which refers to the drastic performance drop on previous tasks after learning new tasks. This phenomenon is caused by the inaccessibility to previous data while learning on new data. Catastrophic forgetting presents a bigger challenge for incremental few-shot learning. Due to the small amount of training data in new tasks, the model tends to severely overfit on new classes while quickly forgetting old classes, resulting in catastrophic performance.

Current research. The study of incremental few-shot learning has just started [47, 41, 60, 9, 8, 34, 59]. Current works mainly borrow ideas from research in incremental learning to overcome the forgetting problem, by enforcing strong constraints on model parameters to penalize the changes of parameters [34, 28, 56], or by saving a small amount of exemplars from old classes and adding constraints on the exemplars to avoid forgetting [40, 20, 4]. However, in our empirical study, we find

---

*Equal contribution

[†]Corresponding author

35th Conference on Neural Information Processing Systems (NeurIPS 2021).

that an intransigent model that only trains on base classes and does not tune on new tasks consistently outperforms state-of-the-art methods, including a joint-training method [47] that uses all encountered data for training and hence suffers from severe data imbalance. This observation motivates us to address this harsh problem from a different angle.

Our solution. Unlike existing solutions that try to overcome catastrophic forgetting during the process of learning new tasks, we adopt a different approach by considering the catastrophic forgetting problem during the training of base classes. Specifically, we propose to search for flat local minima of the base training objective function by adding random noise to the model parameters. For any parameter vector in the flat minima region, the loss is small and the base classes are well separated. In the following incremental few-shot learning tasks, we fine-tune the model parameters within the flat region by clamping the parameters. In this way, the model can learn new classes while preserving the old ones. Our key contributions are summarized as follows:

- We conduct a comprehensive empirical study on existing incremental few-shot learning methods and discover that a simple baseline model that only trains on base classes outperforms prior state-of-the-art methods, demonstrating the severity of catastrophic forgetting.

- We propose a novel approach to overcome catastrophic forgetting in incremental few-shot learning by addressing the problem in the primitive stage. Through finding the flat minima region during training base classes and fine-tuning within the region on new tasks, our model can overcome catastrophic forgetting and avoid overfitting.

- Comprehensive experimental results on CIFAR-100, *mini*ImageNet and CUB-200-2011 show that our approach outperforms all state-of-the-art methods and achieves performance that is very close to the approximate upper bound.

2   Related Work

Few-shot learning aims to learn to generalize to new categories with a few labelled samples in each class. Current few-shot methods mainly consist of optimization-based methods [12, 23, 32, 39, 45, 46, 55] and metric-based methods [13, 19, 44, 49, 52, 58, 57, 53]. Optimization-based methods can achieve fast adaptation to new tasks with limited samples by learning a specific optimization algorithm. Metric-based approaches exploit different distance metrics such as L2 distance [**?**], cosine similarity [49], and DeepEMD [58] in the learned representation space to measure the similarity between samples. Recently, Tian *et al.* [48] find that standard supervised training on meta-training sets can learn good metric representations even for unseen classes, which echoes with our observation on the proposed baseline model.

Incremental learning focuses on the challenging problem of continually learning to recognize new classes in new coming data without forgetting the old classes [6, 7, 10, 51]. Existing works mainly include two groups, multi-class incremental learning [4, 38, 22, 33, 54, 51] and multi-task incremental learning [21, 31, 42]. To overcome catastrophic forgetting, some attempts impose strong constraints on model parameters by penalizing the changes of parameters [28, 1]. Other attempts enforce constraints on the exemplars of old classes such as restricting the output logits [40] and penalizing the changes of embedding angles [20]. Our empirical experiments reveal that imposing strong constraints on the arriving new classes may not be a promising way to tackle incremental few-shot learning due to data scarcity.

Incremental few-shot learning [47, 41, 60, 9, 8] aims to incrementally learn from very few samples. TOPCI [47] adopts a neural gas (NG) network to learn and preserve the topology of the feature manifold formed by different classes. FSLL [34] selects very few parameters from the model for incremental learning and ensure that the parameters are close to the optimal parameters. To overcome catastrophic forgetting, IDLVQC [8] imposes constraints on the exemplars by restricting the embedding drift, and Zhang *et al.* [59] propose to fix the embedding networks for incremental learning. Similar to Zhang *et al.*, we discover that a simple baseline model with embedding fixed for inference can outperform prior state-of-the-art methods.

Robust Optimization. It has been found that flat local minima leads to better generalization capabilities than sharp minima in the sense that a flat minimizer is more robust when the test loss is shifted due to random perturbations [18, 17, 24]. A substantial body of methods [2, 37, 11, 15] have been proposed to optimize neural networks towards flat local minima. In this paper, we show that for

incremental few-shot learning, finding flat minima in the base session and tuning the model within the flat region on new tasks can significantly mitigate catastrophic forgetting.

3 Severity of Catastrophic Forgetting in Incremental Few-Shot Learning

3.1 Problem Statement

Incremental few-shot learning (IFL) aims to continually learn to recognize new classes with only a few examples. Similar to incremental learning (IL), an IFL model is trained by a sequence of training sessions $\{\mathcal{D}^1, \cdots, \mathcal{D}^t\}$, where $\mathcal{D}^t = \{z_i = (x_i^t, y_i^t)\}_i$ is the training data of session t and x_i^t is an example of class $y_i^t \in \mathcal{C}^t$ (the class set of session t). In IFL, the base session $\mathcal{D}^1$ usually contains a large number of classes with sufficient training data for each class, while the following sessions ($t \geq 2$) only have a small number of classes with a few training samples per class, e.g., $\mathcal{D}^t$ is often presented as an N-way K-shot task with small N and K. The key difference between IL and IFL is, for IL, sufficient training data is provided in each session. Similar to IL, in each training session t of IFL, the model has only access to the training data $\mathcal{D}^t$ and possibly a small amount of saved exemplars from previous sessions. After training in session t, the model is evaluated on test samples from all the encountered classes $\mathcal{C} = \bigcup_{i=1}^t \mathcal{C}^i$, where it is assumed that there is no overlap between the classes of different sessions, i.e., $\forall i, j$ and $i \neq j$, $\mathcal{C}^i \bigcap \mathcal{C}^j = \emptyset$.

Catastrophic forgetting. IFL is undoubtedly a more challenging problem than IL due to the data scarcity setting. IL suffers from catastrophic forgetting, a well-known phenomenon and long-standing issue, which refers to the drastic drop in test performance on previous (old) classes, caused by the inaccessibility of old data in the current training session. Unfortunately, catastrophic forgetting is an even bigger issue for IFL, because data scarcity makes it difficult to adapt well to new tasks and learn new concepts, whereas the adaptation process could easily lead to catastrophic forgetting of the base classes. In the following, we illustrate this point by evaluating a simple baseline model for IFL.

3.2 A Simple Baseline Model for IFL

We consider an intransigent model that simply does not adapt to new tasks. Particularly, the model only needs to be trained in the base session $\mathcal{D}^1$ and is directly used for inference in all sessions.

Training ($t = 1$). We train a feature extractor f parameterized by ϕ with a fully-connected layer as classifier by minimizing the standard cross-entropy loss using the training examples of $\mathcal{D}^1$. The feature extractor f is *fixed* for the following sessions ($t \geq 2$) without any fine-tuning on new classes.

Inference (test). In each session, the inference is conducted by a simple nearest class mean (NCM) classification algorithm [36]. Specifically, all the training and test samples are mapped to the embedding space of the feature extractor f, and Euclidean distance $d(\cdot, \cdot)$ is used to measure the similarity between them. The classifier is given by

$$c_k^\star = \operatorname*{argmin}_{c \in \mathcal{C}} d(f(x; \phi), p_c), \text{ where } p_c = \frac{1}{N_c} \sum_i \mathbb{1}(y_i = c) f(x_i; \phi), \tag{1}$$

where $\mathcal{C}$ denotes all the encountered classes, p_c refers to the prototype of class c (the mean vector of all the training samples of class c in the embedding space), and N_c denotes the number of the training images of class c. Note that we *save* the prototypes of all classes in $\mathcal{C}^t$ for later evaluation.

The baseline model outperforms state-of-the-art IFL and IL methods. We compare the above baseline model against state-of-the-art IFL methods including FSLL [34], IDLVQC [8] and TOPIC [47], IL methods including Rebalance [20] and iCarl [40], and a joint-training method that uses all previously seen data including the base and the following few-shot tasks for training. The performance for IFL is evaluated on miniImageNet, CIFAR-100, and CUB-200. All the compared methods are tuned to their best performance (higher than the results reported in the original papers). More experimental details are provided in Sec. 5. As shown in Fig. 1, the baseline model consistently outperforms all the compared methods including the joint-training method (suffers from severe data imbalance) on every dataset[3]. The fact that an intransigent model performs best suggests that

---

[3]We notice that a similar observation is made in a newly released paper [59].

Figure 1: Comparison of the proposed baseline model with state-of-the-art IFL and IL methods and the joint-training method.The baseline model outperforms all the other methods.

- For IFL, preserving the old (base classes) may be more critical than adapting to the new. Due to data scarcity, the performance gain on new classes is limited and cannot make up for the significant performance drop on base classes.

- Prior works [47, 8, 34, 20, 40] that enforce strong constraints on model parameters or exemplars during fine-tuning on new classes cannot effectively prevent catastrophic forgetting in IFL, indicating that actions may need to be taken in the base training stage.

4 Overcoming Catastrophic Forgetting in IFL by Finding Flat Minima

The goal of IFL is to preserve the old while adapting to the new efficiently. The results and analysis in Sec. 3 suggest that it might be "a bit late" to try to prevent catastrophic forgetting in the few-shot learning sessions ($t \geq 2$), which motivates us to consider this problem in the base training session.

Overview of our approach. To overcome catastrophic forgetting in IFL, we propose to find a b-flat ($b > 0$) local minima $\theta^\star$ of the base training objective function and then fine-tune the model within the flat region in later few-shot learning sessions. Specifically, for any parameter vector θ in the flat region, i.e., $\theta^\star - b \preceq \theta \preceq \theta^\star + b$, the risk (loss) of the base classes is minimized such that the classes are well separated in the embedding space of f_θ. In the later incremental few-shot learning sessions ($t \geq 2$), we fine-tune the model parameters within this region to learn new classes, i.e., to find

$$\theta' = \arg\min_\theta \sum_{z \in \mathcal{D}^t} \mathcal{L}(z; \theta), \ \ \text{s.t.} \ \ \theta^\star - b \preceq \theta \preceq \theta^\star + b.$$

As such, the fine-tuned model θ' can adapt to new classes while preserving the old ones. Also, due to the nature of few-shot learning, to avoid excessive training and overfitting, it suffices to tune the model in a relatively small region. A graphical illustration of our approach and prior arts, as well as the notions of sharp minima and flat minima, are presented in Fig. 2.

4.1 Searching for Flat Local Minima in the Base Training Stage

A formal definition of b-flat local minima is given as follows.

Definition 1 (b-Flat Local Minima). *Given a real-valued objective function $\mathcal{L}(z; \theta)$, for any $b > 0$, $\theta^\star$ is a b-flat local minima of $\mathcal{L}(z; \theta)$, if the following conditions are satisfied.*

- *Condition 1: $\mathcal{L}(z; \theta^\star) = \mathcal{L}(z; \theta^\star + \epsilon)$, where $-\mathbf{b} \preceq \epsilon \preceq \mathbf{b}$ and $\mathbf{b}_i = b$.*

- *Condition 2: there exist $\mathbf{c}_1 \prec \theta^\star - b$ and $\mathbf{c}_2 \succ \theta^\star + b$, s.t. $\mathcal{L}(z; \theta) > \mathcal{L}(z; \theta^\star)$, where $\mathbf{c}_1 \prec \theta \prec \theta^\star - b$ and $\mathcal{L}(z; \theta^\star) < \mathcal{L}(z; \theta)$, where $\theta^\star + b \prec \theta \prec \mathbf{c}_2$.*

In practice, it is hard to find the flat local minima that strictly satisfies the above definition, which may not even exist. Hence, our goal is to find an approximately flat local minima of the base training objective function. To this end, we propose to add some small random noise to the model parameters. The noise can be added for multiple times to obtain similar but different loss functions, which will be

Figure 2: Illustration of our approach and existing solutions. $\rightarrow$ indicates the incremental learning steps on new classes. R_1 and R_2 respectively denote the loss of base classes before and after minimizing the loss of new classes. (a) SGD finds sharp minima in the base training. Directly tuning the model on new classes will result in a severe performance drop on base classes. (b) Enforcing strong constraints on parameters by penalizing parameter changes [1, 28, 34] may still lead to a significant performance drop on base classes. (c) Finding flat local minima of base classes and clamping the parameters after trained on new classes to make them fall within the flat region can effectively mitigate catastrophic forgetting.

optimized together to locate the flat minima region. The intuition is clear – the parameter vectors around the flat local minima also have small function values.

To formally state the idea, we assume that the model is parameterized by $\theta = \{\phi, \psi\}$, where ϕ denotes the parameters of the embedding network and ψ denotes the parameters of the classifier. z denotes a labelled training sample. Denote the loss function by $\mathcal{L}: \mathbb{R}^{d_z} \rightarrow \mathbb{R}$. Our target is to minimize the expected loss function $R: \mathbb{R}^d \rightarrow \mathbb{R}$ w.r.t. the joint distribution of data z and noise ϵ, i.e.,

$$R(\theta) = \int_{\mathbb{R}^{d_\epsilon}} \int_{\mathbb{R}^{d_z}} \mathcal{L}(z; \phi + \epsilon, \psi) \, dP(z) dP(\epsilon) = \mathbb{E}[\mathcal{L}(z; \phi + \epsilon, \psi)], \tag{2}$$

where $P(z)$ is the data distribution and $P(\epsilon)$ is the noise distribution, and z and ϵ are independent. Since it is impossible to minimize the expected loss, we minimize its estimation, the empirical loss, which is given by

$$\mathcal{L}(\theta) = \frac{1}{M} \sum_{j=1}^{M} \mathcal{L}_{\text{base}}(z; \phi + \epsilon_j, \psi), \text{ where} \tag{3}$$

$$\mathcal{L}_{\text{base}}(z; \phi + \epsilon_j, \psi) = \frac{1}{|\mathcal{D}^1|} \sum_{z \in \mathcal{D}^1} \mathcal{L}_{ce}(z; \phi + \epsilon_j, \psi) + \lambda \frac{1}{|\mathcal{C}^1|} \sum_{c \in \mathcal{C}^1} \|p_c - p_c^*\|_2^2, \tag{4}$$

where ϵ_j is a noise vector sampled from $P(\epsilon)$, M is the sampling times, $\mathcal{L}_{ce}(z; \phi + \epsilon_j, \psi)$ refers to the cross-entropy loss of a training sample z, and p_c and p_c^* are the class prototypes before and after injecting noise respectively. The first term of $\mathcal{L}_{base}$ is designed to find the flat region where the parameters ϕ of the embedding network can well separate the base classes. The second term enforces the class prototypes fixed within such region, which is designed to solve the prototype drift problem [54, 8] (the class prototypes change after updating the network) in later incremental learning sessions such that the saved base class prototypes can be directly used for evaluation in later sessions.

4.2 Incremental Few-shot Learning within the Flat Region

In the incremental few-shot learning sessions ($t \geq 2$), we fine-tune the parameters ϕ of the embedding network *within the flat region* to learn new classes. It is worth noting that while the flat region might be relatively small, it is enough for incremental few-shot learning. Because only few training samples are provided for each new class, to prevent overfitting in few-shot learning, excessive training should be avoided and only a small number of update iterations should be applied.

Algorithm 1: F2M

Input: the flat region bound b, randomly initialized $\theta = \{\phi, \psi\}$, the step sizes α and β.

// `Training over base classes` $t = 1$

for epoch k = 1,2,... **do**

    for j = 1,2,..., M **do**

        Sample a noise vector $\epsilon_j \sim P(\epsilon)$, s.t. $-\mathbf{b} \preceq \epsilon_j \preceq \mathbf{b}$;

        Add the noise to the parameters of the embedding network, i.e., $\theta = \{\phi + \epsilon_j, \psi\}$;

        Compute the base loss $\mathcal{L}_{base}$ with Eq. 4;

        Reset the parameters, i.e., $\theta = \{\phi, \psi\}$;

    end

    Update $\theta = \theta - \alpha \nabla \mathcal{L}(\theta)$ with the loss $\mathcal{L}$ defined in Eq. 3.

end

Normalize and save the prototype of each base class;

// `Incremental learning` $t \geq 2$

Combine the training data $\mathcal{D}^t$ and the exemplars saved in previous few-shot sessions $2 \leq t_e < t$;

for epoch k = 1,2,... **do**

    Compute the metric-based classification loss $\mathcal{L}_m$ by Eq. 5;

    Update $\phi = \phi - \beta \nabla \mathcal{L}_m(z; \phi)$;

    Clamp the parameters ϕ to ensure they fall in the flat minima region;

end

Randomly select and save a few exemplars from the training data $\mathcal{D}^t$;

Normalize and save the prototype of each new class;

Output: Model parameters $\theta = \{\phi, \psi\}$.

We employ a metric-based classification algorithm with Euclidean distance to fine-tune the parameters. The loss function is defined as

$$\mathcal{L}_m(z; \phi) = -\sum_{z \in \mathcal{D}} \sum_{c \in \mathcal{C}} \mathbb{1}(y = c) \log \left(\frac{e^{-d(p_c, f(x; \phi))}}{\sum_{c_k \in \mathcal{C}} e^{-d(p_{c_k}, f(x; \phi))}} \right), z \tag{5}$$

where $d(\cdot, \cdot)$ denotes Euclidean distance, p_c is the prototype of class c, $\mathcal{C} = \bigcup_{i=1}^{t} \mathcal{C}^i$ refers to all encountered classes, and $\mathcal{D} = \mathcal{D}^t \bigcup \mathcal{P}$ denotes the union of the current training data $\mathcal{D}^t$ and the exemplar set $\mathcal{P} = \{P_2, ..., P_{t-1}\}$, where $P_{t_e}(2 \leq t_e < t)$ is the set of saved exemplars in session t_e. Note that the prototypes of new classes are computed by Eq. 1, and those of base classes are saved in the base session. After updating the embedding network parameters, we clamp them to ensure that they fall within the flat region, i.e. $\phi^\star - b \preceq \phi \preceq \phi^\star + b$, where $\phi^\star$ denotes the optimal parameter vector learned in the base session. After fine-tuning, we evaluate the model using the nearest class mean classifier as in Eq. 1, with previously saved prototypes and newly computed ones. The whole training process is described in Algorithm 1. Note that to calibrate the estimates of the classifier, we normalize all prototypes to make those of base classes and those of new classes have the same norm.

4.3 Convergence Analysis

Our aim is to find a flat region within which all parameter vectors work well. We then minimize the expected loss w.r.t. the joint distribution of noise ϵ and data z. To approximate this expected loss, we sample from $P(\epsilon)$ for multiple times in each iteration and optimize the objective function using stochastic gradient descent (SGD). Here, we provide theoretical guarantees for our method. Given the non-convex loss function in Eq. 3, we prove the convergence of our proposed method. The proof idea is inspired by the convergence analysis of SGD [3, 27].

Formally, in each batch k, let z_k denote the batch data, $\{\epsilon_j\}_{j=1}^{M}$ be the sampled noises, and α_k be the step size. In the base training session, we update the model parameters as follows:

$$\theta_{k+1} = \theta_k - \frac{\alpha_k}{M} \sum_{j=1}^{M} \nabla \mathcal{L}_{\text{base}}(z_k; \phi_k + \epsilon_j, \psi_k) = \theta_k - \frac{\alpha_k}{M} \sum_{j=1}^{M} g(z_k; \phi_k + \epsilon_j, \psi_k), \tag{6}$$

where $g(z_k; \phi_k + \epsilon_j, \psi_k) = \nabla \mathcal{L}_{\text{base}}(z_k; \phi_k + \epsilon_j, \psi_k)$ is the gradient. To formally analyze the convergence of our algorithm, we define the following assumptions.

Assumption 4.1 (L-smooth risk function). *The expected loss function $R : \mathbb{R}^d \to \mathbb{R}$ (Eq. 2) is continuously differentiable and L-smooth with constant $L > 0$ such that*

$$\|\nabla R(\theta) - \nabla R(\theta')\|_2 \leq L\|\theta - \theta'|. \tag{7}$$

This assumption is significant for the convergence analysis of gradient-based optimization algorithms, since it limits how fast the gradient of the loss function can change w.r.t. the parameter vector.

Assumption 4.2. *The expected loss function satisfies the following conditions:*

- *Condition 1: R is bounded below by a scalar $R^\star$, given the sequence of parameters $\{\theta_k\}$.*

- *Condition 2: For all $k \in \mathbb{N}$ and $j \in [1, M]$,*

$$\mathbb{E}_{z_k, \epsilon_j}[g(z_k; \phi_k + \epsilon_j, \psi_k)] = \nabla R(\theta_k). \tag{8}$$

- *Condition 3: There exist scalars $m_1 \geq 0$ and $m_2 \geq 0$, for all $k \in \mathbb{N}$ and $j \in [1, M]$,*

$$\mathbb{V}_{z_k, \epsilon_j}[g(z_k; \phi_k + \epsilon_j, \psi_k)] \leq m_1 + m_2\|\nabla R(\theta_k)\|_2^2. \tag{9}$$

$\mathbb{E}_{z_k, \epsilon_j}[\cdot]$ denotes the expectation w.r.t. the joint distribution of random variables z_k and ϵ_j, and $\mathbb{V}_{z_k, \epsilon_j}[\cdot]$ denotes the variance. Condition 1 ensures that the expected loss R is bounded by a minimum value $R^\star$ during the updates, which is a natural and practical assumption. Condition 2 assumes that the gradient $g(z_k; \phi_k + \epsilon_j, \psi_k)$ is an unbiased estimate of $\nabla R(\theta_k)$. This is a strict assumption made to simplify the proof, but it can be easily relaxed to a general and easily-met condition that there exist $\mu_1 \geq \mu_2 > 0$ satisfying $\|\mathbb{E}_{z_k, \epsilon_j}[g(z_k; \phi_k + \epsilon_j, \psi_k)]\|_2 \leq \mu_1\|\nabla R(\theta_k)\|_2$ and $\nabla R(\theta_k)^T \mathbb{E}_{z_k, \epsilon_j}[g(z_k; \phi_k + \epsilon_j, \psi_k)] \geq \mu_2\|\nabla R(\theta_k)\|_2^2$. Therefore, the convergence can be proved in a similar way using the techniques presented in the Appendix. Condition 3 assumes the variance of the gradient $g(z_k; \phi_k + \epsilon_j, \psi_k)$ cannot be arbitrarily large, which is also reasonable in practice. To facilitate later analysis, similar to [43], we restrict the step sizes as follows.

Assumption 4.3. *The learning rates satisfy:*

$$\sum_{k=1}^{\infty} \alpha_k = \infty, \ \ \sum_{k=1}^{\infty} \alpha_k^2 < \infty. \tag{10}$$

This assumption can be easily met, since in practice the learning rate α_k is usually far less than 1 and decreases w.r.t. k. Based on the above assumptions, we can derive the following theorem.

Theorem 4.1. *Under assumptions 4.1, 4.2 and 4.3, we further assume that the risk function R is twice differentiable, and that $\|\nabla R(\theta)\|_2^2$ is L_2-smooth with constant $L_2 > 0$, then we have*

$$\lim_{k \to \infty} \mathbb{E}[\|\nabla R(\theta_k)\|_2^2] = 0. \tag{11}$$

This theorem establishes the convergence of our algorithm. The proof is provided in Appendix A.1.

5   Experiments

In this section, we empirically evaluate our proposed method for incremental few-shot learning and demonstrate its effectiveness by comparison with state-of-the-art methods.

5.1   Experimental Setup

Datasets. For CIFAR-100 and *mini*ImageNet, we randomly select 60 classes as the base classes and the remaining 40 classes as the new classes. In each incremental learning session, we construct 5-way 5-shot tasks by randomly picking 5 classes and sampling 5 examples for each class. For CUB-200-2011 with 200 classes, we select 100 classes as the base classes and 100 classes as the new ones. We test 10-way 5-shot tasks on this dataset.

Baselines. We compare our method F2M with 8 methods: the Baseline proposed in Sec. 3, a joint-training method that uses all previously seen data including the base and the following few-shot

Table 1: Classification accuracy on CIFAR-100 for 5-way 5-shot incremental learning. * indicates our re-implementation.

Method	sessions									The gap with cRT
	1	2	3	4	5	6	7	8	9	
cRT [25]*	65.18	63.89	60.20	57.23	53.71	50.39	48.77	47.29	45.28	-
Joint-training*	65.18	61.45	57.36	53.68	50.84	47.33	44.79	42.62	40.08	-5.20
Baseline	65.18	61.67	58.61	55.11	51.86	49.43	47.60	45.64	43.83	-1.45
iCaRL [40]*	66.52	57.26	54.27	50.62	47.33	44.99	43.14	41.16	39.49	-5.79
Rebalance [20]*	**66.66**	61.42	57.29	53.02	48.85	45.68	43.06	40.56	38.35	-6.93
FSLL [34]*	65.18	56.24	54.55	51.61	49.11	47.27	45.35	43.95	42.22	-3.08
iCaRL [40]	64.10	53.28	41.69	34.13	27.93	25.06	20.41	15.48	13.73	-31.55
Rebalance [20]	64.10	53.05	43.96	36.97	31.61	26.73	21.23	16.78	13.54	-31.74
TOPIC [47]	64.10	55.88	47.07	45.16	40.11	36.38	33.96	31.55	29.37	-15.91
FSLL [34]	64.10	55.85	51.71	48.59	45.34	43.25	41.52	39.81	38.16	-7.12
FSLL+SS [34]	66.76	55.52	52.20	49.17	46.23	44.64	43.07	41.20	39.57	-5.71
F2M	64.71	**62.05**	**59.01**	**55.58**	**52.55**	**49.96**	**48.08**	**46.28**	**44.67**	**-0.61**

Table 2: Classification accuracy on *mini*ImageNet for 5-way 5-shot incremental learning. * indicates our re-implementation.

Method	sessions									The gap with cRT
	1	2	3	4	5	6	7	8	9	
cRT [25]*	67.30	64.15	60.59	57.32	54.22	51.43	48.92	46.78	44.85	-
Joint-training*	67.30	62.34	57.79	54.08	50.93	47.65	44.64	42.61	40.29	-4.56
Baseline	67.30	63.18	59.62	56.33	53.28	50.50	47.96	45.85	43.88	-0.97
iCaRL [40]*	67.35	59.91	55.64	52.60	49.43	46.73	44.13	42.17	40.29	-4.56
Rebalance [20]*	67.91	63.11	58.75	54.83	50.68	47.11	43.88	41.19	38.72	-6.13
FSLL [34]*	67.30	59.81	57.26	54.57	52.05	49.42	46.95	44.94	42.87	-1.11
iCaRL [40]	61.31	46.32	42.94	37.63	30.49	24.00	20.89	18.80	17.21	-27.64
Rebalance [20]	61.31	47.80	39.31	31.91	25.68	21.35	18.67	17.24	14.17	-30.68
TOPIC [47]	61.31	50.09	45.17	41.16	37.48	35.52	32.19	29.46	24.42	-20.43
FSLL [34]	66.48	61.75	58.16	54.16	51.10	48.53	46.54	44.20	42.28	-2.57
FSLL+SS [34]	**68.85**	63.14	59.24	55.23	52.24	49.65	47.74	45.23	43.92	-0.93
IDLVQ-C [8]	64.77	59.87	55.93	52.62	49.88	47.55	44.83	43.14	41.84	-3.01
F2M	67.28	**63.80**	**60.38**	**57.06**	**54.08**	**51.39**	**48.82**	**46.58**	**44.65**	**-0.20**

tasks for training, the classifier re-training method (cRT) [25] for long-tailed classification trained with all encountered data, iCaRL [40], Rebalance [20], TOPIC [47], FSLL [34], and IDLVQ-C [8]. For a fair comparison, we re-implement cRT [25], iCaRL [40], Rebalance [20], FSLL [34], and the joint-training method. Note that for IL, joint-training is naturally the upper bound of incremental learning algorithms, however, for IFL, joint-training is not a good approximation of the upper bound because data imbalance makes the model perform significantly poorer on new classes (long-tailed classes). To address the data imbalance issue, we re-implement the cRT method as the *approximate upper bound*.

Experiment Details. We use NVIDIA GPU RTX3090 with CUDA 11.0 to conduct the experiments. We randomly split each dataset into multiple tasks (sessions). For each dataset (with a fixed split), we run each algorithm for 10 times and report the mean accuracy. We adopt ResNet18 [16] as the backbone network. For data augmentation, we use standard random crop and horizontal flip. In the base training stage, we select the last 4 or 8 convolution layers to inject noise, because these layers output higher-level feature representations. The flat region bound b is set as 0.01. We set the number of times for noise sampling as $M = 2 \sim 4$, since a larger M will increase the training time. In each incremental few-shot learning session, the total number of training epochs is 6, and the learning rate is 0.02. To verify the correctness of our implementation, we conduct experiments on incremental learning and compare our results to those reported on CIFAR-100 in Appendix A.3. More experiment details are provided in Appendix A.2.

Table 3: Classification accuracy on CUB-200-2011 for 10-way 5-shot incremental learning.* indicates our re-implementation.

Method	sessions											The gap with cRT
	1	2	3	4	5	6	7	8	9	10	11	
cRT [25]*	80.83	78.51	76.12	73.93	71.46	68.96	67.73	66.75	64.22	62.53	61.08	-
Joint-training*	80.83	77.57	74.11	70.75	68.52	65.97	64.58	62.22	60.18	58.49	56.78	-4.30
Baseline	80.87	77.15	74.46	72.26	69.47	67.18	65.62	63.68	61.30	59.72	58.12	-2.96
iCaRL [40]*	79.58	67.63	64.17	61.80	58.10	55.51	53.34	50.89	48.62	47.34	45.60	-15.48
Rebalance [20]*	80.94	70.32	62.96	57.19	51.06	46.70	44.03	40.15	36.75	34.88	32.09	-28.99
FSLL [34]*	80.83	77.38	72.37	71.84	67.51	65.30	63.75	61.16	59.05	58.03	55.82	-5.26
iCaRL [40]	68.68	52.65	48.61	44.16	36.62	29.52	27.83	26.26	24.01	23.89	21.16	-39.92
Rebalance [20]	68.68	57.12	44.21	28.78	26.71	25.66	24.62	21.52	20.12	20.06	19.87	-41.21
TOPIC [47]	68.68	62.49	54.81	49.99	45.25	41.40	38.35	35.36	32.22	28.31	26.28	-34.80
FSLL [34]	72.77	69.33	65.51	62.66	61.10	58.65	57.78	57.26	55.59	55.39	54.21	-6.87
FSLL+SS [34]	75.63	71.81	68.16	64.32	62.61	60.10	58.82	58.70	56.45	56.41	55.82	-5.26
F2M	**81.07**	**78.16**	**75.57**	**72.89**	**70.86**	**68.17**	**67.01**	**65.26**	**63.36**	**61.76**	**60.26**	**-0.82**

Table 4: Comparison of the flatness of the local minima found by the Baseline and our F2M.

Method	Indicator I		Variance σ^2	
	Training Set	Testing Set	Training Set	Testing Set
Baseline	0.2993	0.4582	0.1451	0.2395
F2M	**0.0506**	**0.0800**	**0.0296**	**0.0334**

5.2 Comparison with the State-of-the-Art

F2M outperforms the state-of-the-art methods. The main results on CIFAR-100, miniImageNet and CUB-200-2011 are presented in Table 1, Table 2 and Table 3 respectively. Based on the experiment results, we have the following observations: **(1)** The Baseline introduced in Sec. 3 outperforms the state-of-the-art approaches on all incremental sessions. **(2)** As expected, cRT consistently outperforms the Baseline up to 1% to 3% by considering the data imbalance problem and applying proper techniques to tackle the long-tailed classification problem to improve performance. Hence, it is reasonable to use cRT as the approximate upper bound of IFL. **(3)** Our F2M outperforms the state-of-the-art methods and the Baseline. Moreover, the performance of F2M is very close to the approximate upper bound, i.e., the gap with cRT is only 0.2% in the last session on *mini*ImageNet. The results show that even with strong constraints [20, 40, 34] and saved examplars of base classes [20, 40, 8], current methods cannot effectively address the catastrophic forgetting problem. In contrast, finding flat minima seems a promising approach to overcome this harsh problem.

5.3 Ablation Study and Analysis

Analysis on the flatness of local minima. Here, we verify that our method can find a more flat local minima than the Baseline. For a found local minima $\theta^\star$, we measure its flatness as follows. We sample the noise for 1000 times. For each time, we inject the sampled noise to $\theta^\star$ and calculate the loss $\mathcal{L}_i$. Then, we adopt the indicator $I = \frac{1}{1000}\sum_{i=1}^{1000}(\mathcal{L}_i - \mathcal{L}^*)^2$ and variance $\sigma^2 = \frac{1}{1000}\sum_{i=1}^{1000}(\mathcal{L}_i - \overline{\mathcal{L}})^2$ to measure the flatness. $\mathcal{L}^*$ denotes the loss of $\theta^\star$, and $\overline{\mathcal{L}}$ denotes the average loss of $\{\mathcal{L}_i\}_{i=1}^{1000}$. The values of the indicator and variance of F2M and the Baseline are presented in Table 4, which clearly demonstrate that our method can find a more flat local minima.

Ablation study on the designs of our method. Here, we study the effectiveness of each design of our method, including adding noise to the model parameters for finding b-flat local minima (FM) during the base training session, the prototype fixing term (PF) used in the base training objective (Eq. 4), parameter clamping (PC) during incremental learning, and prototype normalization (PN). We conduct an ablation study by removing each component in turn and report the experimental results in Table 5.

Finding b-flat local minima. Standard supervised training with SGD as the optimizer tends to converge to a sharp local minima. It leads to a significant drop in performance because the loss changes quickly in the neighborhood of the sharp local minima. As shown in Table 5, even with parameter clamping

Table 5: Ablation study of our F2M on CIFAR-100. PD refers to the performance dropping rate.

FM	PF	PC	PN	sessions									PD↓
				1	2	3	4	5	6	7	8	9	
				65.18	60.83	53.13	43.57	23.75	10.76	08.26	07.24	06.45	58.73
		✓		**65.18**	59.48	56.77	52.99	50.09	47.80	45.92	44.20	42.55	22.63
✓	✓		✓	64.71	59.54	53.03	45.09	41.68	39.04	38.64	37.19	36.01	28.70
✓		✓	✓	64.55	61.27	58.33	54.82	51.60	49.22	47.48	45.78	44.08	20.47
✓	✓	✓		64.71	61.75	58.80	55.33	52.27	49.75	47.72	46.01	44.43	20.28
✓	✓	✓	✓	64.71	**61.99**	**58.99**	**55.58**	**52.55**	**49.96**	**48.08**	**46.28**	**44.67**	**20.04**

Table 6: Study of the flat region bound b for 5-way 5-shot incremental learning on CIFAR-100. The top 3 results in each row are in boldface.

Session	The hyperparameter b					
	0.0025	0.005	0.01	0.02	0.04	0.08
Session 1 (60 bases classes)	**64.85**	64.67	**64.81**	**64.71**	63.30	62.25
Session 9 (All 100 classes)	44.16	**44.54**	**44.58**	**44.67**	43.75	43.04
Session 9 (60 base classes)	**59.58**	**59.69**	**59.73**	59.44	58.38	57.21
Session 9 (40 new classes)	21.03	**21.81**	**21.86**	**22.52**	21.80	21.77

during incremental learning, the performance still drops significantly. In contrast, restricting the parameters in a small flat region can mitigate the forgetting problem.

Prototype fixing. Without fixing the prototypes after injecting noise to selected layers during the process of finding local minima, i.e. removing the second term of Eq. 4, it is still possible to tune the model within the flat region to well separate base classes. However, the saved prototypes of base classes will become less accurate because the embeddings of the base samples suffer from semantic drift [54]. As shown in Table 5, it results in a performance drop of nearly 0.6%.

Parameter clamping. Parameter clamping restricts the model parameters to the b-flat region after incremental few-shot learning. Outside the b-flat region, the performance drops quickly. It can be seen from Table 5 that removing parameter clamping leads to a significant drop in performance.

Prototype normalization. As mentioned in Sec. 4.2, we normalize the class prototypes to calibrate the estimates of the class mean classifier. The results in Table 5 show the effectiveness of normalization, which helps to further improve the performance.

Study of the flat region bound b**.** We study the effect of the flat region bound b for 5-way 5-shot incremental learning on CIFAR-100. We report the test accuracy in session 1 (base session) and session 9 (last session) w.r.t. different b in Table 6. It can be seen that the best results are achieved for $b \in [0.005, 0.02]$. A larger b (e.g., 0.04 or 0.08) leads to a significant performance drop on base classes, even for those in session 1, indicating that there may not exist a large flat region around a good local minima. Meanwhile, a smaller b (e.g., 0.0025) results in a performance decline on new classes, due to the overly small capacity of the flat region. This illustrates the trade-off effect of b.

6   Conclusion

We have proposed a novel approach to overcome catastrophic forgetting in incremental few-shot learning by finding flat local minima of the objective function in the base training stage and then fine-tuning the model within the flat region on new tasks. Extensive experiments on benchmark datasets show that our model can effectively mitigate catastrophic forgetting and adapt to new classes. A limitation of our method is that it may not be suitable for medium- or high-shot tasks, since the flat region is relatively small, which limits the model capacity. However, it is still possible to adapt our core idea for incremental learning. For example, one can search for a less flat but wider local minima region in the base training stage and tune the model within this region during incremental learning sessions, where previous techniques such as elastic weight consolidation (EWC) [28] can be used to constraint the model parameters. We plan to explore this direction in the future.

Acknowledgments and Disclosure of Funding

We would like to thank the anonymous reviewers for their insightful and helpful comments. This research was supported by the grant of DaSAIL project P0030935 funded by PolyU/UGC.

References

[1] Rahaf Aljundi, Francesca Babiloni, Mohamed Elhoseiny, Marcus Rohrbach, and Tinne Tuytelaars. Memory aware synapses: Learning what (not) to forget. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pages 139–154, 2018.

[2] Carlo Baldassi, Fabrizio Pittorino, and Riccardo Zecchina. Shaping the learning landscape in neural networks around wide flat minima. *Proc. Natl. Acad. Sci. USA*, 117(1):161–170, 2020.

[3] Léon Bottou, Frank E Curtis, and Jorge Nocedal. Optimization methods for large-scale machine learning. *Siam Review*, 60(2):223–311, 2018.

[4] Francisco M Castro, Manuel J Marín-Jiménez, Nicolás Guil, Cordelia Schmid, and Karteek Alahari. End-to-end incremental learning. In *Proceedings of the European conference on computer vision (ECCV)*, pages 233–248, 2018.

[5] Arslan Chaudhry, Puneet K Dokania, Thalaiyasingam Ajanthan, and Philip HS Torr. Riemannian walk for incremental learning: Understanding forgetting and intransigence. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pages 532–547, 2018.

[6] Arslan Chaudhry, Marc'Aurelio Ranzato, Marcus Rohrbach, and Mohamed Elhoseiny. Efficient lifelong learning with a-gem. In *International Conference on Learning Representations*, 2018.

[7] Hung-Jen Chen, An-Chieh Cheng, Da-Cheng Juan, Wei Wei, and Min Sun. Mitigating forgetting in online continual learning via instance-aware parameterization. *Advances in Neural Information Processing Systems*, 33, 2020.

[8] Kuilin Chen and Chi-Guhn Lee. Incremental few-shot learning via vector quantization in deep embedded space. In *International Conference on Learning Representations*, 2021.

[9] Ali Cheraghian, Shafin Rahman, Pengfei Fang, Soumava Kumar Roy, Lars Petersson, and Mehrtash Harandi. Semantic-aware knowledge distillation for few-shot class-incremental learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 2534–2543, 2021.

[10] Prithviraj Dhar, Rajat Vikram Singh, Kuan-Chuan Peng, Ziyan Wu, and Rama Chellappa. Learning without memorizing. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2019.

[11] Gintare Karolina Dziugaite and Daniel M. Roy. Computing nonvacuous generalization bounds for deep (stochastic) neural networks with many more parameters than training data. In Gal Elidan, Kristian Kersting, and Alexander T. Ihler, editors, *Proceedings of the Thirty-Third Conference on Uncertainty in Artificial Intelligence, UAI 2017, Sydney, Australia, August 11-15, 2017*. AUAI Press, 2017.

[12] Chelsea Finn, Pieter Abbeel, and Sergey Levine. Model-agnostic meta-learning for fast adaptation of deep networks. In *International Conference on Machine Learning*, pages 1126–1135. PMLR, 2017.

[13] Spyros Gidaris and Nikos Komodakis. Dynamic few-shot visual learning without forgetting. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 4367–4375, 2018.

[14] Ian J Goodfellow, Mehdi Mirza, Da Xiao, Aaron Courville, and Yoshua Bengio. An empirical investigation of catastrophic forgetting in gradient-based neural networks. *arXiv preprint arXiv:1312.6211*, 2013.

[15] Haowei He, Gao Huang, and Yang Yuan. Asymmetric valleys: Beyond sharp and flat local minima. In Hanna M. Wallach, Hugo Larochelle, Alina Beygelzimer, Florence d'Alché-Buc, Emily B. Fox, and Roman Garnett, editors, *Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, December 8-14, 2019, Vancouver, BC, Canada*, pages 2549–2560, 2019.

[16] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.

[17] Geoffrey E. Hinton and Drew van Camp. Keeping the neural networks simple by minimizing the description length of the weights. In Lenny Pitt, editor, *Proceedings of the Sixth Annual ACM Conference on Computational Learning Theory, COLT 1993, Santa Cruz, CA, USA, July 26-28, 1993*, pages 5–13. ACM, 1993.

[18] Sepp Hochreiter and Jürgen Schmidhuber. Simplifying neural nets by discovering flat minima. In Gerald Tesauro, David S. Touretzky, and Todd K. Leen, editors, *Advances in Neural Information Processing Systems 7, [NIPS Conference, Denver, Colorado, USA, 1994]*, pages 529–536. MIT Press, 1994.

[19] Ruibing Hou, Hong Chang, Bingpeng Ma, Shiguang Shan, and Xilin Chen. Cross attention network for few-shot classification. In *Proceedings of the 33rd International Conference on Neural Information Processing Systems*, pages 4003–4014, 2019.

[20] Saihui Hou, Xinyu Pan, Chen Change Loy, Zilei Wang, and Dahua Lin. Learning a unified classifier incrementally via rebalancing. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 831–839, 2019.

[21] Wenpeng Hu, Zhou Lin, Bing Liu, Chongyang Tao, Zhengwei Tao, Jinwen Ma, Dongyan Zhao, and Rui Yan. Overcoming catastrophic forgetting for continual learning via model adaptation. In *International Conference on Learning Representations*, 2018.

[22] Xinting Hu, Kaihua Tang, Chunyan Miao, Xian-Sheng Hua, and Hanwang Zhang. Distilling causal effect of data in class-incremental learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 3957–3966, 2021.

[23] Muhammad Abdullah Jamal and Guo-Jun Qi. Task agnostic meta-learning for few-shot learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 11719–11727, 2019.

[24] Yiding Jiang*, Behnam Neyshabur*, Hossein Mobahi, Dilip Krishnan, and Samy Bengio. Fantastic generalization measures and where to find them. In *International Conference on Learning Representations*, 2020.

[25] Bingyi Kang, Saining Xie, Marcus Rohrbach, Zhicheng Yan, Albert Gordo, Jiashi Feng, and Yannis Kalantidis. Decoupling representation and classifier for long-tailed recognition. In *International Conference on Learning Representations*, 2019.

[26] Ronald Kemker and Christopher Kanan. Fearnet: Brain-inspired model for incremental learning. In *International Conference on Learning Representations*, 2018.

[27] J. Kiefer and J. Wolfowitz. Stochastic estimation of the maximum of a regression function. *Annals of Mathematical Statistics*, 23:462–466, 1952.

[28] James Kirkpatrick, Razvan Pascanu, Neil Rabinowitz, Joel Veness, Guillaume Desjardins, Andrei A Rusu, Kieran Milan, John Quan, Tiago Ramalho, Agnieszka Grabska-Barwinska, et al. Overcoming catastrophic forgetting in neural networks. *Proceedings of the national academy of sciences*, 114(13):3521–3526, 2017.

[29] Alex Krizhevsky et al. Learning multiple layers of features from tiny images. 2009.

[30] Ilja Kuzborskij, Francesco Orabona, and Barbara Caputo. From n to n+ 1: Multiclass transfer incremental learning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 3358–3365, 2013.

[31] Zhizhong Li and Derek Hoiem. Learning without forgetting. *IEEE transactions on pattern analysis and machine intelligence*, 40(12):2935–2947, 2017.

[32] Yaoyao Liu, Bernt Schiele, and Qianru Sun. An ensemble of epoch-wise empirical bayes for few-shot learning. In *European Conference on Computer Vision*, pages 404–421. Springer, 2020.

[33] Yaoyao Liu, Yuting Su, An-An Liu, Bernt Schiele, and Qianru Sun. Mnemonics training: Multi-class incremental learning without forgetting. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 12245–12254, 2020.

[34] Pratik Mazumder, Pravendra Singh, and Piyush Rai. Few-shot lifelong learning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pages 2337–2345, 2021.

[35] Michael McCloskey and Neal J Cohen. Catastrophic interference in connectionist networks: The sequential learning problem. In *Psychology of learning and motivation*, volume 24, pages 109–165. Elsevier, 1989.

[36] Thomas Mensink, Jakob Verbeek, Florent Perronnin, and Gabriela Csurka. Distance-based image classification: Generalizing to new classes at near-zero cost. *IEEE transactions on pattern analysis and machine intelligence*, 35(11):2624–2637, 2013.

[37] Fabrizio Pittorino, Carlo Lucibello, Christoph Feinauer, Gabriele Perugini, Carlo Baldassi, Elizaveta Demyanenko, and Riccardo Zecchina. Entropic gradient descent algorithms and wide flat minima. In *International Conference on Learning Representations*, 2021.

[38] Jathushan Rajasegaran, Salman Khan, Munawar Hayat, Fahad Shahbaz Khan, and Mubarak Shah. itaml: An incremental task-agnostic meta-learning approach. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 13588–13597, 2020.

[39] Sachin Ravi and Hugo Larochelle. Optimization as a model for few-shot learning. 2016.

[40] Sylvestre-Alvise Rebuffi, Alexander Kolesnikov, Georg Sperl, and Christoph H Lampert. icarl: Incremental classifier and representation learning. In *Proceedings of the IEEE conference on Computer Vision and Pattern Recognition*, pages 2001–2010, 2017.

[41] Mengye Ren, Renjie Liao, Ethan Fetaya, and Richard S Zemel. Incremental few-shot learning with attention attractor networks. In *Proceedings of the 33rd International Conference on Neural Information Processing Systems*, pages 5275–5285, 2019.

[42] Matthew Riemer, Ignacio Cases, Robert Ajemian, Miao Liu, Irina Rish, Yuhai Tu, and Gerald Tesauro. Learning to learn without forgetting by maximizing transfer and minimizing interference. In *International Conference on Learning Representations*, 2018.

[43] H. Robbins. A stochastic approximation method. *Annals of Mathematical Statistics*, 22:400–407, 2007.

[44] Jake Snell, Kevin Swersky, and Richard Zemel. Prototypical networks for few-shot learning. In *Proceedings of the 31st International Conference on Neural Information Processing Systems*, pages 4080–4090, 2017.

[45] Qianru Sun, Yaoyao Liu, Zhaozheng Chen, Tat-Seng Chua, and Bernt Schiele. Meta-transfer learning through hard tasks. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2020.

[46] Qianru Sun, Yaoyao Liu, Tat-Seng Chua, and Bernt Schiele. Meta-transfer learning for few-shot learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 403–412, 2019.

[47] Xiaoyu Tao, Xiaopeng Hong, Xinyuan Chang, Songlin Dong, Xing Wei, and Yihong Gong. Few-shot class-incremental learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 12183–12192, 2020.

[48] Yonglong Tian, Yue Wang, Dilip Krishnan, Joshua B Tenenbaum, and Phillip Isola. Rethinking few-shot image classification: a good embedding is all you need? In *Computer Vision–ECCV 2020: 16th European Conference, Glasgow, UK, August 23–28, 2020, Proceedings, Part XIV 16*, pages 266–282. Springer, 2020.

[49] Oriol Vinyals, Charles Blundell, Timothy Lillicrap, Koray Kavukcuoglu, and Daan Wierstra. Matching networks for one shot learning. In *Proceedings of the 30th International Conference on Neural Information Processing Systems*, pages 3637–3645, 2016.

[50] Peter Welinder, Steve Branson, Takeshi Mita, Catherine Wah, Florian Schroff, Serge Belongie, and Pietro Perona. Caltech-ucsd birds 200. 2010.

[51] Qianru Sun Yaoyao Liu, Bernt Schiele. Adaptive aggregation networks for class-incremental learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2021.

[52] Han-Jia Ye, Hexiang Hu, and De-Chuan Zhan. Learning adaptive classifiers synthesis for generalized few-shot learning. *International Journal of Computer Vision*, pages 1–24, 2021.

[53] Han-Jia Ye, Hexiang Hu, De-Chuan Zhan, and Fei Sha. Few-shot learning via embedding adaptation with set-to-set functions. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 8808–8817, 2020.

[54] Lu Yu, Bartlomiej Twardowski, X. Liu, Luis Herranz, Kai Wang, Yong mei Cheng, Shangling Jui, and Joost van de Weijer. Semantic drift compensation for class-incremental learning. *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 6980–6989, 2020.

[55] Zhongqi Yue, Hanwang Zhang, Qianru Sun, and Xian-Sheng Hua. Interventional few-shot learning. *Advances in Neural Information Processing Systems*, 33, 2020.

[56] Friedemann Zenke, Ben Poole, and Surya Ganguli. Continual learning through synaptic intelligence. In *International Conference on Machine Learning*, pages 3987–3995. PMLR, 2017.

[57] Chi Zhang, Yujun Cai, Guosheng Lin, and Chunhua Shen. Deepemd: Differentiable earth mover's distance for few-shot learning. *arXiv e-prints*, pages arXiv–2003, 2020.

[58] Chi Zhang, Yujun Cai, Guosheng Lin, and Chunhua Shen. Deepemd: Few-shot image classification with differentiable earth mover's distance and structured classifiers. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 12203–12213, 2020.

[59] Chi Zhang, Nan Song, Guosheng Lin, Yun Zheng, Pan Pan, and Yinghui Xu. Few-shot incremental learning with continually evolved classifiers. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 12455–12464, 2021.

[60] Hanbin Zhao, Yongjian Fu, Mintong Kang, Q Tian, F Wu, and X Li. Mgsvf: Multi-grained slow vs. fast framework for few-shot class-incremental learning. *arXiv preprint arXiv:2006.15524*.