Forget What's Sensitive, Remember What Matters: Token-Level Differential Privacy in Memory Sculpting for Continual Learning

Abstract

Continual Learning (CL) models, while adept at sequential knowledge acquisition, face significant and often overlooked privacy challenges due to accumulating diverse information. Traditional privacy methods, like a uniform Differential Privacy (DP) budget, indiscriminately protect all data, leading to substantial model utility degradation and hindering CL deployment in privacy-sensitive areas. To overcome this, we propose a privacy-enhanced continual learning (PeCL) framework that forgets what's sensitive and remembers what matters. Our approach first introduces a token-level dynamic Differential Privacy strategy that adaptively allocates privacy budgets based on the semantic sensitivity of individual tokens. This ensures robust protection for private entities while minimizing noise injection for non-sensitive, general knowledge. Second, we integrate a privacy-guided memory sculpting module. This module leverages the sensitivity analysis from our dynamic DP mechanism to intelligently forget sensitive information from the model's memory and parameters, while explicitly preserving the task-invariant historical knowledge crucial for mitigating catastrophic forgetting. Extensive experiments show that PeCL achieves a superior balance between privacy preserving and model utility, outperforming baseline models by maintaining high accuracy on previous tasks while ensuring robust privacy.

1 Introduction

The rapidly expanding field of Continual Learning (CL) seeks to enable models to acquire and integrate new knowledge sequentially without forgetting what they've already learned, much like human intelligence (Yang et al., 2025; Shi et al., 2024). This capability is essential for real-world applications where data streams are continuous and dynamic, such as in personalized recommendation systems, autonomous driving, and healthcare diagnostics. However, as CL models, particularly powerful Large Language Models (LLMs), continuously assimilate diverse and evolving datasets, they inherently accumulate vast amounts of information. Much of this information can contain sensitive personal or proprietary data (Carlini et al., 2021; Charles et al., 2024). This inherent characteristic poses significant and often overlooked privacy challenges, raising concerns about potential data leakage and misuse.

Research shows that LLMs can inadvertently memorize sensitive or personally identifiable information (PII) during training or fine-tuning (Meng et al., 2025; Kuo et al., 2025). Once embedded, such data become extremely difficult to audit, modify, or erase, posing significant legal and ethical challenges (Liu et al., 2025; Wang et al., 2024). Differential Privacy (DP) offers a mathematically rigorous solution by limiting the influence of individual training samples on model outputs (Dwork, 2006). While promising, applying DP to LLMs, particularly in continual learning settings, poses significant challenges. Standard methods like DPSGD (Abadi et al., 2016) and federated approaches like DP-FedEXP (Takakura et al., 2025) typically apply noise globally, often degrading performance in diverse tasks. While PMixED (Flemings et al., 2024) introduces an effective token-level DP baseline for next-token prediction, it is designed for static datasets and does not address catastrophic forgetting in continual learning (CL). These limitations are exacerbated in batch-incremental continual learning, as data arrive sequentially in this setting, which most DP methods designed for static datasets and single-round training are ill-equipped to handle (Abadi et al., 2016).

Specifically within CL, some works have investigated private data replay or private memory management to mitigate catastrophic forgetting while preserving privacy. In such scenarios, privacy risks can accumulate across training phases as each task

introduces different types of sensitive information (Desai et al., 2021). Recent alternative methods exploring synthetic data (Murtaza et al., 2023) or computer vision-focused subnetwork isolation like PALL (Özdenizci et al., 2025) are not directly applicable to token-level privacy in LLMs. Furthermore, as theoretically proven by Chourasia and Shah (2023), achieving selective forgetting without degrading overall model utility remains fundamentally challenging. This capability is essential for trustworthy and privacy-compliant continual learning. However, these methods often struggle to differentiate between the varying levels of sensitivity within data, leading to either insufficient protection for highly sensitive information or excessive noise injection for general knowledge.

The primary challenges in achieving privacy-enhanced continual learning lie in three key areas. Firstly, effectively discerning and quantifying the sensitivity of different pieces of information at a fine-grained level (e.g., token-level in text) remains a significant hurdle. Without this nuanced understanding, a blanket privacy approach either over-protects non-sensitive data, leading to unnecessary utility loss, or under-protects truly sensitive data, resulting in privacy breaches. Secondly, balancing the often conflicting goals of privacy protection and knowledge retention (i.e., mitigating catastrophic forgetting) is a complex optimization problem. Injecting noise for privacy can inadvertently corrupt crucial historical knowledge, making it difficult for the model to recall past tasks. Finally, integrating a privacy mechanism seamlessly into the CL paradigm, where knowledge acquisition is sequential and dynamic, requires a novel architectural design that can adapt its privacy enforcement based on the evolving nature of the learned information.

To address these challenges, we propose a novel privacy-enhanced continual learning (PeCL) framework that champions the principle of "forgetting what's sensitive and remembering what matters". Our approach is built upon two core innovations. First, we introduce a token-level dynamic Differential Privacy strategy that adaptively allocates privacy budgets based on the semantic sensitivity of individual tokens. This mechanism intelligently identifies and quantifies the privacy risk associated with each token, ensuring robust protection for private entities while minimizing noise injection for non-sensitive, general knowledge. Second, we integrate a privacy-guided memory sculpting module. This module leverages the fine-grained

sensitivity analysis from our dynamic DP mechanism to intelligently and selectively forget sensitive information from the model's memory and parameters. Crucially, it simultaneously and explicitly preserves the task-invariant historical knowledge that is vital for mitigating catastrophic forgetting. We conduct extensive experiments across various continual learning benchmarks, demonstrating that our method achieves a superior balance between privacy protection and model utility. Our approach significantly outperforms baseline models by maintaining high accuracy on previous tasks while ensuring robust privacy guarantees.

In summary, our paper makes the following three main contributions:

- We propose a novel token-level dynamic Differential Privacy strategy that adaptively allocates privacy budgets based on the semantic sensitivity of individual tokens, enabling fine-grained and efficient privacy protection in continual learning.

- We introduce a privacy-guided memory sculpting module that intelligently forgets sensitive information from the model's memory while explicitly preserving task-invariant historical knowledge crucial for mitigating catastrophic forgetting.

- We empirically demonstrate that our framework achieves a superior balance between privacy protection and model utility, significantly outperforming state-of-the-art baselines in continual learning scenarios.

2 Related Work

2.1 Privacy-Preserving in LLMs

The growing deployment of LLMs in privacy-sensitive domains has intensified interest in privacy-preserving training techniques. A key line of research applies DP to large-scale models, with early methods such as DPSGD (Abadi et al., 2016) and recent advances like large-scale DP pretraining (Yu et al., 2021). Moreover, DP-MLM (Meisenbacher et al., 2024) introduces per-token protection via masked prediction and differential privacy constraints, improving the fidelity of downstream tasks while maintaining privacy. Others have explored attention-based perturbations to preserve privacy (Huang et al., 2022) or enforcing local differential privacy at inference time, such as segmentation denoising (Mai et al., 2023) . PMixED (Flemings et al., 2024) provides a robust token-level DP baseline for next-token prediction, but it is limited to

static datasets rather than continual learning. Meanwhile, anti-learning-based techniques such as ForgetMeNot (Feldman, 2020) and SISA (Bourtoule et al., 2021) attempt to remove data effects retroactively, but typically require retraining or model partitioning, which is not feasible in parameter-efficient continuous learning settings. Unlike these approaches, we integrate token-level sensitivity estimation and dynamic perturbations directly into the continuous learning phase. Furthermore, we introduce selective anti-learning capabilities via memory shaping, enabling privacy-aware adaptation without expensive retraining.

2.2 Continual Learning of LLMs

Continual learning (CL) for large language models (LLMs) aims to enable models to incrementally acquire new knowledge across multiple tasks while mitigating catastrophic forgetting (Yang et al., 2025). Classical CL techniques, including Elastic Weight Consolidation (EWC) (Kirkpatrick et al., 2017), Experience Replay (ER) (Rolnick et al., 2019), and functional regularization (Gomez-Villa et al., 2022) , constrain parameter drift to preserve prior knowledge. However, these methods scale poorly with large models and often require full access to task-specific data or gradients.

Recent research has further explored more efficient and modular paradigms for continual learning. For instance, some works decouple parameter updates for different tasks by introducing orthogonal or low-rank subspaces, thereby enabling the effective learning and retention of new knowledge with almost no increase in model parameters (Wang et al., 2023; Yadav et al., 2023). Other studies have focused on constructing dynamic, modular architectures that activate relevant model components for specific tasks at inference time through task routers or a combination of expert models (Jung and Kim, 2024; Huai et al., 2025). Such methods not only enhance the model's scalability and forward transfer capabilities but also offer new solutions for mitigating interference between tasks through explicit functional separation, allowing large models to adapt more flexibly to continuously changing data streams. However, most CL methods ignore privacy or rely on unrealistic full data access. A pioneering exception is Desai et al. (2021), who introduced a sequence-level DP-CL algorithm using episodic memory. PeCL advances this paradigm by replacing coarse-grained sequence-level perturbations with fine-grained, token-level dynamic noise, and substituting standard episodic memory with privacy-guided memory sculpting to better mitigate catastrophic forgetting.

3 Our Approach

In this paper, we propose a privacy-preserving framework for continual learning (Figure 1) that dynamically protects sensitive information at the token level through fine-grained sensitivity analysis, while actively sculpting the model's memory to forget sensitive data and consolidate general knowledge. The framework comprises two key components: (1) Token-level Dynamic Differential Privacy, which adaptively allocates privacy budgets based on the sensitivity of each token, and (2) Privacy-Guided Memory Sculpting, a mechanism that integrates targeted forgetting of sensitive content with preservation of general knowledge, guided by the sensitivity signals from the first component.

3.1 Task Formulation

Formally, we consider a continual learning (CL) setup, where a sequence of tasks $\mathcal{T}_1, \mathcal{T}_2, \ldots, \mathcal{T}_N$ arrives incrementally. Each task $\mathcal{T}_n = \{(x_i, y_i)\}$ consists of input–output pairs from distinct tasks. Let $t = (t_1, \ldots, t_n)$ denote a tokenized sequence. Instead of applying a uniform privacy budget across tokens or tasks, we assign a privacy-aware sensitivity score $\text{Score}(t_i) \in [0, 1]$ to each token t_i, based on both model behavior and corpus-level statistics. This score dynamically adjusts the local DP budget ϵ_i and guides subsequent gradient perturbation and memory regularization. The goal of this task is to learn new knowledge without forgetting the skills learned from previous tasks under the privacy protection setting.

3.2 Token-level Dynamic Differential Privacy

We propose a *Token-level Dynamic Differential Privacy* (TDP) mechanism that adaptively calibrates privacy protection according to the sensitivity of individual tokens. Our approach dynamically adjusts the noise scale applied during training or inference based on a per-token sensitivity score, and we provide a theoretical guarantee that the resulting mechanism satisfies local differential privacy at the token level.

Token Sensitivity Calculation. For each token t_i in an input sequence, we compute a privacy sensitivity score $\text{Score}(t_i) \in [0, 1]$, which reflects

Figure 1: The framework of our PeCL, which is designed to balance privacy and utility by dynamically applying token-level differential privacy and intelligently sculpting model memory to retain crucial knowledge while forgetting sensitive information. The framework comprises two core modules: (a) Token-level Dynamic Differential Privacy, which adaptively injects noise into token embeddings based on their calculated sensitivity, and (b) Privacy-Guided Memory Sculpting, which leverages this sensitivity information to dynamically regularize parameters and implement privacy-aware unlearning, ensuring both catastrophic forgetting mitigation and robust privacy guarantees across sequential tasks.

how likely the token is to contain private or task-specific information. This score is derived from a weighted combination of two complementary indicators—model uncertainty and contextual discriminativeness as follows:

$$\text{Score}(t_i) =$$
$$1-\exp\Big(-\big(\alpha \cdot \text{Score}_1(t_i)+(1-\alpha) \cdot \text{Score}_2(t_i)\big)\Big), \tag{1}$$

where $\alpha \in [0,1]$ is a tunable hyperparameter that balances the contributions of the two components. A larger α places greater emphasis on model uncertainty (Score_1), while a smaller α prioritizes contextual informativeness (Score_2).

The first component, $\text{Score}_1(t_i)$, quantifies the model's predictive uncertainty about token t_i given its preceding context $t_{<i}$. Formally, it is defined as the negative log-likelihood under the model's predictive distribution:

$$\text{Score}_1(t_i) = -\log P_\theta(t_i \mid t_{<i}), \tag{2}$$

where P_θ denotes the probability assigned by the model parameterized by θ. A higher value of $\text{Score}_1(t_i)$ indicates that the token is either rare, highly context-dependent, or inconsistent with the model's expectations—characteristics often associated with sensitive content.

The second component, $\text{Score}_2(t_i)$, captures the token's contextual discriminativeness across a set of tasks $\mathcal{T}_1, \ldots, \mathcal{T}_N$. Inspired by the classic TF-IDF (Term Frequency-Inverse Document Frequency) algorithm (Salton and Buckley, 1988), we adapt and extend traditional document-level statistics to a task-level formulation to measure token specificity. Unlike simple frequency-based measures, this adapted score emphasizes tokens that are strongly associated with specific tasks, as such tokens may inadvertently reveal private or task-identifying information. It is computed as:

$$\text{Score}_2(t_i) = \frac{1}{N} \sum_{n=1}^{N} p_n(t_i) \cdot \log\left(\frac{N}{1+d(t_i)}\right), \tag{3}$$

where $p_n(t_i)$ denotes the normalized contextual salience of token t_i within task $\mathcal{T}_n$, defined by

$$p_n(t_i) = \frac{f_n(t_i)}{f_n^{\max}}. \tag{4}$$

Here, $f_n(t_i)$ is the raw frequency of t_i across all samples in task $\mathcal{T}_n$, and $f_n^{\max}$ is the maximum to-

ken frequency observed in the same task, ensuring that $p_n(t_i) \in [0, 1]$.

To assess how broadly a token appears across tasks, we define the task-wise support count $d(t_i)$ as the number of tasks in which t_i exhibits non-negligible relevance:

$$d(t_i) = |\{n \in \{1, \ldots, N\} \,|\, p_n(t_i) \geq \tau\}|, \quad (5)$$

where $\tau \in (0, 1)$ (e.g., $\tau = 0.2$) is a small threshold. Tokens with low $d(t_i)$—i.e., those that are salient in only a few tasks—are assigned higher discriminativeness scores, as they are more likely to carry task-specific or sensitive signals.

By integrating predictive uncertainty and cross-task discriminativeness, our sensitivity scoring mechanism enables fine-grained, context-aware privacy control. This, in turn, allows the TDP framework to dynamically modulate the magnitude of injected noise per token, ensuring stronger protection for high-sensitivity tokens while preserving utility for less sensitive ones.

Token-wise Dynamic Privacy Allocation. Based on the fused sensitivity score $\text{Score}(t_i)$, we define a token-wise dynamic privacy budget ϵ_i as:

$$\epsilon_i = \epsilon_{\text{lower}} + (\epsilon_{\text{upper}} - \epsilon_{\text{lower}}) \cdot (1 - \text{Score}(t_i))^2, \quad (6)$$

where ϵ_{lower} and ϵ_{upper} are the minimum and maximum allowable privacy budgets. This formulation ensures that tokens with higher sensitivity (closer to 1) receive smaller privacy budgets (i.e., stronger protection), while less sensitive tokens (closer to 0) are granted larger ϵ_i to preserve utility. Following prior work on differential privacy (Abadi et al., 2016), we set the token-level privacy budget range to $\epsilon_i \in [1, 10]$, reflecting a practical balance between model utility and privacy consistent with widely adopted DP regimes.

To enforce (ϵ_i, δ)-differential privacy at the token level, we inject calibrated Gaussian noise into the input embedding of each token. δ represents the probability that the privacy guarantee is violated and is typically set to a cryptographically small value. Specifically, let $e_i \in \mathbb{R}^d$ denote the input embedding retrieved directly from the vocabulary lookup table before entering any layers. Injecting noise at this initial stage ensures local differential privacy at the source, preventing sensitive information leakage prior to contextual mixing in the self-attention mechanism. Let C be a predefined clipping norm bound. The perturbed embedding $\tilde{e}_i$ is computed as:

$$\tilde{e}_i = \text{clip}(e_i, C) + \mathcal{N}(0, \sigma_i^2 I), \quad (7)$$

where $\sigma_i = \frac{2C \cdot \sqrt{2 \log(1.25/\delta)}}{\epsilon_i}$. Only tokens with a non-zero sensitivity score (and thus a defined ϵ_i) receive noise. The $\text{clip}(\cdot, C)$ operation ensures that the ℓ_2 norm of the embedding is bounded before noise injection, which is a necessary condition for satisfying DP guarantees. This mechanism allows our model to adaptively trade off between privacy and utility at a fine-grained level, directly guided by the semantic and contextual signals encoded in $\text{Score}(t_i)$. By tailoring noise strength per token, our approach achieves localized privacy protection, ensuring that each token embedding satisfies (ϵ_i, δ)-DP while maintaining overall task performance.

3.3 Privacy-Guided Memory Sculpting

While token-level dynamic differential privacy provides localized privacy at the input embedding level, it does not inherently prevent sensitive information from being memorized within the model parameters over time. To address this, we introduce Privacy-guided Memory Sculpting (PMS), which reshapes parameter updates by integrating token-level privacy sensitivity into the learning dynamics. Our method comprises two complementary components: Memory Regularization and Privacy-Aware Unlearning.

Memory Regularization. For each incoming task $\mathcal{T}_k$, we first compute the parameter increment for LoRA (Hu et al., 2022) adapter j as:

$$\Delta W_j^{(k)} = B_j^{(k)} A_j^{(k)}. \quad (8)$$

where $\Delta W_j^{(k)}$ means the learned update specific to task $\mathcal{T}_k$. Next, inspired by Sun et al. (2023), we compute a task-specific importance score, Ω_k, by multiplying the Frobenius norm of $\Delta W_j^{(k)}$ with the L_2 norm of the input activations x corresponding to task $\mathcal{T}_k$:

$$\Omega_k = \left\| \Delta W_j^{(k)} \right\|_F \times \|x\|_2. \quad (9)$$

We then accumulate the importance across tasks using an online average, which serves as a measure of the cumulative importance of previously learned knowledge:

$$\bar{\Omega}_k = \frac{1}{k} \sum_{i=1}^{k} \Omega_i. \quad (10)$$

Method	Task1	Task2	Task3	Task4	Task5	Task6	BWT	Last	Avg
SeqFT+DPSGD	0.141	0.293	0.633	0.345	0.149	0.493	-0.116	0.342	0.403
ER+DPSGD	0.438	0.463	0.536	0.443	0.152	0.573	-0.136	0.434	0.486
EWC+DPSGD	0.444	0.284	0.471	0.302	0.160	0.481	-0.137	0.358	0.393
GEM+DPSGD	0.337	0.333	0.394	0.339	0.179	0.356	-0.157	0.323	0.387
OLora+DPSGD	0.297	0.338	0.438	0.322	0.164	0.405	-0.166	0.327	0.395
SeqFT+FN	0.101	0.204	0.145	0.200	0.135	0.331	-0.306	0.186	0.351
ER+FN	**0.456**	0.420	0.673	0.371	0.029	0.309	-0.121	0.376	0.492
EWC+FN	0.260	0.231	0.208	0.236	0.261	0.183	-0.248	0.230	0.397
GEM+FN	0.365	0.253	0.519	0.276	0.285	0.210	-0.193	0.318	0.428
OLora+FN	0.329	0.192	0.240	0.177	0.106	0.165	-0.294	0.202	0.363
PMixED	0.431	0.110	0.737	0.338	0.376	0.419	-0.118	0.402	0.463
PeCL (Ours)	0.436	**0.521**	**0.769**	**0.444**	**0.456**	**0.714**	**-0.093**	**0.573**	**0.535**
MTL+DPSGD (Upper Bound)	0.456	0.538	0.780	0.482	0.197	0.334	-	0.464	-
MTL+FN (Upper Bound)	0.405	0.463	0.808	0.448	0.503	0.305	-	0.489	-

Table 1: Performance comparison of different methods.

Finally, inspired by the classic Elastic Weight Consolidation (EWC) (Kirkpatrick et al., 2017) approach, we define the stability-aligned regularization loss. While EWC typically relies on the Fisher Information Matrix, we adapt this regularization principle directly to the LoRA parameter space to stabilize parameters crucial for retaining historical knowledge:

$$\mathcal{L}_{\text{reg}} = \lambda_{\text{dyn}} \cdot \bar{\Omega}_k \cdot \left\| W_j^{(k)} - W_j^{(k-1)} \right\|_F^2, \quad (11)$$

where $W_j^{(k)}$ denotes the current LoRA parameters for task k, and λ_{dyn} is a dynamic regularization weight.

To introduce privacy-aware adaptivity into this regularization, we modulate the regularization strength dynamically according to the average token sensitivity score $\bar{s}_k$ of task $\mathcal{T}_k$. Specifically, we define the dynamic coefficient λ_{dyn} as:

$$\lambda_{\text{dyn}} = \lambda_{\text{max}} \cdot (1 - \bar{s}_k) + \lambda_{\text{min}} \cdot \bar{s}_k, \quad (12)$$

where λ_{max} and λ_{min} represent the maximum and minimum levels of regularization strength, respectively. This formulation ensures that tasks involving less sensitive content (i.e., lower $\bar{s}_k$) are regularized more strictly to retain prior knowledge, while more privacy-sensitive tasks are allowed greater flexibility for adaptation and forgetting. The average sensitivity $\bar{s}_k$ for task $\mathcal{T}_k$ is computed as the mean of $\text{Score}(t_i)$ over all tokens t_i in the task's data.

Privacy-Aware Unlearning. To further reshape learning dynamics by directly addressing sensitive information, we define a second loss term called Privacy-Aware Unlearning. This term directly adjusts token-level gradient contributions using their fused sensitivity scores. The formulation is:

$$\mathcal{L}_{\text{unlearn}} = \frac{1}{M} \sum_{i=1}^{M} (\text{Score}(t_i) - \theta) \cdot \ell(t_i) \cdot \mathbb{I}(\text{Score}(t_i) > \theta), \quad (13)$$

where $\ell(t_i)$ is the cross-entropy loss of token t_i, θ is a predefined sensitivity threshold, and M is the number of tokens in the sequence. $\mathbb{I}(\cdot)$ is the indicator function, meaning this term contributes only for tokens whose sensitivity $\text{Score}(t_i)$ exceeds the threshold θ. This formulation specifically targets high-sensitivity tokens: by multiplying their loss contribution by $(\text{Score}(t_i) - \theta)$, we encourage the model to unlearn or softly suppress the reinforcement of information associated with these tokens.

The overall training objective combines task-specific prediction, memory regularization, and unlearning:

$$\mathcal{L}_{\text{total}} = \mathcal{L}_{\text{task}} + \mathcal{L}_{\text{reg}} + \lambda_{\text{unlearn}} \cdot \mathcal{L}_{\text{unlearn}}, \quad (14)$$

where $\mathcal{L}_{\text{task}}$ is the standard task-specific loss (e.g., cross-entropy loss for classification or language modeling), and λ_{unlearn} is a hyperparameter controlling the strength of the privacy-aware unlearning component.

This unified objective enables continual learning that dynamically aligns parameter retention and forgetting with token-level privacy sensitivity, ensuring both task stability and robust privacy guarantees.

Together, TDP and PMS form a **Dual-Layer Defense**. While PMS triggers parameter-level unlearn-

ing for tokens above the threshold θ, TDP protects "near-threshold" tokens. Since TDP allocates noise continuously, tokens below θ with non-zero sensitivity still receive proportional perturbation. This "soft suppression" ensures robust privacy at the input level even without explicit memory sculpting.

4 Experiments

4.1 Experiments Setups

Datasets. To evaluate our privacy-enhanced continual learning framework, we construct a multi-task dataset covering six distinct domains with varying privacy sensitivities. In the absence of any public benchmark for privacy-preserving continual learning, we select six tasks: FOMC (Shah et al., 2023), Yelp (Asghar, 2016), AGNews (Zhang et al., 2015), Amazon[1], Mentill[2], and Yahoo[3], and sample 3,000 examples for each task. All tasks are formulated as text classification. These datasets are selected because they originate from real-world user reviews and Q&A platforms, naturally containing unstructured and potentially sensitive personal information, making them ideal benchmarks for evaluating privacy-preserving continual learning.

Evaluation Metrics. Evaluation Metrics. We employ three widely used continual learning metrics: Average Accuracy (Avg), Last Accuracy (Last), and Backward Transfer (BWT) (Chaudhry et al., 2018; Lopez-Paz and Ranzato, 2017). Avg measures the mean accuracy across all tasks at each training step, Last reflects the final average accuracy after sequentially learning all tasks, and BWT quantifies the effect of learning new tasks on previously acquired knowledge (i.e., catastrophic forgetting). Formal mathematical definitions are detailed in Appendix A.

Baselines. To evaluate the effectiveness of our approach, we compare against several representative baselines. For continual learning, we consider ER (Rolnick et al., 2019), EWC (Kirkpatrick et al., 2017), GEM (Lopez-Paz and Ranzato, 2017), and O-LoRA (Wang et al., 2023), covering replay-based, regularization-based, and adapter-based strategies. For privacy protection, we include DPSGD (Abadi et al., 2016) and a frozen embedding with additive noise (FN) as baselines. Additionally, we report two control setups: Multi-

---
[1] https://www.kaggle.com/datasets/kritanjalijain/amazon-reviews
[2] https://huggingface.co/datasets/mavinsao/reddit-mental-illnes
[3] https://www.kaggle.com/datasets/bhavikardeshna/yahoo-email-classification

task training (MTL) is always regarded as the upper bound, which simultaneously learns all tasks (MTL), and Sequential Finetuning (SeqFT), which sequentially learns each task. Furthermore, to provide a comprehensive comparison in fine-grained privacy, we also include PMixED (Flemings et al., 2024), a recent token-level privacy baseline.

4.2 Main Results

Table 1 presents the evaluation of various CL methods under differential privacy constraints across six tasks, measured by Backward Transfer (BWT), Last accuracy, and Average accuracy (Avg). The results yield three key insights:

First, PeCL achieves the best overall performance across all three metrics, demonstrating the efficacy of combining token-level dynamic privacy with memory sculpting. Notably, it surpasses the recent token-level DP baseline, PMixED, by achieving a superior balance between privacy protection and knowledge retention. As expected, SeqFT variants exhibit the most severe catastrophic forgetting, underscoring the necessity of dedicated CL mechanisms under privacy constraints.

Second, PeCL consistently outperforms baselines like ER+DPSGD and ER+FN, highlighting the clear advantage of our adaptive noise allocation over static noise injection strategies. Furthermore, traditional regularization-based methods (e.g., EWC and GEM) and adapter-based approaches (like OLora) show limited effectiveness. This indicates that fixed parameter constraints or standard adapters struggle to stabilize learning under the disruptive effects of rigorous privacy noise.

Third, PeCL surprisingly surpasses the multitask learning baseline (MTL+DPSGD) in both Last and Avg accuracy. Achieving this in a realistic, task-incremental setting rather than a centralized joint-training scenario strongly underscores the robustness and practical applicability of our framework in privacy-sensitive continual learning environments.

4.3 Ablation Studies

To assess the effectiveness of each component in our framework, we conduct an ablation study as summarized in Table 2. We focus on two major modules: Token-level Differential Privacy (TDP) and Privacy-Guided Memory Sculpting (PMS), as well as its two internal mechanisms: Memory Regularization (MemReg) and Privacy-Aware Unlearning. TDP serves as the foundation of our privacy design: when replaced with coarser sentence-level pri-

Method	Task1	Task2	Task3	Task4	Task5	Task6	BWT	Last	Avg
PeCL (Ours)	0.436	**0.521**	**0.869**	**0.444**	**0.456**	0.714	**-0.093**	**0.573**	**0.535**
-w/o TDP	**0.445**	0.313	0.422	0.297	0.149	0.146	-0.155	0.295	0.473
-w/o PMS	0.294	0.224	0.349	0.219	0.262	0.710	-0.430	0.312	0.465
-w/o MemReg	0.385	0.387	0.730	0.371	0.434	0.725	-0.212	0.505	0.496
-w/o Unlearning	0.407	0.499	0.857	0.421	0.350	0.727	-0.133	0.544	0.524

Table 2: The results of ablation studies.

Figure 2: Results of different task order.

vacy (w/o TDP), both performance and forgetting degrade significantly, indicating that fine-grained sensitivity modulation is essential for balancing utility and protection. PMS further enhances long-term performance, as removing it entirely (w/o PMS) leads to the largest drop in average accuracy and a sharp increase in forgetting. Within PMS, Memory Regularization and Unlearning target complementary aspects: disabling MemReg results in weakened task stability, while removing the unlearning component slightly reduces accuracy but notably increases forgetting. In summary, TDP enables precise privacy modulation, MemReg stabilizes knowledge across tasks, and Unlearning effectively removes sensitive traces, together forming a cohesive and robust privacy-preserving continual learning framework.

4.4 Further Analysis

In this section, we conduct extensive sensitivity analyses to gain deeper insights into the proposed method. We primarily focus on the Influence of Task Order to evaluate the model's robustness against varying task arrival sequences, as well as the Impact of Hyperparameter α to understand the balance between uncertainty and context in privacy sensitivity scoring. For additional analyses, including the Impact of Hyperparameter λ_{unlearn} and Impact of Hyperparameter α and θ, please refer to the Appendix B.

Influence of Task Order. We consider three task orders: a natural progression (order1: $1 \rightarrow 2 \rightarrow ... \rightarrow 6$), the reversed sequence (order2: $6 \rightarrow 5 \rightarrow ... \rightarrow 1$), and a deliberately shuffled permutation (order3: $4 \rightarrow 5 \rightarrow 1 \rightarrow 3 \rightarrow 6 \rightarrow 2$). Figure 2 illustrates how different task arrival sequences affect model performance. Across all task orders, our PeCL consistently outperforms baselines such as ER+DPSGD and EWC+DPSGD in terms of both accuracy and forgetting. Notably, PeCL exhibits strong stability in order1 and order2, maintaining high final accuracy and low forgetting. While there is a slight performance drop in order3, PeCL still remains competitive and significantly more robust than other methods, whose results vary more dramatically across different orders. These results demonstrate that PeCL can adapt well to varying task sequences.

5 Conclusions and Future Work

In this paper, we present PeCL, a novel privacy-enhanced continual learning framework designed to address the critical challenges of data privacy and catastrophic forgetting in sequential learning scenarios, particularly with LLMs. Our approach tackles this challenge through two key innovations: a token-level dynamic Differential Privacy strategy and a privacy-guided memory sculpting module. Extensive experiments demonstrate that PeCL achieves superior performance compared to state-of-the-art baselines, delivering higher average accuracy, better retention of past knowledge, and stronger privacy guarantees. Ablation studies confirm the necessity of the main components, while further analysis shows the robustness of our method across varying task orders and hyperparameter settings. The results highlight the importance of integrating sensitivity-aware, adaptive privacy mechanisms into continual learning systems.

Limitations

While PeCL establishes a strong foundation, several challenges remain. First, the privacy budget ϵ accumulates in long-context scenarios, potentially exceeding strict bounds. Future work will explore Rényi Differential Privacy (RDP) to establish tighter boundaries for extended sequences. Second, beyond theoretical DP guarantees, empirical assessments against membership inference (MIA) and data extraction attacks are needed to validate practical robustness. Finally, transitioning our heuristic-based sensitivity scoring to formal principles, such as Fisher Information or the Information Bottleneck, would further enhance theoretical rigor.

Ethical considerations

The six datasets used in the experiments including FOMC, Yelp, AGNews, Amazon, Mentill and Yahoo are widely used datasets. Our research strictly adheres to the Code of Ethics, particularly regarding data privacy, transparency, and responsible computing practices. And there is no participant involved.

References

Martin Abadi, Andy Chu, Ian Goodfellow, H Brendan McMahan, Ilya Mironov, Kunal Talwar, and Li Zhang. 2016. Deep learning with differential privacy. In *Proceedings of the 2016 ACM SIGSAC conference on computer and communications security*, pages 308–318.

Nabiha Asghar. 2016. Yelp dataset challenge: Review rating prediction. *arXiv preprint arXiv:1605.05362*.

Lucas Bourtoule, Varun Chandrasekaran, Christopher A Choquette-Choo, Hengrui Jia, Adelin Travers, Baiwu Zhang, David Lie, and Nicolas Papernot. 2021. Machine unlearning. In *2021 IEEE symposium on security and privacy (SP)*, pages 141–159. IEEE.

Nicholas Carlini, Florian Tramer, Eric Wallace, Matthew Jagielski, Ariel Herbert-Voss, Katherine Lee, Adam Roberts, Tom Brown, Dawn Song, Ulfar Erlingsson, and 1 others. 2021. Extracting training data from large language models. In *30th USENIX security symposium (USENIX Security 21)*, pages 2633–2650.

Zachary Charles, Arun Ganesh, Ryan McKenna, H Brendan McMahan, Nicole Mitchell, Krishna Pillutla, and Keith Rush. 2024. Fine-tuning large language models with user-level differential privacy. *arXiv preprint arXiv:2407.07737*.

Arslan Chaudhry, Puneet K Dokania, Thalaiyasingam Ajanthan, and Philip HS Torr. 2018. Riemannian walk for incremental learning: Understanding forgetting and intransigence. In *Proceedings of the European conference on computer vision (ECCV)*, pages 532–547.

Rishav Chourasia and Neil Shah. 2023. Forget unlearning: Towards true data-deletion in machine learning. In *International conference on machine learning*, pages 6028–6073. PMLR.

Pradnya Desai, Phung Lai, NhatHai Phan, and My T Thai. 2021. Continual learning with differential privacy. In *International Conference on Neural Information Processing*, pages 334–343. Springer.

Cynthia Dwork. 2006. Differential privacy. In *International colloquium on automata, languages, and programming*, pages 1–12. Springer.

Vitaly Feldman. 2020. Does learning require memorization? a short tale about a long tail. In *Proceedings of the 52nd annual ACM SIGACT symposium on theory of computing*, pages 954–959.

James Flemings, Meisam Razaviyayn, and Murali Annavaram. 2024. Differentially private next-token prediction of large language models. *arXiv preprint arXiv:2403.15638*.

Alex Gomez-Villa, Bartlomiej Twardowski, Lu Yu, Andrew D Bagdanov, and Joost Van de Weijer. 2022. Continually learning self-supervised representations with projected functional regularization. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 3867–3877.

Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, Weizhu Chen, and 1 others. 2022. Lora: Low-rank adaptation of large language models. *ICLR*, 1(2):3.

Tianyu Huai, Jie Zhou, Xingjiao Wu, Qin Chen, Qingchun Bai, Ze Zhou, and Liang He. 2025. Clmoe: Enhancing multimodal large language model with dual momentum mixture-of-experts for continual visual question answering. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pages 19608–19617.

Qingfu Huang, Zhichao Lian, and Qianmu Li. 2022. Attention based adversarial attacks with low perturbations. In *2022 IEEE International Conference on Multimedia and Expo (ICME)*, pages 1–6. IEEE.

Min Jae Jung and JooHee Kim. 2024. Pmoe: Progressive mixture of experts with asymmetric transformer for continual learning. *arXiv preprint arXiv:2407.21571*.

James Kirkpatrick, Razvan Pascanu, Neil Rabinowitz, Joel Veness, Guillaume Desjardins, Andrei A Rusu, Kieran Milan, John Quan, Tiago Ramalho, Agnieszka Grabska-Barwinska, and 1 others. 2017. Overcoming catastrophic forgetting in neural networks. *Proceedings of the national academy of sciences*, 114(13):3521–3526.

Martin Kuo, Jingyang Zhang, Jianyi Zhang, Minxue Tang, Louis DiValentin, Aolin Ding, Jingwei Sun, William Chen, Amin Hass, Tianlong Chen, and 1 others. 2025. Proactive privacy amnesia for large language models: Safeguarding pii with negligible impact on model utility. *arXiv preprint arXiv:2502.17591*.

Sijia Liu, Yuanshun Yao, Jinghan Jia, Stephen Casper, Nathalie Baracaldo, Peter Hase, Yuguang Yao, Chris Yuhao Liu, Xiaojun Xu, Hang Li, and 1 others. 2025. Rethinking machine unlearning for large language models. *Nature Machine Intelligence*, pages 1–14.

David Lopez-Paz and Marc'Aurelio Ranzato. 2017. Gradient episodic memory for continual learning. *Advances in neural information processing systems*, 30.

Peihua Mai, Ran Yan, Zhe Huang, Youjia Yang, and Yan Pang. 2023. Split-and-denoise: Protect large language model inference with local differential privacy. *arXiv preprint arXiv:2310.09130*.

Stephen Meisenbacher, Maulik Chevli, Juraj Vladika, and Florian Matthes. 2024. Dp-mlm: Differentially private text rewriting using masked language models. *arXiv preprint arXiv:2407.00637*.

Wenlong Meng, Zhenyuan Guo, Lenan Wu, Chen Gong, Wenyan Liu, Weixian Li, Chengkun Wei, and Wenzhi Chen. 2025. Rr: Unveiling llm training privacy through recollection and ranking. *arXiv preprint arXiv:2502.12658*.

Hajra Murtaza, Musharif Ahmed, Naurin Farooq Khan, Ghulam Murtaza, Saad Zafar, and Ambreen Bano. 2023. Synthetic data generation: State of the art in health care domain. *Computer Science Review*, 48:100546.

Ozan Özdenizci, Elmar Rueckert, and Robert Legenstein. 2025. Privacy-aware lifelong learning. *arXiv preprint arXiv:2505.10941*.

David Rolnick, Arun Ahuja, Jonathan Schwarz, Timothy Lillicrap, and Gregory Wayne. 2019. Experience replay for continual learning. *Advances in neural information processing systems*, 32.

Gerard Salton and Christopher Buckley. 1988. Term-weighting approaches in automatic text retrieval. *Information processing & management*, 24(5):513–523.

Agam Shah, Suvan Paturi, and Sudheer Chava. 2023. Trillion dollar words: A new financial dataset, task & market analysis. *arXiv preprint arXiv:2305.07972*.

Haizhou Shi, Zihao Xu, Hengyi Wang, Weiyi Qin, Wenyuan Wang, Yibin Wang, Zifeng Wang, Sayna Ebrahimi, and Hao Wang. 2024. Continual learning of large language models: A comprehensive survey. *ACM Computing Surveys*.

Mingjie Sun, Zhuang Liu, Anna Bair, and J Zico Kolter. 2023. A simple and effective pruning approach for large language models. *arXiv preprint arXiv:2306.11695*.

Shokichi Takakura, Seng Pei Liew, and Satoshi Hasegawa. 2025. Accelerating differentially private federated learning via adaptive extrapolation. *arXiv preprint arXiv:2504.09850*.

Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, and 1 others. 2023. Llama: Open and efficient foundation language models. *arXiv preprint arXiv:2302.13971*.

Weiqi Wang, Zhiyi Tian, Chenhan Zhang, and Shui Yu. 2024. Machine unlearning: A comprehensive survey. *arXiv preprint arXiv:2405.07406*.

Xiao Wang, Tianze Chen, Qiming Ge, Han Xia, Rong Bao, Rui Zheng, Qi Zhang, Tao Gui, and Xuanjing Huang. 2023. Orthogonal subspace learning for language model continual learning. *arXiv preprint arXiv:2310.14152*.

Prateek Yadav, Derek Tam, Leshem Choshen, Colin A Raffel, and Mohit Bansal. 2023. Ties-merging: Resolving interference when merging models. *Advances in Neural Information Processing Systems*, 36:7093–7115.

Yutao Yang, Jie Zhou, Xuanwen Ding, Tianyu Huai, Shunyu Liu, Qin Chen, Yuan Xie, and Liang He. 2025. Recent advances of foundation language models-based continual learning: A survey. *ACM Computing Surveys*, 57(5):1–38.

Da Yu, Saurabh Naik, Arturs Backurs, Sivakanth Gopi, Huseyin A Inan, Gautam Kamath, Janardhan Kulkarni, Yin Tat Lee, Andre Manoel, Lukas Wutschitz, and 1 others. 2021. Differentially private fine-tuning of language models. *arXiv preprint arXiv:2110.06500*.

Xiang Zhang, Junbo Zhao, and Yann LeCun. 2015. Character-level convolutional networks for text classification. *Advances in neural information processing systems*, 28.

A Evaluation Metrics

To rigorously evaluate the performance of our privacy-enhanced continual learning framework, we employ three standard metrics: Backward Transfer (BWT), Last Accuracy (Last), and Average Accuracy (Avg). Let N denote the total number of tasks, and $R_{k,i}$ denote the test accuracy on task i after the model has been sequentially trained on tasks 1 through k.

Backward Transfer (BWT). BWT quantifies the effect of learning new tasks on previously acquired knowledge. A negative BWT indicates catastrophic forgetting, while a positive BWT indicates forward knowledge transfer. It is defined as:

$$\text{BWT} = \frac{1}{N-1} \sum_{i=1}^{N-1} \left(R_{N,i} - R_{i,i} \right) \qquad (15)$$

where $R_{N,i}$ is the accuracy on task i after training on all N tasks, and $R_{i,i}$ is the accuracy on task i immediately after it was first learned.

Last Accuracy (Last). Last accuracy measures the model's final average performance across all N tasks after the entire sequential training process is complete:

$$\text{Last} = \frac{1}{N} \sum_{i=1}^{N} R_{N,i} \qquad (16)$$

Average Accuracy (Avg). Avg measures the mean accuracy over all evaluated tasks at every training step, providing a comprehensive view of the model's performance trajectory throughout the continual learning process:

$$\text{Avg} = \frac{1}{N} \sum_{k=1}^{N} \left(\frac{1}{k} \sum_{i=1}^{k} R_{k,i} \right) \qquad (17)$$

B Analysis of Hyperparameter

Impact of Hyperparameter α. We investigate the effect of the balancing coefficient $\alpha \in [0,1]$, which controls the trade-off between model uncertainty $\text{Score}_1(t_i)$ and contextual informativeness $\text{Score}_2(t_i)$ in the privacy sensitivity score. As shown in Figure 3 and Figure 5a, both the Avg performance and BWT reach their optimal values when $\alpha = 0.5$, suggesting that a balanced combination of the two factors leads to the best performance. Increasing α beyond 0.5 (favoring uncertainty) results in degraded BWT, indicating more forgetting. Conversely, lower α values (favoring context) also hurt Avg, likely due to insufficient attention to uncertain tokens. These results validate the effectiveness of integrating both uncertainty and contextual features, with $\alpha = 0.5$ serving as a robust choice.

Impact of Hyperparameter λ_{unlearn}. We study the influence of the hyperparameter λ_{unlearn}, which controls the strength of the unlearning regularization term. As shown in Figure 4, setting $\lambda_{\text{unlearn}} = 1$ achieves the best trade-off between stability and performance, yielding the highest average score (0.535) and the lowest forgetting as measured by BWT (-0.093). When $\lambda_{\text{unlearn}} = 0$, i.e., no unlearning applied, BWT degrades to -0.133, showing more severe forgetting. As λ increases beyond 1, the Avg score drops (e.g., 0.454 at $\lambda = 5$), likely due to over-regularization that hurts forward transfer. These results suggest that a moderate unlearning strength is beneficial for mitigating forgetting without compromising overall task performance.

Impact of Hyperparameter θ. We investigate the impact of the sensitivity threshold θ in the Privacy-Aware Unlearning loss, which determines which tokens are softly suppressed during training. As shown in Figure 5b, $\theta = 0.6$ achieves the best trade-off, yielding the highest Avg (0.535) and lowest forgetting (BWT $= -0.093$). A lower threshold (e.g., $\theta = 0.3$) suppresses too many tokens, hurting performance (Avg $= 0.514$, BWT $= -0.108$), while a higher one (e.g., $\theta = 0.9$) retains overly sensitive tokens (Avg $= 0.523$, BWT $= -0.105$). These results suggest that a moderate θ best balances utility and privacy at the token level.

C Per-Task Performance of Task Order

Table 3 lists the full classification accuracy of each task for the continual learning methods that performed better in different orders. The six columns in the middle correspond to tasks 1-6, and the three columns on the far right provide BWT, Last, and Avg.

D Per-Task Performance of Hyperparameter α.

Table 4 lists the complete classification accuracy of our method on each task under different hyperparameters α. The middle six columns correspond to tasks 1-6, and the rightmost three columns provide BWT, Last, and Avg.

Figure 3: The performance of α.

Figure 4: The Impact of λ_{unlearn}.

E Per-Task Performance of Hyperparameter λ_{unlearn}.

Table 5 lists the complete classification accuracy of our method on each task under different hyperparameters λ_{unlearn}. The middle six columns correspond to tasks 1-6, and the rightmost three columns provide BWT, Last, and Avg.

F Baseline Details.

To evaluate the effectiveness of our approach, we compare it against a diverse set of representative baselines spanning different methodological paradigms.

For continual learning, we consider four established methods:

- **Experience Replay (ER)** (Rolnick et al., 2019), a replay-based approach that stores past examples in a buffer for rehearsal. When learning a new task, ER mixes old and new data for joint training, allowing the model to revisit learned knowledge to combat forgetting.

Figure 5: The Impact of Hyperparameter α and θ.

- **Elastic Weight Consolidation (EWC)** (Kirkpatrick et al., 2017), a regularization-based method that penalizes changes to parameters important for previous tasks. EWC identifies these key parameters using the Fisher Information Matrix and adds a penalty term to the loss function to constrain their drift while learning new tasks.

- **Gradient Episodic Memory (GEM)** (Lopez-Paz and Ranzato, 2017), which constrains gradient updates to avoid increasing the loss on previously seen tasks. Specifically, if a gradient update for the current task conflicts with the gradient directions from stored past examples, GEM projects it to a non-conflicting direction.

- **O-LoRA** (Wang et al., 2023), an adapter-based strategy that leverages orthogonal low-rank adaptation modules to mitigate interference across tasks. It assigns an independent LoRA module to each task and enforces an orthogonality constraint, ensuring that parameter updates for different tasks occur in their own subspaces to achieve knowledge isolation.

For privacy-preserving learning, we include two baselines:

- **Differentially Private Stochastic Gradient Descent (DPSGD)** (Abadi et al., 2016), which injects calibrated noise into gradients to enforce differential privacy. Before each update, this method first clips the L2 norm of per-sample gradients to bound their sensitivity and then adds Gaussian noise to the aggregated gradient, providing rigorous privacy guarantees for model training.

- **Frozen Embedding with Additive Noise (FN)** (Yu et al., 2021), a simple baseline that freezes the embedding layer and adds noise directly to its outputs. This strategy reduces the computational overhead of privacy reserving by fixing the large embedding layer, while the injected noise serves to perturb the input representations, offering an efficient privacy-preserving mechanism for the subsequent model layers.

In addition, we report results on two control setups to provide context for performance bounds:

- **Multitask Learning (MTL)**, which trains on all tasks simultaneously and serves as an upper-bound reference.

Task Order	Method	task1	task2	task3	task4	task5	task6	BWT	Last	Avg
	ER+DPSGD	0.438	0.463	0.536	0.443	0.152	0.573	-0.136	0.434	0.486
	EWC+DPSGD	0.444	0.284	0.471	0.302	0.160	0.481	-0.137	0.358	0.393
order1	ER+FN	0.456	0.420	0.673	0.371	0.029	0.309	-0.121	0.376	0.492
	EWC+FN	0.260	0.231	0.208	0.236	0.261	0.183	-0.248	0.230	0.397
	PeCL	0.436	0.521	0.869	0.444	0.456	0.714	-0.093	0.573	0.535
	ER+DPSGD	0.155	0.139	0.450	0.575	0.473	0.476	-0.070	0.378	0.291
	EWC+DPSGD	0.142	0.117	0.414	0.312	0.419	0.480	-0.142	0.314	0.256
order2	ER+FN	0.148	0.364	0.470	0.591	0.468	0.526	-0.071	0.428	0.319
	EWC+FN	0.104	0.123	0.347	0.502	0.322	0.480	-0.186	0.313	0.282
	PeCL	0.276	0.368	0.541	0.798	0.618	0.567	-0.057	0.528	0.446
	ER+DPSGD	0.174	0.493	0.450	0.657	0.283	0.546	-0.039	0.434	0.336
	EWC+DPSGD	0.089	0.462	0.262	0.496	0.302	0.516	-0.159	0.355	0.318
order3	ER+FN	0.184	0.493	0.558	0.601	0.147	0.521	-0.005	0.417	0.346
	EWC+FN	0.126	0.528	0.427	0.426	0.179	0.590	-0.158	0.379	0.341
	PeCL	0.233	0.555	0.300	0.522	0.359	0.598	-0.073	0.428	0.357

Table 3: Per-Task performance of task order.

	task1	task2	task3	task4	task5	task6	BWT	Last	Avg
α=0.2	0.395	0.485	0.865	0.423	0.330	0.705	-0.130	0.534	0.518
α=0.3	0.419	0.513	0.858	0.467	0.349	0.708	-0.104	0.552	0.523
α=0.5	0.436	0.521	0.869	0.444	0.456	0.714	-0.093	0.573	0.535
α=0.7	0.409	0.483	0.866	0.435	0.297	0.699	-0.121	0.532	0.510
α=0.8	0.401	0.427	0.874	0.378	0.253	0.699	-0.148	0.505	0.489

Table 4: Per-Task Performance of Hyperparameter α.

- **Sequential Finetuning (SeqFT)**, which learns tasks one after another sequentially without any mechanism to mitigate catastrophic forgetting.

G Implementation Details.

In our experiments, we train our models on A800-80GB GPUs. All methods employ the LLaMA-2-7B-hf (Touvron et al., 2023) for text-based tasks. For all baseline methods, we follow the implementation details and configurations from the original papers to ensure faithful reproduction. During training, we train each task for three epochs with a batch size of 32. For the hyperparameters of our approach, we set $\alpha = 0.5$, $\epsilon_{upper} = \lambda_{max} = 10$, $\epsilon_{lower} = \lambda_{min} = 1$, $\delta = 1.0e - 6$, $\lambda_{unlearn} = 1$, and $\theta = 0.6$. We use AdamW as the optimizer with a learning rate of $5.0e - 4$ and employ a cosine learning rate scheduler.

H Theoretical Proof of Privacy Guarantee

We present a formal analysis showing that our Token-level Dynamic Differential Privacy (TDP) mechanism, as defined in Section 3.2, satisfies (ϵ_i, δ)-local differential privacy for each token t_i.

To rigorously establish this guarantee, we proceed in a structured manner. First, we recall the standard definition of (ϵ, δ)-local differential privacy, which serves as our formal privacy notion. Next, we bound the ℓ_2 sensitivity of the clipped token embedding—a critical prerequisite for applying the Gaussian mechanism. With this sensitivity bound in hand, we invoke the well-known privacy guarantee of the Gaussian mechanism to derive the required noise scale σ_i that ensures (ϵ_i, δ)-LDP for each token. Finally, we connect this analysis back to our dynamic sensitivity scoring framework by showing that the sensitivity score $\text{Score}(t_i)$ is properly bounded in $[0, 1]$, which in turn guarantees that the derived privacy budget ϵ_i remains within a valid and interpretable range. Together, these components form a complete chain of reasoning that validates the per-token privacy guarantee of our TDP mechanism.

Definition 1 (Local Differential Privacy).
A randomized mechanism $\mathcal{M}$ satisfies (ϵ, δ)-local differential privacy if for any two inputs x and x' differing in one entry (e.g., one token), and for any measurable set of outputs $\mathcal{S}$, it holds that:

$$\Pr[\mathcal{M}(x) \in \mathcal{S}] \leq e^{\epsilon} \cdot \Pr[\mathcal{M}(x') \in \mathcal{S}] + \delta.$$

Lemma 1 (Sensitivity of Clipped Embedding).
Let $e_i, e_i' \in \mathbb{R}^d$ be two embeddings corresponding to tokens t_i and t_i' respectively. If both are clipped

λ_{unlearn}	task1	task2	task3	task4	task5	task6	BWT	Last	Avg
0	0.407	0.499	0.857	0.421	0.350	0.727	-0.133	0.544	0.524
1	0.436	0.521	0.869	0.444	0.456	0.714	-0.093	0.573	0.535
3	0.395	0.489	0.864	0.431	0.305	0.718	-0.127	0.534	0.511
5	0.315	0.429	0.846	0.396	0.314	0.706	-0.101	0.501	0.454
7	0.393	0.482	0.850	0.439	0.413	0.718	-0.093	0.549	0.513
10	0.440	0.471	0.850	0.423	0.333	0.715	-0.059	0.539	0.476

Table 5: Per-Task Performance of Hyperparameter λ_{unlearn}.

such that $\|e_i\|_2 \leq C$ and $\|e'_i\|_2 \leq C$, then the ℓ_2 sensitivity of the mechanism is bounded as:

$$\Delta = \|clip(e_i, C) - clip(e'_i, C)\|_2 \leq 2C.$$

Proposition 1 (Per-token Differential Privacy Guarantee)**.**
Let $\tilde{e}_i = \mathcal{M}(e_i)$ denote the perturbed embedding of token t_i. Then $\mathcal{M}$ satisfies (ϵ_i, δ)-differential privacy for each token t_i.

Proof. This proposition follows directly from the Gaussian Mechanism guarantee. The mechanism adds noise $\mathcal{N}(0, \sigma_i^2 I)$ calibrated to a sensitivity of $\Delta = 2C$ (from Lemma 1). To satisfy (ϵ_i, δ)-DP, the noise standard deviation must meet the condition:

$$\sigma_i \geq \frac{2C \cdot \sqrt{2 \log(1.25/\delta)}}{\epsilon_i}.$$

Our setting for σ_i, as defined in Equation 5 (Section 3.1), matches this bound precisely.

Lemma 2 (Range of Sensitivity Score)**.**
The fused sensitivity score $Score(t_i)$ defined as:

$$Score(t_i) = 1 - \exp\Big(-\big(\alpha \cdot Score_1(t_i) + (1 - \alpha) \cdot Score_2(t_i)\big)\Big)$$

which is bounded in $[0, 1]$ for any $\alpha \in [0, 1]$, provided that $Score_1(t_i) \geq 0$ and $Score_2(t_i) \geq 0$.

Proof. Since both $Score_1$ and $Score_2$ are non-negative, their convex combination is also non-negative. Hence,

$$Score(t_i) = 1 - \exp(-z) \in [0, 1), \quad \text{where } z \geq 0.$$

Thus, the score lies in $[0, 1)$, which we clip to 1 for completeness.

Corollary 1 (Dynamic Privacy Budget Range)**.**
Using $Score(t_i) \in [0, 1]$, the dynamically assigned privacy budget

$$\epsilon_i = \epsilon_{lower} + (\epsilon_{upper} - \epsilon_{lower})(1 - Score(t_i))^2$$

is always in the range $[\epsilon_{lower}, \epsilon_{upper}]$.

Token	Score(t_i)	Budget (ϵ_i)	Noise (σ_i)	Token Type
Crystal	0.52	3.07	1.73	PII (Name)
Robinson	0.53	3.03	1.75	PII (Name)
scored	0.42	4.03	1.32	General verb
16	0.52	3.07	1.73	Number / Detail
points	0.14	7.66	0.69	General noun
to	0.00	10.0	0.53	Stop word
rally	0.45	3.72	1.42	General verb
the	0.00	10.0	0.53	Stop word
New	0.46	3.62	1.46	Specific Entity
York	0.14	7.66	0.69	Specific Entity
Liberty	0.62	2.31	2.29	Specific Team

Table 6: Case study of token-wise sensitivity, privacy budget, and noise allocation by the TDP mechanism.

Remark 1 (Privacy Composition Across Sequence)**.**
If needed, a user-level privacy budget for a token sequence $\{t_1, \ldots, t_L\}$ can be computed via advanced composition. For example, the total privacy budget ϵ_{total} for L tokens under sequential composition is:

$$\epsilon_{total} \approx \sum_{i=1}^{L} \epsilon_i + \sqrt{2L \log(1/\delta')} \cdot \max_i \epsilon_i,$$

with final failure probability $\delta + \delta'$. Alternatively, one may use RDP accounting for tighter bounds.

I Qualitative Analysis and Case Study

To intuitively demonstrate how the TDP mechanism discriminates between sensitive and non-sensitive content, we conduct a word-by-word sensitivity analysis on a sample sentence containing Personally Identifiable Information (PII) and specific entities. The complete statistical breakdown is provided in Table 6.

The analysis reveals that functional stopwords (e.g., "to" and "the") receive a baseline sensitivity score of 0, maximizing their privacy budget ($\epsilon_i = 10$) and minimizing noise injection to preserve syntactic structure. Conversely, sensitive entities such as names ("Crystal", "Robinson") and specific organizations ("Liberty") trigger significant sensitivity spikes (scores between 0.52 and

0.62). This restricts their privacy budgets strictly below 3.1 and amplifies the injected Gaussian noise by over 3 to 4 times compared to stopwords. These results validate that our TDP module intelligently concentrates privacy protection precisely on the most vulnerable tokens while maintaining utility for general context.