Testing Low-Resource Language Support in LLMs Using Language Proficiency Exams: the Case of Luxembourgish

Abstract

Large Language Models (LLMs) have become an increasingly important tool in research and society at large. While LLMs are regularly used all over the world by experts and lay-people alike, they are predominantly developed with English-speaking users in mind, performing well in English and other wide-spread languages while less-resourced languages such as Luxembourgish are seen as a lower priority. This lack of attention is also reflected in the sparsity of available evaluation tools and datasets. In this study, we investigate the viability of language proficiency exams as such evaluation tools for the Luxembourgish language. We find that large models such as Claude and DeepSeek-R1 typically achieve high scores, while smaller models show weak performances. We also find that the performances in such language exams can be used to predict performances in other NLP tasks in Luxembourgish.

1 Introduction

Large Language Models (LLMs) have become increasingly ubiquitous in recent research, with new models being frequently released and updated. They have become similarly omnipresent in the everyday lives of private and professional users, with models being deployed in wide-ranging domains such as finance, medicine, and coding.

While LLMs are primarily catered towards speakers of widespread languages such as English, Spanish, and Chinese, low-resource languages are generally regarded as a lower priority. Indeed, many major LLMs such as the Llama family (Touvron et al., Touvron et al., 2023, Grattafiori et al., 2024) are trained nearly exclusively on English data, and even LLMs with a focus on non-English languages such as BLOOM (Le Scao et al., 2023) barely include low-resource languages. As a consequence, numerous mistakes can occur due to cross-lingual transfer between related languages. These mistakes include mistranslated words and partial code-switching, incorrect word order, misgendered nouns, and violation of language-exclusive rules such as the n-rule (Eifeler Regel) in the Luxembourgish language (Gilles, 2006).

As such, it is important to determine the capabilities of models to understand and generate texts in such languages, and to recognise when they can fail. The benefits of such research are two-fold as it allows (1) to find general weaknesses and pitfalls that can be addressed and mitigated in future LLMs; (2) to make recommendations on which LLM to use for a given scenario in a given low-resource language. The latter is especially important in use cases where an LLM would have to handle sensitive data such as financial or medical information that is not allowed to leave a financial or medical institution due to internal policies and data privacy laws such as the Luxembourgish Data Protection Law (Grand-Duché de Luxembourg, 2018) or the General Data Protection Regulation (European Union, 2016). In such cases, data must be processed using locally deployed models that do not access the internet.

In this study, we aim to investigate the capabilities of LLMs for Luxembourgish, a low-resource language spoken by nearly 600,000 people worldwide[1], but predominantly in Luxembourg. We want to determine those capabilities from two angles, (a) how well LLMs perform in linguistic proficiency exams used in language institutions; (b) whether their performance in such exams can predict their performance in Natural Language Generation (NLG) tasks.

Specifically, we investigate 53 LLMs from a wide array of LLM families that we compare systematically. In addition, we ascertain in which cases LLMs fail and discover trends and common weaknesses using language exams. Finally, we aim to determine whether or not such exams are a useful tool to predict how well an LLM performs in

---

[1] https://cursus.edu/en/23040/luxembourgish-at-its-best

two tasks related to text summarisation. While this study focuses on the Luxembourgish language, we believe that our methodology can be generalised to other low-resource languages as well.

In summary, our contributions are as follows:

(a) A systematic comparison of 53 popular LLMs with regard to their linguistic proficiency in Luxembourgish.

(b) A quantitative and qualitative error analysis.

(c) An analysis on the usefulness of language exams as a tool for performance prediction on NLG tasks for Luxembourgish.

(d) An accessible and interactive public leaderboard for performance in Luxembourgish that we will extend as new LLMs are released.[2]

2 Related Work

2.1 Testing LLMs on Knowledge Exams

Many recent studies have used exams to test the knowledge of LLMs in a variety of domains. These domains predominantly cover the medical domain (Gotta et al., 2024, Stribling et al., 2024, Şahin et al., 2025, Abbas et al., 2024, Zong et al., 2024), but also computer science and programming (Dinh et al., 2024, Ellis et al., 2024, Li et al., 2025,VarastehNezhad et al., 2024), and the legal domain (Katz et al., 2024, Martínez, 2024). The general consensus is that LLMs perform well in these exams, often surpassing human candidates. However, most of these studies cover exams written in English, with only a few covering exams from Non-English speaking countries. Koto (2024) released IndoCareer, an exam benchmark covering various topics in Indonesian. They test it on a large number of LLMs with mixed results. Koto et al. (2023) also conducted a similar study using Indonesian school exams, where they found that most LLMs managed to only pass primary school exams. Jassem et al. (2025) presented LLMzSzŁ, a benchmark of Polish national exams covering various subjects. They test numerous LLMs in both English and Polish, showing that most LLMs perform better than randomly guessing. Locatelli et al. (2024) tested LLMs on a standardised entry exam for Brazilian universities covering different high

school subjects. They found that all LLMs performed very well on the exams, however, the number of tested LLMs was very low compared to our study. Dao et al. (2023) compared two LLMs using Vietnamese high school physics exams, showing that they perform worse than students.

2.2 Testing Linguistic capabilities of LLMs with Language exams

While there are numerous studies on the performance of LLMs on general NLP tasks, they are far less commonly focused specifically on language exams. Dar̀gis et al. (2024) systematically test numerous LLMs on standardised high school language tests in Latvian and manually evaluate their outputs with a human expert. Mayor-Rocher et al. (2024) tested several LLMs on TELEIA, a benchmark of exams for Spanish as a second language, as well as a Spanish test for foreign university students. Similarly, Mercorio et al. (2024) test numerous LLMs on the novel Italian language exam benchmark IN-VALSI, finding that large models consistently outperform smaller ones, and that the performance degrades on harder tests.

However, compared to related studies, we do not only assess LLM performance on language exams, but we also explore their usefulness to predict LLM performance in general NLP tasks. Furthermore, we use tests that follow the Common European Framework of Reference for Languages (CEFR) (Council of Europe, 2001) to evaluate LLMs.

3 Methodology

In this section, we give details on the methodology of this study and on our experiments, including the datasets we used, the LLMs we targeted, the metrics to compare the LLMs, the prompt design, and hyperparameters of the studied models. We also present and elaborate on the research questions we address in this paper.

We evaluate LLMs in two general disciplines: (1) language fluency and (2) language generation. The language fluency test consists of solving language exams that comprise sets of multiple-choice questions that relate to the general understanding of the language itself. In order to evaluate NLG, we use two tasks from the LuxGen benchmark (Plum et al., 2025), specifically the Headline Generation and Short Description tasks. These tasks both consist of processing texts and generating appropriate

---

[2]The leaderboard can be found at `https://applux-nnjdvksvbpgovzux7dtqts.streamlit.app/`

Figure 1: General testing pipeline.

Category	A1	A2	B1	B2	C1	C2	Total
Vocabulary	26	26	25	28	24	26	155
Grammar	26	26	26	34	29	23	164
Reading C.	26	26	25	26	26	26	155
Conversation C.	26	26	26	26	25	26	155
Total	104	104	102	114	104	101	629

Table 1: Statistics for language tests.

summaries, either in form of a short description or a news headline.

Testing is done in a zero-shot fashion for all tasks. Figure 1 shows the general testing pipeline. We first initiate the model with a unified prompt across every LLM (1). This initiation prompt consists of explaining the LLM's role and the general task it needs to solve, as well as specifying the format of the inputs and outputs. We then pre-process the test samples to make them uniform and compatible with our prompts (2), and give them to the LLM one at a time and in random order (3). For the language exams, we apply a post-processing step before comparing it to the ground truth (4). Post-processing generally consists of automatically correcting minor typos if the output is different from each of the provided answers (however, we judge outputs as being invalid if they deviate significantly or are ambiguous and could be attributed to multiple answers). Finally, (5) the LLM's performance will be measured using task-specific metrics (see Section 3.4).

3.1 Research Questions

In this study, we aim to answer the following three research questions:

RQ1: How well do LLMs perform in Luxembourgish language tests? To answer this question, we let LLMs solve language exams. We compare their performances in terms of number of correctly answered questions and determine a "winner".

RQ2: In which cases do LLMs fail to understand Luxembourgish? For this question, we categorise the exam questions to determine which categories are more difficult for LLMs to solve.

RQ3: Is there a correlation between performing well in a language exam and performing well in an NLG task? For the final question, we determine whether using language exams is an appropriate method to decide an LLM's language capabilities

and if the "winners" of the exams manage to perform well in generation tasks.

3.2 Datasets

3.2.1 Language Tests

In order to evaluate the fluency of each model, we use official language exams for Luxembourgish provided to us by the Institut National des Langues Luxembourg (INLL), a language institute in Luxembourg[3]. The difficulty level of each test follows CEFR guidelines, and thusly ranges from A1 (beginner) to C2 (proficient). The tests consist of mixtures of multiple-choice questions (MCQs) and open fill-in-the-blank type questions. The number of open questions differs depending on the CEFR level and are either related to grammar or vocabulary. Appendix A shows the exact number and distribution of open questions in the exams. The A1 and A2 levels do not contain any open questions, then, from B1 level, the higher the level the higher the number of open questions.

However, for our experiments, we unify the exams by transforming them into the same type of questions. Two Luxembourgish-speaking authors converted the open questions into MCQs as this allows to use a single standardised prompt across all tests, and simplifies the error analysis. The designated authors made sure that the difficulty of the converted questions is adequate for the level of the corresponding exams by writing distractors that matched the difficulty of the given exam, taking other MCQ questions from the same level as inspiration. Distractors for grammar-related questions include lexically similar misspellings of the correct answer, incorrectly conjugated verbs, and incorrect usage of prepositions. Vocabulary-related distractors generally include lexically similar words to the correct answer and near-synonyms to the correct answer that are wrong in the context of the given text. Questions fall into one of four broad categories: vocabulary, grammar, reading comprehension (RC), and listening comprehension. Note that the data for the latter category consists of transcripts rather than audio files. As such, we will refer to that category

---

[3]https://www.inll.lu/en/

as conversation comprehension (CC) in this paper. Table 6 shows further details for the tests. Further note that we do not have permission to give access to the actual dataset, but we can establish contact between interested researchers and the INLL.

3.2.2 News Headline Generation

The Headline Generation task, being part of Plum et al.'s (2025) LuxGen benchmark for assessing Luxembourgish language models, consists of generating an appropriate title for a given news article. The articles were sourced from the Luxembourgish news agency RTL. The original test set comprises 13 852 samples, but for our purposes, we use a subset of 300 randomly selected samples due to the vast number of LLMs we are investigating.

3.2.3 Short Description Generation

The second LuxGen task we consider involves generating short descriptions of Luxembourgish Wikipedia articles. The descriptions featured on Wikidata serve as a ground truth for this task. The original test set consists of 2094 articles, but similarly to the Headline Generation task, we limit ourselves to a random selection of 300 samples.

3.3 Models

We perform our experiments on a large number of LLMs from a wide array of language model families and model sizes. As models are not explicitly reported to understand Luxembourgish, the main criteria for including a given LLM in our selection is their reported ability to (a) understand a closely related Germanic language such as German or Dutch, or (b) understand a very large number of languages. Specifically, we include the following models: Alfred (Hallström et al., 2023), Aya-23 (Aryabumi et al., 2024), ChatGPT (OpenAI, 2023, OpenAI, 2024a, OpenAI, 2024b), Claude 3.5 Sonnet (Anthropic, 2024), Command-R (Cohere For AI, 2024), DeepSeek-R1 (DeepSeek-AI, 2025), EuroLLM (Martins et al., 2024), Gemini 2.0 Flash (Google, 2024), LeChat (Mistral AI, 2023a), Gemma 2 (Mesnard et al., 2024), GLM 4 (Zeng et al., 2024), Gemma 3 (Kamath et al., 2025), Llama 2 (Touvron et al., 2023), Llama 3, Llama 3.1, Llama 3.2 (Grattafiori et al., 2024), Mistral (Mistral AI, 2023b), Mixtral (Mistral AI, 2024), Phi 3, Phi 3.5 (Abdin et al., 2024a), Phi 4 (Abdin et al., 2024b), Qwen 2 (Yang et al., 2024a), QWQ (Yang et al., 2024b, Qwen, 2025), StableLM 2 (Bellagente et al., 2024), and WizardLM 2 (Xu et al., 2024).

Appendix B shows the full list of LLMs together with model sizes and reasons for inclusion.

Model sizes range from 0.5 billion parameters (Qwen2:0.5B) to 671 billion (DeepSeek-R1:671B). We divide them into 3 size categories: *small* ($\leq$ 15B parameters), *medium-sized* ($>$ 15B & $\leq$ 200B parameters), and *large* ($>$ 200B parameters). Note that although some model sizes are unknown to us as they are not communicated by the companies releasing them, they are estimated to be at least hundreds of billions of parameters. As such, we categorise the concerned LLMs as *large*.

3.4 Metrics

We measure the performance of LLMs using different metrics depending on the task. For the language exams, we use simple accuracy, i.e., the percentage of questions that an LLM answers correctly.

For language generation, we evaluate the outputs of LLMs in terms of grammar and spelling as well as similarity to the ground truth. We measure the performance on both of these tasks in an LLM-as-a-judge (LaaJ) fashion using an LLM that is not part of the ones we are investigating as the judging LLM. We choose the judging LLM based on its ability to solve the task at hand, which we manually verify. The metrics should meet the following requirements:

Grammar and Spelling metric

1. range between 0 and 1 where 0 is incomprehensible and 1 is perfect with neither spelling nor grammar mistakes.
2. punish non-Luxembourgish outputs, i.e., return 0 if the output is written in a different language.

Ground Truth Similarity metric

1. range between 0 and 1 where 1 is identical to the ground truth and decreases the less similar the output is to the ground truth and the more it deviates from the text on a semantic level.
2. punish descriptions that are deemed too long.

Considering that such LLM-generated metrics are essentially black boxes and non-deterministic due to the inherent random nature of LLMs, we repeat the generation a total of three times in order to reduce variation. In addition to the LaaJ metrics, we use two traditional metrics: METEOR (Banerjee and Lavie, 2005) and BERTScore (Zhang et al., 2019), using the Luxembourgish Luxem-BERT (Lothritz et al., 2022) as the embedding model for BERTScore.

Model	Size	A1	A2	B1	B2	C1	C2	Model	Size	A1	A2	B1	B2	C1	C2
Small Models (≤ 15B)								Medium-sized Models (> 15B& ≤ 200B)							
Qwen 2	0.5	26.9	22.1	23.3	22.8	22.1	15.8	Mistral-Small	22	51.9	46.2	31.1	39.5	38.5	25.7
Llama 3.2	1	26.0	19.2	28.2	21.1	19.2	12.9	Gemma 2	27	66.3	63.5	54.4	45.6	50.0	41.6
Gemma 3	1	45.2	36.5	38.8	40.4	25.0	33.7	Gemma 3	27	**71.2**	**72.1**	**62.1**	**60.5**	**60.6**	**44.6**
Qwen 2	1.5	32.7	27.9	25.2	31.6	21.2	23.8	QWQ	32	60.6	49.0	51.5	47.4	38.5	**44.6**
StableLM 2	1.6	22.1	14.4	21.4	16.7	15.4	16.8	Aya-23	35	43.3	37.5	39.8	36.0	33.7	34.7
EuroLLM	1.7	17.3	21.2	12.6	23.7	26.0	17.8	Command-R	35	51.0	38.5	33.0	42.1	35.6	37.6
Gemma 2	2	39.4	32.7	31.1	32.5	27.9	28.7	Alfred	40	42.3	39.4	29.1	29.8	36.5	29.7
Llama 3.2	3	37.5	35.6	26.2	35.1	30.8	24.8	Mixtral	8x7	50.0	41.3	34.0	39.5	31.7	29.7
Phi 3	3.8	45.2	36.5	27.2	26.3	27.9	17.8	Llama 2	70	38.5	33.7	28.2	39.5	26.0	39.6
Phi 3.5	3.8	39.4	27.9	11.7	10.5	7.7	10.9	Llama 3	70	52.9	49.0	38.8	35.1	38.5	43.6
Gemma 3	4	54.8	43.3	39.8	46.5	36.5	31.7	Llama 3.1	70	55.8	56.7	49.5	52.6	47.1	41.6
Qwen 2	7	48.1	36.5	32.0	36.0	39.4	31.7	DeepSeek-R1	70	64.4	51.0	56.3	54.4	49.0	41.6
Llama 2	7	36.5	38.5	24.3	39.5	25.0	26.7	Qwen 2	72	60.6	46.2	40.8	51.8	41.3	40.6
WizardLM 2	7	44.2	38.5	21.4	31.6	28.8	29.7	Command-R+	104	52.9	38.5	39.8	44.7	31.7	32.7
Mistral	7	35.6	35.6	34.0	30.7	34.6	26.7	Mistral-Large	123	66.3	50.0	42.7	52.6	43.3	**44.6**
Aya-23	8	40.4	30.8	30.1	31.6	31.7	31.7	Mixtral	8x22	62.5	49.0	41.7	42.1	39.4	39.6
Llama 3.1	8	56.7	33.7	33.0	33.3	30.8	33.7	WizardLM 2	8x22	58.7	40.4	40.8	43.0	35.6	34.7
Llama 3	8	45.2	35.6	35.0	36.0	28.8	31.7	Large Models (> 200B)							
DeepSeek-R1	8	53.8	39.4	38.8	39.5	34.6	28.7	Llama 3.1	405	78.8	39.4	48.5	59.6	55.8	46.5
GLM 4	9	54.8	41.3	37.9	45.6	44.2	35.6	DeepSeek-R1	671	**92.3**	83.7	73.8	76.3	73.1	**81.2**
EuroLLM	9	44.2	45.2	33.0	34.2	31.7	25.7	ChatGPT 3.5	unk.	**92.3**	85.6	**80.6**	83.3	76.0	66.3
Gemma 2	9	58.7	47.1	38.8	49.1	40.4	34.7	Claude 3.5 Sonnet	unk.	**92.3**	**92.3**	**80.6**	**86.8**	**77.9**	69.3
Mistral-Nemo	12	52.9	36.5	28.2	33.3	29.8	20.8	ChatGPT 4o	unk.	**92.3**	85.6	78.6	84.2	74.0	60.4
StableLM 2	12	27.9	35.6	26.2	28.9	27.9	23.8	ChatGPT 4o mini	unk.	90.4	90.4	59.2	59.6	54.8	43.6
Gemma 3	12	**62.5**	**58.7**	**53.4**	**50.9**	**47.1**	**40.6**	Gemini 2.0 Flash	unk.	89.4	84.6	74.8	80.7	76.0	54.5
Llama 2	13	27.9	14.4	23.3	26.3	23.1	26.7	LeChat	unk.	42.3	53.8	38.8	51.8	41.3	32.7
Phi 3	14	45.2	38.5	38.8	39.5	27.9	21.8	Baseline (average chance rate)							
Phi 4	14	53.8	51.9	42.7	44.7	34.6	33.7	Random Baseline	/	37.6	37.5	33.3	33.0	31.8	33.5

Table 2: Total results of language exams. **Bold** numbers indicate highest performance for each size category.

3.5 Prompt Design

We experimented with prompts of different lengths and degrees of complexity to find a prompt that yields the best result for solving the language exams. See Appendix C for the full prompt. Regarding the prompts for the Headline Generation and Short Description summary tasks, we reuse the prompts used by Plum et al. (2025) for every model we investigate. The prompts used for evaluating the LuxGen tasks that use the metric requirements described in Section 3.4 can be found in Appendix D.

3.6 Hyperparameters

For all our experiments, models and metrics, we use the default hyperparameters. The exceptions are the models solving the language exams, for which we set the temperature to 0 to reduce randomness of the answers.

4 Results

4.1 RQ1: How well do LLMs perform in Luxembourgish language tests?

Table 2 shows the overall results of the LLMs we tested as well as a baseline determined as the average performance for a model that randomly guesses the answers of the exams. See Appendix E for a breakdown of results across the four categories. For a more convenient way of exploring the results, we also release an interactive web app with the results.

We observe a clear trend where the *large* models typically perform well above average. Claude 3.5 Sonnet achieves the highest scores across every test except for the C2 test for which DeepSeek-R1:671B performs best. Among the *small* models, many models show promise to be adequate for further fine-tuning on Luxembourgish data despite their small size as they perform better than the random baseline and either approach or slightly surpass the 50% mark on the easier tests. We deem Gemma3:12B the best *small* model as it performs best in all exams out of the models in the *small* category.

Medium-sized models generally perform consistently better than *small* models. Gemma3:27B is the overall winner among the *medium-sized* models, performing significantly better than all of its counterparts except for the C2 exams where it ties with the QWQ and Mistral-Large models.

Furthermore, as expected, performances drop for higher CEFR levels as the tests become increasingly more difficult, with one notable exception. Most models achieve a higher performance on the B2 test than on the B1 test. Specifically, they per-

form surprisingly well on the Reading Comprehension questions, however, it is unclear why those questions appear to be easier for LLMs to solve.

4.2 RQ2: In which cases do LLMs fail to understand Luxembourgish?

model	Size	Vocab.	Grammar	RC	CC
Small Models ($\leq 15B$)					
Qwen 2	0.5	25.7	19.7	21.2	22.6
Llama 3.2	1	21.3	23.7	20.5	18.8
Gemma 3	1	27.4	37.8	41.7	39.9
Qwen 2	1.5	29.6	28.3	25.0	25.2
StableLM 2	1.6	23.2	28.5	5.8	13.5
EuroLLM	1.7	24.0	20.0	16.7	18.1
Gemma 2	2	34.4	29.7	29.5	34.8
Llama 3.2	3	31.7	28.3	32.1	35.5
Phi 3	3.8	27.8	25.3	29.5	38.0
Phi 3.5	3.8	17.3	20.0	15.4	19.3
Gemma 3	4	46.2	32.9	43.6	47.1
Qwen 2	7	35.8	31.2	35.9	47.1
Llama 2	7	30.7	26.7	35.3	34.8
WizardLM 2	7	35.9	32.3	28.8	32.8
Mistral	7	31.2	28.3	34.6	38.1
Aya-23	8	31.7	29.5	32.1	37.4
Llama 3.1	8	30.1	33.5	39.7	44.4
Llama 3	8	34.5	33.7	35.3	38.6
DeepSeek-R1	8	40.6	34.5	40.4	41.3
GLM 4	9	50.3	27.3	43.6	52.8
EuroLLM	9	40.0	32.0	35.9	35.5
Gemma 2	9	57.3	34.1	44.9	43.8
Mistral-Nemo	12	36.2	27.7	34.6	36.7
StableLM 2	12	35.1	17.1	30.8	31.7
Gemma 3	12	**63.1**	32.4	**54.5**	**59.9**
Llama 2	13	25.6	26.6	21.2	21.3
Phi 3	14	34.0	35.8	32.7	38.6
Phi 4	14	46.2	**36.7**	45.5	45.8
Medium-sized Models ($> 15B\ \&\ \leq 200B$)					
Mistral-Small	22	41.3	29.5	34.6	50.3
Gemma 2	27	60.1	36.7	57.1	62.0
Gemma 3	27	**71.1**	**51.7**	**60.9**	**64.5**
QWQ	32	59.5	38.1	41.7	56.0
Aya-23	35	39.6	30.7	40.4	40.0
Command-R	35	39.4	34.4	44.2	41.3
Alfred	40	34.3	32.3	34.6	36.8
Mixtral	8x7	47.1	27.3	36.5	40.7
Llama 2	70	28.8	28.3	36.5	43.1
Llama 3	70	53.0	35.6	40.4	43.8
Llama 3.1	70	60.4	46.0	45.5	50.9
DeepSeek-R1	70	64.5	42.2	44.9	60.6
Qwen 2	72	51.6	36.5	48.7	51.5
Command-R+	104	46.5	31.1	40.4	42.5
Mistral-Large	123	64.9	41.1	42.3	52.2
Mixtral	8x22	49.4	40.5	42.3	50.9
WizardLM 2	8x22	40.4	37.7	41.7	49.0
Large Models ($> 200B$)					
Llama 3.1	405	63.4	43.0	54.5	59.3
DeepSeek-R1	671	**92.2**	75.2	74.4	79.9
ChatGPT 3.5	unk.	91.6	72.1	73.7	85.8
Claude 3.5 Sonnet	unk.	87.8	**82.4**	**76.9**	**86.4**
ChatGPT 4o	unk.	88.3	71.5	73.1	84.5
ChatGPT 4o mini	unk.	76.7	55.4	62.2	71.5
Gemini 2.0 Flash	unk.	82.0	68.1	73.7	83.8
LeChat	unk.	59.7	34.7	32.1	48.4

Table 3: Coarse-grained category results of language exams. **Bold** numbers indicate highest performance for each size category.

In order to answer this question, we analyse trends and patterns relating to the four categories

mentioned in Section 3.2.1. Table 3 contains the performances of the studied language models per category. From the results, we note that overall, LLMs perform almost consistently best in vocabulary questions while grammar appears to be the hardest category. Furthermore, although the Reading Comprehension and Conversation Comprehension questions are nominally different, there is no statistical difference between the performances of the LLMs in either category (according to a paired t-test). However, when taking into account the size categories of the LLMs, *large* models perform significantly better in the conversation comprehension category than reading comprehension questions.

In addition to the coarse-grained ones, we created fine-grained categories for the questions in the language tests (see Appendix G for more information on the categories).

We present the results of the best-performing models in Table 4. Due to space issues, we put the entire table in Appendix F. The categorisation was done in a supervised fashion using Claude 3.7 Sonnet and category explanations as well as a separate manually annotated language exam that were added to the prompt. We provide the descriptions for each category as well as the prompt for annotation in Appendices G and H. We manually reviewed the automatically annotated questions to ensure correctness. It is to note that for this categorisation, we do not differentiate between reading comprehension and conversation comprehension, and thusly group them together.

For vocabulary-related questions, there is a clear pattern showing that LLMs perform worse in categories that require "language-exclusive" knowledge and cannot be easily inferred from other languages, i.e., idioms and native words. Regarding grammar, the hardest categories for the large models are adjectives, past tense, and cases. The main challenge appears to be related to the fact that the possible answers for many of those questions are almost identical. For example, one question from the adjectives category is:

Op ___ Weiere kann een de Wanter Schlittschong fueren

with the possible answers being:

zougefruer, zougefruerene, zougefruerenen, zougefréieren

For the reading comprehension questions, we split them into three categories: *true/false*, *simple*, and *complex*. *Simple* questions do not require an understanding of the entire given text excerpt, and the correct answer for those questions can be found

model	Llama 3.1 405B	DeepSeek-R1 671B	ChatGPT 3.5	Claude 3.5	ChatGPT 4o	ChatGPT 4o m	Gemini 2.0	LeChat
V_Idioms	42.9	81.0	71.4	42.9	52.4	38.1	33.3	38.1
V_Noun	67.9	94.0	91.7	85.7	86.9	79.8	81.0	65.5
V_Verb	68.2	93.2	90.9	88.6	90.9	68.2	84.1	61.4
V_Adjective	47.8	91.3	100.0	100.0	95.7	87.0	87.0	47.8
V_Native	33.3	100.0	50.0	50.0	66.7	16.7	16.7	50.0
G_Gender	37.8	70.3	73.0	70.3	78.4	56.8	70.3	24.3
G_Pronouns	40.0	65.0	60.0	75.0	60.0	65.0	70.0	50.0
G_Verb	40.7	68.5	75.9	90.7	75.9	53.7	75.9	35.2
G_Adjective	22.2	55.6	44.4	66.7	55.6	22.2	66.7	44.4
G_Tense	36.7	69.4	77.6	91.8	77.6	55.1	79.6	34.7
G_Past	30.0	55.0	75.0	85.0	70.0	50.0	75.0	30.0
G_Present	53.8	84.6	92.3	100.0	92.3	76.9	84.6	38.5
G_Subjunctive	28.6	71.4	71.4	92.9	78.6	42.9	71.4	35.7
G_Modal	14.3	100.0	71.4	85.7	85.7	71.4	85.7	42.9
G_Prepositions	55.6	81.5	75.9	85.2	74.1	64.8	68.5	35.2
G_Cases	33.3	64.1	69.2	69.2	64.1	51.3	53.8	35.9
RC_TF	55.9	79.6	85.5	88.2	83.6	61.8	80.9	39.5
RC_Simple	63.6	86.4	88.6	86.4	86.4	86.4	86.4	40.9
RC_Complex	59.1	84.8	83.3	86.4	83.3	81.8	84.8	47.0

Table 4: Performance of large models on fine-grained categories. V: Vocabulary; G: Grammar; RC: Reading Comprehension; TF: True/False

either explicitly written in the text or by understanding a portion of the text. *True/false* and *complex* questions require models to fully understand the given text excerpt, the main difference being that *True/False* questions are binary while *complex* ones have three or four possible answers. As such, the latter questions are considered harder. This assumption is indeed confirmed by the results as the *large* models seem to perform best for *simple* questions.

It is to note, that these observations largely hold true for *small* and *medium-sized* models except for simple reading comprehension questions which was often the hardest category for those models.

4.3 RQ3: Are there correlations between performing well in a language exam and performing well in an NLG task?

For this research question, we first average out the performances of every LLM on all six language exams, resulting in their overall exam performance score. We then let the LLMs solve both of the Lux-Gen tasks, and evaluate the outputs using an LLM-as-a-judge (LaaJ). Our LLM of choice is Claude 3.7 Sonnet (Anthropic, 2025). After manually verifying its capabilities to solve the tasks at hand, we deemed it an adequate LLM to evaluate the experiments as it solved both tasks well and with minimal spelling mistakes. In addition to the LaaJ-metrics, we employ the METEOR and BERTScore metrics which also allow us to assess the usefulness of our novel metrics (see Appendix J). For both tasks and all metrics we employ, we calculate mean performance scores for each LLM. Figure 2 shows the performances of all LLMs on the Head-

Task	Small	Medium	Large	All
Claude-G	0.651	0.735	0.291	0.837
Claude-A	0.648	0.585	0.301	0.794
METEOR	0.427	0.450	0.089	0.667
BERTScore	0.407	0.116	0.266	0.622

(a) Pearson Correlation Coefficients

	small	medium	large	all
Claude-G	6.127	7.743	2.171	10.938
Claude-A	6.072	5.145	2.255	9.327
METEOR	3.369	3.600	0.639	6.390
BERTScore	3.179	0.837	1.972	5.676

(b) T-Scores

	small	medium	large	all
Claude-G	1.299E-07	3.667E-10	0.0346	5.552E-15
Claude-A	1.583E-07	4.318E-06	0.0285	1.312E-12
METEOR	0.0014	0.0007	0.5259	4.998E-08
BERTScore	0.0025	0.4064	0.0541	6.578E-07

(c) P-Values

Table 5: Correlation tests between the overall exam scores and Headline Generation task performances.

line Generation task (y-axis) plotted against their respective overall exam performances (x-axis). See Appendix K for plots for the Short Description task and Appendix I for detailed results for both tasks. Generally, the LuxGen performances of the LLMs appear to strongly positively correlate with their exam performances. This is true for all metrics, although the spread and average performance is lower for the non-LaaJ metrics.

To confirm our observations, we calculate Pearson's Correlation Coefficients (PCCs) for each set of performances (see Table 5). For most cases, we note moderate to strong PCCs. Some notable exceptions are the *medium* and *large* categories of LLMs with BERTScore and METEOR metrics, re-

(a) Claude Score - Grammar and Spelling

(b) Claude Score - Adequacy

(c) BERTScore

(d) METEOR Score

Figure 2: Performance on language exams vs performance on the Headline Generation task.

spectively, where there appears to be either a weak positive correlation or no correlation at all. We further calculate corresponding t-scores and p-values, and show that our findings are significant in most cases for $\alpha = 0.05$ except for the aforementioned exceptions and BERTScore for the *large* category. We repeat the same significance tests for the Short Description task (see Appendix K) and find consistently high positive PCCs for all metrics, significant at $\alpha = 0.05$.

5 Discussion

Generally, we conclude that language exams can indeed be a useful tool to assess the generation capabilities of LLMs. For the NLP tasks we tested, we can to a certain degree predict if an LLM performs well given how well it scored on the exams. However, there are some caveats to keep in mind:

Firstly, it is important to consider for what type of task an LLM is considered. Language exams are used to evaluate the general proficiency in a language across multiple disciplines. As such, the overall exam score can be dragged down by irrelevant categories of questions, e.g., an LLM used to detect hate speech in an online forum does not necessarily need to have a perfect grasp on obscure grammar rules. In such a case, it is preferable to adjust the exam to only include certain question categories. Secondly, for this study, we did not do any additional fine-tuning on Luxembourgish data which might have altered the performances of the tested LLMs to different degrees. It is possible that certain LLMs adapt better when fine-tuned on an instruction tuning dataset.

6 Conclusion

In this study, we investigated the performance of a large number of recent LLMs on official language exams, and assessed whether or not they serve as a useful tool to determine the capabilities of language models. We found that many models struggle with even the easier exams, with only the largest models scoring well in every exam. We also delved into dividing the exam questions into fine-grained categories to assess which types of questions are harder to solve for LLMs, finding that questions requiring language-exclusive knowledge as well as questions with similar answers pose problems to many models. Finally, we determined that using such exams can indeed be used as an indicator for language generation and understanding capabilities of LLMs, with some caveats to consider.

7 Limitations

While we are confident about the findings and conclusions of our studies, there are still certain limitations to consider. First, while we aimed to include a comprehensive list of current LLMs in our experiments, it is a nearly impossible task considering the frequent release of new models. We even had to scrap parts of our experiments that were done using Gemini 1.5 Flash as it became inaccessible after the release of the 2.0 model. We are also fully aware that many new model versions have been released that we did not consider for this study. We however remain confident that our selection of LLMs gives a good overview of available models. Another limitation relates to the relatively small number of generation tasks we considered for RQ3. As they are essentially both summarisation tasks, it is possible that our conclusions do not apply to other types of NLP tasks. This could be a useful research direction for future work. In addition, we only used a small sample of those two summarisation tasks due to the large number of LLMs we considered. Furthermore, as the data that was used to create those tasks are publicly available, it is possible that at least a subset of the studied LLMs saw that data during training which would have influenced their performance in those tasks. Finally, it is possible that our conclusions are not generalisable to other languages since we are limiting ourselves to Luxembourgish. Again, studying if we can apply our methodology to other low-resource languages would be a worthwhile research direction that can benefit other language communities.

References

Ali Abbas, Mahad S Rehman, and Syed S Rehman. 2024. Comparing the performance of popular large language models on the national board of medical examiners sample questions. *Cureus*, 16(3).

Marah Abdin, Jyoti Aneja, Hany Awadalla, Ahmed Awadallah, Ammar Ahmad Awan, Nguyen Bach, Amit Bahree, Arash Bakhtiari, Jianmin Bao, Harkirat Behl, et al. 2024a. Phi-3 technical report: A highly capable language model locally on your phone. *arXiv preprint arXiv:2404.14219*.

Marah Abdin, Jyoti Aneja, Harkirat Behl, Sébastien Bubeck, Ronen Eldan, Suriya Gunasekar, Michael Harrison, Russell J Hewett, Mojan Javaheripi, Piero Kauffmann, et al. 2024b. Phi-4 technical report. *arXiv preprint arXiv:2412.08905*.

Anthropic. 2024. Claude 3.5 Sonnet. https://www.anthropic.com/. Large Language Model.

Anthropic. 2025. Claude 3.7 sonnet. Anthropic. AI assistant.

Viraat Aryabumi, John Dang, Dwarak Talupuru, Saurabh Dash, David Cairuz, Hangyu Lin, Bharat Venkitesh, Madeline Smith, Kelly Marchisio, Sebastian Ruder, Acyr Locatelli, Julia Kreutzer, Nick Frosst, Phil Blunsom, Marzieh Fadaee, Ahmet Üstün, and Sara Hooker. 2024. Aya 23: Open weight releases to further multilingual progress.

Satanjeev Banerjee and Alon Lavie. 2005. Meteor: An automatic metric for mt evaluation with improved correlation with human judgments. In *Proceedings of the acl workshop on intrinsic and extrinsic evaluation measures for machine translation and/or summarization*, pages 65–72.

Marco Bellagente, Jonathan Tow, Dakota Mahan, Duy Phung, Maksym Zhuravinskyi, Reshinth Adithyan, James Baicoianu, Ben Brooks, Nathan Cooper, Ashish Datta, et al. 2024. Stable lm 2 1.6 b technical report. *arXiv preprint arXiv:2402.17834*.

Cohere For AI. 2024. c4ai-command-r-08-2024.

Council of Europe. 2001. *Common European framework of reference for languages: Learning, teaching, assessment*. Cambridge University Press.

Xuan-Quy Dao, Ngoc-Bich Le, Xuan-Dung Phan, Bac-Bien Ngo, and TD Vo. 2023. Evaluation of chatgpt and microsoft bing ai chat performances on physics exams of vietnamese national high school graduation examination. *arXiv Prepr. arXiv2306*, 4538.

Roberts Darģis, Guntis Barzdins, Inguna Skadiņa, and Baiba Saulīte. 2024. Evaluating open-source llms in low-resource languages: Insights from latvian high school exams. In *Proceedings of the 4th International Conference on Natural Language Processing for Digital Humanities*, pages 289–293.

DeepSeek-AI. 2025. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning.

Tu Dinh, Carlos Mullov, Leonard Bärmann, Zhaolin Li, Danni Liu, Simon Reiß, Jueun Lee, Nathan Lerzer, Jianfeng Gao, Fabian Peller-Konrad, et al. 2024. Sciex: Benchmarking large language models on scientific exams with human expert grading and automatic grading. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 11592–11610.

Michael E Ellis, K Mike Casey, and Geoffrey Hill. 2024. Chatgpt and python programming homework. *Decision Sciences Journal of Innovative Education*, 22(2):74–87.

Protection European Union. 2016. Regulation (EU) 2016/679 of the European Parliament and of the Council. *Regulation (eu)*, 679:2016.

Peter Gilles. 2006. Phonologie der n-tilgung im moselfränkischen ('eifler regel'). ein beitrag zur dialektologischen prosodieforschung.

Google. 2024. Gemini 2.0 flash. Large language model.

Jennifer Gotta, Quang Anh Le Hong, Vitali Koch, Leon D Gruenewald, Tobias Geyer, Simon S Martin, Jan-Erik Scholtz, Christian Booz, Daniel Pinto Dos Santos, Scherwin Mahmoudi, et al. 2024. Large language models (llms) in radiology exams for medical students: Performance and consequences. In *RöFo-Fortschritte auf dem Gebiet der Röntgenstrahlen und der bildgebenden Verfahren*. Georg Thieme Verlag KG.

Grand-Duché de Luxembourg. 2018. Loi du 1er août 2018 portant organisation de la Commission nationale pour la protection des données et mise en œuvre du règlement (UE) 2016/679. https://data.legilux.public.lu/filestore/eli/etat/leg/loi/2018/08/01/a686/jo/fr/html/eli-etat-leg-loi-2018-08-01-a686-jo-fr-html.html. Journal officiel du Grand-Duché de Luxembourg, Mémorial A n°686.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, et al. 2024. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*.

Oskar Hallström, Amélie Chatelain, Clément Thiriet, Julien Séailles, Adrien Cavaillès, and Axel Marmet. 2023. Alfred-40b-1023.

Krzysztof Jassem, Michał Ciesiółka, Filip Graliński, Piotr Jabłoński, Jakub Pokrywka, Marek Kubis, Monika Jabłońska, and Ryszard Staruch. 2025. Llmzsz {\L}: a comprehensive llm benchmark for polish. *arXiv preprint arXiv:2501.02266*.

Aishwarya Kamath, Johan Ferret, Shreya Pathak, Nino Vieillard, Ramona Merhej, Sarah Perrin, Tatiana Matejovicova, Alexandre Ramé, Morgane Rivière, et al. 2025. Gemma 3 technical report. *arXiv preprint arXiv:2503.19786*.

Daniel Martin Katz, Michael James Bommarito, Shang Gao, and Pablo Arredondo. 2024. Gpt-4 passes the bar exam. *Philosophical Transactions of the Royal Society A*, 382(2270):20230254.

Fajri Koto. 2024. Cracking the code: Multi-domain llm evaluation on real-world professional exams in indonesia. *arXiv preprint arXiv:2409.08564*.

Fajri Koto, Nurul Aisyah, Haonan Li, and Timothy Baldwin. 2023. Large language models only pass primary school exams in indonesia: A comprehensive test on indommlu. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 12359–12374.

Teven Le Scao, Angela Fan, Christopher Akiki, Ellie Pavlick, Suzana Ilić, Daniel Hesslow, Roman Castagné, Alexandra Sasha Luccioni, François Yvon, Matthias Gallé, et al. 2023. Bloom: A 176b-parameter open-access multilingual language model.

Nero Li, Shahar Broner, Yubin Kim, Katrina Mizuo, Elijah Sauder, Claire To, Albert Wang, Ofek Gila, and Michael Shindler. 2025. Investigating the capabilities of generative ai in solving data structures, algorithms, and computability problems. In *Proceedings of the 56th ACM Technical Symposium on Computer Science Education V. 1*, pages 659–665.

Marcelo Sartori Locatelli, Matheus Prado Miranda, Igor Joaquim da Silva Costa, Matheus Torres Prates, Victor Thomé, Mateus Zaparoli Monteiro, Tomas Lacerda, Adriana Pagano, Eduardo Rios Neto, Wagner Meira Jr, et al. 2024. Examining the behavior of llm architectures within the framework of standardized national exams in brazil. In *Proceedings of the 2024 AAAI/ACM Conference on AI, Ethics, and Society*, pages 879–890.

Cedric Lothritz, Bertrand Lebichot, Kevin Allix, Lisa Veiber, Tegawendé François D Assise Bissyande, Jacques Klein, Andrey Boytsov, Anne Goujon, and Clément Lefebvre. 2022. Luxembert: Simple and practical data augmentation in language model pre-training for luxembourgish. In *13th Language Resources and Evaluation Conference (LREC 2022)*.

Eric Martínez. 2024. Re-evaluating gpt-4's bar exam performance. *Artificial intelligence and law*, pages 1–24.

Pedro Henrique Martins, Patrick Fernandes, João Alves, Nuno M Guerreiro, Ricardo Rei, Duarte M Alves, José Pombal, Amin Farajian, Manuel Faysse, Mateusz Klimaszewski, et al. 2024. Eurollm: Multilingual language models for europe. *arXiv preprint arXiv:2409.16235*.

Marina Mayor-Rocher, Nina Melero, Elena Merino-Gómez, María Grandury, Javier Conde, and Pedro Reviriego. 2024. Evaluating large language models with tests of spanish as a foreign language: Pass or fail? *arXiv preprint arXiv:2409.15334*.

Fabio Mercorio, Mario Mezzanzanica, Daniele PotertĂŹ, Antonio Serino, and Andrea Seveso. 2024. Disce aut deficere: Evaluating llms proficiency on the invalsi italian benchmark. *arXiv preprint arXiv:2406.17535*.

Thomas Mesnard, Cassidy Hardin, Robert Dadashi, Surya Bhupatiraju, Laurent Sifre, Morgane Rivière, Mihir Sanjay Kale, Juliette Love, Pouya Tafti, Léonard Hussenot, and et al. 2024. Gemma.

Mistral AI. 2023a. Lechat. Large language model.

Mistral AI. 2023b. Mistral 7b. Large language model.

Mistral AI. 2024. Mixtral 8x7b. Large language model.

OpenAI. 2023. Chatgpt-3.5. Large language model. Version: ChatGPT-3.5, URL: https://openai.com/chatgpt.

OpenAI. 2024a. Chatgpt-4o. Large language model. Version: ChatGPT-4o, URL: https://openai.com/chatgpt.

OpenAI. 2024b. Chatgpt-4o mini. Large language model. Version: ChatGPT-4o Mini, URL: https://openai.com/chatgpt.

Alistair Plum, Tharindu Ranasinghe, and Christoph Purschke. 2025. Text generation models for luxembourgish with limited data: A balanced multilingual strategy. *VarDial 2025*, page 93.

Qwen. 2025. Qwq-32b: Embracing the power of reinforcement learning.

Mehmet Fatih Şahin, Çağrı Doğan, Erdem Can Topkaç, Serkan Şeramet, Furkan Batuhan Tuncer, and Cenk Murat Yazıcı. 2025. Which current chatbot is more competent in urological theoretical knowledge? a comparative analysis by the european board of urology in-service assessment. *World Journal of Urology*, 43(1):116.

Daniel Stribling, Yuxing Xia, Maha K Amer, Kiley S Graim, Connie J Mulligan, and Rolf Renne. 2024. The model student: Gpt-4 performance on graduate biomedical science exams. *Scientific Reports*, 14(1):5670.

Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothee Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, et al. Llama: Open and efficient foundation language models.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. 2023. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*.

Arya VarastehNezhad, Reza Tavasoli, Mostafa Masumi, and Fattaneh Taghiyareh. 2024. Llm performance assessment in computer science graduate entrance exams. In *2024 11th International Symposium on Telecommunications (IST)*, pages 232–237. IEEE.

Can Xu, Qingfeng Sun, Kai Zheng, Xiubo Geng, Pu Zhao, Jiazhan Feng, Chongyang Tao, Qingwei Lin, and Daxin Jiang. 2024. WizardLM: Empowering large pre-trained language models to follow complex instructions. In *The Twelfth International Conference on Learning Representations*.

An Yang, Baosong Yang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Zhou, Chengpeng Li, Chengyuan Li, Dayiheng Liu, Fei Huang, Guanting Dong, Haoran Wei, Huan Lin, Jialong Tang, Jialin Wang, Jian Yang, Jianhong Tu, Jianwei Zhang, Jianxin Ma, Jianxin Yang, Jin Xu, Jingren Zhou, Jinze Bai, Jinzheng He, Junyang Lin, Kai Dang, Keming Lu, Keqin Chen, Kexin Yang, Mei Li, Mingfeng Xue, Na Ni, Pei Zhang, Peng Wang, Ru Peng, Rui Men, Ruize Gao, Runji Lin, Shijie Wang, Shuai Bai, Sinan Tan, Tianhang Zhu, Tianhao Li, Tianyu Liu, Wenbin Ge, Xiaodong Deng, Xiaohuan Zhou, Xingzhang Ren, Xinyu Zhang, Xipin Wei, Xuancheng Ren, Xuejing Liu, Yang Fan, Yang Yao, Yichang Zhang, Yu Wan, Yunfei Chu, Yuqiong Liu, Zeyu Cui, Zhenru Zhang, Zhifang Guo, and Zhihao Fan. 2024a. Qwen2 technical report.

An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chengyuan Li, Dayiheng Liu, Fei Huang, Haoran Wei, Huan Lin, Jian Yang, Jianhong Tu, Jianwei Zhang, Jianxin Yang, Jiaxi Yang, Jingren Zhou, Junyang Lin, Kai Dang, Keming Lu, Keqin Bao, Kexin Yang, Le Yu, Mei Li, Mingfeng Xue, Pei Zhang, Qin Zhu, Rui Men, Runji Lin, Tianhao Li, Tianyi Tang, Tingyu Xia, Xingzhang Ren, Xuancheng Ren, Yang Fan, Yang Su, Yichang Zhang, Yu Wan, Yuqiong Liu, Zeyu Cui, Zhenru Zhang, and Zihan Qiu. 2024b. Qwen2.5 technical report. *arXiv preprint arXiv:2412.15115*.

Aohan Zeng, Bin Xu, Bowen Wang, Chenhui Zhang, Da Yin, Diego Rojas, Guanyu Feng, Hanlin Zhao, Hanyu Lai, Hao Yu, Hongning Wang, Jiadai Sun, Jiajie Zhang, Jiale Cheng, Jiayi Gui, Jie Tang, Jing Zhang, Juanzi Li, Lei Zhao, Lindong Wu, Lucen Zhong, Mingdao Liu, Minlie Huang, Peng Zhang, Qinkai Zheng, Rui Lu, Shuaiqi Duan, Shudan Zhang, Shulin Cao, Shuxun Yang, Weng Lam Tam, Wenyi Zhao, Xiao Liu, Xiao Xia, Xiaohan Zhang, Xiaotao Gu, Xin Lv, Xinghan Liu, Xinyi Liu, Xinyue Yang, Xixuan Song, Xunkai Zhang, Yifan An, Yifan Xu, Yilin Niu, Yuantao Yang, Yueyan Li, Yushi Bai, Yuxiao Dong, Zehan Qi, Zhaoyu Wang, Zhen Yang, Zhengxiao Du, Zhenyu Hou, and Zihan Wang. 2024. Chatglm: A family of large language models from glm-130b to glm-4 all tools.

Tianyi Zhang, Varsha Kishore, Felix Wu, Kilian Q Weinberger, and Yoav Artzi. 2019. Bertscore: Evaluating text generation with bert. *arXiv preprint arXiv:1904.09675*.

Hui Zong, Rongrong Wu, Jiaxue Cha, Jiao Wang, Erman Wu, Jiakun Li, Yi Zhou, Chi Zhang, Weizhe Feng, and Bairong Shen. 2024. Large language models in worldwide medical exams: Platform development and comprehensive analysis. *Journal of Medical Internet Research*, 26:e66114.

A Number and Distribution of Open Questions in Language Exams

Category	A1	A2	B1	B2	C1	C2	Total
Vocabulary	0	0	13	13	14	12	52
Grammar	0	0	0	17	14	25	56
Total	0	0	13	30	28	37	108

Table 6: Number of open questions in language exams

B Full List of LLMs and Reasons for Inclusion

Table 7 contains the full list of LLMs we include in this study.

C Language Exam Prompt

We use the following prompt for testing LLMs on language exams:

```
"I will give you a language test for
Luxembourgish. For each part, you will
get a TEXT with one part missing marked
by [BLANK] and a list of possible
ANSWERS where every possible option is
separated with a comma. You MUST choose
the option out of the provided list that
best fits as replacement for the given
BLANK. As output, ONLY write the chosen
option, nothing else. DO NOT WRITE ANY
ADDITIONAL TEXT."

INPUT: [the question and possible answers]
OUTPUT:
```

where the INPUTs for the exams are formatted as follows:

```
TEXT: Den Direkter ass houfereg [BLANK]
eis Leeschtung.
ANSWERS: [iwwert,fir,mat,op]
```

D Evaluation Metric Prompts for LuxGen

For each task and metric, we designed different prompts for a total of four prompts:

Grammar and Spelling Metric for Small Description Task:

```
I will give you a table as a TSV file. This
table contains Luxembourgish Wikipedia
articles in the first column, the second
column contains ground truth short
descriptions for the articles. The rest of
the columns contain short descriptions
generated by various language models. The
generated descriptions are supposed to be
written in correct Luxembourgish. Your
task is to judge the generated descriptions
in terms of grammatical correctness and
spelling. Keep in mind that the descriptions
do not need to be complete sentences.

For each language model and sample, return
a score ranging from 0 to 1 with two
decimals behind the comma. For the score,
1 means that the description is perfectly
written without any grammatical or
spelling mistakes. The more mistakes there
are, the lower the score should be. A 0
means that the headline is full of mistakes
and made up words. Also return 0 if the
description is not written in
Luxembourgish at all.

Return the average scores in a table.
```

Adequacy Metric for Small Description Task:

```
I will give you a table as a TSV file. This
table contains Luxembourgish Wikipedia
articles in the first column, the second
column contains ground truth short
descriptions for the articles. The rest of
the columns contain short descriptions
generated by various language models. The
generated descriptions are supposed to be
written in correct Luxembourgish. Your
task is to judge the generated
descriptions in terms of the content
being an adequate description of the
article. Keep in mind that the
descriptions do not need to be complete
sentences.

For each language model and sample, return
a score ranging from 0 to 1 with two
decimals behind the comma. For the score,
1 means that the description is identical
to the ground truth, and should be lower
the more it deviates from the meaning of
the article. The score should also be
lowered for descriptions that are too long.
```

Model	Size	Reason for Inclusion
Small Models ($\leq 15B$)		
Qwen 2	0.5	Supports German and Dutch
Llama 3.2	1	Supports German
Gemma 3	1	Officially supports only English but manages to generate Luxembourgish in experiments
Qwen 2	1.5	Supports German and Dutch
StableLM 2	1.6	Supports German and Dutch
EuroLLM	1.7	Supports German and Dutch
Gemma 2	2	Was trained on multilingual data
Llama 3.2	3	Supports German
Phi 3	3.8	Tested on multilingual NLP tasks
Phi 3.5	3.8	Tested on multilingual NLP tasks
Gemma 3	4	Supports 140+ languages/ not explicitly supporting Luxembourgish
Qwen 2	7	Supports German and Dutch
Llama 2	7	Was trained on multilingual data / not explicitly multilingual
WizardLM 2	7	claims to be multilingual
Mistral	7	European model / not explicitly multilingual
Aya-23	8	Supports German and Dutch
Llama 3.1	8	Supports German
Llama 3	8	Performed well on multilingual NLP task including German
DeepSeek-R1	8	smaller version of massively multilingual model
GLM 4	9	Supports German
EuroLLM	9	Supports German and Dutch
Gemma 2	9	Training on multilingual data
Mistral-Nemo	12	Supports German
StableLM 2	12	Supports German and Dutch
Gemma 3	12	Supports 140+ languages/ not explicitly supporting Luxembourgish
Llama 2	13	Was trained on multilingual data
Phi 3	14	Tested on multilingual NLP tasks
Phi 4	14	Trained on German data
Medium-sized Models ($> 15B \& \leq 200B$)		
Mistral Small	22	Supports German and Dutch
Gemma 2	27	Training on multilingual data
Gemma 3	27	Supports 140+ languages/ not explicitly supporting Luxembourgish
QWQ	32	Supports 29 languages/ not explicitly supporting Luxembourgish
Aya-23	35	Supports German and Dutch
Command-R	35	Supports German
Alfred	40	Supports German
Mixtral	8x7	Supports German
Llama 2	70	Was trained on multilingual data
Llama 3	70	Performed well on multilingual NLP task including German
Llama 3.1	70	Supports German
DeepSeek-R1	70	smaller version of massively multilingual model
Qwen 2	72	Supports German and Dutch
Command-R+	104	Supports German
Mistral-Large	123	Supports German
Mixtral	8x22	Supports German
WizardLM 2	8x22	claims to be multilingual
Large Models ($> 200B$)		
Llama 3.1	405	Supports German
DeepSeek-R1	671	Massively Multilingual Model
ChatGPT 3.5	175	Massively Multilingual Model
Claude 3.5 Sonnet	unk	Massively Multilingual Model
ChatGPT 4o	unk	Massively Multilingual Model
ChatGPT 4o mini	unk	Massively Multilingual Model
Gemini 2.0 Flash	unk	Massively Multilingual Model
LeChat	unk	Massively Multilingual Model

Table 7: Full list of LLMs and our reasoning for including them in this study

A 0 means that the description is completely irrelevant to the article.

Return the average scores in a table.

Grammar and Spelling Metric for News Headline Task:

You are a news editor for a Luxembourgish news paper. I will give you a table as a TSV file. This table contains news articles in the first column, the second column contains ground truth headlines for the articles. The rest of the columns will contain headlines that were produced by various language models. Your task is to judge the produced headlines in terms of grammatical correctness and spelling.

For each language model and sample, return a score ranging from 0 to 1 with two decimals behind the comma. For the score, 1 means that the headline is perfectly written without any grammatical or spelling mistakes. The more mistakes there are, the lower the score should be. A 0 means that the headline is full of mistakes and made up words. Also return 0 if the description is not written in Luxembourgish at all.

Return the average scores in a table.

Adequacy Metric for News Headline Task:

You are a news editor for a Luxembourgish news paper. I will give you a table as a TSV file. This table contains news articles in the first column, the second column contains ground truth headlines for the articles. The rest of the columns will contain headlines that were produced by various language models. Your task is to judge the produced headlines in terms of summary of the content of the article.

For each language model and sample, return a score ranging from 0 to 1 with two decimals behind the comma. For the score, a 1 means that headline is

identical to the ground truth, and should decrease the more its meaning deviates from the content in the news article. The score should also be lowered for headlines that are too long. A 0 means that the headline is completely irrelevant to the article.

Return the average scores in a table.

E Coarse-grained Exam Results

Table 8 shows the full breakdown of our results on language tests for each language level.

F Fine-grained Exam Results

Table 9 shows results of our experiments on fine-grained categories for all LLMs.

G Fine-grained Category Description

Table 10 contains explanations and statistics for the fine-grained categories we created for the exam dataset.

H Fine-grained Category Annotation Prompt

We use the following prompt to categorise the exam questions:

I have a language test for Luxembourgish where I would like you to categorise every question into different types of skill they are testing. For every question and every category, determine and mark whether or not a given question belongs to a given category, as follows:

0, the question does not belong to the category
1, the question belongs to the category

Write the output in tabular form like TSV.

The file I am uploading are some questions that I already manually annotated.
Use it as a guideline.
The list of categories and explanations is as follows:
vocabulary: any question relating to vocabulary
grammar: any question relating

```
to grammar
vocabulary_idiom: a question relating
to idioms or metaphors
vocabulary_noun: a vocabulary question
relating to a noun
vocabulary_verb: a vocabulary question
relating to a verb
vocabulary_adjective: a vocabulary
question relating to an adjective
vocabulary_native_word: a vocabulary
question where the correct answer is a
word exclusive to Luxembourgish
grammar_gender: a question relating to determining the gender
of a determinant, adjective, or pronoun
grammar_pronouns: a question relating to pronouns
grammar_verbs:  a question relating to conjugations of verbs
grammar_adjectives:  a question relating to adjectives
grammar_tense: a question relating to the correct use of tenses
grammar_tense_past: a question relating to the past tense
grammar_tense_present: a question relating to the present tense
grammar_tense_subjunctive: a question relating to the subjunctive tense
grammar_verbs_modal_verbs: a question relating to modal verbs
grammar_preposition_conjunction: a question relating to the correct use
of prepositions or conjunctions
grammar_cases: a question relating to nominative,genitive,dative, or accusative
reading_comprehension_true_false: a reading comprehension question where the answer
is either true or false
reading_comprehension_simple: a reading comprehension question that does not require to
understand the entire text excerpt to answer correctly
reading_comprehension_complex: a reading comprehension question that requires a deeper
understanding of the entire text excerpt to answer correctly
```

I   LuxGen Evaluation Results using LLM-as-a-Judge metrics

Table 11 shows the full evaluation results of the LuxGen experiments over three runs as well as the average performances.

Model	Size	A1				A2				B1				B2				C1				C2			
		Voc.	Gra.	RC	CC	Voc.	Gra.	RC	CC	Voc.	Gra.	RC	CC	Voc.	Gra.	RC	CC	Voc.	Gra.	RC	CC	Voc.	Gra.	RC	CC
Qwen 2	0.5	38.5	26.9	23.1	19.2	34.6	11.5	19.2	23.1	32.0	15.4	23.1	23.1	25.0	17.6	19.2	30.8	16.7	20.7	30.8	20.0	7.7	26.1	11.5	19.2
Llama 3.2	1	15.4	34.6	34.6	19.2	26.9	11.5	19.2	19.2	32.0	46.2	19.2	15.4	21.4	20.6	19.2	23.1	16.7	20.7	11.5	28.0	15.4	8.7	19.2	7.7
Gemma 3	1	38.5	46.2	50.0	46.2	19.2	34.6	50.0	42.3	44.0	42.3	34.6	34.6	14.3	44.1	50.0	53.8	29.2	20.7	26.9	24.0	19.2	39.1	38.5	38.5
Qwen 2	1.5	34.6	38.5	42.3	15.4	38.5	26.9	23.1	23.1	28.0	30.8	19.2	23.1	28.6	38.2	23.1	34.6	25.0	13.8	19.2	28.0	23.1	21.7	23.1	26.9
StableLM 2	1.6	30.8	34.6	7.7	15.4	19.2	23.1	0.0	15.4	20.0	30.8	11.5	23.1	25.0	23.5	11.5	3.8	20.8	24.1	3.8	12.0	23.1	34.8	0.0	11.5
EuroLLM	1.7	19.2	15.4	11.5	23.1	23.1	23.1	15.4	23.1	24.0	11.5	11.5	3.8	21.4	29.4	23.1	19.2	33.3	27.6	15.4	28.0	23.1	13.0	23.1	11.5
Gemma 2	2	38.5	46.2	38.5	34.6	38.5	23.1	34.6	46.2	44.0	19.2	30.8	30.8	17.9	32.4	30.8	50.0	29.2	31.0	19.2	32.0	38.5	26.1	23.1	26.9
Llama 3.2	3	34.6	38.5	46.2	34.6	38.5	23.1	26.9	53.8	32.0	38.5	26.9	23.1	32.1	26.5	42.3	19.2	37.5	31.0	23.1	40.0	15.4	34.8	30.8	19.2
Phi 3	3.8	26.9	46.2	57.7	50.0	34.6	23.1	38.5	50.0	24.0	23.1	23.1	38.5	25.0	26.5	15.4	38.5	33.3	24.1	23.1	32.0	23.1	8.7	19.2	19.2
Phi 3.5	3.8	34.6	50.0	30.8	42.3	26.9	30.8	15.4	38.5	8.0	19.2	11.5	7.7	14.3	8.8	11.5	7.7	12.5	6.9	7.7	4.0	7.7	4.3	15.4	15.4
Gemma 3	4	65.4	26.9	69.2	57.7	38.5	38.5	34.6	50.0	28.0	34.6	30.8	61.5	57.1	29.4	42.3	61.5	33.3	17.2	53.8	44.0	34.6	39.1	15.4	23.1
Qwen 2	7	42.3	26.9	69.2	53.8	23.1	38.5	38.5	46.2	28.0	23.1	15.4	61.5	28.6	35.3	38.5	42.3	58.3	24.1	19.2	40.0	34.6	39.1	38.5	38.5
Llama 2	7	26.9	34.6	53.8	30.8	46.2	23.1	34.6	50.0	24.0	26.9	26.9	19.2	46.4	32.4	30.8	30.8	29.2	17.2	23.1	36.0	26.9	26.1	38.5	30.8
WizardLM 2	7	42.3	34.6	65.4	34.6	50.0	34.6	26.9	42.3	24.0	15.4	15.4	30.8	42.9	23.5	30.8	30.8	29.2	37.9	23.1	24.0	26.9	47.8	11.5	34.6
Mistral	7	30.8	26.9	46.2	38.5	23.1	23.1	42.3	46.2	34.0	34.6	30.8	34.6	28.6	23.5	26.9	30.8	41.7	27.6	26.1	36.0	23.1	26.1	26.1	26.9
Aya-23	8	38.5	38.5	46.2	38.5	30.8	19.2	30.8	42.3	36.0	19.2	26.9	38.5	25.0	32.4	26.9	42.3	29.2	41.4	23.1	32.0	30.8	26.1	38.5	30.8
Llama 3.1	8	50.0	61.5	57.7	57.7	30.8	30.8	26.9	46.2	16.0	38.5	19.2	57.7	32.1	23.5	53.8	26.9	20.8	20.7	50.0	32.0	30.8	26.1	30.8	46.2
Llama 3	8	42.3	42.3	50.0	46.2	30.8	30.8	26.9	53.8	48.0	30.8	30.8	34.6	25.0	38.2	42.3	38.5	45.8	17.2	50.0	28.0	23.1	39.1	30.8	23.1
DeepSeek-R1	8	69.2	42.3	57.7	46.2	46.2	38.5	26.9	65.4	48.0	42.3	30.8	53.8	35.7	38.2	46.2	38.5	29.2	24.1	50.0	36.0	15.4	21.7	30.8	46.2
GLM 4	9	57.7	42.3	69.2	50.0	50.0	19.2	42.3	69.2	56.0	15.4	26.9	53.8	60.7	26.5	50.0	50.0	54.2	34.5	46.2	44.0	38.5	26.1	26.9	50.0
EuroLLM	9	53.8	30.8	57.7	34.6	50.0	38.5	42.3	50.0	32.0	42.3	30.8	26.9	39.3	23.5	34.6	42.3	41.7	31.0	23.1	32.0	23.1	26.1	26.9	26.9
Gemma 2	9	76.9	50.0	61.5	46.2	61.5	38.5	30.8	57.7	36.0	26.9	34.6	46.2	64.3	38.2	38.5	38.5	58.3	20.7	42.3	40.0	34.6	30.4	42.3	30.8
Mistral-Nemo	12	61.5	50.0	53.8	46.2	34.6	26.9	38.5	46.2	36.0	15.4	23.1	38.5	28.6	23.5	38.5	46.2	37.5	24.1	26.9	32.0	19.2	26.1	26.9	11.5
StableLM 2	12	42.3	15.4	30.8	23.1	4.62	19.2	34.6	42.3	44.0	11.5	19.2	42.3	21.4	17.6	50.0	30.8	37.5	17.2	19.2	40.0	38.5	21.7	30.8	23.1
Gemma 3	12	76.9	30.8	73.1	69.2	80.8	42.3	46.2	65.4	64.0	46.2	42.3	61.5	32.1	29.4	57.7	57.7	54.2	24.1	61.5	52.0	34.6	21.7	46.2	53.8
Llama 2	13	34.6	38.5	15.4	23.1	19.2	11.5	15.4	11.5	8.0	34.6	19.2	30.8	32.1	20.6	30.8	23.1	25.0	24.1	23.1	20.0	34.6	30.4	23.1	19.2
Phi 3	14	42.3	42.3	50.0	46.2	38.5	42.3	30.8	42.3	40.0	38.5	30.8	42.3	46.4	35.3	34.6	42.3	41.7	34.5	30.8	20.0	11.5	21.7	19.2	34.6
Phi 4	14	50.0	50.0	65.4	50.0	65.4	42.3	50.0	50.0	36.0	42.3	34.6	57.7	57.1	44.1	46.2	30.8	41.7	24.1	34.6	40.0	26.9	17.4	42.3	46.2
Medium-sized Models ($> 15B \& \leq 200B$)																									
Mistral Small	22	46.2	34.6	69.2	57.7	57.7	19.2	34.6	73.1	44.0	19.2	15.4	46.2	42.9	38.2	30.8	46.2	45.8	31.0	38.5	40.0	11.5	34.8	19.2	38.5
Gemma 2	27	65.4	46.2	80.8	73.1	73.1	50.0	57.7	73.1	68.0	38.5	42.3	69.2	60.7	26.5	57.7	42.3	62.5	24.1	50.0	68.0	30.8	34.8	53.8	46.2
Gemma 3	27	76.9	46.2	84.6	92.3	100.0	57.7	61.5	88.5	76.0	61.5	42.3	69.2	67.9	52.9	65.4	57.7	75.0	48.3	61.5	60.0	38.5	43.5	34.6	65.4
QWQ	32	80.8	46.2	61.5	88.5	61.5	42.3	30.8	61.5	76.0	42.3	34.6	65.4	50.0	38.2	53.8	65.4	62.5	20.7	34.6	40.0	38.5	39.1	34.6	65.4
Aya-23	35	34.6	34.6	61.5	42.3	46.2	15.4	38.5	50.0	40.0	46.2	30.8	42.3	57.1	17.6	46.2	26.9	25.0	31.0	34.6	44.0	34.6	39.1	30.8	34.6
Command-R	35	42.3	53.8	61.5	46.2	46.2	19.2	38.5	50.0	36.0	26.9	30.8	38.5	35.7	35.3	46.2	26.9	37.5	27.6	38.5	40.0	38.5	43.5	46.2	23.1
Alfred	40	30.8	38.5	61.5	38.5	46.2	19.2	26.9	50.0	24.0	30.8	26.9	38.5	50.0	32.4	50.0	50.0	45.8	31.0	30.4	36.0	26.9	34.8	30.8	34.6
Mixtral	56	50.0	38.5	61.5	50.0	50.0	19.2	42.3	53.8	48.0	19.2	26.9	42.3	50.0	38.2	34.6	34.6	50.0	13.8	23.1	44.0	34.6	34.8	30.8	19.2
Llama 2	70	23.1	34.6	57.7	46.2	34.6	26.9	30.8	42.3	24.0	26.9	30.8	34.6	39.3	35.3	30.8	53.8	25.0	24.1	26.9	28.0	26.9	21.7	46.2	61.5
Llama 3	70	61.5	38.5	65.4	50.0	50.0	38.5	38.5	50.0	36.0	38.5	38.5	38.5	42.9	47.1	38.5	50.0	58.3	31.0	26.9	32.0	26.9	52.2	26.9	50.0
Llama 3.1	70	57.7	38.5	69.2	57.7	84.6	34.6	42.3	65.4	56.0	53.8	34.6	53.8	71.4	44.1	46.2	50.0	58.3	48.3	42.3	40.0	34.6	56.5	38.5	38.5
DeepSeek-R1	70	76.9	53.8	65.4	61.5	69.2	30.8	30.8	73.1	68.0	61.5	42.3	53.8	67.9	35.3	50.0	69.2	62.5	41.4	38.5	56.0	42.3	30.4	42.3	50.0
Qwen 2	72	65.4	53.8	65.4	65.4	65.4	34.6	42.3	61.5	44.0	34.6	42.3	46.2	57.1	41.2	57.7	53.8	62.5	24.1	42.3	40.0	30.8	30.4	46.2	53.8
Command-R+	104	57.7	38.5	61.5	53.8	57.7	19.2	38.5	42.3	57.7	30.8	30.8	46.2	42.9	47.1	50.0	50.0	45.8	24.1	23.1	28.0	30.8	30.4	46.2	38.5
Mistral-Large	123	84.6	57.7	73.1	50.0	65.4	34.6	38.5	61.5	44.0	42.3	30.8	53.8	75.0	38.2	50.0	50.0	66.7	34.5	26.9	48.0	53.8	39.1	34.6	50.0
Mixtral	176	57.7	57.7	73.1	61.5	57.7	50.0	38.5	73.1	44.0	30.8	38.5	53.8	60.7	35.3	34.6	38.5	41.7	34.5	38.5	44.0	34.6	34.8	38.5	57.7
WizardLM 2	176	53.8	50.0	65.4	65.4	42.3	30.8	30.8	57.7	32.0	38.5	38.5	53.8	50.0	41.2	46.2	34.6	37.5	31.0	34.6	44.0	26.9	34.8	38.5	38.5
Large Models ($> 200B$)																									
Llama 3.1	405	92.3	57.7	80.8	84.6	26.9	38.5	34.6	57.7	72.0	46.2	26.9	50.0	67.9	47.1	65.4	61.5	79.2	37.9	57.7	52.0	42.3	30.4	61.5	50.0
DeepSeek-R1	671	96.2	84.6	96.2	92.3	100.0	65.4	76.9	92.3	88.0	76.9	42.3	88.5	89.3	58.8	80.8	76.9	83.3	65.5	73.1	72.0	96.2	100.0	73.1	57.7
ChatGPT 3.5 S	unk	100.0	76.9	100.0	92.3	100.0	84.6	88.5	88.5	96.0	92.3	38.5	96.2	89.3	76.5	80.8	88.5	87.5	72.4	76.9	84.0	43.5	43.5	76.9	65.4
Claude 3.5 S	unk	100.0	80.8	100.0	88.5	96.2	88.5	88.5	96.2	96.0	92.3	38.5	96.2	85.7	82.4	84.6	96.2	87.5	55.2	80.8	72.0	61.5	78.3	69.2	69.2
ChatGPT4o	unk	96.2	84.6	100.0	92.3	100.0	73.1	80.8	96.2	96.0	84.6	38.5	96.2	92.9	79.4	80.8	84.6	83.3	55.2	73.1	88.0	61.5	52.2	65.4	61.5
ChatGPT4o m	unk	96.2	73.1	100.0	92.3	100.0	84.6	80.8	96.2	88.0	84.6	42.3	84.6	75.0	55.9	57.7	57.7	75.0	62.1	73.1	52.0	34.8	34.8	42.3	50.0
Gemini 2.0 F	unk	88.5	76.9	96.2	96.2	96.2	65.4	80.8	96.2	88.0	26.9	42.3	84.6	89.3	67.6	80.8	88.5	87.5	62.1	80.8	76.0	42.3	52.2	61.5	61.5
LeChat	unk	80.8	26.9	3.8	57.7	73.1	50.0	38.5	53.8	32.0	38.5	34.6	50.0	71.4	32.4	46.2	53.8	54.2	41.4	26.9	44.0	34.6	30.4	34.6	30.8

Table 8: Detailed results on experiments with coarse-grained categories

Model	Size	V_Idioms	V_Noun	V_Verb	V_Adj.	V_Native	G_Gender	G_Pron.	G_Verb	G_Adj.	G_Tense	G_Past	G_Present	G_Subj.	G_Modal	G_Prep.	G_Cases	RC_TF	RC_S.	RC_C.
Small Models (≤15B)																				
Qwen 2	0.5	14.3	25.0	22.7	39.1	16.7	13.5	15.0	22.2	0.0	24.5	20.0	30.8	28.6	14.3	22.2	20.5	42.8	0.0	1.5
Llama 3.2	1	14.3	26.2	20.5	17.4	33.3	21.6	10.0	22.2	11.1	22.4	25.0	30.8	21.4	0.0	31.5	17.9	26.3	13.6	18.2
Gemma 3	1	33.3	32.1	18.2	21.7	33.3	35.1	20.0	38.9	55.6	34.7	40.0	46.2	21.4	28.6	35.2	35.9	58.6	29.5	34.8
Qwen 2	1.5	33.3	31.0	27.3	30.4	16.7	32.4	50.0	20.4	22.2	20.4	30.0	23.1	0.0	0.0	33.3	30.8	38.2	9.1	13.6
StableLM 2	1.6	19.0	16.7	22.7	17.4	16.7	13.5	10.0	24.1	11.1	26.5	20.0	23.1	28.6	28.6	27.8	12.8	10.5	4.5	9.1
EuroLLM	1.7	19.0	25.0	13.6	43.5	16.7	13.5	15.0	18.5	11.1	16.3	25.0	15.4	7.1	0.0	33.3	15.4	25.7	11.4	9.1
Gemma 2	2	33.3	35.7	27.3	43.5	33.3	37.8	35.0	31.5	22.2	32.7	40.0	23.1	35.7	0.0	25.9	23.1	44.7	18.2	21.2
Llama 3.2	2	28.6	34.5	27.3	34.8	33.3	18.9	15.0	27.8	44.4	24.5	20.0	38.5	21.4	14.3	35.2	20.5	39.5	22.7	30.3
Phi 3	3	23.8	25.0	36.4	21.7	33.3	27.0	35.0	24.1	11.1	26.5	25.0	30.8	14.3	42.9	25.9	20.5	40.1	29.5	33.3
Phi 3.5	3.8	9.5	17.9	11.4	26.1	0.0	16.2	20.0	24.1	0.0	22.4	20.0	30.8	14.3	42.9	18.5	12.8	20.4	20.5	16.7
Gemma 3	4	33.3	51.2	50.0	30.4	50.0	35.1	20.0	29.6	22.2	28.6	25.0	46.2	7.1	14.3	33.3	30.8	44.1	61.4	40.9
Qwen 2	7	33.3	38.1	34.1	30.4	50.0	37.8	40.0	25.9	33.3	16.3	15.0	38.5	21.4	42.9	25.9	41.0	45.4	40.9	37.9
Llama 2	7	28.6	32.1	27.3	34.8	33.3	37.8	20.0	22.2	33.3	26.5	25.0	38.5	0.0	0.0	27.8	28.2	46.7	22.7	33.3
WizardLM 2	7	19.0	33.3	40.9	34.8	16.7	40.5	30.0	25.9	22.2	26.5	25.0	15.4	50.0	42.9	29.6	41.0	35.5	15.9	34.8
Mistral	7	33.3	38.1	25.0	21.7	16.7	27.0	35.0	27.8	22.2	24.5	35.0	15.4	14.3	28.6	24.1	30.8	42.8	25.0	37.9
Aya-23	8	47.6	34.5	27.3	34.8	16.7	37.8	30.0	16.7	55.6	14.3	5.0	15.4	21.4	14.3	33.3	38.5	40.1	45.5	40.9
Llama 3.1	8	33.3	29.8	34.1	21.7	16.7	37.8	40.0	25.9	22.2	28.6	30.0	38.5	7.1	28.6	35.2	30.8	45.4	31.8	42.4
Llama 3	8	28.6	35.7	34.1	26.1	16.7	32.4	35.0	22.2	33.3	24.5	25.0	38.5	0.0	14.3	38.9	33.3	42.1	31.8	43.9
DeepSeek-R1	8	33.3	44.0	31.8	52.2	0.0	27.0	35.0	40.7	11.1	40.8	35.0	38.5	42.9	28.6	38.9	20.5	42.1	43.2	45.5
GLM 4	9	57.1	56.0	52.3	43.5	33.3	24.3	20.0	33.3	11.1	30.6	30.0	30.8	28.6	14.3	25.9	25.6	46.1	54.5	56.1
EuroLLM	9	38.1	42.9	27.3	60.9	50.0	32.4	50.0	29.6	22.2	26.5	30.0	30.8	7.1	28.6	33.3	33.3	40.8	38.6	40.9
Gemma 2	9	57.1	61.9	50.0	65.2	33.3	29.7	30.0	37.0	11.1	40.8	20.0	53.8	42.9	71.4	35.2	23.1	44.7	47.7	45.5
Mistral-Nemo	12	28.6	42.9	31.8	17.4	16.7	24.3	30.0	29.6	22.2	28.6	25.0	23.1	35.7	42.9	29.6	15.4	40.8	27.3	36.4
StableLM 2	12	23.8	28.6	25.0	30.4	16.7	8.1	5.0	3.7	11.1	4.1	5.0	0.0	0.0	14.3	25.9	7.7	30.9	27.3	24.2
Gemma 3	12	47.6	65.5	56.8	73.9	33.3	29.7	25.0	25.9	33.3	24.5	30.0	23.1	21.4	28.6	42.6	20.5	53.9	77.3	60.6
Llama 2	13	38.1	32.1	25.0	13.0	50.0	35.1	10.0	18.5	44.4	20.4	20.0	30.8	7.1	0.0	33.3	23.1	23.7	25.0	24.2
Phi 3	14	19.0	35.7	34.1	30.4	16.7	35.1	50.0	29.6	33.3	26.5	35.0	30.8	14.3	42.9	40.7	33.3	40.8	29.5	39.4
Phi 4	14	23.8	48.8	45.5	47.8	33.3	35.1	50.0	42.6	11.1	42.9	30.0	61.5	35.7	57.1	38.9	30.8	47.4	59.1	51.5
Medium-sized Models (>15B & ≤200B)																				
Mistral Small	22	28.6	50.0	36.4	26.1	16.7	16.2	25.0	35.2	33.3	38.8	35.0	46.2	42.9	42.9	27.8	15.4	48.0	38.6	50.0
Gemma 2	27	47.6	66.7	52.3	60.9	50.0	35.1	45.0	29.6	11.1	28.6	25.0	30.8	21.4	42.9	46.3	35.9	51.3	77.3	72.7
Gemma 3	27	38.1	75.0	56.8	87.0	50.0	54.1	55.0	50.0	44.4	51.0	55.0	38.5	35.7	57.1	61.1	46.2	61.8	70.5	69.7
QWQ	32	47.6	66.7	45.5	60.9	33.3	40.5	40.0	42.6	11.1	42.9	45.0	38.5	42.9	71.4	35.2	35.9	40.8	70.5	63.6
Aya-23	35	28.6	44.0	31.8	47.8	16.7	32.4	30.0	29.6	22.2	26.5	25.0	23.1	21.4	42.9	31.5	30.8	39.5	43.2	50.0
Command-R	35	38.1	44.0	38.6	39.1	16.7	32.4	35.0	33.3	44.4	36.7	25.0	69.2	21.4	28.6	35.2	35.9	40.1	34.1	53.0
Alfred	40	23.8	32.1	50.0	34.8	33.3	29.7	20.0	37.0	11.1	36.7	35.0	53.8	21.4	28.6	25.9	35.9	44.7	36.4	30.3
Mixtral	8x7	28.6	46.4	31.8	43.5	16.7	27.0	30.0	24.1	22.2	26.5	20.0	38.5	14.3	42.9	35.2	23.1	37.5	34.1	51.5
Llama 2	70	33.3	32.1	45.5	17.4	33.3	27.0	20.0	24.1	33.3	24.5	25.0	46.2	7.1	0.0	33.3	25.6	48.0	34.1	39.4
Llama 3	70	52.4	58.3	56.8	56.5	33.3	35.1	25.0	31.5	33.3	30.6	25.0	38.5	14.3	28.6	37.0	33.3	42.8	50.0	48.5
Llama 3.1	70	28.6	63.1	56.8	65.2	33.3	35.1	35.0	48.1	44.4	46.9	40.0	38.5	57.1	57.1	53.7	30.8	47.4	52.3	54.5
DeepSeek-R1	70	47.6	73.8	56.8	47.8	16.7	29.7	40.0	46.3	11.1	49.0	55.0	38.5	42.9	42.9	51.9	17.9	46.1	65.9	66.7
Qwen 2	72	33.3	56.0	50.0	47.8	0.0	40.5	35.0	38.9	33.3	38.8	30.0	38.5	57.1	57.1	35.2	33.3	45.4	54.5	60.6
Command-R+	104	23.8	47.6	43.2	52.2	50.0	21.6	0.0	38.9	11.1	36.7	30.0	46.2	35.7	42.9	44.4	5.1	46.1	43.2	40.9
Mistral-Large	123	42.9	75.0	56.8	56.5	50.0	45.9	50.0	40.7	33.3	40.8	35.0	61.5	21.4	14.3	37.0	35.9	44.1	68.2	50.0
Mixtral	8x22	38.1	48.8	54.5	56.5	33.3	54.1	45.0	38.9	44.4	38.8	35.0	53.8	21.4	42.9	35.2	43.6	45.4	52.3	54.5
WizardLM 2	8x22	28.6	47.6	36.4	26.1	16.7	29.7	35.0	37.0	33.3	34.7	40.0	53.8	14.3	0.0	48.1	23.1	46.1	52.3	51.5
Large Models (>200B)																				
Llama 3.1	405	42.9	67.9	68.0	47.8	33.3	37.8	40.0	40.7	22.2	36.7	30.0	53.8	28.6	14.3	55.6	33.3	55.9	63.6	59.1
DeepSeek-R1	671	81.0	94.0	93.2	91.3	100.0	70.3	65.0	68.5	55.6	69.4	55.0	84.6	71.4	100.0	81.5	64.1	79.6	86.4	84.8
ChatGPT 3.5	unk	71.4	91.7	90.9	100.0	50.0	73.0	60.0	75.9	44.4	77.6	75.0	92.3	71.4	71.4	75.9	69.2	85.5	88.6	83.3
Claude 3.5 S	unk	42.9	85.7	88.6	100.0	50.0	70.3	75.0	90.7	66.7	91.8	85.0	100.0	92.9	85.7	85.2	69.2	88.2	86.4	86.4
ChatGPT 4o	unk	52.4	86.9	90.9	95.7	66.7	78.4	60.0	75.9	55.6	77.6	70.0	92.3	78.6	85.7	74.1	64.1	83.6	86.4	83.3
ChatGPT 4o m	unk	38.1	79.8	68.2	87.0	16.7	56.8	65.0	53.7	22.2	55.1	70.0	76.9	42.9	71.4	64.8	51.3	61.8	86.4	81.8
Gemini 2.0 F	unk	33.3	81.0	84.1	87.0	50.0	70.3	70.0	75.9	66.7	79.6	75.0	84.6	71.4	85.7	68.5	53.8	80.9	86.4	84.8
LeChat	unk	38.1	65.5	61.4	47.8	33.3	24.3	50.0	35.2	44.4	34.7	30.0	38.5	35.7	42.9	35.2	35.9	39.5	40.9	47.0

Table 9: Complete results of experiments on fine-grained categories

Category name	Category Description	#
V_idiom	a question relating to idioms or metaphors	21
V_noun	a vocabulary question relating to a noun	84
V_verb	a vocabulary question relating to a verb	44
V_adjective	a vocabulary question relating to an adjective	23
V_native	a vocabulary question where the correct answer is a word exclusive to Luxembourgish	6
G_gender	a question relating to determining the gender of a determinant, adjective, or pronoun	37
G_pronouns	a question relating to pronouns	20
G_verbs	a question relating to conjugations of verbs	55
G_adjective	a question relating to adjectives	9
G_tense	a question relating to the correct use of tenses	50
G_past	a question relating to the past tense	21
G_present	a question relating to the present tense	13
G_subjunctive	a question relating to the subjunctive tense	14
G_modal	a question relating to modal verbs	7
G_preposition	a question relating to the correct use of prepositions or conjunctions	54
G_cases	a question relating to nominative,genitive,dative, or accusative	39
RC_TF	a reading comprehension question where the answer is either true or false	152
RC_Simple	a reading comprehension question that does not require to understand the entire text excerpt to answer correctly	72
RC_Complex	a reading comprehension question requiring a deeper understanding of the entire text excerpt to answer correctly	86

Table 10: Statistics for fine-grained categories for exam questions.

Table 11: Detailed LuxGen Evaluation Results

Model	Size	Exam Score	Small Description								News Headline							
			Grammar				Adequacy				Grammar				Adequacy			
			Run 1	Run 2	Run 3	Average	Run 1	Run 2	Run 3	Average	Run 1	Run 2	Run 3	Average	Run 1	Run 2	Run 3	Average
Small Models (≤ 15B)																		
Qwen 2	0.5	0.220	0.174	0.318	0.290	0.261	0.451	0.340	0.330	0.374	0.124	0.160	0.352	0.212	0.303	0.303	0.433	0.347
Llama 3.2	1	0.044	0.534	0.520	0.582	0.545	0.521	0.572	0.550	0.548	0.338	0.256	0.418	0.337	0.228	0.257	0.525	0.337
Gemma 3	1	0.005	0.700	0.700	0.800	0.733	0.630	0.790	0.590	0.670	0.300	0.250	0.010	0.187	0.350	0.290	0.260	0.300
Qwen 2	1.5	0.286	0.538	0.433	0.502	0.491	0.553	0.462	0.442	0.485	0.226	0.162	0.406	0.265	0.398	0.377	0.492	0.422
StableLM 2	1.6	0.094	0.025	0.232	0.332	0.196	0.284	0.298	0.212	0.265	0.214	0.256	0.390	0.287	0.360	0.285	0.513	0.386
EuroLLM	1.7	0.006	0.090	0.030	0.170	0.0967	0.220	0.370	0.130	0.240	0.100	0.220	0.000	0.107	0.210	0.210	0.220	0.213
Gemma 2	2	0.278	0.456	0.642	0.568	0.555	0.533	0.535	0.658	0.575	0.304	0.408	0.438	0.383	0.608	0.492	0.495	0.532
Llama 3.2	3	0.321	0.830	0.782	0.812	0.808	0.689	0.737	0.648	0.691	0.692	0.702	0.656	0.683	0.653	0.647	0.695	0.665
Phi 3	3.8	0.300	0.045	0.362	0.477	0.294	0.391	0.320	0.362	0.358	0.220	0.202	0.434	0.285	0.327	0.320	0.600	0.416
Phi 3.5	3.8	0.101	0.267	0.258	0.287	0.271	0.243	0.150	0.147	0.180	0.118	0.065	0.488	0.224	0.240	0.328	0.625	0.398
Gemma 3	4	0.004	0.760	0.720	0.810	0.763	0.650	0.800	0.630	0.693	0.650	0.260	0.020	0.310	0.550	0.320	0.270	0.380
Qwen 2	7	0.373	0.456	0.725	0.687	0.623	0.644	0.660	0.688	0.664	0.380	0.336	0.546	0.421	0.597	0.578	0.548	0.574
Llama 2	7	0.141	0.054	0.275	0.238	0.189	0.296	0.275	0.225	0.265	0.146	0.180	0.424	0.250	0.425	0.408	0.522	0.452
WizardLM 2	7	0.267	0.140	0.440	0.585	0.388	0.529	0.572	0.432	0.511	0.298	0.248	0.466	0.337	0.505	0.553	0.615	0.558
Mistral	7	0.325	0.242	0.767	0.650	0.553	0.634	0.695	0.680	0.670	0.518	0.474	0.548	0.513	0.548	0.537	0.633	0.573
Aya-23	8	0.322	0.377	0.470	0.708	0.518	0.510	0.515	0.448	0.491	0.086	0.142	0.446	0.225	0.340	0.372	0.557	0.423
Llama 3.1	8	0.384	0.655	0.658	0.755	0.689	0.610	0.487	0.620	0.572	0.684	0.644	0.704	0.677	0.528	0.643	0.603	0.592
Llama 3	8	0.357	0.624	0.690	0.722	0.678	0.630	0.643	0.627	0.633	0.322	0.310	0.554	0.395	0.600	0.578	0.630	0.603
DeepSeek-R1	8	0.338	0.628	0.592	0.667	0.629	0.533	0.507	0.482	0.507	0.576	0.458	0.532	0.522	0.637	0.592	0.543	0.591
GLM 4	9	0.421	0.721	0.783	0.795	0.766	0.591	0.590	0.715	0.632	0.322	0.252	0.402	0.325	0.580	0.658	0.578	0.606
EuroLLM	9	0.002	0.250	0.560	0.300	0.370	0.590	0.750	0.210	0.517	0.150	0.240	0.010	0.133	0.430	0.250	0.240	0.307
Gemma 2	9	0.360	0.622	0.807	0.818	0.749	0.623	0.645	0.762	0.677	0.738	0.584	0.652	0.658	0.730	0.678	0.550	0.653
Mistral-Nemo	12	0.340	0.698	0.737	0.753	0.729	0.663	0.718	0.698	0.693	0.578	0.502	0.572	0.551	0.707	0.752	0.677	0.712
StableLM 2	12	0.235	0.263	0.577	0.348	0.396	0.437	0.320	0.325	0.361	0.202	0.190	0.442	0.278	0.323	0.432	0.572	0.442
Gemma 2	12	0.128	0.800	0.850	0.820	0.823	0.670	0.820	0.740	0.743	0.780	0.270	0.130	0.393	0.680	0.330	0.290	0.433
Llama 2	13	0.147	0.140	0.438	0.315	0.298	0.286	0.230	0.295	0.270	0.200	0.236	0.512	0.316	0.460	0.468	0.583	0.504
Phi 3	14	0.370	0.124	0.358	0.435	0.306	0.331	0.328	0.242	0.300	0.212	0.152	0.422	0.262	0.307	0.263	0.582	0.384
Phi 4	14	0.028	0.170	0.900	0.800	0.623	0.690	0.770	0.740	0.733	0.600	0.460	0.330	0.463	0.510	0.630	0.320	0.487
Medium-sized Models (> 15B & ≤ 200B)																		
Mistral Small	22	0.024	0.675	0.843	0.848	0.789	0.633	0.620	0.692	0.648	0.812	0.772	0.738	0.774	0.750	0.780	0.620	0.717
Gemma 2	27	0.066	0.648	0.853	0.882	0.794	0.663	0.728	0.808	0.733	0.776	0.674	0.730	0.727	0.780	0.760	0.607	0.716
Gemma 3	27	0.245	0.850	0.860	0.820	0.843	0.680	0.840	0.740	0.753	0.650	0.280	0.300	0.410	0.720	0.510	0.300	0.510
QWQ	32	0.102	0.190	0.150	0.800	0.380	0.700	0.630	0.490	0.607	0.500	0.470	0.530	0.500	0.250	0.300	0.370	0.307
Aya-23	35	0.036	0.711	0.620	0.667	0.666	0.631	0.697	0.573	0.634	0.450	0.374	0.508	0.444	0.558	0.558	0.625	0.581
Command-R	35	0.021	0.517	0.653	0.745	0.638	0.621	0.658	0.667	0.649	0.182	0.423	0.642	0.416	0.617	0.688	0.670	0.658
Alfred	40	0.011	0.206	0.402	0.503	0.370	0.381	0.420	0.405	0.402	0.272	0.350	0.272	0.298	0.495	0.573	0.342	0.470
Mixtral	8x7	0.003	0.226	0.470	0.503	0.400	0.454	0.437	0.512	0.468	0.292	0.258	0.504	0.351	0.630	0.638	0.663	0.644
Llama 2	70	0.005	0.464	0.632	0.592	0.562	0.599	0.505	0.623	0.576	0.152	0.212	0.482	0.282	0.432	0.495	0.622	0.516
Llama 3	70	0.101	0.788	0.815	0.860	0.821	0.719	0.778	0.763	0.753	0.336	0.294	0.580	0.403	0.735	0.722	0.718	0.725
Llama 3.1	70	0.121	0.842	0.865	0.895	0.867	0.731	0.818	0.800	0.783	0.712	0.730	0.810	0.751	0.777	0.800	0.700	0.759
DeepSeek-R1	70	0.107	0.872	0.865	0.838	0.858	0.597	0.767	0.652	0.672	0.772	0.630	0.724	0.709	0.762	0.785	0.618	0.722
Qwen 2	72	0.068	0.776	0.803	0.708	0.762	0.684	0.652	0.633	0.656	0.584	0.516	0.730	0.610	0.747	0.765	0.655	0.722
Command-R+	104	0.057	0.705	0.777	0.818	0.737	0.627	0.683	0.700	0.670	0.646	0.682	0.754	0.694	0.697	0.693	0.693	0.722
Mistral-Large	123	0.076	0.752	0.777	0.832	0.787	0.663	0.682	0.752	0.699	0.852	0.790	0.822	0.821	0.827	0.818	0.743	0.796
Mixtral	8x22	0.011	0.515	0.622	0.790	0.642	0.566	0.567	0.528	0.554	0.620	0.604	0.700	0.641	0.780	0.782	0.700	0.754
WizardLM 2	8x22	0.037	0.216	0.520	0.428	0.388	0.407	0.360	0.392	0.386	0.404	0.390	0.600	0.465	0.720	0.740	0.658	0.706
Large Models (> 200B)																		
Llama 3.1	405	0.552	0.776	0.762	0.755	0.764	0.666	0.695	0.623	0.661	0.874	0.814	0.854	0.847	0.800	0.803	0.742	0.788
DeepSeek-R1	671	0.804	0.980	0.857	0.890	0.909	0.630	0.705	0.760	0.698	0.866	0.658	0.653	0.726	0.817	0.760	0.647	0.754
ChatGPT 3.5	unk	0.809	0.632	0.833	0.750	0.738	0.659	0.718	0.682	0.686	0.610	0.716	0.614	0.647	0.595	0.670	0.643	0.636
Claude 3.5 Sonnet	unk	0.834	0.874	0.752	0.875	0.834	0.739	0.667	0.780	0.728	0.884	0.856	0.740	0.827	0.862	0.860	0.777	0.833
ChatGPT 4o	unk	0.795	0.873	0.902	0.910	0.895	0.726	0.673	0.760	0.720	0.728	0.834	0.720	0.761	0.833	0.845	0.765	0.814
ChatGPT 4o mini	unk	0.666	0.863	0.735	0.858	0.819	0.500	0.608	0.680	0.596	0.766	0.754	0.684	0.735	0.705	0.718	0.720	0.714
Gemini 2.0 Flash	unk	0.768	0.814	0.792	0.815	0.807	0.606	0.555	0.512	0.557	0.544	0.550	0.512	0.535	0.698	0.777	0.675	0.717
LeChat	unk	0.438	0.639	0.505	0.543	0.562	0.444	0.630	0.597	0.557	0.778	0.578	0.455	0.604	0.705	0.725	0.597	0.676

	Claude-G	Claude-A	METEOR	BERTScore
Claude-G	1.00	0.86	0.71	0.70
Claude-A	0.86	1.00	0.56	0.55
METEOR	0.71	0.56	1.00	0.95
BERTScore	0.70	0.55	0.95	1.00

(a) Pearson Correlation Coefficient

	Claude-G	Claude-A	METEOR	BERTScore
Claude-G	/	11.90	7.27	7.07
Claude-A	11.90	/	4.82	4.72
METEOR	7.27	4.82	/	22.60
BERTScore	7.07	4.72	22.60	/

(b) T-Scores

	Claude-G	Claude-A	METEOR	BERTScore
Claude-G	/	2.472E-16	2.050E-09	4.241E-09
Claude-A	2.472E-16	/	1.322E-05	1.859E-05
METEOR	2.051E-09	1.322E-05	/	3.134E-28
BERTScore	4.241E-09	1.859E-05	3.134E-28	/

(c) P-Values

Table 12: Correlation tests for different metrics on the headline generation task.

J Comparison of LLM-as-a-Judge and traditional metrics

In this section, we compare our LLM-as-a-Judge metrics to the BERTScore and METEOR scores in order to assess the usefulness of our novel metrics. Figure 3 and 4 show performances of every studied LLM on the Headline Generation and Short Description tasks using the four different metrics, respectively. We observe that while the scores are different for each metric they appear to be highly correlated to each other. This is further corroborated by Tables 12a through 13c which contain correlation matrices with Pearson Correlation Coefficients, t-scores, and p-values between every metric, showing strong correlations between the traditional metrics and the LLM-as-a-Judge metrics, with the significance tests showing the correlations to be significant at a significance level $\alpha = 0.01$.

	Claude-G	Claude-A	METEOR	BERTScore
Claude-G	1.00	0.90	0.65	0.72
Claude-A	0.90	1.00	0.60	0.73
METEOR	0.65	0.60	1.00	0.89
BERTScore	0.72	0.73	0.89	1.00

(a) Pearson Correlation Coefficient

	Claude-G	Claude-A	METEOR	BERTScore
Claude-G	/	15.08	6.13	7.36
Claude-A	15.08	/	5.33	7.67
METEOR	6.13	5.33	/	14.31
BERTScore	7.36	7.67	14.31	/

(b) T-Scores

	Claude-G	Claude-A	METEOR	BERTScore
Claude-G	/	1.941E-20	1.266E-07	1.466E-09
Claude-A	1.941E-20	/	2.215E-06	4.740E-10
METEOR	1.266E-07	2.215E-06	/	1.736E-19
BERTScore	1.466E-09	4.740E-10	1.736E-19	/

(c) P-Values

Table 13: Correlation tests for different metrics on the Short Description task.

Figure 3: Comparison between LLM-as-a-Judge metrics, BERTScore, and METEOR on the headline generation task. We are using a stacked line chart to better highlight the correlations between the metrics.

Figure 4: Comparison between LLM-as-a-Judge metrics, BERTScore, and METEOR on the short description task. We are using a stacked line chart to better highlight the correlations between the metrics.

K Results for the Short Description Task

Figure 5 shows the LLM performances on the Short Description task plotted against their performances on the proficiency exams while Table 14 shows PCCs, t-scores, and corresponding p-values.

Task	Small	Medium	Large	All
Claude-G	0.670	0.773	0.926	0.779
Claude-A	0.700	0.812	0.859	0.660
METEOR	0.743	0.550	0.780	0.702
BERTScore	0.749	0.595	0.618	0.604

(a) Pearson Correlation Coefficients

	small	medium	large	all
Claude-G	6.443	8.702	17.516	8.884
Claude-A	7.005	9.935	11.970	6.279
METEOR	7.935	4.700	8.911	7.036
BERTScore	8.072	5.293	5.612	5.419

(b) T-Scores

	small	medium	large	all
Claude-G	4.126E-08	1.182E-11	3.185E-23	6.204E-12
Claude-A	5.338E-09	1.609E-13	1.980E-16	7.483E-08
METEOR	1.837E-10	2.009E-05	5.635E-12	4.770E-09
BERTScore	1.119E-10	2.563E-06	8.25E-07	1.64E-06

(c) P-Values

Table 14: Correlation tests between the overall exam scores and Short Description task performances.

(a) Claude Score - Grammar and Spelling

(b) Claude Score - Adequacy

(c) BERTScore

(d) METEOR Score

Figure 5: Performance on Language Exams vs Performance on the Short Description Task.