Unconstrained Salient and Camouflaged Object Detection

Abstract

Visual Salient Object Detection (SOD) and Camouflaged Object Detection (COD) are two interrelated yet distinct tasks. Both tasks model the human visual system's ability to perceive the presence of objects. The traditional SOD datasets and methods are designed for scenes where only salient objects are present, similarly, COD datasets and methods are designed for scenes where only camouflaged objects are present. However, scenes where both salient and camouflaged objects coexist, or where neither is present, are not considered. This simplifies the existing research on SOD and COD. In this paper, to explore a more generalized approach to SOD and COD, we introduce a benchmark called Unconstrained Salient and Camouflaged Object Detection (**USCOD**), which supports the simultaneous detection of salient and camouflaged objects in unconstrained scenes, regardless of their presence. Towards this, we construct a large-scale dataset, **CS12K**, that encompasses a variety of scenes, including four distinct types: scenes containing only salient objects, scenes with only camouflaged objects, scenes where both salient and camouflaged objects coexist, and scenes without any objects. In our benchmark experiments, we find that a major challenge in USCOD is distinguishing salient objects from camouflaged objects within the same model. To address this, we propose a USCOD baseline called **USCNet**, which freezes the SAM mask decoder for mask reconstruction, allowing the model to focus on distinguishing between salient and camouflaged objects. Furthermore, to evaluate models' ability to distinguish between salient and camouflaged objects, we design a metric called Camouflage-Saliency Confusion Score (**CSCS**). The proposed method achieves state-of-the-art performance on the newly introduced USCOD task. The code and dataset will be publicly available.

1 Introduction

The attention mechanism is one of the key cognitive functions of humans Posner et al. (1990). In real-world scenarios, people are often drawn to salient objects while overlooking camouflaged ones. The goal of Salient Object Detection (SOD) is to detect objects in an image that the human visual system considers most salient or attention-grabbing, while Camouflaged Object Detection (COD) aims to detect objects that are difficult to perceive or blend seamlessly with their surroundings Li et al. (2021). SOD simulates the human ability to focus on salient objects, while COD mimics the human ability to discover camouflaged objects. Both of them exhibit significant potential across various fields, such as anomaly detection in medical image analysis Tang et al. (2023), obstacle recognition in autonomous driving, camouflage detection in military reconnaissance Lin & Prasetyo (2019), and wildlife tracking in environmental monitoring Stevens & Merilaita (2009). Currently, existing methods follow the training and inference paradigms of popular datasets, such as COD10K Fan et al. (2020) in COD and DUTS Wang et al. (2017a) in SOD, and have made significant progress.

Limitations of existing SOD and COD methods. Existing SOD and COD methods often rely on strong pre-defined constraints specific to the tasks, which may limit their generalizability. The classic SOD and COD methods are designed for detecting their respective attribute-specific objects, considering only scenes where single-attribute objects exist (Figure 1. Scene A and Scene B). They overlook more complex scenes where both salient and camouflaged objects coexist (Figure 1. Scene C) or where neither type of object is present (Figure 1. Scene D). Some works have already explored how to handle SOD and COD simultaneously. EVP Liu et al. (2023) achieves the detection of

Figure 1: SOD supports scenes that only exist salient objects, *e.g., (A)*. COD supports scenes that only exist camouflaged objects, *e.g., (B)*. Compared with classic SOD and COD, the proposed **Unconstrained Salient and Camouflaged Object Detection (USCOD)** supports scenes may existing salient objects, camouflaged objects, both, or neither, *e.g., (A-D)*. In Desired Output, the **red** mask indicates the salient object, and the **green** mask represents the camouflaged object.

salient and camouflaged objects by switching different visual prompts. VSCode Luo et al. (2024) and Spider Zhao et al. (2024) achieve the detection of salient and camouflaged objects through joint training on multiple datasets and specific task prompts. However, these methods have certain constraints. The visual prompt of EVP needs to be retrained according to the datasets of different tasks and requires pre-defining the category of the detection task. Similarly, in VSCode and Spider, while only one combined training process is needed for multiple datasets of different tasks, the task prompts for difference datasets still need to be pre-defined. These methods cannot adaptively detect salient and camouflaged objects based on the content of the image. Furthermore, these methods cannot handle situations where both salient and camouflaged objects exist in the same image.

New benchmark and dataset. To overcome these constraints, we propose a new benchmark called Unconstrained Salient and Camouflaged Object Detection (USCOD), which allows the detection of both salient and camouflaged objects in unconstrained scenes (refer to Figure 1. Scene A-D). However, most existing SOD and COD datasets do not include Scene C and Scene D, as they only contain scenes with single-attribute objects. Although COD10K has collected image samples for Scene D, these samples have not yet been effectively utilized in models. To address the limitations of existing datasets and advance USCOD research, we construct a new USCOD dataset named CS12K. It contains 12,000 images, covering the four scenes: 3,000 images of Scene A; 3,000 images of Scene B; and two scenes lacking in existing datasets, including 3,000 images of Scene C and 3,000 images of Scene D, which are manually collected and annotated. The comparison of the data analysis between our dataset and the existing SOD and COD datasets is shown in Table 1.

New evaluation metric. For the USCOD benchmark, one key issue is how to evaluate the ability of the model to understand the semantic differences between salient and camouflaged objects. However, existing metrics fail to effectively capture this ability, as they only assess the detection performance of salient and camouflaged objects individually, such as weighted F-measure Margolin et al. (2014), Structural measure Fan et al. (2017). To fill this gap, we design a metric called

Camouflage-Saliency Confusion Score (CSCS) to evaluate the ability of the model to distinguish between salient and camouflaged objects.

Challenge and A baseline method. To explore solutions for the USCOD problem, we retrain and evaluate 19 SOD and COD models. Our findings reveal that existing models struggle to accurately distinguish between salient and camouflaged objects in unconstrained scenes, often leading to confusion. For example, in Scene A of Figure 5, a prominent duck may be misidentified as a camouflaged object, while in Scene C of Figure 5, a person disguised as grass is recognized as a salient object. To address this issue, we propose a USCOD baseline model, USCNet, which decouples the learning of attribute distinction from mask reconstruction. By freezing the SAM mask decoder, allowing it to focus on attribute distinction of salient objects, camouflaged objects, and background. Additionally, we design an APG module that integrates dynamic and static queries to enhance the semantic differentiation between salient and camouflaged objects. The results demonstrate that decoupling the learning processes enables USCNet to achieve state-of-the-art performance across all metrics in overall scenes, *e.g.*, 78.03% on the mIoU and 7.49% on the CSCS.

In summary, our contributions are listed as follows:

- We propose a new benchmark called **USCOD**, which supports the detection of both salient and camouflaged objects in unconstrained scenes. Further, a new metric, **CSCS**, is introduced to assess the model's confusion between salient and camouflaged objects.

- We introduce a large-scale USCOD dataset **CS12K**. To our knowledge, this is the first dataset that covers multiple scenes without restrictions on the presence of salient or camouflaged objects.

- A novel baseline **USCNet** decouples the learning of attribute distinction from mask reconstruction, utilizing an Attribute-specific Prompt Generation (APG) that focuses on differentiating salient objects from camouflaged objects, while the frozen SAM mask decoder is used for reconstructing the object masks.

- Based on CS12K, we establish the complete CS12K **benchmark** to conduct a broader study of the USCOD task. USCNet is compared with 19 cutting-edge SOD and COD models and shows promising performance.

2 RELATED WORK

2.1 SALIENT AND CAMOUFLAGED OBJECT DETECTION

SOD. In recent years, salient object detection models have focused on better detecting salient objects in images using various approaches. The main approaches can be divided into attention-based methods Liu et al. (2018); Piao et al. (2019); Zhang et al. (2018), multi-level feature-based methods Fang et al. (2022); Hou et al. (2017); Pang et al. (2020); Wang et al. (2017b); Zhao et al. (2020), and recurrent-based methods Deng et al. (2018); Liu & Han (2016); Wang et al. (2018). Saliency detection Zhao et al. (2020); Zhang et al. (2021); Liu et al. (2021a); Zhuge et al. (2022) primarily focus on achieving saliency predictions while preserving the structure.

COD. Compared to salient object detection, current COD methods Fan et al. (2021); Mei et al. (2021); Pang et al. (2022); He et al. (2023); Jia et al. (2022) focus primarily on edge-aware perception and texture perception. Mainly divided into the following two types, multi-level feature-based methods Zhang et al. (2022); Yang et al. (2021); Ren et al. (2021); Zhai et al. (2022), Edge joint learning Zhai et al. (2021); Sun et al. (2022); He et al. (2023).

Unified. SOD and COD are distinct yet interrelated tasks Luo et al. (2024). Recently, some works have already begun to unify the two tasks. EVP Liu et al. (2023) solves the detection of Camouflaged, Forgery, Shadow, and Defocus Blur by adding a visual prompt to the same base segmentation model, allowing a single base model to handle different tasks by using specific visual prompt. VSCode Luo et al. (2024) uses a multi-dataset joint training approach, simultaneously utilizing datasets from RGB SOD, RGB COD, RGB-D SOD, RGB-D COD, RGB-T SOD, Video SOD (VSOD), and VCOD, and assigning different task prompts for SOD and COD tasks to achieve task unification. Similarly, Spider Zhao et al. (2024) uses a comparable method to unify Context-dependent tasks. It also requires the input of specific task prompts.

The unified models mentioned above have two constrains. First, they require the task type to be pre-defined in advance, with a specific prompt input into the model, thus being constrained by the prompt. Second, they cannot handle scenarios where both salient object and camouflaged object are present simultaneously, being constrained by the scenario. The USCOD task we proposed successfully addresses these two aspects, achieving unconstrained by both the prompt and the scenario.

2.2 Applications of SAM.

The Segment Anything Model (SAM) Kirillov et al. (2023) represents a significant advancement in scene segmentation using large vision models. Its versatility and adaptability underscore its capability to comprehend complex scenarios and objects, thereby pushing the boundaries of image segmentation tasks even further. Current works leveraging SAM Chen et al. (2023a); Zhang et al. (2023); Xiong et al. (2023); Ma et al. (2024) showcase its adaptability to downstream tasks, notably in areas where traditional segmentation models struggle, such as EfficientSAM Xiong et al. (2023) and MedSAM Ma et al. (2024). More recently, the release of SAM2 Ravi et al. (2024) enhances the original SAM's ability to handle video content while demonstrating improved segmentation accuracy and inference efficiency in image segmentation across various downstream applications Zhu et al. (2024); Yan et al. (2024); Lian & Li (2024); Lou et al. (2024).

Some works that use SAM for SOD and COD are closely related to our research. MDSAM Gao et al. (2024) is a novel multi-scale and detail-enhanced SOD model based on SAM, aimed at improving the performance and generalization capability of SOD task. SAM-Adapter Chen et al. (2023a) and SAM2-Adapter Chen et al. (2024) offers a parameter-efficient fine-tuning way to enhance performance of SAM and SAM2 in downstream tasks like COD and medical image segmentation by adding task-specific knowledge. Nevertheless, these methods may be suboptimal for fine-tuning SAM for the USCOD task, as they discard prompt architecture of SAM and tune the mask decoder to simultaneously learn distinguishing attributes and segmenting mask, even though the mask decoder is not designed for attribute distinction. Therefore, we retain the mask decoder solely for mask reconstruction and use independent learning for attribute distinction to better differentiate between salient objects, camouflaged objects, and background.

3 Proposed CS12K Dataset

The current datasets for camouflaged object detection, such as COD10K Fan et al. (2020), CAMO Le et al. (2019), NC4K Lv et al. (2021), primarily feature scenes with exclusively camouflaged objects. Similarly, datasets for salient object detection, such as DUTS Wang et al. (2017a), and HKU-IS Li & Yu (2015), predominantly focus on scenes with solely salient objects. There are relatively few samples with both salient objects and camouflaged objects in an image, which is not conducive to the realization of the unconstrained existence of salient and camouflaged object detection. Therefore, we introduce the **CS12K**, a dataset that includes more comprehensive and complex scenarios for unconstrained salient and camouflaged object detection. It includes scenes with both salient and camouflaged objects, scenes with only one type, and scenes without either. We will describe the details of CS12K in terms of three key aspects, as follows.

3.1 Data Collection

Under the premise of ensuring sample balance, we collect 12,000 images from 8 different sources and divide them into four scenes after manual filtering: (A) Scenes with only salient objects: 3,000 images containing only salient objects selected from SOD datasets DUTS and HKU-IS; (B) Scenes with only camouflaged objects: 3,000 images containing only camouflaged objects selected from COD datasets COD10K and CAMO; (C) Scenes with both salient and camouflaged objects: 342 images from the COD datasets COD10K, CAMO, and NC4K, along with 41 images from the datasets LSUI Peng et al. (2023) and AWA2 Xian et al. (2018), and an additional 2,617 images collected from the internet, making a total of 3,000 images; (D)Scenes without salient and camouflaged objects, considered as background: 1,564 images from COD10K, and 1,436 images from the Internet. Finally, we get 12,000 images, with the training set containing 8,400 images and the testing set containing 3,600 images. The data source is shown in Figure 2 (Left).

Figure 2: **Left**: The data source and distribution of different data types. **Right**: Categories and groups of our CS12K dataset. **Zoom-in for better view**.

Table 1: Data analysis of existing datasets.

Task	Dataset	#Ann. IMG	Class	Scene A	Scene B	Scene C	Scene D
SOD	SOD Movahedi & Elder (2010)	300	-	300	✗	✗	✗
	PASCAL-S Li et al. (2014)	850	-	850	✗	✗	✗
	ECSSD Yan et al. (2013)	1000	-	1000	✗	✗	✗
	HKU-IS Li & Yu (2015)	4447	-	4447	✗	✗	✗
	MSRA-B Liu et al. (2011)	5000	-	5000	✗	✗	✗
	DUT-OMRON Yang et al. (2013)	5168	-	5168	✗	✗	✗
	MSRA10K Cheng et al. (2015)	10000	-	10000	✗	✗	✗
	DUTS Wang et al. (2017a)	15572	-	15572	✗	✗	✗
	SOC Fan et al. (2018a)	3000	80	3000	✗	✗	✗
COD	CAMO Le et al. (2019)	1250	8	✗	1250	✗	✗
	CHAMELEON Skurowski et al. (2018)	76	-	✗	76	✗	✗
	NC4K Lv et al. (2021)	4121	-	✗	4121	✗	✗
	COD10K Fan et al. (2020)	7000	78	✗	5066	✗	1934
USCOD	**CS12K(Ours)**	12000	179	3000	3000	3000	3000

3.2 DATA ANNOTATION

We use SAM Kirillov et al. (2023) for mask labeling and manual correction. When labeling, we first retain the RGB pixels corresponding to the object instance in the image, set the remaining pixels to 0, obtain the rough classification results through CLIP Radford et al. (2021), and then perform manual comparison and correction. In addition to the camouflaged object category labels already included in the images from COD10K Fan et al. (2020), the remaining objects require category assignment. Some example images of different scenes from our CS12K dataset are shown in Figure 3. Then we assign category labels to each image, including 9 super-classes and 179 sub-classes. Figure 2 (Right) illustrates the class breakdown of our CS12K dataset.

3.3 DATA ANALYSIS

For deeper insights into USCOD dataset, we compare our CS12K against 13 other related datasets including: (1) nine SOD datasets: SOD Movahedi & Elder (2010), PASCAL-S Li et al. (2014), ECSSD Yan et al. (2013), HKU-IS Li & Yu (2015), MSRA-B Liu et al. (2011), DUT-OMRON Yang et al. (2013), MSRA10K Cheng et al. (2015), DUTS Wang et al. (2017a), and SOC Fan et al. (2018a); (2) four COD datasets: CAMO Le et al. (2019), CHAMELEON Skurowski et al. (2018), COD10K Fan et al. (2020), and NC4K Lv et al. (2021); Table 1 shows the detailed information of these datasets. It can be seen that except for COD10K, all SOD datasets only contain salient objects, and all COD datasets only contain camouflaged objects. The scene of these datasets are relatively single. It is worth noting that, although the COD dataset COD10K contains some images with salient objects and images without any objects, these images lack labels and are not included in the training process. In contrast, the CS12K dataset we propose imposes no restrictions on scenes

Figure 3: Example images from the CS12K dataset: Scene A: Only camouflaged object. Scene B: Only salient object. Scene C: Both salient and camouflaged objects simultaneously. Scene D: Background, with the absence of both types of objects. More examples can be found in Appendix.§E.

and includes labels for three attributes: saliency, camouflage, and background, with a well-balanced distribution. We aim to advance the field and explore effective methods for capturing camouflage and saliency patterns in unconstrained scenes.

4 PROPOSED USCNET BASELINE

Overview. As illustrated in Figure 4, the main components of the proposed USCNet include: (1) A SAM image encoder to extract object feature representation with adapter layers. (2) An Attribute-specific Prompt Generation (APG) that generates three discriminative prompts for each attribute: saliency, camouflage, and background. (3) A frozen mask decoder of SAM that is applied to predict the final saliency, camouflaged, and background masks based on different attribute prompts.

4.1 SEGMENT ANYTHING MODEL

SAM Kirillov et al. (2023) designs a flexible prompting-enabled model architecture for category-agnostic segmentation. Specifically, SAM consists of an image encoder, a prompt encoder, and a mask decoder. The image encoder is pre-trained using the Masked Auto Encoder (MAE) He et al. (2022), the prompt encoder handles dense and sparse inputs like boxes and points, and the mask decoder predicts the masks based on the encoded embeddings. In USCNet, we utilize the prompt architecture of SAM for identifying three attributes: saliency, camouflage, and background. The attribute prompts is generated by a designed APG module, eliminating the need for manual prompt. As a result, each attribute prompt is mapped to a distinct binary mask.

4.2 SAM ENCODER WITH ADAPTER

To leverage knowledge from SAM, SAM-Adapter Chen et al. (2023a) adapts SAM to downstream tasks and achieve enhanced performance with a parameter-efficient fine-tuning approach. Following that, USCNet integrates adapters into each layer of the SAM encoder, as depicted in Figure 4. As a result, the output image embedding F from the tuned SAM Encoder exhibits features adept at addressing USCOD task. Through this approach, USCNet blending USCOD-specific knowledge with the general knowledge acquired by the larger model, better adapting to unconstrained scenes.

4.3 ATTRIBUTE-SPECIFIC PROMPT GENERATION

Our insight is that the detection of salient and camouflaged objects within a sample requires consideration of features across two dimensions: (i) Sample-generic features: For all samples, characteristics such as the size, position, color, and texture of the object serve as important generic features

Figure 4: Architecture of our USCNet. USCNet includes: SAM image encoder with adapter, Attribute-specific Prompt Generation (APG) module, and frozen SAM mask decoder.

for distinguishing salient and camouflaged objects. These features are applicable in most scenarios and can act as universal criteria for judgment; (ii) Sample-specific features: Relying solely on sample-generic features may not suffice in certain complex situations. For instance, when the salient and camouflaged objects share similar colors or categories, sample-generic features alone are insufficient for effective differentiation. In such cases, it is crucial to consider the specific contextual information within the sample and learn features that are closely associated with the current sample to assist in making an accurate judgment.

Based on this, we propose Attribute- specific Prompt Generation (APG) integrates both Dynamic Prompt Query (DPQ) and Static Prompt Query (SPQ) to generate discriminative attribute-specific prompts, where SPQ to extract sample-generic features, capturing attribute information that applies to all samples, and DPQ to extract sample-specific features, focusing on the unique contextual information of the current sample. Specifically, as depicted in Figure 4, the APG integrates both the Dynamic Prompt Query (DPQ) and Static Prompts Query (SPQ) to create attribute-specific prompts. The SPQ consists of a set of learnable query embeddings, which are designed to encapsulate general attributes. To formulate the DPQ, the system initially extracts features F from the encoder to generate a coarse prediction, which is then processed through a sigmoid function to produce an attention map. This attention map is then element-wise multiplied with the original features F to isolate attribute-specific features. These features are further refined through a linear layer to produce the DPQ, tailored to capture nuanced and specific attributes within individual samples. The DPQ generation process can be described by the formula:

$$[Q_{D\_S}, Q_{D\_C}, Q_{D\_B}] = MLP(\sigma(\Phi_{CH}(F)) \otimes F), \tag{1}$$

where Q_{D_S}, Q_{D_C}, and Q_{D_B} represent the DPQ for saliency, camouflage, and background, respectively. MLP stands for a Multi-Layer Perceptron that processes the output. σ denotes the sigmoid function, and Φ_{CH} represents the operation to predict a coarse prediction from the features F. The symbol $\otimes$ denotes element-wise multiplication. Unlike standard query embeddings which are fixed after training, the DPQ changes according to the sample, making it highly adaptable and capable of explicitly capturing the distinctive features of the camouflage and saliency across varying samples. The DPQ captures feature information from specific images, whereas the SPQ discerns the fundamental differences among three attributes. By combining the two, our APG attains improved performance. Subsequently, we employ self-attention to establish relationships between queries, and query-to-image ($Q2I$) attention to interact with image embedding, ultimately generating prompts for the three attributes: P_S, P_C, P_B. The process can be formulated as follows:

$$[P_S, P_C, P_B] = MLP(Q2I(SA(DPQ + SPQ), F)), \tag{2}$$

where P_S, P_C, and P_B represent the prompts generated for identifying saliency, camouflage, and background elements, respectively. SA represents the self-attention. $Q2I$ denotes the cross-attention from queries to the image embedding F, enabling the model to focus on relevant parts of the input based on the queries. Furthermore, we use a cross-attention from the image embedding to queries ($I2Q$) to focus on features related to attributes.

Based on the three attribute-specific prompts fed into the pre-trained mask decoder in SAM, three masks are obtained: $Mask\_S$, $Mask\_C$, and $Mask\_B$, representing the output saliency, camouflage, and background predictions, respectively. The process can be described as:

$$[Mask\_S, Mask\_C, Mask\_B] = MaskDe([P_S, P_C, P_B], F), \tag{3}$$

where MaskDe denotes frozen SAM mask decoder. Finally, a softmax function is applied to produce the final prediction.

Table 2: Quantitative comparisons with 19 related methods for USCOD. IoU_S ↑: IoU score for salient objects. IoU_C ↑: IoU score for camouflaged objects. The best two scores are highlighted in **red** and **green**, respectively. All metrics presented in the table are expressed as percentages (%). We use mIoU↑, mAcc↑, and CSCS↓ to evaluate the models in overall scenes.

Task	Model	Venue	Update Para.(M)	Scene A IoU_S	Scene B IoU_C	Scene C IoU_S	Scene C IoU_C	Overall IoU_S	Overall IoU_C	mIoU	mAcc	CSCS
SOD	GateNet Zhao et al. (2020)	ECCV	128	68.32	54.26	66.85	35.03	65.08	44.17	68.27	78.07	11.30
	F3Net Wei et al. (2020)	AAAI	26	70.05	52.62	67.20	36.38	66.12	44.81	68.80	77.86	9.36
	MSFNet Zhang et al. (2021)	MM	28	70.14	54.78	69.92	36.64	66.69	45.89	69.40	79.77	9.90
	VST Liu et al. (2021a)	ICCV	43	68.14	49.82	61.61	22.56	63.18	38.45	65.55	74.77	11.30
	EDN Wu et al. (2022)	TIP	43	71.59	57.94	69.37	37.70	68.00	48.27	70.70	80.60	9.23
	ICON Zhuge et al. (2022)	TPAMI	32	68.09	50.57	67.48	30.65	65.86	45.53	68.99	79.53	10.24
COD	SINet-V2 Fan et al. (2021)	TPAMI	27	72.96	56.16	67.21	36.06	69.50	47.47	70.20	79.58	8.83
	PFNet Mei et al. (2021)	CVPR	47	69.07	52.83	67.20	32.81	65.73	43.76	68.30	78.00	10.04
	ZoomNet Pang et al. (2022)	CVPR	33	74.11	51.12	66.79	29.69	66.43	43.28	68.35	77.72	8.88
	FEDER He et al. (2023)	CVPR	44	74.35	58.04	67.66	32.26	68.65	46.46	70.32	81.27	10.01
	PRNet Hu et al. (2024)	TCSVT	13	76.10	61.54	60.10	32.16	68.68	50.88	71.87	82.89	8.40
	ICEG He et al. (2024)	ICLR	100	73.67	68.38	68.43	44.33	69.22	58.71	74.68	83.53	8.16
	CamoDiffusion Chen et al. (2023b)	AAAI	72	75.01	59.39	53.49	45.03	63.49	52.80	70.70	77.73	7.73
	CamoFormer Yin et al. (2024)	TPAMI	71	75.88	66.19	73.33	44.14	71.86	56.09	74.81	84.17	7.57
	PGT Wang et al. (2024)	CVIU	68	72.75	61.51	70.01	41.21	71.46	56.83	75.03	83.35	9.09
	SAM-Adapter Chen et al. (2023a)	ICCVW	4.11	78.90	67.69	68.19	27.73	70.66	52.69	73.38	83.35	10.28
	SAM2-Adapter Chen et al. (2024)	arXiv	4.36	78.75	70.28	69.01	38.20	71.42	56.71	74.98	84.74	9.12
Unified	EVP Liu et al. (2023)	CVPR	4.95	75.85	59.81	71.41	37.64	70.30	50.36	72.16	79.96	8.67
	VSCode Luo et al. (2024)	CVPR	60	71.43	54.64	65.26	30.58	67.09	46.91	69.78	78.92	9.72
USCOD	USCNet (Ours)	-	4.04	79.70	74.99	74.80	45.73	75.57	61.34	78.03	87.92	7.49

4.4 Loss Function

We use the ground truth (GT) to supervise the final prediction and coarse prediction. The total loss function of USCNet can be defined as:

$$L_{Total} = L_{CE}(I_{GT}, I_{Pred}) + L_{CE}(I_{GT}, I_{Coarse}), \tag{4}$$

where I_{GT}, I_{Pred} and I_{Coarse} respectively represent ground truth, final prediction, and the coarse prediction, while L_{CE} represents the Cross Entropy loss.

5 CS12K Benchmark

As discussed above, our CS12K dataset is characterized by existence unconstrained, meaning each image may contain salient objects, camouflaged objects, both, or neither. Moreover, it covers categories spanning from salient to camouflaged objects. In CS12K benchmark, all models are trained and tested on the training set of CS12K (8,400 images) and the testing set of CS12K (3,600 images). To assess generalization, we also evaluated the model's performance across six widely used datasets. This includes common COD datasets such as COD10K, NC4K, and CAMO-TE, as well as popular SOD datasets like DUT-TE, HKU-IS, and DUT-OMRON. The results and specific settings of all generalization experiments are included in the Appendix.§C.

Metrics. Unlike the binary evaluation metrics widely used in SOD and COD (*e.g.* maximal F-measure Achanta et al. (2009)), the USCOD task involves three distinct attributes: saliency, camouflage, and background. To assess the performance of models tackling this multifaceted challenge, we leverage three established metrics for semantic segmentation: mean pixel accuracy of different categories (mAcc ↑), Intersection-over-Union of different categories (IoU ↑), and mean IoU (mIoU ↑). Inspired by Li et al. (2024), we also employ metrics AUC↑, SI-AUC↑, F_m^β↑, SI-F_m^β↑, F_{max}^β↑, SI-F_{max}^β↑, E_m↑ to evaluate the model's capability in detecting objects of varying sizes. Additionally, to evaluate the ability of the model to distinguish between salient and camouflaged objects, we propose a novel metric, the **C**amouflage-**S**aliency **C**onfusion **S**core (**CSCS** ↓), which is formulated as follows:

$$\text{CSCS} = \frac{1}{2}\left(\frac{\mathcal{P}_{CS}}{\mathcal{P}_{BS} + \mathcal{P}_{SS} + \mathcal{P}_{CS}} + \frac{\mathcal{P}_{SC}}{\mathcal{P}_{BC} + \mathcal{P}_{SC} + \mathcal{P}_{CC}}\right), \tag{5}$$

Figure 5: Qualitative comparisons of USCNet with five baselines across overall scenes. More visualization can be seen in Appendix.§F.

where $\mathbb{P} = \{\mathcal{P}_{\lambda\theta} \mid \lambda \in \Theta, \theta \in \Theta\}$, $\Theta = \{B, C, S\}$, the B, C and S denotes background, camouflage and saliency. As shown in Figure 6, $\mathcal{P}_{CS}$ represents regions where camouflage is predicted as salient, while $\mathcal{P}_{SC}$ represents regions where saliency is predicted as camouflage; both are regions of confusion. A lower CSCS indicates a stronger robustness to distinguish between salient and camouflaged objects. More details of CSCS can be seen in Appendix.§A.

Competitors. We compared our USCNet with 19 recent related models, including (I) SOD models: GateNet Zhao et al. (2020), F3Net Wei et al. (2020), MSFNet Zhang et al. (2021), VST Liu et al. (2021a), EDN Wu et al. (2022), ICON Zhuge et al. (2022); (II) COD models: SINet-V2 Fan et al. (2021), PFNet Mei et al. (2021), ZoomNet Pang et al. (2022),FEDER He et al. (2023), ICEG He et al. (2024), PRNet Hu et al. (2024), CamoDiffusion Chen et al. (2023b), CamoFormer Yin et al. (2024), PGT Wang et al. (2024), SAM-Adapter Chen et al. (2023a) and SAM2-Adapter Chen et al. (2024); (III) Unified methods: VSCode Luo et al. (2024) and EVP Liu et al. (2023).

Technical Details. All models are retrained using the training set of CS12K with an input image resolution of 352×352. Horizontal flipping and random cropping are applied for data augmentation. The experiments are conducted in PyTorch on one NVIDIA L40 GPU. The number of parameters fine-tuned for all models is detailed in Table 2. For our model, we use hiera-large version of SAM2 following the SAM2-Adapter Chen et al. (2024). AdamW optimizer is used a warm-up strategy and linear decay strategy. The initial learning rate is set to 0.0001. The batch size is set to 24, and the maximum number of epochs is set to 90. The technical details of all other comparison methods can be found in the Appendix.§D.

5.1 QUANTITATIVE EVALUATION

We present in Table 2 the performance of compared models on USCOD benchmark. Comparing the results of the models in single-attribute scenes (refer to Scene A and Scene B) with those in multi-attribute scenes (refer to Scene C) reveals that all models achieve lower scores in Scene C than in Scene A and Scene B. This indicates that the simultaneous presence of both salient objects and camouflaged objects increases the difficulty for the models to recognize both. Our method also achieves a greater lead in Scene C, *e.g.*, 74.80% on the IoU_S and 45.73% on the IoU_C, demonstrating that our model is more adaptable when faced with more challenging scenarios. Furthermore, USCNet achieves the best performance in all scenarios compared to all other compared methods. Additionally, the evaluation results for other metrics, including AUC↑, SI-AUC↑, F_m^β↑, SI-F_m^β↑, $F_{\max}^\beta$↑, SI-$F_{\max}^\beta$↑, and E_m↑, can be found in Table 4 and Table 5 in Appendix.§B.

5.2 QUALITATIVE EVALUATION

In Figure 5, we compare our qualitative results with SOD models (ICON Zhuge et al. (2022), EDN Wu et al. (2022)), COD model (ICEG He et al. (2024) , PFNet Mei et al. (2021) and SAM2-Adapter Chen et al. (2024)). In the Scene A and Scene B of Figure 5, our method exhibited a better

Table 3: **Left:** Performance of different base model. *In the original SAM or SAM2, we only fine-tune the mask decoder. **Right:** Effectiveness of different components in APG. DPQ: dynamic prompt query. SPQ: static prompt query. Q2I: query-to-image attention. I2Q: image-to-query attention. Para.: update parameter (M). All metrics tested on the overall scenes test set and presented in the table are expressed as percentages (%).

Method	Base	Para.	IoU_S	IoU_C	mIoU	mAcc	CSCS
SAM*	SAM	3.92	51.07	33.00	59.56	68.73	18.66
USCNet	SAM	4.08	73.93	56.50	75.87	83.86	8.24
SAM2*	SAM2	4.22	66.42	44.02	68.78	77.65	11.58
USCNet	SAM2	4.04	**75.57**	**61.34**	**78.03**	**87.92**	**7.49**

Encoder	Decoder	DPQ	SPQ	Q2I	I2Q	Para.	IoU_S	IoU_C	mIoU	mAcc	CSCS
Frozen	Tuning	✗	✗	✗	✗	4.22	66.42	44.02	68.78	77.65	11.58
Tuning	Tuning	✗	✗	✗	✗	4.36	71.42	56.71	74.98	84.74	9.12
Tuning	Frozen	✗	✓	✓	✓	3.44	71.68	57.53	75.31	85.15	9.07
Tuning	Frozen	✓	✗	✓	✓	4.03	74.32	58.91	76.96	85.80	7.98
Tuning	Frozen	✓	✓	✗	✗	0.75	70.97	56.56	74.77	84.43	9.85
Tuning	Frozen	✓	✓	✓	✗	2.40	73.08	58.45	76.73	85.63	8.52
Tuning	Frozen	✓	✓	✓	✓	4.04	**75.57**	**61.34**	**78.03**	**87.92**	**7.49**

detection capability for salient objects or camouflaged objects. Benefiting from the APG module, our method better distinguished salient objects and camouflaged objects in the same image within Scene C of Figure 5. For Scene D, SOD and COD methods become confused when encountering backgrounds, resulting in poor performance and unstable robustness, whereas our model demonstrates better performance in this scenario. More qualitative evaluation can be seen in Appendix.§F.

5.3 ABLATION STUDY

Performance of Different Base Models. We conducted ablation experiments to evaluate the performance of different base models, as presented in Table 3.(**Left**). First, as shown in the first two and last two rows of the table, our model demonstrates significant performance improvements on the USCOD benchmark, regardless of whether SAM Kirillov et al. (2023) (default vit-huge version) or SAM2 Ravi et al. (2024) (default hiera-large version) is used as the base model. For instance, when using SAM as the base model, our method achieves a 16.31% gain in mIoU compared to the original SAM, while utilizing SAM2 results in a 9.25% improvement in mIoU over the original SAM2. Additionally, transitioning from SAM to SAM2 (as shown in rows 2 and 4) results in performance gains across all metrics with fewer fine-tuned parameters.

Effectiveness of Different Components in APG. As we shown in Table 3. (**Right**), ablation experiments were conducted to validate the effectiveness of the proposed components in APG module. From the third, fourth, and seventh rows, it is evident that both DPQ and SPQ improve the performance of model, with DPQ providing a greater performance enhancement than SPQ when used together, achieving optimal results. The fifth, sixth, and seventh rows demonstrate that Q2I and I2Q also facilitate the distinction of salient camouflaged objects, leading to reductions in CSCS of 2.36% and 1.08%, respectively. Additionally, compared to the original SAM2 (refer to line 1) and SAM2-Adapter (refer to line 2), the proposed USCNet enhances performance on the USCOD task across all metrics through a more efficient fine-tuning approach by incorporating the APG module and freezing the mask decoder.

6 CONCLUSION

We analyze and address the limitations of classical SOD and COD tasks, which restrict research to scenarios with only salient or only camouflaged objects. Based on that, a new benchmark called Unconstrained Salient and Camouflaged Object Detection (USCOD), is defined to allow for the unrestricted presence of both salient and camouflaged objects within images. We propose a new evaluation metric, *i.e.*, the Camouflage-Saliency Confusion Score (CSCS), to assess the confusion of the model between camouflaged and salient objects. To support research on USCOD, we have constructed a large-scale dataset, CS12K, that features a diverse range of scenes and categories. We introduce a baseline method, USCNet, which decouples mask reconstruction from attribute distinction to focus on learning the differences between saliency and camouflage patterns, achieving state-of-the-art performance on the USCOD task. The proposed USCOD reduces reliance on specific scenarios, increasing the representation of scenes where both salient and camouflaged objects coexist, as well as scenes where neither is present, thus enhancing generalizability across diverse natural environments.

REFERENCES

Radhakrishna Achanta, Sheila Hemami, Francisco Estrada, and Sabine Susstrunk. Frequency-tuned salient region detection. In *CVPR*, pp. 1597–1604, Miami, Florida, USA, 2009. IEEE.

Tianrun Chen, Lanyun Zhu, Chaotao Deng, Runlong Cao, Yan Wang, Shangzhan Zhang, Zejian Li, Lingyun Sun, Ying Zang, and Papa Mao. Sam-adapter: Adapting segment anything in underperformed scenes. In *ICCV*, pp. 3367–3375, 2023a.

Tianrun Chen, Ankang Lu, Lanyun Zhu, Chaotao Ding, Chunan Yu, Deyi Ji, Zejian Li, Lingyun Sun, Papa Mao, and Ying Zang. Sam2-adapter: Evaluating & adapting segment anything 2 in downstream tasks: Camouflage, shadow, medical image segmentation, and more. *arXiv preprint arXiv:2408.04579*, 2024.

Zhongxi Chen, Ke Sun, Xianming Lin, and Rongrong Ji. Camodiffusion: Camouflaged object detection via conditional diffusion models. *arXiv preprint arXiv:2305.17932*, 2023b.

Ming-Ming Cheng, Niloy J. Mitra, Xiaolei Huang, Philip H. S. Torr, and Shi-Min Hu. Global contrast based salient region detection. *IEEE TPAMI*, 37(3):569–582, 2015.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *CVPR*, pp. 248–255, Miami, Florida, USA, 2009. IEEE.

Zijun Deng, Xiaowei Hu, Lei Zhu, Xuemiao Xu, Jing Qin, Guoqiang Han, and Pheng-Ann Heng. R3net: Recurrent residual refinement network for saliency detection. In *Proceedings of the 27th international joint conference on artificial intelligence*, volume 684690. AAAI Press Menlo Park, CA, USA, 2018.

Deng-Ping Fan, Ming-Ming Cheng, Yun Liu, Tao Li, and Ali Borji. Structure-measure: A new way to evaluate foreground maps. In *ICCV*, pp. 4548–4557, Venice, Italy, 2017. IEEE.

Deng-Ping Fan, Ming-Ming Cheng, Jiang-Jiang Liu, Shang-Hua Gao, Qibin Hou, and Ali Borji. Salient objects in clutter: Bringing salient object detection to the foreground. In *ECCV*, 2018a.

Deng-Ping Fan, Cheng Gong, Yang Cao, Bo Ren, Ming-Ming Cheng, and Ali Borji. Enhanced-alignment measure for binary foreground map evaluation. In *IJCAI*, pp. 1–10, Stockholm, Sweden, 2018b. AAAI Press.

Deng-Ping Fan, Ge-Peng Ji, Guolei Sun, Ming-Ming Cheng, Jianbing Shen, and Ling Shao. Camouflaged object detection. In *CVPR*, pp. 2777–2787, 2020.

Deng-Ping Fan, Ge-Peng Ji, Ming-Ming Cheng, and Ling Shao. Concealed object detection. *IEEE TPAMI*, 44(10):6024–6042, 2021.

Chaowei Fang, Haibin Tian, Dingwen Zhang, Qiang Zhang, Jungong Han, and Junwei Han. Densely nested top-down flows for salient object detection. *Science China Information Sciences*, 65(8): 182103, 2022.

Shang-Hua Gao, Ming-Ming Cheng, Kai Zhao, Xin-Yu Zhang, Ming-Hsuan Yang, and Philip Torr. Res2net: A new multi-scale backbone architecture. *IEEE TPAMI*, 43(2):652–662, 2019.

Shixuan Gao, Pingping Zhang, Tianyu Yan, and Huchuan Lu. Multi-scale and detail-enhanced segment anything model for salient object detection. *arXiv preprint arXiv:2408.04326*, 2024.

Chunming He, Kai Li, Yachao Zhang, Longxiang Tang, Yulun Zhang, Zhenhua Guo, and Xiu Li. Camouflaged object detection with feature decomposition and edge reconstruction. In *CVPR*, pp. 22046–22055, 2023.

Chunming He, Kai Li, Yachao Zhang, Yulun Zhang, Chenyu You, Zhenhua Guo, Xiu Li, Martin Danelljan, and Fisher Yu. Strategic preys make acute predators: Enhancing camouflaged object detectors by generating camouflaged objects. In *The Twelfth International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=hywpSoHwgX.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *CVPR*, pp. 770–778, Las Vegas, NV, USA, 2016. IEEE.

Kaiming He, Xinlei Chen, Saining Xie, Yanghao Li, Piotr Dollár, and Ross Girshick. Masked autoencoders are scalable vision learners. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 16000–16009, 2022.

Qibin Hou, Ming-Ming Cheng, Xiaowei Hu, Ali Borji, Zhuowen Tu, and Philip HS Torr. Deeply supervised salient object detection with short connections. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 3203–3212, 2017.

Xihang Hu, Xiaoli Zhang, Fasheng Wang, Jing Sun, and Fuming Sun. Efficient camouflaged object detection network based on global localization perception and local guidance refinement. *IEEE Transactions on Circuits and Systems for Video Technology*, 2024.

Shuwei Ji and Hongyuan Zhang. ISAT with Segment Anything: An Interactive Semi-Automatic Annotation Tool, 2023. URL https://github.com/yatengLG/ISAT_with_segment_anything. Updated on 2023-06-03.

Qi Jia, Shuilian Yao, Yu Liu, Xin Fan, Risheng Liu, and Zhongxuan Luo. Segment, magnify and re-iterate: Detecting camouflaged objects the hard way. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 4713–4722, 2022.

Alexander Kirillov, Eric Mintun, Nikhila Ravi, Hanzi Mao, Chloe Rolland, Laura Gustafson, Tete Xiao, Spencer Whitehead, Alexander C Berg, Wan-Yen Lo, et al. Segment anything. *arXiv preprint arXiv:2304.02643*, 2023.

Trung-Nghia Le, Tam V Nguyen, Zhongliang Nie, Minh-Triet Tran, and Akihiro Sugimoto. Anabranch network for camouflaged object segmentation. *CVIU*, 184:45–56, 2019.

Aixuan Li, Jing Zhang, Yunqiu Lv, Bowen Liu, Tong Zhang, and Yuchao Dai. Uncertainty-aware joint salient object and camouflaged object detection. In *CVPR*, pp. 10071–10081, 2021.

Feiran Li, Qianqian Xu, Shilong Bao, Zhiyong Yang, Runmin Cong, Xiaochun Cao, and Qingming Huang. Size-invariance matters: Rethinking metrics and losses for imbalanced multi-object salient object detection. *arXiv preprint arXiv:2405.09782*, 2024.

Guanbin Li and Yizhou Yu. Visual saliency based on multiscale deep features. In *CVPR*, 2015.

Yin Li, Xiaodi Hou, Christof Koch, James M Rehg, and Alan L Yuille. The secrets of salient object segmentation. In *CVPR*, 2014.

Shijie Lian and Hua Li. Evaluation of segment anything model 2: The role of sam2 in the underwater environment. *arXiv preprint arXiv:2408.02924*, 2024.

Chiuhsiang Joe Lin and Yogi Tri Prasetyo. A metaheuristic-based approach to optimizing color design for military camouflage using particle swarm optimization. *Color Research & Application*, 44(5):740–748, 2019.

Weifeng Lin, Ziheng Wu, Jiayu Chen, Jun Huang, and Lianwen Jin. Scale-aware modulation meet transformer. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 6015–6026, 2023.

Nian Liu and Junwei Han. Dhsnet: Deep hierarchical saliency network for salient object detection. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 678–686, 2016.

Nian Liu, Junwei Han, and Ming-Hsuan Yang. Picanet: Learning pixel-wise contextual attention for saliency detection. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 3089–3098, 2018.

Nian Liu, Ni Zhang, Kaiyuan Wan, Ling Shao, and Junwei Han. Visual saliency transformer. In *ICCV*, pp. 4722–4732, 2021a.

Tie Liu, Zejian Yuan, Jian Sun, Jingdong Wang, Nanning Zheng, Xiaoou Tang, and Heung-Yeung Shum. Learning to detect a salient object. *IEEE TPAMI*, 33(2):353–367, 2011.

Weihuang Liu, Xi Shen, Chi-Man Pun, and Xiaodong Cun. Explicit visual prompting for low-level structure segmentations. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 19434–19445, 2023.

Ze Liu, Yutong Lin, Yue Cao, Han Hu, Yixuan Wei, Zheng Zhang, Stephen Lin, and Baining Guo. Swin transformer: Hierarchical vision transformer using shifted windows. In *Proceedings of the IEEE/CVF international conference on computer vision*, pp. 10012–10022, 2021b.

Jonathan Long, Evan Shelhamer, and Trevor Darrell. Fully convolutional networks for semantic segmentation. In *CVPR*, pp. 3431–3440, 2015.

Ange Lou, Yamin Li, Yike Zhang, Robert F Labadie, and Jack Noble. Zero-shot surgical tool segmentation in monocular video using segment anything model 2. *arXiv preprint arXiv:2408.01648*, 2024.

Ziyang Luo, Nian Liu, Wangbo Zhao, Xuguang Yang, Dingwen Zhang, Deng-Ping Fan, Fahad Khan, and Junwei Han. Vscode: General visual salient and camouflaged object detection with 2d prompt learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 17169–17180, 2024.

Yunqiu Lv, Jing Zhang, Yuchao Dai, Aixuan Li, Bowen Liu, Nick Barnes, and Deng-Ping Fan. Simultaneously localize, segment and rank the camouflaged objects. In *CVPR*, pp. 11591–11601, 2021.

Jun Ma, Yuting He, Feifei Li, Lin Han, Chenyu You, and Bo Wang. Segment anything in medical images. *Nature Communications*, 15(1):654, 2024.

Ran Margolin, Lihi Zelnik-Manor, and Ayellet Tal. How to evaluate foreground maps? In *CVPR*, pp. 248–255, Columbus, OH, USA, 2014. IEEE.

Haiyang Mei, Ge-Peng Ji, Ziqi Wei, Xin Yang, Xiaopeng Wei, and Deng-Ping Fan. Camouflaged object segmentation with distraction mining. In *CVPR*, pp. 8772–8781, 2021.

Vida Movahedi and James H Elder. Design and perceptual validation of performance measures for salient object segmentation. In *CVPRW*, 2010.

Youwei Pang, Xiaoqi Zhao, Lihe Zhang, and Huchuan Lu. Multi-scale interactive network for salient object detection. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 9413–9422, 2020.

Youwei Pang, Xiaoqi Zhao, Tian-Zhu Xiang, Lihe Zhang, and Huchuan Lu. Zoom in and out: A mixed-scale triplet network for camouflaged object detection. In *CVPR*, pp. 2160–2170, 2022.

Lintao Peng, Chunli Zhu, and Liheng Bian. U-shape transformer for underwater image enhancement. *IEEE Transactions on Image Processing*, 2023.

Federico Perazzi, Philipp Krähenbühl, Yael Pritch, and Alexander Hornung. Saliency filters: Contrast based filtering for salient region detection. In *CVPR*, pp. 733–740, Providence, RI, USA, 2012. IEEE.

Yongri Piao, Wei Ji, Jingjing Li, Miao Zhang, and Huchuan Lu. Depth-induced multi-scale recurrent attention network for saliency detection. In *Proceedings of the IEEE/CVF international conference on computer vision*, pp. 7254–7263, 2019.

Michael I Posner, Steven E Petersen, et al. The attention system of the human brain. *Annual review of neuroscience*, 13(1):25–42, 1990.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International conference on machine learning*, pp. 8748–8763. PMLR, 2021.

Nikhila Ravi, Valentin Gabeur, Yuan-Ting Hu, Ronghang Hu, Chaitanya Ryali, Tengyu Ma, Haitham Khedr, Roman Rädle, Chloe Rolland, Laura Gustafson, et al. Sam 2: Segment anything in images and videos. *arXiv preprint arXiv:2408.00714*, 2024.

Jingjing Ren, Xiaowei Hu, Lei Zhu, Xuemiao Xu, Yangyang Xu, Weiming Wang, Zijun Deng, and Pheng-Ann Heng. Deep texture-aware features for camouflaged object detection. *IEEE Transactions on Circuits and Systems for Video Technology*, 33(3):1157–1167, 2021.

Przemysław Skurowski, Hassan Abdulameer, Jakub Błaszczyk, Tomasz Depta, Adam Kornacki, and Przemysław Kozieł. Animal camouflage analysis: Chameleon database. *Unpublished Manuscript*, 2018.

Martin Stevens and Sami Merilaita. Animal camouflage: current issues and new perspectives. *Philosophical Transactions of the Royal Society B: Biological Sciences*, 364(1516):423–427, 2009.

Robin Strudel, Ricardo Garcia, Ivan Laptev, and Cordelia Schmid. Segmenter: Transformer for semantic segmentation. In *ICCV*, pp. 7262–7272, 2021.

Yujia Sun, Shuo Wang, Chenglizhao Chen, and Tian-Zhu Xiang. Boundary-guided camouflaged object detection. *arXiv preprint arXiv:2207.00794*, 2022.

Longxiang Tang, Kai Li, Chunming He, Yulun Zhang, and Xiu Li. Source-free domain adaptive fundus image segmentation with class-balanced mean teacher. In *International Conference on Medical Image Computing and Computer-Assisted Intervention*, pp. 684–694. Springer, 2023.

Lijun Wang, Huchuan Lu, Yifan Wang, Mengyang Feng, Dong Wang, Baocai Yin, and Xiang Ruan. Learning to detect salient objects with image-level supervision. In *CVPR*, 2017a.

Linzhao Wang, Lijun Wang, Huchuan Lu, Pingping Zhang, and Xiang Ruan. Salient object detection with recurrent fully convolutional networks. *IEEE transactions on pattern analysis and machine intelligence*, 41(7):1734–1746, 2018.

Rui Wang, Caijuan Shi, Changyu Duan, Weixiang Gao, Hongli Zhu, Yunchao Wei, and Meiqin Liu. Camouflaged object segmentation with prior via two-stage training. *Computer Vision and Image Understanding*, 246:104061, 2024.

Tiantian Wang, Ali Borji, Lihe Zhang, Pingping Zhang, and Huchuan Lu. A stagewise refinement model for detecting salient objects in images. In *Proceedings of the IEEE international conference on computer vision*, pp. 4019–4028, 2017b.

Wenguan Wang, Qiuxia Lai, Huazhu Fu, Jianbing Shen, Haibin Ling, and Ruigang Yang. Salient object detection in the deep learning era: An in-depth survey. *IEEE TPAMI*, 44(6):3239–3259, 2021.

Wenhai Wang, Enze Xie, Xiang Li, Deng-Ping Fan, Kaitao Song, Ding Liang, Tong Lu, Ping Luo, and Ling Shao. Pvtv2: Improved baselines with pyramid vision transformer. *Computational Visual Media*, 8(3):1–10, 2022.

Jun Wei, Shuhui Wang, and Qingming Huang. F³net: fusion, feedback and focus for salient object detection. In *Proceedings of the AAAI conference on artificial intelligence*, volume 34, pp. 12321–12328, 2020.

Yu-Huan Wu, Yun Liu, Le Zhang, Ming-Ming Cheng, and Bo Ren. Edn: Salient object detection via extremely-downsampled network. *IEEE Transactions on Image Processing*, 31:3125–3136, 2022.

Yongqin Xian, Christoph H Lampert, Bernt Schiele, and Zeynep Akata. Zero-shot learning—a comprehensive evaluation of the good, the bad and the ugly. *IEEE TPAMI*, 41(9):2251–2265, 2018.

Enze Xie, Wenhai Wang, Zhiding Yu, Anima Anandkumar, Jose M Alvarez, and Ping Luo. Segformer: Simple and efficient design for semantic segmentation with transformers. *Advances in neural information processing systems*, 34:12077–12090, 2021.

Yunyang Xiong, Bala Varadarajan, Lemeng Wu, Xiaoyu Xiang, Fanyi Xiao, Chenchen Zhu, Xiaoliang Dai, Dilin Wang, Fei Sun, Forrest Iandola, et al. Efficientsam: Leveraged masked image pretraining for efficient segment anything. *arXiv preprint arXiv:2312.00863*, 2023.

Qiong Yan, Li Xu, Jianping Shi, and Jiaya Jia. Hierarchical saliency detection. In *CVPR*, 2013.

Zhiling Yan, Weixiang Sun, Rong Zhou, Zhengqing Yuan, Kai Zhang, Yiwei Li, Tianming Liu, Quanzheng Li, Xiang Li, Lifang He, et al. Biomedical sam 2: Segment anything in biomedical images and videos. *arXiv preprint arXiv:2408.03286*, 2024.

Chuan Yang, Lihe Zhang, Huchuan Lu, Xiang Ruan, and Ming-Hsuan Yang. Saliency detection via graph-based manifold ranking. In *CVPR*, 2013.

Fan Yang, Qiang Zhai, Xin Li, Rui Huang, Ao Luo, Hong Cheng, and Deng-Ping Fan. Uncertainty-guided transformer reasoning for camouflaged object detection. In *Proceedings of the IEEE/CVF international conference on computer vision*, pp. 4146–4155, 2021.

Bowen Yin, Xuying Zhang, Deng-Ping Fan, Shaohui Jiao, Ming-Ming Cheng, Luc Van Gool, and Qibin Hou. Camoformer: Masked separable attention for camouflaged object detection. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2024.

Li Yuan, Yunpeng Chen, Tao Wang, Weihao Yu, Yujun Shi, Zi-Hang Jiang, Francis EH Tay, Jiashi Feng, and Shuicheng Yan. Tokens-to-token vit: Training vision transformers from scratch on imagenet. In *ICCV*, pp. 558–567, 2021.

Qiang Zhai, Xin Li, Fan Yang, Chenglizhao Chen, Hong Cheng, and Deng-Ping Fan. Mutual graph learning for camouflaged object detection. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 12997–13007, 2021.

Wei Zhai, Yang Cao, Jing Zhang, and Zheng-Jun Zha. Exploring figure-ground assignment mechanism in perceptual organization. *Advances in Neural Information Processing Systems*, 35:17030–17042, 2022.

Chaoning Zhang, Dongshen Han, Yu Qiao, Jung Uk Kim, Sung-Ho Bae, Seungkyu Lee, and Choong Seon Hong. Faster segment anything: Towards lightweight sam for mobile applications. *arXiv preprint arXiv:2306.14289*, 2023.

Miao Zhang, Tingwei Liu, Yongri Piao, Shunyu Yao, and Huchuan Lu. Auto-msfnet: Search multi-scale fusion network for salient object detection. In *ACM MM*, pp. 667–676, 2021.

Miao Zhang, Shuang Xu, Yongri Piao, Dongxiang Shi, Shusen Lin, and Huchuan Lu. Preynet: Preying on camouflaged objects. In *Proceedings of the 30th ACM international conference on multimedia*, pp. 5323–5332, 2022.

Xiaoning Zhang, Tiantian Wang, Jinqing Qi, Huchuan Lu, and Gang Wang. Progressive attention guided recurrent network for salient object detection. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 714–722, 2018.

Xiaoqi Zhao, Youwei Pang, Lihe Zhang, Huchuan Lu, and Lei Zhang. Suppress and balance: A simple gated network for salient object detection. In *ECCV*, pp. 35–51. Springer, 2020.

Xiaoqi Zhao, Youwei Pang, Wei Ji, Baicheng Sheng, Jiaming Zuo, Lihe Zhang, and Huchuan Lu. Spider: A unified framework for context-dependent concept segmentation. In *ICML*, 2024.

Jiayuan Zhu, Yunli Qi, and Junde Wu. Medical sam 2: Segment medical images as video via segment anything model 2. *arXiv preprint arXiv:2408.00874*, 2024.

Mingchen Zhuge, Deng-Ping Fan, Nian Liu, Dingwen Zhang, Dong Xu, and Ling Shao. Salient object detection via integrity learning. *IEEE TPAMI*, 45(3):3738–3752, 2022.

APPENDIX

Table of contents:

A   CSCS METRIC

Contrary to the Intersection over Union (IoU) that measures accuracy for a single class, the Camouflage-Saliency Confusion Score (CSCS) assesses the misclassification between two distinct classes. The CSCS, designed to evaluate the confusion between camouflaged and salient objects, is calculated as follows:

$$\text{CSCS} = \frac{1}{2}\left(\frac{\mathcal{P}_{CS}}{\mathcal{P}_{BS} + \mathcal{P}_{SS} + \mathcal{P}_{CS}} + \frac{\mathcal{P}_{SC}}{\mathcal{P}_{BC} + \mathcal{P}_{SC} + \mathcal{P}_{CC}}\right), \tag{6}$$

where $\mathbb{P} = \{\mathcal{P}_{\lambda\theta} \,|\, \lambda \in \Theta, \theta \in \Theta\}$, $\Theta = \{B, C, S\}$, the B, C and S denote background, camouflage and saliency. A lower CSCS value indicates a stronger ability of the network to discriminate between salient and camouflaged objects. $\mathcal{P}_{CS}$ represents the label as camouflage but is predicted as saliency. We aim to minimize the misclassification of camouflaged pixels as salient, ensuring the network correctly distinguishes between camouflaged and salient objects. The same applies to $\mathcal{P}_{SC}$. As shown in Figure 7, we present the confusion matrix of the proposed USCNet on the CS12K test set. Our model balances improvements across all metrics, achieving a mIoU of 0.775 and a CSCS of 0.0749 (see Table 2 in the manuscript).

Image   GT   Prediction

Figure 6: The illustration of $\mathcal{P}_{BS}$, $\mathcal{P}_{SS}$, $\mathcal{P}_{CS}$, $\mathcal{P}_{BC}$, $\mathcal{P}_{SC}$, and $\mathcal{P}_{CC}$ in the CSCS metric. The **red** mask represents the salient regions, and the **green** mask denotes the camouflaged regions.

B   PERFORMANCE OF MODELS IN DETECTING OBJECTS OF VARYING SIZES

To evaluate the model's ability to detect objects of varying sizes, we employ several metrics: AUC↑, SI-AUC↑, F_m^β↑, SI-F_m^β↑, $F_{\max}^\beta$↑, SI-$F_{\max}^\beta$↑, E_m↑. From Table 4 and Table 5, it can be observed that, compared to the size-sensitive(e.g., AUC↑ and F_m^β↑) and size-invariance metrics(e.g., SI-AUC↑ and SI-F_m^β↑), our method exhibits smaller performance fluctuations, demonstrating its robustness to variations in object size and number in the scene.

Figure 7: Confusion matrix of our USCNet on the CS12K test set. The units of the values in the confusion matrix are in tens of thousands (**1E+04**).

Table 4: Performance of different models detecting salient objects on CS12K testing set.

Task	Model	Update Params(M)	CS12K-SOD						
			AUC↑	SI-AUC↑	F_m^β↑	SI-F_m^β↑	F_{max}^β↑	SI-F_{max}^β↑	E_m↑
SOD	GateNet Zhao et al. (2020)	128	.810	.812	.696	.754	.706	.764	.775
	F3Net Wei et al. (2020)	26	.828	.826	.722	.765	.734	.777	.803
	MSFNet Zhang et al. (2021)	28	.832	.831	.726	.772	.735	.782	.805
	VST Liu et al. (2021a)	43	.777	.777	.642	.732	.650	.741	.742
	EDN Wu et al. (2022)	43	.831	.830	.726	.769	.736	.780	.804
	ICON Zhuge et al. (2022)	32	.821	.832	.702	.764	.711	.774	.795
COD	SINetV2 Fan et al. (2021)	27	.843	.842	.755	.783	.765	.793	.827
	PFNet Mei et al. (2021)	47	.820	.822	.712	.756	.724	.767	.799
	ZoomNet Pang et al. (2022)	33	.821	.823	.710	.765	.720	.774	.791
	FEDER He et al. (2023)	44	.841	.842	.742	.784	.750	.796	.820
	ICEG He et al. (2024)	100	.830	.825	734	.762	.743	.770	.831
	PRNet Hu et al. (2024)	13	.851	.845	.742	.779	.750	.792	.832
	CamoFormer Yin et al. (2024)	71.4	.844	.843	.750	.782	.758	.790	.821
	PGT Wang et al. (2024)	68	.831	.828	.717	.773	.727	.784	.791
	SAM2-Adapter Chen et al. (2024)	4.36	.847	.847	.741	.783	.751	.794	.816
Unified	VSCode Luo et al. (2024)	60	.826	.830	.720	.769	.731	.790	.802
	EVP Liu et al. (2023)	4.95	.850	.847	.751	.782	.771	.792	.830
USCOD	USCNet(ours)	**4.04**	**.853**	**.850**	**.761**	**.787**	**.772**	**.798**	**.833**

Table 5: Performance of different models detecting camouflaged objects on CS12K testing set.

Task	Model	Update Params(M)	CS12K-COD						
			AUC↑	SI-AUC↑	F_m^β↑	SI-F_m^β↑	F_{max}^β↑	SI-F_{max}^β↑	E_m↑
SOD	GateNet Zhao et al. (2020)	128	.692	.687	.443	.558	.453	.569	.651
	F3Net Wei et al. (2020)	26	.695	.687	.449	.564	.458	.574	.649
	MSFNet Zhang et al. (2021)	28	.698	.691	.455	.565	.465	.576	.659
	VST Liu et al. (2021a)	43	.626	.625	.303	.536	.312	.546	.524
	EDN Wu et al. (2022)	43	.709	.703	.476	.575	.485	.585	.670
	ICON Zhuge et al. (2022)	32	.663	.663	.384	.549	.394	.560	.587
COD	SINetV2 Fan et al. (2021)	27	.715	.705	.505	.588	.514	.598	.690
	PFNet Mei et al. (2021)	47	.678	.672	.429	.544	.440	.555	.630
	ZoomNet Pang et al. (2022)	33	.657	.653	.394	.545	.405	.556	.588
	FEDER He et al. (2023)	44	.710	.703	.486	.567	.497	.578	.689
	ICEG He et al. (2024)	100	.730	.717	.525	.601	.532	.609	.719
	PRNet Hu et al. (2024)	13	.705	.695	.454	.569	.464	.579	.652
	CamoFormer Yin et al. (2024)	71.4	.756	.745	.565	.626	.575	.636	.743
	PGT Wang et al. (2024)	68	.746	.734	.527	.596	.539	.607	.715
	SAM2-Adapter Chen et al. (2024)	4.36	.770	.761	.575	.637	.585	.647	.746
Unified	VSCode Luo et al. (2024)	60	.735	.727	.519	.601	.525	.597	.722
	EVP Liu et al. (2023)	4.95	.695	.684	.485	.577	.494	.587	.650
USCOD	USCNet(ours)	**4.04**	**.801**	**.794**	**.610**	**.658**	**.619**	**.667**	**.795**

C   RESULTS ON COD AND SOD DATASETS

To further validate the effectiveness and robustness of our method regarding generalizability, we conduct tests on popular SOD datasets (DUTS Wang et al. (2017a), HKU-IS Li & Yu (2015), and

Table 6: Quantitative comparisons with related methods on the DUTS, HKU-IS, and DUT-OMRON test sets. ↑ / ↓ represents the higher/lower the score, the better.

Task	Model	Update Params(M)	DUTS $F_\beta^{\max}\uparrow$	$F_\beta^\omega\uparrow$	$M\downarrow$	$S_\alpha\uparrow$	$E_\phi^m\uparrow$	HKU-IS $F_\beta^{\max}\uparrow$	$F_\beta^\omega\uparrow$	$M\downarrow$	$S_\alpha\uparrow$	$E_\phi^m\uparrow$	DUT-OMRON $F_\beta^{\max}\uparrow$	$F_\beta^\omega\uparrow$	$M\downarrow$	$S_\alpha\uparrow$	$E_\phi^m\uparrow$
SOD	GateNet Zhao et al. (2020)	128	.666	.644	.062	.755	.765	.804	.785	.049	.841	.857	.634	.603	.079	.747	.751
	F3Net Wei et al. (2020)	26	.703	.683	.055	.783	.794	.832	.816	.044	.853	.881	.638	.615	.073	.747	.758
	MSFNet Zhang et al. (2021)	28	.651	.638	.063	.749	.758	.824	.806	.045	.853	.877	.641	.611	.076	.751	.764
	VST Liu et al. (2021a)	43	.630	.610	.061	.744	.749	.777	.760	.052	.820	.851	.580	.560	.073	.720	.715
	EDN Wu et al. (2022)	43	.692	.676	.053	.784	.785	.820	.806	.043	.852	.873	.616	.597	.071	.742	.735
	ICON Zhuge et al. (2022)	32	.679	.647	.069	.769	.785	.814	.787	.051	.843	.874	.615	.576	.099	.728	.738
COD	SINetV2 Fan et al. (2021)	27	.732	.710	.052	.801	.821	.838	.822	.046	.847	.884	.665	.642	.068	.763	.786
	PFNet Mei et al. (2021)	47	.691	.668	.060	.775	.790	.818	.801	.048	.843	.876	.643	.614	.075	.747	.764
	ZoomNet Pang et al. (2022)	33	.729	.709	.053	.801	.813	.785	.774	.051	.830	.842	.623	.601	.075	.742	.735
	FEDER He et al. (2023)	44	.736	.714	.052	.808	.821	.839	.827	.045	.869	.881	.645	.615	.077	.755	.760
	PRNet Hu et al. (2024)	13	.773	.756	.043	.830	.849	.840	.833	.044	.857	.880	.708	.685	.057	**.796**	.808
	ICEG He et al. (2024)	100	.719	.700	.050	.789	.820	.832	.815	.045	.848	**.896**	.664	.645	.061	.762	.785
	CamoFormer Yin et al. (2024)	71.4	.733	.715	.049	.813	.819	.838	.817	.046	.857	.884	.687	.661	.066	.783	.793
	PGT Wang et al. (2024)	68	.686	.670	.053	.786	.779	.819	.802	.044	.855	.871	.642	.619	.068	.758	.754
	SAM-Adapter Chen et al. (2023a)	4.11	.761	.746	.048	.834	.796	.822	.806	.043	.836	.869	.708	.685	.059	.793	.802
	SAM2-Adapter Chen et al. (2024)	4.36	.776	.762	.041	.831	.848	.831	.828	**.042**	.849	.881	.706	.692	**.056**	.790	.810
Unified	VSCode Luo et al. (2024)	60	.724	.706	.060	.795	.812	.834	.830	.043	.851	.885	.636	.608	.075	.748	.753
	EVP Liu et al. (2023)	4.95	.769	.750	.045	.833	.836	.835	.832	.043	.852	.878	**.710**	.692	.057	.794	.810
USCOD	**USCNet(ours)**	**4.04**	**.784**	**.780**	**.040**	**.835**	**.852**	**.844**	**.840**	**.042**	**.860**	.886	**.710**	**.697**	**.056**	**.796**	**.814**

Table 7: Quantitative comparisons with ten related methods on CAMO , COD10K , and NC4K test set. ↑ / ↓ represents the higher/lower the score, the better.

Task	Model	Update Params(M)	CAMO $F_\beta^{\max}\uparrow$	$F_\beta^\omega\uparrow$	$M\downarrow$	$S_\alpha\uparrow$	$E_\phi^m\uparrow$	NC4K $F_\beta^{\max}\uparrow$	$F_\beta^\omega\uparrow$	$M\downarrow$	$S_\alpha\uparrow$	$E_\phi^m\uparrow$	COD10K $F_\beta^{\max}\uparrow$	$F_\beta^\omega\uparrow$	$M\downarrow$	$S_\alpha\uparrow$	$E_\phi^m\uparrow$
SOD	GateNet Zhao et al. (2020)	128	.573	.542	.109	.666	.680	.562	.529	.047	.707	.724	.675	.645	.066	.752	.777
	F3Net Wei et al. (2020)	26	.538	.506	.117	.643	.657	.576	.539	.047	.712	.744	.661	.633	.070	.738	.773
	MSFNet Zhang et al. (2021)	28	.568	.535	.113	.661	.682	.543	.534	.052	.692	.719	.671	.645	.067	.747	.778
	VST Liu et al. (2021a)	43	.484	.455	.109	.661	.631	.468	.430	.055	.661	.670	.597	.567	.072	.710	.732
	EDN Wu et al. (2022)	43	.573	.542	.109	.666	.680	.595	.562	.044	.727	.756	.688	.660	.063	.761	.795
	ICON Zhuge et al. (2022)	32	.520	.481	.125	.641	.648	.540	.502	.053	.695	.715	.631	.596	.076	.724	.752
COD	SINetV2 Fan et al. (2021)	27	.590	.562	.102	.681	.694	.609	.577	.043	.729	.763	.662	.639	.066	.740	.769
	PFNet Mei et al. (2021)	47	.535	.505	.110	.652	.661	.556	.524	.049	.699	.730	.660	.633	.068	.737	.769
	ZoomNet Pang et al. (2022)	33	.494	.472	.113	.635	.612	.520	.496	.048	.488	.671	.596	.576	.074	.708	.706
	FEDER He et al. (2023)	44	.567	.538	.106	.669	.687	.636	.598	.042	.749	.793	.688	.664	.063	.758	.790
	PRNet Hu et al. (2024)	13	.648	.607	.096	.716	.766	.709	.672	.059	.772	.820	.650	.603	.038	.756	.815
	ICEG He et al. (2024)	100	.728	.697	.066	.769	.820	.735	.708	.051	.786	.840	.645	.610	.035	.753	.807
	CamoFormer Yin et al. (2024)	71	.645	.618	.078	.732	.750	.729	.707	.054	.789	.822	.668	.639	.035	.770	.811
	PGT Wang et al. (2024)	68	.635	.612	.089	.718	.730	.729	.706	.052	.791	.819	.642	.612	.036	.758	.786
	SAM-Adapter Chen et al. (2023a)	4.11	.661	.638	.080	.744	.753	.688	.667	.037	.788	.808	.727	.710	.051	.794	.809
	SAM2-Adapter Chen et al. (2024)	4.36	.717	.692	.074	.779	.807	.724	.694	.044	.809	.847	.735	.694	.045	.819	.845
Unified	VSCode Luo et al. (2024)	60	.562	.532	.109	.658	.678	.626	.591	.043	.744	.787	.684	.662	.067	.753	.783
	EVP Liu et al. (2023)	4.95	.636	.637	.085	.701	.718	.693	.694	.040	.742	.775	.615	.614	.069	.724	.749
USCOD	**USCNet(ours)**	**4.04**	**.829**	**.790**	**.049**	**.845**	**.886**	**.794**	**.768**	**.039**	**.839**	**.877**	**.743**	**.700**	**.030**	**.821**	**.869**

DUT-OMRON Yang et al. (2013)) and COD datasets (CAMO Le et al. (2019), COD10K Fan et al. (2020), and NC4K Lv et al. (2021)), with all methods uniformly trained using our CS12k dataset. We adopt five metrics that are widely used in COD and SOD tasks Wang et al. (2021); Fan et al. (2021). These metrics include maximal F-measure ($F_\beta^{\max}$ ↑) Achanta et al. (2009), weighted F-measure (F_β^ω ↑) Margolin et al. (2014), Mean Absolute Error (MAE, M ↓) Perazzi et al. (2012), Structural measure (S-measure, S_α ↑) Fan et al. (2017), and mean Enhanced alignment measure (E-measure, E_ϕ^m ↑) Fan et al. (2018b). As shown in Table 6 and Table 7, our USCNet achieves state-of-the-art performance on these datasets through parameter-efficient fine-tuning. This further confirms the strong capability of our method to accurately identify both salient and camouflaged objects in unconstrained environments. This achievement is attributed to the exceptional versatility of SAM in class-agnostic segmentation tasks and the discriminative ability of our specially designed APG for distinguishing between salient and camouflaged objects.

D MORE TECHNICAL DETAILS

Backbone of models. The models compared can be divided into two categories based on their papers: one is full-tuning models, and the other is parameter-efficient fine-tuning (PEFT) models.(i)Full Tuning models: Include all SOD and COD methods and VSCode in the Unified Method. For fairness, the models compared are all trained according to the configurations specified in their original papers. (ii)PEFT models: SAM-Adapter, SAM2-Adapter, EVP in the Unified Method and our model. The backbone architectures across various models consist of several types. For full tuning, VST employs a transformer encoder based on T2T-ViT Yuan et al. (2021), while SINet-V2utilizes Res2Net-50 Gao et al. (2019). VSCode uses Swin-T Liu et al. (2021b), and ICEG adopts Swin-B Liu et al. (2021b). PRNet is based on the SMT backbone Lin et al. (2023), and both CamoD-iffusion, CamoFormer, and PGT use PVTv2-b4 Wang et al. (2022). Other models generally rely on ResNet-50 He et al. (2016) with pre-trained weights from ImageNet Deng et al. (2009). In the case of PEFT models, EVP uses SegFormer-B4 Xie et al. (2021) as its base, SAM-Adapter uses the default ViT-H version of SAM Kirillov et al. (2023), and both SAM2-Adapter and our model employ the hiera-large version of SAM2 Ravi et al. (2024).

Training and Inference. For traditional SOD and COD models: The task of USCOD is defined by three attributes: saliency, camouflage, and background. Conventional methods for COD and SOD are crafted for dichotomous mapping tasks and don't seamlessly transition to the nuanced demands of USCOD. Inspired by seminal works in semantic segmentations Long et al. (2015); Strudel et al. (2021), we retool the output layers of our models to yield a tripartite representation for saliency, camouflage, and background. This is achieved by harnessing a softmax layer to generate a predictive mapping. We employ a cross-entropy loss function to refine the model, which is congruent with our overarching methodological framework. For unified models: VSCode and EVP, which require task-specific prompts for each dataset, we create two copies of the CS12K training set. One copy is used for SOD, with the ground truth being the SOD-only mask, and is used to train the prompts corresponding to the SOD task. The other copy is used for COD, with the ground truth being the COD-only mask, and is used to train the prompts corresponding to the COD task.VSCode is trained once using all 16,800 images (two copies of 8,400 images), while EVP is trained twice on the two separate training sets (each containing 8,400 images) to obtain the two task-specific prompts. During Inference, all unified models perform inference on the testing set of CS12K twice, with the corresponding prompt enabled for each task. The first inference run generates the SOD results, and the second inference run generates the COD results. The final prediction is obtained by merging the SOD and COD predictions. For overlapping pixels, the attribute with the higher prediction value between the two tasks is chosen as the final attribute for that pixel.

E MORE CS12K DATASET DETAIL AND EXAMPLES

Object number distribution. Our CS12K dataset contains images with different numbers of objects. To show it more clearly, we have counted the distribution of images with different numbers of objects in CS12K, as shown in the following Table 8.

Table 8: Distribution of Images with Different Numbers of Objects in CS12K.

Number of objects	0	1	2	>2
Number of images	3000	4197	2335	2468

Detail of annotation process. For Scene A and B, we retained their original annotations, while Scene D did not require additional annotation. Therefore, we focus here on detailing the annotation process for Scene C.

- **Initial Determination of Object Attributes:** We invited 7 observers to perform the initial identification of salient and camouflaged objects in the images. A voting process was used to determine the salient and camouflaged objects in each image, with objects and their attributes receiving more than half of the votes being retained. We then used Photoshop to apply red boxes for salient objects and green boxes for camouflaged objects, which served as the reference for the subsequent mask annotation step.

- **Mask Annotation:** We invited 9 volunteers to perform detailed mask annotation for the dataset using the ISAT interactive annotation tool Ji & Zhang (2023), which supports SAM semi-automatic labeling.

- **Annotation Quality Control:** After annotation, we invited an additional 3 observers to review and refine the results. Masks with imprecise or incorrect annotations were manually corrected.

More CS12K examples. In Figure 8, we illustrate a selection of images from the CS12K dataset, each featuring both salient and camouflaged objects. The main difference between our CS12K dataset and existing SOD and COD datasets is that it includes a curated subset of 3,000 images, each featuring both salient and camouflaged objects. We invest significant time and effort in finding and annotating these images. Our dataset spans an extensive variety of environments, including, but not limited to, terrestrial, aquatic, alpine, sylvan, and urban ecosystems, and encompasses a broad spectrum of categories, such as lion, flower and various fruit species. This dataset is designed to assist the SOD and COD research communities in advancing the state-of-the-art in discerning more sophisticated saliency and camouflage patterns.

Figure 8: Additional Example images where exist both camouflaged and salient objects from the CS12K dataset. Our collection comprises 3,000 carefully curated and annotated images, encompassing a diverse range of scenes and categories. **Please zoom in for an enhanced view**.

F ADDITIONAL QUALITATIVE RESULTS

We present additional predictive results of our USCNet model compared to other COD and SOD models in the CS12K test set. As illustrated in Figure 11, our model outperforms its competitors. Specifically, across four different scenes, our model demonstrates a high degree of consistency with the ground truth, especially in distinguishing between salient and camouflaged objects. Our model is adept at learning distinctive features of saliency and camouflage. For instance, it can accurately identify patterns such as camouflaged humans (refer to the fifth column of Figure 11). Moreover, in scenes devoid of salient or camouflaged objects, our model remains unaffected by complex backgrounds (refer to the sixth column of Figure 11). This further underscores the robustness and accuracy of our USCNet model.

G   PRACTICAL APPLICATIONS OF USCOD

Military Surveillance and Enemy Reconnaissance. In a military environment, salient objects might include large military equipment such as vehicles, tanks, helicopters, etc., while camouflaged objects could be soldiers or equipment hidden in vegetation or camouflage materials. The simultaneous detection of both salient and camouflaged objects helps enhance battlefield situational awareness and prevents overlooking potential threats.

Post-Disaster Search and Rescue. After a disaster, salient objects might include obvious signs of life in rubble (such as clearly visible trapped individuals), while camouflaged objects could be life signs that are difficult to detect due to obstruction or chaotic environments (such as partially buried survivors). The simultaneous detection of both salient and camouflaged objects is crucial for improving search and rescue efficiency.

Ecological Protection and Wildlife Monitoring. In natural environments, salient objects might be easily visible animals (such as birds in open areas), while camouflaged objects could be animals hidden in vegetation (such as insects with protective coloration). The simultaneous detection of both salient and camouflaged objects allows for more comprehensive wildlife population surveys and ecological research.

Multi-Level Lesion Detection. In medical imaging, detecting both salient lesions (such as obvious tumors or organ damage) and camouflaged lesions (such as those blurred by background textures or early-stage lesions) helps doctors more thoroughly assess a patient's health condition.

Diving Hazard Warnings. During diving, salient objects might include coral or schools of fish that attract the diver's attention, while camouflaged objects could be hidden dangerous creatures (such as stonefish or moray eels). The simultaneous detection of both salient and camouflaged objects helps guide divers in more comprehensively avoiding dangers.

H   DIFFICULTY OF USCOD

As illustrated in Figure 11, most methods encounter difficulties in distinguishing salient objects from camouflaged on CS12K benchmark. The essence of the challenge in USCOD lies in differentiating between salient and camouflaged objects within unconstrained scenes, mirroring the capabilities of human vision. Moving beyond the simplicity of traditional classification tasks, distinguishing between visual saliency and camouflage requires a deeper semantic insight. Our observation indicates that when a vanilla network architecture is used for the USCOD task, a decoder responsible for differentiating, localizing, and segmenting both salient and camouflaged objects encounters challenges in acquiring highly discriminative visual features. To address this, our approach leverages a specialized decoder focused on precise localization and segmentation. This allows for more effective learning of the subtle distinctions between saliency and camouflage patterns, enhancing the ability to discern and differentiate these complex visual cues. Figure 9 showcases our architectural innovation, incorporating a frozen, pre-trained SAM mask decoder and an APG representing our venture into mining highly discriminative features. This design separates feature analysis from object segmentation, enabling our model to focus on and extract distinct attributes crucial for differentiating saliency from camouflage patterns, thereby improving its performance in complex visual environments.

(a) Vanilla   (b) Proposed

Figure 9: (a) In Vanilla network architecture, a decoder is used for both localization and segmentation. (b) In our proposed architecture, the APG is used for localizing salient and camouflaged objects, while the mask decoder is used for segmentation.

Image   USCOD-GT   USCIS-GT

Figure 10: An illustration of the USCOD and USCIS tasks: In contrast to USCOD, USCIS requires not only the identification of salient versus camouflaged objects but also the discrimination between individual instances of saliency and camouflage.

I LIMITATIONS

USCOD aims to adaptively identify salient and camouflaged objects in unconstrained open scenarios, where each image may exist salient object, camouflaged object, both, or neither of them. Although our proposed CS12K dataset encompasses a wide array of scenarios and object categories, thereby enriching the learning experience for salient and camouflaged feature detection within unconstrained scenes for the COD and SOD communities, USCOD falls short in one critical aspect: it lacks the capability to differentiate between individual instances of salient and camouflaged objects. Specifically, USCOD is limited in recognizing the quantity of such instances and in distinguishing among different objects. This limitation undermines the effectiveness of algorithm in accurately discerning the unique camouflage and saliency patterns of each object. Moving forward, our research will venture into the domain of Unconstrained Salient and Camouflaged Instance Segmentation (USCIS), which strives to identify and segment each individual instance of salient and camouflaged objects. Figure 10 illustrates the label differences between USCOD and USCIS within the same image.

Figure 11: Additional visualizations of the proposed USCNet and other state-of-the-art methods on the CS12K test set. **Zoom-in for better view.**