Molecule Generation by Principal Subgraph Mining and Assembling

Abstract

Molecule generation is central to a variety of applications. Current attention has been paid to approaching the generation task as subgraph prediction and assembling. Nevertheless, these methods usually rely on hand-crafted or external subgraph construction, and the subgraph assembling depends solely on local arrangement. In this paper, we define a novel notion, *principal subgraph* that is closely related to the informative pattern within molecules. Interestingly, our proposed merge-and-update subgraph extraction method can automatically discover frequent principal subgraphs from the dataset, while previous methods are incapable of. Moreover, we develop a two-step subgraph assembling strategy, which first predicts a set of subgraphs in a sequence-wise manner and then assembles all generated subgraphs globally as the final output molecule. Built upon graph variational auto-encoder, our model is demonstrated to be effective in terms of several evaluation metrics and efficiency, compared with state-of-the-art methods on distribution learning and (constrained) property optimization tasks.

1 Introduction

Generating chemically valid molecules with desired properties is central to a variety of applications in drug discovery and material science. In contrast to searching countless potential candidates by expert chemists or pharmacologists, designing generative models that can produce molecules automatically is more efficient and now a prevailing topic in machine learning. Recently, there have been various works[18, 26, 45, 24, 9, 38, 20] utilizing graphs to characterize the distribution of atoms and bonds within each molecule.

Figure 1: Five frequent subgraphs in standard ZINC250K [16, 23]. The percentage means the ratio of the molecules that contain the subgraph.

In general, these graph-based generation methods can be clustered into two categories: the atom level [25, 45, 26, 20] and the subgraph level [18, 19, 44], in terms of what the basic generation unit is. Compared with the atom-level methods, exploring subgraphs for generating molecules (as illustrated in Figure 1) exhibits three potential benefits. First, it can capture the regularities of atomic combinations and discover repetitive patterns in molecules, thus more capable of generating realistic molecules. Second, it is able to reflect chemical properties, since it has been revealed that the chemical properties are closely related to certain substructures (i.e., subgraphs) [30, 20]. Finally, leveraging subgraphs as the building blocks enables efficient training and inference, as the searching time is remarkably reduced by representing a molecule as a set of subgraphs other than atoms.

However, current subgraph-level methods [18, 19, 44] are still suboptimal in two senses. For one thing, the vocabulary of the molecular fragments is constructed by simple hand-crafted rules [18, 19] or borrowed straightly from external chemical fragment libraries [44], which is unable (at least uncertain) to reveal the frequent patterns existing in the dataset. For another, the prediction and the assembling of the subgraphs are conducted either autoregressively [19, 44] or according to a pre-defined tree structure [18], both of which are inflexible and defective, since each newly predicted subgraph is only allowed to attach a local set of previous subgraphs during the assembling process.

To address the above two pitfalls, this paper proposes Principal Subgraph Variational Auto-Encoder (PS-VAE), a novel framework for molecule generation. PS-VAE first creates a vocabulary of molecular fragments from any given dataset, which starts from all distinct atoms and then merges the neighboring fragments as a new one to update the vocabulary. Interestingly, the fragments derived by such a merge-and-update strategy are actually *principal subgraphs* which, as a novel concept defined by this paper, represent the frequent and largest repetitive patterns of molecules. We also theoretically prove that any principal subgraph can be universally covered by our vocabulary. Moreover, we develop a two-step subgraph assembling strategy, which first predicts a set of fragments in a sequence-wise manner and then assembles all generated subgraphs globally as the final output molecule. This two-step fashion makes our method less permutation-dependent and focus more on global connectivity against traditional methods [18, 19, 44].

We conduct extensive experiments on the ZINC250K [16] and QM9 [6, 36] datasets. Results demonstrate that our PS-VAE outperforms state-of-the-art models on distribution learning, (constrained) property optimization as well as GuacaMol goal-directed benchmarks [7]. Besides, PS-VAE is efficient and about six times faster than the fastest autoregressive baseline.

2 Related Work

Molecule Generation. Regarding the representation of molecules, existing generation models can be divided into two categories: text-based and graph-based methods. Text-based models [13, 23, 5] usually adopt the Simplified Molecular-Input Line-entry System ([39], SMILES) to describe each molecular, which is simple and efficient. However, these models are not robust because certain slight perturbations in SMILES could result in significant changes in molecule structure [45, 24]. The graph-based counterparts [9, 38, 20], therefore, have gained increasing attention recently. Li et al. [25] proposed a generation model for graphs and demonstrated it performed better than the text-based strategy. You et al. [45] used reinforcement learning to generate molecules sequentially under the guidance of mixed rewards in terms of the chemical validity and other property scores. Popova et al. [33] proposed MRNN to autoregressively generate nodes and edges. Shi et al. [38] designed a flow-based autoregressive model and exploited reinforcement learning for goal-directed generation. However, these models use atoms as the basic generation unit, leading to long sequences and therefore time-consuming training process. On the contrary, our method applies subgraph-level representation, which not only captures chemical properties but also is computationally efficient.

Subgraph-Level Molecule Generation Several works have been developed for subgraph-level generation. In particular, Jin et al. [18] suggested generating molecules in the form of junction trees where each node is a ring or edge. Jin et al. [19] decomposed molecules into subgraphs by breaking all the bridge bonds. It used a complex hierarchical model for polymer generation and graph-to-graph translation. Yang et al. [44] integrated reinforcement learning with the subgraph vocabulary created from existing chemical fragment libraries. Different from Jin et al. [18, 19], Yang et al. [44] which use manual rules to extract subgraphs or utilize existing libraries, we automatically extract frequent principal subgraphs to better capture the regularities in molecules for subgraph-level decomposition. Our work also relates to traditional subgraph mining literature [15, 43, 32]. While seeking generic frequent subgraphs is known to be NP-hard [22, 17], our work focuses on finding frequent principal subgraphs by merging two adjacent fragments, which alleviates time complexity to a large extent. To the best of our knowledge, we are the first to utilize frequent subgraphs in generation tasks.

3 Our Proposed PS-VAE

This section presents the details of the proposed PS-VAE, consisting of the principal subgraph definition and extraction in Section 3.1 and the two-step generation in Section 3.2.

3.1 Principal Subgraph

A molecule can be represented as a graph $\mathcal{G} = \langle \mathcal{V}, \mathcal{E} \rangle$, where $\mathcal{V}$ is a set of nodes corresponding to atoms and $\mathcal{E}$ is a set of edges corresponding to chemical bonds. We define a *subgraph* of $\mathcal{G}$ as $\mathcal{S} = \langle \tilde{\mathcal{V}}, \tilde{\mathcal{E}} \rangle \subseteq \mathcal{G}$, were $\tilde{\mathcal{V}} \subseteq \mathcal{V}$ and $\tilde{\mathcal{E}} \subseteq \mathcal{E}$. We say subgraph $\mathcal{S}$ *spatially intersects* with subgraph $\mathcal{S}'$ if there are certain atoms in a molecule belong to both $\mathcal{S}$ and $\mathcal{S}'$, denoted as $\mathcal{S} \cap \mathcal{S}' \neq \emptyset$. Note that if two subgraphs look the same (with the same topology), but they are constructed by different atom instances, they are not spatial intersected. Similarly, if two subgraphs $\mathcal{S}$ and $\mathcal{S}'$ appear in the same molecule, we call their *spatially union* subgraph as $\mathcal{U} = \mathcal{S} \bigcup \mathcal{S}'$, where the nodes of $\mathcal{U}$ are the union set of $\tilde{\mathcal{V}}$ and $\tilde{\mathcal{V}}'$, and its edges are the union of $\tilde{\mathcal{E}}$ and $\tilde{\mathcal{E}}'$ plus all edges connecting $\mathcal{S}$ and $\mathcal{S}'$. A *decomposition* of a molecule $\mathcal{G}$ is derived as a set of non-overlapped subgraphs $\{\mathcal{S}_i\}_i^n$ and the edges connecting them $\{\mathcal{E}_{ij}\}_{i,j}^{n,n}$, if $\mathcal{G} = (\bigcup_i^n \mathcal{S}_i) \bigcup (\bigcup_{i,j}^{n,n} \mathcal{E}_{ij})$ and $\mathcal{S}_i \cap \mathcal{S}_j = \emptyset$ for any $i \neq j$. The *frequency* of a subgraph occurring in all molecules of a given dataset measures its repeability and epidemicity, which should be an important property. Formally, we define the frequency of a subgraph $\mathcal{S}$ as $c(\mathcal{S}) = \sum_i c(\mathcal{S}|\mathcal{G}_i)$ where $c(\mathcal{S}|\mathcal{G}_i)$ computes the occurrence of $\mathcal{S}$ in a molecule $\mathcal{G}_i$. Without loss of generality, we assume all molecules and subgraphs we discuss are connected.

With the aforementioned notations, we propose a novel and central concept below.

Definition 3.1 (Principal Subgraph). We call subgraph $\mathcal{S}$ a principal subgraph, if any other subgraph $\mathcal{S}'$ that spatially intersects with $\mathcal{S}$ in a certain molecule satisfies either $\mathcal{S}' \subseteq \mathcal{S}$ or $c(\mathcal{S}') \leq c(\mathcal{S})$. Amongst all subgraphs of the larger frequency, a principal subgraph basically represents the "largest" repetitive pattern in size within the data. It is desirable to leverage patterns of this kind as the building blocks for molecule generation since those subgraphs with a larger size than them are less frequent/reusable. We will prove that our designed vocabulary is capable of mining these subgraphs.

Now we introduce the proposed vocabulary construction process. We call each subgraph of the constructed vocabulary as a *fragment*. We generate all fragments via the following stages:

Initialization. The vocabulary $\mathbb{V}$ is initialized with all unique atoms (subgraph with one node).

Merge. For every two neighboring fragments $\mathcal{F}$ and $\mathcal{F}'$ in the current vocabulary, we merge them by deriving the union $\mathcal{F} \bigcup \mathcal{F}'$. Here, the neighboring fragments of a given fragment $\mathcal{F}$ in a molecule is defined as the ones that contain at least one first-order neighbor nodes of a certain node in $\mathcal{F}$.

Update. We count the frequency of each identical merged subgraph in the last stage. We choose the most frequent one as a new fragment in the vocabulary $\mathbb{V}$. Then, we go back to the merge stage until the vocabulary size reaches the predefined number N.

Algorithm 1 Principal Subgraph Extraction

1: **Input:** A set of graphs $\mathcal{D}$ and the desired number N of principal subgraphs to learn.
2: **Output:** A set of principal subgraphs $\mathbb{V}$ and the counter $\mathcal{C}$ of principal subgraphs.
3: $\mathbb{V} \leftarrow \{\text{GraphToSMILES}(\langle\{a\}, \emptyset\rangle)\}$; {*Initially, $\mathbb{V}$ corresponds to all atoms a that appear in $\mathcal{D}$.*}
4: $N' \leftarrow \max(N, |\mathbb{V}|)$;
5: **while** $|\mathbb{V}| < N'$ **do**
6:    $\mathcal{C} \leftarrow \text{EmptyMap}()$; {*Initialize a counter.*}
7:    **for** $\mathcal{G}$ in $\mathcal{D}$ **do**
8:      **for** $\langle \mathcal{F}_i, \mathcal{F}_j, \mathcal{E}_{ij} \rangle$ in $\mathcal{G}$ **do**
9:        $\mathcal{F} \leftarrow \text{Merge}(\langle \mathcal{F}_i, \mathcal{F}_j, \mathcal{E}_{ij} \rangle)$; {*Merge neighboring fragments into a new fragment.*}
10:        $s \leftarrow \text{GraphToSMILES}(\mathcal{F})$; {*Convert the graph to SMILES representation.*}
11:        $\mathcal{C}[s] = \mathcal{C}[s] + 1$; {*Update the counter. The initial value is 0.*}
12:      **end for**
13:    **end for**
14:    $s = \text{TopElem}(\mathcal{C})$; {*Find the most frequent merged fragment.*}
15:    $\mathcal{F} \leftarrow \text{SMILESToGraph}(s)$; {*Convert the SMILES string to graph representation.*}
16:    $\mathbb{V} \leftarrow \mathbb{V} \cup \{s\}; \mathcal{D}' \leftarrow \{\}$;
17:    **for** $\mathcal{G}$ in $\mathcal{D}$ **do**
18:      $\mathcal{G}' \leftarrow \text{MergeSubGraph}(\mathcal{G}, \mathcal{F})$; {*Update the graph representation if possible.*}
19:      $\mathcal{D}' \leftarrow \mathcal{D}' \cup \{\mathcal{G}'\}$;
20:    **end for**
21:    $\mathcal{D} \leftarrow \mathcal{D}'$;
22: **end while**

(a) Initialization   (b) Iteration 1   (c) Iteration 2

Figure 2: Fragment extraction on {C=CC=C,CC=CC,C=CCC}. (a) Initialize vocabulary with atoms. (b) Fragment CC is the most frequent and added to the vocabulary. All CC are merged and highlighted in red. (c) Fragment C=CC is the most frequent and added to the vocabulary. All C=CC are merged and highlighted in green (molecules 1 and 3). After 2 iterations the vocabulary is {C, CC, C=CC}.

Figure 2 illustrates the above processes and Algorithm 1 gives the flowchart. Notice that Algorithm 1 has exploited the conversion from molecular subgraph to SMILES [39] to not only ensure the

Figure 3: Overview of the *principal subgraph variational auto-encoder*. (a) Subgraph-level decomposition. Atoms and bonds of different principal subgraphs are highlighted in different colors. (b) Molecular graph. We inject subgraph-level information into the molecular graph through atom features. (c) Latent space encoding. We obtain the latent variable z through the graph encoder. (d) Subgraph-level sequence generation. A sequence of principal subgraphs is autoregressively decoded from the latent variable by a GRU. (e) Incomplete molecular graph. The generated principal subgraphs form an incomplete molecular graph where inter-subgraph bonds are absent. (f) Bond completion. Completion of inter-subgraph bonds is formalized as a link prediction task for a GNN. After training, we can directly sample from the latent space to generate molecules.

118 uniqueness but also better calculate the occurrence of each merged subgraph by string comparison.
119 One notable merit is that we always track the decomposition of each molecule at each iteration, which
120 is crucial for the training of the two-step decoder introduced in the next subsection.

121 More importantly, we have the following theorem to demonstrate the benefit of Algorithm 1.

122 **Theorem 3.2.** *The vocabulary* $\mathbb{V}$ *constructed by Algorithm 1 exhibits the following advantages.*

123   *(i) **Monotonicity**: The frequency of the non-single-atom fragments in* $\mathbb{V}$ *decreases monotoni-*
124   *cally, namely,* $\forall \mathcal{F}_i, \mathcal{F}_j \in \mathbb{V}, c(\mathcal{F}_i) \leq c(\mathcal{F}_j),$ *if* $i \geq j.$

125   *(ii) **Significance**: Each fragment* $\mathcal{F}$ *in* $\mathbb{V}$ *is a principal subgraph.*

126   *(iii) **Completeness**: For any principal subgraph* $\mathcal{S}$ *arising in the dataset, there always exits a*
127   *fragment* $\mathcal{F}$ *in* $\mathbb{V}$ *satisfying* $\mathcal{S} \subseteq \mathcal{F}, c(\mathcal{S}) = c(\mathcal{F})$*, when* $\mathbb{V}$ *has collected all fragments with*
128   *frequency no less than* $c(\mathcal{S}).$

129 The conclusion by Theorem 3.2 is interesting and valuable. It states that our algorithm is able
130 to discover frequent principal subgraphs, and any principal subgraph can be represented (at least
131 contained) by our certain extracted fragment if the size of the vocabulary is sufficiently large. This
132 is also a meaningful extension to traditional subgraph mining literature [17], in which seeking the
133 most frequent subgraphs is known to be NP-hard. Algorithm 1 can somehow address this problem
134 efficiently by focusing mainly on finding the most frequent principal subgraphs.

135 ## 3.2 Two-step Molecule Generation

136 The molecule generation is modeled as a two-step task: first predicting which fragment should be
137 chosen from the vocabulary created in the last subsection, and then proceeding with how to assemble
138 the predicted fragments. Although in the first step we predict the fragments in a sequence-wise
139 manner, we globally investigate if every two predicted fragments should be linked in the second
140 step. This two-step fashion makes our method not only less permutation-dependent and thus more
141 sample-efficient than the generic autoregressive counterparts [25], but also more flexible than the
142 methods [18] that require predefined junction tree or adjacent connections between subgraphs. We
143 will provide experimental evaluations in Table 4 to justify the benefit of our proposed two-step
144 generation strategy. Below, we provide the details of the two steps.

145 **What to assemble.** This step is of the VAE style [21]. As shown in Figure 3, we use a GNN to
146 encode a molecular graph $\mathcal{G}$ into a latent variable z. Each node v has a feature vector x_v which is the
147 concatenation of three learnable embeddings: its atomic type, fragment type and the generation order
148 of the fragment. Each edge has a feature vector indicating its bond type. Specifically, we utilize GIN
149 with edge feature [14] as the backbone GNN network, which computes the k-th layer as follows:

$$\boldsymbol{a}_v^{(k)} = \sum_{u \in \mathcal{N}(v)} \mathrm{ReLU}(\boldsymbol{h}_u^{(k-1)} + \boldsymbol{e}_{uv}), \tag{1}$$

$$\boldsymbol{h}_v^{(k)} = h_\Theta((1 + \varepsilon)\boldsymbol{h}_v^{(k-1)} + \boldsymbol{a}_v^{(k)}), \tag{2}$$

where, $\boldsymbol{h}_v^{(k)}$ is the hidden activation of node v ($\boldsymbol{h}_v^{(0)} = \boldsymbol{x}_v$), $\boldsymbol{e}_{uv}$ is the edge feature between node u and v, $\mathcal{N}(v)$ returns the neighbos of u, h_Θ is a neural network, and ε is a constant. We implement h_Θ as a 2-layer Multi-Layer Perceptron ([10], MLP) with ReLU activation and set $\varepsilon = 0$. We obtain the final representations of nodes as $\boldsymbol{h}_v = [\boldsymbol{h}_v^{(1)}, \ldots, \boldsymbol{h}_v^{(t)}]$ so that it contains the contextual information from 1-hop to t-hop. The graph-level representation is given by summation $\boldsymbol{h}_\mathcal{G} = \sum_{v \in \mathcal{V}} \boldsymbol{h}_v$. We use $\boldsymbol{h}_\mathcal{G}$ to obtain the mean $\boldsymbol{\mu}_\mathcal{G}$ and log variance $\boldsymbol{\sigma}_\mathcal{G}$ of variational posterior approximation $q(\boldsymbol{z}|\mathcal{G})$ through two separate linear layers and use the reparameterization trick [21] to sample from the distribution in the training process.

Given a latent variable $\boldsymbol{z}$, our model first uses an autoregressive sequence generation model $P(\mathcal{F}_i|\mathcal{F}_{<i}, \boldsymbol{z})$ to decode an sequence of graph fragments $[\mathcal{F}_1, \ldots, \mathcal{F}_n]$. Note that the set of subgraphs into which a molecule is decomposed should not be ordered. Here, although we violate this law by using the ordered decoder, this issue is practically relieved by data augmentation of random fragment permutations during training, and it is further mitigated by the second step (presented later) where the assembling of the predicted subgraphs is not order-sensitive. During training, we insert two special tokens "<bos>" and "<eos>" indicating the beginning and the end of sequence generation, respectively. We implement the sequence model via a single layer of GRU [8] and project the latent variable $\boldsymbol{z}$ to the initial state of GRU. The training objective of this stage is to minimize the log-likelihood $\mathcal{L}_\mathcal{P}$ of the ground truth fragment sequence:

$$\mathcal{L}_\mathcal{F} = \sum_{i=1}^{n} -\log P(\mathcal{F}_i|\mathcal{F}_{<i}, \boldsymbol{z}). \tag{3}$$

During testing, the generation stops when a "<eos>" is outputted.

How to assemble. This step estimates all inter-fragment edges $\{\mathcal{E}_{ij}\}$ non-autoregressively and globally. Specifically, we use a GNN with the same architecture in the last step but with different parameters to obtain the representations $\boldsymbol{h}_v$ of each atom v in all fragments. Given nodes v and u in two different fragments, we predict their connections as follows:

$$P(\boldsymbol{e}_{uv}|\boldsymbol{z}) = H_\theta([\boldsymbol{h}_v; \boldsymbol{h}_u; \boldsymbol{z}]), \tag{4}$$

where H_θ is a 3-layer MLP with ReLU activation. Apart from the types of chemical bonds, we also add a special type "<none>" to the edge vocabulary which indicates there is no connection between two nodes. During training, we predict both $P(\boldsymbol{e}_{uv})$ and $P(\boldsymbol{e}_{vu})$ to let H_θ learn the undirected nature of chemical bonds. We use negative sampling [12] to balance the ratio of "<none>" and chemical bonds. Since only about 2% pairs of nodes has inter-fragment connections, negative sampling significantly improves the computational efficiency and scalability. The training objective of this stage is to minimize the log-likelihood:

$$\mathcal{L}_\mathcal{E} = \sum_{u \in \mathcal{F}_i, v \in \mathcal{F}_j, i \neq j} -\log P(\boldsymbol{e}_{uv}|\boldsymbol{z}). \tag{5}$$

Joining the reconstruction losses of both steps (Eq. 3 and Eq. 5), we arrive at: $\mathcal{L}_{\mathrm{rec}} = \mathcal{L}_\mathcal{F} + \mathcal{L}_\mathcal{E}$. When considering target property, we jointly train a 2-layer MLP from $\boldsymbol{z}$ to predict the scores of target properties using the MSE loss. By denoting this extra loss as $\mathcal{L}_{\mathrm{prop}}$, the final objective of our PS-VAE becomes:

$$\mathcal{L} = \alpha\mathcal{L}_{\mathrm{rec}} + (1 - \alpha)\mathcal{L}_{\mathrm{prop}} + \beta D_{\mathrm{KL}}, \tag{6}$$

where the the KL divergence D_{KL} aligns the distribution of $\boldsymbol{z}$ with the prior distribution $\mathcal{N}(\mathbf{0}, \mathbf{I})$; α and β balance the trade-off between different losses.

To decode $\{\mathcal{E}_{ij}\}$ in the inference phase, the decoder first assigns all possible inter-fragment connections with a bond type and a corresponding confidence level. We try to add bonds that have a

confidence level higher than $\delta_{\text{th}} = 0.5$ to the molecule in order of confidence level from high to low. For each attempt, we perform a valency and a cycle check to reject the connections that will cause violation of valency or form unstable rings which are too small or too large. Since this procedure may form unconnected graphs, we find the maximal connected component as the final result. The pseudo code for inference is deferred to Appendix G.

4   Experiments

Evaluation Tasks   We first report the empirical results for the distribution-learning tasks in *GuacaMol benchmarks* [7] to evaluate if the model can generate realistic and diverse molecules. Then we validate our model on two common problems and the goal-directed tasks of the *GuacaMol benchmarks*. *Property Optimization* requires generating molecules with optimized properties. *Constrained Property Optimization* concentrates on improving the properties of given molecules with a restricted degree of modification. *GuacaMol Goal-Directed Benchmarks* consist of 20 molecular design tasks carefully curated by domain-experts [46, 41, 11].

Dataset   We use the ZINC250K [16] dataset for training, which contains 250,000 drug-like molecules up to 38 atoms. For GuacaMol benchmark, we add extra results on the QM9 [6, 36] dataset, which has 133,014 molecules up to 23 atoms.

Baselines   We compare our principal subgraph variational auto-encoder (**PS-VAE**) with the following state-of-the-art models. **JT-VAE** [18] is a variational auto-encoder that represents molecules as junction trees. It performs Bayesian optimization on the latent variable for property optimization. **GCPN** [45] combines reinforcement learning and graph representation for goal-directed molecular graph generation. **MRNN** [33] adopts two RNNs to autoregressively generate atoms and bonds respectively. It combines policy gradient optimization to generate molecules with desired properties. **GraphAF** [38] is a flow-based autoregressive model which is first pretrained for likelihood modeling and then fine-tuned with reinforcement learning for property optimization. **GA** [31] adopts genetic algorithms for property optimization and models the selection of the subsequent population with a neural network. **HierVAE** [19] extracts fragments by breaking bridge bonds in molecules and uses them as building blocks. **FREED** [44] is an RL-based model and uses fragments from existing chemical libraries to construct the subgraph vocabulary. **MARS** [42] adopts Markov chain Monte Carlo sampling for generation and is the state-of-the-art approach on the GuacaMol goal-directed benchmarks. Since our generation model is universally compatible with molecular decomposition of non-overlapping fragments, we also integrate vocabularies from **HierVAE** and **FREED** into our two-step generation model, which are abbreviated as **H-VAE*** and **F-VAE***, respectively.

Implementation Details   We choose $N = 300$ for property optimization and $N = 500$ for constrained property optimization. PS-VAE is trained for 6 epochs with a batch size of 32 and a learning rate of 0.001. We set $\alpha = 0.1$ and initialize $\beta = 0$. We adopt a warm-up method that increases β by 0.002 every 1000 steps to a maximum of 0.01. More details are in Appendix H.

4.1   Results

GuacaMol Distribution-Learning Benchmarks   These benchmarks evaluate four metrics on 10,000 molecules generated by the models. Since all methods introduce validity check into generation, they can always generate chemically valid molecules. *Uniqueness* measures the ratio of unique ones in generated molecules. *Novelty* assesses the ability of the models to generate molecules not contained in the training set. *KL Divergence* evaluates the closeness between the training set molecules and the generated molecules in terms of the distributions of various physicochemical properties. *Fréchet ChemNet Distance (FCD)* calculates the closeness of the two sets of molecules with respect to their hidden representations in the ChemNet [34]. Each metric is normalized to 0 to 1, and a higher value indicates better performance. Table 1 shows the results of distribution-learning benchmarks on QM9 and ZINC250K. Our model achieves competitive results in all four metrics, which indicates our model can generate realistic molecules and prevent overfitting the training set. In addition, with the same vocabulary, H-VAE* surpasses HierVAE consistently, confirming the advantage of our two-step generation model over the one used in HierVAE. Moreover, even sharing the same two-step decoder, PS-VAE is still better than H-VAE* and F-VAE* consistently, which is probably because our

constructed vocabulary discovers more meaningful and reusable patterns than H-VAE* and F-VAE*. We have displayed some molecules sampled from the prior distribution in Appendix M.

Table 1: Results of GuacaMol distribution-learning benchmarks on QM9 and ZINC250K. Uniq, KL Div and FCD refer to Uniqueness, KL Divergence and Fréchet ChemNet Distance, respectively.

Model	QM9				ZINC250K			
	Uniq($\uparrow$)	Novelty($\uparrow$)	KL Div($\uparrow$)	FCD($\uparrow$)	Uniq($\uparrow$)	Novelty($\uparrow$)	KL Div($\uparrow$)	FCD($\uparrow$)
JT-VAE	0.549	0.386	0.891	0.588	0.988	0.988	**0.882**	0.263
GCPN	0.533	0.320	0.552	0.174	0.982	0.982	0.456	0.003
GraphAF	0.500	0.453	0.761	0.326	0.288	0.287	0.508	0.023
GA	0.008	0.008	0.429	0.004	0.008	0.008	0.705	0.001
HierVAE	0.416	0.285	0.802	0.426	0.131	0.131	0.602	0.001
H-VAE(ours)	0.619	0.487	0.869	0.588	0.991	0.991	0.611	0.037
F-VAE(ours)	0.466	0.400	0.889	0.490	0.988	0.988	0.676	0.085
GP-VAE(ours)	**0.673**	**0.523**	**0.921**	**0.659**	**0.997**	**0.997**	0.850	**0.318**

Property Optimization This task focuses on generating molecules with optimized Penalized logP ([23], PlogP) and QED [4]. PlogP is logP penalized by synthesis accessibility and ring size which has an unbounded range. QED measures the drug-likeness of molecules with a range of $[0, 1]$. Both properties are calculated by empirical prediction models [40, 4], and are widely used in previous works [18, 45, 38]. We constrain all models to generate molecules under 60 atoms to prevent them from utilizing the flaw of PlogP by keeping extending the carbon chain [38]. We first train a predictor on the latent space of previously-trained VAE models to simulate the scoring functions, then perform gradient ascending to search for optimized molecules [18, 27]. Hyperparameters can be found in Appendix H. Following previous works [18, 45, 38], we generate 10,000 optimized molecules and report the top-3 scores found by each model. Results in Table 2 show that our model surpasses the baselines consistently. Note that with the same vocabulary, F-VAE achieves much better results than FREED, which indicates the superiority of our two-step generation strategy to the one in FREED.

Table 2: Comparison of the top-3 property scores.

Method	Penalized logP			QED		
	1st	2nd	3rd	1st	2nd	3rd
JT-VAE	5.30	4.93	4.49	0.925	0.911	0.910
GCPN	7.98	7.85	7.80	**0.948**	0.947	0.946
MRNN	8.63	6.08	4.73	0.844	0.796	0.736
GraphAF	12.23	11.29	11.05	**0.948**	**0.948**	0.947
GA	12.25	12.22	12.20	0.946	0.944	0.932
FREED	6.74	6.65	6.42	0.920	0.919	0.908
H-VAE*	11.41	9.67	9.31	0.947	0.946	0.946
F-VAE*	13.50	12.62	12.40	**0.948**	**0.948**	0.947
PS-VAE (ours)	**13.95**	**13.83**	**13.65**	**0.948**	**0.948**	**0.948**

Constrained Property Optimization This task refines molecular properties under the constraint that the Tanimoto similarity with Morgan fingerprint [35] is above a threshold δ. As suggested by previous works [18, 45, 38], we optimize 800 molecules with the lowest PlogP in the test set of ZINC250K. Similar to the property optimization task, we perform gradient ascending on the latent variable with a max step of 80. We collect all latent variables which have better-predicted scores than the previous iteration and decode each of them 5 times, namely up to 400 molecules. Following Shi et al. [38], we initialize the generation with sub-graphs sampled from the original molecules. Then we choose the highest scoring one from the molecules that meet the similarity constraint. Table 3 shows our model can generate molecules with a higher PlogP score under the similarity constraints. Since our model uses subgraphs as building blocks, the degree of modification tends to be greater than atom-level models, leading to a lower success rate. Even so, the success rates by our model are still on par with the atom-level counterparts and are the best among all subgraph-level methods.

Table 3: Mean (standard deviation) on improvement in constrained property optimization.

Model	$\delta = 0.2$		$\delta = 0.4$		$\delta = 0.6$	
	Improvement	Success	Improvement	Success	Improvement	Success
JT-VAE	1.68±1.85	97.1%	0.84±1.45	83.6%	0.21±0.71	46.4%
GCPN	4.12±1.19	100%	2.49±1.30	100%	0.79±0.63	100%
GraphAF	4.99±1.38	100%	3.74±1.25	100%	1.95±0.99	98.4%
GA	3.04±1.60	100%	2.34±1.34	100%	1.35±1.06	95.9%
H-VAE*	3.42±1.65	89.9%	2.68±1.44	74.0%	1.90±1.06	51.5%
F-VAE*	4.82±1.57	98.9%	3.60±1.39	89.9%	2.40±1.17	68.6%
PS-VAE (ours)	**6.42±1.86**	99.9%	**4.19±1.30**	98.9%	**2.52±1.12**	90.3%

GuacaMol Goal-Directed Benchmarks To further explore the efficacy of PS-VAE, we provide the results for GuacaMol goal-directed benchmarks [7] in Table 4. All scores are continuous values between 0 and 1, and the higher, the better. In order to obtain more discernible results between different approaches, we conduct experiments on QM9 and ZINC250K which have much less high-scoring molecules than ChEMBL [29] to make the tasks more challenging. Otherwise the majority of the benchmarks are easy to be optimized to the upper bound [42]. We adopt the same optimizing strategy as in the property optimization tasks. Hyperparameters can be found in Appendix H. Table 4 shows that our model remarkably performs better than H-VAE* and F-VAE*, and thus exhibits the benefit of our subgraph extraction method. The superior of H-VAE* to HierVAE indicates the advantage of our two-step assembling over the sequential sampling strategy.

Table 4: Results for GuacaMol goal-directed benchmarks. H-VAE*, F-VAE* and PS-VAE refer to VAE models with vocabularies from HierVAE, FREED and our principal subgraphs, respectively.

benchmark	H-VAE*	F-VAE*	HierVAE	MARS	PS-VAE
			ZINC250K		
Celecoxib rediscovery	0.252	0.310	0.223	0.137	**0.451**
Troglitazone rediscovery	0.205	0.215	0.181	0.163	**0.254**
Thiothixene rediscovery	0.240	0.236	0.191	0.072	**0.286**
Aripiprazole similarity	0.382	0.390	0.240	0.350	**0.432**
Albuterol similarity	0.404	0.484	0.430	0.567	**0.611**
Mestranol similarity	0.360	0.377	0.281	0.297	**0.515**
C11H24	0.014	0.050	0.050	0.124	**0.634**
C9H10N2O2PF2Cl	0.523	0.567	0.023	0.435	**0.782**
Median molecules 1	0.191	0.204	0.115	0.167	**0.263**
Median molecules 2	0.178	0.198	0.126	0.166	**0.199**
Osimertinib MPO	0.758	0.768	0.538	0.745	**0.800**
Fexofenadine MPO	0.655	0.685	0.523	0.682	**0.715**
Ranolazine MPO	0.411	0.532	0.305	0.552	**0.688**
Perindopril MPO	0.394	0.403	0.361	0.418	**0.429**
Amlodipine MPO	0.477	0.463	0.341	0.477	**0.544**
Sitagliptin MPO	0.246	0.350	0.092	0.261	**0.439**
Zaleplon MPO	0.394	0.450	0.268	0.329	**0.495**
Valsartan SMARTS	0	0	0	0	5.398×10^{-12}
Deco Hop	0.577	0.577	0.559	0.572	**0.601**
Scaffold Hop	0.443	0.450	0.417	0.442	**0.486**
			QM9		
Celecoxib rediscovery	0.111	0.129	0.059	0.023	**0.210**
Troglitazone rediscovery	0.124	0.131	0.121	0.085	**0.152**
Thiothixene rediscovery	0.115	0.100	0.059	0.037	**0.146**
Aripiprazole similarity	0.167	0.178	0.167	0.104	**0.214**
Albuterol similarity	0.305	0.277	0.380	0.305	**0.463**
Mestranol similarity	0.157	0.122	**0.234**	0.233	0.198
C11H24	6.899×10^{-7}	2.979×10^{-6}	0.007	1.959×10^{-45}	**0.015**
C9H10N2O2PF2Cl	0.236	0.109	0.250	0.190	**0.381**
Median molecules 1	0.195	0.194	0.229	0.143	**0.261**
Median molecules 2	0.091	0.091	0.081	0.085	**0.112**
Osimertinib MPO	0.541	0.554	0.561	0.555	**0.636**
Fexofenadine MPO	0.307	0.290	0.355	**0.443**	0.373
Ranolazine MPO	0.007	0.010	0.011	**0.032**	0.018
Perindopril MPO	0.166	0.165	0.116	0.145	**0.205**
Amlodipine MPO	0.258	0.211	0.300	0.284	**0.303**
Sitagliptin MPO	2.807×10^{-5}	5.114×10^{-5}	0.951×10^{-4}	0.138×10^{-2}	0.319×10^{-3}
Zaleplon MPO	3.41×10^{-5}	5.647×10^{-5}	0.771×10^{-4}	0.033	**0.085**
Valsartan SMARTS	0	0	0	0	0
Deco Hop	0.506	0.492	0.512	0.513	**0.545**
Scaffold Hop	0.340	0.354	0.351	0.362	**0.393**

4.2 Ablation Study

We conduct an ablation study to further validate the effects of principal subgraphs and the two-step generation approach. We first downgrade the vocabulary to contain only single atoms. Then we replace the two-step decoder with a fully autoregressive decoder. We present the performance on (constrained) property optimization in Table 5 and Table 6. The direct introduction of the two-step generation approach leads to improvement in property optimization but harms the performance on constrained property optimization. This is reasonable as separating the generation of atoms and bonds brings in information loss of bonds for the atom-level generation process. However, the adoption of principal subgraphs as building blocks alleviates this negative effect since the principal subgraphs themselves contain rich bond information. Therefore, integrating principal subgraphs with our two-step generation approach leads to the best choice in our model design. Furthermore, we provide the runtime cost of baselines and PS-VAE in Appendix F to demonstrate the improvement in efficiency brought by the principal subgraphs and the two-step generation approach.

Table 5: Comparison of the top-3 property scores found by PS-VAE without certain modules

Method	Penalized logP			QED		
	1st	2nd	3rd	1st	2nd	3rd
PS-VAE	**13.95**	**13.83**	**13.65**	**0.948**	**0.948**	**0.948**
- PS	6.91	5.50	5.12	0.870	0.869	0.869
- two-step	3.54	3.54	3.22	0.737	0.734	0.729

Table 6: Comparison of PS-VAE without certain modules on constrained property optimization.

Model	$\delta = 0.2$		$\delta = 0.4$		$\delta = 0.6$	
	Improvement	Success	Improvement	Success	Improvement	Success
PS-VAE	**6.42±1.86**	99.9%	**4.19±1.30**	98.9%	**2.52±1.12**	90.3%
- PS	2.33±1.46	74.8%	2.12±1.36	50.9%	1.87±1.12	27.0%
- two-step	3.36±1.58	98.6%	2.72±1.24	82.0%	1.88±1.05	45.1%

5 Analysis

Principal Subgraph Statistics   We compare the distributions of the vocabulary of JT-VAE, FREED, HierVAE, and the vocabulary constructed by our principal subgraph extraction methods with a size of 100, 300, 500, and 700. Figure 4 shows the proportion of fragments with different numbers of atoms in the vocabulary and their frequencies of occurrence in the ZINC250K dataset. The fragments in the vocabulary of JT-VAE mainly contain 5 to 8 atoms with a sharp distribution. However, starting from fragments with 3 atoms, the frequency of occurrence is already close to zero. Therefore, the majority of fragments in the vocabulary of JT-VAE are actually not common fragments. On the contrary, the fragments in the vocabulary of principal subgraphs have a relatively smooth distribution over 4 to 10 atoms. Moreover, these fragments also have a much higher frequency of occurrence compared to those by JT-VAE. Vocabularies constructed by our method show similar advantages compared to those of HierVAE and FREED. We present samples of principal subgraphs in Appendix L.

Figure 4: The left and right figures show the proportion of and frequency of occurrence of fragments with different number of atoms in the vocabulary, respectively.

Principal Subgraph - Property Correlation   To analyze the principal subgraph - property correlation and whether our model can discover and utilize the correlation, we present the normalized distribution of generated fragments and Pearson correlation coefficient between the fragments and Penalized logP (PlogP) in Figure 6. The curve of the Pearson correlation coefficient indicates that some fragments positively correlate with PlogP while some negatively correlate with it. Compared with the flat distribution under the non-optimization setting, the generated distribution shifts towards the fragments positively correlated with PlogP under the PlogP-optimization setting. The generation of fragments negatively correlated with PlogP is also suppressed. Therefore, correlations exist between fragments and PlogP, and our model can accurately discover and utilize these correlations.

6 Conclusion

We propose an algorithm to automatically discover the regularity in molecules and extract them as *principal subgraphs*. With the extracted principle subgraphs at hand, we generate molecules in two phases. Our model consistently outperforms state-of-the-art models on distribution-learning, (constrained) property optimization, and GuacaMol goal-directed benchmarks, and exhibits higher computational efficiency than certain widely-used baselines. Our work provides insights into the selection of subgraphs on molecular graph generation and can inspire future search in this direction.

References

[1] S. Ahn, J. Kim, H. Lee, and J. Shin. Guiding deep molecular optimization with genetic exploration. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin, editors, *Advances in Neural Information Processing Systems*, volume 33, pages 12008–12021. Curran Associates, Inc., 2020. URL https://proceedings.neurips.cc/paper/2020/file/8ba6c657b03fc7c8dd4dff8e45defcd2-Paper.pdf.

[2] B. Allison, D. Guthrie, and L. Guthrie. Another look at the data sparsity problem. In *International Conference on Text, Speech and Dialogue*, pages 327–334. Springer, 2006.

[3] C. Bentz and D. Alikaniotis. The word entropy of natural languages. *arXiv preprint arXiv:1606.06996*, 2016.

[4] G. R. Bickerton, G. V. Paolini, J. Besnard, S. Muresan, and A. L. Hopkins. Quantifying the chemical beauty of drugs. *Nature chemistry*, 4(2):90–98, 2012.

[5] E. J. Bjerrum and R. Threlfall. Molecular generation with recurrent neural networks (rnns). *arXiv preprint arXiv:1705.04612*, 2017.

[6] L. C. Blum and J.-L. Reymond. 970 million druglike small molecules for virtual screening in the chemical universe database GDB-13. *J. Am. Chem. Soc.*, 131:8732, 2009.

[7] N. Brown, M. Fiscato, M. H. Segler, and A. C. Vaucher. Guacamol: benchmarking models for de novo molecular design. *Journal of chemical information and modeling*, 59(3):1096–1108, 2019.

[8] K. Cho, B. Van Merriënboer, C. Gulcehre, D. Bahdanau, F. Bougares, H. Schwenk, and Y. Bengio. Learning phrase representations using rnn encoder-decoder for statistical machine translation. *arXiv preprint arXiv:1406.1078*, 2014.

[9] N. De Cao and T. Kipf. Molgan: An implicit generative model for small molecular graphs. *arXiv preprint arXiv:1805.11973*, 2018.

[10] M. W. Gardner and S. Dorling. Artificial neural networks (the multilayer perceptron)—a review of applications in the atmospheric sciences. *Atmospheric environment*, 32(14-15):2627–2636, 1998.

[11] J. Gasteiger and T. Engel. *Chemoinformatics: a textbook*. John Wiley & Sons, 2006.

[12] Y. Goldberg and O. Levy. word2vec explained: deriving mikolov et al.'s negative-sampling word-embedding method. *arXiv preprint arXiv:1402.3722*, 2014.

[13] R. Gómez-Bombarelli, J. N. Wei, D. Duvenaud, J. M. Hernández-Lobato, B. Sánchez-Lengeling, D. Sheberla, J. Aguilera-Iparraguirre, T. D. Hirzel, R. P. Adams, and A. Aspuru-Guzik. Automatic chemical design using a data-driven continuous representation of molecules. *ACS central science*, 4(2):268–276, 2018.

[14] W. Hu, B. Liu, J. Gomes, M. Zitnik, P. Liang, V. Pande, and J. Leskovec. Strategies for pre-training graph neural networks. *arXiv preprint arXiv:1905.12265*, 2019.

[15] A. Inokuchi, T. Washio, and H. Motoda. An apriori-based algorithm for mining frequent substructures from graph data. In *European conference on principles of data mining and knowledge discovery*, pages 13–23. Springer, 2000.

[16] J. J. Irwin, T. Sterling, M. M. Mysinger, E. S. Bolstad, and R. G. Coleman. Zinc: a free tool to discover chemistry for biology. *Journal of chemical information and modeling*, 52(7):1757–1768, 2012.

[17] A. Jazayeri and C. Yang. Frequent subgraph mining algorithms in static and temporal graph-transaction settings: A survey. *IEEE Transactions on Big Data*, 2021.

[18] W. Jin, R. Barzilay, and T. Jaakkola. Junction tree variational autoencoder for molecular graph generation. In *International Conference on Machine Learning*, pages 2323–2332. PMLR, 2018.

[19] W. Jin, R. Barzilay, and T. Jaakkola. Hierarchical generation of molecular graphs using structural motifs. In *International Conference on Machine Learning*, pages 4839–4848. PMLR, 2020.

[20] W. Jin, R. Barzilay, and T. Jaakkola. Multi-objective molecule generation using interpretable substructures. In *International Conference on Machine Learning*, pages 4849–4859. PMLR, 2020.

[21] D. P. Kingma and M. Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

[22] M. Kuramochi and G. Karypis. Frequent subgraph discovery. In *Proceedings 2001 IEEE international conference on data mining*, pages 313–320. IEEE, 2001.

[23] M. J. Kusner, B. Paige, and J. M. Hernández-Lobato. Grammar variational autoencoder. In *International Conference on Machine Learning*, pages 1945–1954. PMLR, 2017.

[24] Y. Kwon, J. Yoo, Y.-S. Choi, W.-J. Son, D. Lee, and S. Kang. Efficient learning of non-autoregressive graph variational autoencoders for molecular graph generation. *Journal of Cheminformatics*, 11(1):1–10, 2019.

[25] Y. Li, O. Vinyals, C. Dyer, R. Pascanu, and P. Battaglia. Learning deep generative models of graphs. *arXiv preprint arXiv:1803.03324*, 2018.

[26] Y. Li, L. Zhang, and Z. Liu. Multi-objective de novo drug design with conditional graph generative model. *Journal of cheminformatics*, 10(1):1–24, 2018.

[27] R. Luo, F. Tian, T. Qin, E. Chen, and T.-Y. Liu. Neural architecture optimization. *arXiv preprint arXiv:1808.07233*, 2018.

[28] N. F. Martin and J. W. England. *Mathematical theory of entropy*. Number 12. Cambridge university press, 2011.

[29] D. Mendez, A. Gaulton, A. P. Bento, J. Chambers, M. De Veij, E. Félix, M. P. Magariños, J. F. Mosquera, P. Mutowo, M. Nowotka, et al. Chembl: towards direct deposition of bioassay data. *Nucleic acids research*, 47(D1):D930–D940, 2019.

[30] C. W. Murray and D. C. Rees. The rise of fragment-based drug discovery. *Nature chemistry*, 1 (3):187–192, 2009.

[31] A. Nigam, P. Friederich, M. Krenn, and A. Aspuru-Guzik. Augmenting genetic algorithms with deep neural networks for exploring the chemical space. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020. URL https://openreview.net/forum?id=H1lmyRNFvr.

[32] S. Nijssen and J. N. Kok. A quickstart in frequent structure mining can make a difference. In *Proceedings of the tenth ACM SIGKDD international conference on Knowledge discovery and data mining*, pages 647–652, 2004.

[33] M. Popova, M. Shvets, J. Oliva, and O. Isayev. Molecularrnn: Generating realistic molecular graphs with optimized properties. *arXiv preprint arXiv:1905.13372*, 2019.

[34] K. Preuer, P. Renz, T. Unterthiner, S. Hochreiter, and G. Klambauer. Fréchet chemnet distance: a metric for generative models for molecules in drug discovery. *Journal of chemical information and modeling*, 58(9):1736–1741, 2018.

[35] D. Rogers and M. Hahn. Extended-connectivity fingerprints. *Journal of chemical information and modeling*, 50(5):742–754, 2010.

[36] M. Rupp, A. Tkatchenko, K.-R. Müller, and O. A. von Lilienfeld. Fast and accurate modeling of molecular atomization energies with machine learning. *Physical Review Letters*, 108:058301, 2012.

[37] R. Sennrich, B. Haddow, and A. Birch. Neural machine translation of rare words with subword units. *arXiv preprint arXiv:1508.07909*, 2015.

[38] C. Shi, M. Xu, Z. Zhu, W. Zhang, M. Zhang, and J. Tang. Graphaf: a flow-based autoregressive model for molecular graph generation. *arXiv preprint arXiv:2001.09382*, 2020.

[39] D. Weininger. Smiles, a chemical language and information system. 1. introduction to methodology and encoding rules. *Journal of chemical information and computer sciences*, 28(1):31–36, 1988.

[40] S. A. Wildman and G. M. Crippen. Prediction of physicochemical parameters by atomic contributions. *Journal of chemical information and computer sciences*, 39(5):868–873, 1999.

[41] P. Willett, J. M. Barnard, and G. M. Downs. Chemical similarity searching. *Journal of chemical information and computer sciences*, 38(6):983–996, 1998.

[42] Y. Xie, C. Shi, H. Zhou, Y. Yang, W. Zhang, Y. Yu, and L. Li. Mars: Markov molecular sampling for multi-objective drug discovery. *arXiv preprint arXiv:2103.10432*, 2021.

[43] X. Yan and J. Han. gspan: Graph-based substructure pattern mining. In *2002 IEEE International Conference on Data Mining, 2002. Proceedings.*, pages 721–724. IEEE, 2002.

[44] S. Yang, D. Hwang, S. Lee, S. Ryu, and S. J. Hwang. Hit and lead discovery with explorative rl and fragment-based molecule generation. *Advances in Neural Information Processing Systems*, 34, 2021.

[45] J. You, B. Liu, R. Ying, V. Pande, and J. Leskovec. Graph convolutional policy network for goal-directed molecular graph generation. *arXiv preprint arXiv:1806.02473*, 2018.

[46] A. Zaliani, K. Boda, T. Seidel, A. Herwig, C. H. Schwab, J. Gasteiger, H. Claußen, C. Lemmen, J. Degen, J. Pärn, et al. Second-generation de novo design: a view from a medicinal chemist perspective. *Journal of computer-aided molecular design*, 23(8):593–602, 2009.