FaceZip: Automatic Texture Compression for Facial Blendshapes

Category: Research

uncompressed: 63 MB   compressed: 17 MB

Figure 1: We present a method to compress the information of the texture that dynamically changes with the underlying blendshape mesh. Compared to the naïve method of storing all the textures on the blendshape mesh (left), our approach (right) significantly reduces the size with only a small loss of quality.

ABSTRACT

Recently, numerous cinematic and interactive entertainment production companies have adopted advanced capture systems for acquiring faithful facial geometries and their corresponding textures. However, animating these captured models in a controllable way for real-time application is difficult. While blendshape is typically used for parameterizing facial geometries, dynamically changing the texture of the geometry is challenging. Since texture data is significantly larger than the vertex coordinates of the meshes, storing the texture of all the blendshape meshes is impractical. We present a method to compress the texture data in a way compatible with blendshape for real-time applications, such as video games. Our method takes advantage of the locality of the difference between facial textures by blending a few textures with spatially different weights. Our method achieved more accurate reconstructions of the original textures comparing the baseline of principal component analysis.

Index Terms: Computing methodologies—Computer graphics—Image Compression; Computing methodologies—Computer graphics—Texturing

1 INTRODUCTION

Recently, the demand has significantly increased for realistic digital human models in various applications such as cinema, interactive entertainment, and the metaverse. Photogrammetry is typically used to automatically capture the 3D geometries and materials of the actors. However, a wide range of skilled artists in modeling, sculpting, texture painting, rigging, and animation is still necessary to bring life to the captured model. This difficulty largely originated from the parameterization of the acquired model to efficiently represent the surface material and deformation in an efficient and controllable way. The overall facial deformation is typically parameterized using the blendshape model and the detailed surface appearance is represented in the 2D textures. However, the coupling of the two — dynamically changing the texture according to the blendshape parameter – has been challenging. It has been difficult to represent details such as wrinkles, dimples, and furrows, that are dynamically created with various expressions.

The blendshape is a popular facial animation technique because it can create complicated deformation by the simple linear combination of the semantically meaningful (typically 50 to 100) blendshape meshes. Theoretically, the texture on the blendshape can also be represented using the linear combination of the texture on the blendshape meshes. However, storing all the textures of the blendshape mesh is not practical, as the memory requirement of the texture is significantly larger than that of the vertex coordinates of the blendshape mesh. Especially in real-time applications such as games, the current hardware requires keeping the number of texture accesses to 10 or fewer.

A typical technique used in the gaming industry is to store a texture of a neutral face and several textures that collect wrinkles of large expressions (e.g., [26]). These textures are blended *non-uniformly* using the weight map i.e., the spatially changing weights. The advantage of this approach is that the artist has control over all textures, allowing for authoring exaggerated facial expressions. On the other hand, it is time-consuming and requires a lot of skills to manually create such weight maps and textures of wrinkles.

We present a technique to automatically generate the compressed texture for the blendshape model (see Figure 1). Our algorithm leverages the locality of the wrinkles by dividing the entire texture into many fragments. These fragments are seamlessly stitched back to several textures while avoiding blur using our optimized selection of the combination of the fragments. Furthermore, we extend our model to the blendshape generated from the example-based blendshape technique [13], which is a popular way to generate the blendshape meshes of Ekman's Facial Action Coding System (FACS) [6] from fewer example meshes.

We demonstrate our approach by the comparison against the baseline of principal component analysis (PCA). The contributions to our proposed method include

- Automatic compression of textures for the application of facial blendshape.

- The extension of the texture generation for the blendshape generated by example-based blendshape technique [13].

2 RELATED WORK

The generation of facial models has been studied for many years. We refer to the surveys [18, 29] for the comprehensive review. This paper

Figure 2: Overview of our method. For each texture, we first compute the difference from the neutral texture and apply a mask to decompose the texture into localized fragments. Then, the fragments from the same mask are split into four clusters. The fragments from different masks are reassembled into difference textures with a combination that reduces reconstruction error. In the run-time computation, the weight maps are blended with the blendshape weights. For the blendshape generated by the example-based rigging, we augment the weight map.

focuses on the texture compression of the application of blendshape in a real-time environment.

Parametric Facial Deformation Skinning [11] is one of the simplest methods to animate faces by placing fictitious facial bones under the skin. Because it is difficult to faithfully reproduce facial deformation with bones, blendshape deformation [20] is often used instead for high-quality animation. The blendshape typically deforms the vertices of the meshes with the linear combination of the differences from the neutral mesh [12]. Neumann et al. [19] propose a method that extracts sparse and localized deformation modes from an animated mesh sequence so that extracted dimensions often have interpretable meaning. These parameterizations work well for vertices of meshes but are often difficult to handle textures because the amount of data is huge.

Expression Capture High-quality facial capture setups are increasingly common in the industry. These systems typically use the photometric stereo technique with polarizers to obtain albedo, specular, normal, and roughness textures from vertical and parallel polarization images [8]. Riviere et al. [22] avoid the sequential light flashing in estimating these textures by applying inverse rendering for cross- and parallel-polarized images. Zhang et al. [28] modified the Light Stage [4] for high-speed cameras and developed a mechanism to directly take the animation sequence itself at video rate instead of the discrete expressions. While expression capture requires multiple separated workflows such as mesh reconstruction, fitting to a base mesh, and computation of each texture, Liu et al. [15] proposed a single end-to-end neural network acquisition framework.

FACS Blendshape Generation Productions typically use the meshes of FACS poses to create the blendshapes for the facial animation. As FACS are typically made up of 50 to over 100 independent meshes, there is a demand to build all FACS blendshape meshes from the limited number of captures. Li et al. [13] present a retargeting technique to synthesize blendshape meshes of FACS poses from a small number of expression capture. However, this work focuses on the facial geometry, not the texture. Li et al. [14] proposed a neural network to generate FACS expressions and their corresponding textures from a single neural facial scan. However, the resulting textures are too expensive to be directly blended in real time.

Facial Material Representation Facial animation has been studied for many years, but only a few researches focused on the compression of facial texture. The 3D morphable model (3DMM) represents the detailed 3D model in lower dimensional parameters. We refer to the recent survey on the morphable facial model by Egger et al. [5]. These parametric models can also decompose the animation data and change the facial expressions by changing the

parameters. The pioneering work by Blanz et al. [3] parameterizes both vertex coordinates and the RGB texture value using the principal component analysis (PCA).

Recent studies using neural networks are still expensive to evaluate in real time for high-resolution material generation. Machine learning approaches that use convolutional neural networks (CNN) [21, 24] to directly output meshes and textures. But they all need a large amount of training data and can not be used for real-time purposes. Lombardi et al. [16] represented the facial data as a set of neural radiance field models instead of a mesh and textures. The performance of the learning method can be very poor if the real data is greatly different from the training data, in age, skin color, etc.

Garrido1 et al. [7] and Shi et al. [25] represented small surface detail by shape-from-shading techniques which generate highly detailed surface geometry dynamically according to the expressions. However, these approaches require extremely high computational complexity and are not suitable for real-time application. Huang et al. [9] and Ma et al. [17] generate the detail of different expressions by detail maps while keeping the diffuse texture not changed. However, the diffuse map typically changes as the wrinkles appear depending on the expressions.

3 METHODS

Texture Compression Let us assume we have N number of RGB textures $\mathcal{I}_n$ where $n \in \{1, ..., N\}$ and one RGB "neutral texture" $\mathcal{I}_0$. Our algorithm computes four RGB "difference textures" $\mathcal{D}_i$ where $i \in \{1, ..., 4\}$ and weight maps $\mathcal{W}_{in} \in \mathbb{R}$. With these computed values, we efficiently approximate the n-th original texture $\mathcal{I}_n$ as

$$\mathcal{I}_n \simeq \bar{\mathcal{I}}_n = \mathcal{I}_0 + \sum_{i=1}^{4} \mathcal{D}_i \odot \mathcal{W}_{in}, \tag{1}$$

where the $\odot$ symbol stands for the Hadamart product, i.e., pixel-wise product. Figure 3 visually explains the reconstruction formulation in (1). Note that we have four source textures because the weight maps can be efficiently stored in the RGBA texture space. The weight $\mathcal{W}$ is smoothly defined, thus it can be stored in a down-sampled image without significant loss of quality. In this paper, the ratio of down-sampling is eight, thus the size of the weight is 64 times smaller than the original one. With input texture size $W \times H$, the original textures require $N \times W \times H$ space, while the compressed model requires $(5 + N/64) \times W \times H$ resulting in a significantly smaller memory footprint especially when N is large.

This paper presents a method to compute the decomposition of the input textures in (1) for the application of facial blendshape. Specifically, we generate textures for the example-based facial rigging [13], where the input textures are given in a small number of

neutral texture

difference textures

weight maps

reconstructed textures

Figure 3: Our texture compression approach. For each blendshape mesh, we have four corresponding weight maps. These weight maps are applied to the four difference textures. The summation of all the weighted difference textures and the neutral texture reconstructs the texture of the blendshape mesh.

Figure 4: Our mask computation approach. Given an input mesh (a), we first manually select a region of interest (b). Then, the vertices are uniformly sampled over the selected region (c). Finally, the biharmonic equation is solved on mesh while fixing the value at one of the sampled vertex as one and the others zero (d).

example shapes. When the weights of the blendshape change and thus the expression changes, our method outputs the texture with corresponding fine detail such as wrinkles.

We present an overview of our method in Figure 2. We first decompose the textures into fragments. Then, all the fragments are clustered into four groups. Finally, we find an optimal arrangement to store the fragments in the source textures and generate weight maps for every blendshape mesh. Section 3.1 explains this precomputation and Section 3.2 explains the following run-time computation.

3.1 Compression of Textures

The deformation of the entire face has rich varieties, but if we focus on a specific location, the deformation can be approximated with several modes. For example, a forehead exhibits horizontal furrows when the character raises the eyebrows and vertical furrows when the character frowns. To take advantage of such a locality, we first divide the input texture $\mathcal{I}_j$ into small fragments. This fragment can be simply computed by applying the mask $\mathcal{M}_k$ in the input texture

$$\hat{\mathcal{D}}_{nk} = (\mathcal{I}_n - \mathcal{I}_0) \odot \mathcal{M}_k, \tag{2}$$

where $k \in \{1, ..., \#\text{mask}\}$ is the index of the mask. Note that we apply the mask to the difference between the neutral texture and the input texture $(\mathcal{I}_j - \mathcal{I}_0)$ here.

The mask takes the value between $[0, 1]$ where the value outside the fragment is zero. To make the seam less visible, the masks need to smoothly change their value in the 3D space. Moreover, we define the masks such that they add up to one $\sum \mathcal{M} = 1$.

Mask Computation We compute such smooth masks by solving the biharmonic equation (see Figure 4) inspired by the computation of the rigging weights in [10]. For the input mesh of the head, we first manually extract the set of triangles that corresponds to the face. Then we randomly sample the vertices of the extracted triangles. To sample uniformly over the 3D mesh, we use the Poisson disk sampling with the dart-throwing algorithm. Here, we reject samples within a $3\,\text{cm}$ radius. The number of the sampled vertices is the number of the masks $\#\text{mask}$. In total, we sampled 53 vertices.

Let $\phi \in \mathbb{R}$ are the values defined on the vertices of extracted face triangles. We solve the biharmonic equation by minimizing $||\Delta\phi||^2$

with the fixed boundary condition where $\phi = 1$ at one vertex and $\phi = 0$ at the other vertices. We use combinatorial Laplacian on the 3D mesh to robustly compute the minimization using an iterative solver for a sparse linear system. Finally, the k-th mask is computed by normalizing the solution in the UV space $\mathcal{M}_k = \phi_k / \sum_{k'=1}^{\#\text{mask}} \phi_{k'}$.

Clustering The fragment of the input texture has several dominant modes. We extract such modes using K-means clustering method where the number of the cluster is four. Since the K-means clustering minimizes the variance inside the cluster, we can best select the four representative fragments of all fragments with the same mask. For each mask k, we record the four cluster centers of each cluster $\hat{\mathcal{D}}'_{ik}$ where $i \in \{1, ..., 4\}$.

Difference Texture Generation We now have four fragments for every mask, we are stitching these fragments back to four full textures. Naïvely adding up the fragments with the same texture index i will lead to blurring the texture around the border of the fragments. Hence, we optimize the combination of the fragments for each texture such that the adjacent fragments match together. Let $\sigma(i, k)$ be a permutation of index i for each mask k. We define the cost of a certain permutation index σ as

$$C(\sigma) = \sum_{\{k_1, k_2\}=1}^{\#\text{mask}} \sum_{i=1}^{4} \left\| \hat{\mathcal{D}}''_{ik_1k_2}(\sigma) - \hat{\mathcal{D}}''_{ik_2k_1}(\sigma) \right\|^2, \tag{3}$$

$$\text{where} \quad \hat{\mathcal{D}}''_{ik_1k_2}(\sigma) = \hat{\mathcal{D}}'_{\sigma(i,k_1)k_1} \odot \mathcal{M}_{k_2}. \tag{4}$$

Note that in (4), we apply the two masks $\mathcal{M}_{k_1} \odot \mathcal{M}_{k_2}$ to the difference texture (see the definition of the fragment in (2)). The Hadamard product of the two masks takes non-zero positive value only around the intersection of the mask k_1 and k_2.

The number of the possible permutation indexes σ is finite but it is too large to compute by exhaustive search (i.e., $4!^{\#\text{mask}}$). Thus, we present a method to iteratively reduce the cost to find an approximate minimizer. In each iteration, we look at a mask one by one. For each mask, we compute all the possible $4!$ index permutations for the mask and update the index to the minimizer while the indexes of other masks are fixed. By iterating this procedure 10 times, we reach convergence (see Figure 7-left). We repeat this procedure 100 times and record the permutation with the smallest cost.

Finally, we compute the four difference texture and the weights

as

$$\mathcal{D}_i = \sum_{k=1}^{\#\text{mask}} \hat{\mathcal{D}}'_{\sigma(i,k)k}, \qquad (5)$$

$$\mathcal{W}_{in} = \sum_{k=1}^{\#\text{mask}} \alpha_{ink} \mathcal{M}_k, \qquad (6)$$

where α_{ink} takes the value 1 if the fragmented image $\hat{\mathcal{D}}_{nk}$ belongs to the $\sigma^{-1}(i,k)$-th cluster and otherwise it takes the value 0.

3.2 Texture Generation for Blendshapes

In this section, we describe texture generation for blendshape using our texture compression technique. The blendshape is often used to make a controllable face. Suppose we have a list of the vertices for the mesh of neutral face V_0 and the vertices for example face meshes V_j the blendshape computes the vertex from the parameter $\beta_n \in [0, 1]$ where $n \in \{1, ..., N\}$ as

$$V(\boldsymbol{\beta}) = V_0 + \sum_{n=1}^{N} \beta_n (V_n - V_0) \qquad (7)$$

Note that the blendshape formulation in (7) is specifically called *delta blendshape* [12] (see Figure 5-left).

blendshape   texture for blendshape

Figure 5: We blend difference textures with the same weight as the blendshape weight.

With the textures that correspond neutral mesh $\mathcal{I}_0$ and the other example meshes $\mathcal{I}_n$, our compressed texture model compute the texture for the list of blendshape parameter $\boldsymbol{\beta}$ as

$$\mathcal{I}(\boldsymbol{\beta}) = \mathcal{I}_0 + \sum_{i=1}^{4} \mathcal{D}_i \odot \left(\sum_{n=1}^{N} \beta_n \mathcal{W}_{in} \right). \qquad (8)$$

Note that in (8), we blend the texture with the ratio $\boldsymbol{\beta}$ in a similar manner as the blending for the vertex positions in (7) (see Figure 5). By blending the weight map $\mathcal{W}$, which is actually stored in the lower resolution, we can reduce the amount of computation.

Texture for Example-based Facial Rigging   We extend our texture compression for blendshape in (8) to the blendshape in example-based facial rigging in [13]. The example-based facial rigging generates blendshape meshes with new vertex positions V_m^* where $m \in \{1, ..., M\}$ from the training meshes V_n where $n \in \{1, ..., N\}$. We aim to synthesize the texture for the generated blendshape V_m^* when the texture $\mathcal{I}_n$ is given for the training meshes V_n. We first compute the weight map $\mathcal{W}_{in}$ and the difference texture $\mathcal{D}_i$ for the example meshes.

We refer to the original paper [13] for the detail of the example-based facial rigging. The basic idea of example-based facial rigging

is to optimize the generated blendshape mesh V_m^* such that the training mesh V_n can be reconstructed as

$$V_n \simeq V_0 + \sum_{m=1}^{M} \bar{\beta}_{nm}(V_m^* - V_0), \qquad (9)$$

where $\bar{\beta}_{nm} \in \mathbb{R}$ is the blending parameters that are optimized in the example-based facial rigging algorithm.

We synthesize the texture for generated blendshape such that it will reproduce the original compressed texture for the training meshes. This can be done by choosing the weight map for generated blendshape $\mathcal{W}_{im}^*$ to satisfy

$$\mathcal{W}_{in} = \sum_{m=1}^{M} \bar{\beta}_{nm} \mathcal{W}_{im}^*. \qquad (10)$$

Unfortunately, the equation (10) alone cannot specify the weight map $\mathcal{W}_{im}^*$, since the equations are underdetermined (i.e., $N < M$). Our observation is that the weight maps should be sparse to avoid blending many weights. Hence, we minimize a regularizer $|| \sum_{m=1}^{M} \mathcal{W}_{im}^* ||^2$ to make the weight maps as small as possible while satisfying the constraint (10). This results in the weight map

$$\mathcal{W}_{im}^* = \sum_{n=1}^{N} B_{mn}^+ \mathcal{W}_{in}, \qquad (11)$$

where $B^+ = B^T (BB^T)^{-1}$ is the pseudo-inverse of the matrix $B = [\bar{\beta}_{nm}]_{N \times M}$. Finally, the texture for the example-based facial rigging is synthesized as

$$\mathcal{I}(\boldsymbol{\beta}^*) = \mathcal{I}_0 + \sum_{i=1}^{4} \mathcal{D}_i \odot \left(\sum_{m=1}^{M} \beta_m^* \mathcal{W}_{im}^* \right), \qquad (12)$$

where $\boldsymbol{\beta}^*$ is the set of coefficients for example-based blendshape.

4 RESULTS

Evaluation Data   We evaluate our algorithm using the high-resolution multi-view photos of 20 expressions we purchased at the website [1]. For each expression model, we reconstruct the 3D mesh using the multi-view stereo software, Metashape [2]. Since these models are not represented by a consistent mesh, we fit a base mesh to these models using the commercial software, Wrap [23]. The resulting mesh has roughly 52k triangles.

In the supplementary video, we demonstrate our real-time dynamically changing texture for the blendshape implemented on Unity. All the weight maps are combined into one big RGBA texture and a simple shader program blends these textures on GPU fully in parallel. Hence the cost of texture synthesis in (8) is negligible. For the example-based facial rigging [13], we use the implementation in the FaceScape [27] to generate the blendshape of 52 meshes that is compatible with Apple's ARKit.

Performance   Table 1 lists the information on computation time for offline precomputation and run-time memory consumption. These performance numbers are measured on a machine with Intel 12600K and Windows 11 OS. The pre-computation is implemented in Python language. Specifically, we use Scikit-learn library for K-means clustering.

For the example-based blendshape of 52 meshes, our method uses a similar amount of memory compared with the PCA baseline. Note that our method requires slightly more memory because we need to store the weight maps. Compared to the naïve approach of storing all the textures for the blendshape meshes our algorithm work on about 8 times smaller memory, which agrees with the estimation in Section 3.

Resolution	Computation Time (s)		Memory Consumption (MB)		
	Clustering	Permutation	Ours	PCA	Raw data
512×512	113	989	4.77	3.93	40.89
1024×1024	347	3447	19.07	15.72	163.58
2048×2048	1714	14502	76.28	62.91	654.31

Table 1: Timing of offline computation and the comparison of memory consumption for different methods measured for different texture resolutions for example-based blendshape (blending 53 meshes). The "Clustering" stands for time for K-means clustering for all the fragments, "Permutation" stands for time to find the permutation with a small cost value.

Texture Quality To evaluate our texture compression performance, we compare Root Mean Square Error (RMSE) reconstruction errors against the compression using PCA, which is often used in the texture compression of blendshape [3]. We illustrate our comparison result in Figure 6. The error of PCA is very large in areas such as eyebrows and lips where there are a lot of fine details. As the ablation study, we also performed the comparison against the compression without permutation optimization. We observed that our approach without permutation is generally better than the naïve approach of PCA. Our approach with the weight maps and permutation optimization constantly produced the smallest errors against the other approaches.

Figure 6: Reconstruction error of 19 blendshape textures computed by three different methods. Our method achieves the lowest error of three in all the texture reconstructions.

Choice of the Number of the Masks Figure 7 shows the statistics of errors with respect to different numbers of masks. We record the distribution of the RMSE reconstruction error for 1000 different random initializations. We observe that the global minimum decreases as #mask goes up. However, if #mask is too large, reaching the global minimum becomes harder. Generally, the global minimum can be reached within 20 tries when #mask = 5

but 1000 tries will not be enough when #mask = 63. We choose 53 to be the final choice of #mask as it keeps a good balance of the reconstruction accuracy and the complexity to find the overall minimum. While our permutation optimization reduces the error a lot, proposing an efficient algorithm to find a near-optimal permutation is one of our future works.

Figure 7: Left: Convergence of the cost function for permutation optimization for 100 different initialization. Right: Box and the whisker plot of the sum of the reconstruction errors when we change the number of masks and run the permutation optimization with random initialization 1000 times.

Textures for Example-based Blendshapes In Figure 8, we compare the quality of the textures generated for example-based blendshape (blending 52 meshes). As for the baseline, we compute the texture for one of the example-based meshes by the weighted sum of the difference texture $\bar{\mathcal{I}}_m = \mathcal{I}_0 + \sum_{n=1}^{N} B_{mn}^+ (\mathcal{I}_n - \mathcal{I}_0)$. Here we choose 6-th blendshape (i.e., $m = 6$) of the ARKit. Since the pixel is synthesized pixel by pixel independently, the texture of the baseline model is full of noise. Moreover, unnatural wrinkles appear since the baseline model does not use smooth weight maps. Our method achieves better results with significantly smaller memory consumption as shown in Table 1.

5 CONCLUSION AND FUTURE WORK

Conclusion We present a method that can automatically compress the blendshape textures into one neutral texture and four difference textures. The difference textures can then be added up by spatially non-uniform weight maps which are smooth and stored in a low resolution. In this way, our method can significantly reduce memory consumption.

By combining the high-resolution difference textures and the low-resolution weight maps, the result of our method provides better-localized details than the global compression method such as PCA. The smoothness of the weight maps also prevents artifacts of extreme values and noise when blending the weights in the blendshape model. Our method does not need any prior knowledge about the texture image which is often required in data-driven methods and is fully compatible with blendshape for real-time applications.

Ours   Naïve

Figure 8: Reconstruction of the texture on one of the example-based blendshape mesh. The naïve approach blends the example textures while our approach blend the weight maps. The naïve approach results in high-frequency noise and false wrinkles in white color.

Future Work Currently, our work only compresses the albedo textures ignoring the other textures such as normal maps, specular maps, and roughness maps. Although extending our compression method to other textures is straightforward, there is potential to further compress the set of textures by leveraging the correlation between them.

We are also interested in applying our method other than facial textures. Especially, we are interested in efficiently representing the wrinkles of the garment in the texture space.

REFERENCES

[1] Triplegangers. `https://triplegangers.com/`. Accessed: March 30th, 2023.

[2] Agisoft. Metashape. `https://www.agisoft.com/`. Accessed: March 30th, 2023.

[3] V. Blanz and T. Vetter. A morphable model for the synthesis of 3D faces. In *Proceedings of the 26th Annual Conference on Computer Graphics and Interactive Techniques*, SIGGRAPH '99, p. 187–194. ACM Press/Addison-Wesley Publishing Co., USA, 1999.

[4] P. Debevec, T. Hawkins, C. Tchou, H.-P. Duiker, W. Sarokin, and M. Sagar. Acquiring the reflectance field of a human face. In *Proceedings of the 27th Annual Conference on Computer Graphics and Interactive Techniques*, SIGGRAPH '00, p. 145–156. ACM Press/Addison-Wesley Publishing Co., USA, 2000. doi: 10.1145/344779.344855

[5] B. Egger, W. A. P. Smith, A. Tewari, S. Wuhrer, M. Zollhoefer, T. Beeler, F. Bernard, T. Bolkart, A. Kortylewski, S. Romdhani, C. Theobalt, V. Blanz, and T. Vetter. 3D morphable face models—past, present, and future. *ACM Trans. Graph.*, 39(5), jun 2020.

[6] P. Ekman and W. V. Friesen. Facial action coding system. *Environmental Psychology & Nonverbal Behavior*, 1978.

[7] P. Garrido, L. Valgaert, C. Wu, and C. Theobalt. Reconstructing detailed dynamic face geometry from monocular video. *ACM Trans. Graph.*, 32(6), nov 2013. doi: 10.1145/2508363.2508380

[8] A. Ghosh, G. Fyffe, B. Tunwattanapong, J. Busch, X. Yu, and P. Debevec. Multiview face capture using polarized spherical gradient illumination. In *Proceedings of the 2011 SIGGRAPH Asia Conference*, SA '11. Association for Computing Machinery, New York, NY, USA, 2011.

[9] H. Huang, K. Yin, L. Zhao, Y. Qi, Y. Yu, and X. Tong. Detail-preserving controllable deformation from sparse examples. *IEEE Transactions on Visualization and Computer Graphics*, 18(8):1215–1227, 2012. doi: 10.1109/TVCG.2012.88

[10] A. Jacobson, I. Baran, J. Popović, and O. Sorkine. Bounded biharmonic weights for real-time deformation. *ACM Trans. Graph.*, 30(4), jul 2011. doi: 10.1145/2010324.1964973

[11] A. Jacobson, Z. Deng, L. Kavan, and J. P. Lewis. Skinning: Real-time shape deformation (full text not available). In *ACM SIGGRAPH 2014 Courses*, SIGGRAPH '14. Association for Computing Machinery, New York, NY, USA, 2014.

[12] J. P. Lewis, K. Anjyo, T. Rhee, M. Zhang, F. Pighin, and Z. Deng. Practice and Theory of Blendshape Facial Models. In S. Lefebvre and M. Spagnuolo, eds., *Eurographics 2014 - State of the Art Reports*. The Eurographics Association, 2014. doi: 10.2312/egst.20141042

[13] H. Li, T. Weise, and M. Pauly. Example-based facial rigging. In *ACM SIGGRAPH 2010 Papers*, SIGGRAPH '10. Association for Computing Machinery, New York, NY, USA, 2010.

[14] J. Li, Z. Kuang, Y. Zhao, M. He, K. Bladin, and H. Li. Dynamic facial asset and rig generation from a single scan. *ACM Trans. Graph.*, 39(6), nov 2020. doi: 10.1145/3414685.3417817

[15] S. Liu, Y. Cai, H. Chen, Y. Zhou, and Y. Zhao. Rapid face asset acquisition with recurrent feature alignment. *ACM Trans. Graph.*, 41(6), nov 2022. doi: 10.1145/3550454.3555509

[16] S. Lombardi, T. Simon, G. Schwartz, M. Zollhoefer, Y. Sheikh, and J. Saragih. Mixture of volumetric primitives for efficient neural rendering. *ACM Trans. Graph.*, 40(4), jul 2021.

[17] W.-C. Ma, A. Jones, J.-Y. Chiang, T. Hawkins, S. Frederiksen, P. Peers, M. Vukovic, M. Ouhyoung, and P. Debevec. Facial performance synthesis using deformation-driven polynomial displacement maps. In *ACM SIGGRAPH Asia 2008 Papers*, SIGGRAPH Asia '08. Association for Computing Machinery, New York, NY, USA, 2008. doi: 10.1145/1457515.1409074

[18] A. Morales, G. Piella, and F. M. Sukno. Survey on 3D face reconstruction from uncalibrated images. *Computer Science Review*, 40:100400, 2021. doi: 10.1016/j.cosrev.2021.100400

[19] T. Neumann, K. Varanasi, S. Wenger, M. Wacker, M. Magnor, and C. Theobalt. Sparse localized deformation components. *ACM Trans. Graph.*, 32(6), nov 2013.

[20] F. I. Parke and K. Waters. *Computer Facial Animation*. A K Peters/CRC Press, hardcover ed., 9 2008.

[21] E. Richardson, M. Sela, and R. Kimmel. 3D face reconstruction by learning from synthetic data. 09 2016.

[22] J. Riviere, P. Gotardo, D. Bradley, A. Ghosh, and T. Beeler. Single-shot high-quality facial geometry and skin appearance capture. *ACM Trans. Graph.*, 39(4), aug 2020.

[23] Russian3DScanner. Wrap. `https://www.russian3dscanner.com/`. Accessed: March 30th, 2023.

[24] M. Sela, E. Richardson, and R. Kimmel. Unrestricted facial geometry reconstruction using image-to-image translation. pp. 1585–1594, 10 2017. doi: 10.1109/ICCV.2017.175

[25] F. Shi, H.-T. Wu, X. Tong, and J. Chai. Automatic acquisition of high-fidelity facial performances using monocular videos. *ACM Trans. Graph.*, 33(6), nov 2014. doi: 10.1145/2661229.2661290

[26] A. Spring. Facs rigging & texture blending, 2020. `https://adamspring.co.uk/2020/05/25/facs-rigging-texture-blending-digital-humans/` [Accessed: (March 30th, 2023)].

[27] H. Yang, H. Zhu, Y. Wang, M. Huang, Q. Shen, R. Yang, and X. Cao. Facescape: a large-scale high quality 3d face dataset and detailed riggable 3d face prediction. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2020.

[28] L. Zhang, C. Zeng, Q. Zhang, H. Lin, R. Cao, W. Yang, L. Xu, and J. Yu. Video-driven neural physically-based facial asset for production, 2022.

[29] M. Zollhöfer, J. Thies, P. Garrido, D. Bradley, T. Beeler, P. Pérez, M. Stamminger, M. Nießner, and C. Theobalt. State of the art on monocular 3D face reconstruction, tracking, and applications. *Computer Graphics Forum*, 37(2):523–550, 2018. doi: 10.1111/cgf.13382