Shallow and Deep Networks are Near-Optimal Approximators of Korobov Functions

Abstract

In this paper, we analyze the number of neurons and training parameters that a neural network needs to approximate multivariate functions of bounded second mixed derivatives — Korobov functions. We prove upper bounds on these quantities for shallow and deep neural networks, drastically lessening the curse of dimensionality. Our bounds hold for general activation functions, including ReLU. We further prove that these bounds nearly match the minimal number of parameters any continuous function approximator needs to approximate Korobov functions, showing that neural networks are near-optimal function approximators.

1 Introduction

Neural networks have known tremendous success in the past years in many applications such as computer vision and pattern detection (Krizhevsky et al., 2017; Silver et al., 2016). A natural question that arises is how to explain their practical success theoretically. Neural networks are shown to be universal (Hornik et al., 1989): any Borel-measurable function can be approximated arbitrarily well by a neural network provided the network has a sufficient number of neurons. Furthermore, universality holds for as low as 1-hidden-layer neural network with reasonable activation functions. However, these results do not specify the number of neurons and parameters to train needed for this approximation. If these numbers are unreasonably high, the universality of neural networks would not explain their practical success.

We are interested in evaluating the number of neurons and training parameters needed to approximate a given function within ϵ with a neural network. An interesting question is how do these numbers scale with ϵ and the dimensionality of the problem, that is, the number of variables of the function. Mhaskar (1996) showed that any function of the Sobolev space of order r and dimension d can be approximated within ϵ with a 1-layer neural network with $\mathcal{O}(\epsilon^{-\frac{d}{r}})$ neurons and an infinitely differentiable activation function. This bound exhibits the curse of dimensionality: the number of neurons needed for an $\epsilon-$approximation scales exponentially in the dimension of the problem d. Thus, Mhaskar's bound raises the question of whether this curse is inherent to neural networks.

DeVore et al. (1989) showed an important result towards answering this question. They proved that any continuous function approximator (a notion we formalize in Section 5) that approximates all Sobolev functions of order r and dimension d within ϵ, needs at least $\Theta(\epsilon^{-\frac{d}{r}})$ parameters. This result bridges the gap with Mhaskar's bound and confirms that neural networks cannot escape the curse of dimensionality for the Sobolev space. A main question is therefore for which set of functions can neural networks break this curse of dimensionality.

One way to circumvent the curse of dimensionality is to restrict considerably the considered space of functions and focus on functions with specific structures adapted to neural networks. For example, Mhaskar et al. (2016) showed that compositional functions with regularity r can be approximated within ϵ with deep neural networks with $\mathcal{O}(d \cdot \epsilon^{-\frac{2}{r}})$ neurons. Another example is the class of Sobolev functions of order d/α and dimension d for which Mhaskar's bound becomes $\mathcal{O}(\epsilon^{-\alpha})$. Recently, Montanelli et al. (2019) considered bandlimited functions and showed that they can be approximated within ϵ by deep networks with depth $\mathcal{O}((\log \frac{1}{\epsilon})^2)$ and $\mathcal{O}(\epsilon^{-2}(\log \frac{1}{\epsilon})^2)$ neurons. Weinan et al. (2019) showed that the closure of the space of 2-layer neural networks with a particular regularity (namely a restriction on the size of the network's weights) is the Barron space. They further show that Barron functions can be approximated within ϵ with 2-layer networks with $\mathcal{O}(\epsilon^{-2})$ neurons.

Similar line of work restrict the function space with spectral conditions that allows functions to be written as limits of shallow networks (Barron, 1994; Klusowski & Barron, 2016; 2018).

In this work, we are interested in more general and generic spaces of functions. Our space of interest is the space of multivariate functions of bounded second mixed derivatives, namely the Korobov space. This space is included in the Sobolev space but is reasonably large and general. Recently, Montanelli & Du (2019) showed that deep neural networks with depth $\mathcal{O}(\log \frac{1}{\epsilon})$ and $\mathcal{O}(\epsilon^{-\frac{1}{2}}(\log \frac{1}{\epsilon})^{\frac{3(d-1)}{2}+1})$ neurons can approximate Korobov functions within ϵ, lessening the curse of dimensionality for deep neural networks asymptotically in ϵ. While they used deep structures to prove their result, the question of whether shallow neural networks also break the curse of dimensionality for the Korobov space remains open.

In this paper, we study deep and shallow neural network's approximation power for the Korobov space and make the following contributions:

- **Representation power of shallow neural networks.** We prove that any Korobov function can be approximated within ϵ with a 2-layer neural network with ReLU activation function with $\mathcal{O}(\epsilon^{-1}(\log \frac{1}{\epsilon})^{\frac{3(d-1)}{2}+1})$ neurons and $\mathcal{O}(\epsilon^{-\frac{1}{2}}(\log \frac{1}{\epsilon})^{\frac{3(d-1)}{2}})$ training parameters (Theorem 3.1). We further extend this result to a large class of commonly used activation functions (Theorem 3.4). Asymptotically in ϵ, our bound can be written as $\mathcal{O}(\epsilon^{-1-\delta})$ for all $\delta > 0$, and in that sense breaks the curse of dimensionality for shallow neural networks.

- **Representation power of deep neural networks.** We prove that any function of the Korobov space can be approximated within ϵ with a deep neural network of depth $\lceil \log_2(d) \rceil + 1$ independent of ϵ, with non-linear $\mathcal{C}^2$ activation function, $\mathcal{O}(\epsilon^{-\frac{1}{2}}(\log \frac{1}{\epsilon})^{\frac{3(d-1)}{2}})$ neurons and $\mathcal{O}(\epsilon^{-\frac{1}{2}}(\log \frac{1}{\epsilon})^{\frac{3(d-1)}{2}})$ training parameters (Theorem 4.1). This result improves over the result in Montanelli & Du (2019) that constructed an approximating neural network with larger depth $\mathcal{O}(\log \frac{1}{\epsilon} \log d)$ –increasing with the precision ϵ– and larger number of neurons $\mathcal{O}(\epsilon^{-\frac{1}{2}}(\log \frac{1}{\epsilon})^{\frac{3(d-1)}{2}+1})$. We note however that they used a different activation function, namely ReLU.

- **Near-optimality of neural networks as function approximators.** Under continuous function approximators model introduced by DeVore et al. (1989), we prove that any continuous function approximator needs $\Theta(\epsilon^{-\frac{1}{2}}(\log \frac{1}{\epsilon})^{\frac{d-1}{2}})$ parameters to approximate functions of the Korobov space within ϵ (Theorem 5.2). This lower bound nearly matches our established upper bounds on the number of training parameters needed by deep and shallow neural networks to approximate functions of the Korobov space, proving that deep and shallow neural networks are near-optimal function approximators of the Korobov space.

Table 1 summarizes our new bounds and some of the existing bounds on shallow and deep neural network approximation power for the Korobov space, Sobolev space and bandlimited functions. Our proofs are constructive and give explicit structures to construct such neural networks with ReLU and general activation functions. Our constructions rely on sparse grid approximation introduced by Zenger (1991), and studied in detail in Bungartz (1992); Bungartz & Griebel (2004).

The rest of the paper is structured as follows. In Section 2, we define the notions of interest, formalize our objective and introduce the sparse grids approach which will be key in our constructions. In Section 3 and 4, we prove our bounds on the number of neurons and training parameters needed by a neural network to approximate functions of the Korobov space. Section 3 provides bounds for shallow networks and Section 4 for deep networks. Finally, we formalize in Section 5 the notion of optimal continuous function approximators and prove our near-optimality result.

2 Preliminaries

We begin by presenting the basic definitions that will be used in the paper. In this work, we consider feed-forward neural networks, using a linear output neuron and a non-linear activation function $\sigma :$ $\mathbb{R} \to \mathbb{R}$ for the other neurons, such as the commonly-used rectified unit (ReLU) $\sigma(x) = \max(x, 0)$, the sigmoid $\sigma(x) = (1 + e^{-x})^{-1}$ or the Heaviside function $\sigma(x) = \mathbf{1}_{\{x \geq 0\}}$. Let $d \geq 1$ be the

Space	Nb. of neurons	Nb. of training parameters	Depth	Activation σ	Reference
$W^{r,p}$	$\epsilon^{-\frac{d}{r}}$	$\epsilon^{-\frac{d}{r}}$	1	$\mathcal{C}^\infty$, non-poly	Mhaskar (1996)
$X^{2,\infty}$	$\epsilon^{-1}(\log\frac{1}{\epsilon})^{\frac{3(d-1)}{2}+1}$	$\epsilon^{-\frac{1}{2}}(\log\frac{1}{\epsilon})^{\frac{3(d-1)}{2}}$	2	ReLU-like	**This paper**
$X^{2,\infty}$	$\epsilon^{-\frac{3}{2}}(\log\frac{1}{\epsilon})^{\frac{3(d-1)}{2}}$	$\epsilon^{-\frac{1}{2}}(\log\frac{1}{\epsilon})^{\frac{3(d-1)}{2}}$	2	Sigmoid-like	**This paper**
$W^{r,p}$	$\epsilon^{-\frac{d}{r}}\log\frac{1}{\epsilon}$	$\epsilon^{-\frac{d}{r}}\log\frac{1}{\epsilon}$	$\mathcal{O}(\log\frac{1}{\epsilon})$	ReLU	Yarotsky (2017) Liang & Srikant (2016)
Bandlimited functions	$\epsilon^{-2}(\log\frac{1}{\epsilon})^2$	$\epsilon^{-2}(\log\frac{1}{\epsilon})^2$	$\mathcal{O}((\log\frac{1}{\epsilon})^2)$	ReLU	Montanelli et al. (2019)
$X^{2,\infty}$	$\epsilon^{-\frac{1}{2}}(\log\frac{1}{\epsilon})^{\frac{3(d-1)}{2}+1}$	$\epsilon^{-\frac{1}{2}}(\log\frac{1}{\epsilon})^{\frac{3(d-1)}{2}}$	$\mathcal{O}(\log d\cdot\log\frac{1}{\epsilon})$	ReLU	Montanelli & Du (2019)
$X^{2,\infty}$	$\epsilon^{-\frac{1}{2}}(\log\frac{1}{\epsilon})^{\frac{3(d-1)}{2}}$	$\epsilon^{-\frac{1}{2}}(\log\frac{1}{\epsilon})^{\frac{3(d-1)}{2}}$	$\lceil\log_2 d\rceil+1$	$\mathcal{C}^2$, non-linear	**This paper**

Table 1: Approximation results for Sobolev $W^{r,p}$ and Korobov $X^{2,\infty}$ functions by shallow and deep networks. Number of neurons and training parameters are given in O notation.

dimension of the input. We define a 1-hidden-layer network with N neurons as

$$\boldsymbol{x} \mapsto \sum_{k=1}^{N} u_k \sigma(\boldsymbol{w_k}^\top \boldsymbol{x} + b_k),$$

where $\boldsymbol{w_k} \in \mathbb{R}^d$, $b_k \in \mathbb{R}$ for $i = 1, \ldots, N$ are the parameters of the network. A neural network with several hidden layers is obtained by feeding the outputs of a given layer as inputs to the next layer. We are interested in the expressive power of neural networks i.e. the ability to approximate a target function $f : \mathbb{R}^d \to \mathbb{R}$ with as few neurons as possible, on the unit hyper-cube $\Omega := [0, 1]^d$. Another relevant metric is the number of parameters that needs to be trained to approximate the function, that is, the number of parameters of the approximating network (u_k, $\boldsymbol{w}_k$ and b_k) depending on the function to approximate. We will adopt L^∞ norm as a measure of approximation error.

Let us now define some notations that are necessary to present the space of functions that we will approximate. For an integer r, we denote $\mathcal{C}^r$ the space of one dimensional functions differentiable r times and with continuous derivatives. In our analysis, we consider functions f with bounded mixed derivatives. For a multi-index $\boldsymbol{\alpha} \in \mathbb{N}^d$, we define the derivative of order $\boldsymbol{\alpha}$, $D^{\boldsymbol{\alpha}} f := \frac{\partial^{|\boldsymbol{\alpha}|_1} f}{\partial x_1^{\alpha_1} \ldots \partial x_d^{\alpha_d}}$, where $|\boldsymbol{\alpha}|_1 = \sum_{i=1}^{d} |\alpha_i|$. Two common function spaces in a compact $\Omega \subset \mathbb{R}^d$ are the Sobolev spaces $W^{r,p}(\Omega)$ of functions having weak partial derivatives up to order r in $L^p(\Omega)$ and the Korobov spaces $X^{r,p}(\Omega)$ of functions vanishing at the boundary and having weak mixed second derivatives up to order r in $L^p(\Omega)$.

$$W^{r,p}(\Omega) = \{f \in L^p(\Omega) \ : \ D^{\boldsymbol{\alpha}} f \in L^p(\Omega), |\boldsymbol{\alpha}|_1 \leq r\},$$
$$X^{r,p}(\Omega) = \{f \in L^p(\Omega) \ : \ f|_{\partial\Omega} = 0, D^{\boldsymbol{\alpha}} f \in L^p(\Omega), |\boldsymbol{\alpha}|_\infty \leq r\}.$$

where $\partial\Omega$ denotes the boundary of Ω, $|\boldsymbol{\alpha}|_1 = \sum_{i=1}^{d} |\alpha_i|$ and $|\boldsymbol{\alpha}|_\infty = \sup_{i=1,\ldots,d} |\alpha_i|$ are respectively the L^1 and infinity norm. Note that Korobov spaces $X^{r,p}(\Omega)$ are subsets of Sobolev spaces $W^{r,p}(\Omega)$. For $p = \infty$, the usual norms on these spaces are given by

$$|f|_{W^{r,p}(\Omega)} := \max_{|\boldsymbol{\alpha}|_1 \leq r} \|D^{\boldsymbol{\alpha}} f\|_\infty, \quad |f|_{X^{r,p}(\Omega)} := \max_{|\boldsymbol{\alpha}|_\infty \leq r} \|D^{\boldsymbol{\alpha}} f\|_\infty,$$

For simplicity we will write $|\cdot|_{2,\infty}$ for $|\cdot|_{X^{2,\infty}}$. We focus our analysis on approximating functions on the Korobov space $X^{2,\infty}(\Omega)$ for which we show that neural networks are near-optimal. We give further discussions on Korobov functions and provide examples in Appendix A.

2.1 THE CURSE OF DIMENSIONALITY

In analysing neural networks representation power, we adopt the point of view of asymptotic results in ϵ (or equivalently, in the number of neurons), which is a well-established setting in the literature Mhaskar (1996); Bungartz & Griebel (2004); Yarotsky (2017); Montanelli & Du (2019). In the rest of the paper, for convenience, we use $\mathcal{O}$ notation which hide constants in d. For each result, full dependencies in d are provided in the appendix.

Previous efforts to quantify the number of neurons needed to approximate large general class of functions within ϵ showed that neural networks and most classical functional approximation schemes

exhibit the curse of dimensionality. For example, in the case of Sobolev functions, Mhaskar proved the following approximation bound.

Theorem 2.1 (Mhaskar (1996))**.** *Let $p, r \geq 1$, and $\sigma : \mathbb{R} \rightarrow \mathbb{R}$ be an infinitely differentiable activation function, non-polynomial on any interval of $\mathbb{R}$. Let $\epsilon > 0$ sufficiently small. For any $f \in W^{r,p}$, there exists a shallow neural network with one hidden layer, activation function σ, and $\mathcal{O}(\epsilon^{-\frac{d}{r}})$ neurons approximating f within ϵ for the infinity norm.*

Therefore, the approximation of Sobolev functions by neural networks suffers from the curse of dimensionality since the number of neurons needed grows exponentially with the input space dimension d. This curse is not due to poor performance of neural networks but rather to the choice of the Sobolev space. DeVore et al. (1989) proved that any learning algorithm with continuous parameters needs at least $\Theta(\epsilon^{-\frac{d}{r}})$ parameters to approximate the Sobolev space $W^{r,p}$. This shows that the class of Sobolev functions suffers inherently from the curse of dimensionality and no continuous function approximator can overcome it. We detail this notion later in Section 5.

The natural question that arises is whether there exists a reasonable and sufficiently large class of functions for which there is no inherent curse of dimensionality. We are interested in this case in the performance of neural networks in approximating this space of functions. Instead of the Sobolev space, we turn to Korobov space $X^{2,\infty}(\Omega)$ of functions with bounded mixed derivatives. Korobov spaces have been introduced for solving partial differential equations (Korobov, 1959; Smolyak, 1963), and have then been used extensively in the context of high-dimensional function approximation (Zenger & Hackbusch, 1991; Bungartz & Griebel, 2004). Notice that this space of functions is included in the Sobolev space, but still reasonably large as the regularity condition concerns only second order derivatives. Two questions will be of interest. First, how many neurons and training parameters a neural network needs to approximate any Korobov function within ϵ in the L^∞ norm? Second, how does neural network performance compare to the theoretically best possible function approximators for Korobov space?

2.2 SPARSE GRIDS AND HIERARCHICAL BASIS

We review in this subsection the notion of sparse grids which will be key in our neural networks constructions to approximate Korobov functions. Sparse grids were introduced by Zenger Zenger (1991) and have since then been extensively used for high-dimensional function approximation. They have been proven to lessen the curse of dimensionality for Korobov spaces. We refer to Bungartz & Griebel (2004) for a thorough review of the topic.

The goal is to define discrete approximation spaces with basis functions. Instead of a classical uniform grid partition of the hyper-cube $[0, 1]^d$ involving n^d components, where n is the number of partitions in each coordinate, the sparse grid approach uses a smarter partitioning of the cube preserving the approximation accuracy while drastically reducing the number of components of the grid. The construction involves a 1-dimensional mother function ϕ which is used to generate all the functions of the basis. For example, a simple choice for the building block ϕ is the standard hat function $\phi(x) := (1 - |x|)_+$. The hat function is not the only possible choice. In the latter proofs we will specify which mother function is used, in our case either the interpolates of Deslauriers & Dubuc (1989) (which we define rigorously later in our proofs) or the hat function ϕ which can be seen as the Deslaurier-Dubuc interpolet of order 1. These more elaborate mother functions enjoy more smoothness while essentially preserving the approximation power.

Assume the mother function has support in $[-k, k]$. For $j = 1, \ldots, d$, it can be used to generate a set of local functions $\phi_{l_j, i_j} : [0, 1] \longrightarrow \mathbb{R}$ for all $l_j \geq 1$ and $1 \leq i_j \leq 2^{l_j} - 1$ with support $\left[\frac{i_j - k}{2^{l_j}}, \frac{i_j + k}{2^{l_j}} \right]$ as follows, $\phi_{l_j, i_j}(x) := \phi(2^{l_j} x - i_j), \ x \in [0, 1]$. We then define a basis of d-dimensional functions by taking the tensor product of these 1-dimensional functions. For all $\boldsymbol{l}, \boldsymbol{i} \in \mathbb{N}^d$ with $\boldsymbol{l} \geq \boldsymbol{1}$ and $\boldsymbol{1} \leq \boldsymbol{i} \leq 2^{\boldsymbol{l}} - \boldsymbol{1}$ where $2^{\boldsymbol{l}}$ denotes $(2^{l_1}, \ldots, 2^{l_d})$, define $\phi_{\boldsymbol{l}, \boldsymbol{i}}(\boldsymbol{x}) := \prod_{j=1}^d \phi_{l_j, i_j}(x_j), \ \boldsymbol{x} \in \mathbb{R}^d$. For a fixed $\boldsymbol{l} \in \mathbb{N}^d$, we will consider the *hierarchical increment space* $W_{\boldsymbol{l}}$ which is the subspace spanned by the functions $\{\phi_{\boldsymbol{l}, \boldsymbol{i}} \ : \ \boldsymbol{1} \leq \boldsymbol{i} \leq 2^{\boldsymbol{l}} - \boldsymbol{1}\}$, as illustrated in Figure 1,

$$W_{\boldsymbol{l}} := \text{span}\{\phi_{\boldsymbol{l}, \boldsymbol{i}}, \ \boldsymbol{1} \leq \boldsymbol{i} \leq 2^{\boldsymbol{l}} - \boldsymbol{1}, \ i_j \text{ odd for all } 1 \leq j \leq d\}.$$

Note that in the hierarchical increment $W_{\boldsymbol{l}}$, all basis functions have disjoint support. A key obser-

Figure 1: Hierarchical basis from the sparse grid construction using the hat function $(1 - |\cdot|)_+$.

vation is that Korobov functions $X^{2,p}(\Omega)$ can be expressed uniquely in this hierarchical basis. More precisely, there is a unique representation of $u \in X^{2,p}(\Omega)$ as $u(\boldsymbol{x}) = \sum_{\boldsymbol{l},\boldsymbol{i}} v_{\boldsymbol{l},\boldsymbol{i}}\phi_{\boldsymbol{l},\boldsymbol{i}}(\boldsymbol{x})$, where the sum is taken over all multi-indices $\boldsymbol{l} \geq 1$ and $1 \leq \boldsymbol{i} \leq 2^{\boldsymbol{l}} - 1$ where all components of $\boldsymbol{i}$ are odd. In particular, all basis functions are linearly independent. Notice that this sum is infinite, the objective is now to define a finite-dimensional subspace of $X^{2,p}(\Omega)$ that will serve as an approximation space. Sparse grids use a carefully chosen subset of the hierarchical basis functions to construct the approximation space $V_n^{(1)} := \bigoplus_{|\boldsymbol{l}|_1 \leq n+d-1} W_{\boldsymbol{l}}$. For the particular choice of the hat function for ϕ, Bungartz and Griebel Bungartz & Griebel (2004) showed that this choice of approximating space leads to a good approximating error.

Theorem 2.2 (Bungartz and Griebel Bungartz & Griebel (2004)). *Let $f \in X^{2,\infty}(\Omega)$ and $f_n^{(1)}$ be the projection of f on the subspace $V_n^{(1)}$. We have, $\|f - f_n^{(1)}\|_\infty = O\left(2^{-2n}n^{d-1}\right)$. Furthermore, if $v_{\boldsymbol{l},\boldsymbol{i}}$ denotes the coefficient of $\phi_{\boldsymbol{l},\boldsymbol{i}}$ in the decomposition of $f_n^{(1)}$ in $V_n^{(1)}$, then we have the upper bound $|v_{\boldsymbol{l},\boldsymbol{i}}| \leq 2^{-d}c^{-2|\boldsymbol{l}|_1}|f|_{2,\infty}$, for all $\boldsymbol{l}, \boldsymbol{i} \in \mathbb{N}^d$ with $|\boldsymbol{l}|_1 \leq n + d - 1$, $\boldsymbol{1} \leq \boldsymbol{i} \leq 2^{\boldsymbol{l}} - 1$ where $\boldsymbol{i}$ has odd components.*

3   THE REPRESENTATION POWER OF SHALLOW NEURAL NETWORKS

It has recently been shown that deep neural networks, with depth scaling with ϵ, lessen the curse of dimensionality on the numbers of neuron needed to approximate the Korobov space Montanelli & Du (2019). However, to the best of our knowledge, the question of whether shallow neural networks with fixed universal depth — independent of ϵ and d — escape the curse of dimensionality as well for the Korobov space remains open. We settle this question by proving that shallow neural networks also lessen the curse of dimensionality for Korobov space.

Theorem 3.1. *Let $\epsilon > 0$. For all $f \in X^{2,\infty}(\Omega)$, there exists a neural network with 2 layers, ReLU activation, $\mathcal{O}(\epsilon^{-1}(\log \frac{1}{\epsilon})^{\frac{3(d-1)}{2}+1})$ neurons, and $\mathcal{O}(\epsilon^{-\frac{1}{2}}(\log \frac{1}{\epsilon})^{\frac{3(d-1)}{2}})$ training parameters that approximates f within ϵ for the infinity norm.*

In order to prove Theorem 3.1, we construct the approximating neural network explicitly. The first step is to construct a neural network architecture with two layers and $\mathcal{O}(d^{\frac{3}{2}}\epsilon^{-\frac{1}{2}}\log\frac{1}{\epsilon})$ neurons that approximates the product function $p : \boldsymbol{x} \in [0,1]^d \longmapsto \prod_{i=1}^n x_i$ within ϵ for all $\epsilon > 0$.

Proposition 3.2. *For all $\epsilon > 0$, there exists a neural network with depth 2, ReLU activation and $\mathcal{O}(d^{\frac{3}{2}}\epsilon^{-\frac{1}{2}}\log\frac{1}{\epsilon})$ neurons, that approximates the product function $p : \boldsymbol{x} \in [0,1]^d \longrightarrow \prod_{i=1}^d x_i$ within ϵ for the infinity norm.*

Sketch of proof   The proof builds upon the observation that $p(\boldsymbol{x}) = \exp(\sum_{i=1}^d \log x_i)$. We construct an approximating 2-layer neural network where the first layer approximates $\log x_i$ for $1 \leq i \leq d$, and the second layer approximates the exponential. We illustrate the construction of the proof in Figure 2. More precisely, fix $\epsilon > 0$. Consider the function $h_\epsilon : x \in [0,1] \mapsto \max(\log x, \ \log \epsilon)$. We approximate h_ϵ within $\frac{\epsilon}{d}$ with a piece-wise affine function with $\mathcal{O}(d^{\frac{1}{2}}\epsilon^{-\frac{1}{2}}\log\frac{1}{\epsilon})$ pieces and then represent this piece-wise affine function with a single layer neural network $\hat{h}_\epsilon$ with the same number of neurons as the number of pieces (Lemma B.1, Appendix B.1). This 1-layer network verifies, therefore, $\|h_\epsilon - \hat{h}_\epsilon\|_\infty \leq \frac{\epsilon}{d}$. The first layer of our final network is the union of d copies of the 1-layer network $\hat{h}_\epsilon$: one for each dimension i, approximating $\log x_i$. Similarly, consider the exponential $g : x \in \mathbb{R}_- \mapsto e^x$. We construct a 1-layer neural network $\hat{g}_\epsilon$ with $\mathcal{O}(\epsilon^{-\frac{1}{2}}\log\frac{1}{\epsilon})$ neurons such that $\|g - \hat{g}_\epsilon\|_\infty \leq \epsilon$. This will serve as second layer. Formally, the constructed approximation $\hat{p}_\epsilon$ of

Figure 2: Shallow neural network with ReLU activation implementing the product function $\prod_{i=1}^{d} x_i$ within ϵ in infinity norm. The network has $\mathcal{O}(d^{\frac{3}{2}}\epsilon^{-\frac{1}{2}}\log\frac{1}{\epsilon})$ neurons on the first layer and $\mathcal{O}(\epsilon^{-\frac{1}{2}}\log\frac{1}{\epsilon})$ neurons on the second layer.

the product function is $\hat{p}_\epsilon = \hat{g}_\epsilon\left(\sum_{i=1}^{d}\hat{h}_\epsilon(x_i)\right)$. This 2-layer neural network has $\mathcal{O}(d^{\frac{3}{2}}\epsilon^{-\frac{1}{2}}\log\frac{1}{\epsilon})$ neurons and verifies $\|\hat{p}_\epsilon - p\|_\infty \le \epsilon$.

We use this result to prove Theorem 3.1 and show that we can approximate any Korobov function $f \in X^{2,\infty}(\Omega)$ within ϵ with a 2-layer neural network of $\mathcal{O}(\epsilon^{-\frac{1}{2}}(\log\frac{1}{\epsilon})^{\frac{3(d-1)}{2}})$ neurons. Consider the sparse grid construction of the approximating space $V_n^{(1)}$ using the standard hat function as mother function to create the hierarchical basis $W_{\boldsymbol{l}}$ (introduced in Section 2.2). Recall that the approximation space is defined as $V_n^{(1)} := \bigoplus_{|\boldsymbol{l}|_1 \le n+d-1} W_{\boldsymbol{l}}$. The key idea is to construct a shallow neural network approximating the sparse grid approximation and then use the result of Theorem 2.2 to derive the approximation error. Let $f_n^{(1)}$ be the projection of f on the subspace $V_n^{(1)}$ defined in Section 2.2. $f_n^{(1)}$ can be written as $f_n^{(1)}(\boldsymbol{x}) = \sum_{(\boldsymbol{l},\boldsymbol{i})\in U_n^{(1)}} v_{\boldsymbol{l},\boldsymbol{i}}\phi_{\boldsymbol{l},\boldsymbol{i}}(\boldsymbol{x})$, where $U_n^{(1)}$ contains the indices $(\boldsymbol{l}, \boldsymbol{i})$ of basis functions present in $V_n^{(1)}$. We can use Theorem 2.2 and choose n carefully such that $f_n^{(1)}$ approximates f within ϵ for L^∞ norm. The goal is now to approximate $f_n^{(1)}$ with a shallow neural network. Note that the basis functions can be written as a product of univariate functions $\phi_{\boldsymbol{l},\boldsymbol{i}} = \prod_{j=1}^{d}\phi_{l_j,i_j}$. We can therefore use a similar structure to the product approximation of Proposition 3.2 to approximate the basis functions. Specifically, the first layer approximate the $d(2^n - 1) = \mathcal{O}(\epsilon^{-\frac{1}{2}}(\log\frac{1}{\epsilon})^{\frac{d-1}{2}})$ terms $\log\phi_{l_j,i_j}$ necessary to construct the basis functions of $V_n^{(1)}$ and a second layer to approximate the exponential in order to obtain approximations of the $\mathcal{O}(2^n n^{d-1}) = \mathcal{O}(\epsilon^{-\frac{1}{2}}(\log\frac{1}{\epsilon})^{\frac{3(d-1)}{2}})$ basis functions of $V_n^{(1)}$. We provide a detailed figure illustrating the construction, Figure 5 in Appendix B.3.

The shallow network that we constructed in Theorem 3.1 uses the ReLU activation function. We extend this result to a larger class of activation functions which include commonly used ones.

Definition 3.3. *A* sigmoid-like *activation function* $\sigma : \mathbb{R} \to \mathbb{R}$ *is a non-decreasing function having finite limits in* $\pm\infty$. *A* ReLU-like *activation function* $\sigma : \mathbb{R} \to \mathbb{R}$ *is a function having a horizontal asymptote in* $-\infty$ *i.e.* σ *is bounded in* $\mathbb{R}_-$, *and an affine (non-horizontal) asymptote in* $+\infty$, *i.e. there exists* $b > 0$ *such that* $\sigma(x) - bx$ *is bounded in* $\mathbb{R}_+$.

The majority of the commonly used activation functions fall into one of the two classes. Examples of sigmoid-like activations include the Heaviside, logistic, tanh, arctan and softsign activations, while ReLU-like activations include the ReLU, ISRLU, ELU and soft-plus activations. We extend Theorem 3.1 to all these activations.

Theorem 3.4. *For any approximation tolerance* $\epsilon > 0$, *and for any* $f \in X^{2,\infty}(\Omega)$ *there exists a neural network with depth 2 and* $\mathcal{O}(\epsilon^{-\frac{1}{2}}(\log\frac{1}{\epsilon})^{\frac{3(d-1)}{2}})$ *training parameters that approximates* f *within* ϵ *for the infinity norm, with* $O\left(\epsilon^{-1}\log(\frac{1}{\epsilon})^{\frac{3(d-1)}{2}+1}\right)$ *(resp.* $\mathcal{O}(\epsilon^{-\frac{3}{2}}\log(\frac{1}{\epsilon})^{\frac{3(d-1)}{2}})$*) neurons for a ReLU-like (resp. sigmoid-like) activation.*

4   THE REPRESENTATION POWER OF DEEP NEURAL NETWORKS

Montanelli and Du Montanelli & Du (2019) used the sparse grid approach to construct deep neural networks with ReLU activation, approximating Korobov functions with $\mathcal{O}(\epsilon^{-\frac{1}{2}}(\log\frac{1}{\epsilon})^{\frac{3(d-1)}{2}+1})$ neurons, and depth $\mathcal{O}(\log\frac{1}{\epsilon})$ for the L^{∞} norm. We show that we can improve this bound for deep neural networks with $\mathcal{C}^2$ non-linear activation functions. We prove that we only need $\mathcal{O}(\epsilon^{-\frac{1}{2}}(\log\frac{1}{\epsilon})^{\frac{3(d-1)}{2}})$ neurons and fixed depth, independent of ϵ, to approximate the unit ball of the Korobov space within ϵ in the L^{∞} norm.

Theorem 4.1. *Let $\sigma \in \mathcal{C}^2$ be a non-linear activation function. Let $\epsilon > 0$. For any function $f \in X^{2,\infty}(\Omega)$, there exists a neural network of depth $\lceil \log_2 d \rceil + 1$, with ReLU activation on the first layer and activation function σ for the next layers, $\mathcal{O}(\epsilon^{-\frac{1}{2}}(\log\frac{1}{\epsilon})^{\frac{3(d-1)}{2}})$ neurons, and $\mathcal{O}(\epsilon^{-\frac{1}{2}}(\log\frac{1}{\epsilon})^{\frac{3(d-1)}{2}})$ training parameters approximating f within ϵ for the infinity norm.*

This new bound on the number of parameters and neurons matches the approximation power of sparse grids. In fact, sparse grids use $\Theta(\epsilon^{-\frac{1}{2}}(\log\frac{1}{\epsilon})^{\frac{3(d-1)}{2}})$ parameters (weights of basis functions) to approximate Korobov functions within ϵ. Our construction in Theorem 4.1 shows that deep neural networks with fixed depth in ϵ can fully encode sparse grids approximators. Neural networks are therefore more powerful function approximators. In particular, any sparse grid approximation using $\mathcal{O}(N(\epsilon))$ parameters, can be represented exactly by a neural network using $\mathcal{O}(N(\epsilon))$ neurons.

Figure 3: Deep neural network approximating a Korobov function $f \in X^{2,\infty}(\Omega)$ within ϵ. It contains $|U_n^{(1)}|$ sub-networks $\mathcal{P}_{\boldsymbol{l},\boldsymbol{i}}$ implementing the basis $\phi_{\boldsymbol{l},\boldsymbol{i}}$ with arbitrary precision. The complete network has $\mathcal{O}(\epsilon^{-\frac{1}{2}}(\log\frac{1}{\epsilon})^{\frac{3(d-1)}{2}})$ neurons and depth $\lceil \log_2 d \rceil + 1$.

The deep approximating neural network (see Figure 3) has a very similar structure to our construction of an approximating shallow network in the Theorem 3.1. The main difference lies in the approximation of the product function. Instead of using a 2-layer neural network, we now make use of a deep network. The following result of Lin et al. (Lin et al., 2017, Appendix A) shows that deep neural networks can represent exactly the product function.

Proposition 4.2 (Lin et al. (2017)). *Let σ be $\mathcal{C}^2$ non linear activation function. For any approximation error $\epsilon > 0$, there exists a neural network with $\lceil \log_2 d \rceil$ hidden layers and activation σ, using at most $8d$ neurons arranged in a binary tree network that approximates the product function $\prod_{i=1}^{d} x_i$ on $[0,1]^d$ within ϵ for the infinity norm.*

An important remark is that the structure of the constructed neural network is independent of ϵ. In particular, the depth and number of neurons is independent of the approximation precision ϵ, which

we refer to as *exact* approximation. It is known that an exponential number of neurons is needed in order to *exactly* approximate the product function with a 1-layer neural network Lin et al. (2017), however, the question of whether one could approximate the product with a shallow network and a polynomial number of neurons, remained open. In Proposition 3.2, we answer positively to this question by constructing an ϵ-approximating neural network of depth 2 with ReLU activation and $\mathcal{O}(d^{\frac{3}{2}}\epsilon^{-\frac{1}{2}}\log\frac{1}{\epsilon})$ neurons. Using the same ideas as in Theorem 3.4, we can generalize this result to obtain an ϵ-approximating neural network of depth 2 with $\mathcal{O}(d^{\frac{3}{2}}\epsilon^{-\frac{1}{2}}\log\frac{1}{\epsilon})$ neurons for a ReLU-like activation, or $\mathcal{O}(d^2\epsilon^{-1}\log\frac{1}{\epsilon})$ neurons for a sigmoid-like activation.

5   NEURAL NETWORKS ARE NEAR-OPTIMAL FUNCTION APPROXIMATORS

In the previous sections, we proved and discussed upper bounds on the number of neurons and training parameters needed by deep and shallow neural networks to approximate the Korobov space $X^{2,\infty}(\Omega)$. In this section, we investigate how good is the performance of neural networks as functional approximators. We prove a lower bound on the number of parameters needed by any continuous function approximator to approximate the Korobov space. We will show in particular that neural networks, deep and shallow, nearly match this lower bound, making them near-optimal function approximators. Let us first formalize the notion of continuous function approximators, following the framework of DeVore et al. DeVore et al. (1989).

For any Banach space $\mathcal{X}$ — one can think of $\mathcal{X}$ as a space of functions — and a subset $K \subset \mathcal{X}$ of elements to approximate, we define a continuous function approximator with N parameters as a continuous parametrization $a : K \to \mathbb{R}^N$ together with a reconstruction scheme which is a N-dimensional manifold $\mathcal{M}_N : \mathbb{R}^N \to \mathcal{X}$. For any element $f \in K$, the approximation given is $\mathcal{M}_N(a(f))$: the parametrization a is derived continuously from the function f and then given as input to the reconstruction manifold that outputs an approximation function in $\mathcal{X}$. The error of this function approximator is defined as $E_{N,a,\mathcal{M}_N}(K)_{\mathcal{X}} := \sup_{f\in K}|f - \mathcal{M}_N(a(f))|_{\mathcal{X}}$. The best function approximator for space K minimizes this error. The minimal error for space K is given by

$$E_N(K)_{\mathcal{X}} = \min_{a,\mathcal{M}_N} E_{N,a,\mathcal{M}_N}(K)_{\mathcal{X}}.$$

In other terms, a continuous function approximator with N parameters cannot hope to approximate K better than within $E_N(K)_{\mathcal{X}}$. A class of function approximators is a set of function approximators with a given structure. For example, neural networks with continuous parametrizations are a class of function approximators where the number of parameters corresponds to the number of training parameters i.e, the parameters of the network that depend on the desired function to approximate. We say that a class of function approximators is optimal for the space of functions K if it matches this minimal error asymptotically in N, within a constant multiplicative factor. In other words, the number of parameters needed by the class to approximate functions in K within ϵ matches asymptotically, within a constant, the least number of parameters N needed to satisfy $E_N(K)_{\mathcal{X}} \le \epsilon$. The norm considered in the approximation of the functions of K is the norm associated to the space $\mathcal{X}$. DeVore et al. DeVore et al. (1989) showed that this minimum error $E_N(K)_{\mathcal{X}}$ admits a lower bound characterized by the Bernstein width of the subset $K \subset \mathcal{X}$ defined as

$$b_N(K)_{\mathcal{X}} := \sup_{X_{N+1}} \sup\{\rho : \rho U(X_{N+1}) \subset K\},$$

where the outer sup is taken over all $N + 1$ dimensional linear sub-spaces of $\mathcal{X}$, and $U(Y)$ denotes the unit ball of Y for any linear subspace Y of $\mathcal{X}$.

Theorem 5.1 (DeVore et al. (1989)). *Let $\mathcal{X}$ be a Banach space and let $K \subset \mathcal{X}$. Then, $E_N(K)_{\mathcal{X}} \ge b_N(K)_{\mathcal{X}}$.*

We prove a lower bound on the least number of parameters any class of continuous function approximators needs to approximate functions of the Korobov space.

Theorem 5.2. *Take $\mathcal{X} = L^\infty(\Omega)$ and $K = \{f \in X^{2,\infty}(\Omega) : |f|_{X^{2,\infty}(\Omega)} \le 1\}$ the unit ball of the Korobov space. Then, there exists $c > 0$ such that $E_N(K)_{\mathcal{X}} \ge \frac{c}{N^2}(\log N)^{d-1}$.*

Equivalently, for $\epsilon > 0$, a continuous function approximator approximating the unit Korobov ball within ϵ in L^∞ norm uses at least $\Theta(\epsilon^{-\frac{1}{2}}(\log\frac{1}{\epsilon})^{\frac{d-1}{2}})$ parameters.

This lower bound matches within a logarithmic factor the upper bound on the number of training parameters needed by deep and shallow neural networks to approximate the Korobov space within ϵ: $\mathcal{O}(\epsilon^{-\frac{1}{2}}(\log\frac{1}{\epsilon})^{\frac{3(d-1)}{2}})$ (Theorem 3.1 and Theorem 4.1). It exhibits the same exponential dependence in d with base $\log\frac{1}{\epsilon}$ and the same main dependence on ϵ of $\epsilon^{-\frac{1}{2}}$. Note that the upper and lower bound can be rewritten as $\mathcal{O}(\epsilon^{-1/2-\delta})$ for all $\delta > 0$. Moreover, our constructions in Theorem 3.1 and Theorem 4.1 are continuous, which comes directly from the continuity of the sparse grid parameters (see bound on $v_{l,i}$ in Theorem 2.2). Our bounds prove therefore that deep and shallow neural networks are near optimal classes of function approximators for the Korobov space.

Sketch of proof We seek an appropriate subspace X_{N+1} in order to get lower bound the Bernstein width $b_N(K)_{\mathcal{X}}$, which in turn provides a lower bound on the approximation error (Theorem 5.1). To do so, we use the Deslaurier-Dubuc interpolet of degree 2, $\phi^{(2)}$ (see Figure 6) which is $\mathcal{C}^2$. Using the sparse grids approach, we construct a hierarchical basis in $X^{2,\infty}(\Omega)$ using $\phi^{(2)}$ as mother function and define X_{N+1} as the approximation space $V_n^{(1)}$. Here n is chosen such that the dimension of $V_n^{(1)}$ is roughly $N + 1$. The goal is to estimate $\sup\{\rho : \rho U(X_{N+1}) \subset K\}$, which will lead to a bound on $b_N(K)_{\mathcal{X}}$. To do so, we upper bound the Korobov norm by the L^∞ norm for elements of X_{N+1}. For any function $u \in X_{N+1}$ we can write $u = \sum_{l,i} v_{l,i} \cdot \phi_{l,i}$. Using a stencil representation of the coefficients $v_{l,i}$, we are able to obtain an upper bound $|u|_{X^{2,\infty}} \leq \Gamma_d \|u\|_\infty$ where $\Gamma_d = \mathcal{O}(2^{2n}n^{d-1})$. Then, $b_N(K)_{\mathcal{X}} \geq 1/\Gamma_d$ which yields the desired bound.

Interestingly, the subspace X_{N+1} our proof uses to show the lower bound is essentially the same as the subspace we use to approximate Koborov functions in our proof of the upper bounds (Theorem 3.1 and 4.1). The difference is in the choice of the interpolate ϕ to construct the basis functions, degree 2 for the former (which provides needed regularity for the proof), and 1 for the later.

6 CONCLUSION AND DISCUSSION

We have proved new upper and lower bounds on the number of neurons and training parameters needed by shallow and deep neural networks to approximate functions of the Korobov space. Our bounds show that shallow and deep networks, not only lessen the curse of dimensionality but are also near-optimal function approximators of the space of Korobov functions. This work therefore contributes to understanding the practical success of neural networks theoretically.

Our work suggests several extensions. First, we have constructed throughout the paper explicitly deep and shallow structures nearly reaching the optimal number of parameters needed to approximate Korobov functions. It would be very interesting to see if the theoretical near-optimality of these structures translates into powerful empirical performance. While commonly used structures (e.g. Convolution Neural Networks, or Recurrent Neural Networks) are motivated by properties of the data such as symmetries, our structures are motivated by theoretical insights on how to optimally approximate a large general class of functions with a given number of neurons and parameters. These new structures might prove to be competitive with commonly used structures and constitute new building blocks of neural networks in learning tasks.

Second, our upper bounds (Theorem 3.1 and 4.1) nearly match our lower bound (Theorem 5.2) on the least number of training parameters needed to approximate functions of the Korobov space. We wonder if it is possible to close the gap between these bounds and prove neural network's optimality as function approximators. Using our approach, proving neural network's optimality would boil down to proving that sparse grids are optimal function approximators by improving our lower bound to match sparse grid number of parameters $\mathcal{O}(\epsilon^{-\frac{1}{2}}(\log\frac{1}{\epsilon})^{\frac{3(d-1)}{2}})$.

Finally, we showed the near-optimality of neural networks among the set of continuous function approximators. An interesting question would be to explore lower bounds (analog to Theorem 5.2) that we can get when considering larger sets of function approximators. One possibility would be that the curse of dimensionality vanishes for the Sobolev space when considering discontinuous function approximators. In this case, it would be insightful to investigate whether some discontinuous neural network construction can break the curse of dimensionality for the Sobolev space leading to stronger approximation results. The question is then whether neural networks are still near-optimal in these larger sets of function approximators.

REFERENCES

Andrew R Barron. Approximation and estimation bounds for artificial neural networks. *Machine learning*, 14(1):115–133, 1994.

Hans-Joachim Bungartz. *Dünne Gitter und deren Anwendung bei der adaptiven Lösung der dreidimensionalen Poisson-Gleichung*. Technische Universität München, 1992.

Hans-Joachim Bungartz and Michael Griebel. Sparse grids. *Acta numerica*, 13(1):147–269, 2004.

Gilles Deslauriers and Serge Dubuc. Symmetric iterative interpolation processes. In *Constructive approximation*, pp. 49–68. Springer, 1989.

Ronald A DeVore, Ralph Howard, and Charles Micchelli. Optimal nonlinear approximation. *Manuscripta mathematica*, 63(4):469–478, 1989.

Kurt Hornik, Maxwell Stinchcombe, and Halbert White. Multilayer feedforward networks are universal approximators. *Neural networks*, 2(5):359–366, 1989.

Jason M Klusowski and Andrew R Barron. Risk bounds for high-dimensional ridge function combinations including neural networks. *arXiv preprint arXiv:1607.01434*, 2016.

Jason M Klusowski and Andrew R Barron. Approximation by combinations of relu and squared relu ridge functions with l1 and l0 controls. *IEEE Transactions on Information Theory*, 64(12): 7649–7656, 2018.

NM Korobov. Approximate solution of integral equations. *Doklady Akademii Nauk SSSR*, 128(2): 235–238, 1959.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. *Communications of the ACM*, 60(6):84–90, 2017.

Shiyu Liang and Rayadurgam Srikant. Why deep neural networks for function approximation? *arXiv preprint arXiv:1610.04161*, 2016.

Henry W Lin, Max Tegmark, and David Rolnick. Why does deep and cheap learning work so well? *Journal of Statistical Physics*, 168(6):1223–1247, 2017.

Hrushikesh Mhaskar, Qianli Liao, and Tomaso Poggio. Learning functions: when is deep better than shallow. *arXiv preprint arXiv:1603.00988*, 2016.

Hrushikesh N Mhaskar. Neural networks for optimal approximation of smooth and analytic functions. *Neural computation*, 8(1):164–177, 1996.

Hadrien Montanelli and Qiang Du. New error bounds for deep ReLU networks using sparse grids. *SIAM Journal on Mathematics of Data Science*, 1(1):78–92, 2019.

Hadrien Montanelli, Haizhao Yang, and Qiang Du. Deep ReLU networks overcome the curse of dimensionality for bandlimited functions. *arXiv preprint arXiv:1903.00735*, 2019.

David Silver, Aja Huang, Chris J Maddison, Arthur Guez, Laurent Sifre, George Van Den Driessche, Julian Schrittwieser, Ioannis Antonoglou, Veda Panneershelvam, Marc Lanctot, et al. Mastering the game of Go with deep neural networks and tree search. *Nature*, 529(7587):484–489, 2016.

Sergei Abramovich Smolyak. Quadrature and interpolation formulas for tensor products of certain classes of functions. In *Doklady Akademii Nauk*, volume 148, pp. 1042–1045. Russian Academy of Sciences, 1963.

Matus Telgarsky. Benefits of depth in neural networks. In *Conference on learning theory*, pp. 1517–1539. PMLR, 2016.

E Weinan, Chao Ma, and Lei Wu. Barron spaces and the compositional function spaces for neural network models. *arXiv preprint arXiv:1906.08039*, 2019.

Dmitry Yarotsky. Error bounds for approximations with deep ReLU networks. *Neural Networks*, 94:103–114, 2017.

Ch Zenger and W Hackbusch. Parallel algorithms for partial differential equations. In *Notes on Numerical Fluid Mechanics*, volume 31, pp. 241–251. Vieweg, 1991.

Christoph Zenger. Sparse grids. *Parallel Algorithms for Partial Differential Equations*, 31, 1991.

APPENDIX

A ON KOROBOV FUNCTIONS

In this section, we further discuss Korobov functions $X^{2,p}(\Omega)$. Korobov functions enjoy more smoothness than Sobolev functions: smoothness for $X^{2,p}(\Omega)$ is measured in terms of *mixed derivatives* of order two. Korobov functions $X^{2,p}(\Omega)$ can be differentiated twice in *each* coordinates simultaneously, while Sobolev $W^{2,p}(\Omega)$ functions can only be differentiated twice in total. For example, in two dimensions, for a function f to be Korobov it is required to have

$$\frac{\partial f}{\partial x_1}, \frac{\partial f}{\partial x_2}, \frac{\partial^2 f}{\partial^2 x_1}, \frac{\partial^2 f}{\partial^2 x_2}, \frac{\partial^2 f}{\partial x_1 \partial x_2}, \frac{\partial^3 f}{\partial^2 x_1 \partial x_2}, \frac{\partial^3 f}{\partial x_1 \partial^2 x_2}, \frac{\partial^4 f}{\partial^2 x_1 \partial^2 x_2} \in L^p(\Omega),$$

while for f to be Sobolev it requires only

$$\frac{\partial f}{\partial x_1}, \frac{\partial f}{\partial x_2}, \frac{\partial^2 f}{\partial^2 x_1}, \frac{\partial^2 f}{\partial^2 x_2}, \frac{\partial^2 f}{\partial x_1 \partial x_2} \in L^p(\Omega).$$

The former can be seen from $|\boldsymbol{\alpha}|_\infty \leq 2$ and the latter from $|\boldsymbol{\alpha}|_1 \leq 2$ in the definition of $X^{r,p}(\Omega)$ and $W^{r,p}(\Omega)$.

We now provide intuition on why Korobov functions are easier to approximate. One of the key difficulties in approximating Sobolov functions are possible high frequency oscillations which may require an exponential number of neurons Telgarsky (2016). For instance, consider functions which have similar structure to $W_{(n...n)}$ (defined in Subsection 2.2): for any smooth basis function ϕ with support on the unit cube (see Figure 6 for example), consider the linear function space formed by linear combinations of dilated function ϕ with support on each cube d-dimensional grid of step 2^{-n}. This corresponds exactly to the construction of $W_{(n...n)}$ which uses the product of hat function on each dimension as basis function ϕ. This function space can have strong oscillations in *all* directions at a time. The Korobov space prohibits such behavior by ensuring that functions can be differentiated twice on each dimension, simultaneously. As a result, functions cannot oscillate in all directions at a time without having large Korobov norm.

A concrete example of Korobov functions is given by an analogous of the function space $V_n^{(1)}$ which we used as approximation space in the proof of our results (see Section 2.2). Similarly to the previous paragraph, one should use a smooth basis function to ensure differentiability. Recall that $V_n^{(1)}$ is defined as

$$V_n^{(1)} := \bigoplus_{|\boldsymbol{l}|_1 \leq n+d-1} W_{\boldsymbol{l}}.$$

Intuitively, this approximation space introduces a "budget" of oscillations for *all* dimensions through the constraint $\sum_{i=1}^d l_i \leq n+d-1$. As a result, dilations of the basis function can only occur in a restricted set of directions at a time, which ensures that the Korobov norm stays bounded.

B PROOFS OF SECTION 3

B.1 APPROXIMATING THE PRODUCT FUNCTION

In this subsection, we construct a neural network architecture with two layers and $\mathcal{O}(d^{\frac{3}{2}} \epsilon^{-\frac{1}{2}} \log \frac{1}{\epsilon})$ neurons that approximates the product function $p : \boldsymbol{x} \in [0,1]^d \longmapsto \prod_{i=1}^n x_i$ within ϵ for all $\epsilon > 0$, which proves Proposition 3.2. We first prove a simple lemma to represent univariate piece-wise affine functions by shallow neural networks.

Lemma B.1. *Any one dimensional continuous piece-wise affine function with m pieces is representable exactly by a shallow neural network with ReLU activation, with m neurons on a single layer.*

Proof. This is a simple consequence from Proposition 1 in Yarotsky (2017). We recall the proof for completeness. Let $x_1 \leq \cdots \leq x_{m-1}$ be the subdivision of the piece-wise affine function f. We use a neural network of the form

$$g(x) := f(x_1) + \sum_{k=1}^{m-1} w_k (x - x_k)_+ - w_0(x_1 - x)_+,$$

where w_0 is the slope of f on the piece $\leq x_1$, w_1 is the slope of f on the piece $[x_1, x_2]$,

$$w_k = \frac{f(x_{k+1}) - f(x_1) - \sum_{i=1}^{k-1} w_i(x_{k+1} - x_i)}{x_{k+1} - x_k},$$

for $k = 1, \cdots, m-2$, and $w_{m-1} = \tilde{w} - \sum_{k=1}^{m-2} w_k$ where $\tilde{w}$ is the slope of f on the piece $\geq x_{m-1}$. Notice that f and g coincide on all x_k for $1 \leq k \leq m - 1$. Furthermore, g has same slope as f on each pieces, therefore, $g = f$. $\qquad\square$

We can approximate univariate right continuous functions by piece-wise affine functions, and then use Lemma B.1 to represent them by shallow neural networks. The following lemma shows that $\mathcal{O}(\epsilon^{-1})$ neurons are sufficient to represent an increasing right-continuous function with a shallow neural network.

Lemma B.2. *Let $f : I \longrightarrow [c, d]$ be a right-continuous increasing function where I is an interval, and let $\epsilon > 0$. There exists a shallow neural network with ReLU activation, with $\lceil \frac{d-c}{\epsilon} \rceil$ neurons on a single layer, that approximates f within ϵ for the infinity norm.*

Proof. Let $m = \lfloor \frac{d-c}{\epsilon} \rfloor$ Define a subdivision of the image interval $c \leq y_1 \leq \ldots \leq y_m \leq d$ where $y_k = c + k\epsilon$ for $k = 1, \ldots, m$. Note that this subdivision contains exactly $\lceil \frac{d-c}{\epsilon} \rceil$ pieces. Now define a subdivision of I, $x_1 \leq x_2 \leq \ldots \leq x_m$ by

$$x_k := \sup\{x \in I, f(x) \leq y_k\},$$

for $k = 1, \ldots, m$. This subdivision stills has $\lceil \frac{d-c}{\epsilon} \rceil$ pieces. We now construct our approximation function $\hat{f}$ on I as the continuous piece-wise affine function on the subdivision $x_1 \leq \ldots \leq x_m$ such that $\hat{f}(x_k) = y_k$ for all $1 \leq k \leq m$ and $\hat{f}$ is constant before x_1 and after x_m (see Figure 4). Let $x \in I$.

- If $x \leq x_1$, because f is increasing and right-continuous, $c \leq f(x) \leq f(x_1) \leq y_1 = c + \epsilon$. Therefore $|f(x) - \hat{f}(x)| = |f(x) - (c + \epsilon)| \leq \epsilon$.

- If $x_k < x \leq x_{k+1}$, we have $y_k < f(x) \leq f(x_{k+1}) \leq y_{k+1}$. Further note that $y_k \leq \hat{f}(x) \leq y_{k+1}$. Therefore $|f(x) - \hat{f}(x)| \leq y_{k+1} - y_k = \epsilon$.

- If $x_m < x$, then $y_m < f(x) \leq d$. Again, $|f(x) - \hat{f}(x)| = |f(x) - y_m| \leq d - y_m \leq \epsilon$.

Therefore $\|f - \hat{f}\|_\infty \leq \epsilon$. We can now use Lemma B.1 to end the proof. $\qquad\square$

If the function to approximate has some regularity, the number of neurons needed for approximation can be significantly reduced. In the following lemma, we show that $\mathcal{O}(\epsilon^{-\frac{1}{2}})$ neurons are sufficient to approximate a $\mathcal{C}^2$ univariate function with a shallow neural network.

Lemma B.3. *Let $f : [a, b] \longrightarrow [c, d] \in \mathcal{C}^2$, and let $\epsilon > 0$. There exists a shallow neural network with ReLU activation, with $\frac{1}{\sqrt{2\epsilon}} \min(\int \sqrt{|f''|}(1 + \mu(f, \epsilon)), (b-a)\sqrt{\|f''\|_\infty})$ neurons on a single layer, where $\mu(f, \epsilon) \to 1$ as $\epsilon \to 0$, that approximates f within ϵ for the infinity norm.*

Proof. See Appendix B.2.1. $\qquad\square$

We will now use the ideas of Lemma B.2 and Lemma B.3 to approximate a truncated $\log$ function, which we will use in the construction of our neural network approximating the product.

Figure 4: Approximation of a right-continuous increasing function (blue) in an interval $[c, d]$ within ϵ by a piece-wise linear function (red) with $\lfloor \frac{d-c}{\epsilon} \rfloor$ pieces. The approximation is constructed using a regular subdivision of the y axis of step ϵ and constructing a linear approximation in the pre-image of each part of the subdivision.

Corollary B.4. *Let $\epsilon > 0$ sufficiently small and $\delta > 0$. Consider the truncated logarithm function* $\log : [\delta, 1] \longrightarrow \mathbb{R}$. *There exists a shallow neural network with ReLU activation, with $\epsilon^{-\frac{1}{2}} \log \frac{1}{\delta}$ neurons on a single layer, that approximates f within ϵ for the infinity norm.*

Proof. See Appendix B.2.2. □

We are now ready to construct a neural network approximating the product function and prove Proposition 3.2. The proof builds upon on the observation that $\prod_{i=1}^{d} x_i = \exp(\sum_{i=1}^{d} \log x_i)$. We construct an approximating 2-layer neural network where the first layer computes $\log x_i$ for $1 \leq i \leq d$, and the second layer computes the exponential. We illustrate the construction of the proof in Figure 2.

Proof of Proposition 3.2 Fix $\epsilon > 0$. Consider the function $h_\epsilon : x \in [0, 1] \mapsto \max(\log x, \ \log \epsilon) \in [\log \epsilon, 0]$. Using Corollary B.4, there exists a neural network $\hat{h}_\epsilon : [0, 1] \longrightarrow [\log \epsilon, 0]$ with $1 + \lceil d^{\frac{1}{2}} \epsilon^{-\frac{1}{2}} \log \frac{1}{\epsilon} \rceil$ neurons on a single layer such that $\|h_\epsilon - \hat{h}_\epsilon\|_\infty \leq \frac{\epsilon}{d}$. Indeed, one can take the ϵ-approximation of $h_\epsilon : x \in [\epsilon, 1] \mapsto \log x \in [\log \epsilon, 0]$, then extend this function to $[0, \epsilon]$ with a constant equal to $\log \epsilon$. The resulting piece-wise affine function has one additional segment corresponding to one additional neuron in the approximating function. Similarly, consider the exponential $g : x \in \mathbb{R}_- \mapsto e^x \in [0, 1]$. Because g is right-continuous increasing, we can use Lemma B.3 to construct a neural network $\hat{g}_\epsilon : \mathbb{R}_- \longrightarrow [0, 1]$ with $1 + \lceil \frac{1}{\sqrt{2\epsilon}} \log \frac{1}{\epsilon} \rceil$ neurons on a single layer such that $\|g - \hat{g}_\epsilon\|_\infty \leq \epsilon$. Indeed, again one can take the ϵ-approximation of $g_\epsilon : x \in [\log \epsilon, 0] \mapsto e^x \in [0, 1]$, then extend this function to $(-\infty, \log \epsilon]$ with a constant equal to ϵ. The corresponding neural network has an additional neuron. We construct our final neural network $\hat{\phi}_\epsilon$ (see Figure 2) as

$$\hat{\phi}_\epsilon = \hat{g}_\epsilon \left(\sum_{i=1}^{d} \hat{h}_\epsilon(x_i) \right).$$

Note that $\hat{\phi}_\epsilon$ can be represented as a 2-layer neutral network: the first layer is composed of the union of the $1 + \lceil d^{\frac{1}{2}} \epsilon^{-\frac{1}{2}} \log \frac{1}{\epsilon} \rceil$ neurons composing each of the 1-layer neural networks $\hat{h}_\epsilon^i : \boldsymbol{x} \in [0, 1]^d \mapsto \hat{h}_\epsilon(x_i) \in \mathbb{R}$ for each dimension $i \in \{1, \ldots, d\}$. The second layer is composed of the $1 + \lceil \frac{1}{\sqrt{2\epsilon}} \log \frac{1}{\epsilon} \rceil$

neurons of $\hat{g}_\epsilon$. Hence, the constructed neural network $\hat{\phi}_\epsilon$ has $\mathcal{O}(d^{\frac{3}{2}}\epsilon^{-\frac{1}{2}}\log\frac{1}{\epsilon})$ neurons. Let us now analyze the approximation error. Let $\boldsymbol{x} \in [0,1]^d$. For the sake of brevity, denote $\hat{y} = \sum_{i=1}^d \hat{h}_\epsilon(x_i)$ and $y = \sum_{i=1}^d \log(x_i)$. We have,

$$|\hat{\phi}_\epsilon(\boldsymbol{x}) - p(\boldsymbol{x})| \leq |\hat{\phi}_\epsilon(\boldsymbol{x}) - \exp(\hat{y})| + |\exp(\hat{y}) - \exp(y)| \leq \epsilon + \prod_{i=1}^d x_i \cdot |\exp(\hat{y}-y)-1|,$$

where we used the fact that $|\hat{\phi}_\epsilon(\boldsymbol{x}) - \exp(\hat{y})| = |\hat{g}_\epsilon(\hat{y}) - g(\hat{y})| \leq \|\hat{g}_\epsilon - g\|_\infty \leq \epsilon$.

First suppose that $\boldsymbol{x} \geq \epsilon$. In this case, for all $i \in \{1,\ldots,d\}$ we have $|\hat{h}_\epsilon(x_i) - \log(x_i)| = |\hat{h}_\epsilon(x_i) - h_\epsilon(x_i)| \leq \frac{\epsilon}{d}$. Then, $|\hat{y}-y| \leq \epsilon$. Consequently, $|\hat{\phi}_\epsilon(\boldsymbol{x})-p(\boldsymbol{x})| \leq \epsilon+\max(|e^\epsilon-1|,|e^{-\epsilon}-1|) \leq 3\epsilon$, for $\epsilon > 0$ sufficiently small. Without loss of generality now suppose $x_1 \leq \epsilon$. Then $\hat{y} \leq h_\epsilon(x_1) \leq \log\epsilon$, so by definition of $\hat{g}_\epsilon$, we have $0 \leq \hat{\phi}_\epsilon(\boldsymbol{x}) = \hat{g}_\epsilon(\hat{y}) \leq \exp(\log\epsilon) = \epsilon$. Also, $0 \leq p(x) \leq \epsilon$ so finally $|\hat{\phi}_\epsilon(\boldsymbol{x}) - p(\boldsymbol{x})| \leq \epsilon$.

Remark B.5. *Note that using Lemma B.2 instead of Lemma B.3 to construct approximating shallow networks for* $\log$ *and* $\exp$ *would yield approximation functions* $\hat{h}_\epsilon$ *with* $\mathcal{O}(\lceil\frac{d}{\epsilon}\log\frac{1}{\epsilon}\rceil)$ *neurons and* $\hat{g}_\epsilon$ *with* $\mathcal{O}(\lceil\frac{1}{\epsilon}\rceil)$ *neurons. Therefore, the corresponding neural network would approximate the product* p *with* $\mathcal{O}(d^2\epsilon^{-1}\log\frac{1}{\epsilon})$ *neurons.*

B.2 MISSING PROOFS OF SECTION B.1

B.2.1 PROOF OF LEMMA B.3

Proof. Similarly as the proof of Lemma B.2, the goal is to approximate f by a piece-wise affine function $\hat{f}$ defined on a subdivision $x_0 = a \leq x_1 \leq \ldots \leq x_m \leq x_{m+1} = b$ such that f and $\hat{f}$ coincide on $x_0,\ldots,x_{m+1}$. We first analyse the error induced by a linear approximation of the function on each piece. Let $x \in [u,v]$ for $u,v \in I$. Using the mean value theorem, there exists $\alpha_x \in [u,x]$ such that $f(x) - f(u) = f'(\alpha_x)(x-u)$ and $\beta_x \in [x,v]$ such that $f(v) - f(x) = f'(\beta_x)(v-x)$. Combining these two equalities, we get,

$$f(x) - f(u) - (x-u)\frac{f(v)-f(u)}{v-u} = \frac{(v-x)(f(x)-f(u)) - (x-u)(f(v)-f(x))}{v-u}$$

$$= (x-u)(x-v)\frac{f'(\beta_x)-f'(\alpha_x)}{v-u}$$

$$= (x-u)(v-x)\frac{\int_{\alpha_x}^{\beta_x} f''(t)dt}{v-u}$$

Hence,

$$f(x) = f(u) + (x-u)\frac{f(v)-f(u)}{v-u} + (x-u)(v-x)\frac{\int_{\alpha_x}^{\beta_x} f''(t)dt}{v-u}. \tag{1}$$

We now apply this result to bound the approximation error on each pieces of the subdivision. Let $k \in [m]$. Recall $\hat{f}$ is linear on the subdivision $[x_k,x_{k+1}]$ and $\hat{f}(x_k) = f(x_k)$ and $\hat{f}(x_{k+1}) = f(x_{k+1})$. Hence, for all $x \in [x_k,x_{k+1}]$, $\hat{f}(x) = f(x_k) + (x-x_k)\frac{f(x_{k+1})-f(x_k)}{x_{k+1}-x_k}$. Using Equation equation 1 with $u = x_k$ and $v = x_{k+1}$, we get,

$$\|f - \hat{f}\|_{\infty,[x_k,x_{k+1}]} \leq \sup_{x\in[x_k,x_{k+1}]}\left|(x-x_k)(x_{k+1}-x)\frac{\int_{\alpha_x}^{\beta_x} f''(t)dt}{x_{k+1}-x_k}\right|$$

$$\leq \frac{1}{2}(x_{k+1}-x_k)\int_{x_k}^{x_{k+1}}|f''(t)|dt$$

$$\leq \frac{1}{2}(x_{k+1}-x_k)^2\|f''\|_{\infty,[x_k,x_{k+1}]}.$$

Therefore, using a regular subdivision with step $\sqrt{\frac{2\epsilon}{\|f''\|_\infty}}$ yields an ϵ-approximation of f with $\left\lceil\frac{(b-a)\sqrt{\|f''\|_\infty}}{\sqrt{2\epsilon}}\right\rceil$ pieces.

We now show that for any $\mu > 0$, there exists an ϵ-approximation of f with at most $\frac{\int \sqrt{|f''|}}{\sqrt{2\epsilon}}(1 + \mu)$ pieces. To do so, we use the fact that the upper Riemann sum for $\sqrt{f''}$ converges to the integral since $\sqrt{f''}$ is continuous on $[a, b]$. First define a partition $a = X_0 \leq X_K = b$ of $[a, b]$ such that the upper Riemann sum $\mathcal{R}(\sqrt{f''})$ on this subdivision satisfies $\mathcal{R}(\sqrt{f''}) \leq (1 + \mu/2) \int_a^b \sqrt{f''}$. Now define on each interval I_k of the partition a regular subdivision with step $\sqrt{\frac{2\epsilon}{\|f''\|_{I_k}}}$ as before. Finally, consider the subdivision union of all these subdivisions, and construct the approximation $\hat{f}$ on this final subdivision. By construction, $\|f - \hat{f}\|_\infty \leq \epsilon$ because the inequality holds on each piece of the subdivision. Further, the number of pieces is

$$\sum_{i=0}^{K-1} 1 + \frac{(X_{i+1} - X_i) \sup_{[X_i, X_{i+1}]} \sqrt{f''}}{\sqrt{2\epsilon}} = \frac{\mathcal{R}(\sqrt{f''})}{\sqrt{2\epsilon}} + K \leq \frac{\int \sqrt{|f''|}}{\sqrt{2\epsilon}}(1 + \mu),$$

for $\epsilon > 0$ small enough. Using Lemma B.1 we can complete the proof. $\qquad\square$

B.2.2 PROOF OF COROLLARY B.4

Proof. In view of Lemma B.3, the goal is to show that we can remove the dependence of $\mu(f, \epsilon)$ in δ. This essentially comes from the fact that the upper Riemann sum behaves well for approximating $\log$. Consider the subdivision $x_0 := \delta \leq x_1 \leq \ldots \leq x_m \leq x_{m+1} := 1$ with $m = \left\lfloor \frac{1}{\tilde{\epsilon}} \log \frac{1}{\delta} \right\rfloor$ where $\tilde{\epsilon} := \log(1 + \sqrt{2\epsilon})$, such that $x_k = e^{\log \delta + k\tilde{\epsilon}}$, for $k = 0, \ldots, m - 1$. Denote $\hat{f}$ the corresponding piece-wise affine approximation. Similarly to the proof of Lemma B.3, for $k = 0, \ldots, m - 1$,

$$\| \log - \hat{f} \|_{\infty, [x_k, x_{k+1}]} \leq \frac{1}{2}(x_{k+1} - x_k)^2 \|f''\|_{\infty, [x_k, x_{k+1}]} \leq \frac{(e^{\tilde{\epsilon}} - 1)^2}{2} \leq \epsilon.$$

The proof follows. $\qquad\square$

B.3 PROOF OF THEOREM 3.1: APPROXIMATING THE KOROBOV SPACE $X^{2,\infty}(\Omega)$

In this subsection, we prove Theorem 3.1 and show that we can approximate any Korobov function $f \in X^{2,\infty}(\Omega)$ within ϵ with a 2-layer neural network of $\mathcal{O}(\epsilon^{-\frac{1}{2}} (\log \frac{1}{\epsilon})^{\frac{3(d-1)}{2}})$ neurons. We illustrate the construction in Figure 5. Our proof combines the constructed network approximating the product function and a decomposition of f as a sum of separable functions, i.e. a decomposition of the form

$$f(\boldsymbol{x}) \approx \sum_{k=1}^K \prod_{j=1}^d \phi_j^{(k)}(x_j), \quad \forall \boldsymbol{x} \in [0, 1]^d.$$

Consider the sparse grid construction of the approximating space $V_n^{(1)}$ using the standard hat function as mother function to create the hierarchical basis W_l (introduced in Section 2.2). We recall that the approximation space is defined as $V_n^{(1)} := \bigoplus_{|l|_1 \leq n+d-1} W_l$. We will construct a neural network approximating the sparse grid approximation and then use the result of Theorem 2.2 to derive the approximation error. Figure 5 gives an illustration of the construction.

Let $f_n^{(1)}$ be the projection of f on the subspace $V_n^{(1)}$. $f_n^{(1)}$ can be written as

$$f_n^{(1)}(\boldsymbol{x}) = \sum_{(\boldsymbol{l}, \boldsymbol{i}) \in U_n^{(1)}} v_{\boldsymbol{l}, \boldsymbol{i}} \phi_{\boldsymbol{l}, \boldsymbol{i}}(\boldsymbol{x}),$$

where $U_n^{(1)}$ contains the indices $(\boldsymbol{l}, \boldsymbol{i})$ of basis functions present in $V_n^{(1)}$ i.e.

$$U_n^{(1)} := \{(\mathbf{l}, \mathbf{i}), \quad |\mathbf{l}|_1 \leq n + d - 1, \ \mathbf{1} \leq \mathbf{i} \leq 2^{\mathbf{l}} - \mathbf{1}, \ i_j \text{ odd for all } 1 \leq j \leq d\}. \tag{2}$$

Throughout the proof, we explicitly construct a neural network that uses this decomposition to approximate $f_n^{(1)}$. We then use Theorem 2.2 and choose n carefully such that $f_n^{(1)}$ approximates f within ϵ for L^∞ norm. Note that the basis functions can be written as a product of univariate functions $\phi_{\boldsymbol{l}, \boldsymbol{i}} = \prod_{j=1}^d \phi_{l_j, i_j}$. We can therefore use the product approximation of Proposition 3.2

Figure 5: Shallow neural network with ReLU activation approximating a Korobov function $f \in X^{2,\infty}(\Omega)$ within ϵ in infinity norm. The network has $\mathcal{O}(\epsilon^{-1}(\log \frac{1}{\epsilon})^{\frac{d+1}{2}})$ neurons on the first layer and $\mathcal{O}(\epsilon^{-1}\left(\log \frac{1}{\epsilon}\right)^{\frac{3(d-1)}{2}+1})$ neurons on the second layer.

to approximate the basis functions. Specifically, we will use one layer to approximate the terms $\log \phi_{l_j,i_j}$ and a second layer to approximate the exponential.

We now present in detail the construction of the first layer. First, recall that ϕ_{l_j,i_j} is a piece-wise affine function with subdivision $0 \leq \frac{i_j-1}{2^{l_j}} \leq \frac{i_j}{2^{l_j}} \leq \frac{i_j+1}{2^{l_j}} \leq 1$. Define the error term $\tilde{\epsilon} := \frac{\epsilon}{2|f|_{2,\infty}}$. We consider a symmetric subdivision of the interval $\left[\frac{i_j-1+\tilde{\epsilon}}{2^{l_j}}, \frac{i_j+1-\tilde{\epsilon}}{2^{l_j}}\right]$. We define it as follows: $x_0 = \frac{i_j-1+\tilde{\epsilon}}{2^{l_j}} \leq x_1 \leq \cdots \leq x_{m+1} = \frac{i_j}{2^{l_j}} \leq x_{m+2} \leq \cdots \leq x_{2m+2} = \frac{i_j+1-\tilde{\epsilon}}{2^{l_j}}$ where $m = \left\lfloor \frac{1}{\epsilon_0} \log \frac{1}{\tilde{\epsilon}} \right\rfloor$ and $\epsilon_0 := \log(1 + \sqrt{2\tilde{\epsilon}/d})$, such that

$$x_k = \frac{i_j + e^{\log \tilde{\epsilon} + k\epsilon_0}}{2^{l_j}} \qquad 0 \leq k \leq m,$$

$$x_k = \frac{i_j + 1 - e^{\log \tilde{\epsilon} + (2m+2-k)k\epsilon_0}}{2^{l_j}} \qquad m+2 \leq k \leq 2m+2.$$

Note that with this definition, the terms $\log(2^{l_j}x_k - i_j)$ form a regular sequence with step ϵ_0. We now construct the piece-wise affine function $\hat{g}_{l_j,i_j}$ on the subdivision $x_0 \leq \cdots \leq x_{2m+2}$ which co-incides with $\log \phi_{l_j,i_j}$ on $x_0, \cdots, x_{2m+2}$ and is constant on $[0, x_0]$ and $[x_{2m+2}, 1]$. By Lemma B.1, this function can be represented by a 1-layer neural network with as much neurons as the number of pieces of $\hat{g}$, i.e. at most $2\sqrt{\frac{3d}{\tilde{\epsilon}}} \log \frac{1}{\tilde{\epsilon}}$ neurons for ϵ sufficiently small. A similar proof to that of Corollary B.4 shows that $\hat{g}$ approximates $\max(\log \phi_{l_j,i_j}, \log(\tilde{\epsilon}/3))$ within $\tilde{\epsilon}/(3d)$ for the infinity norm. We use this construction to compute in parallel, $\tilde{\epsilon}/(3d)$-approximations of $\max(\log \phi_{l_j,i_j}(x_j), \log \tilde{\epsilon})$ for all $1 \leq j \leq d$, and $1 \leq l_j \leq n, 1 \leq i_j \leq 2^{l_j}$ where i_j is odd. These are exactly the 1-dimensional functions that we will need, in order to compute the d-dimensional function basis of the approximation space $V_n^{(1)}$. There are $d(2^n - 1)$ such univariate functions, therefore our first layer contains at most $2^{n+1}d\sqrt{\frac{3d}{\tilde{\epsilon}}} \log \frac{1}{\tilde{\epsilon}}$ neurons.

We now turn to the second layer. The result of the first two layers will be $\tilde{\epsilon}/3$-approximations of $\phi_{\mathbf{l},\mathbf{i}}$ for all $(\mathbf{l},\mathbf{i}) \in U_n^{(1)}$. Recall that $U_n^{(1)}$ contains the indices for the functions forming a basis of the approximation space $V_n^{(1)}$. To do so, for each indexes $(\mathbf{l},\mathbf{i}) \in U_n^{(1)}$ we construct a 1-layer neural network approximating the function $\exp$, which will compute an approximation of $\exp(\hat{g}_{l_1,i_1} + \cdots + \hat{g}_{l_d,i_d})$. The approximation of $\exp$ is constructed in the same way as for Lemma B.3. Consider a

regular subdivision of the interval $[\log(\tilde{\epsilon}/3), 0]$ with step $\sqrt{2(\tilde{\epsilon}/3)}$, i.e. $x_0 := \log(\tilde{\epsilon}/3) \le x_1 \le \cdots \le x_m \le x_{m+1} = 0$ where $m = \left\lfloor \sqrt{\frac{3}{2\tilde{\epsilon}}} \log \frac{3}{\epsilon} \right\rfloor$, such that $x_k = \log \tilde{\epsilon} + k\sqrt{2\tilde{\epsilon}}, \quad 0 \le k \le m$. Construct the piece-wise affine function $\hat{h}$ on the subdivision $x_0 \le \cdots \le x_{m+1}$ which coincides with $\exp$ on $x_0, \cdots, x_{m+1}$ and is constant on $(-\infty, x_0]$. Lemma B.3 shows that $\hat{h}$ approximates $\exp$ on $\mathbb{R}_-$ within $\tilde{\epsilon}$ for the infinity norm. Again, Lemma B.1 gives a representation of $\hat{h}$ as a 1-layer neural network with as many neurons as pieces in $\hat{h}$ i.e. $1 + \left\lceil \sqrt{\frac{3}{2\tilde{\epsilon}}} \log \frac{3}{\epsilon} \right\rceil$. The second layer is the union of 1-layer neural networks approximating $\exp$ within $\tilde{\epsilon}/3$, for each indexes $(\mathbf{l}, \mathbf{i}) \in U_n^{(1)}$. Therefore, the second layer contains $\left| U_n^{(1)} \right| \left(1 + \left\lceil \sqrt{\frac{3}{2\tilde{\epsilon}}} \log \frac{3}{\epsilon} \right\rceil \right)$ neurons. As shown in Bungartz & Griebel (2004),

$$\left| U_n^{(1)} \right| = \sum_{i=0}^{n-1} 2^i \cdot \binom{d-1+i}{d-1} = (-1)^d + 2^n \sum_{i=0}^{d-1} \binom{n+d-1}{i} (-2)^{d-1-i} = 2^n \cdot \left(\frac{n^{d-1}}{(d-1)!} + \mathcal{O}(n^{d-2}) \right).$$

Therefore, the second layer has $O\left(2^n \frac{n^{d-1}}{(d-1)!} \tilde{\epsilon}^{-\frac{1}{2}} \log \frac{1}{\epsilon} \right)$ neurons. Finally, the output layer computes the weighted sum of the basis functions to approximate $f_n^{(1)}$. Denote by $\hat{f}_n^{(1)}$ the corresponding function of the constructed neural network (see Figure 5), i.e.

$$\hat{f}_n^{(1)} = \sum_{(\mathbf{l}, \mathbf{i}) \in U_n^{(1)}} v_{\mathbf{l}, \mathbf{i}} \cdot \hat{h} \left(\sum_{j=1}^{d} \hat{g}(x_j) \right).$$

Let us analyze the approximation error of our neural network. The proof of Proposition 3.2 shows that the output of the two first layers $h\left(\sum_{j=1}^{d} \hat{g}(\cdot_j) \right)$ approximates $\phi_{\mathbf{l}, \mathbf{i}}$ within $\tilde{\epsilon}$. Therefore, we obtain $\|f_n^{(1)} - \hat{f}_n^{(1)}\|_\infty \le \tilde{\epsilon} \sum_{(\mathbf{l}, \mathbf{i}) \in U_n^{(1)}} |v_{\mathbf{l}, \mathbf{i}}|$. We now use approximation bounds from Theorem 2.2 on $f_n^{(1)}$.

$$\|f - \hat{f}_n^{(1)}\|_\infty \le \|f - f_n^{(1)}\|_\infty + \|f_n^{(1)} - \hat{f}_n^{(1)}\|_\infty \le \frac{2 \cdot |f|_{2,\infty}}{8^d} \cdot 2^{-2n} \cdot A(d, n) + \frac{\epsilon}{2|f|_{2,\infty}} \sum_{(\mathbf{l}, \mathbf{i}) \in U_n^{(1)}} |v_{\mathbf{l}, \mathbf{i}}|,$$

where

$$\sum_{(\mathbf{l}, \mathbf{i}) \in U_n^{(1)}} |v_{\mathbf{l}, \mathbf{i}}| \le |f|_{2,\infty} 2^{-d} \sum_{i \ge 0} 2^{-i} \cdot \binom{d-1+i}{d-1} \le |f|_{2,\infty}.$$

Let us now take $n_\epsilon = \min \left\{ n : \frac{2|f|_{2,\infty}}{8^d} 2^{-2n} A(d, n) \le \frac{\epsilon}{2} \right\}$. Then, using the above inequality shows that the neural network $\hat{f}_{n_\epsilon}^{(1)}$ approximates f within ϵ for the infinity norm. We will now estimate the number of neurons in each layer of this network. Note that

$$n_\epsilon \sim \frac{1}{2 \log 2} \log \frac{1}{\epsilon} \quad \text{and} \quad 2^{n_\epsilon} \le \frac{4}{8^{\frac{d}{2}} (2 \log 2)^{\frac{d-1}{2}} (d-1)!^{\frac{1}{2}}} \sqrt{\frac{|f|_{2,\infty}}{\epsilon}} \left(\log \frac{1}{\epsilon} \right)^{\frac{d-1}{2}} \cdot (1 + \mathcal{O}(1)). \tag{3}$$

We can use the above estimates to show that the constructed neural network has at most N_1 (resp. N_2) neurons on the first (resp. second) layer where

$$N_1 \underset{\epsilon \to 0}{\sim} \frac{8\sqrt{6}d^2}{8^{\frac{d}{2}} (2 \log 2)^{\frac{d-1}{2}} d!^{\frac{1}{2}}} \cdot \frac{|f|_{2,\infty}}{\epsilon} \left(\log \frac{1}{\epsilon} \right)^{\frac{d+1}{2}},$$

$$N_2 \underset{\epsilon \to 0}{\sim} \frac{4\sqrt{3}d^{\frac{3}{2}}}{8^{d/2} (2 \log 2)^{\frac{3(d-1)}{2}} d!^{\frac{3}{2}}} \cdot \frac{|f|_{2,\infty}}{\epsilon} \left(\log \frac{1}{\epsilon} \right)^{\frac{3(d-1)}{2} + 1}.$$

This proves the bound the number of neurons. Finally, to prove the bound on the number of training parameters of the network, notice that the only parameters of the network that depend on the function f are the parameters corresponding to the weighs $v_{l,i}$ of the sparse grid decomposition. This number is $|U_{n_\epsilon}^{(1)}| = \mathcal{O}(2^{n_\epsilon} n_\epsilon^{d-1}) = \mathcal{O}(\epsilon^{-\frac{1}{2}} (\log \frac{1}{\epsilon})^{\frac{3(d-1)}{2}})$.

B.4   Proof of Theorem 3.4: Generalization to general activation functions

We start by formalizing the intuition that a sigmoid-like (resp. ReLU-like) function is a function that resembles the Heaviside (resp. ReLU) function by zooming out along the x (resp. x and y) axis.

Lemma B.6. *Let σ be a sigmoid-like activation with limit a (resp. b) in $-\infty$ (resp.$+\infty$). For any $\delta > 0$ and error tolerance $\epsilon > 0$, there exists a scaling $M > 0$ such that $x \mapsto \frac{\sigma(Mx)}{b-a} - a$ approximates the Heaviside function within ϵ outside of $(-\delta, \delta)$ for the infinity norm. Furthermore, this function has values in $[0, 1]$.*

Let σ be a ReLU-like activation with asymptote $b \cdot x + c$ in $+\infty$. For any $\delta > 0$ and error tolerance $\epsilon > 0$, there exists a scaling $M > 0$ such that $x \mapsto \frac{\sigma(Mx)}{Mb}$ approximates the ReLU function within ϵ for the infinity norm.

Proof. Let $\delta, \epsilon > 0$ and σ a sigmoid-like activation with limit a (resp. b) in $-\infty$ (resp. $+\infty$). There exists $x_0 > 0$ sufficiently large such that $(b-a)|\sigma(x)-a| \leq \epsilon$ for $x \leq -x_0$ and $(b-a)|\sigma(x)-b| \leq \epsilon$ for $x \geq x_0$. It now suffices to take $M := x_0/\delta$ to obtain the desired result.

Now let σ be a ReLU-like activation with oblique asymptote bx in $+\infty$ where $b > 0$. Let M such that $|\sigma| \leq Mb\epsilon$ for $x \leq 0$ and $|\sigma(x) - bx| \leq Mb\epsilon$ for $x \geq 0$. One can check that $|\frac{\sigma(Mx)}{Mb}| \leq \epsilon$ for $x \leq 0$, and $|\frac{\sigma(Mx)}{Mb} - x| \leq \epsilon$ for $x \geq 0$. $\qquad\square$

Using this approximation, we reduce the analysis of sigmoid-like (resp. ReLU-like) activations to the case of a Heaviside (resp ReLU) activation to prove the desired theorem.

Proof of Theorem 3.4   We start by the class of ReLU-like activations. Let σ be a ReLU-like activation function. Lemma B.6 shows that one can approximate arbitrarily well the ReLU activation with a linear map σ. Take the neural network approximator $\hat{f}$ of a target function f given by Theorem 3.1. At each node, we can add the linear map corresponding to $x \mapsto \frac{\sigma(Mx)}{Mb}$ with no additional neuron nor parameter. Because the approximation is continuous, we can take $M > 0$ arbitrarily large in order to approximate $\hat{f}$ with arbitrary precision on the compact $[0, 1]^d$.

The same argument holds for sigmoid-like activation functions in order to reduce the problem to Heaviside activation functions. Although quadratic approximations for univariate functions similar to Lemma B.3 are not valid for general sigmoid-like activations – in particular the Heaviside — we can obtain an analog to Lemma B.2 as Lemma B.7 given in the Appendix B.4.1. This results is an increased number of neurons. In order to approximate a target function $f \in X^{2,\infty}(\Omega)$, we use the same structure as the neural network constructed for ReLU activations and use the same notations as in the proof of Theorem 3.1. The first difference lies in the approximation of $\log \phi_{l_j,i_j}$ in the first layer. Instead of using Corollary B.4, we use Lemma B.7. Therefore, $\frac{12d}{\tilde{\epsilon}} \log \frac{3}{\tilde{\epsilon}}$ neurons are needed to compute a $\tilde{\epsilon}/(3d)$-approximation of $\max(\log \phi_{l_j,i_j}, \log(\tilde{\epsilon}/3))$. The second difference is in the approximation of the exponential in the second layer. Again, we use Lemma B.7 to construct a $\tilde{\epsilon}/3$-approximation of the exponential on $\mathbb{R}_-$ with $\frac{6}{\tilde{\epsilon}}$ neurons for the second layer. As a result, the first layer contains at most $2^{n+2}\frac{3d^2}{\tilde{\epsilon}} \log \frac{1}{\tilde{\epsilon}}$ neurons for ϵ sufficiently small, and the second layer contains $\left|U_n^{(1)}\right| \frac{6}{\tilde{\epsilon}}$ neurons. Using the same estimates as in the proof of Theorem 3.1 shows that the constructed neural network has at most N_1 (resp. N_2) neurons on the first (resp. second) layer where

$$N_1 \underset{\epsilon \to 0}{\sim} \frac{3 \cdot 2^5 \cdot d^{5/2}}{8^{\frac{d}{2}}(2\log 2)^{\frac{d-1}{2}} d!^{\frac{1}{2}}} \frac{|f|_{2,\infty}^{\frac{3}{2}}}{\epsilon^{\frac{3}{2}}} \left(\log \frac{1}{\epsilon}\right)^{\frac{d+1}{2}},$$

$$N_2 \underset{\epsilon \to 0}{\sim} \frac{24 \cdot d^{\frac{3}{2}}}{8^{\frac{d}{2}}(2\log 2)^{\frac{3(d-1)}{2}} d!^{\frac{3}{2}}} \cdot \frac{|f|_{2,\infty}^{\frac{3}{2}}}{\epsilon^{\frac{3}{2}}} \left(\log \frac{1}{\epsilon}\right)^{\frac{3(d-1)}{2}}.$$

This ends the proof.

B.4.1   Proof of Lemma B.7

Lemma B.7. *Let σ be a sigmoid-like activation. Let $f : I \longrightarrow [c, d]$ be a right-continuous increasing function where I is an interval, and let $\epsilon > 0$. There exists a shallow neural network*

with activation σ, with at most $2\frac{d-c}{\epsilon}$ neurons on a single layer, that approximates f within ϵ for the infinity norm.

Proof. The proof is analog to that of Lemma B.2. Let $m = \lfloor \frac{d-c}{\epsilon} \rfloor$. We define a regular subdivision of the image interval $c \leq y_1 \leq \ldots \leq y_m \leq d$ where $y_k = c + k\epsilon$ for $k = 1, \ldots, m$, then using the monotony of f, we can define a subdivision of I, $x_1 \leq \ldots \leq x_m$ such that $x_k := \sup\{x \in I, f(x) \leq y_k\}$. Let us first construct an approximation neural network $\hat{f}$ with the Heaviside activation. Consider

$$\hat{f}(x) := y_1 + \epsilon \sum_{i=1}^{m-1} \mathbf{1}\left(x - \frac{x_i + x_{i+1}}{2} \geq 0\right).$$

Let $x \in [c, d]$ and k such that $x \in [x_k, x_{k+1}]$. We have by monotony $y_k \leq f(x) \leq y_{k+1}$ and $y_k = y_1 + (k-1)\epsilon \leq \hat{f}(x) \leq y_1 + k\epsilon = y_{k+1}$. Hence, $\hat{f}$ approximates f within ϵ in infinity norm.

Let $\delta < \min_{i=1,\ldots,m}(x_{i+1} - x_i)/4$ and σ a general sigmoid-like activation with limits a in $-\infty$ and b in $+\infty$. Take M given by Lemma B.7 such that $\frac{\sigma(Mx)}{b-a} - a$ approximates the Heaviside function within $1/m$ outside of $(-\delta, \delta)$ and has values in $[0, 1]$. Using the same arguments as above, the function

$$\hat{f}(x) := y_1 + \epsilon \sum_{i=1}^{m-1} \frac{\sigma\left(Mx - M\frac{x_i + x_{i+1}}{2}\right)}{b-a} - a$$

approximates f within 2ϵ for the infinity norm. The proof follows. $\qquad\square$

C   PROOFS OF SECTION 4

C.1   PROOF OF THEOREM 4.1: APPROXIMATING KOROBOV FUNCTIONS WITH DEEP NEURAL NETWORKS

Let $\epsilon > 0$. We construct a similar structure to the network defined in Theorem 3.1 by using the sparse grid approximation of Subsection 2.2. For a given n, let $f_n^{(1)}$ be the projection of f in the approximation space $V_n^{(1)}$ (defined in Subsection 2.2) and $U_n^{(1)}$ (defined in equation 2) the set of indices $(\boldsymbol{l}, \boldsymbol{i})$ of basis functions present in $V_n^{(1)}$. Recall $f_n^{(1)}$ can be uniquely decomposed as

$$f_n^{(1)}(\mathbf{x}) = \sum_{(\mathbf{l}, \mathbf{i}) \in U_n^{(1)}} v_{\mathbf{l}, \mathbf{i}} \phi_{\mathbf{l}, \mathbf{i}}(\mathbf{x}).$$

where $\phi_{\boldsymbol{l}, \boldsymbol{i}} = \prod_{j=1}^d \phi_{l_j, i_j}$ are the basis functions defined in Subsection 2.2. In the first layer, we compute exactly the piece-wise linear hat functions ϕ_{l_j, i_j}, then in the next set of layers, we use the product-approximating neural network given by Proposition 4.2 to compute the basis functions $\phi_{\boldsymbol{l}, \boldsymbol{i}} = \prod_{j=1}^d \phi_{l_j, i_j}$ (see Figure 3). The output layer computes the weighted sum $\sum_{(\mathbf{l}, \mathbf{i}) \in U_n^{(1)}} v_{\mathbf{l}, \mathbf{i}} \phi_{\mathbf{l}, \mathbf{i}}(\mathbf{x})$ and outputs $f_n^{(1)}$. Because the approximation has arbitrary precision, we can chose the network of Proposition 4.2 such that the resulting network $\hat{f}$ verifies $\|\hat{f} - f_n^{(1)}\|_\infty \leq \epsilon/2$.

More precisely, as ϕ_{l_j, i_j} is piece-wise linear with four pieces, we can compute it exactly with four neurons with ReLU activation on a single layer (Lemma B.1). Our first layer is composed of the union of all these ReLU neurons, for the $d(2^n - 1)$ indices l_j, i_j such that $1 \leq j \leq d$, $1 \leq l_j \leq n$, $1 \leq i_j \leq 2^{l_j}$ and i_j is odd. Therefore, it contains at most $d2^{n+2}$ neurons with ReLU activation. The second set of layers is composed of the union of product-approximating neural networks to compute $\phi_{\boldsymbol{l}, \boldsymbol{i}}$ for all $(\boldsymbol{l}, \boldsymbol{i}) \in U_n^{(1)}$. This set of layers contains $\lceil \log_2 d \rceil$ layers with activation σ and at most $|U_n^{(1)}| \cdot 8d$ neurons. The output of these two sets of layers is an approximation of the basis functions $\phi_{\boldsymbol{l}, \boldsymbol{i}}$ with arbitrary precision. Consequently, the final output of the complete neural network is an approximation of $f_n^{(1)}$ with arbitrary precision. Similarly to the proof of Theorem 3.1, we can chose the smallest n such that $\|f - f_n^{(1)}\|_\infty \leq \epsilon/2$ (see equation 3 for details). Finally, the network has

Figure 6: Deslaurier-Dubuc interpolets of degree 1, 2 and 3.

depth at most $\log_2 d + 2$ and N neurons where

$$N = 8d|U_{n_\epsilon}^{(1)}| \underset{\epsilon \to 0}{\sim} \frac{2^5 \cdot d^{5/2}}{8^{\frac{d}{2}} (2\log 2)^{\frac{3(d-1)}{2}} d!^{\frac{3}{2}}} \cdot \sqrt{\frac{|f|_{2,\infty}}{\epsilon}} \left(\log \frac{1}{\epsilon}\right)^{\frac{3(d-1)}{2}}.$$

The parameters of the network depending on the function are exactly the coefficients $v_{l,i}$ of the sparse grid approximation. Hence, the network has $\mathcal{O}(\epsilon^{-\frac{1}{2}} (\log \frac{1}{\epsilon})^{\frac{3(d-1)}{2}})$ training parameters.

D   Proofs of Section 5

D.1   Proof of Theorem 5.2: Near-Optimality of Neural Networks for Korobov functions

Our goal is to define an appropriate subspace X_{N+1} in order to get a good lower bound on the Bernstein width $b_N(K)_X$, defined in equation 5, which in turn provides a lower bound on the approximation error (Theorem 5.1).

To do so, we introduce the Deslaurier-Dubuc interpolet $\phi^{(L)} : \mathbb{R} \to \mathbb{R}$. The construction of this function uses an interpolating scheme on binary rationals. First, $\phi^{(L)}$ is defined on all integers $\phi^{(L)}(k) = \mathbb{1}_{k=0}$ for $k \in \mathbb{Z}$. Then, we define the function on half integers $\frac{2k+1}{2}$ by fitting a polynomial of degree $2L - 1$ interpolating the standard hat function ϕ at $k - L + 1, \cdots, k + L$. Iteratively, we define the interpolet on binary rationals of the form $\frac{2k+1}{2^{j+1}}$ from the value of the interpolet on rationals with denominator 2^j. Specifically, let $P_{j,k}^{(L)}$ be the unique polynomial of degree $2L$ interpolating $\phi^{(L)}$ at points $\frac{k'}{2^j}$ for $k' \in \{k - L + 1, \cdots, k + L\}$. We set

$$\phi^{(L)}\left(\frac{2k+1}{2^{j+1}}\right) := P_{j,k}^{(L)}\left(\frac{2k+1}{2^j}\right).$$

For example, for $L = 2$ we get $\phi^{(2)}(\frac{2k+1}{2^{j+1}}) := \frac{9}{16}\phi^{(2)}(\frac{k}{2^j}) + \frac{9}{16}\phi^{(2)}(\frac{k+1}{2^j}) - \frac{1}{16}\phi^{(2)}(\frac{k-2}{2^j}) - \frac{1}{16}\phi^{(2)}(\frac{k+3}{2^j})$. This process defines the interpolet on binary rationals. We then extend the function to the real line by continuity. See Figure 6 for an illustration. Deslauriers & Dubuc (1989) proved that the regularity of the interpolet is an increasing function of L the degree of interpolation. We now prove results in the case $L = 2$.

Lemma D.1. *The interpolet of degree* 2, $\phi^{(2)}$ *is* $\mathcal{C}^2$ *and has support* $Supp\left(\phi^{(2)}\right) = [-3, 3]$.

Proof. See Appendix D.2.1. $\qquad\square$

We will now use the interpolet $\phi^{(2)}$ to construct the subspace X_{N+1}. Using the sparse grids approach, we can construct a hierarchical basis in $X^{2,\infty}(\Omega)$ using the interpolet $\phi^{(2)}$ as mother function. In the remaining of the proof, we will write ϕ instead of $\phi^{(2)}$ for simplicity, and use the

notations and definitions related to sparse grids, introduced in Subsection 2.2. Because $E_N(K)$ is decreasing in N, it suffices to show the result for N_n when we define our space X_{N+1} to be exactly the approximating space $V_n^{(1)}$ of sparse grids $X_{N_n+1} := V_n^{(1)}$. The following equation establishes the relation between n and N_n. In the following, for simplicity, we will write N instead of N_n.

$$N = dim(V_n^{(1)}) - 1 = \sum_{|l|_1 \leq n+d-1} 2^{|l|_1 - 1} - 1 = \sum_{i=0}^{n-1} 2^{i-d} \binom{d-1+i}{d-1} - 1 = 2^n \cdot \left(\frac{n^{d-1}}{(d-1)!} + \mathcal{O}(n^{d-2}) \right).$$

First, let us give some properties about the subspace X_{N+1}.

Proposition D.2. *Let $u \in X_{N+1}$ and write it in decomposed form $u = \sum_{l,i} v_{l,i} \cdot \phi_{l,i}$, where the sum is taken over all multi-indices corresponding to basis functions of X_{N+1}. The coefficients $v_{l,i}$ can be computed in the following way.*

$$v_{l,i} = \left(\prod_{j=1}^{d} I_{l_j, i_j} \right) u =: I_{l,i} u$$

where $I_{l_j, i_j} u = u(\frac{i_j}{2^j}) - \frac{9}{16} u(\frac{i_j-1}{2^j}) - \frac{9}{16} u(\frac{i_j+1}{2^j}) + \frac{1}{16} u(\frac{i_j-3}{2^j}) + \frac{1}{16} u(\frac{i_j+3}{2^j})$. Here, $I_{l,i}$ denotes the d-dimensional stencil which gives a linear combination of values of u at 5^d nodal points.

Proof. See Appendix D.2.2. $\qquad\square$

Note that the stencil representation of the coefficients gives directly $|v_{l,i}| \leq 5^d \|u\|_\infty$. We are now ready to make our estimates. The goal is to compute $\sup\{\rho : \ \rho U(X_{N+1}) \subset K\}$, which will lead to a bound on $b_N(K)_{\mathcal{X}}$. To do so, it suffices to upper bound the Korobov norm by the L^∞ norm for elements of X_{N+1}. In fact, if $\Gamma_d > 0$ satisfies for all $u \in U(X_{N+1})$, $|u|_{X^{2,\infty}} \leq \Gamma_d \|u\|_\infty$, then $b_N(K)_{\mathcal{X}} \geq 1/\Gamma_d$.

Now take $u \in X_{N+1}$ and let us write $u = \sum_{l,i} v_{l,i} \cdot \phi_{l,i}$. Note that basis functions in the same hierarchical class W_l are almost disjoint. More precisely, at each point $x \in \Omega$, at most 3^d basis functions $\phi_{l,i}$ have non-zero contribution to $u(x)$. Therefore, for any $0 \leq \alpha \leq 2 \cdot 1$,

$$\|D^\alpha u\|_\infty \leq \sum_{|l|_1 \leq n+d-1} 3^d \max_{1 \leq i \leq 2^l - 1, \ i \text{ odd}} |v_{l,i}| \cdot 2^{\langle \alpha, l \rangle} \|D^\alpha \phi\|_\infty$$

$$= 60^d |\phi|_{X^{2,\infty}(\Omega)} \|u\|_\infty \cdot \sum_{i=0}^{n-1} 2^{2i} \binom{d-1+i}{d-1}$$

$$= \frac{60^d}{(d-1)!} |\phi|_{X^{2,\infty}(\Omega)} \cdot 2^{2n} \left(n^{d-1} + \mathcal{O}(n^{d-2}) \right) \|u\|_\infty.$$

Finally, denoting by C_d the constant $\frac{60^d}{(d-1)!} |\phi|_{X^{2,\infty}(\Omega)}$, we get for n sufficiently large

$$b_N(K)_{\mathcal{X}} \geq \frac{1}{2C_d} \cdot \frac{1}{2^{2n} \cdot n^{d-1}}.$$

Furthermore, recall $N = \frac{1}{(d-1)!} 2^n \cdot n^{d-1} \cdot \left(1 + O\left(\frac{1}{n}\right) \right)$. Therefore, $n \sim \frac{\log N}{\log 2}$, and $2^n \sim (d-1)! (\log 2)^{d-1} \cdot \frac{N}{(\log N)^{d-1}}$. Finally we obtain for some constant $c_d > 0$,

$$b_N(K)_{\mathcal{X}} \geq c_d \frac{1}{N^2} (\log N)^{d-1}.$$

We conclude by analyzing the minimum number of parameters in order to get an ϵ-approximation of the Korobov unit ball K. Define $n_\epsilon := \min\{n : \ \frac{2}{C_d} \frac{1}{2^{2n} \cdot n^{d-1}} \leq \epsilon\}$. This yields $n_\epsilon \sim \frac{1}{2 \log 2} \log \frac{1}{\epsilon}$, and $2^n \sim \sqrt{\frac{2}{\tilde{C}_d}} (2 \log 2)^{d-1} \frac{1}{\sqrt{\epsilon} \cdot (\log \frac{1}{\epsilon})^{\frac{d-1}{2}}}$. The number of needed parameters to obtain an ϵ approximation K is therefore

$$N_\epsilon \sim \tilde{C}_d \cdot \frac{1}{\sqrt{\epsilon}} \left(\log \frac{1}{\epsilon} \right)^{\frac{d-1}{2}},$$

for some constant $\tilde{C}_d > 0$.

Interestingly, the subspace X_{N+1} our proof uses to show the lower bound is essentially the same as the subspace we use to approximate Koborov functions in our proof of the upper bounds (Theorem 3.1, 4.1). The difference is in the choice of the interpolate ϕ to construct the basis functions, degree 1 for the former, and 2 for the later.

D.2   MISSING PROOFS OF SUBSECTION D.1

D.2.1   PROOF OF LEMMA D.1

Lemma D.3. *The interpolet of degree* 2, $\phi^{(2)}$ *is* $\mathcal{C}^2$ *and has support* $Supp\left(\phi^{(2)}\right) = [-3, 3]$.

Proof. To analyze the regularity of the interpolet, we introduce the trigonometric polynomial

$$P^{(2)}(\theta) := \sum_{k \in \mathbb{Z}} \phi^{(2)}\left(\frac{k}{2}\right) e^{ik\theta} = 1 + \frac{9}{16}(e^{i\theta} + e^{-i\theta}) - \frac{1}{16}(e^{3i\theta} + e^{-3i\theta}).$$

We can write $P^{(2)}(\theta)$ as

$$P^{(2)}(\theta) = \left[\frac{\sin\theta}{\sin\left(\frac{\theta}{2}\right)}\right]^4 \cdot S(\theta),$$

where $S(\theta) = \frac{1}{4} - \frac{1}{16}(e^{i\theta} + e^{-i\theta})$ is a trigonometric polynomial of degree 1. Deslaurier and Dubuc (Deslauriers & Dubuc, 1989, Theorem 7.11) showed that the interpolet $\phi^{(2)}$ has regularity $\left\lfloor -\frac{\log r}{\log 2} \right\rfloor$ where r is the spectral radius of the matrix $B := [s_{j-2k}]_{-1 \leq j,k \leq 1}$ where s_j are the coefficients of the trigonometric polynomial $S(\theta)$. In our case, matrix B writes

$$B = \begin{pmatrix} -1/16 & -1/16 & 0 \\ 0 & 1/4 & 0 \\ 0 & -1/16 & -1/16 \end{pmatrix},$$

and has spectral radius $r = 1/4$. Therefore, the regularity of $\phi^{(2)}$ is at least $\left\lfloor -\frac{\log r}{\log 2} \right\rfloor = 2$. For the support, one can check that more generally $Supp(\phi^{(L)}) = [-2L + 1, 2L - 1]$. $\qquad \square$

D.2.2   PROOF OF PROPOSITION D.2

Proposition D.4. *Let* $u \in X_{N+1}$ *and write it in decomposed form* $u = \sum_{l,i} v_{l,i} \cdot \phi_{l,i}$, *where the sum is taken over all multi-indices corresponding to basis functions of* X_{N+1}. *The coefficients* $v_{l,i}$ *can be computed in the following way.*

$$v_{l,i} = \left(\prod_{j=1}^{d} I_{l_j, i_j}\right) u =: I_{l,i} u$$

where $I_{l_j, i_j} u = u(\frac{i_j}{2^j}) - \frac{9}{16} u(\frac{i_j-1}{2^j}) - \frac{9}{16} u(\frac{i_j+1}{2^j}) + \frac{1}{16} u(\frac{i_j-3}{2^j}) + \frac{1}{16} u(\frac{i_j+3}{2^j})$. *Here,* $I_{l,i}$ *denotes the d-dimensional stencil which gives a linear combination of values of* u *at* 5^d *nodal points.*

Proof. We start by looking at the 1-dimensional case. One can check that $I_{l,i}\phi_{\tilde{l},\tilde{i}} = \mathbf{1}_{\tilde{l}=l,\tilde{i}=i}$. Indeed, if $\tilde{l} > l$ of if $\tilde{l} = l$ and $\tilde{i} \neq i$, then $\phi_{\tilde{l},\tilde{i}}$ will be zero at the nodal values of $I_{l,i}$. Further, if $\tilde{l} < l$ the iterative construction of ϕ gives directly.

$$\phi_{\tilde{l},\tilde{i}}\left(\frac{i}{2^j}\right) = \frac{9}{16}\phi_{\tilde{l},\tilde{i}}\left(\frac{i+1}{2^j}\right) + \frac{9}{16}\phi_{\tilde{l},\tilde{i}}\left(\frac{i-1}{2^j}\right) - \frac{1}{16}\phi_{\tilde{l},\tilde{i}}\left(\frac{i+3}{2^j}\right) - \frac{1}{16}\phi_{\tilde{l},\tilde{i}}\left(\frac{i-3}{2^j}\right).$$

Therefore, we obtain $I_{l,i}\phi_{\tilde{l},\tilde{i}} = 0$. Finally, $I_{l,i}u = \sum_{\tilde{l},\tilde{i}} v_{\tilde{l},\tilde{i}} \cdot I_{l,i}\phi_{\tilde{l},\tilde{i}} = v_{l,i} \cdot I_{l,i}\phi_{l,i} = v_{l,i}$. This proves the stencil representation of $v_{l,i}$ for dimension 1. Finally, using the tensor product approach of the stencil operator $I_{l,i}$ we can generalize the formula to general dimensions. $\qquad \square$

E   SUBMISSION OF CONFERENCE PAPERS TO ICLR 2022

ICLR requires electronic submissions, processed by `https://openreview.net/`. See ICLR's website for more instructions.

If your paper is ultimately accepted, the statement `\iclrfinalcopy` should be inserted to adjust the format to the camera ready requirements.

The format for the submissions is a variant of the NeurIPS format. Please read carefully the instructions below, and follow them faithfully.

E.1   STYLE

Papers to be submitted to ICLR 2022 must be prepared according to the instructions presented here.

Authors are required to use the ICLR LATEX style files obtainable at the ICLR website. Please make sure you use the current files and not previous versions. Tweaking the style files may be grounds for rejection.

E.2   RETRIEVAL OF STYLE FILES

The style files for ICLR and other conference information are available online at:

$$\text{http://www.iclr.cc/}$$

The file `iclr2022_conference.pdf` contains these instructions and illustrates the various formatting requirements your ICLR paper must satisfy. Submissions must be made using LATEX and the style files `iclr2022_conference.sty` and `iclr2022_conference.bst` (to be used with LATEX2e). The file `iclr2022_conference.tex` may be used as a "shell" for writing your paper. All you have to do is replace the author, title, abstract, and text of the paper with your own.

The formatting instructions contained in these style files are summarized in sections F, G, and H below.

F   GENERAL FORMATTING INSTRUCTIONS

The text must be confined within a rectangle 5.5 inches (33 picas) wide and 9 inches (54 picas) long. The left margin is 1.5 inch (9 picas). Use 10 point type with a vertical spacing of 11 points. Times New Roman is the preferred typeface throughout. Paragraphs are separated by 1/2 line space, with no indentation.

Paper title is 17 point, in small caps and left-aligned. All pages should start at 1 inch (6 picas) from the top of the page.

Authors' names are set in boldface, and each name is placed above its corresponding address. The lead author's name is to be listed first, and the co-authors' names are set to follow. Authors sharing the same address can be on the same line.

Please pay special attention to the instructions in section H regarding figures, tables, acknowledgments, and references.

There will be a strict upper limit of 9 pages for the main text of the initial submission, with unlimited additional pages for citations.

G   HEADINGS: FIRST LEVEL

First level headings are in small caps, flush left and in point size 12. One line space before the first level heading and 1/2 line space after the first level heading.

G.1 Headings: second level

Second level headings are in small caps, flush left and in point size 10. One line space before the second level heading and 1/2 line space after the second level heading.

G.1.1 Headings: third level

Third level headings are in small caps, flush left and in point size 10. One line space before the third level heading and 1/2 line space after the third level heading.

H Citations, figures, tables, references

These instructions apply to everyone, regardless of the formatter being used.

H.1 Citations within the text

Citations within the text should be based on the `natbib` package and include the authors' last names and year (with the "et al." construct for more than two authors). When the authors or the publication are included in the sentence, the citation should not be in parenthesis using `\citet{}` (as in "See **?** for more information."). Otherwise, the citation should be in parenthesis using `\citep{}` (as in "Deep learning shows promise to make progress towards AI (**?**).").

The corresponding references are to be listed in alphabetical order of authors, in the REFERENCES section. As to the format of the references themselves, any style is acceptable as long as it is used consistently.

H.2 Footnotes

Indicate footnotes with a number[1] in the text. Place the footnotes at the bottom of the page on which they appear. Precede the footnote with a horizontal rule of 2 inches (12 picas).[2]

H.3 Figures

All artwork must be neat, clean, and legible. Lines should be dark enough for purposes of reproduction; art work should not be hand-drawn. The figure number and caption always appear after the figure. Place one line space before the figure caption, and one line space after the figure. The figure caption is lower case (except for first word and proper nouns); figures are numbered consecutively.

Make sure the figure caption does not get separated from the figure. Leave sufficient space to avoid splitting the figure and figure caption.

You may use color figures. However, it is best for the figure captions and the paper body to make sense if the paper is printed either in black/white or in color.

H.4 Tables

All tables must be centered, neat, clean and legible. Do not use hand-drawn tables. The table number and title always appear before the table. See Table 2.

Place one line space before the table title, one line space after the table title, and one line space after the table. The table title must be lower case (except for first word and proper nouns); tables are numbered consecutively.

I Default Notation

In an attempt to encourage standardized notation, we have included the notation file from the textbook, *Deep Learning* **?** available at `https://github.com/goodfeli/dlbook_`

---

[1] Sample of the first footnote

[2] Sample of the second footnote

Figure 7: Sample figure caption.

Table 2: Sample table title

PART	DESCRIPTION
Dendrite	Input terminal
Axon	Output terminal
Soma	Cell body (contains cell nucleus)

`notation/`. Use of this style is not required and can be disabled by commenting out `math_commands.tex`.

Numbers and Arrays

a	A scalar (integer or real)
$\boldsymbol{a}$	A vector
$\boldsymbol{A}$	A matrix
$\mathbf{A}$	A tensor
$\boldsymbol{I}_n$	Identity matrix with n rows and n columns
$\boldsymbol{I}$	Identity matrix with dimensionality implied by context
$\boldsymbol{e}^{(i)}$	Standard basis vector $[0, \ldots, 0, 1, 0, \ldots, 0]$ with a 1 at position i
$\mathrm{diag}(\boldsymbol{a})$	A square, diagonal matrix with diagonal entries given by $\boldsymbol{a}$
a	A scalar random variable
$\mathbf{a}$	A vector-valued random variable
$\mathbf{A}$	A matrix-valued random variable

Sets and Graphs

$\mathbb{A}$	A set
$\mathbb{R}$	The set of real numbers
$\{0, 1\}$	The set containing 0 and 1
$\{0, 1, \dots, n\}$	The set of all integers between 0 and n
$[a, b]$	The real interval including a and b
$(a, b]$	The real interval excluding a but including b
$\mathbb{A} \backslash \mathbb{B}$	Set subtraction, i.e., the set containing the elements of $\mathbb{A}$ that are not in $\mathbb{B}$
$\mathcal{G}$	A graph
$Pa_{\mathcal{G}}(\mathrm{x}_i)$	The parents of x_i in $\mathcal{G}$

Indexing

a_i	Element i of vector $\boldsymbol{a}$, with indexing starting at 1
a_{-i}	All elements of vector $\boldsymbol{a}$ except for element i
$A_{i,j}$	Element i, j of matrix $\boldsymbol{A}$
$\boldsymbol{A}_{i,:}$	Row i of matrix $\boldsymbol{A}$
$\boldsymbol{A}_{:,i}$	Column i of matrix $\boldsymbol{A}$
$\mathsf{A}_{i,j,k}$	Element (i, j, k) of a 3-D tensor A
$\mathsf{A}_{:,:,i}$	2-D slice of a 3-D tensor
a_i	Element i of the random vector a

Calculus

$\dfrac{dy}{dx}$	Derivative of y with respect to x
$\dfrac{\partial y}{\partial x}$	Partial derivative of y with respect to x
$\nabla_{\boldsymbol{x}} y$	Gradient of y with respect to $\boldsymbol{x}$
$\nabla_{\boldsymbol{X}} y$	Matrix derivatives of y with respect to $\boldsymbol{X}$
$\nabla_{\mathsf{X}} y$	Tensor containing derivatives of y with respect to X
$\dfrac{\partial f}{\partial \boldsymbol{x}}$	Jacobian matrix $\boldsymbol{J} \in \mathbb{R}^{m \times n}$ of $f : \mathbb{R}^n \to \mathbb{R}^m$
$\nabla_{\boldsymbol{x}}^2 f(\boldsymbol{x})$ or $\boldsymbol{H}(f)(\boldsymbol{x})$	The Hessian matrix of f at input point $\boldsymbol{x}$
$\displaystyle\int f(\boldsymbol{x}) d\boldsymbol{x}$	Definite integral over the entire domain of $\boldsymbol{x}$
$\displaystyle\int_{\mathbb{S}} f(\boldsymbol{x}) d\boldsymbol{x}$	Definite integral with respect to $\boldsymbol{x}$ over the set $\mathbb{S}$

Probability and Information Theory

$P(\mathrm{a})$	A probability distribution over a discrete variable
$p(\mathrm{a})$	A probability distribution over a continuous variable, or over a variable whose type has not been specified
$\mathrm{a} \sim P$	Random variable a has distribution P
$\mathbb{E}_{\mathrm{x} \sim P}[f(x)]$ or $\mathbb{E} f(x)$	Expectation of $f(x)$ with respect to $P(\mathrm{x})$
$\mathrm{Var}(f(x))$	Variance of $f(x)$ under $P(\mathrm{x})$
$\mathrm{Cov}(f(x), g(x))$	Covariance of $f(x)$ and $g(x)$ under $P(\mathrm{x})$
$H(\mathrm{x})$	Shannon entropy of the random variable x
$D_{\mathrm{KL}}(P\|Q)$	Kullback-Leibler divergence of P and Q
$\mathcal{N}(\boldsymbol{x}; \boldsymbol{\mu}, \boldsymbol{\Sigma})$	Gaussian distribution over $\boldsymbol{x}$ with mean $\boldsymbol{\mu}$ and covariance $\boldsymbol{\Sigma}$

Functions

$f : \mathbb{A} \to \mathbb{B}$	The function f with domain $\mathbb{A}$ and range $\mathbb{B}$
$f \circ g$	Composition of the functions f and g
$f(\boldsymbol{x}; \boldsymbol{\theta})$	A function of $\boldsymbol{x}$ parametrized by $\boldsymbol{\theta}$. (Sometimes we write $f(\boldsymbol{x})$ and omit the argument $\boldsymbol{\theta}$ to lighten notation)
$\log x$	Natural logarithm of x
$\sigma(x)$	Logistic sigmoid, $\dfrac{1}{1 + \exp(-x)}$
$\zeta(x)$	Softplus, $\log(1 + \exp(x))$
$\|\boldsymbol{x}\|_p$	L^p norm of $\boldsymbol{x}$
$\|\boldsymbol{x}\|$	L^2 norm of $\boldsymbol{x}$
x^+	Positive part of x, i.e., $\max(0, x)$
$\mathbf{1}_{\mathrm{condition}}$	is 1 if the condition is true, 0 otherwise

J   FINAL INSTRUCTIONS

Do not change any aspects of the formatting parameters in the style files. In particular, do not modify the width or length of the rectangle the text should fit into, and do not change font sizes (except perhaps in the REFERENCES section; see below). Please note that pages should be numbered.

K   PREPARING POSTSCRIPT OR PDF FILES

Please prepare PostScript or PDF files with paper size "US Letter", and not, for example, "A4". The -t letter option on dvips will produce US Letter files.

Consider directly generating PDF files using `pdflatex` (especially if you are a MiKTeX user). PDF figures must be substituted for EPS figures, however.

Otherwise, please generate your PostScript and PDF files with the following commands:

```
dvips mypaper.dvi -t letter -Ppdf -G0 -o mypaper.ps
ps2pdf mypaper.ps mypaper.pdf
```

K.1   MARGINS IN LATEX

Most of the margin problems come from figures positioned by hand using `\special` or other commands. We suggest using the command `\includegraphics` from the graphicx package.

Always specify the figure width as a multiple of the line width as in the example below using .eps graphics

```
\usepackage[dvips]{graphicx} ...
\includegraphics[width=0.8\linewidth]{myfile.eps}
```

or

```
\usepackage[pdftex]{graphicx} ...
\includegraphics[width=0.8\linewidth]{myfile.pdf}
```

for .pdf graphics. See section 4.4 in the graphics bundle documentation (`http://www.ctan.org/tex-archive/macros/latex/required/graphics/grfguide.ps`)

A number of width problems arise when LaTeX cannot properly hyphenate a line. Please give LaTeX hyphenation hints using the `\-` command.

AUTHOR CONTRIBUTIONS

If you'd like to, you may include a section for author contributions as is done in many journals. This is optional and at the discretion of the authors.

ACKNOWLEDGMENTS

Use unnumbered third level headings for the acknowledgments. All acknowledgments, including those to funding agencies, go at the end of the paper.

A   APPENDIX

You may include other additional sections here.