A Reparametrization-Invariant Sharpness Measure Based on Information Geometry

Abstract

It has been observed that the generalization performance of neural networks correlates with the sharpness of their loss landscape. Dinh et al (2017) [8] have observed that existing formulations of sharpness measures fail to be invariant with respect to scaling and reparametrization. While some scale-invariant measures have recently been proposed, reparametrization-invariant measures are still lacking, as are any theoretical insights into generalization performance. Based on an information geometric analysis of the neural network parameter space, in this paper we propose a reparametrization-invariant sharpness measure that captures the change in loss with respect to changes in the probability distribution modeled by neural networks, rather than with respect to changes in the parameter values. We reveal some theoretical connections of our measure to generalization performance. In particular, experiments confirm that using our measure as a regularizer in neural network training significantly improves performance.

1 Introduction

From recent discoveries in deep learning, it has been conjectured that the generalization performance of neural networks correlates with the sharpness of their loss landscape. In particular, lower generalization performance of large-batch training of stochastic gradient descent (SGD) has been attributed to its convergence to sharper minima [22, 48], and several optimization methods have shown better generalization performance by actively finding solutions with lower sharpness [7, 19, 4, 42, 12, 24]. Minimum description length (MDL)-based arguments [16, 17] and the generalization upper bound of the PAC-Bayes theory for neural networks [10] also suggest that the flatter the loss landscape, the better the generalization performance. Furthermore, in [21, 31], measures based on the sharpness concept show better performance in predicting the generalization performance of models among various generalization measures considered in the past including the margin [5] and norm [33, 32].

Various masures for sharpness and flatness have been proposed in the literature. [17] propose the concept of 'flat minima,' in which the flatness of a minimum is interpreted as the volume of the connected region in the parameter space over which the loss has approximately similar values. Similarly, the sharpness has often been measured by the maximum loss value (inside a Euclidean ball) near the minimum [22] or by the spectral norm of the Hessian at the minimum [48].

The above definitions of sharpness have some notable critical flaws. [8] point out that certain reparametrizations and parameter scalings (for example, with ReLU activation functions in the case of neural networks [30]) may have no effect on the model output or overall generalization performance, and yet lead to wildly different values of sharpness. Other sharpness measures designed to address the lack of scale-invariance have been proposed [26, 45, 39, 38], but these measures fail to be invariant with respect to reparametrizations; Section 5 of [8] offers several nonlinear

reparametrization examples. The connections between sharpness and generalization performance also remain elusive.

In this paper we address the lack of scale- and reparametrization-invariance of existing sharpness measures, as well as their inability to explain generalization performance of deep learning networks. Our approach rests on the observation and insight that sharpness should be measured taking into proper account the geometry of the underlying parameter space. For this purpose we draw upon tools from information geometry, paying attention to the fact that in most classification problems, probabilistic classification models are parametrized in terms of neural networks. In information geometry, the Fisher information matrix (FIM) serves as a natural Riemannian metric for the parameter space [3] and allows for measuring the change in probability density with respect changes in the parameter values.

The eigenspectra of the FIM of a neural network are observed to have a small number of positive outliers (the number is usually equated with the number of classes) and the bulk consisting of small eigenvalues [40, 36, 35, 47, 14]. This observation indicates that the number of principal varying components of the probability densities modeled by neural networks are significantly less compared to the number of parameters. Therefore, identically weighting every possible parameter change direction in the parameter space – that is, applying Euclidean geometry – can be problematic, since it places too much weight on parameter change directions that are meaningless with respect to changes in the probabilistic model, or equivalently, not enough weight is placed along meaningful directions.

We argue that one should consider these implications and use the change in probabilistic models as a 'ruler' when defining a sharpness measure of neural network loss landscapes that does not depend on how the model is parametrized.

Building on the above geometric analysis of the neural network parameter space, in this paper we propose a new sharpness measure based on information geometry. This measure is by definition reparametrization-invariant. Additionally, we show that this sharpness measure simultaneously satisfies various types of scale invariance for neural networks with ReLU activation functions, since it is invariant for parameter transforms that do not change the model output. Hence our measure is free from all the reparametrization- and scale-invariance issues of previous sharpness measures raised by [8].

As a second contribution of this paper, we also show that our geometric sharpness measure sheds important insight on generalization performance. As detailed in Section 3, when the FIM is replaced with the Hessian in our measure, the measure is in a form similar to Takeuchi's information criterion (TIC), which is a quantity that predicts the bias of the likelihood value calculated at the maximum likelihood estimates [43]. TIC for neural networks has been shown to have a strong correlation with the generalization gap in [44]. One can apply the same argument to our measure since the FIM can be approximated by the Hessian under mild conditions for deep neural networks [28]. In addition, we show that our measure can be linked to generalization in another geometrical way. The measure is associated with a margin defined in an information geometric sense, enabling the interpretation that a smaller sharpness measure indicates larger margins. We demonstrate experimentally that using our measure as a regularizer to train neural networks can significantly improve generalization performance.

Our contributions can be summarized as follows:

- We provide an information geometric analysis of the neural network parameter space by investigating the eigensubspace of the Fisher information matrix (FIM) of neural networks.

- We propose a reparametrization- and scale-invariant sharpness measure based on information geometry that is free from the problems of existing sharpness measures posed by [8]), and discuss the relation between the measure and generalization performance.

- We use the proposed measure as a regularizer when training neural networks, and demonstrate improved generalization performance.

We provide an information geometric analysis of the neural network parameter space in Section 2. Building on this analysis, Section 3 presents our reparametrization-invariant sharpness measure based on information geometry and connects the proposed measure to generalization. In Section 4, we perform numerical experiments using our measure as a regularizer to improve generalization performance in neural network training.

2 An information geometric analysis of the neural network parameter space

In this paper, we focus on the probabilistic classification models parametrized by neural networks. Let $x \in \mathbb{R}^D$ denote data, and $y \in \{1, \ldots, C\}$ denote class labels with C as the number of classes. Let $p(x, y)$ and $p(y|x; \theta)$ respectively denote the data generating distribution and the parametric model of the probability density of classes given data. Here the parameter $\theta \in \mathbb{R}^m$ is the set of all the weight and bias parameters of neural networks. We consider a neural network as a function $f(\cdot; \theta) : \mathbb{R}^D \to \mathbb{R}^C, x \mapsto f(x; \theta) = (f_1(x; \theta), \ldots, f_C(x; \theta))^\top$, where $f_j(\cdot; \theta) : \mathbb{R}^D \to \mathbb{R}$ is a function that returns the j-th logit for $j = 1, \ldots, C$. Our parametric model is then represented as $p(y|x; \theta) = \frac{\exp(f_y(x))}{\sum_j \exp(f_j(x))}$, and we denote the negative log-likelihood by $l(y, f(x; \theta)) = -\log p(y|x; \theta)$.

Suppose data $\{(x_1, y_1), \ldots, (x_N, y_N)\}$ are drawn i.i.d. from the data generating distribution $p(x, y)$. The cross-entropy loss, our training objective function throughout the paper, can be written as follows:

$$\mathcal{L}(\theta) = \frac{1}{N} \sum_{i=1}^{N} l_i(\theta), \tag{1}$$

where $l_i(\theta) = l(y_i, f(x_i; \theta)) = -\log p(y_i|x_i; \theta)$.

2.1 The Fisher information matrix (FIM)

The Fisher information matrix (FIM) for the family of probability density functions $p(x, y; \theta) = p(x)p(y|x; \theta)$ parametrized by the neural network parameters θ is defined as

$$F(\theta) = \mathbb{E}_{p(x)} \left[\mathbb{E}_{p(y|x; \theta)} \left[\left(\frac{\partial l}{\partial \theta} \right)^\top \left(\frac{\partial l}{\partial \theta} \right) \right] \right] = \mathbb{E}_{p(x)} \left[J(x)^\top \mathbb{E}_{p(y|x; \theta)} \left[\left(\frac{\partial l}{\partial f} \right)^\top \left(\frac{\partial l}{\partial f} \right) \right] J(x) \right]$$

$$= \frac{1}{N} \sum_{i=1}^{N} J_i^\top \left(\mathrm{diag}(p_i) - p_i p_i^\top \right) J_i, \tag{2}$$

where the dependence of $l(y, f(x; \theta))$ to $y, f(x; \theta)$ is omitted for simplicity and $J(x) = \frac{\partial f}{\partial \theta}(x) \in \mathbb{R}^{C \times m}$ is the Jacobian of the logits with respect to the parameters. In deriving (2), the expectation with respect to $p(x)$ is approximated by the finite sum over data points $x_1, \ldots, x_N$ drawn i.i.d. from $p(x)$, $J_i = J(x_i)$, and we use the fact that $\mathbb{E}_{p(y|x_i; \theta)} \left[\left(\frac{\partial l}{\partial f} \right)^\top \left(\frac{\partial l}{\partial f} \right) \right] = \mathrm{diag}(p_i) - p_i p_i^\top$, where $p_i = (p(1|x_i; \theta), \ldots, p(C|x_i; \theta))^\top \in \mathbb{R}^C$ is the model's prediction on the probability that x_i belongs to each class and $\mathrm{diag}(p_i) \in \mathbb{R}^{C \times C}$ is a diagonal matrix whose (j, j) entry is $(p_i)_j$.

In this paper, among many of the important properties and applications of the FIM (e.g., being the Cramer-Rao lower bound of estimator variances in estimation theory and statistics), we focus on the fact that the FIM can serve as a metric to measure the distance between the parametric probability density models in information geometry. Differential geometrically speaking, the FIM acts as a natural Riemannian metric on the statistical manifold, a space where the family of probability densities modeled with smoothly varying parameters $\theta \in \mathbb{R}^m$ is gathered.[1] The FIM makes it possible to measure geometric quantities such as length, angle, and volume on the manifold. (We refer the reader to [6, 11] for the backgrounds on the Riemannian manifolds and differential geometry, and [3, 34, 28] for those on the information geometry and the Fisher information matrix.) Note that when the FIM is not full-rank, e.g., in the case of overparameterized neural networks with $m \gg N$, the FIM can be used as a pseudo metric.

The FIM is closely related to the KL-divergence, which is frequently used as an information theoretic measure of discrepancy between probability density functions. The KL-divergence between two probability density functions with infinitesimal parameter difference $d\theta \in \mathbb{R}^m$ can be approximated as

$$\mathrm{KL}(p(x, y; \theta + d\theta) || p(x, y; \theta)) \approx \frac{1}{2} d\theta^\top F(\theta) d\theta. \tag{3}$$

---

[1]Note that the family of probabilistic models from neural networks is usually not a manifold in a mathematically rigorous sense due to the inherent singularities in the neural network parameter space (see Section 12.2 of [3]), but this fact is not crucial for our discussion.

(a) Top 20 eigenvalues of $F(\theta)$

(b) Perturbed decision boundaries from $\Delta\theta_1$

(c) Perturbed decision boundaries from $\Delta\theta_2$

(d) Perturbed decision boundaries from $\Delta\theta_{10}$

Figure 1: A synthetic three-class classification example. For (b)-(d), the black, red, and blue lines correspond to decision boundaries of the neural network with the trained parameters, and parameters perturbed along the k-th eigenvector $\Delta\theta_k \in \mathbb{R}^m$ (associated with the k-th eigenvalue) of $F(\theta)$ with steps of 0.5 and -0.5, respectively.

2.2 An analysis of the eigensubspace of the FIM

This section discusses the characteristics of the eigensubspace of FIM of neural networks. In the analysis of the eigenspectra of deep neural network Hessians of [36], the FIM in (2) has been decomposed as follows:

$$F(\theta) = \frac{1}{N} \sum_{i=1}^{N} J_i^\top \left(\mathrm{diag}(p_i) - p_i p_i^\top \right) J_i = \frac{1}{N} \sum_{i=1}^{N} J_i^\top M_i^\top M_i J_i, \qquad (4)$$

where $M_i = \mathrm{diag}(\sqrt{p_i}) \left(I - \mathbb{1} p_i^\top \right) \in \mathbb{R}^{C \times C}$, $\sqrt{p_i} = (\sqrt{(p_i)_1}, \ldots, \sqrt{(p_i)_C})^\top \in \mathbb{R}^C$, and $\mathbb{1} = (1, \ldots, 1)^\top \in \mathbb{R}^C$ is a vector whose elements are all one.

According to the decomposition, the FIM can be thought of as a non-centralized second moment of the (modified) logit gradients, i.e., each row of $M_i J_i \in \mathbb{R}^{C \times m}$ whose j-th row vector is represented as

$$(M_i J_i)_{j:}^\top = \sqrt{(p_i)_j} \cdot \left((J_{i,j})^\top - \sum_{j'=1}^{C} (p_i)_{j'} (J_{i,j'})^\top \right) \in \mathbb{R}^m, \qquad (5)$$

where $J_{i,j} \in \mathbb{R}^{1 \times m}$ is the j-th row of J_i. It has been observed that these logit gradients form a kind of hierarchical structure after sufficient training. In the observation from [35], the gradients of the $c' \neq c$-th logit calculated from the data in class c are gathered to form a cluster. A matrix obtained from averaging the outer products of the averaged logit gradients belonging to each cluster is then attributed to the outliers of the eigenspectra, and the outliers of the eigenvalues appear as much as the number of classes. That is, the principal eigenvalues of the FIM (and possibly the eigenvectors) can be closely connected with distinguishing each class c from the rest of the $c' \neq c$ classes (as can be implied from averaging (5) for $j \neq c$ and by assuming $(p_i)_c \approx 1$). This becomes more evident in Appendix A, which assumes the prediction is balanced as $(p_i)_{c'} = \epsilon$ for all $c' \neq c$ with $\epsilon \ll 1$.

In order to more intuitively understand the characteristics of the eigensubspace of FIM implied from the above analysis, we provide a classification example for two-dimensional synthetic data generated from mixtures of three Gaussians in Figure 1. We trained a three-layer fully connected neural network with 70-dimensional hidden units (the number of parameters = 5,393).

In Figure 1 (a) are the top twenty eigenvalues of the FIM of the trained neural network. Note that there are few outliers among the eigenvalues in the entire 5,393-dimensional parameter space, with the remainder being almost 0. The eigenvalues indicate the rate of change of the probability density (modeled by the neural network) measured by the KL-divergence for a unit change of parameters along the corresponding eigenvectors. The existence of a few outliers means that the density change mainly occurs in only a few specific directions and that the amount of change in probability density can vary significantly according to the direction of the parameter change.

This fact can also be observed in decision boundaries obtained from neural networks with the parameters perturbed along some eigenvectors shown in Figure 1 (b-d). When perturbing the parameters along the principal eigenvectors, a significant change appears in the decision boundary, increasing or decreasing the margin of certain classes. On the other hand, for eigenvectors with small eigenvalues,

it can be seen that there is almost no change in the decision boundary according to the same level of change in parameters (in the Euclidean sense).

These examples imply that it would be more meaningful to reflect the different influences on the probabilistic model according to the change direction when we measure the quantities concerning the parameter change, e.g., the sharpness of the loss landscape. By reflecting on these implications and using the unit change in probability distribution modeled by neural networks as our 'ruler' to measure the sharpness, that is, applying the information geometry, the following section presents a sharpness measure that does not rely on how the model is parametrized.

3 An information geometric sharpness measure

Based on the above analysis, we define an information geometric sharpness (IGS) measure as follows:

$$\text{IGS}(\theta) = \frac{1}{N} \sum_{i=1}^{N} \left(\frac{\partial l_i}{\partial \theta} \right) F(\theta)^\dagger \left(\frac{\partial l_i}{\partial \theta} \right)^\top, \tag{6}$$

where $F(\theta)^\dagger \in \mathbb{R}^{m \times m}$ is the pseudo-inverse of $F(\theta)$ and $l_i = l(y_i, f(x_i; \theta))$ is the cross-entropy loss evaluated at the i-th data (x_i, y_i).

Our sharpness measure in (6) is an intrinsic quantity, i.e., coordinate-invariant (in differential geometric terms). To see why, observe that under a local coordinate transformations $\phi : \mathbb{R}^m \to \mathbb{R}^m$, $\theta \mapsto \theta' = \phi(\theta)$, F and $\left(\frac{\partial l_i}{\partial \theta} \right)$ transform according to the following rules: (i) $F \mapsto F' = \Phi^{-\top} F \Phi^{-1}$, where $\Phi = \frac{\partial \phi}{\partial \theta} \in \mathbb{R}^{m \times m}$; (ii) $\left(\frac{\partial l_i}{\partial \theta} \right) \mapsto \left(\frac{\partial l_i}{\partial \theta'} \right) = \left(\frac{\partial l_i}{\partial \theta} \right) \Phi^{-1}$, where it can be verified that the $\left(\frac{\partial l_i}{\partial \theta} \right) F(\theta)^\dagger \left(\frac{\partial l_i}{\partial \theta} \right)^\top$ remains the same. Since the above measure gives the same value regardless of which parametrization (e.g., θ or θ') the statistical model is parametrized, it is free from the reparametrization-variant issues raised in [8].

Our measure evaluates the squared norm of the loss gradients calculated at each data point using the (pseudo-inverse of) FIM and averages them for all data points. Since $\left(\frac{\partial l_i}{\partial \theta} \right)^\top \in \mathbb{R}^m$ belongs to the span of the eigenvectors of $F(\theta)$ with non-zero eigenvalues, our sharpness measure is well-defined in the sense that there are not any components of $\left(\frac{\partial l_i}{\partial \theta} \right)$ neglected in measuring its information geometric norm (we elaborate on this in Appendix B). The reason for defining the sharpness measure as in (6) will be evident in Section 3.3 where we develop the relationship between our measure and the generalization.

We can also define various measures that are reparametrization-invariant using the FIM, not only the one in (6) but also ones that measure the norm of the gradients of the entire loss or the mini-batch losses. For mini-batches of size b, the corresponding measure can be defined as follows:

$$\text{IGS}_b(\theta) = \mathbb{E}_{p(B)} \left[\left(\frac{1}{b} \sum_{x_i \in B} \frac{\partial l_i}{\partial \theta} \right) F(\theta)^\dagger \left(\frac{1}{b} \sum_{x_i \in B} \frac{\partial l_i}{\partial \theta} \right)^\top \right], \tag{7}$$

where $\mathbb{E}_{p(B)}[\cdot]$ denotes the expectation with respect to some distribution $p(B)$ of mini-batches $B \subset \{x_1, \ldots, x_N\}$ of size $|B| = b$. We discuss the relation between (6) and (7) in Appendix C. Note that this definition can be linked to the concept of m-sharpness, which measures the sharpness of the loss landscape by averaging the sharpness of mini-batch losses and show a better correlation to the generalization as the batch size reduces [12].

3.1 Transformation invariance

Neural networks composed of activation functions such as ReLU and leaky ReLU possess scale-invariant properties. In the case of layer-wise scaling, for consecutive layers of linear transforms and ReLU, e.g., $f(x; \{W_1, \ldots, W_L\}) = W_L \cdot \text{ReLU}(W_{L-1} \cdots \text{ReLU}(W_1 x))$, where $W_l \in \mathbb{R}^{d_l \times d_{l-1}}$ for $l = 1, \ldots, L$ with $d_0 = D$ and $d_L = C$, if each weight W_l is multiplied by a constant $c_l > 0$ and the constants satisfy $\prod_{l=1}^{L} c_l = 1$, there is no change in the outputs of the neural network under the same input values. A similar concept includes the node-wise scaling, multiplying weights entering a node (or a hidden variable in neural networks) by a positive constant, and dividing weights out of the node by the same constant.

Figure 2: The ratio of sharpness measures evaluated for the reparametrized models to those for the original models ($\frac{\text{Sharpness (re.)}}{\text{Sharpness (ori.)}}$). Note that the y-axis is in the log scale. For the nonlinear reparametrization, we use $\eta = g(\theta) = (|\theta - \hat{\theta}|^2 + b)^a (\theta - \hat{\theta}) + \hat{\eta}$ considered in [8] with several choices of (a, b), which are represented by different colors.

Figure 3: Change in the decision boundary according to the perturbation in parameters $\theta \rightarrow \theta + \epsilon_{i,k}\Delta\theta_k$.

These kinds of weight scaling can be viewed as a mapping between parameter spaces that ensures that neural network models maintain identical probability density functions, i.e., remain equivalent. If a mapping between parameter space is differentiable and locally invertible without changing the probability density function that the neural network parameter models for all parameters on a given neighborhood $U \subseteq \mathbb{R}^m$ of θ, our measures defined in (6), (7) become invariant with respect to such a mapping between parameters. This fact can be expressed as the following proposition:

Proposition 3.1. *Suppose there exist open subsets $U, V \subseteq \mathbb{R}^m$ and an invertible and locally differentiable mapping $g : U \rightarrow V$ that satisfies $f(x; \theta) = \tilde{f}(x; g(\theta))$ for all $x \in \mathbb{R}^D$ and $\theta \in U$ with $g(U) \subseteq V$. The information geometric sharpness measures in (6) and (7) are then invariant to such a mapping, i.e., $\text{IGS}(\theta) = \text{IGS}(g(\theta))$ (or $\text{IGS}_b(\theta) = \text{IGS}_b(g(\theta))$) for all $\theta \in U$.*

The proof of Proposition 3.1 is provided in Appendix D.

Since the layer-wise and node-wise scalings considered for neural networks with ReLU satisfy the assumptions of Prop. 3.1, our measures in (6) and (7) are invariant to such scalings.

3.2 A comparison to some previous sharpness measures

After [8] pointed out the critical reparametrization- and scale-variant issues in the sharpness measures considered in [17, 22, 48], various scale-invariant sharpness measures have been proposed that suit to neural networks with activation functions satisfying the non-negative homogeneity conditions (i.e., $\sigma(a \cdot x) = a \cdot \sigma(x)$ for $a > 0$) such as ReLU [39, 38, 45, 26]. The measure presented in [39] is based on the geometry of the quotient manifold obtained from an equivalence class of neural networks, establishing the scale invariance depending on the considered equivalence types. The work in [38] considers a layer-wise flatness measure for neural networks and additionally explores the conditions for the measure to explain the generalization well. Also, a scale-invariant sharpness measure based on the PAC-Bayes theory is developed in [45]. The Fisher-Rao norm is proposed as a capacity measure for neural networks in [26] and defined as $\theta^\top F(\theta)\theta$, which is scale-invariant.

However, the above measures do not satisfy the invariance to general nonlinear reparametrizations, hence solving the problem raised by [8] only partially. That is, for a nonlinear reparametrization $\theta \mapsto \eta = g(\theta)$, the measures evaluated on the reparametrized model $\tilde{f}(\cdot; \eta) = f(\cdot; g^{-1}(\eta)) = f(\cdot; \theta)$ (with respect to η) can arbitrarily vary from those evaluated on the original model $f(\cdot; \theta)$ (with respect to θ). In Figure 2, we empirically demonstrate the existence of this problem in conventional sharpness measures such as the trace of the Hessian, the measures of [26], [39], and [38] (respectively denoted as $\text{Tr}(H)$, Fisher-Rao, Rangamani et al., and Petzka et al. on the x-axis of the figure; see Appendix G.1 for details). We can observe that the magnitudes of these measures can vary significantly.

Compared with the previous measures, only our measure (denoted as IGS on the x-axis of Figure 2) is invariant to the considered reparametrizations. These experiments empirically demonstrate that our measure satisfies the reparametrization invariance, hence providing a solution that properly resolves the issues posed by [8].

3.3 Connections to the generalization

3.3.1 Connections to Takeuchi's information criterion (TIC)

Our measures can be linked to generalization in different aspects. When we perform the maximum likelihood estimation (this is equivalent to minimizing the negative log-likelihood of (1)), we can obtain the maximum likelihood estimate, which is asymptotically unbiased, guaranteed theoretically by the asymptotic normality. However, the likelihood value evaluated at the obtained estimate does not enjoy such a property.

The well-known Akaike's information criterion (AIC) in the model selection literature calculates this bias under the assumption that the parametric model contains the actual data distribution [1]. Takeuchi's information criterion (TIC) is a generalized form of the AIC by considering the case of misspecified models, i.e., the parametric models do not contain the actual data distribution [43, 9, 44]. TIC is defined as follows:

$$\text{TIC} = \frac{1}{N}\text{Tr}(H(\hat{\theta})^{-1}C(\hat{\theta})), \tag{8}$$

where $\hat{\theta} \in \mathbb{R}^m$ is a local minimum of the loss in (1), $H(\hat{\theta}) \in \mathbb{R}^{m \times m}$ is the Hessian of the (expected) loss and $C(\hat{\theta}) = \mathbb{E}_{p(x,y)}\left[\left(\frac{\partial l(y,f(x;\theta))}{\partial \theta}\right)^{\top}\left(\frac{\partial l(y,f(x;\theta))}{\partial \theta}\right)\right]\Big|_{\theta=\hat{\theta}} \in \mathbb{R}^{m \times m}$ is the non-centered covariance of the loss gradients. Here both $H(\hat{\theta})$ and $C(\hat{\theta})$ are evaluated using the data generating distribution $p(x,y)$.

The formulation in (8) is very similar to our information geometric sharpness measure when evaluated at the local minimum $\hat{\theta}$. Compared to TIC, our measure in (6) contains the FIM instead of the Hessian, and the expectation for $C(\theta)$ is taken with respect to the empirical distribution rather than the true distribution. After a model is sufficiently trained, the Hessian can be approximated to the FIM [35, 28], so we can notice that our sharpness measure is closely related to TIC.

It has been observed that TIC predicts the generalization gap of neural network models well when the expectation with respect to $p(x,y)$ is approximated by a finite sum of the integrands over the test data [44]. These findings are also confirmed by experiments using our measures, of which the details are given in Appendix E.

3.3.2 Connections to the margin

Our measure can also be linked to generalization in terms of margin. Unlike the general definition of the margin as the distance from the decision boundary to its closest data, we devise a similar concept developed in the parametric model space rather than the input space.

Given a model parameter, if we perturb the parameter so that the model's decision boundary passes through the location of a nearby data as shown in Figure 3, the difference between the initial and the perturbed parameter corresponds to a sort of margin defined in the model parameter space. Since the parameter space dimension is high, we can perturb the model parameter in various directions. Considering the perturbations of parameters along the eigenvectors of the FIM results in an interesting connection between this margin and our sharpness measure. We now formalize this relationship for the binary classification case, while that for the multi-class case is derived in Appendix F.

We define the binary cross-entropy loss as $l_i(\theta) = l_{BCE}(x_i, z_i; \theta) = -z_i \log p(x_i; \theta) - (1 - z_i)\log(1 - p(x_i; \theta))$, where $z_i \in \{0, 1\}$ and $p(x_i; \theta)$ denotes the model's prediction on the probability that an input $x_i \in \mathbb{R}^D$ belongs to class one. The condition for $x_i \in \mathbb{R}^D$ to lie on the decision boundary is $p(x_i) = \frac{1}{2}$, which is equal to $l_i(\theta) = \log 2$ regardless of $z_i \in \{0, 1\}$.

Suppose we perturb the neural network parameter from θ to $\theta + \epsilon_{i,k}\Delta\theta_k$, where $\Delta\theta_k$ is the k-th eigenvector of the FIM associated with the k-th eigenvalue λ_k and $\epsilon_{i,k}$ is a scalar. For the decision boundary of the perturbed model to lie on x_i, $\epsilon_{i,k}$ should satisfy $\log 2 = l_i(\theta + \epsilon_{i,k}\Delta\theta_k) \approx l_i(\theta) + \epsilon_{i,k}\left(\frac{\partial l_i}{\partial \theta}\right)\Delta\theta_k$, where we apply the first-order Taylor expansion by assuming small $\epsilon_{i,k}$. The scalar $\epsilon_{i,k}$ can then be approximated as $\epsilon_{i,k} \approx \frac{\log 2 - l_i(\theta)}{\left(\frac{\partial l_i}{\partial \theta}\right)\Delta\theta_k}$.

(a) Decision boundary from SGD

(b) Decision boundary from SGD with regularization

(c) Loss values from SGD

(d) Loss values from SGD with regularization

Figure 4: A synthetic three-class classification example trained using SGD with and without regularization under the effect of poison data. The loss values are smoothed for better visualization.

A sort of margin can be derived in an information geometric sense by computing the squared norm of the perturbation vector $\epsilon_{i,k}\Delta\theta_k$ using the inner product based on the FIM as follows:

$$\epsilon_{i,k}^2\Delta\theta_k^\top F(\theta)\Delta\theta_k = \epsilon_{i,k}^2\lambda_k \approx \lambda_k\left(\frac{\log 2 - l_i(\theta)}{\left(\frac{\partial l_i}{\partial\theta}\right)\Delta\theta_k}\right)^2. \tag{9}$$

The summation over $k = 1,\ldots,m'$ (with m' as the largest k with non-zero λ_k) of the reciprocal of these squared norms (hence weighing more on small $\epsilon_{i,k}^2$ values which would reduce the error from approximations) can then be related to our sharpness measure as follows:

$$\sum_{k=1}^{m'}\frac{1}{\epsilon_{i,k}^2\lambda_k} \approx \sum_{k=1}^{m'}\frac{1}{\lambda_k}\left(\frac{\left(\frac{\partial l_i}{\partial\theta}\right)\Delta\theta_k}{\log 2 - l_i(\theta)}\right)^2 = \frac{\left(\frac{\partial l_i}{\partial\theta}\right)F(\theta)^\dagger\left(\frac{\partial l_i}{\partial\theta}\right)^\top}{(\log 2 - l_i(\theta))^2}, \tag{10}$$

where we have used $F(\theta)^\dagger = \sum_{k=1}^{m'}\frac{1}{\lambda_k}\Delta\theta_k\Delta\theta_k^\top$ in deriving the last identity. Note that our sharpness measure at each data (x_i, y_i) appears in the numerator of (10). This indicates that the smaller our sharpness measure, the larger the squared norms ($\epsilon_{i,k}^2\lambda_k$) in the LHS, which means that the margin becomes larger in an information geometric sense.

4 Using the sharpness measure as a regularizer to train neural networks

We now apply our sharpness measure as a regularizer to train neural networks to see if regularizing the measure can improve the generalization performance. The corresponding loss function is written as

$$\mathcal{L}(\theta) = \frac{1}{N}\sum_{i=1}^{N}l_i(\theta) + \rho\cdot\mathrm{IGS}(\theta), \tag{11}$$

where ρ is a coefficient for the regularization term. We consider a toy example and then consider image classification tasks involving MNIST and CIFAR-10/100 data sets. We also provide some tractable and possibly efficient ways to regularize our sharpness measure. All the experiments have been performed using the PyTorch library [37].

4.1 Toy example

We first apply our regularizer to a toy example. In [18], they have trained neural networks on poison data with the wrong labels to hamper the generalization performance and make the loss landscape extremely sharp while fitting all the training data. We follow this experimental setting and check whether the obtained solution can avoid the undesirable generalization performance and loss landscapes when applying our regularizer (calculated on the training data). The experimental details, as well as how the IGS is approximated for this example, are provided in Appendix G.2.

The experimental results are shown in Figure 4. The results from SGD without regularization show very irregular decision boundaries, whereas relatively soft boundaries appear when our regularizer is used, especially around the training data. Applying our regularizer also shows a lower generalization gap, i.e., the difference between the training and test losses, than the SGD without regularization.

Table 1: Classification accuracies for SGD, GR, SAM, ASAM, and SGD with our regularization method on MNIST, CIFAR-10, and CIFAR-100 data sets.

DATA SET	MODEL	SGD	GR	SAM	ASAM	OURS
MNIST	3FCN	98.13 ± 0.05	98.20 ± 0.01	98.62 ± 0.01	$\mathbf{98.65} \pm 0.07$	$\mathbf{98.65} \pm 0.03$
CIFAR-10	VGG11-BN	92.75 ± 0.11	93.13 ± 0.14	93.61 ± 0.08	93.78 ± 0.13	$\mathbf{93.81} \pm 0.06$
	RESNET-56	94.08 ± 0.17	94.40 ± 0.23	95.22 ± 0.11	$\mathbf{95.36} \pm 0.06$	94.96 ± 0.01
	WRN-16-8	95.98 ± 0.03	96.15 ± 0.10	96.70 ± 0.14	$\mathbf{97.03} \pm 0.06$	96.57 ± 0.10
CIFAR-100	VGG11-BN	72.25 ± 0.17	73.05 ± 0.32	73.69 ± 0.20	73.61 ± 0.18	$\mathbf{74.24} \pm 0.22$
	RESNET-56	73.14 ± 0.10	74.67 ± 0.25	75.90 ± 0.25	75.87 ± 0.27	$\mathbf{76.07} \pm 0.11$
	WRN-16-8	80.55 ± 0.33	81.13 ± 0.06	82.20 ± 0.11	82.38 ± 0.09	$\mathbf{82.44} \pm 0.29$

4.2 MNIST and CIFAR-10/100

To check the effect of the regularizer in more realistic settings, we apply our regularizer to the classification of MNIST and CIFAR-10/100 data sets. For this experiment, we regularize the mini-batch IGS defined in (7). For an efficient implementation of our regularizer, the following approximation on perturbed loss functions with a perturbation $\delta = \rho F(\theta)^{\dagger} \left(\frac{\partial l}{\partial \theta} \right)^{\top} \in \mathbb{R}^m$ (with a small $\rho > 0$) is useful:

$$ l(\theta + \delta) \approx l(\theta) + \left(\frac{\partial l}{\partial \theta} \right) \delta \approx l(\theta) + \rho \cdot \left(\frac{\partial l}{\partial \theta} \right) F(\theta)^{\dagger} \left(\frac{\partial l}{\partial \theta} \right)^{\top}. \tag{12} $$

Note that for $l = \frac{1}{b} \sum_{x_i \in B} l_i$ with a mini-batch B of size $|B| = b$, minimizing (12) becomes minimizing a stochastic version of (11) (with $\mathrm{IGS}_b(\theta)$), where the stochasticity comes from sampling a mini-batch B. Therefore we minimize (12) in our experiments with ρ as a tunable hyperparameter. To obtain δ, we resort to an EKFAC-based approximation for the natural gradients [13] as detailed in Appendix G.3.1.

A three-layer fully connected neural network (3FCN) is used for the experiments using MNIST data, and various convolutional neural networks such as VGG [41], ResNet [15], and WideResNet [49] are used for CIFAR-10/100 experiments, with data augmentation, cosine annealing [27], and label smoothing [29] methods additionally applied. For comparison, we consider the gradient regularization (GR) method [4, 42], sharpness-aware minimization (SAM) method [12], and the adaptive SAM (ASAM) method [24], an extension of SAM to involve the scale invariance. The detailed experimental settings are explained in Appendix G.3.2.

As can be seen from Table 1, one can confirm that the generalization performance of SGD is significantly improved with our regularizer. Furthermore, our method shows better performance than the GR method and a comparable performance improvement with the SAM and ASAM methods.

5 Conclusion

Various empirical results observed from running deep learning algorithms such as SGD have suggested that minima with a flatter loss landscape tend to show better generalization performance. However, the previous definitions of sharpness/flatness have faced a severe dependence on reparametrizations or parameter scalings that do not change the model output and the generalization performance [8].

In this paper, based on an information geometric analysis of the neural network parameter space, we have proposed an information geometric sharpness measure which is reparametrization- and scale-invariant hence free from the issues posed by [8]. We have also discussed the connection of the measure to generalization. In addition, a regularizer that reduces the suggested sharpness measure is proposed, showing a significant improvement in generalization performance under practical settings.

Unlike many other sharpness measures, the Fisher information matrix (FIM) plays a crucial role in our measure. Since it can be computationally demanding to calculate the FIM and our sharpness measure for large-scale neural networks, more efficient evaluation methods should be developed to apply our measure to such networks. Furthermore, analyzing the generalization properties of models obtained from deep learning algorithms such as SGD or natural gradient descent [2, 28] using our measure would be another intriguing future work.

References

[1] Akaike, H.: A new look at the statistical model identification. IEEE transactions on automatic control **19**(6), 716–723 (1974)

[2] Amari, S.I.: Natural gradient works efficiently in learning. Neural computation **10**(2), 251–276 (1998)

[3] Amari, S.i.: Information geometry and its applications, vol. 194. Springer (2016)

[4] Barrett, D.G., Dherin, B.: Implicit gradient regularization. arXiv preprint arXiv:2009.11162 (2020)

[5] Bartlett, P.L., Foster, D.J., Telgarsky, M.J.: Spectrally-normalized margin bounds for neural networks. Advances in Neural Information Processing Systems **30**, 6240–6249 (2017)

[6] Boothby, W.M.: An introduction to differentiable manifolds and Riemannian geometry, Revised, vol. 120. Gulf Professional Publishing (2003)

[7] Chaudhari, P., Choromanska, A., Soatto, S., LeCun, Y., Baldassi, C., Borgs, C., Chayes, J., Sagun, L., Zecchina, R.: Entropy-sgd: Biasing gradient descent into wide valleys. Journal of Statistical Mechanics: Theory and Experiment **2019**(12), 124018 (2019)

[8] Dinh, L., Pascanu, R., Bengio, S., Bengio, Y.: Sharp minima can generalize for deep nets. In: International Conference on Machine Learning, pp. 1019–1028. PMLR (2017)

[9] Dixon, M., Ward, T.: Takeuchi's information criteria as a form of regularization. arXiv preprint arXiv:1803.04947 (2018)

[10] Dziugaite, G.K., Roy, D.M.: Computing nonvacuous generalization bounds for deep (stochastic) neural networks with many more parameters than training data. arXiv preprint arXiv:1703.11008 (2017)

[11] Fomenko, A., Novikov, S., Dubrovin, B.: Modern Geometry-Methods and Applications, Part I: The Geometry of Surfaces, Transformation Groups, and Fields. Springer, Berlin (1992)

[12] Foret, P., Kleiner, A., Mobahi, H., Neyshabur, B.: Sharpness-aware minimization for efficiently improving generalization. arXiv preprint arXiv:2010.01412 (2020)

[13] George, T., Laurent, C., Bouthillier, X., Ballas, N., Vincent, P.: Fast approximate natural gradient descent in a kronecker factored eigenbasis. Advances in Neural Information Processing Systems **31** (2018)

[14] Ghorbani, B., Krishnan, S., Xiao, Y.: An investigation into neural net optimization via hessian eigenvalue density. In: International Conference on Machine Learning, pp. 2232–2241. PMLR (2019)

[15] He, K., Zhang, X., Ren, S., Sun, J.: Deep residual learning for image recognition. In: Proceedings of the IEEE conference on computer vision and pattern recognition, pp. 770–778 (2016)

[16] Hinton, G.E., Van Camp, D.: Keeping the neural networks simple by minimizing the description length of the weights. In: Proceedings of the sixth annual conference on Computational learning theory, pp. 5–13 (1993)

[17] Hochreiter, S., Schmidhuber, J.: Flat minima. Neural computation **9**(1), 1–42 (1997)

[18] Huang, W.R., Emam, Z., Goldblum, M., Fowl, L., Terry, J.K., Huang, F., Goldstein, T.: Understanding generalization through visualizations (2020)

[19] Izmailov, P., Podoprikhin, D., Garipov, T., Vetrov, D., Wilson, A.G.: Averaging weights leads to wider optima and better generalization. In: 34th Conference on Uncertainty in Artificial Intelligence 2018, UAI 2018, pp. 876–885. Association For Uncertainty in Artificial Intelligence (AUAI) (2018)

[20] Jastrzebski, S., Arpit, D., Astrand, O., Kerg, G.B., Wang, H., Xiong, C., Socher, R., Cho, K., Geras, K.J.: Catastrophic fisher explosion: Early phase fisher matrix impacts generalization. In: International Conference on Machine Learning, pp. 4772–4784. PMLR (2021)

[21] Jiang, Y., Neyshabur, B., Mobahi, H., Krishnan, D., Bengio, S.: Fantastic generalization measures and where to find them. In: International Conference on Learning Representations (2019)

[22] Keskar, N.S., Nocedal, J., Tang, P.T.P., Mudigere, D., Smelyanskiy, M.: On large-batch training for deep learning: Generalization gap and sharp minima. In: 5th International Conference on Learning Representations, ICLR 2017 (2017)

[23] Kunstner, F., Hennig, P., Balles, L.: Limitations of the empirical fisher approximation for natural gradient descent. Advances in neural information processing systems **32** (2019)

[24] Kwon, J., Kim, J., Park, H., Choi, I.K.: Asam: Adaptive sharpness-aware minimization for scale-invariant learning of deep neural networks. arXiv preprint arXiv:2102.11600 (2021)

[25] LeCun, Y., Bottou, L., Bengio, Y., Haffner, P.: Gradient-based learning applied to document recognition. Proceedings of the IEEE **86**(11), 2278–2324 (1998)

[26] Liang, T., Poggio, T., Rakhlin, A., Stokes, J.: Fisher-rao metric, geometry, and complexity of neural networks. In: The 22nd International Conference on Artificial Intelligence and Statistics, pp. 888–896. PMLR (2019)

[27] Loshchilov, I., Hutter, F.: Sgdr: Stochastic gradient descent with warm restarts. arXiv preprint arXiv:1608.03983 (2016)

[28] Martens, J.: New insights and perspectives on the natural gradient method. Journal of Machine Learning Research **21**, 1–76 (2020)

[29] Müller, R., Kornblith, S., Hinton, G.: When does label smoothing help? arXiv preprint arXiv:1906.02629 (2019)

[30] Nair, V., Hinton, G.E.: Rectified linear units improve restricted boltzmann machines. In: Icml (2010)

[31] Neyshabur, B., Bhojanapalli, S., Mcallester, D., Srebro, N.: Exploring generalization in deep learning. Advances in Neural Information Processing Systems **30**, 5947–5956 (2017)

[32] Neyshabur, B., Salakhutdinov, R., Srebro, N.: Path-sgd: path-normalized optimization in deep neural networks. In: Proceedings of the 28th International Conference on Neural Information Processing Systems-Volume 2, pp. 2422–2430 (2015)

[33] Neyshabur, B., Tomioka, R., Srebro, N.: Norm-based capacity control in neural networks. In: Conference on Learning Theory, pp. 1376–1401. PMLR (2015)

[34] Nielsen, F.: An elementary introduction to information geometry. Entropy **22**(10), 1100 (2020)

[35] Papyan, V.: The full spectrum of deepnet hessians at scale: Dynamics with sgd training and sample size. arXiv preprint arXiv:1811.07062 (2018)

[36] Papyan, V.: Measurements of three-level hierarchical structure in the outliers in the spectrum of deepnet hessians. In: International Conference on Machine Learning, pp. 5012–5021. PMLR (2019)

[37] Paszke, A., Gross, S., Chintala, S., Chanan, G., Yang, E., DeVito, Z., Lin, Z., Desmaison, A., Antiga, L., Lerer, A.: Automatic differentiation in pytorch (2017)

[38] Petzka, H., Kamp, M., Adilova, L., Sminchisescu, C., Boley, M.: Relative flatness and generalization. Advances in Neural Information Processing Systems **34** (2021)

[39] Rangamani, A., Nguyen, N.H., Kumar, A., Phan, D., Chin, S.P., Tran, T.D.: A scale invariant measure of flatness for deep network minima. In: ICASSP 2021-2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), pp. 1680–1684. IEEE (2021)

[40] Sagun, L., Evci, U., Guney, V.U., Dauphin, Y., Bottou, L.: Empirical analysis of the hessian of over-parametrized neural networks. arXiv preprint arXiv:1706.04454 (2017)

[41] Simonyan, K., Zisserman, A.: Very deep convolutional networks for large-scale image recognition. arXiv preprint arXiv:1409.1556 (2014)

[42] Smith, S.L., Dherin, B., Barrett, D.G., De, S.: On the origin of implicit regularization in stochastic gradient descent. arXiv preprint arXiv:2101.12176 (2021)

[43] Takeuchi, K.: The distribution of information statistics and the criterion of goodness of fit of models. Mathematical Science **153**, 12–18 (1976)

[44] Thomas, V., Pedregosa, F., Merriënboer, B., Manzagol, P.A., Bengio, Y., Le Roux, N.: On the interplay between noise and curvature and its effect on optimization and generalization. In: International Conference on Artificial Intelligence and Statistics, pp. 3503–3513. PMLR (2020)

[45] Tsuzuku, Y., Sato, I., Sugiyama, M.: Normalized flat minima: Exploring scale invariant definition of flat minima for neural networks using pac-bayesian analysis. In: International Conference on Machine Learning, pp. 9636–9647. PMLR (2020)

[46] Wu, J., Hu, W., Xiong, H., Huan, J., Braverman, V., Zhu, Z.: On the noisy gradient descent that generalizes as sgd. In: International Conference on Machine Learning, pp. 10367–10376. PMLR (2020)

[47] Yao, Z., Gholami, A., Keutzer, K., Mahoney, M.W.: Pyhessian: Neural networks through the lens of the hessian. In: 2020 IEEE International Conference on Big Data (Big Data), pp. 581–590. IEEE (2020)

[48] Yao, Z., Gholami, A., Lei, Q., Keutzer, K., Mahoney, M.W.: Hessian-based analysis of large batch training and robustness to adversaries. Advances in Neural Information Processing Systems **31** (2018)

[49] Zagoruyko, S., Komodakis, N.: Wide residual networks. arXiv preprint arXiv:1605.07146 (2016)

Appendix

A   The Fisher information matrix and class margins

As mentioned in Section 2.2 of the manuscript, [36] suggested a hierarchy of the logit gradients based on the following decomposition of the Fisher information matrix:

$$\frac{1}{N}\sum_{i=1}^{N} J_i^\top \left(\operatorname{diag}(p_i) - p_i p_i^\top \right) J_i = \frac{1}{N}\sum_{i=1}^{N} J_i^\top M_i^\top M_i J_i, \tag{13}$$

where $M_i = \operatorname{diag}(\sqrt{p_i})\left(I - \mathbb{1}p_i^\top\right) \in \mathbb{R}^{C\times C}$, $\sqrt{p_i} = (\sqrt{(p_i)_1}, \dots, \sqrt{(p_i)_C}) \in \mathbb{R}^C$, and $\mathbb{1} = (1, \dots, 1) \in \mathbb{R}^C$ is a vector whose elements are all one.

According to the proposed hierarchy, the dominant component of the FIM attributing the outliers of the eigenspectra turns out to be

$$G = (C-1)\sum_{c=1}^{C} \frac{N_c}{N}\delta_c\delta_c^\top, \tag{14}$$

where N_c is the number of data belongs to class c. Here the vector $\delta_c \in \mathbb{R}^m$ is defined as

$$\delta_c = \frac{1}{N_c \cdot (C-1)} \sum_{c' \neq c} \sum_{i \in I_c} \delta_{i,c'}, \tag{15}$$

where $\delta_{i,j} \in \mathbb{R}^m$ is the j-th row vector of the matrix $M_i J_i \in \mathbb{R}^{C \times m}$ (also defined in (5)) and $I_c = \{i \in \{1, \dots, N\} | y_i = c\}$ is the set of indices for data in class c.

The dominant component of FIM in (14) implies that the FIM can be related to the difference between the c-th component and $c' \neq c$-th components in the logit derivatives. This relation can be seen more evidently using some assumptions on the predicted probability p_i.

Assuming the prediction for the classes $c' \neq c$ are balanced, i.e., $(p_i)_{c'}$, the c'-th component of p_i for $c' \neq c$, are all equal to a constant $\epsilon \ll 1$, we can approximate $\delta_{i,c'}$ and δ_c as follows:

$$\delta_{i,c'} = \sqrt{\epsilon} \cdot (J_{i,c'} - J_{i,c})^\top + o(\sqrt{\epsilon}), \tag{16}$$

$$\delta_c = \sqrt{\epsilon} \cdot \left(\frac{1}{N_c} \sum_{i \in I_c} \left(\frac{1}{C-1} \sum_{c' \neq c} J_{i,c'} - J_{i,c} \right)^\top \right) + o(\sqrt{\epsilon}), \tag{17}$$

where $J_{i,j} \in \mathbb{R}^{1 \times m}$ denotes the j-th row of the logit derivative $J_i \in \mathbb{R}^{C \times m}$. In this case, δ_c can be interpreted as the gradient of the differences in the averaged logit values that can discriminate the class c from the other classes $c' \neq c$. Since the dominant component of the FIM is insisted to be the G term in (14), we conjecture that the eigensubspace of the FIM can be related to the class margins as long as the hierarchy from [36] is valid. Similar derivations can be found in [35].

B On the IGS for a rank-deficient $F(\theta)$

From (2), the Fisher information matrix can be rewritten as

$$F(\theta) = \frac{1}{N} \sum_{i=1}^{N} J_i^\top \left(\mathrm{diag}(p_i) - p_i p_i^\top \right) J_i, \tag{18}$$

where $J_i = \left(\frac{\partial f}{\partial \theta}(x) \right) \Big|_{x=x_i} \in \mathbb{R}^{C \times m}$ and $p_i = (p(1|x_i; \theta), \dots, p(C|x_i; \theta)) \in \mathbb{R}^C$ is the model's prediction on the probability that x_i belongs to each class.

The FIM is positive semi-definite when the number of parameters is very large, e.g., for the over-parametrized models with $m \gg N$. Therefore, we need to verify if our definition of information geometric measure in (6) involving the pseudo-inverse of $F(\theta)$ is well-defined in the sense that there are not any components of $\left(\frac{\partial l_i}{\partial \theta} \right)$ neglected in measuring the information geometric norm by (6). For this purpose, we characterize the null space of $F(\theta)$ and compare it to that of the loss derivative $\left(\frac{\partial l_i}{\partial \theta} \right) \in \mathbb{R}^{1 \times m}$.

From (18) the null space of $F(\theta)$, $\mathrm{Null}(F(\theta)) = N_1 \cup N_2$, where N_1 and N_2 are defined as

$$N_1 = \{\dot\theta \in \mathbb{R}^m \mid J_i \dot\theta = 0, \quad \forall i \in \{1, \dots, N\}\}, \tag{19}$$

$$N_2 = \{\dot\theta \in \mathbb{R}^m \mid J_i \dot\theta = c \cdot (1, \dots, 1)^\top, \quad c \in \mathbb{R}, \quad \forall i \in \{1, \dots, N\}\}. \tag{20}$$

Note that the condition for N_2 comes from the fact that the matrix $\left(\mathrm{diag}(p_i) - p_i p_i^\top \right) \in \mathbb{R}^{C \times C}$ in (18) possesses the vector $(1, \dots, 1)^\top \in \mathbb{R}^C$ as its eigenvector with zero eigenvalue.

For $\dot\theta \in \mathrm{Null}(F(\theta))$, we can easily show that $\left(\frac{\partial l_i}{\partial \theta} \right) \dot\theta = 0$ for all $i = 1, \dots, N$, since $\left(\frac{\partial l_i}{\partial \theta} \right) = -(e_{y_i}^\top - \sum_j (p_i)_j e_j^\top) J_i \dot\theta = 0$ for both the cases of $\dot\theta \in N_1$ and $\dot\theta \in N_2$. Therefore, $\mathrm{Null}(F(\theta)) \subset \mathrm{Null}(\left(\frac{\partial l_i}{\partial \theta} \right))$ holds, and we can say that the vector $\left(\frac{\partial l_i}{\partial \theta} \right)^\top \in \mathbb{R}^m$ belongs to the span of the eigenvectors of $F(\theta)$ with non-zero eigenvalues for all $i = 1, \dots, N$. Hence our information geometric measure in (6) does not neglect any components in $\left(\frac{\partial l_i}{\partial \theta} \right)$.

C On the relationship between IGS and mini-batch IGS

To obtain the relationship between IGS in (6) and mini-batch IGS in (7), we express them as follows:

$$\text{IGS}(\theta) = \frac{1}{N} \sum_{i=1}^{N} \left(\frac{\partial l_i}{\partial \theta} \right) F(\theta)^\dagger \left(\frac{\partial l_i}{\partial \theta} \right)^\top = \text{Tr}\left(F(\theta)^\dagger S(\theta) \right), \tag{21}$$

$$\text{IGS}_b(\theta) = \mathbb{E}_B \left[\left(\frac{1}{b} \sum_{x_i \in B} \frac{\partial l_i}{\partial \theta} \right) F(\theta)^\dagger \left(\frac{1}{b} \sum_{x_i \in B} \frac{\partial l_i}{\partial \theta} \right)^\top \right] = \text{Tr}\left(F(\theta)^\dagger S_b(\theta) \right), \tag{22}$$

where $S(\theta) = \frac{1}{N} \sum_{i=1}^{N} \left(\frac{\partial l_i}{\partial \theta} \right)^\top \left(\frac{\partial l_i}{\partial \theta} \right) \in \mathbb{R}^{m \times m}$ is the second moment of the (individual) loss gradients and $S_b(\theta) = \mathbb{E}_B \left[\left(\frac{1}{b} \sum_{x_i \in B} \frac{\partial l_i}{\partial \theta} \right)^\top \left(\frac{1}{b} \sum_{x_i \in B} \frac{\partial l_i}{\partial \theta} \right) \right] \in \mathbb{R}^{m \times m}$ is that of the mini-batch loss gradients with a batch size of b.

For our purpose, the relationship between the covariance of loss gradients and that of mini-batch loss gradients is useful. The relationship is established in [46] as $C_b(\theta) = \frac{\gamma_{b,N}}{b} C(\theta)$, where $C(\theta) \in \mathbb{R}^{m \times m}$ and $C_b(\theta) \in \mathbb{R}^{m \times m}$ are respectively the covariance of the loss gradients and mini-batch loss gradients (with a batch size of b), and $\gamma_{b,N} = \frac{N-b}{N-1}$ if mini-batches are sampled without replacement and 1 if sampled with replacement. From the relations between the covariances and second moments given as $C(\theta) = S(\theta) - S_N(\theta)$ and $C_b(\theta) = S_b(\theta) - S_N(\theta)$ with $S_N(\theta) = \left(\frac{1}{N} \sum_{i=1}^{N} \frac{\partial l_i}{\partial \theta} \right)^\top \left(\frac{1}{N} \sum_{i=1}^{N} \frac{\partial l_i}{\partial \theta} \right) \in \mathbb{R}^{m \times m}$, we can relate $S(\theta)$ and $S_b(\theta)$ as follows:

$$S_b(\theta) = C_b(\theta) + S_N(\theta) = \frac{\gamma_{b,N}}{b} C(\theta) + S_N(\theta) \tag{23}$$

$$= \frac{\gamma_{b,N}}{b} S(\theta) + (1 - \frac{\gamma_{b,N}}{b}) S_N(\theta). \tag{24}$$

By applying (24) to (22), we can obtain the relationship between IGS and mini-batch IGS as follows:

$$\text{IGS}_b(\theta) = \frac{\gamma_{b,N}}{b} \text{Tr}\left(F(\theta)^\dagger S(\theta) \right) + (1 - \frac{\gamma_{b,N}}{b}) \text{Tr}\left(F(\theta)^\dagger S_N(\theta) \right) \tag{25}$$

$$= \frac{\gamma_{b,N}}{b} \text{IGS}(\theta) + (1 - \frac{\gamma_{b,N}}{b}) \text{IGS}_N(\theta). \tag{26}$$

By defining other information geometric sharpness measures as $\text{IGS-C}(\theta) \equiv \text{IGS}(\theta) - \text{IGS}_N(\theta)$ and $\text{IGS}_b\text{-C}(\theta) \equiv \text{IGS}_b(\theta) - \text{IGS}_N(\theta)$, which can be considered as replacing the second moments with covariances in (21) and (22), the relationship between them becomes as follows:

$$\text{IGS}_b\text{-C}(\theta) = \frac{\gamma_{b,N}}{b} \text{IGS-C}(\theta). \tag{27}$$

D Proof of Proposition 3.1

Proof. To prove $\text{IGS}(\theta) = \text{IGS}(g(\theta))$ (or $\text{IGS}_b(\theta) = \text{IGS}_b(g(\theta))$) for all $\theta \in U$, we have to show whether the following equality holds for any $\theta \in U$ and $i, j \in \{1, \ldots, N\}$:

$$\left(\frac{\partial l_i}{\partial \theta} \right) F(\theta)^\dagger \left(\frac{\partial l_j}{\partial \theta} \right)^\top = \left(\frac{\partial l_i}{\partial g(\theta)} \right) F(g(\theta))^\dagger \left(\frac{\partial l_j}{\partial g(\theta)} \right)^\top. \tag{28}$$

By differentiating $f(x; \theta) = f(x; g(\theta))$ with respect to θ, we get $\left(\frac{\partial f}{\partial \theta} \right) = \left(\frac{\partial f}{\partial g(\theta)} \right) \left(\frac{\partial g(\theta)}{\partial \theta} \right)$, where $\left(\frac{\partial g(\theta)}{\partial \theta} \right) \in \mathbb{R}^{m \times m}$ is invertible by the assumption. Applying this identity to the definition of the Fisher information matrix gives the transformation rule of $F(\theta) = \left(\frac{\partial g(\theta)}{\partial \theta} \right)^\top F(g(\theta)) \left(\frac{\partial g(\theta)}{\partial \theta} \right)$. Furthermore, from the chain rule, $\left(\frac{\partial l_i}{\partial \theta} \right) = \left(\frac{\partial l_i}{\partial g(\theta)} \right) \left(\frac{\partial g(\theta)}{\partial \theta} \right)$. Combining these two identities and using the fact that $\left(\frac{\partial g(\theta)}{\partial \theta} \right)$ is invertible and $(AMA^\top)^\dagger = A^{-\top} M^\dagger A^{-1}$ for an invertible matrix $A \in \mathbb{R}^{m \times m}$ and any $M \in \mathbb{R}^{m \times m}$ give the desired (28). $\square$

E   Correlations of the IGS to the generalization gap

To investigate the correlation between the IGS and the generalization performances, we experiment using LeNet-5 [25] trained on MNIST and CIFAR-10 data sets via SGD. To obtain models possessing different generalization performances for MNIST data sets, we train the models via SGD with learning rates in $\{0.002, 0.005, 0.01, 0.02, 0.05, 0.1\}$ and batch sizes in $\{64, 128, 256, 512, 1024\}$, and the training is terminated when the training loss becomes lower than 0.01. For CIFAR-10 data sets, we use learning rates in $\{0.001, 0.002, 0.005, 0.01, 0.02, 0.05\}$ and the identical batch sizes to the above, and the training is terminated when the training loss gets lower than 0.1. All the experiments are performed for two different random seeds, and only the models with loss converged in a specified number of iterations are considered.

For the trained models, the IGS is evaluated on test data similarly to [44]. We can observe that the IGS has a good correlation with the generalization gap defined as the difference between the train and test losses in Figure 5.

| (a) MNIST experiments | (b) CIFAR-10 experiments |

Figure 5: Plots for generalization gap vs. IGS.

A crucial difference to [44] is that we use LeNet-5, of which the number of parameters exceeds 60,000. Therefore, it is difficult to compute the exact values of IGS for the obtained models. Here we briefly explain how the IGS is evaluated in our experiments. To obtain the eigenvalues/eigenvectors of the FIM, we first subsample N_s data points $\{x_1, \ldots, x_{N_s}\}$ from the data set ($N_s = 1,024$ in our experiments). We then calculate the Jacobian of the loss for the sampled labels with respect to the parameters, i.e., $\tilde{J} = \left(\frac{\partial \tilde{l}}{\partial \theta}\right) \in \mathbb{R}^{N_s \times m}$, where $\tilde{l} = (l(\tilde{y}_1, f(x_1; \theta)), \ldots, l(\tilde{y}_{N_s}, f(x_{N_s}; \theta))) \in \mathbb{R}^{N_s}$ and the labels $\tilde{y}_i$ are sampled according to the probabilistic model $p(y|x_i; \theta)$ that the neural network models for $i = 1, \ldots, N_s$ as discussed in [20]. The FIM can then be approximated as $F(\theta) \approx \frac{1}{N_s} \tilde{J}^\top \tilde{J}$, and its top-$k$ eigenvalues/eigenvectors are numerically obtained via the power iterations. The dimension k of eigensubspace to consider (for the pseudo-inverse of the approximated FIM) is chosen to be the least number that makes the sum of top-k eigenvalues exceed 95% of $\text{Tr}(F(\theta)) \approx \frac{1}{N_s} \text{Tr}(\tilde{J}^\top \tilde{J})$. To further reduce the computational costs, the mini-batch IGS in (7) is computed from mini-batch gradients (with a batch size of 128) obtained by iterating for an epoch to consider each data for once, and then converted to IGS using (26). We perform these procedures for five different subsamples to approximate the FIM, and average the obtained IGS values.

F   An information geometric margin for multi-class problems

An information geometric margin can also be formulated in the multi-class classification case similarly as done in Section 3.3. For a data point (x_i, y_i) of class $y_i = c$, we consider the decision boundary between class c and class c' for all $c' \neq c$. The condition for a point $x \in \mathbb{R}^D$ to lie on this decision boundary between classes c and c' is given as $f_c(x; \theta) = f_{c'}(x; \theta)$, where $f_j(\cdot; \theta) : \mathbb{R}^D \to \mathbb{R}$ is the j-th logit function (or the j-th output of the neural network). Again, we consider perturbing the parameters along the eigenvectors of the Fisher information matrix to make the data (x_i, y_i) lie on this decision boundary.

The following should be satisfied for the perturbation from the k-th eigenvector (associated with the k-th eigenvalue λ_k) with perturbation step size $\epsilon_{i,k,c'}$ to achieve the above condition:

$$f_{i,c}(\theta + \epsilon_{i,k,c'} \Delta\theta_k) = f_{i,c'}(\theta + \epsilon_{i,k,c'} \Delta\theta_k), \tag{29}$$

where $f_{i,j}(\theta) \in \mathbb{R}$ is the $f_j(x_i; \theta)$.

From the first-order Taylor expansion assuming small $\epsilon_{i,k,c'}$, the following approximations hold:

$$f_{i,c}(\theta) + \epsilon_{i,k,c'} J_{i,c} \Delta\theta_k \approx f_{i,c'}(\theta) + \epsilon_{i,k,c'} J_{i,c'} \Delta\theta_k, \tag{30}$$

$$\epsilon_{i,k,c'} \approx \frac{f_{i,c}(\theta) - f_{i,c'}(\theta)}{(J_{i,c'} - J_{i,c})\,\Delta\theta_k}, \tag{31}$$

$$\frac{f_{i,c}(\theta) - f_{i,c'}(\theta)}{\epsilon_{i,k,c'}} \approx (J_{i,c'} - J_{i,c})\,\Delta\theta_k, \tag{32}$$

where $J_{i,j} = \left(\frac{\partial f_{i,j}}{\partial\theta}\right) \in \mathbb{R}^{1\times m}$. Note that $\epsilon_{i,k,c'}$ can have different signs for different c's according to the sign of the $(J_{i,c'} - J_{i,c})\,\Delta\theta_k$ term.

Considering the weighted sum of (32) with the weights of the probability $p_{i,c'}$, i.e., the probability of x_i being class c' predicted from the model, we can approximate the directional derivative of the cross-entropy loss using $\epsilon_{i,k,c'}$ as follows:

$$\sum_{c'\neq c} p_{i,c'} \left(\frac{f_{i,c}(\theta) - f_{i,c'}(\theta)}{\epsilon_{i,k,c'}}\right) \approx \left(\sum_{c'\neq c} p_{i,c'} J_{i,c'} - (1 - p_{i,c}) J_{i,c}\right)\Delta\theta_k = \left(\frac{\partial l_i}{\partial\theta}\right)\Delta\theta_k, \tag{33}$$

where we have used $\left(\frac{\partial l_i}{\partial\theta}\right) = -(e_{y_i}^\top - \sum_j p_{i,j} e_j^\top) J_i \in \mathbb{R}^{1\times m}$.

Our sharpness measure can then be related to the (signed) norm of the perturbation vector $\sqrt{\lambda_k}\epsilon_{i,k,c'}$ as follows:

$$\left(\frac{\partial l_i}{\partial\theta}\right) F^\dagger(\theta) \left(\frac{\partial l_i}{\partial\theta}\right)^\top = \sum_{k=1}^{m'} \frac{1}{\lambda_k} \left(\left(\frac{\partial l_i}{\partial\theta}\right)\Delta\theta_k\right)^2 \approx \sum_{k=1}^{m'} \left(\sum_{c'\neq c} p_{i,c'}\left(\frac{f_{i,c}(\theta) - f_{i,c'}(\theta)}{\sqrt{\lambda_k}\epsilon_{i,k,c'}}\right)\right)^2, \tag{34}$$

where the last approximation comes from applying (33). Therefore as in the binary classification case, we can observe that reducing our sharpness measure can be connected to increasing the magnitude of the margin $\sqrt{\lambda_k}\epsilon_{i,k,c'}$ in the information geometric sense.

G Experimental details

G.1 Reparametrization invariance

We examine the reparametrization invariance of the IGS and compare it to other sharpness measures such as the trace of the Hessian, the spectral norm (or the top eigenvalue) of the Hessian, the Fisher-Rao norm [26], the Rangamani et al.'s measure [39], and the Petzka et al.'s measure [38].[2]

We consider a two-layer fully connected neural network with 20-dimensional hidden units and ReLU activation functions for this experiment. The neural network is trained on two-dimensional synthetic data generated from mixtures of three Gaussians via SGD with a learning rate of 0.1 and a batch size of 40 until the training loss gets lower than 5e-3. After training ten neural networks initialized with different random seeds, we obtain reparametrized neural networks for each of them by considering an element-wise nonlinear reparametrization $\eta = g(\theta) = (|\theta - \hat{\theta}|^2 + b)^a(\theta - \hat{\theta}) + \hat{\eta}$, which is presented as an example in Section 5 of [8]. We consider several pairs of (a, b) for $a \in \{-0.5, 0.5\}$ and $b \in \{0.01, 0.1, 1\}$ in defining $g(\theta)$, with $\hat{\theta}$ set as the obtained parameter and $\hat{\eta}$ sampled from the standard normal distribution. The above measures are then calculated for both the original models (with respect to θ) and their reparametrized ones $\tilde{f}(\cdot; \eta) = f(\cdot; g^{-1}(\eta)) = f(\cdot; \theta)$ (with respect to η).

In Figure 6, we plot the sharpness measures calculated for the original models on the x-axis and the logarithm of those for the reparametrized ones on the y-axis. Points with the same x-axis values correspond to reparametrizations from the identical original model with different choices of (a, b).

---

[2]To evaluate the latter two sharpness measures we use the codes in the following URL:
https://github.com/kampmichael/RelativeFlatnessAndGeneralization (Apache License 2.0).

Figure 6: Sharpness measures evaluated for the original models vs. the logarithm (to base 10) of sharpness measures for the reparametrized models. We consider nonlinear reparametrizations of $\eta = g(\theta) = (|\theta - \hat{\theta}|^2 + b)^a(\theta - \hat{\theta}) + \hat{\eta}$ considered in [8] with several choices of (a, b), which are represented by different colors. The solid lines ($y = \log_{10}(x)$) denote the case of reparametrization invariance.

The solid lines ($y = \log_{10}(x)$) denote the case in which the sharpness measures evaluated for the original model and the reparameterized model are the same. From the figure, we can observe that only the IGS is invariant to the considered reparametrizations, while the other measures including the scale-invariant ones can be arbitrarily varied in their magnitudes significantly. These figures are merged into a single figure in Figure 2 of the manuscript, reporting the ratio of the sharpness measures evaluated for the reparameterized models to those evaluated for the original models.

G.2 Toy example

G.2.1 A finite difference-based approximation of IGS

Consider the following eigendecomposition of the Fisher information matrix

$$F(\theta) = \sum_{k=1}^{m'} \lambda_k \Delta\theta_k \Delta\theta_k^\top, \tag{35}$$

where λ_k, $\Delta\theta_k$ are respectively the k-th eigenvalue and eigenvector of $F(\theta)$, and m' is the largest index of non-zero λ_k. The sharpness measure is then approximated as follows:

$$\text{IGS}(\theta) = \frac{1}{N} \sum_{i=1}^{N} \left(\frac{\partial l_i}{\partial \theta}\right) \left(\sum_{k=1}^{m'} \frac{1}{\lambda_k} \Delta\theta_k \Delta\theta_k^\top\right) \left(\frac{\partial l_i}{\partial \theta}\right)^\top \tag{36}$$

$$= \frac{1}{N} \sum_{i=1}^{N} \sum_{k=1}^{m'} \left(\frac{1}{\sqrt{\lambda_k}} \left(\frac{\partial l_i}{\partial \theta}\right) \Delta\theta_k\right)^2 \tag{37}$$

$$\approx \frac{1}{N \cdot \alpha^2} \sum_{i=1}^{N} \mathbb{E}_\epsilon \left[\left(l_i\left(\theta + \alpha \sum_{k=1}^{m'} \frac{\epsilon_k}{\sqrt{\lambda_k}} \Delta\theta_k\right) - l_i(\theta)\right)^2\right], \tag{38}$$

where $\mathbb{E}_\epsilon[\cdot]$ denotes the expectation with respect to an m'-dimensional vector $\epsilon = (\epsilon_1, \ldots, \epsilon_{m'}) \sim N(0, I)$ in (38), and the first-order approximation is used to derive (38) with $\alpha > 0$ as a small scalar.

To avoid possible numerical instabilities stemming from the varying scales of the eigenvalues, we can consider following regularizer using a fixed amount of perturbation from θ in the first $l_i(\cdot)$-term in

 (38):

$$\text{IGS}(\theta) \approx \frac{1}{N \cdot \alpha^2} \sum_{i=1}^{N} \mathbb{E}_\epsilon \left[\|v_\epsilon\|^2 \left(l_i(\theta + \alpha \frac{v_\epsilon}{\|v_\epsilon\|}) - l_i(\theta) \right)^2 \right], \tag{39}$$

where $v_\epsilon \equiv \sum_{k=1}^{m'} \frac{\epsilon_k}{\sqrt{\lambda_k + \eta}} \Delta\theta_k$ is a perturbation vector with $\eta \geq 0$ included for numerical stability.

G.2.2 Data sets, models, and hyperparameters

For the toy examples in Section 4.1, we consider classifying two-dimensional synthetic data generated from mixtures of three Gaussians. As shown in Figure 7, we assign distinct labels for each Gaussian for training data. Test data are labeled analogously to the training data. For poison data, we assign labels different from training and test data for each Gaussian by randomly choosing labels for each data among the other two labels. We sample 60 data for each training, test, and poison data.

(a) Training data   (b) Test data   (c) Poison data

Figure 7: Data used in the experiments in Section 4.1.

A six-layer fully connected neural network with 100-dimensional hidden units and hyperbolic tangent (Tanh) activation functions is used for the experiments. We use a learning rate of 0.1 and a batch size of 30 for both SGD with and without regularization. The hyperparameters for regularization are set as $\alpha = 0.5, \tilde{\rho} = \rho/\alpha^2 = 2.0$, and $\eta = 0.01$. We use the top three eigenvalues and eigenvectors obtained from [47][3] for regularization and update them every 20 iterations.

For a better interpretation of the loss trajectory, we have smoothed the trajectory by averaging 20 consecutive loss values in Figures 4 (c) and (d).

G.3 MNIST and CIFAR-10/100

G.3.1 Approximations of the natural gradients

As mentioned in Section 4.2, it is required to approximate the natural gradient $F(\theta)^\dagger \left(\frac{\partial l}{\partial \theta} \right)^\top \in \mathbb{R}^m$ in (12) to regularize the mini-batch IGS. In this experiment, we consider an approximation based on the EKFAC method [13][4] to efficiently approximate the FIM and its (pseudo-)inverse. We devise three different methods for the approximation; the methods differ in detail from each other in terms of which labels are used to approximate the FIM or to calculate $\left(\frac{\partial l}{\partial \theta} \right)$ in the EKFAC method. The methods are classified as follows:

- In [20], they used sampled labels according to the probabilistic model that the neural network models with current parameters to approximate $F(\theta)$. We follow this idea and use sampled labels to approximate $F(\theta)$ and the original labels for $\left(\frac{\partial l}{\partial \theta} \right)$ in our first method denoted as **Ours 1** in Table 2.

- The second method uses original labels for both $F(\theta)$ and $\left(\frac{\partial l}{\partial \theta} \right)$ and is denoted as **Ours 2** in Table 2. This method can be considered as utilizing the empirical Fisher discussed in [23].

- The third method uses sampled labels for both $F(\theta)$ and $\left(\frac{\partial l}{\partial \theta} \right)$ and is denoted as **Ours 3** in Table 2. (The results from this method are reported in Table 1, and the method is denoted as **Ours** in the table.)

---

[3]URL: https://github.com/amirgholami/PyHessian (MIT license).
[4]URL: https://github.com/Thrandis/EKFAC-pytorch (MIT License).

The classification accuracies obtained from all of our regularization methods as well as SGD, SAM, and ASAM methods are reported in Table 2. All of our methods show superior performance to SGD, and the third method (Ours 3) shows the best performance among them for most of the considered settings.

Table 2: Classification accuracies for SGD, SAM, ASAM, and SGD with our regularization methods on MNIST, CIFAR-10, and CIFAR-100 data sets.

DATA SET	MODEL	SGD	GR	SAM	ASAM	OURS 1	OURS 2	OURS 3
MNIST	3FCN	98.13 ± 0.05	98.20 ± 0.01	98.62 ± 0.01	$\mathbf{98.65} \pm 0.07$	98.52 ± 0.05	98.56 ± 0.02	$\mathbf{98.65} \pm 0.03$
CIFAR-10	VGG11-BN	92.75 ± 0.11	93.13 ± 0.14	93.61 ± 0.08	93.78 ± 0.13	93.67 ± 0.10	93.74 ± 0.09	$\mathbf{93.81} \pm 0.06$
	RESNET-20	92.68 ± 0.20	93.05 ± 0.21	93.46 ± 0.11	$\mathbf{93.65} \pm 0.20$	93.42 ± 0.11	93.31 ± 0.03	93.40 ± 0.16
	RESNET-56	94.08 ± 0.17	94.40 ± 0.23	95.22 ± 0.11	$\mathbf{95.36} \pm 0.06$	95.08 ± 0.26	95.05 ± 0.08	94.96 ± 0.01
	WRN-16-4	95.37 ± 0.16	95.43 ± 0.11	96.19 ± 0.12	$\mathbf{96.37} \pm 0.18$	95.98 ± 0.04	96.04 ± 0.04	96.01 ± 0.10
	WRN-16-8	95.98 ± 0.03	96.15 ± 0.10	96.70 ± 0.14	$\mathbf{97.03} \pm 0.06$	96.67 ± 0.08	96.64 ± 0.02	96.57 ± 0.10
CIFAR-100	VGG11-BN	72.25 ± 0.17	73.05 ± 0.32	73.69 ± 0.20	73.61 ± 0.18	73.69 ± 0.16	73.64 ± 0.39	$\mathbf{74.24} \pm 0.22$
	RESNET-20	69.01 ± 0.54	70.00 ± 0.27	70.57 ± 0.30	$\mathbf{70.82} \pm 0.23$	70.75 ± 0.14	70.40 ± 0.58	70.63 ± 0.26
	RESNET-56	73.14 ± 0.10	74.67 ± 0.25	75.90 ± 0.25	75.87 ± 0.27	75.98 ± 0.25	75.91 ± 0.13	$\mathbf{76.07} \pm 0.11$
	WRN-16-4	77.18 ± 0.36	78.02 ± 0.21	79.64 ± 0.13	$\mathbf{79.97} \pm 0.11$	79.70 ± 0.10	79.57 ± 0.13	$\mathbf{79.97} \pm 0.07$
	WRN-16-8	80.55 ± 0.33	81.13 ± 0.06	82.20 ± 0.11	82.38 ± 0.09	81.95 ± 0.03	81.92 ± 0.42	$\mathbf{82.44} \pm 0.29$

G.3.2 Models and hyperparameters

A three-layer fully connected neural network with 200-dimensional hidden units and ReLU activation functions is used for the experiments using MNIST data. The neural network is trained with a learning rate of 0.1 and a batch size of 128 for 200 epochs.

For CIFAR-10/100 experiments, convolutional neural networks such as VGG [41], ResNet [15], and WideResNet [49] are used. The neural networks are trained with a batch size of 128 and a weight decay coefficient of 5e-4 for 200 epochs. We additionally apply data augmentation and label smoothing [29] methods, and the learning rates are scheduled according to the cosine annealing method [27] with the maximum learning rate of 0.1 and 10 epochs to warm up.

In approximating the natural gradient using the EKFAC method [13], we set the (Kronecker-factored) eigenbasis update frequency of 100 and 500 for the MNIST and CIFAR-10/100 experiments, respectively. We also apply the running average option in correcting the scaling of natural gradients. The hyperparameters for our regularization method are chosen among $\rho \in \{0.01, 0.02, 0.03, 0.05, 0.1\}$ for the MNIST experiments and $\rho \in \{0.001, 0.002, 0.003, 0.005, 0.01, 0.02\}$ for the CIFAR-10/100 experiments. To provide the sensitivity to the hyperparameter ρ of our method (the thrid one proposed in Appendix G.3.1), we have depicted the results under various choices of ρ in Figure 8. We consider the regularization coefficient $\rho \in \{5e-4, 0.001, 0.002, 0.003, 0.005, 0.01, 0.02, 0.03, 0.05\}$ for the squared gradient norm in the GR method [42]. We consider $\rho \in \{0.05, 0.1, 0.2, 0.3, 0.5, 1.0\}$ for the SAM method [12], and consider $\rho \in \{0.3, 0.5, 1.0, 2.0, 3.0, 5.0\}$ and $\eta = 0.01$ for the ASAM method [24], where the hyperparameters ρ and η are defined as in [12, 24].[5] We report the results obtained from hyperparameters showing the best test accuracy in Tables 1 and 2, where the results are averaged over trials from three different random seeds. Due to the space constraints, in Table 1 of the manuscript, we report only the results from VGG11-BN, ResNet-56, and WRN-16-8 for CIFAR-10/100 experiments and only the third method among the methods introduced in Appendix G.3.1.

Under our experimental settings, elapsed times per epoch (in seconds) during training for SGD/GR/SAM/ASAM/Ours are 1.68/3.50/3.60/3.85/5.70 in MNIST experiments. For CIFAR-10/100 experiments, those are 5.95/24.7/14.8/16.1/40.1 for VGG11-BN, 25.7/98.3/63.7/68.3/66.9 for ResNet-56, and 24.2/145/47.8/48.0/80.7 for WRN-16-8. Most of the experiments have been performed using NVIDIA Tesla V100 GPUs.

---

[5]URLs: https://github.com/SamsungLabs/ASAM (Apache License 2.0), https://github.com/davda54/sam (MIT license).

Figure 8: Test accuracies according to varying ρ.