POWDERWORLD: A PLATFORM FOR UNDERSTANDING GENERALIZATION VIA RICH TASK DISTRIBUTIONS

ABSTRACT

One of the grand challenges of reinforcement learning is the ability to generalize to new tasks. However, general agents require a set of rich, diverse tasks to train on. Designing a 'foundation environment' for such tasks is tricky – the ideal environment would support a range of emergent phenomena, an expressive task space, and fast runtime. To take a step towards addressing this research bottleneck, this work presents Powderworld, a lightweight yet expressive simulation environment running directly on the GPU. Within Powderworld, two motivating task distributions are presented, one for world-modelling and one for reinforcement learning. Each contains hand-designed test tasks to examine generalization. Experiments indicate that increasing the environment's complexity improves generalization for world models, yet causes reinforcement learning agents to struggle. Powderworld aims to support the study of generalization by providing a source of diverse tasks arising from the same core rules.

1 INTRODUCTION

One of the grand challenges of reinforcement learning (RL), and of decision-making in general, is the ability to generalize to new tasks. RL agents have shown incredible performance on single task settings (Berner et al., 2019; Lillicrap et al., 2015; Mnih et al., 2013), yet frequently stumble when presented with unseen challenges. Single-task RL agents are largely overfit on the tasks they are trained on (Kirk et al., 2021), limiting their practical use. In contrast, a general agent, which can robustly perform well on a wide range of novel tasks, can then be adapted to solve downstream tasks and unseen challenges.

General agents greatly depend on a diverse set of tasks to train on. Recent progress in deep learning has shown that as the amount of data increases, so do generalization capabilities of trained models (Brown et al., 2020; Ramesh et al., 2021; Bommasani et al., 2021; Radford et al., 2021). Agents trained on environments with domain randomization or procedural generation capabilities transfer better to unseen test tasks Cobbe et al. (2020); Tobin et al. (2017); Risi & Togelius (2020); Khalifa et al. (2020). However, as creating training tasks is expensive and challenging, most standard environments are inherently over-specific or limited by their focus on a single task type, e.g. robotic control or gridworld movement.

As the need to study the relationships between training tasks and generalization increases, the RL community would benefit greatly from a 'foundation environment' supporting diverse tasks arising from the same core rules. The benefits of expansive task spaces have been showcased in Unsupervised Environment Design (Wang et al., 2019; Dennis et al., 2020; Jiang et al., 2021; Parker-Holder et al., 2022), but gridworld domains fail to display how such methods scale up. Previous works have proposed specialized task distributions for multi-task training (Samvelyan et al., 2021; Suarez et al., 2019; Fan et al., 2022; Team et al., 2021), each focusing on a specific decision-making problem. To further investigate generalization, it is beneficial to have an environment where many variations of training tasks can easily be compared.

As a step toward lightweight yet expressive environments, this paper present Powderworld, a simulation environment geared to support procedural data generation, agent learning, and multi-task generalization. Powderworld aims to efficiently provide environment dynamics by running directly on the GPU. Elements (e.g. sand, water, fire) interact in a modular manner within local neighborhoods, allowing for efficient runtime. The free-form nature of Powderworld enables construction of

Build an Arch   Transport Sand   Freeze a Path   Burn the Gas

Figure 1: **Examples of tasks created in the Powderworld engine.** Powderworld provides a physics-inspired simulation over which many distributions of tasks can be defined. Pictured above are human-designed challenges where a player must construct unstable arches, transport sand through a tunnel, freeze water to create a bridge, and draw a path with plants. Tasks in Powderworld creates challenges from a set of core rules, allowing agents to learn generalizable knowledge.

a tasks ranging from simple manipulation objectives to complex multi-step goals. Powderworld aims to 1) be modular and supportive of emergent interactions, 2) allow for expressive design capability, and 3) support efficient runtime and representations.

Additionally presented are two motivating frameworks for defining world-modelling and reinforcement learning tasks within Powderworld. World models trained on increasingly complex environments show superior transfer performance. In addition, models trained over more element types show greater capacity to fine-tune on novel environments. In the reinforcement learning case, performance scales with the numbers of training tasks, however increases in task complexity harms learning, which may be due to instability in the resulting reward signal. These findings provide a starting point for future directions in studying generalization using Powderworld as a foundation.

2 RELATED WORK

Task Distributions for RL. Video games are a popular setting for studying multi-task RL, and environments have been built off NetHack (Samvelyan et al., 2021; Küttler et al., 2020), Minecraft (Fan et al., 2022; Johnson et al., 2016; Guss et al., 2019), Doom (Kempka et al., 2016), and Atari (Bellemare et al., 2013). Team et al. (2021); Yu et al. (2020); Cobbe et al. (2020) describe task distributions focused on meta-learning, and Fan et al. (2022); Suarez et al. (2019); Hafner (2021); Perez-Liebana et al. (2016) detail more open-ended environments containing multiple task types. Most similar to this work may be ProcGen (Cobbe et al., 2020), a platform that supports infinite procedurally generated environments. However, while ProcGen games each have their own rulesets, Powderworld aims to share core rules across all tasks. Powderworld focuses specifically on runtime and expressivity, taking inspiration from online "powder games" where players build ranges of creations out of simple elements (bal; pow; Bittker).

Generalization in RL. Multi-task reinforcement learning agents are generally valued for their ability to perform on unseen training tasks (Packer et al., 2018; Kirk et al., 2021). The sim2real problem requires agents aim to generalize to out-of-distribution real world domains (Tobin et al., 2017; Sadeghi & Levine, 2016). The platforms cited above also target generalization, often within the context of solving unseen levels within a game. This work aims to study generalization within a physics-inspired simulated setting, and creates out-of-distribution challenges by hand-designing a set of unseen test tasks.

3 POWDERWORLD ENVIRONMENT

The main contribution of this work is an environment specifically for training generalizable agents over easily customizable distributions of tasks. Powderworld is designed to feature:

- **Modularity and support for emergent phenomena.** The core of Powderworld is a set of fundamental rules defining how two neighboring elements interact. The consistent nature

Figure 2: **Powderworld runs on the GPU and can simulate many worlds in parallel.** GPU simulation provides a significant speedup and allows simulation time to scale with batch size. World size can be increased to simulate more elements in a single world. Simulation speed is limited largely by the memory of the GPU, as shown in the right graph.

> of these rules is key to agent generalization; e.g. fire will always burn wood, and agents can learn these inherent properties of the environment. Furthermore, local interactions can build up to form emergent wider-scale phenomena, e.g. fire spreading throughout the world. This capacity for emergence enables tasks to be diverse yet share consistent properties. Thus, fundamental Powderworld priors exist that agents can take advantage of to generalize.

- **Expressive task design capability.** A major challenge in the study of RL generalization is that tasks are often static and nonadjustable. Instead, an ideal environment should present an explorable space of tasks, capable of representing interesting challenges, goals, and constraints. Tasks should be parametrized in a way that allows for automated design and interpretable control. Powderworld represents each task as a 2D array of elements, enabling a variety of procedural generation methods. There are also many ways to test a specific agent capability, e.g. "burn plants to create a gap", increasing the chance that agents encounter these challenges.

- **Fast runtime and representation.** As multi-task learning can be computationally expensive, it is important that the underlying environment runs efficiently. Powerworld is designed to run on the GPU, enabling large batches of simulation to be run in parallel. Additionally, Powderworld employs a neural-network-friendly matrix representation for both task design and agent observations. To simplify the training of decision-making agents, the Powderworld representation is fully-observable and runs on a discrete timescale (but partial-observability is an easy modification if desired).

3.1 ENGINE

Described below is an overview of the engine used for the Powderworld simulator. Additional technical details can be founded in the Appendix.

World matrix. The core structure of Powderworld is a matrix of elements W representing the world. Each location $W_{x,y}$ holds a vector of information representing that location in the world. Namely, each vector contains a one-hot encoding of the occupying element, plus additional values indicating gravity, density, and velocity. The W matrix is a Markovian state of the world, and thus past W matrices are unnecessary for state transitions. Every timestep, a new W matrix is generated via a stochastic update function, as described below.

Gravity. Certain elements are affected by gravity, as noted by the IsGravity flag in Figure 3. Each gravity-affected element also holds a density value, which determines the element's priority during the gravity calculation. Every timestep, each element checks with its neighbor below. If both elements are gravity-affected, and the neighbor below has a lower density, then the two elements swap positions. This interaction functions as a core rule in the Powderworld simulation and allows elements to stack, displace, and block each other.

Element-specific reactions. The behavior of Powderworld arises from a set of modular, local element reactions. Element reactions can occur either within a single element, or as a reaction when two elements are neighbors to each other. These reactions are designed to facilitate larger-scale behaviors; e.g. the sand element falls to neighboring locations, thus areas of sand form pyramid-

Figure 3: **A list of elements and reactions in the Powderworld simulation.** Elements each contain gravity and density information. A set of element-specific reactions dictates how each element behaves and reacts to neighbors. Certain reactions manipulate the world's velocity field, which can push further elements away. Together, the gravity, velocity, and reaction systems create a core set of rules by which interesting simulations arise.

like structures. Elements such as water, gas, and lava are fluids, and move horizontally to occupy available space. Finally, pairwise reactions provide interactions between specific elements, e.g. fire spreads to flammable elements, and plants grow when water is nearby. See Figure 3 for a description of the Powderworld reactions, and full documentation is given in the appendix and code.

Velocity system. Another interaction method is applying movement through the velocity system. Certain reactions, such as fire burning or dust exploding, add to the velocity field. Velocity is represented via an two-component $V_{x,y}$ vector at each world location. If the magnitude of the velocity field at a location is greater than a threshold, elements are moved in one of eight cardinal directions, depending on the velocity angle. Velocity naturally diffuses and spreads in its own direction, thus a velocity difference will spread outwards before fading away. Walls are immune to velocity affects. Additionally, the velocity field can be directly manipulated by an interacting agent.

All operators are local and translation equivariant, yielding a simple implementation in terms of (nonlinear) convolutional kernels. To exploit GPU-optimized operators, Powderworld is implemented in Pytorch (Paszke et al., 2019), and performance scales with GPU capacity (Figure 2).

4 EXPERIMENTS

The following section presents a series of motivating experiments showcasing task distributions within Powderworld. These tasks intend to provide two frameworks for accessing the richness of the Powderworld simulation, one through supervised learning and one through reinforcement learning. While these tasks aim to specifically highlight how Powderworld can be used to generate diverse task distributions, the presented tasks are by no means exhaustive, and future work may easily define modifications or additional task objectives as needed.

In all tasks, the model is provided the $W \in \mathbb{R}^{H \times W \times 20}$ matrix as an observation, which is a Markovian state containing element, gravity, density, and velocity information. All task distributions also include a procedural generation algorithm for generating training tasks, as well as human-designed test tasks used to measure transfer learning.

In all the experiments below, we evaluate on the out-of-distribution hand-designed test tasks shown in Figure 4 and Figure 9.

4.1 WORLD MODELLING TASK

This section examines a world-modelling objective in which a neural network is given an observation of the world, and must then predict a future observation. World models can be seen as learning how to encode an environment's dynamics, and have proven to hold great practical value in downstream decision making (Ha & Schmidhuber, 2018; Hafner et al., 2019b;a). A model which can correctly predict the future of any observation can be seen as thoroughly understanding the core rules of the environment. The world-modelling task does not require reinforcement learning, and is instead solved via a supervised objective with the future state as the target.

Figure 4: **World modelling test tasks are designed to showcase specific element interactions.** Test tasks are out-of-distribution and unseen during training, but follow the same rules as training tasks. The generalization capability of a world model is measured by how accurate its future predictions are on all eight tasks. Shown are starting and ending states of the test tasks, each focused on a certain emergent interaction.

Figure 5: **World model generalization improves as the number of training tasks is increased.** Shown are the test performances of world models trained with data from 10 tasks, 100 tasks, 1000 tasks, etc. Models trained on less data show greater instability, as observed by the spikes in test loss. Right: Comparison of world model predictions on a test task.

Specifically, given an observation $W^0 \in \mathbb{R}^{H \times W \times N}$ of the world, the agent is tasked with generating a $W' \in \mathbb{R}^{H \times W \times N}$ matrix of the world 8 timesteps in the future. W' values corresponds to logit probabilities of the N different elements, and loss is computed via cross-entropy between the true and predicted world. Tasks are represented by a tuple of starting and ending observations.

Tasks for the world-modelling task are created via an parametrized procedural generation algorithm. The algorithm synthesizes starting states by randomly selecting elements and drawing a series of lines, circles, and squares. Thus, the training task distribution can be modified by specifying how many of each shape to draw, out of which elements, and how many total training tasks should be generated. A set of hand-designed test tasks are provided as shown in Figure 4 which each test a distinct property of Powderworld, e.g. simulate sand falling through water, fire burning a vine, or gas flowing upwards. To generate the targets, each world is simulated forward a total of 128 steps, broken into 16 observations spaced 8 timesteps apart. This results in 15 training pairs per simulation.

The model is a convolutional U-net network (Ronneberger et al., 2015), operating over a world size of 64x64 and 14 distinct elements. The agent network consists of three U-net blocks with 32, 64, and 128 features respectively. Each U-net block contains two convolutional kernels with a kernel size of three and ReLU activation, along with a MaxPool layer in the encoder blocks. The model is trained with Adam for 5000 iterations with a batch size of 256 and learning rate of 0.005. During training, a replay buffer of 1024*256 data points is randomly sampled to form the training batch, and the oldest data points are rotated out for fresh examples generated via the Powderworld simulator.

4.1.1 CAN WORLD MODELS TRAINED ON MANY TASKS GENERALIZE TO UNSEEN TEST CHALLENGES?

A starting experiment examines whether world models trained purely on simulated data can correctly generalize to solving hand-designed test tasks. The set of test tasks, as shown in Figure 4, are out-

Figure 6: **Increasing environment complexity by including additional shapes improves transfer performance.** World models trained on tasks including lines, circles, and squares create diversity, enabling generalization to unseen tasks. Right: Sampled tasks generated with varying types of shapes.

of-distribution hand-designed worlds that do not appear in the training set. A world model must discover the core ruleset of environmental dynamics in order to successfully generalize.

Scaling laws for training large neural networks have shown that more data and larger model sizes help improve performance (Kaplan et al., 2020; Zhai et al., 2022). Figure 5 shows this observation to be true in this domain as well; world models trained on increasing amounts of training data display higher performance on a set of test tasks. In this case, tasks are defined as initial states for generating simulated data. A world model trained on 10 training tasks would therefore only observations generated from 10 initial states. Each world model is trained on the same number of training examples and for the same amount of timesteps, the only difference is how this data is generated. Runs are trained for three trials and the average test loss over training time is displayed.

Results show that the 10-task world model overfits and does not generalize to the test tasks. In contrast, the 100-task model achieves much higher test accuracy, and the trend continues as the number of training tasks improves. Note that each run trains on 10x more data as the previous, and there are diminishing returns for further increases training data. These results show that the Powderworld world-modelling task demonstrates similar scaling laws as real-world data.

4.1.2 How do increasingly complex training tasks affect generalization?

The previous section shows that more data help improve performance, however, how does performance change as the underlying distribution of training data changes? Specifically, as the training data expands to include more varieties of starting states, does world model performance over a set of test tasks improve? More complex training data may allow world models to learn more robust representations, but may also introduce variance which harms learning or create degenerate training examples when many elements overlap.

Figure 6 displays how as additional shapes are included within the training distribution, zero-shot test performance successfully increases. World models are trained on distributions of training tasks characterized by which shapes are present between lines, circles, and square. Lines are assigned a random (X^1, Y^1), (X^2, Y^2), and thickness. Circles and Squares are assigned a random (X^1, Y^1) along with a radius. Each shape is filled in with a randomly selected element, and for each shape, a random amount between 0 and 5 are drawn. Interestingly, training tasks with less shape variation also display higher instability, as shown in the test loss spikes for Line-only, Circle-only, and Square-only runs. This behavior may indicate that models trained over more diverse training data learn representations which are more resistant to perturbations.

Figure 7 also highlights the benefits of increasing complexity, this time along a different axis. In this experiment, only lines are drawn into the starting state, with the maximum number of lines varied per run. World models operating over training distributions with a greater number of lines display higher test performance. Combined with Figure 6, results showcase how in Powderworld, as more diverse data is created from the same set of core rules, world models become stronger in their ability to solve related yet novel tasks.

Figure 7: **Training on environments with more lines results in stronger generalization.** Models are trained on environments with varying numbers of lines, then evaluated on test tasks. In each task, a random number of lines are drawn up to the maximum specified. A higher number of lines increases the diversity of the training distribution, but may also create destructive reactions.

Figure 8: **World models trained on more elements showcase better performance when fine-tuned on novel elements.** When transferring to an environment containing three held-out elements (gas, stone, acid), models exposed to more elements during training perform better. These results show that Powderworld provides a rich enough simulation that world models learn robust representations capable of adaptation. The richer the simulation, the stronger these representations become.

4.1.3 DOES ENVIRONMENT RICHNESS INFLUENCE TRANSFER TO NOVEL ELEMENTS?

A final world-modelling experiment examines whether world models can adapt to unseen elemental interactions. This task requires more than accuracy: A perfect world model will always correctly predict the future from any starting state, however there are no guarantees the model will easily learn new dynamics. This experiment therefore tests the adaptability of the learned representation of the world, by examining if the world models can quickly learn from new information.

Powderworld's ruleset is also of importance, as models will only transfer to new elements if elements share fundamental similarities that can be learned. Powderworld elements naturally share a set of behaviors, e.g. gravity, reactions-on-contact, and velocity. Thus, this experiment measures whether Powderworld presents a rich enough simulation that models can generalize to new *rules* within the environment.

To run the experiment, distinct world models are trained on distributions containing a limited set of elements. The 1-element model sees only sand, the 2-element sees only sand and water, the 3-element sees sand, water, and wall, and so on. Worlds are generated via the same procedural generation algorithm, specifically up to 5 lines are drawn. After training for the standard 5000 iterations, each world model is then fine-tuned for 100 iterations on a training distribution containing three held-out elements: gas, stone, and acid. The world model loss is then measured on a new environment containing only these three elements (sampled from the test suite in Figure 4).

Figure 8 highlights how world models trained on increasing numbers of elements show greater performance when fine-tuned on a set of unseen elements. These results indicate that world models trained on richer simulations also develop more robust representations, as these representations can more easily be trained on additional information. In other words, Powderworld world models learn not only the core rules of the world, but also general features describing those rules, that can then be used to learn new rules.

Move Forward	Blocking Wall	Diagonal Path	Up and Over	Inside Water	Plant/Lava Wall	Stone Wall	Lava Corridor

Figure 9: **The Sand-Pushing task domain highlights a range of agent skills.** A robust agent must interact with the world in a variety of ways to maneuver sand into the goal. The above test tasks each measure a specific skill, such as pushing sand around a wall, dealing with sand submerged in water, or removing a plant wall by setting it on fire.

Figure 10: **An agent creating wind to push sand towards the goal.** In the Sand-Pushing task, wind (shown in yellow/purple) is used to push a block of sand elements (shown in red) between obstacles to reach the goal slot on the right. Tasks are randomly generated via a procedural algorithm.

5 REINFORCEMENT LEARNING TASK: SAND-PUSHING

The Sand-Pushing environment is an RL environment where agents must move sand particles into a goal slot. The observation space contains the Powderworld world state $W \in \mathbb{R}^{64 \times 64 \times 20}$, and the action space defines the position and velocity to produce wind at (X, Y, V_x, V_y). By producing wind, agents interact with the velocity field, allowing them to push and move elements around. Wind affects the velocity field in a 10x10 area around the specified position. Reward equals the number of sand elements within the goal slot, and episodes are run for 64 timesteps.

To learn to control in this environment, a Stable Baselines 3 PPO agent (Raffin et al., 2021; Schulman et al., 2017) is trained over 2,500,000 environment interactions. The agent model is comprised of two convolutional layers with feature size 32 and 64 and kernel size of three, followed by two fully-connected layers. A learning rate of 0.0003 is used, along with a batchsize of 256. An off-the-shelf RL algorithm is intentionally chosen, so experiments can focus on the impact of training tasks.

Figure 10 highlights an agent pushing sand into the goal slot. Note that wind and velocity affect all elements present, so an agent must be careful to only push only the sand. Training tasks for the Sand-Pushing environment are generated using the same procedural generation algorithm as the world-modelling task, with the addition of an initial block of sand as well as a goal slot. A set of hand-designed test tasks (Fig 9) are presented to test various skills that a robust agent may learn.

As displayed in Figure 11 (Left), agents trained on a distribution of Sand-Pushing tasks can successfully generalize to the test tasks, as long as the training distribution is large enough. Similarly to world-modelling, a minimum number of training tasks is required to see generalization. However, in the RL case, agents trained on even larger numbers of training tasks still display similar levels of performance. This observation may suggest that RL representations are simple enough that additional data is unnecessary, or that reward-based learning fails to fully utilize expressive data.

Figure 11 (Right) shows that unlike in world-modelling, increased complexity on RL tasks decreases test performance. This difference may arise from RL's need for exploration as well as its sensitivity to variance. Due to these factors, RL is highly dependent on early reward signal in order to correctly continue to explore and improve performance. RL agents trained on complex tasks also show lower validation reward, displaying that agent learning suffers with complexity (Figure 12). Additional complexity in training tasks may result in a noisy reward signal which harms agent learning.

The difference in how complexity affects training in Powderworld world-modelling and reinforcement learning highlights a motivating platform for further investigation. While baseline RL methods fail to scale with additional complexity and instead suffer due to variance, alternative learning techniques may better handle the learning problem and show higher generalization.

Figure 11: **Left: Agents trained on larger numbers of training tasks achieve higher test reward.** While there is negligible difference at larger numbers, agents require a baseline number of training tasks to generalize without overfitting. **Right: In contrast to the world-modelling results, increasing complexity in the reinforcement learning harms performance.** Reinforcement learning methods are sensitive to variance, and high-complexity tasks may inhibit the reward signal to an extent that agents struggle to correctly learn.

Figure 12: **Test vs. Validation show opposite correlations in world-modelling and RL.** Plotted are test and validation scores on models trained over increasing environment complexity (# of lines). Validation scores are computed on tasks sampled from the training distribution. Both world models and RL agents achieve worse validation scores on environments with higher complexity. However, high-complexity world models show increased generalization to test tasks, whereas high-complexity RL agents fail on both validation and test tasks. RL agents may suffer from learning issues in high-complexity environments, leading to general failure.

6 CONCLUSION

Generalizing to novel unseen tasks is one of the grand challenges of reinforcement learning. Consistent lessons in deep learning show that *training data* is of crucial importance, which in the case of RL is training tasks. To study how and when agents generalize, the research community will benefit from more expressive foundation environments supporting many tasks arising from the same core rules.

This work introduced Powderworld, an expressive simulation environment that can generate both supervised and reinforcement learning task distributions. Powderworld's ruleset encourages modular interactions and emergent phenomena, resulting in world models which can accurately predict unseen states and even adapt to novel elemental behaviors. Experimental results show that while increased task complexity helps in the supervised world-modelling setting, complexity hampers the performance of a standard RL agent.

Powderworld is built to encourage future research endeavors, providing a rich yet computationally efficient backbone for defining tasks and challenges. The provided experiments hope to showcase how Powderworld can be used as a platform for examining task complexity and agent generalization. Future work may use Powderworld as an environment for studying open-ended agent learning, unsupervised environment design techniques, or other directions. As such, all code for Powderworld is released online in support of extensions.

REFERENCES

Physics simulation game: Powder game. URL `https://dan-ball.jp/en/javagame/dust/`.

Marc G Bellemare, Yavar Naddaf, Joel Veness, and Michael Bowling. The arcade learning environment: An evaluation platform for general agents. *Journal of Artificial Intelligence Research*, 47: 253–279, 2013.

Christopher Berner, Greg Brockman, Brooke Chan, Vicki Cheung, Przemysław Debiak, Christy Dennison, David Farhi, Quirin Fischer, Shariq Hashme, Chris Hesse, et al. Dota 2 with large scale deep reinforcement learning. *arXiv preprint arXiv:1912.06680*, 2019.

Max Bittker. Making sandspiel. URL `https://maxbittker.com/making-sandspiel`.

Rishi Bommasani, Drew A Hudson, Ehsan Adeli, Russ Altman, Simran Arora, Sydney von Arx, Michael S Bernstein, Jeannette Bohg, Antoine Bosselut, Emma Brunskill, et al. On the opportunities and risks of foundation models. *arXiv preprint arXiv:2108.07258*, 2021.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901, 2020.

Karl Cobbe, Chris Hesse, Jacob Hilton, and John Schulman. Leveraging procedural generation to benchmark reinforcement learning. In *International conference on machine learning*, pp. 2048–2056. PMLR, 2020.

Michael Dennis, Natasha Jaques, Eugene Vinitsky, Alexandre Bayen, Stuart Russell, Andrew Critch, and Sergey Levine. Emergent complexity and zero-shot transfer via unsupervised environment design. *Advances in neural information processing systems*, 33:13049–13061, 2020.

Linxi Fan, Guanzhi Wang, Yunfan Jiang, Ajay Mandlekar, Yuncong Yang, Haoyi Zhu, Andrew Tang, De-An Huang, Yuke Zhu, and Anima Anandkumar. Minedojo: Building open-ended embodied agents with internet-scale knowledge. *arXiv preprint arXiv:2206.08853*, 2022.

William H Guss, Cayden Codel, Katja Hofmann, Brandon Houghton, Noburu Kuno, Stephanie Milani, Sharada Prasanna Mohanty, Diego Perez Liebana, Ruslan Salakhutdinov, Nicholay Topin, et al. The minerl competition on sample efficient reinforcement learning using human priors. 2019.

David Ha and Jürgen Schmidhuber. Recurrent world models facilitate policy evolution. *Advances in neural information processing systems*, 31, 2018.

Danijar Hafner. Benchmarking the spectrum of agent capabilities. *arXiv preprint arXiv:2109.06780*, 2021.

Danijar Hafner, Timothy Lillicrap, Jimmy Ba, and Mohammad Norouzi. Dream to control: Learning behaviors by latent imagination. *arXiv preprint arXiv:1912.01603*, 2019a.

Danijar Hafner, Timothy Lillicrap, Ian Fischer, Ruben Villegas, David Ha, Honglak Lee, and James Davidson. Learning latent dynamics for planning from pixels. In *International conference on machine learning*, pp. 2555–2565. PMLR, 2019b.

Minqi Jiang, Edward Grefenstette, and Tim Rocktäschel. Prioritized level replay. In *International Conference on Machine Learning*, pp. 4940–4950. PMLR, 2021.

Matthew Johnson, Katja Hofmann, Tim Hutton, and David Bignell. The malmo platform for artificial intelligence experimentation. In *Ijcai*, pp. 4246–4247. Citeseer, 2016.

Jared Kaplan, Sam McCandlish, Tom Henighan, Tom B Brown, Benjamin Chess, Rewon Child, Scott Gray, Alec Radford, Jeffrey Wu, and Dario Amodei. Scaling laws for neural language models. *arXiv preprint arXiv:2001.08361*, 2020.

Michał Kempka, Marek Wydmuch, Grzegorz Runc, Jakub Toczek, and Wojciech Jaśkowski. Vizdoom: A doom-based ai research platform for visual reinforcement learning. In *2016 IEEE conference on computational intelligence and games (CIG)*, pp. 1–8. IEEE, 2016.

Ahmed Khalifa, Philip Bontrager, Sam Earle, and Julian Togelius. Pcgrl: Procedural content generation via reinforcement learning. In *Proceedings of the AAAI Conference on Artificial Intelligence and Interactive Digital Entertainment*, volume 16, pp. 95–101, 2020.

Robert Kirk, Amy Zhang, Edward Grefenstette, and Tim Rocktäschel. A survey of generalisation in deep reinforcement learning. *arXiv preprint arXiv:2111.09794*, 2021.

Heinrich Küttler, Nantas Nardelli, Alexander Miller, Roberta Raileanu, Marco Selvatici, Edward Grefenstette, and Tim Rocktäschel. The nethack learning environment. *Advances in Neural Information Processing Systems*, 33:7671–7684, 2020.

Timothy P Lillicrap, Jonathan J Hunt, Alexander Pritzel, Nicolas Heess, Tom Erez, Yuval Tassa, David Silver, and Daan Wierstra. Continuous control with deep reinforcement learning. *arXiv preprint arXiv:1509.02971*, 2015.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Alex Graves, Ioannis Antonoglou, Daan Wierstra, and Martin Riedmiller. Playing atari with deep reinforcement learning. *arXiv preprint arXiv:1312.5602*, 2013.

Charles Packer, Katelyn Gao, Jernej Kos, Philipp Krähenbühl, Vladlen Koltun, and Dawn Song. Assessing generalization in deep reinforcement learning. *arXiv preprint arXiv:1810.12282*, 2018.

Jack Parker-Holder, Minqi Jiang, Michael Dennis, Mikayel Samvelyan, Jakob Foerster, Edward Grefenstette, and Tim Rocktäschel. Evolving curricula with regret-based environment design. *arXiv preprint arXiv:2203.01302*, 2022.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, high-performance deep learning library. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 32*, pp. 8024–8035. Curran Associates, Inc., 2019. URL `http://papers.neurips.cc/paper/9015-pytorch-an-imperative-style-high-performance-deep-learning-library.pdf`.

Diego Perez-Liebana, Spyridon Samothrakis, Julian Togelius, Tom Schaul, and Simon M Lucas. General video game ai: Competition, challenges and opportunities. In *Thirtieth AAAI conference on artificial intelligence*, 2016.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International Conference on Machine Learning*, pp. 8748–8763. PMLR, 2021.

Antonin Raffin, Ashley Hill, Adam Gleave, Anssi Kanervisto, Maximilian Ernestus, and Noah Dormann. Stable-baselines3: Reliable reinforcement learning implementations. *Journal of Machine Learning Research*, 2021.

Aditya Ramesh, Mikhail Pavlov, Gabriel Goh, Scott Gray, Chelsea Voss, Alec Radford, Mark Chen, and Ilya Sutskever. Zero-shot text-to-image generation. In *International Conference on Machine Learning*, pp. 8821–8831. PMLR, 2021.

Sebastian Risi and Julian Togelius. Increasing generality in machine learning through procedural content generation. *Nature Machine Intelligence*, 2(8):428–436, 2020.

Olaf Ronneberger, Philipp Fischer, and Thomas Brox. U-net: Convolutional networks for biomedical image segmentation. In *International Conference on Medical image computing and computer-assisted intervention*, pp. 234–241. Springer, 2015.

Fereshteh Sadeghi and Sergey Levine. Cad2rl: Real single-image flight without a single real image. *arXiv preprint arXiv:1611.04201*, 2016.

Mikayel Samvelyan, Robert Kirk, Vitaly Kurin, Jack Parker-Holder, Minqi Jiang, Eric Hambro, Fabio Petroni, Heinrich Küttler, Edward Grefenstette, and Tim Rocktäschel. Minihack the planet: A sandbox for open-ended reinforcement learning research. *arXiv preprint arXiv:2109.13202*, 2021.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Joseph Suarez, Yilun Du, Phillip Isola, and Igor Mordatch. Neural mmo: A massively multiagent game environment for training and evaluating intelligent agents. *arXiv preprint arXiv:1903.00784*, 2019.

Open Ended Learning Team, Adam Stooke, Anuj Mahajan, Catarina Barros, Charlie Deck, Jakob Bauer, Jakub Sygnowski, Maja Trebacz, Max Jaderberg, Michael Mathieu, et al. Open-ended learning leads to generally capable agents. *arXiv preprint arXiv:2107.12808*, 2021.

Josh Tobin, Rachel Fong, Alex Ray, Jonas Schneider, Wojciech Zaremba, and Pieter Abbeel. Domain randomization for transferring deep neural networks from simulation to the real world. In *2017 IEEE/RSJ international conference on intelligent robots and systems (IROS)*, pp. 23–30. IEEE, 2017.

Rui Wang, Joel Lehman, Jeff Clune, and Kenneth O Stanley. Paired open-ended trailblazer (poet): Endlessly generating increasingly complex and diverse learning environments and their solutions. *arXiv preprint arXiv:1901.01753*, 2019.

Tianhe Yu, Deirdre Quillen, Zhanpeng He, Ryan Julian, Karol Hausman, Chelsea Finn, and Sergey Levine. Meta-world: A benchmark and evaluation for multi-task and meta reinforcement learning. In *Conference on robot learning*, pp. 1094–1100. PMLR, 2020.

Xiaohua Zhai, Alexander Kolesnikov, Neil Houlsby, and Lucas Beyer. Scaling vision transformers. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 12104–12113, 2022.

Figure 13: **The Powderworld Web GUI allows users to directly edit the state of a world by drawing on various elements.** World states can be generated at custom resolutions, and the simulation runs in real-time. Powderworld runs on a GPU server, with the web app acting only as a display and controller.

A APPENDIX

A.1 POWDERWORLD ENGINE

Described in this section is an overview of the technical details of the Powderworld Engine. We provide these details 1) as a reference for future work built on top of Powderworld, and 2) as a framework for building simulations and environments that run on the GPU. Powderworld is designed to run as fast as possible on a standard GPU environment, as many deep learning setups already support GPU access. Thus, Powderworld interacts with the GPU through Pytorch functions.

Data Representation. The state in Powderworld is represented as a BxHxWxN size tensor. One benefit of running on the GPU is that multiple simulations can be run in parallel, therefore all functions in Powderworld are written to support *batches* of data. The other dimensions refer to height and width, along with an N-size vector representing the data stored in each location. This data is specifically a one-hot vector of the current element at the location, along with indices dictating gravity, density, flow state, and velocity.

Matrix Operations. To remain efficient and parallalizable, operations in Powderworld are not implemented as loops over XY space, but rather as series of matrix operations. For example, to simulate the world falling down one block, one can call the following function:

```
world[:] = torch.roll(world, shifts=1, dims=2)
```

In the codebase, there are helper functions for shifting the world each of four directions: getBelow, getAbove, getLeft, getRight. These functions are called frequently and used to build up more complex operations.

Additionally, since operations need to occur over the entire world matrix, to modify specific portions of the matrix we must construct a mask. We can do this by doing any kind of comparison over values in the world matrix, then setting the world matrix to a weighted sum of world = (world*(1-mask) + newWorld*mask). For example, to change all fire elements into water elements, the following pseudocode works:

```
// Transform fire into water.
mask = (world[:, fire_index] == 1)
world[:] = world*(1-mask) + water_vec*(mask)
```

Gravity. In Powderworld, each element has a Density and an IsGravity flag. These values are stored in the 1st and 2nd indicies of the world array. Gravity operates as a series of switches: if an element is above another element and the top element has greater density, and both elements are gravity-enabled, then the two elements swap. As a baseline, empty space (Air) has a density of 1,

thus elements like Sand (density=2) will fall, and elements such as Gas (density=0) will rise. The IsGravity flag is necessary to prevent elements from falling through stationary elements such as wall or wood, which should remain static. Gravity handles only vertical swaps, and in combination with other behaviors creates the piling and flowing mechanics seen in sand and water.

One crucial component of the gravity procedure is that due to the nature of switching, two elements cannot attempt to switch into the same position. Swaps are performed simultaneously, and a swap involves setting the upper position to the lower element, and vice versa. If two elements swap into the same position, then that position will be written to twice, and the original element will duplicate itself above and below. Therefore, all swap operations must be sure to never swap two elements into the same position. To solve this in the gravity case, we iterate gravity as a loop over the possible densities. If all densities were computed together, a vertical stack of densities [0,1,2] would result in the elements with densities of 0 and 2 both attempting to move into the center position. By processing downward swaps for each density iteratively, an order is established and the conflict does not occur (in the example provided, 0 would first swap with 1, and then 0 would swap with 2 in the following iteration.

```
// Run gravity.
for currDensity in [0,1,2,3]:
{
density = world[:, density_index]
# Delta between ABOVE and current
density_delta = get_above(density) - density
is_density_above_greater = (density_delta > 0)
# If BELOW has density_above_greater, then density_below_less
is_density_below_less = get_below(is_density_above_greater)
is_density_current = (density == currDensity)
is_density_above_current = get_above(is_density_current)
is_gravity = (world[:, gravity_index] == 1)
is_center_and_below_gravity = get_below(is_gravity) & is_gravity
is_center_and_above_gravity = get_above(is_gravity) & is_gravity

world_above = get_above(world)
world_below = get_below(world)
world[:] = world[:]*(1-does_become_below-does_become_above)
    + world_below*does_become_below + world_above*does_become_above
}
```

Sand-Piling. Both the sand and dust elements display additional behavior when falling. These elements cannot support themselves upright, and if there is an empty space to their bottom-left or bottom-right then the element will fall into that location. In practice, this means that the sand elements form stable pyramids and hills.

To implement the sand-piling behavior, we check if each element is a sand-type (sand or dust), then if either the bottom-left or bottom-right space is a lower density, the two elements swap. To prevent ambiguity from left/right falling and break symmetry, a random value is sampled for each position dictating whether to check bottom-left first or bottom-right.

Water-Flowing. Water and other fluids (water, lava, acid) behave similarly to sand, except that these elements can also flow left and right. This behavior is implemented in a similar fashion to sand-piling, except that the left and right adjustment elements are considered for swapping, instead of bottom-left and bottom-right.

In addition, an optimization is implemented to increase the effective velocity of fluids. With the naive setup, each fluid can flow either left or right. However, this means that large clumps of fluids often have a hard time spreading out, as they rely on random osmisis in order to fully spread horizontally. To speed up the process, an index is reserved to keep track of the direction that a given fluid element has previously flowed in. If a fluid has previously flowed to the left, then the next timestep it will first check if it can move to the left (rather than randomly selecting left/right). This ruleset means that a single particle of water will continue flowing left until it hits a wall, rather than randomly move between left/right, creating a more dynamic fluid system.

Ice and Water. The goal with ice and water are to create two elements with different phases (solid and liquid), which transition between one another depending on their number of neighbors. Ice has a default chance of melting into water (2% a timestep), and water has a chance of freezing into ice if it has three or more ice neighbors (5% a timestep).

To compute the number of neighbors for this behavior and more, a simple convolutional kernel is employed. The kernel has a 3x3 kernel size and contains all ones, resulting in each position after running the convolution containing the number of a specific element that exist next to that position.

```
self.neighbor_kernel = torch.ones((1, 1, 3, 3), device=device)
water_can_freeze = (F.conv2d(self.get_elem(world, "ice"),
    self.neighbor_kernel, padding=1) >= 3)
does_turn_ice = self.get_bool(world, "water") & water_can_freeze
    & (ice_chance < 0.05)
world[:] = interp(switch=does_turn_ice, if_false=world,
    if_true=self.elem_vecs['ice'])
```

Fire-Burning. Fire is implement as an element which cannot survive on its own. Fire always has a chance to burn away into air. However, fire that is next to a burnable element (wood, plant, dust) will not burn away, and instead has a chance to transform that element into fire. Thus, fire will travel along the paths of burnable elements, setting fire to anything close enough to touch. Fire also naturally moves upwards, thus fire can jump from one element to another even across a small air gap.

Note that each burnable element has a distinct behavior when burned. Wood burns the slowest, as it has the lowest chance of burning when in contact with a fire element. Plant burns faster, and dust burns the fastest and additionally creates large amounts of velocity when burned. This aims to simulate an explosive effect as the velocity will scatter nearby particles outwards.

Plant-growing. Plants spread in water, but in an incomplete fashion. The intent is to create a vine-like structure where plants absorb water and create more plant, leaving behind a web of plant elements. Specifically, water elements that are near greater than four plants have a chance to turn into either water or air.

Lava. Lava is a liquid that flows similarly to water. Lava that is exposed to air continuously creates fire at those positions, thus lava acts as a constant source of fire that does not naturally dissipate. As lava obeys gravity and fluid flowing, lava can flow down structures and reach new locations. Lava that comes into contact with water forms a stone element in that location.

Acid. Acid is a fluid which destroys other elements. Specifically, if acid is neighboring a non-empty element, then there is a 20% that the acid block will dissapear along with any neighboring elements. Normally, elements should not be able to interact with all its neighbors simultaneously (may cause conflicts), but since acid only destroys things, there is no issue.

Cloner. The final element is a cloner, which keeps track of the first element that touches it, then continuously produces that element at any adjacent empty positions. Cloner elements are meant to be used as a source of mobile elements such as water or gas, and once assigned on contact can create structures such as waterfalls or spouts.

Velocity System. Powderworld elements interact with each other via elemental reactions as well as a global velocity system. Each position in the world holds an x and y velocity, and blocks move if the magnitude of the velocity at that position is greater than a threshold. The moving behavior consists of a loop over the eight primary directions, and first checks if the velocity at each location is aligned in that direction. Then, assuming the velocity magnitude is great enough, the procedure checks if there is an empty space in that direction, and if so, the element moves. All elements are effected by velocity except for walls.

Additionally, the velocity layer also goes through its own simulation. While other powder games use fluid dynamics to simulate velocity, this work instead opts to use a simpler but quicker method. Specifically, velocities create additional velocity in the direction they point in. This is done during the same loop as above. Next, velocities are slightly averaged with their neighbors, and the entire velocity layer is scaled down by a factor of 0.95. Overall, the velocity simulation allows velocity values to travel forwards in the direction they point in, while slightly spreading out and decaying.

Figure 14: **Training tasks at various environment complexities.** Environment complexity is defined as the number of shapes included within the procedural generation algorithm. Each shape is generated up to five times, at random positions, sizes, and with a random element.

Figure 15: **Training tasks at various numbers of lines.** Note that each line number represents the maximum possible number of lines, thus the 4-Line environment can generate [0,1,2,3,4] lines. Blank worlds appear when no lines are generated, or lines are generated out of unstable elements (e.g. fire) that disappear over time.

Figure 16: **World model predictions over test tasks.** This figure showcases the eight test tasks simulated for 16 timesteps into the future. World models are trained to predict 8 timesteps forwards, thus results are shown with each world model applying two updates.

Figure 17: **Cont: World model predictions over test tasks.**

Figure 18: **World model training curves on environments with increasing complexity.** The Validation loss represents the performance of the world models on tasks sampled from their training distribution (i.e. only circle, only squares, etc.) Note that these tasks are never actually seen during training. The loss represents performance over an arbitrarily-chosen set of tasks, specifically, worlds with 5 lines.

Figure 19: **World model training curves on environments with increasing number of lines.** Note the mirrored correlations: world models trained on more complex environments show higher validation loss (as the tasks are harder) but lower benchmark loss.

Figure 20: **World model training curves on increasing number of training tasks.** More training tasks consistently improves both Validation and Benchmark performance.

Figure 21: **Transfer performance to novel elements, over fine-tune time.** Showcased are world models trained on increasing numbers of elements, then fine-tuned on an environment with three novel elements (gas, stone, acid). While in the zero-shot setting there is little correlation in performance, fine-tuning reveals that models trained on larger numbers of elements can more efficiently adapt to the new environment.

Figure 22: **Reinforcement learning training curves on environments with increasing numbers of lines.** The Validation loss represents the performance of the RL agents on tasks sampled from their training distribution (i.e. 1 line, 2 lines, etc.) Note that these tasks are never actually seen during training. The Benchmark loss represents performance over an arbitrarily-chosen set of tasks, specifically, worlds with 5 lines.

Note how unlike in the world-modelling case, the Validation and Benchmark graphs are similar and not mirrored. This observation showcases how RL performance is greatly dependent on a stable training set. RL agents trained on complex tasks fail to learn in general, and cannot perform well on both training and test tasks.

Figure 23: **Reinforcement learning training curves on increasing amounts of training tasks.** Larger amounts of training tasks generally improve agent performance across all tasks.