RANDOMIZED ENSEMBLED DOUBLE Q-LEARNING: LEARNING FAST WITHOUT A MODEL

ABSTRACT

Using a high Update-To-Data (UTD) ratio, model-based methods have recently achieved much higher sample efficiency than previous model-free methods for continuous-action DRL benchmarks. In this paper, we introduce a simple model-free algorithm, Randomized Ensembled Double Q-Learning (REDQ), and show that its performance is just as good as, if not better than, a state-of-the-art model-based algorithm for the MuJoCo benchmark. Moreover, REDQ can achieve this performance using fewer parameters than the model-based method, and with less wall-clock run time. REDQ has three carefully integrated ingredients which allow it to achieve its high performance: (i) a UTD ratio $>> 1$; (ii) an ensemble of Q functions; (iii) in-target minimization across a random subset of Q functions from the ensemble. Through carefully designed experiments, we provide a detailed analysis of REDQ and related model-free algorithms. To our knowledge, REDQ is the first successful model-free DRL algorithm for continuous-action spaces using a UTD ratio $>> 1$.

1 INTRODUCTION

Recently, model-based methods in continuous action space domains have achieved much higher sample efficiency than previous model-free methods. Model-based methods often attain higher sample efficiency by using a high Update-To-Data (UTD) ratio, which is the number of updates taken by the agent compared to the number of actual interactions with the environment. For example, Model-Based Policy Optimization (MBPO) (Janner et al., 2019), is a state-of-the-art model-based algorithm which updates the agent with a mix of real data from the environment and "fake" data from its model, and uses a large UTD ratio of 20-40. Compared to Soft-Actor-Critic (SAC), which is model-free and uses a UTD of 1, MBPO achieves much higher sample efficiency in the OpenAI MuJoCo benchmark (Todorov et al., 2012; Brockman et al., 2016). This raises the question of whether it is also possible to achieve such high performance without a model?

In this paper, we introduce a simple model-free algorithm called Randomized Ensemble Double Q learning (REDQ), and show that its performance is just as good as, if not better than, MBPO. The result indicates, that at least for the MuJoCo benchmark, simple model-free algorithms can attain the performance of current state-of-the-art model-based algorithms. Moreover, REDQ can achieve this performance using fewer parameters than MBPO, and with less wall-clock run time.

Like MBPO, REDQ employs a UTD ratio that is $>> 1$, but unlike MBPO it is model-free, has no roll outs, and performs all updates with real data. In addition to using a UTD ratio that is $>> 1$, it has two other carefully integrated ingredients: an ensemble of Q functions; and in-target minimization across a *random subset* of Q functions from the ensemble.

Through carefully designed experiments, we provide a detailed analysis of REDQ. We introduce the metrics of average Q-function bias and standard deviation (std) of Q-function bias. Our results show that using ensembles with in-target minimization reduces the std of the Q-function bias to close to zero for most of training, even when the UTD is very high. Furthermore, by adjusting the number of randomly selected Q-functions for in-target minimization, REDQ can control the average Q-function bias. In comparison with standard ensemble averaging and with SAC with a higher UTD, REDQ has much lower std of Q-function bias while maintaining an average bias that is negative but close to zero throughout most of training, resulting in significantly better learning performance. We perform an ablation study, and show that REDQ is very robust to choices of hyperparameters, and can work

well with a small ensemble and a small number of Q functions in the in-target minimization. We also provide a theoretical analysis, providing additional insights into REDQ. Finally, we consider combining the REDQ algorithm with an online feature extractor network (OFENet) (Ota et al., 2020) to further improve performance, particularly for the more challenging environments Ant and Humanoid. We achieve more than 7x the sample efficiency of SAC to reach a score of 5000 for both Ant and Humanoid. In Humanoid, REDQ-OFE also greatly outperforms MBPO, reaching a score of 5000 at 150K interactions, which is 3x MBPO's score at that point.

To ensure our comparisons are fair, and to ensure our results are reproducible (Henderson et al., 2018; Islam et al., 2017; Duan et al., 2016), we provide open source code. For all algorithmic comparisons, we use the same codebase (except for MBPO, for which we use the authors' code).

2 RANDOMIZED ENSEMBLED DOUBLE Q-LEARNING (REDQ)

Janner et al. (2019) proposed Model-Based Policy Optimization (MBPO), which was shown to be much more sample efficient than popular model-free algorithms such as SAC and PPO for the MuJoCo environments. MBPO learns a model, and generates "fake data" from its model as well as "real data" through environment interactions. It then performs parameter updates using both the fake and the real data. One of the distinguishing features of MBPO is that it has a UTD ratio $>> 1$ for updating its Q functions, enabling MBPO to achieve high sample efficiency.

Algorithm 1 Randomized Ensembled Double Q-learning (REDQ)

1: Initialize policy parameters θ, N Q-function parameters ϕ_i, $i = 1, \ldots, N$, empty replay buffer $\mathcal{D}$. Set target parameters $\phi_{\text{targ},i} \leftarrow \phi_i$, for $i = 1, 2, \ldots, N$
2: **repeat**
3:     Take one action $a_t \sim \pi_\theta(\cdot|s_t)$. Observe reward r_t, new state s_{t+1}.
4:     Add data to buffer: $\mathcal{D} \leftarrow \mathcal{D} \cup \{(s_t, a_t, r_t, s_{t+1})\}$
5:     **for** G updates **do**
6:         Sample a mini-batch $B = \{(s, a, r, s')\}$ from $\mathcal{D}$
7:         Sample a set $\mathcal{M}$ of M distinct indices from $\{1, 2, \ldots, N\}$
8:         Compute the Q target y (same for all of the N Q-functions):

$$y = r + \gamma \left(\min_{i \in \mathcal{M}} Q_{\phi_{\text{targ},i}} (s', \tilde{a}') - \alpha \log \pi_\theta (\tilde{a}' \mid s') \right), \quad \tilde{a}' \sim \pi_\theta (\cdot \mid s')$$

9:         **for** $i = 1, \ldots, N$ **do**
10:             Update ϕ_i with gradient descent using

$$\nabla_\phi \frac{1}{|B|} \sum_{(s,a,r,s') \in B} (Q_{\phi_i}(s, a) - y)^2$$

11:             Update target networks with $\phi_{\text{targ},i} \leftarrow \rho \phi_{\text{targ},i} + (1 - \rho)\phi_i$
12:     Update policy parameters θ with gradient ascent using

$$\nabla_\theta \frac{1}{|B|} \sum_{s \in B} \left(\frac{1}{N} \sum_{i=1}^{N} Q_{\phi_i} (s, \tilde{a}_\theta(s)) - \alpha \log \pi_\theta (\tilde{a}_\theta(s)|s) \right), \quad \tilde{a}_\theta(s) \sim \pi_\theta(\cdot \mid s)$$

We propose Randomized Ensembled Double Q-learning (REDQ), a novel model-free algorithm whose sample-efficiency performance is just as good as, if not better than, the state-of-the-art model-based algorithm for the MuJoCo benchmark. The pseudocode for REDQ is shown in Algorithm 1. REDQ can be used with any standard off-policy model-free algorithm, such as SAC (Haarnoja et al., 2018b), SOP (Wang et al., 2019), TD3 (Fujimoto et al., 2018), or DDPG (Lillicrap et al., 2015). For the sake of concreteness, we use SAC in Algorithm 1. REDQ has the following key components: (i) To improve sample efficiency, the UTD ratio G is much greater than one; (ii) To reduce the variance in the Q-function estimate, REDQ uses an ensemble of N Q-functions, with each Q-function randomly and independently initialized but updated with the same target; (iii) To reduce over-estimation bias, the target for the Q-function includes a minimization over a *random*

subset $\mathcal{M}$ of the N Q-functions. The size of the subset $\mathcal{M}$ is kept fixed, and is denoted as M, and is referred to as the *in-target minimization parameter*. Since our default choice for M is $M = 2$, we refer to the algorithm as Randomized Ensembled *Double* Q-learning (REDQ).

REDQ shares some similarities with Maxmin Q-learning (Lan et al., 2020), which also uses ensembles and also minimizes over multiple Q-functions in the target. However, Maxmin Q-learning and REDQ have many differences, e.g., Maxmin Q-learning minimizes over the full ensemble in the target, whereas REDQ minimizes over a random subset of Q-functions. Unlike Maxmin Q-learning, REDQ controls over-estimation bias and variance of the Q estimate by separately setting M and N. REDQ has many possible variations, some of which are discussed in the ablation section.

REDQ has three key hyperparameters, G, N, and M. When $N = M = 2$ and $G = 1$, then REDQ simply becomes the underlying off-policy algorithm such as SAC. When $N = M > 2$ and $G = 1$, then REDQ is similar to, but not equivalent to, Maxmin Q-learning (Lan et al., 2020). In practice, we find $M = 2$ works well for REDQ, and that a wide range of values around $N = 10$ and $G = 20$ work well. To our knowledge, REDQ is the first successful model-free DRL algorithm for continuous-action spaces using a UTD ratio $G >> 1$.

2.1 EXPERIMENTAL RESULTS FOR REDQ

We now provide experimental results for REDQ and MBPO for the four most challenging MuJoCo environments, namely, Hopper, Walker2d, Ant, and Humanoid. We have taken great care to make a fair comparison of REDQ and MBPO. The MBPO results are reproduced using the author's open source code, and we use the hyperparameters suggested in the MBPO paper, including $G = 20$. We obtain MBPO results similar to those reported in the MBPO paper. For REDQ, we use $G = 20$, $N = 10$, and $M = 2$ for all environments. We use the evaluation protocol proposed in the MBPO paper. Specifically, after every epoch we run one test episode with the current policy and record the performance as the undiscounted sum of all the rewards in the episode. A more detailed discussion on hyperparameters and implementation details is given in the Appendix.

(a) Hopper   (b) Walker2d

(c) Ant   (d) Humanoid

Figure 1: REDQ compared to MBPO and SAC. Both REDQ and MBPO use $G = 20$.

Figure 1 shows the training curves for REDQ, MBPO, and SAC. For each algorithm, we plot the average return of 5 independent trials as the solid curve, and plot the standard deviation across 5 seeds as the transparent shaded region. For each environment, we train each algorithm for exactly the same number of environment interactions as done in the MBPO paper. Figure 1 shows that both REDQ and MBPO learn much faster than SAC, with REDQ performing somewhat better than MBPO on the whole. In particular, REDQ learns significantly faster for Hopper, and has somewhat better asymptotic performance for Hopper, Walker2d, and Humanoid. A more detailed performance

comparison is given in the Appendix, where it is shown that, averaging across the environments, REDQ performs 1.4x better than MBPO half-way through training and 1.1x better at the end of training. These results taken together are perhaps counter-intuitive. They show that a simple model-free algorithm can achieve as good or better sample-efficiency performance as the state-of-the-art model-based algorithm for the MuJoCo environments.

Does REDQ achieve its sample efficiency using more computational resources than MBPO? We now compare the number of parameters used in REDQ and MBPO. With REDQ, for each Q network and the policy network, we use a multi-layer perceptron with two hidden layers, each with 256 units. For MBPO, we use the default network architectures for the Q networks, policy network, and model ensembles (Janner et al., 2019). The Appendix provides a table comparing the number of parameters: REDQ uses fewer parameters than MBPO for all four environments, specifically, between 26% and 70% as many parameters depending on the environment. Additionally, we measured the runtime on a 2080-Ti GPU and found that MBPO roughly takes 75% longer. In summary, the results in this section show that the model-free algorithm REDQ is not only at least as sample efficient as MBPO, but also has fewer parameters and is significantly faster in terms of wall-clock time.

3 WHY DOES REDQ SUCCEED WHEREAS OTHERS FAIL?

REDQ is a simple model-free algorithm that matches the performance of a state-of-the-art model-based algorithm. Key to REDQ's sample efficiency is using a UTD $>> 1$. Why is it that SAC and ordinary ensemble averaging (AVG) cannot do as well as REDQ by simply increasing the UTD?

To address these questions, let $Q^\pi(s, a)$ be the action-value function for policy π using the standard infinite-horizon discounted return definition. Let $Q_\phi(s, a)$ be an estimate of $Q^\pi(s, a)$, which is defined as the average of $Q_{\phi_i}(s, a)$, $i = 1, \ldots, N$, when using an ensemble. We define the bias of an estimate at state-action pair (s, a) to be $Q_\phi(s, a) - Q^\pi(s, a)$. We are primarily interested in the accuracy of $Q_\phi(s, a)$ over the state-action distribution of the current policy π. To quantitatively analyze how estimation error accumulates in the training process, we perform an analysis that is similar to previous work (Van Hasselt et al., 2016; Fujimoto et al., 2018), but not exactly the same. We run a number of analysis episodes from different random initial states using the current policy π. For each state-action pair visited, we obtain both the discounted Monte Carlo return and the estimated Q value using Q_ϕ, and then compute the difference to obtain an estimate of the bias for that state-action pair. We then calculate the average and std of these bias values. The average gives us an idea of whether Q_ϕ is in general overestimating or underestimating, and the std measures how uniform the bias is across different state-action pairs. We argue that the std is just as important as the average of the bias. As discussed in Van Hasselt et al. (2016), a uniform bias is not necessarily harmful as it does not change the action selection. Thus near-uniform bias can be preferable to a highly non-uniform bias with a small average value. Although average bias has been analyzed in several previous works (Van Hasselt et al., 2016; Fujimoto et al., 2018; Anschel et al., 2017), the std does not seem to have received much attention.

Since the MC return values can change significantly throughout training, to make comparisons more meaningful, we define the normalized bias of the estimate $Q_\phi(s, a)$ to be $(Q_\phi(s, a) - Q^\pi(s, a))/|E_{\bar{s}, \bar{a} \sim \pi}[Q^\pi(\bar{s}, \bar{a})]|$, which is simply the bias divided by the absolute value of the expected discounted MC return for state-action pairs sampled from the current policy. We focus on the normalized bias in our analysis since it helps show how large the bias is, compared to the scale of the current MC return.

In this and the subsequent section, we compare REDQ with several algorithms and variants. We emphasize that all of the algorithms and variants use the same code base as used in the REDQ experiments (including using SAC as the underlying off-policy algorithm). The only difference is how the targets are calculated in lines 7 and 8 of Algorithm 1.

We first compare REDQ with two natural algorithms, which we call SAC-20 and ensemble averaging (AVG). SAC-20 is SAC but with G increased from 1 (as in standard SAC) to 20. For AVG, we use an ensemble of Q functions, and when computing the Q target, we take the average of all Q values without any in-target minimization. In these comparisons, all three algorithms use a UTD of $G = 20$.

Figure 2 presents the results for Ant; the results for the other three environments are consistent with those for Ant and are shown in the Appendix. For each experiment we use 5 random seeds. We first

note REDQ learns significantly faster than both SAC-20 and AVG. Strikingly, relative to the other two algorithms, REDQ has a very low normalized std of bias for most of training, indicating the bias across different in-distribution state-action pairs is about the same. Furthermore, throughout most of training, REDQ has a small and near-constant under-estimation bias. The shaded areas for mean and std of bias are also smaller, indicating that REDQ is robust to random initial conditions.

(a) Performance, Ant   (b) Average bias, Ant   (c) Std of bias, Ant

Figure 2: Performance, mean and std of normalized Q bias for REDQ, AVG, and SAC for Ant. Figures for the other three environments have similar trends and are shown in the Appendix.

SAC with a UTD ratio of 20 performs poorly for the most challenging environments Ant and Humanoid. For SAC-20, the high UTD ratio leads to an average bias that fluctuates during training. We also see a high normalized std of bias, indicating that the bias is highly non-uniform, which can be detrimental. The bias values also have large variance across random initial seeds, as indicated by the large shaded area, showing that the bias in SAC-20 is sensitive to initial conditions. Comparing AVG and SAC-20, we see AVG performs significantly better than SAC-20 in Ant and Humanoid. This can be explained again by the bias: due to ensemble averaging, AVG can achieve a lower std of bias; and when it does, its performance improves significantly faster than SAC-20.

REDQ has two critical components that allow it to maintain stable and near-uniform bias under high UTD ratios: an ensemble and in-target minimization. AVG and SAC-20 each has one of these components but neither has both. Thus the success of REDQ is largely due to a careful integration of both of these critical components. Additionally, as shown in the ablation study, the *random* selection of Q functions in the in-target minimization gives REDQ a further performance boost.

3.1 THEORETICAL ANALYSIS

We now characterize the relation between the estimation error, the in-target minimization parameter M and the size of the ensemble N. We use the theoretical framework introduced in Thrun & Schwartz (1993) and extended in Lan et al. (2020). We do this for the tabular version of REDQ, for which the target for $Q^i(s, a)$ for each $i = 1, \ldots, N$ is:

$$r + \gamma \max_{a' \in \mathcal{A}} \min_{j \in \mathcal{M}} Q^j(s', a') \tag{1}$$

where $\mathcal{A}$ is the finite action space, (s, a, r, s') is a transition, and $\mathcal{M}$ is again a uniformly random subset from $\{1, \ldots, N\}$ with $|\mathcal{M}| = M$. The complete pseudocode for tabular REDQ is provided in the Appendix.

Let $Q^i(s, a) - Q^\pi(s, a)$ be the *pre-update* estimation bias for the ith Q-function, where $Q^\pi(s, a)$ is once again the ground-truth Q-value for the current policy π. We are interested in how the bias changes after an update, and how this change is effected by M and N. Similar to Thrun & Schwartz (1993) and Lan et al. (2020), define the *post-update* estimation bias as the difference between the target (1) and the target when using the ground-truth:

$$Z_{M,N} \triangleq r + \gamma \max_{a' \in \mathcal{A}} \min_{j \in \mathcal{M}} Q^j(s', a') - (r + \gamma \max_{a' \in \mathcal{A}} Q^\pi(s', a'))$$

$$= \gamma (\max_{a' \in \mathcal{A}} \min_{j \in \mathcal{M}} Q^j(s', a') - \max_{a' \in \mathcal{A}} Q^\pi(s', a'))$$

Here we write $Z_{M,N}$ to emphasize its dependence on both M and N. Following Thrun & Schwartz (1993) and Lan et al. (2020), fix s and assume each $Q^i(s, a)$ has a random approximation error e^i_{sa}:

$$Q^i(s, a) = Q^\pi(s, a) + e^i_{sa}$$

where for each fixed s, $\{e_{sa}^i\}$ are zero-mean independent random variables such that $\{e_{sa}^i\}$ are identically distributed across i for each fixed (s, a) pair. Note that due to the zero-mean assumption, the expected pre-update estimation bias is $\mathbb{E}[Q^i(s, a) - Q^\pi(s, a)] = 0$. Thus if $\mathbb{E}[Z_{M,N}] > 0$, then the expected post-update bias is positive and there is a tendency for over-estimation accumulation; and if $\mathbb{E}[Z_{M,N}] < 0$, then there is a tendency for under-estimation accumulation.

Theorem 1.   *1. For any fixed M, $\mathbb{E}[Z_{M,N}]$ does not depend on N.*

2. *$\mathbb{E}[Z_{1,N}] \geq 0$ for all $N \geq 1$.*

3. *$\mathbb{E}[Z_{M+1,N}] \leq \mathbb{E}[Z_{M,N}]$ for any $M < N$.*

4. *Suppose that $e_{sa}^i \leq c$ for some $c > 0$ for all s, a and i. Then there exists an M such that for all $N \geq M$, $\mathbb{E}[Z_{M,N}] < 0$.*

Points 2-4 of the Theorem indicate that we can control the expected post-update bias $\mathbb{E}[Z_{M,N}]$, bringing it from above zero (over estimation) to under zero (under estimation) by increasing M. Moreover, from the first point, the expected bias only depends on M, which implies that increasing N reduces variance of the ensemble average but does not change the expected post-update bias. Thus, we can control the post-update bias with M and separately control the variance of the average of the ensemble with N. Note that this is not possible for Maxmin Q-learning, for which $M = N$, and thus increasing the ensemble size N will also decrease the post-update bias, potentially making it more negative, which can be detrimental. Note that this also cannot be done for standard ensemble averaging, for which there is no in-target minimization parameter M.

Note we make very weak assumptions on the distribution of the error term. Thrun & Schwartz (1993) and Lan et al. (2020) make a strong assumption, namely, the error term is uniformly distributed. Because our assumption is much weaker, our proof methodology (in the Appendix) is very different.

4   REDQ VARIANTS AND ABLATIONS

In this section, we use ablations to provide further insight into REDQ. We focus on the Ant environment. We first look at how the ensemble size N affects REDQ. The top row in Figure 3 shows REDQ with $N = 2, 3, 5, 10, 15$. We can see that when we increase the ensemble size, we generally get a more stable average bias, a lower std of bias, and stronger performance. The result shows that even a small ensemble (e.g., $N = 5$) can greatly help in stabilizing bias accumulation when training under high UTD.

The middle row of Figure 3 shows how M, the in-target minimization parameter, can affect performance. When M is not an integer, e.g., $M = 1.5$, for each update, with probability 0.5 only one randomly-chosen Q function is used in the target, and with probability 0.5, two randomly-chosen functions are used. Similarly, for $M = 2.5$, for each update either two or three Q functions are used. Consistent with the theoretical result in Theorem 1, by increasing M we lower the average bias. When M gets too large, the Q estimate becomes too conservative and the large negative bias makes learning difficult. $M = 2$, which has the overall best performance, strikes a good balance between average bias (small underestimation during most of training) and std of the bias (consistently small).

The bottom row of Figure 3 shows the results for different target computation methods. Random ensemble mixture (REM) is a method originally proposed to boost performance of DQN in the discrete-action action setting. REM uses the random convex combination of the Q values to compute the target: it is similar to ensemble average (AVG), but with more randomization (Agarwal et al., 2020). The Maxmin curve in the figures is a variant based on Maxmin Q-learning, where the min of *all* the Q networks in the ensemble is taken to compute the Q target. As the ensemble size increases, Maxmin Q-learning shifts from overestimation to underestimation (Lan et al., 2020); Figure 3 shows Maxmin with $N = 3$ instead of $N = 10$, since a large N value will cause even more divergence of the Q values. For Weighted, the target is computed as the expectation of all the REDQ targets, where the expectation is taken over all N-choose-2 pairs of Q-functions. This leads to a formula that is a weighted sum of the ordered Q-functions, where the ordering is from the lowest to the highest Q value in the ensemble, as described in the Appendix. Our baseline REDQ in Algorithm 1 can be considered as a random-sample version of Weighted. For the MinPair REDQ variant, we divide the

Figure 3: REDQ ablation results for Ant. The top row shows the effect of the ensemble size N. The middle row shows the effect of the in-target minimization parameter M. The bottom row compares REDQ to several variants.

10 Q networks into 5 fixed pairs, and during an update we sample a pair of Q networks from these 5 fixed pairs.

From Figure 3 we see that REDQ and MinPair are the best and their performance is similar. For Ant, the performance of Weighted is much lower than REDQ, which indicates that the randomization in REDQ makes an important contribution, most likely reducing overfitting. REM has performance similar to AVG, studied in Section 3. In terms of the Q bias, REM has a positive average bias, while REDQ, MinPair, and Weighted all have a small negative average bias. Overall these results indicate that randomly choosing a subset of Q functions from the ensemble is important, but that the REDQ algorithm is robust across different mechanisms for choosing the functions.

4.1 IMPROVING REDQ WITH AUXILIARY FEATURE LEARNING

We now investigate whether we can further improve the performance of REDQ by incorporating better representation learning? Ota et al. (2020) recently proposed the online feature extractor network (OFENet), which learns representation vectors from environment data, and provides them to the agent as additional input, giving significant performance improvement. Is it possible to further improve the performance of REDQ with OFENet? We trained an OFENet together with REDQ to provide extra input, giving the algorithm REDQ-OFE. We found that OFENet did not help much for Hopper and Walker2d, which may be because REDQ already learns very fast, leaving little room for improvement. But as shown in Figure 4, online feature extraction can further improve REDQ performance for the more challenging environments Ant and Humanoid. REDQ-OFE achieves 7x the sample efficiency of SAC to reach 5000 on Ant and Humanoid, and outperforms MBPO with

3.12x and 1.26x the performance of MBPO at 150K and 300K data, respectively. A more detailed performance comparison table can be found in the Appendix.

(a) Performance, Ant   (b) Performance, Humanoid

Figure 4: Performance of REDQ, REDQ with OFE, and SAC.

5 RELATED WORK

It has long been recognized that maximization bias in Q-learning can significantly impede learning. Thrun & Schwartz (1993) first highlighted the existence of maximization bias. Van Hasselt (2010) proposed Double Q-Learning to address maximization bias for the tabular case, and showed that in general it leads to an under-estimation bias. Van Hasselt et al. (2016) showed that adding Double Q-learning to deep Q networks (DQN) (Mnih et al., 2013; 2015) gives a major performance boost for the Atari games benchmark. For continuous-action spaces, Fujimoto et al. (2018) introduced clipped-double Q-learning (CDQ), which further reduces maximization bias and brings significant improvements over the deep deterministic policy gradient (DDPG) algorithm (Lillicrap et al., 2015). CDQ was later combined with entropy maximization in SAC to achieve even stronger performance (Haarnoja et al., 2018a;b). Other bias reduction techniques include using bias-correction terms (Lee et al., 2013), using weighted Q estimates (Zhang et al., 2017; Li & Hou, 2019), penalizing deterministic policies at early stage of training (Fox et al., 2015), using multi-step methods (Meng et al., 2020), performing weighted Bellman updates to mitigate error propagation (Lee et al., 2020), and truncating sampled Q estimates with distributional networks (Kuznetsov et al., 2020).

It has also long been recognized that using ensembles can improve the performance of DRL algorithms (Faußer & Schwenker, 2015; Osband et al., 2016). For Q-learning based methods, Anschel et al. (2017) use the average of multiple Q estimates to reduce variance. Agarwal et al. (2020) introduced Random Ensemble Mixture (REM), which enforces optimal Bellman consistency on random convex combinations of multiple Q estimates. Lan et al. (2020) introduced Maxmin Q-learning, as discussed in Sections 2-4. Although in discrete action domains it has been found that fine-tuning DQN variants, including the UTD, can boost performance, little experimental or theoretical analysis is given to explain how this improvement is obtained (Kielak, 2020; van Hasselt et al., 2019).

To address some of the critical issues in model-based learning (Langlois et al., 2019), recent methods such as MBPO combine a model ensemble with a carefully controlled rollout horizon to obtain better performance (Janner et al., 2019; Buckman et al., 2018). These model-based methods can also be enhanced with advanced sampling (Zhang et al., 2020), bidirectional models (Lai et al., 2020), or backprop through the model (Clavera et al., 2020), and be analyzed through new theoretical frameworks (Rajeswaran et al., 2020; Dong et al., 2020).

6 CONCLUSION

The contributions of this paper are as follows. (1) We propose a simple model-free algorithm that attains sample efficiency that is as good as or better than state-of-the-art model-based algorithms for the MuJoCo benchmark. This result indicates that, at least for the MuJoCo benchmark, models may not be necessary for achieving high sample efficiency. (2) Using carefully designed experiments, we explain why REDQ succeeds when other model-free algorithms with high UTD ratios fail. (3) Finally, we combine REDQ with OFE, and show that REDQ-OFE can learn extremely fast for the challenging environments Ant and Humanoid.

REFERENCES

Rishabh Agarwal, Dale Schuurmans, and Mohammad Norouzi. An optimistic perspective on offline reinforcement learning. In *International Conference on Machine Learning (ICML)*, 2020.

Oron Anschel, Nir Baram, and Nahum Shimkin. Averaged-dqn: Variance reduction and stabilization for deep reinforcement learning. In *International Conference on Machine Learning*, pp. 176–185, 2017.

Greg Brockman, Vicki Cheung, Ludwig Pettersson, Jonas Schneider, John Schulman, Jie Tang, and Wojciech Zaremba. Openai gym. *arXiv preprint arXiv:1606.01540*, 2016.

Jacob Buckman, Danijar Hafner, George Tucker, Eugene Brevdo, and Honglak Lee. Sample-efficient reinforcement learning with stochastic ensemble value expansion. In *Advances in Neural Information Processing Systems*, pp. 8224–8234, 2018.

Ignasi Clavera, Violet Fu, and Pieter Abbeel. Model-augmented actor-critic: Backpropagating through paths. *arXiv preprint arXiv:2005.08068*, 2020.

Kefan Dong, Yuping Luo, Tianhe Yu, Chelsea Finn, and Tengyu Ma. On the expressivity of neural networks for deep reinforcement learning. *International Conference on Machine Learning (ICML)*, 2020.

Yan Duan, Xi Chen, Rein Houthooft, John Schulman, and Pieter Abbeel. Benchmarking deep reinforcement learning for continuous control. In *International Conference on Machine Learning*, pp. 1329–1338, 2016.

Stefan Faußer and Friedhelm Schwenker. Neural network ensembles in reinforcement learning. *Neural Processing Letters*, 41(1):55–69, 2015.

Roy Fox, Ari Pakman, and Naftali Tishby. Taming the noise in reinforcement learning via soft updates. *arXiv preprint arXiv:1512.08562*, 2015.

Scott Fujimoto, Herke van Hoof, and Dave Meger. Addressing function approximation error in actor-critic methods. *arXiv preprint arXiv:1802.09477*, 2018.

Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. *arXiv preprint arXiv:1801.01290*, 2018a.

Tuomas Haarnoja, Aurick Zhou, Kristian Hartikainen, George Tucker, Sehoon Ha, Jie Tan, Vikash Kumar, Henry Zhu, Abhishek Gupta, Pieter Abbeel, et al. Soft actor-critic algorithms and applications. *arXiv preprint arXiv:1812.05905*, 2018b.

Peter Henderson, Riashat Islam, Philip Bachman, Joelle Pineau, Doina Precup, and David Meger. Deep reinforcement learning that matters. In *Thirty-Second AAAI Conference on Artificial Intelligence*, 2018.

Riashat Islam, Peter Henderson, Maziar Gomrokchi, and Doina Precup. Reproducibility of benchmarked deep reinforcement learning tasks for continuous control. *arXiv preprint arXiv:1708.04133*, 2017.

Michael Janner, Justin Fu, Marvin Zhang, and Sergey Levine. When to trust your model: Model-based policy optimization. In *Advances in Neural Information Processing Systems*, pp. 12519–12530, 2019.

Kacper Kielak. Do recent advancements in model-based deep reinforcement learning really improve data efficiency? *arXiv preprint arXiv:2003.10181*, 2020.

Arsenii Kuznetsov, Pavel Shvechikov, Alexander Grishin, and Dmitry Vetrov. Controlling overestimation bias with truncated mixture of continuous distributional quantile critics. *arXiv preprint arXiv:2005.04269*, 2020.

Hang Lai, Jian Shen, Weinan Zhang, and Yong Yu. Bidirectional model-based policy optimization. *arXiv preprint arXiv:2007.01995*, 2020.

Qingfeng Lan, Yangchen Pan, Alona Fyshe, and Martha White. Maxmin q-learning: Controlling the estimation bias of q-learning. *arXiv preprint arXiv:2002.06487*, 2020.

Eric Langlois, Shunshi Zhang, Guodong Zhang, Pieter Abbeel, and Jimmy Ba. Benchmarking model-based reinforcement learning. *arXiv preprint arXiv:1907.02057*, 2019.

Donghun Lee, Boris Defourny, and Warren B Powell. Bias-corrected q-learning to control max-operator bias in q-learning. In *2013 IEEE Symposium on Adaptive Dynamic Programming and Reinforcement Learning (ADPRL)*, pp. 93–99. IEEE, 2013.

Kimin Lee, Michael Laskin, Aravind Srinivas, and Pieter Abbeel. Sunrise: A simple unified framework for ensemble learning in deep reinforcement learning. *arXiv preprint arXiv:2007.04938*, 2020.

Zhunan Li and Xinwen Hou. Mixing update q-value for deep reinforcement learning. In *2019 International Joint Conference on Neural Networks (IJCNN)*, pp. 1–6. IEEE, 2019.

Timothy P Lillicrap, Jonathan J Hunt, Alexander Pritzel, Nicolas Heess, Tom Erez, Yuval Tassa, David Silver, and Daan Wierstra. Continuous control with deep reinforcement learning. *arXiv preprint arXiv:1509.02971*, 2015.

Lingheng Meng, Rob Gorbet, and Dana Kulić. The effect of multi-step methods on overestimation in deep reinforcement learning. *arXiv preprint arXiv:2006.12692*, 2020.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Alex Graves, Ioannis Antonoglou, Daan Wierstra, and Martin Riedmiller. Playing atari with deep reinforcement learning. *arXiv preprint arXiv:1312.5602*, 2013.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Bellemare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, et al. Human-level control through deep reinforcement learning. *Nature*, 518(7540):529, 2015.

Ian Osband, Charles Blundell, Alexander Pritzel, and Benjamin Van Roy. Deep exploration via bootstrapped dqn. In *Advances in neural information processing systems*, pp. 4026–4034, 2016.

Kei Ota, Tomoaki Oiki, Devesh K Jha, Toshisada Mariyama, and Daniel Nikovski. Can increasing input dimensionality improve deep reinforcement learning? *arXiv preprint arXiv:2003.01629*, 2020.

Aravind Rajeswaran, Igor Mordatch, and Vikash Kumar. A game theoretic framework for model based reinforcement learning. *arXiv preprint arXiv:2004.07804*, 2020.

Sebastian Thrun and Anton Schwartz. Issues in using function approximation for reinforcement learning. In *Proceedings of the 1993 Connectionist Models Summer School Hillsdale, NJ. Lawrence Erlbaum*, 1993.

Emanuel Todorov, Tom Erez, and Yuval Tassa. Mujoco: A physics engine for model-based control. In *Intelligent Robots and Systems (IROS), 2012 IEEE/RSJ International Conference on*, pp. 5026–5033. IEEE, 2012.

Hado Van Hasselt. Double q-learning. In *Advances in neural information processing systems*, pp. 2613–2621, 2010.

Hado Van Hasselt, Arthur Guez, and David Silver. Deep reinforcement learning with double q-learning. In *AAAI*, volume 2, pp. 5. Phoenix, AZ, 2016.

Hado P van Hasselt, Matteo Hessel, and John Aslanides. When to use parametric models in reinforcement learning? In *Advances in Neural Information Processing Systems*, pp. 14322–14333, 2019.

Che Wang, Yanqiu Wu, Quan Vuong, and Keith Ross. Striving for simplicity and performance in off-policy drl: Output normalization and non-uniform sampling. *arXiv*, pp. arXiv–1910, 2019.

Chi Zhang, Sanmukh Rao Kuppannagari, and Viktor K Prasanna. Maximum entropy model rollouts: Fast model based policy optimization without compounding errors. *arXiv preprint arXiv:2006.04802*, 2020.

Zongzhang Zhang, Zhiyuan Pan, and Mykel J Kochenderfer. Weighted double q-learning. In *IJCAI*, pp. 3455–3461, 2017.