A Reduction-Based Framework for Conservative Bandits and Reinforcement Learning

Abstract

We study bandits and reinforcement learning (RL) subject to a conservative constraint where the agent is asked to perform at least as well as a given baseline policy. This setting is particular relevant in real-world domains including digital marketing, healthcare, production, finance, etc. In this paper, we present a reduction-based framework for conservative bandits and RL, in which our core technique is to calculate the necessary and sufficient budget obtained from running the baseline policy. For lower bounds, we improve the existing lower bound for conservative multi-armed bandits and obtain new lower bounds for conservative linear bandits, tabular RL and low-rank MDP, through a black-box reduction that turns a certain lower bound in the nonconservative setting into a new lower bound in the conservative setting. For upper bounds, in multi-armed bandits, linear bandits and tabular RL, our new upper bounds tighten or match existing ones with significantly simpler analyses. We also obtain a new upper bound for conservative low-rank MDP.

1 Introduction

This paper studies online sequential decision making problems such as bandits and reinforcement learning (RL) subject to a conservative constraint. Specifically, the agent is given a reliable *baseline policy* that may not be optimal but still satisfactory. In conservative bandits and RL, the agent is asked to perform nearly as well (or better) as the baseline policy at all time. This setting is a natural formalization of many real-world problems such as digital marketing, healthcare, finance, etc. For example, a company may want to explore new strategies to maximize profit while simultaneously maintaining profit above a fixed baseline at any time, in order not to be bankrupted. See (Wu et al., 2016) for more discussions on the motivation of the conservative constraint.

Analogously to the non-conservative case, conservative bandit/RL problems also require us to balance exploration and exploitation carefully. Meanwhile, to ensure the obtained policies outperform the baseline policy, we need to provide a tractable approach to keep the exploration not too aggressive. Solving these two problems simultaneously is the key challenge in conservative bandits and RL.

Existing work proposed algorithms for different settings, including bandits (Wu et al., 2016; Kazerouni et al., 2016; Garcelon et al., 2020b; Katariya et al., 2019; Zhang et al., 2019; Du et al., 2020; Wang et al., 2021) and tabular RL (Garcelon et al., 2020a). However, lower bound exists only for the multi-armed bandit setting (Wu et al., 2016), and there is no lower bound for other widely-adopted settings, such as linear bandits, tabular Markov Decision Process (MDP) and low-rank MDP. In Section 1.3, we provide a more detailed discussion of the related work.

For each of the different settings considered in the literature (i.e., multi-armed bandits, linear bandits, tabular MDPs), existing approaches rely on ad-hoc algorithm design and analysis of the trade-off between the setting-specific regret analysis and the conservative constraint. Furthermore, it is hard to argue about the optimality of the proposed algorithms because it would require clever constructions of the hard instances to prove the non-trivial regret lower bounds under the conservative constraint.[1]

---

[1] We refer non-trivial regret lower bounds to lower bounds that have terms related to the conservative constraints. Note existing lower bounds in the non-conservative setting still hold in the conservative setting.

1.1 Our Contributions

In this paper, we address these limitations and make significant progress in studying the general problem of online sequential decision-making with conservative constraint. We propose a *unified framework* that is generally applicable to online sequential decision-making problems. The common theme underlying our framework is to calculate the necessary and sufficient budget required to enable non-conservative exploration. Such a budget is obtained by running the baseline policy (cf. Section 3). With the new framework, we obtain a novel upper bound on tabular MDPs, which improves the previous result. And we prove a new upper bound on low-rank MDPs. Also, we derive the first lower bounds for linear bandits, tabular and low-rank MDPs, which shows that our upper bound is tight. We summarize our theoretical results in Table 1.

Lower Bounds. For any specific problem (e.g., multi-armed bandits, linear bandits), our framework *immediately* turns a minimax lower bound of the non-conservative setting to a non-trivial lower bound for the conservative case (cf. Section 4). We list some examples to showcase the power of our framework for lower bounds. Full results are given in Table 1.

- We derive a novel lower bound for *multi-armed bandits* that works on a wider range of parameters than the one derived in (Wu et al., 2016). In particular, our lower bound shows a more refined dependence on the value of the baseline policy.
- We derive the *first* regret lower bound for conservative exploration in *linear bandits*, *tabular MDPs* and *low-rank MDPs*. These results allow to establish or disprove the optimality of the algorithms currently available in the literature.

We emphasize our technique for deriving lower bounds is simple and generic, so we believe it can be used to obtain lower bounds for other problems as well.

Upper Bounds. Our novel view of conservative exploration can also be used to derive high probability regret upper-bounds. When the suboptimality gap Δ_0 and the expected return μ_0 of the baseline policy are known, we show that the *BudgetFirst* algorithm (Alg. 1) attains minimax optimal regret in a wide variety of sequential decision-making problems, when associated to any minimax optimal non-conservative algorithm specific to the problem at hand. In the more realistic (and challenging) scenario where Δ_0 and μ_0 are unknown, we show how to simply convert an entire class of algorithms with a sublinear non-conservative regret bound into a conservative algorithms with a sublinear regret bound. With this reduction, we obtain the following results, full details are given in Table 1.

- In the MAB setting, we obtain a regret upper-bound that matches our refined lower-bound, thus improving on existing analysis. In the linear bandit setting, we match existing bounds that are already minimax optimal.
- In the RL setting, we provide two novel results. First, we provide the first minimax optimal result for tabular MDPs, improving over (Garcelon et al., 2020a). Second, we derive the first upper bound for conservative exploration in low-rank MDPs. Our bound matches the rate of existing non-conservative algorithms though it is not minimax optimal. How to achieve minimax optimality in low rank MDPs is an open question even in non-conservative exploration.

Again, our reduction technique is simple and generic, and can be used to obtain new results in previously unstudied settings, like we did for low-rank MDPs.

1.2 Main Challenge and Technique Overview.

Existing conservative algorithms in Wu et al. (2016); Kazerouni et al. (2016); Garcelon et al. (2020b); Katariya et al. (2019); Zhang et al. (2019); Du et al. (2020); Garcelon et al. (2020a); Wang et al. (2021) are variants of non-conservative UCB algorithms. These conservative algorithms design some mechanisms to decide whether to adopt the policy calculated by non-conservative UCB algorithms or the baseline policy. The regret incurred by executing baseline policy poses the main challenge in the analysis. A crucial step in conservative algorithms is bounding the times of executing baseline policy, and then derives the upper bound for the regret. However, except for the MAB setting (Wu et al., 2016), it is unclear whether these upper bounds are tight because of the lack of lower bounds.

Furthermore, it is highly non-trivial to extend the lower bound in Wu et al. (2016) to linear bandits and RL setting because one may need to construct new examples to incorporate the hardness from the

Setting	Lower Bound	Upper Bound
Multi-armed bandits	$\Omega\left(\sqrt{AT} + \frac{A\Delta_0}{\alpha\mu_0(\alpha\mu_0+\Delta_0)}\right)$	$\widetilde{O}\left(\sqrt{AT} + \frac{A\Delta_0}{\alpha\mu_0(\alpha\mu_0+\Delta_0)}\right)$
	$\Omega(\sqrt{AT} + \frac{A}{\alpha\mu_0})$
(Wu et al., 2016) [2]	$\widetilde{O}\left(\sqrt{AT} + \frac{A}{\alpha\mu_0}\right)$
(Wu et al., 2016)
Linear bandits	$\Omega\left(d\sqrt{T} + \frac{d^2\Delta_0}{\alpha\mu_0(\alpha\mu_0+\Delta_0)}\right)$	$\widetilde{O}\left(d\sqrt{T} + \frac{d^2\Delta_0}{\alpha\mu_0(\alpha\mu_0+\Delta_0)}\right)$
This work and (Kazerouni et al., 2016; Garcelon et al., 2020b)
Tabular MDPs	$\Omega\left(\sqrt{H^3SAT} + \frac{SAH^3\Delta_0}{\alpha\mu_0(\alpha_0+\Delta_0)}\right)$	$\widetilde{O}\left(\sqrt{H^3SAT} + \frac{SAH^3\Delta_0}{\alpha\mu_0(\alpha\mu_0+\Delta_0)}\right)$
		$\widetilde{O}\left(\sqrt{H^3SAT} + \frac{S^2AH^5\Delta_0}{\alpha\mu_0(\alpha\mu_0+\Delta_0)}\right)$
(Garcelon et al., 2020a)
Low Rank MDPs	$\Omega\left(\sqrt{d^2H^3T} + \frac{d^2H^3\Delta_0}{\alpha\mu_0(\alpha\mu_0+\Delta_0)}\right)$	$\widetilde{O}\left(\sqrt{d^3H^4T} + \frac{d^3H^4\Delta_0}{\alpha\mu_0(\alpha\mu_0+\Delta_0)}\right)$

Table 1: Comparison of bounds for conservative decision-making. **Our contributions are reported in grey cells.** We denote by T the number of rounds the agent plays (episodes in RL), α the conservative level, μ_0 the expected return of the baseline policy[3], Δ_0 the suboptimality gap of the baseline policy, A the number of actions (or arms), S the number of states and d the feature dimension. The upper bounds hold both in the case Δ_0 and μ_0 are unknown since the lack of knowledge changes the regret only by a constant multiplicative factor (cf. Sect. 5).

conservative constraint. Besides, previous works design different approaches for different settings. It is unclear what is the underlying mechanism among all settings.

To this end, our framework deals with all settings of online sequential decision-making problems at the same time. In this framework, we define a new notion called *budget* for executing any non-conservative algorithm. The budget required by a certain non-conservative algorithm is the minimal number of times that it needs to run the baseline policy, in order not to violate the conservative constraint. With the help of known regret upper/lower bounds for the non-conservative settings, we can calculate the budget required by the algorithm. Hence, we can know exactly how many times the baseline police needs to be executed at most/least, which yields our sharp upper/lower bounds for conservative algorithms. See Sections 4 and 5 for more details.

We point out that although Wu et al. (2016) has a similar concept of budget in their naive Budget First algorithm, they only analyze the budget of UCB algorithm in the MAB setting, and their analysis for budget is not tight. On the other hand, our concept of budget is more general as we deal with any bandit/RL problems, and can yield bounds. In addition, our method is different from previous works Garcelon et al. (2020a); Wu et al. (2016); Kazerouni et al. (2016). Their algorithms run baseline policy when the budget is not enough, and is too conservative. Our algorithm calculates how much budget the algorithm needs in advance, and therefore has a tighter regret bound.

1.3 RELATED WORK

Non-conservative exploration has been widely studied in bandits, and minimax optimal algorithms have been provided for the settings considered in this paper (e.g. Lattimore & Szepesvári, 2020). The exploration problem has been widely studied also in RL but minimax optimal algorithms have not been provided for all the settings. For any finite-horizon time-inhomogeneous MDP with S states, A actions and horizon H, the minimax regret lower bound is $\Omega(\sqrt{H^3SAT})$ (Jaksch et al., 2010; Azar et al., 2017; Jin et al., 2018), where T denotes the number of episodes. For any time-inhomogeneous low-rank MDP with d-dimensional linear representation, the lower-bound is $\Omega(\sqrt{d^2H^3T})$ (Zhou et al., 2020, Remark 5.8). While several minimax optimal algorithms have been provided for tabular MDPs (e.g. Azar et al., 2017; Zanette & Brunskill, 2019; Zhang et al., 2020a;b; Ménard et al., 2021),

---

[2]Although the lower bound in Wu et al. (2016) seems tighter, their bound only holds when the parameter μ_0 satisfies the condition $\frac{\Delta_0}{\alpha\mu_0+\Delta_0} \geq 0.9$. Note under this condition, our lower bound is the same as theirs but our is more general because ours do not need this condition.

[3]In (Garcelon et al., 2020a), the upper bound scales with $r_b = \min_{s\in\mathcal{S},\rho_0(s)>0} V_1^{\pi_0}(s)$ (with ρ_0 the distribution of the starting state), the minimum of the baseline's value function at the first step over the potential starting states. Here, we assume there is a unique starting state hence $r_b = \mu_0$.

the gap between upper bound and lower bound is still open in low-rank MDPs, where LSVI-UCB (Jin et al., 2020) attains a $\widetilde{O}(\sqrt{d^3 H^4 T})$, while ELEANOR (Zanette et al., 2020) improves to $\widetilde{O}(\sqrt{d^2 H^4 T})$ at the cost of being computationally intractable.

In conservative exploration, previous works focus on designing specific conservative algorithms for different settings. The most studied conservative condition is the one w.r.t. the expected cumulative reward of an algorithm, that is also considered here. This conservative scenario was studied in multi-armed bandits (Wu et al., 2016), contextual linear bandits (Kazerouni et al., 2016; Garcelon et al., 2020b), contextual combinatorial bandits (Zhang et al., 2019) and tabular MDPs (Garcelon et al., 2020a). All these works focused on provide an upper-bound to the regret of a conservative algorithm. As far as we know, the only lower bound for conservative exploration is the one proved by Wu et al. (2016) for multi-armed bandits. Other problems that have been considered in conservative exploration are combinatorial semi-bandit with exchangeable actions (Katariya et al., 2019) and contextual combinatorial cascading bandits (Wang et al., 2021). Du et al. (2020) have recently considered conservative exploration with sample-path constraint, i.e., the conservative condition is defined on the observed rewards rather than in expectation.

A related but different problem is the one of safety, where the optimal policy is forced to satisfy a set of constraints, potentially not aligned with the reward signal. This problem was studied both in bandits (Amani et al., 2019; Pacchiano et al., 2021) and in RL (e.g., Zheng & Ratliff, 2020; Efroni et al., 2020; Ding et al., 2020; 2021), where it is often formulated via constrained MDPs (Altman, 1999). Finally, several works have focused on safety w.r.t. a baseline in batch RL (e.g., Thomas et al., 2015a;b; Laroche et al., 2019; Simão & Spaan, 2019)

2 PRELIMINARIES

The objective of this section is to provide a unified view of the settings considered in this paper, i.e., multi-armed bandits, linear bandits, tabular Markov Decision Processes (MDPs) and low-rank MDPs. We use the RL formalism which encompasses the bandit settings.

Notations. We begin by introducing some basic notation. We use $\Delta(\cdot)$ to represent the set of all probability distributions on a set. For $n \in \mathbb{N}_+$, we denote $[n] = \{1, 2, \ldots, n\}$. We use $O(\cdot), \Theta(\cdot), \Omega(\cdot)$ to denote the big-O, big-Theta, big-Omega notations. We use $\widetilde{O}(\cdot)$ to hide logarithmic factors. We denote $A \gtrsim (\lesssim) B$ if there exists a constant c such that $A \geq (\leq) cB$.

Tabular MDPs. A tabular finite-horizon time-inhomogeneous MDP can be represent as a tuple $M = (\mathcal{S}, \mathcal{A}, H, \{p_h\}_{h=1}^H, s_1, \{r_h\}_{h=1}^H)$, where $\mathcal{S}$ is the state space, $\mathcal{A}$ is the action space, H is the length of each episode and s_1 is the initial state.[4] At each stage h, every state-action pair (s, a) is characterized by a reward distribution with mean $r_h(s, a)$ and support in $[0, r_{\max}]$, and a transition distribution $p_h(\cdot|s, a)$ over next states. We denote by $S = |\mathcal{S}|$ and $A = |\mathcal{A}|$. A (randomized) policy $\pi \in \Pi$ is a set of functions $\{\pi_h : \mathcal{S} \mapsto \Delta(\mathcal{A})\}_{h \in [H]}$. For each stage $h \in [H]$ and any state-action pair $(s, a) \in \mathcal{S} \times \mathcal{A}$, the value functions of a policy π are defined as:

$$Q_h^\pi(s, a) = \mathbb{E}\left[\sum_{h'=h}^H r_{h'} | s_h = s, a_h = a, \pi\right], \quad V_h^\pi(s) = \mathbb{E}\left[\sum_{h'=h}^H r_{h'} | s_h = s, \pi\right].$$

For each policy π, we define $V_{H+1}^\pi(s) = 0$ and $Q_{H+1}^\pi(s, a) = 0$ for all $s \in \mathcal{S}, a \in \mathcal{A}$. There exists an optimal policy $\pi^\star$ such that $Q_h^\star(s, a) = Q_h^{\pi^\star}(s, a) = \max_\pi Q_h^\pi(s, a)$ satisfy the optimal Bellman equations $Q_h^\star(s, a) = r_h(s, a) + \mathbb{E}_{s' \sim p_h(s, a)}[V_{h+1}^\star(s')]$ and $V_h^\star = \max_{a \in \mathcal{A}}\{Q_h^\star(s, a)\}$. Then the optimal policy is the greedy policy $\pi_h^\star(s) = \arg\max_{a \in \mathcal{A}}\{Q_h^\star(s, a)\}$.

Low-Rank MDPs. We assume that $\mathcal{S}, \mathcal{A}$ are measurable spaces with possibly infinite number of elements. For algorithmic tractability, we shall restrict the attention to $\mathcal{A}$ being a finite set with cardinality A. When the state space is large or uncountable, value functions cannot be represented in tabular form. A standard approach is to use a parametric representation. Here, we assume that transitions and rewards are linearly representable (Jin et al., 2020).

---

[4]When the initial state is sampled from an initial distribution, we can extend the MDP with a new stage with single state s_1, single action and transitions that match the initial state distribution.

Assumption 1 (Low-rank MDP). *An MDP $(\mathcal{S}, \mathcal{A}, H, p, r)$ is a linear MDP with a feature map $\boldsymbol{\phi} : \mathcal{S} \times \mathcal{A} \to \mathbb{R}^d$, if for any $h \in [H]$, there exist d unknown (signed) measures $\boldsymbol{\mu}_h = \left(\mu_h^{(1)}, \ldots, \mu_h^{(d)} \right)$ over $\mathcal{S}$ and an unknown vector $\boldsymbol{\theta}_h \in \mathbb{R}^d$, such that for any $(x, a) \in \mathcal{S} \times \mathcal{A}$, we have*

$$\mathbb{P}_h(\cdot \mid x, a) = \langle \boldsymbol{\phi}(x, a), \boldsymbol{\mu}_h(\cdot) \rangle, \quad r_h(x, a) = \langle \boldsymbol{\phi}(x, a), \boldsymbol{\theta}_h \rangle. \tag{1}$$

Without loss of generality, we assume $\|\boldsymbol{\phi}(x, a)\| \leq 1$ for all $(x, a) \in \mathcal{S} \times \mathcal{A}$, and $\max \{\|\boldsymbol{\mu}_h(\mathcal{S})\|, \|\boldsymbol{\theta}_h\|\} \leq \sqrt{d}$ for all $h \in [H]$.

Under certain technical conditions (e.g., Shreve & Bertsekas, 1978), all the properties of tabular MDPs extend to low-rank MDPs. In addition, the state-action value function of any policy π is linearly representable in low-rank MDPs. Formally, for any policy π and stage $h \in [H]$, there exists $\theta^\pi \in \mathbb{R}^d$ such that $Q_h^\pi(s, a) = \langle \phi(s, a), \theta_h^\pi \rangle$.

Connection between RL and Bandits. To have a unified view, we can represent a multi-armed bandit as a tabular MDP with $S = 1$, A actions, $H = 1$ and self-loop transitions in s_1. In multi-armed bandits, we consider only deterministic policies so that $\Pi = \mathcal{A}$, then $V^\pi(s_1) = r(s_1, \pi(s_1))$ and the optimal policy is simply $\pi^\star = \arg\max_{a \in \mathcal{A}} r(s_1, a)$. Similarly, a linear bandit can be modeled through low-rank MDPs with $H = 1$. For generality, we allow the action space to be possibly uncounted and we define the value of a deterministic policy $\pi = a$ ($\Pi = \mathcal{A}$) as $V_1^\pi(s_1) = r_1(s_1, a) = \langle \phi(s_1, a), \theta_1 \rangle$. The optimal policy $\pi^\star$ is thus such that $\pi^\star = \arg\max_{a \in \mathcal{A}} \langle \phi(s_1, a), \theta_1 \rangle$. We refer the reader to Appendix A for details.

3 GENERAL FRAMEWORK FOR CONSERVATIVE EXPLORATION

With the unified view provided in the previous section, we can consider a generic sequential decision-making problem $\mathfrak{P}$ over $T \in \mathbb{N}^\star$ episodes. We consider the standard online interaction protocol where, at each episode $t \in [T]$, the learning agent $\mathfrak{A}$ selects a policy π_t, observes and stores a trajectory $(s_i, a_i, r_i)_{i \in [H]}$, updates the policy and restart with the next episode. We evaluate the performance of the learner through the *pseudo-regret*. Let $V^\pi = V_1^\pi(s_1)$ be the value function of a policy π, then the regret is defined as:

$$R_T(\mathfrak{P}, \mathfrak{A}) = \sum_{t=1}^{T} V^\star - V^{\pi_t}. \tag{2}$$

In conservative exploration, the learner aims to minimize the regret while guaranteeing that, at any episode t, their expected performance is (nearly) above the one of a baseline policy π_0. Formally, given a possibly randomized baseline policy $\pi_0 \in \Pi$ and a conservative level $\alpha \in [0, 1]$, the learner should satisfy w.h.p. that

$$\forall t \leq T, \qquad \sum_{j=1}^{t} V^{\pi_j} \geq (1 - \alpha)\, t\, V^{\pi_0}. \tag{3}$$

We assume that the value of conservative policy V^{π_0} is known to the agent. Such assumption can be seen in previous works such as Wu et al. (2016); Kazerouni et al. (2016); Garcelon et al. (2020b;a). This assumption is reasonable in practice because usually the baseline policy has been used for a long time and is well-characterized, and its value can be estimated using historical data. Even if we do not know the value of baseline policy, we can estimate it during the algorithm (e.g., Section 3.5 in Wu et al. (2016)), and we omit here for simplicity.

3.1 BUDGET OF A CONSERVATIVE ALGORITHM

Given the set of policies $\{\pi_t\}_{t \in [T]}$ selected by a conservative algorithm $\mathfrak{A}$, we can divide the episodes into the set $\mathcal{T}_0 = \{t \leq T \mid \pi_t = \pi_0\}$ and its complement $\mathcal{T}_0^c = \{t \leq T \mid \pi_t \neq \pi_0\} = [T] \setminus \mathcal{T}_0$. The set $\mathcal{T}_0^c$ denotes the episodes where the algorithm played an exploratory policy, i.e., it had enough budget to satisfy condition (3) through a policy $\pi_l \neq \pi_0$. This sequence of non-baseline policies $\{\pi_t\}_{t \in \mathcal{T}_0^c}$ defines a new algorithm $\widetilde{\mathfrak{A}}$, that we refer as the non-conservative algorithm. However, the algorithm $\mathfrak{A}$ is conservative therefore, for any $\delta > 0$ and $t \in [T]$, we have with probability at least $1 - \delta$ that $\sum_{l=1}^{t} V^{\pi_l} \geq (1 - \alpha) t V^{\pi_0}$. Hence, for any $t \in [T]$ we have:

$$\alpha V^{\pi_0} |\mathcal{T}_{0,t}| \geq \sum_{l \in \mathcal{T}_{0,t}^c} (1 - \alpha) V^{\pi_0} - V^{\pi_l}, \tag{4}$$

where $\mathcal{T}_{0,t} = \mathcal{T}_0 \cap [t]$ and $\mathcal{T}_{0,t}^c = \mathcal{T}_0^c \cap [t]$. Taking maximum over t in Eq. (4), we have that with high probability the conservative algorithm $\mathfrak{A}$ is such that

$$\alpha V^{\pi_0} |\mathcal{T}_0| \geq \underbrace{\max_{t \leq T} \sum_{l \in \mathcal{T}_{0,t}^c} (1-\alpha)V^{\pi_0} - V^{\pi_l}}_{=\mathcal{B}}.$$

The quantity on the right of the previous equation is exactly the amount of reward that the conservative algorithm $\mathfrak{A}$ has to collect by playing the baseline policy. Hence this quantity acts as a *conservative budget* $\mathcal{B}$. The higher it is, the more $\mathfrak{A}$ needs to play the baseline policy to satisfy the conservative condition. In other words, it is the least amount of reward that an algorithm needs to not violate the conservative constraint. We now extend this notion to any (non necessarily conservative) algorithm.

Definition 1. *For any $T \in \mathbb{N}^\star$, set of episodes $\mathcal{O} \subset [T]$ and arbitrary sequence of policies $\{\pi_t\}_{t \in \mathcal{O}}$, the budget of this sequence of policies is defined as:*

$$\mathcal{B}_T(\mathcal{O}, \{\pi_t\}_{t \in \mathcal{O}}) = \max_{t \in \mathcal{O}} \sum_{l \in \mathcal{O} \cap [t]} (1-\alpha)V^{\pi_0} - V^{\pi_l}. \tag{5}$$

4 REGRET LOWER BOUND FOR CONSERVATIVE EXPLORATION

In this section, we leverage the framework introduced in Section 3 to build lower bounds for several problems. Our result is based on the notion of budget defined in Section 3. This notion is used to build an algorithm whose regret is a lower bound for any conservative algorithm.

Theorem 1 (Conservative Exploration Regret Lower Bound). *Let's consider a decision-making problem $\mathfrak{P}$ over T steps, a conservative level $\alpha \in [0,1]$, a baseline policy π_0, an algorithm $\mathfrak{A}$ and $\delta \in (0,1)$. We assume that:*

- *Lower-bound for non-conservative exploration. There exists a $\xi \in \mathbb{R}_+$ and $T_0 \in \mathbb{N}$ such that for any algorithm $\mathfrak{A}'$ there exists an environment (instance of $\mathfrak{P}$) such that with probability at least $1 - \delta$, $R_T(\mathfrak{P}, \mathfrak{A}') \geq \xi\sqrt{T}$ for $T \geq T_0$.*
- *$\mathfrak{A}$ is conservative. The algorithm $\mathfrak{A}$ is conservative, that is to say with probability at least $1 - \delta$ for any $t \leq T$, $\sum_{l=1}^t V^{\pi_l} \geq (1-\alpha)tV^{\pi_0}$.*

Then, there exists an environment (instance of problem $\mathfrak{P}$) and $T_0 \in \mathbb{N}$ such that with probability at least $1 - \delta$ and $T \geq T_0$:

$$R_T(\mathfrak{A}, \mathfrak{P}) \gtrsim \max\left\{ \xi\sqrt{T}, \frac{\xi^2 \Delta_0}{\alpha V^{\pi_0}(\alpha V^{\pi_0} + \Delta_0)} \right\}.$$

where $\Delta_0 = V^\star - V^{\pi_0}$ is the sub-optimality gap of policy π_0.

Theorem 1 provides a general framework deriving lower-bounds for conservative exploration and highlights the impact of the baseline policy on the regret. In particular, it shows that in any sequential decision-making problem, after a sufficiently large number of episodes the conservative condition can be verified and the baseline policy has no impact anymore on the learning process. The only requirement is the knowledge of a lower-bound for the non-conservative case. Before instantiating the result in specific settings, we provide an intuition about how this result is derived and what is the role of the conservative budget $\mathcal{B}$.

Proof Sketch. Let us consider a conservative algorithm $\mathfrak{A} = \{\pi_t \mid t \leq T\}$, which is associated to a non-conservative algorithm $\widetilde{\mathfrak{A}} = \{\pi_t \mid t \in \mathcal{T}_0^c\}$ with $\mathcal{T}_0^c$ and $\mathcal{T}_0$ the set of non-conservative and conservative episodes as defined in Sec. 3. By the reasoning of the previous section, we have that $|\mathcal{T}_0|\alpha V^{\pi_0} \geq \mathcal{B}_T(\mathcal{T}_0^c, \widetilde{\mathfrak{A}})$ with high-probability. But the regret of $\mathfrak{A}$ can be decomposed as:

$$R_T(\mathfrak{P}, \mathfrak{A}) = \sum_{l \in \mathcal{T}_0^c} V^\star - V^{\pi_l} + \Delta_0 |\mathcal{T}_0| \geq \sum_{l \in \mathcal{T}_0^c} V^\star - V^{\pi_l} + \frac{\Delta_0}{\alpha V^{\pi_0}} \mathcal{B}_T(\mathcal{T}_0^c, \widetilde{\mathfrak{A}}). \tag{6}$$

The right-hand side of Eq. (6) is exactly the regret of an algorithm which would play the baseline policy for the first $\frac{\mathcal{B}_T(\mathcal{T}_0^c, \widetilde{\mathfrak{A}})}{\alpha V^{\pi_0}}$ steps and then chose the policy of $\widetilde{\mathfrak{A}}$. of the algorithm $\mathfrak{A}$. Using the assumption on the regret lower bound for non-conservative algorithm in the problem $\mathfrak{P}$, we show that the budget can be lower-bounded yielding the result thanks to Eq. (6).

Example of Lower Bounds. For instance, in the multi-armed bandits, by leveraging the lower-bound in (Thm. 15.2 Lattimore & Szepesvári, 2020), we can obtain the following corollary of Theorem 1.

Corollary 1. *For any $K \in \mathbb{N}^\star$, $\alpha \in [0,1]$, $\mu_0 \in [0,1]$, $\delta \in (0,1)$ and a conservative algorithm $\mathfrak{A}$ then there exists $\mu \in [0,1]^K$ such that $\sum_{l=1}^t \mu_{\pi_l} \geq (1-\alpha)\mu_0 t$ with high probability for any $t \leq T$. Then, for $T \geq \frac{A}{\alpha\mu_0 \cdot (\alpha\mu_0 + \Delta_0)} + \frac{\sqrt{A}}{\alpha\mu_0 + \Delta_0}$, $R_T(\mu, \mathfrak{A}) \gtrsim \max\left\{ \sqrt{AT}, \frac{A\Delta_0}{\alpha\mu_0 \cdot (\alpha\mu_0 + \Delta_0)} \right\}$.*

This result resemble the lower-bound in (Wu et al., 2016). Their lower bound scales with $\frac{1}{\alpha\mu_0}$, whereas our lower bound has an additional multiplicative term $\frac{\Delta_0}{\alpha\mu_0 + \Delta_0}$. Although our bound seems less tight, by instantiating it in the "hard" instance of Wu et al. (2016, Thm. 9), we recover their lower bound, since $\frac{\Delta_0}{\alpha\mu_0 + \Delta_0} \geq 0.9$ has a constant effect. However, the explicit dependence on the sub-optimality gap Δ_0 makes our lower bound more adaptive and more informative about the shape of regret we should aim at when constructing conservative algorithms.

The generality of Theorem 1 allows us to derive lower-bounds for conservative exploration in many different problems, where the lower-bound was unknown. Table 1 reports the lower-bound obtained through Theorem 1. Please refer to Appendix B for lower-bounds for non-conservative exploration. In linear bandits, the lower bound we obtain matches the result in (Kazerouni et al., 2016; Garcelon et al., 2020b), showing the optimality of their algorithms. In tabular MDPs, our result shows that the dependence on S, A and H of CUCBVI (Garcelon et al., 2020a) is not optimal. Finally, by instantiating Theorem 1 in low-rank MDPs, we obtain the first lower bound for this setting.

5 UPPER BOUNDS

In this section, we show how to leverage the framework of Sec. 3 to derive an algorithm for any conservative sequential decision-making problem. We first show that when knowing Δ_0 a simple algorithm achieves a minimax regret, as prescribed by our lower bound of Sec. 4. Then, we show how to remove this knowledge without hurting the performance by combining our framework and the idea of lower confidence bound. This allows to dynamically adapt the budget and overcome the need of knowing Δ_0. If the non-conservative algorithm is minimax optimal, then also the conservative algorithm is minimax optimal.

5.1 THE BUDGET-EXPORATION ALGORITHM

Given a non-conservative algorithm $\widetilde{\mathfrak{A}}$, the minimum amount of rewards needed to play this non-conservative algorithm for T consecutive steps is the budget defined in Def. 1. Indeed, if we denote by $\{\tilde{\pi}_l \mid l \leq T\}$ the sequence of non-conservative policies executed by $\widetilde{\mathfrak{A}}$, then for any set $\mathcal{O} \subset [T]$ the budget can be rewritten as:

$$\mathcal{B}_T(\mathcal{O}, \{\tilde{\pi}_l \mid l \leq T\}) = \max_{t \in \mathcal{O}} \sum_{l \in \mathcal{O} \cap [t]} (1-\alpha)V^{\pi_0} - V^{\pi_l}$$

$$= \max_{t \in \mathcal{O}} \sum_{l \in \mathcal{O} \cap [t]} \left(V^\star - V^{\pi_l} - (\Delta_0 + \alpha V^{\pi_0})|\mathcal{O} \cap [t]| \right).$$

Let's define $R_{\mathcal{O} \cap [t]}(\widetilde{\mathfrak{A}}) := \sum_{l \in \mathcal{O} \cap [t]} V^\star - V^{\pi_l}$ the regret over the time steps in $\mathcal{O}$ of the non-conservative algorithm $\widetilde{\mathfrak{A}}$. For most non-conservative algorithms with minimax regret bound, $\tilde{R}_T(\widetilde{\mathfrak{A}}, \mathcal{O}) = \mathcal{O}(C\sqrt{|\mathcal{O} \cap [t]|})$ w.h.p., where $C \in \mathbb{R}$ is a problem-dependent quantity as in Theorem 1. For example, in multi-armed bandit $C = \sqrt{A}$ for the UCB algorithm or $C = \sqrt{H^3 SA}$ for the UCBVI-BF algorithm (Azar et al., 2017). This implies that the budget required by $\widetilde{\mathfrak{A}}$ is at least $\frac{C^2}{\Delta_0 + \alpha V^{\pi_0}}$. Therefore, the simple algorithm playing the baseline policy for the first $T_0 := O(\frac{C^2}{(\alpha V^{\pi_0} + \Delta_0)\alpha V^{\pi_0}})$ steps and then running the non-conservative algorithm $\widetilde{\mathfrak{A}}$, is conservative. We call such algorithm Budget-Exporation (see Alg. 1). This algorithm is conservative and minimax optimal. Indeed, we can show (see Theorem 2) that the regret upper bound of Budget-Exporation matches the lower bounds of Section 4. While knowing Δ_0 in advance may be a restrictive assumption, it is interesting that a two-stage algorithm structure (deploying a baseline policy and then a non-conservative policy) is enough to achieve minimax optimality.

Algorithm 1: Budget-Exporation

Input: A non-conservative algorithm $\widetilde{\mathfrak{A}}$, conservative policy cumulative reward V^{π_0},
     conservative level: $\alpha \in (0,1)$,baseline action gap: $\Delta_0 = V^\star - V^{\pi_0}$ and a constant C

1 Set $B = \frac{C^2}{\alpha V^{\pi_0} + \Delta_0}$ and $T_0 = \frac{B}{\alpha V^{\pi_0}}$;
2 **for** $t = 1, \ldots, T$ **do**
3   **if** $t < T_0$ **then**
4   Play π_0;
5   **else**
6   Play according to $\tilde{\mathfrak{A}}$;
7   **end**
8 **end**

Theorem 2. *Consider an algorithm $\widetilde{\mathfrak{A}}$, $\delta \in (0,1)$ and constant $C \in \mathbb{R}$ such that with probability at least $1 - \delta$, for any $T \geq 1$, $R_T(\widetilde{\mathfrak{A}}) \leq \widetilde{O}(C\sqrt{T})$. Then for any $T \geq 1$, the regret of* **Budget-Exporation** *is bounded with probability at least $1 - \delta$ by $\widetilde{O}(C\sqrt{T} + \frac{C^2 \Delta_0}{\alpha V^{\pi_0}(\alpha V^{\pi_0} + \Delta_0)})$.*

Instantiating Thm. 1 with $\widetilde{\mathfrak{A}}$ being the UCB algorithm (Lattimore & Szepesvári, 2020), then $C = \sqrt{A}$ and the regret of **Budget-Exporation** is bounded w.h.p. by $\widetilde{O}(\sqrt{AT} + \frac{A\Delta_0}{\alpha V^{\pi_0}(\alpha \mu_0 + \Delta_0)})$, that matches our novel lower bound introduced in Sec. 4. Similar results can be obtained for the other settings, see Table 1. In linear bandit we consider LinUCB as the non-conservative algorithm, leading to $C = d$. Similarly, in tabular MDP and low-ran MDPs, we get $C = \sqrt{H^3 SA}$ and $C = \sqrt{d^3 H^4}$ respectively using UCBVI-BF (Azar et al., 2017) and LSVI-UCB (Jin et al., 2020). Refer to Table 1 for a complete comparison of the results.

5.2 THE LCBCE ALGORITHM

When Δ_0 is unknown, we aim to use the same idea as Budget-Exporation, that is to say to play a policy different than the baseline one only if the budget is positive. To achieve this, we need to build an online estimate of the conservative budget which amounts to build a lower confidence bound (w.h.p.) on the value function of any policy π. Therefore, assuming a non-conservative algorithm $\widetilde{\mathfrak{A}}$ builds such confidence bounds, for example by estimate the MDP as done by Garcelon et al. (2020a), we show how our budget framework helps to derive a conservative regret bound.

Let's consider a non-conservative algorithm $\widetilde{\mathfrak{A}} = \{\pi_t \mid t \leq T\}$ able to construct a high probability lower bound on the set of selected policies. That is, for any time $t \leq T$ and $\delta \in (0,1)$, $\widetilde{\mathfrak{A}}$ computes a sequence of real numbers $(\lambda_t^{\pi_k}(\delta))_{k \leq t}$ such that with probability at least $1 - \delta$, for all $k \leq t$, $\lambda_t^{\pi_k}(\delta) \leq V^{\pi_k}$. Using these lower bounds, we can define a proxy to the budget for $\widetilde{\mathcal{B}}_{T,\delta}(\mathcal{O}, \widetilde{\mathfrak{A}})$ for any subset $\mathcal{O} \subset [T]$ by

$$\widetilde{B}_{T,\delta}\left(\mathcal{O}, \widetilde{\mathfrak{A}}\right) = \max_{t \in \mathcal{O}} \sum_{l \in \mathcal{O} \cap [t]} \left((1-\alpha)V^{\pi_0} - \lambda_t^{\pi_l}(\delta)\right), \qquad (7)$$

with $(\pi_l)_{l \in O}$ the sequence of policies computed by the non-conservative algorithm $\widetilde{\mathfrak{A}}$. Then following from the definition of $(\lambda_t^{\pi_l}(\delta))_{l \leq t}$, we have that with probability at least $1 - \delta$ that $\widetilde{B}_{T,\delta}\left(O, \widetilde{\mathfrak{A}}\right) \geq \mathcal{B}_T(\mathcal{O}, \widetilde{\mathfrak{A}})$. This shows that it is possible to compute $\widetilde{B}_{T,\delta}\left(O, \widetilde{\mathfrak{A}}\right)$ without knowledge of the environment and the baseline parameters. The idea of our algorithm is now to play a non-conservative policy π_t at time t only if the difference between the proxy to the budget of $\widetilde{\mathfrak{A}}$ and the reward accumulated by playing the baseline policy is negative. Formally, the condition is $\widetilde{B}_{t,\delta}\left(S_t \cup t, \widetilde{\mathfrak{A}}\right) \leq \alpha V^{\pi_0}(t - 1 - |S_t|)$ where S_t is the set of time step where a non-conservative policy was deployed in episodes before t. As a result, the minimum budget that $\widetilde{\mathfrak{A}}$ requires to be conservative is $\max_t \widetilde{B}_{t,\delta}\left(S_t \cup t, \widetilde{\mathfrak{A}}\right) = \max_{t \in [T]} \sum_{l \in S_t} \left((1-\alpha)V^{\pi_0} - \lambda_t^{\pi_l}(\delta)\right)$. The algorithm, called *Lower Confidence Bound for Conservative Exploration* (LCBCE), is detailed in Alg. 2.

Algorithm 2: Lower Confidence Bound for Conservative Exploration

Input: A non-conservative algorithm $\widetilde{\mathfrak{A}}$, $\delta \in (0, 1)$, lower confidence bounds $\lambda_t^{\pi_k} \leq V^{\pi_k}$, conservative policy value V^{π_0}, $\alpha \in (0, 1)$

1 Set $B = 0$;   // the accumulated budget
2 Set $t' = 0$;   // the number of steps in which the agent acts as $\widetilde{\mathfrak{A}}$
3 **for** $t = 1, 2, ..., T$ **do**
4     $\widetilde{\mathfrak{A}}$ gives lower bound $\lambda_{t'+1}$ and a policy $\tilde{\pi}_{t'+1}$;
5   Compute $\lambda = \sum_{k=1}^{t'} \lambda_{t'+1}^{\pi_k} + \lambda_{t'+1}^{\tilde{\pi}_{t'+1}}$;   // lower bound of expected total reward
6   **if** $\lambda - (t'+1)\alpha V^{\pi_0} < B$ **then**
7   Play $\pi_t = \pi_0$;
8        $B = B + \alpha V^{\pi_0}$;
9   **else**
10   Play $\pi_t = \tilde{\pi}_{t'+1}$;
11        $t' = t' + 1$;
12   **end**
13 **end**

Next, we show the regret bound of LCBCE.

Theorem 3. *Consider an algorithm $\widetilde{\mathfrak{A}}$, $\delta \in (0, 1)$ and constant $C \in \mathbb{R}$ such that with probability at least $1 - \delta$, for any $T \geq 1$, $R_T(\widetilde{\mathfrak{A}}) \leq \widetilde{O}(C\sqrt{T})$. If $\widetilde{\mathfrak{A}}$ computes lower confidence bound such that $\sum_{k=1}^{t} \left(V^{\pi_k} - \lambda_t^{\pi_k} \right) \leq \widetilde{O}(C\sqrt{T})$ with probability at least $1 - \delta$, then for any $T \geq 1$, the regret of LCBCE is bounded with probability at least $1 - \delta$ by $\widetilde{O}(C\sqrt{T} + \frac{C^2 \Delta_0}{\alpha V^{\pi_0}(\alpha V^{\pi_0} + \Delta_0)})$.*

In the MAB and tabular case, LCBCE paired with UCB achieves a better regret bound compared with previous papers(Garcelon et al., 2020a; Wu et al., 2016). We also provide the first minimax optimal bound for the case of unknown baseline parameters. Finally, in low rank MDPs we recover the same rate, up to constant term, as in the case of known baseline. See Table 1 for a complete comparison. The improvements are due the use of the budget (as defined in Sec. 3). Indeed, we have that, the regret of LinUCB can be written as:

$$R_T(\mathfrak{A}) \lesssim R_{S_T}(\widetilde{\mathfrak{A}}) + \frac{\max_t \widetilde{B}_{t,\delta}\left(S_t, \widetilde{\mathfrak{A}}\right) \Delta_0}{\alpha V^{\pi_0}}.$$

Therefore, to bound the regret it is sufficient to bound the proxy of the budget. Under the assumption in Thm. 3, we have that:

$$\max_t \widetilde{B}_{t,\delta}\left(S_t, \widetilde{\mathfrak{A}}\right) = \max_{t \leq T} \sum_{l \in S_t}(1-\alpha)V^{\pi_0} - V^{\pi_k} + \sum_{l \in S_t} V^{\pi_k} - \lambda_t^{\pi_l}$$

$$\leq \max_t 2C\sqrt{t} - (\Delta_0 + \alpha V^{\pi_0})t = \widetilde{O}\left(\frac{C^2}{\alpha V^{\pi_0} + \Delta_0}\right).$$

Hence, this leads to the result in Thm. 3.

6 CONCLUSION

We present a unified framework for conservative exploration in sequential decision-making problems. This framework can be leveraged to derive both minimax lower and upper bounds. In bandits, we provide novel lower bounds that highlighted the optimality of existing algorithms. In RL, we provide the first lower bound for tabular MDPs and a matching upper bounds, and the first analysis for low rank MDPs. An interesting question raised by our paper is whether is it possible to leverage this framework to derive problem-dependent logarithmic bounds for conservative exploration. Another direction could be to investigate the usage of model-free algorithms (e.g., Q-learning (Jin et al., 2018)) for conservative exploration.

REFERENCES

Eitan Altman. *Constrained Markov decision processes*, volume 7. CRC Press, 1999.

Sanae Amani, Mahnoosh Alizadeh, and Christos Thrampoulidis. Linear stochastic bandits under safety constraints. In *NeurIPS*, pp. 9252–9262, 2019.

Mohammad Gheshlaghi Azar, Ian Osband, and Rémi Munos. Minimax regret bounds for reinforcement learning. In *International Conference on Machine Learning*, pp. 263–272. PMLR, 2017.

Dongsheng Ding, Kaiqing Zhang, Tamer Basar, and Mihailo R. Jovanovic. Natural policy gradient primal-dual method for constrained markov decision processes. In *NeurIPS*, 2020.

Dongsheng Ding, Xiaohan Wei, Zhuoran Yang, Zhaoran Wang, and Mihailo R. Jovanovic. Provably efficient safe exploration via primal-dual policy optimization. In *AISTATS*, volume 130 of *Proceedings of Machine Learning Research*, pp. 3304–3312. PMLR, 2021.

Yihan Du, Siwei Wang, and Longbo Huang. A one-size-fits-all solution to conservative bandit problems. *CoRR*, abs/2012.07341, 2020.

Yonathan Efroni, Shie Mannor, and Matteo Pirotta. Exploration-exploitation in constrained mdps. *CoRR*, abs/2003.02189, 2020.

Evrard Garcelon, Mohammad Ghavamzadeh, Alessandro Lazaric, and Matteo Pirotta. Conservative exploration in reinforcement learning. In *International Conference on Artificial Intelligence and Statistics*, pp. 1431–1441. PMLR, 2020a.

Evrard Garcelon, Mohammad Ghavamzadeh, Alessandro Lazaric, and Matteo Pirotta. Improved algorithms for conservative exploration in bandits. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pp. 3962–3969, 2020b.

Thomas Jaksch, Ronald Ortner, and Peter Auer. Near-optimal regret bounds for reinforcement learning. *Journal of Machine Learning Research*, 11(4), 2010.

Chi Jin, Zeyuan Allen-Zhu, Sébastien Bubeck, and Michael I. Jordan. Is q-learning provably efficient? In *NeurIPS*, pp. 4868–4878, 2018.

Chi Jin, Zhuoran Yang, Zhaoran Wang, and Michael I Jordan. Provably efficient reinforcement learning with linear function approximation. In *Conference on Learning Theory*, pp. 2137–2143. PMLR, 2020.

Sumeet Katariya, Branislav Kveton, Zheng Wen, and Vamsi K. Potluru. Conservative exploration using interleaving. In *AISTATS*, volume 89 of *Proceedings of Machine Learning Research*, pp. 954–963. PMLR, 2019.

Abbas Kazerouni, Mohammad Ghavamzadeh, Yasin Abbasi-Yadkori, and Benjamin Van Roy. Conservative contextual linear bandits. *arXiv preprint arXiv:1611.06426*, 2016.

Romain Laroche, Paul Trichelair, and Remi Tachet des Combes. Safe policy improvement with baseline bootstrapping. In *ICML*, volume 97 of *Proceedings of Machine Learning Research*, pp. 3652–3661. PMLR, 2019.

Tor Lattimore and Csaba Szepesvári. *Bandit algorithms*. Cambridge University Press, 2020.

Pierre Ménard, Omar Darwiche Domingues, Xuedong Shang, and Michal Valko. UCB momentum q-learning: Correcting the bias without forgetting. *CoRR*, abs/2103.01312, 2021.

Aldo Pacchiano, Mohammad Ghavamzadeh, Peter L. Bartlett, and Heinrich Jiang. Stochastic bandits with linear constraints. In *AISTATS*, volume 130 of *Proceedings of Machine Learning Research*, pp. 2827–2835. PMLR, 2021.

Steven E Shreve and Dimitri P Bertsekas. Alternative theoretical frameworks for finite horizon discrete-time stochastic optimal control. *SIAM Journal on control and optimization*, 16(6):953–978, 1978.

Thiago D. Simão and Matthijs T. J. Spaan. Safe policy improvement with baseline bootstrapping in factored environments. In *AAAI*, pp. 4967–4974. AAAI Press, 2019.

P. Thomas, G. Theocharous, and M. Ghavamzadeh. High confidence off-policy evaluation. In *Proceedings of the Twenty-Ninth Conference on Artificial Intelligence*, 2015a.

P. Thomas, G. Theocharous, and M. Ghavamzadeh. High confidence policy improvement. In *Proceedings of the Thirty-Second International Conference on Machine Learning*, pp. 2380–2388, 2015b.

Kun Wang, Canzhe Zhao, Shuai Li, and Shuo Shao. Conservative contextual combinatorial cascading bandit. *CoRR*, abs/2104.08615, 2021.

Yifan Wu, Roshan Shariff, Tor Lattimore, and Csaba Szepesvári. Conservative bandits. In *International Conference on Machine Learning*, pp. 1254–1262. PMLR, 2016.

Andrea Zanette and Emma Brunskill. Tighter problem-dependent regret bounds in reinforcement learning without domain knowledge using value function bounds. In *ICML*, volume 97 of *Proceedings of Machine Learning Research*, pp. 7304–7312. PMLR, 2019.

Andrea Zanette, Alessandro Lazaric, Mykel J. Kochenderfer, and Emma Brunskill. Learning near optimal policies with low inherent bellman error. In *ICML*, volume 119 of *Proceedings of Machine Learning Research*, pp. 10978–10989. PMLR, 2020.

Xiaojin Zhang, Shuai Li, and Weiwen Liu. Contextual combinatorial conservative bandits. *CoRR*, abs/1911.11337, 2019.

Zihan Zhang, Xiangyang Ji, and Simon S Du. Is reinforcement learning more difficult than bandits? a near-optimal algorithm escaping the curse of horizon. *arXiv preprint arXiv:2009.13503*, 2020a.

Zihan Zhang, Yuan Zhou, and Xiangyang Ji. Almost optimal model-free reinforcement learningvia reference-advantage decomposition. In *NeurIPS*, 2020b.

Liyuan Zheng and Lillian J. Ratliff. Constrained upper confidence reinforcement learning. In *L4DC*, volume 120 of *Proceedings of Machine Learning Research*, pp. 620–629. PMLR, 2020.

Dongruo Zhou, Quanquan Gu, and Csaba Szepesvári. Nearly minimax optimal reinforcement learning for linear mixture markov decision processes. *CoRR*, abs/2012.08507, 2020.