Continuous MDP Homomorphisms and Homomorphic Policy Gradient

Abstract

Abstraction has been widely studied as a way to improve the efficiency and general-ization of reinforcement learning algorithms. In this paper, we study abstraction in the continuous-control setting. We extend the definition of MDP homomorphisms to encompass continuous actions in continuous state spaces. We derive a policy gradient theorem on the abstract MDP, which allows us to leverage approximate symmetries of the environment for policy optimization. Based on this theorem, we propose an actor-critic algorithm that is able to learn the policy and the MDP homo-morphism map simultaneously, using the lax bisimulation metric. We demonstrate the effectiveness of our method on benchmark tasks in the DeepMind Control Suite. Our method's ability to utilize MDP homomorphisms for representation learning leads to improved performance when learning from pixel observations.

1 Introduction

For reinforcement learning from high-dimensional ob-servations, such as images, learning a simpler problem by abstraction from the original problem can be criti-cal [2, 49]. The coupling between states, actions and rewards complicates learning RL abstractions. MDP homomorphisms [64, 65, 67, 59] define a concept that allows one to exploit symmetries, yielding behavioral equivalence and preserving values, while giving the po-tential to arrive at a substantially smaller MDP. Recent works [81, 83, 11] have shown that using MDP homo-morphisms is effective to guide learning in discrete prob-lems. This paper is one of the first to consider MDP homomorphisms in the continuous-control setting and to develop actor-critic algorithms with a tightly inte-grated state-action abstraction. To that end, we identify and answer a series of key challenges:

Figure 1: Schematics of our method. The actual MDP $\mathcal{M}$ is used to train $Q^{\pi^\uparrow}$ and update $\pi^\uparrow$ with DPG, while the abstract MDP $\overline{M}$ is used to train $Q^{\overline{\pi}}$ and update $\overline{\pi}$ with HPG. $\overline{\mathcal{M}}$ is the MDP homomorphic image of $\mathcal{M}$ obtained by learning the ho-momorphism map $h = (f, g_s)$. Policies $\pi^\uparrow$ and $\overline{\pi}$ can be derived from each other.

Can MDP homomorphisms be defined on continuous state and action spaces? Our first contribution is to define continuous MDP homomorphisms on continuous state and action spaces, which requires more intricate proofs that do not follow in any direct way from the finite case and requires tools from measure theory and differential geometry.

Can MDP homomorphisms be tightly integrated into the policy gradient? Our second contri-bution is the derivation of the *homomorphic policy gradient* (HPG) theorem to closely integrate the abstract MDP into the policy gradient. Importantly, we rigorously prove that performing HPG on the abstract MDP is equivalent to performing the deterministic policy gradient (DPG) on the actual

MDP. Therefore, HPG can act as an additional gradient estimator capable of utilizing approximate symmetries for improved sample efficiency. To derive these results, we prove that continuous MDP homomorphisms preserve value functions [33], which in turn enables their use for policy evaluation.

Can MDP homomorphisms be learned simultaneously with the optimal policy in a practical deep reinforcement learning algorithm? We propose a deep actor-critic algorithm, depicted in Figure 1, based on HPG, referred to as *Deep Homomorphic Policy Gradient* (DHPG), that unifies state and action abstractions. DHPG is able to simultaneously learn the policy and the homomorphism map using the lax bisimulation metric [78], a metric for measuring the equivalence of state-action pairs under an MDP homomorphism relation. We empirically show that state-action abstractions learned through MDP homomorphisms provide a natural inductive bias for representation learning.

Despite the existence of well-studied abstraction notions, learning state abstractions in a scalable fashion for continuous control remains a key challenge. In contrast to previous works on learning MDP homomorphisms [81, 83, 11], our algorithm is readily applicable to continuous actions, and compared to previous works guided by bisimulations [91, 29, 46], our algorithm leads to more robust solutions, as suggested by our empirical results. Most importantly, the key difference between prior works [81, 83, 91, 29, 46] and our method is the homomorphic policy gradient theorem which allows for a tight integration of the abstraction notion into the policy gradient. Our contributions are:

1. Defining continuous MDP homomorphisms on continuous state and action spaces, using tools from measure theory and differential geometry.
2. Proving that continuous MDP homomorphisms preserve value and optimal value functions.
3. Deriving the homomorphic policy gradient theorem.
4. Developing a deep actor-critic algorithm for learning the optimal policy simultaneously with the MDP homomorphism map in challenging continuous control problems.

DHPG improves upon strong baselines on pixel observations [88, 91] on DM Control, and our visualizations demonstrate the potential of MDP homomorphisms in learning structured representations that can preserve values and represent the minimal MDP image. To the best of our knowledge, this is the first homomorphic policy gradient derivation and the first work to define and scale up MDP homomorphisms to continuous visual control problems. Our code will be publicly available.

2 Background

2.1 Markov Decision Processes

We consider the standard MDP that is defined by a 5-tuple $(\mathcal{S}, \mathcal{A}, \tau_a, R, \gamma)$, with *state space* $\mathcal{S}$, *action space* $\mathcal{A}$, *transition dynamics* $\tau_a : \mathcal{S} \times \mathcal{A} \to \mathrm{Dist}(\mathcal{S})$, *reward function* $R : \mathcal{S} \times \mathcal{A} \to \mathbb{R}$, and *discount factor* $\gamma \in (0, 1]$. The goal is to find a policy $\pi : \mathcal{S} \to \mathrm{Dist}(\mathcal{A})$ that maximizes the expected sum of discounted rewards, the *expected return*, defined as $\mathbb{E}_\pi[R_t] = \mathbb{E}_\pi[\sum_{k=0}^{T} \gamma^k r_{t+k+1}]$. *Value function* $V^\pi(s)$ denotes the expected return from s under policy π, and *action-value function* $Q^\pi(s, a)$ denotes the expected return from s after taking action a under π. Value functions are fixed points of the Bellman equation [8] and can be computed iteratively through a process referred to as *policy evaluation* [75]. Similarly, optimal value functions $V^*(s)$ and $Q^*(s, a)$ are fixed points of the Bellman optimality equation [8].

2.2 MDP Homomorphisms

MDP homomorphisms are formally defined for finite MDPs by Ravindran and Barto [65] as:

Definition 1 (MDP Homomorphism). An *MDP homomorphism* $h = (f, g_s) : \mathcal{M} \to \overline{\mathcal{M}}$ is a surjective map from a finite MDP $\mathcal{M} = (\mathcal{S}, \mathcal{A}, R, \tau_a, \gamma)$ onto an abstract finite MDP $\overline{\mathcal{M}} = (\overline{\mathcal{S}}, \overline{\mathcal{A}}, \overline{R}, \overline{\tau}_{\overline{a}}, \gamma)$ where $f : \mathcal{S} \to \overline{\mathcal{S}}$ and $g_s : \mathcal{A} \to \overline{\mathcal{A}}$ are surjective maps onto the abstract state and action spaces:

$$\text{Invariance of reward: } \overline{R}(f(s), g_s(a)) = R(s, a) \quad \forall s \in \mathcal{S}, a \in \mathcal{A} \tag{1}$$

$$\text{Equivariance of transitions: } \overline{\tau}_{g_s(a)}(f(s')|f(s)) = \sum_{s'' \in [s']_{B_h|\mathcal{S}}} \tau_a(s''|s) \quad \forall s \in \mathcal{S}, a \in \mathcal{A} \tag{2}$$

where B_h is the partition of $\mathcal{S}$ induced by the equivalence relation of homomorphism h, $B_h|\mathcal{S}$ is the projection of B_h onto $\mathcal{S}$, and $[s']_{B_h|\mathcal{S}}$ denotes the block of $B_h|\mathcal{S}$ to which s' belongs. Thus, when applying action a in state s, the right-hand side is the probability that the resulting state is in

$[s']_{B_h|\mathcal{S}}$. The abstract MDP $\overline{\mathcal{M}}$ is in fact the quotient MDP $\mathcal{M}/B_h$ based on the homomorphism map $h:\mathcal{M} \to \mathcal{M}/B_h$. As MDP homomorphisms are sensitive with respect to changes in rewards or transitions, *approximate* MDP homomorphisms [67] allow equations (1-2) to hold approximately. The significance of MDP homomorphisms is the *optimal value equivalence* between $\mathcal{M}$ and $\overline{\mathcal{M}}$ [65]:

$$V^*(s) = \overline{V}^*(f(s)) \quad \forall s \in \mathcal{S}, \qquad Q^*(s,a) = \overline{Q}^*(f(s), g_s(a)) \quad \forall s \in \mathcal{S}, a \in \mathcal{A} \tag{3}$$

which in turn allows for learning the optimal policy $\overline{\pi}^*$ in the abstract MDP and consequently *lifting* it to obtain the optimal policy in the actual MDP, using:

$$\pi^{\uparrow}(a|s) = \frac{\overline{\pi}(\overline{a}|f(s))}{|\{a \in g_s^{-1}(\overline{a})\}|}, \qquad \forall s \in \mathcal{S}, a \in g_s^{-1}(\overline{a})$$

where $g_s^{-1}(\overline{a})$ denotes the set of actions that have the same image $\overline{a}$ under g_s. Equivalently, the two policies must satisfy $\sum_{a \in g_s^{-1}(\overline{a})} \pi^{\uparrow}(a|s) = \overline{\pi}(\overline{a}|f(s))$ for all $s \in \mathcal{S}$ and $\overline{a} \in \overline{\mathcal{A}}$.

2.3 Bisimulation and Lax Bisimulation Metrics

Bisimulation for finite MDPs [20, 30] defines an equivalence relation on $\mathcal{S}$ where two states s_i and s_j are equivalent or *bisimilar* if $R(s_i, a) = R(s_j, a)$ and $\tau_a(C|s_i) = \tau_a(C|s_j)$ for all $a \in \mathcal{A}$ and every equivalence class C defined by the equivalence relation. The rigidity of bisimulation limits its applications. *Bisimulation metrics* [26, 25, 27] measure the equivalence as an approximation:

$$d_{\mathrm{bisim}}(s_i, s_j) = \max_{a \in \mathcal{A}} c_r |R(s_i, a) - R(s_j, a)| + c_t K(\tau_a(\cdot|s_i), \tau_a(\cdot|s_j)), \tag{4}$$

where the first term measures reward similarity and K is the Kantorovich (Wasserstein) metric measuring the distance between the transition probabilities. However, bisimulation metrics can still be brittle as they require the behaviour to match for all actions. This may be problematic particularly in the case of continuous actions in which small changes to actions may not drastically change the outcome. Additionally, bisimulation metrics are not able to represent environment symmetries. Instead, *lax bisimulation* [78] waives the requirement on action matching in favor of extending the state equivalence relation to state-action equivalence. Taylor et al. [78] show that lax bisimulation is precisely the same relation as the MDP homomorphism and define the *lax bisimulation metric* as:

$$d_{\mathrm{lax}}((s_i, a_i), (s_j, a_j)) = c_r |R(s_i, a_i) - R(s_j, a_j)| + c_t K(\tau_{a_i}(\cdot|s_i), \tau_{a_j}(\cdot|s_j)). \tag{5}$$

Furthermore, Taylor et al. [78] show that minimizing the lax bisimulation metric corresponds to finding approximate MDP homomorphisms and bound the value error.

3 Value Equivalence Property

To motivate the use of MDP homomorphisms for policy evaluation and consequently policy optimization, we first prove their *value equivalence property* in the finite case as the generalization of the prior result of the *optimal* value equivalence [65], stated in Equation (3). The proof is in Appendix C.1.

Theorem 1 (Value Equivalence). *Let $\overline{\mathcal{M}}$ be the image of an MDP homomorphism h from a finite $\mathcal{M}$. Then any two corresponding policies $\pi^{\uparrow} = lift(\overline{\pi})$ have equivalent values:*

$$V^{\pi^{\uparrow}}(s) = V^{\overline{\pi}}(f(s)) \quad \forall s \in \mathcal{S}, \qquad Q^{\pi^{\uparrow}}(s,a) = Q^{\overline{\pi}}(f(s), g_s(a)) \quad \forall s \in \mathcal{S}, a \in \mathcal{A}$$

4 Continuous MDP Homomorphisms

To concretely lay out the foundations of using MDP homomorphisms for continuous control, we extend their definition to continuous state and action spaces, and derive results analogous to the finite case. First, we define continuous MDPs and state our underlying assumptions. Importantly, the correct definitions of continuous MDPs and continuous MDP homomorphisms require care regarding measurability and differentiability of spaces, and our formulation is chosen to fit the HPG derivation; see Appendix A.2 for an overview of the tools we used from measure theory and differential geometry.

Definition 2 (Continuous MDP). A *continuous Markov decision process (MDP)* is a 6-tuple:

$$\mathcal{M} = (\mathcal{S}, \Sigma, \mathcal{A}, \forall a \in \mathcal{A} \ \tau_a : \mathcal{S} \times \Sigma \to [0,1], R : \mathcal{S} \times \mathcal{A} \to \mathbb{R}, \gamma)$$

where $\mathcal{S}$, the state space is assumed to be a Polish space, Σ is a σ-algebra on $\mathcal{S}$[1], $\mathcal{A}$, the space of *actions*, is a locally compact metric space, usually taken to be a subset of $\mathbb{R}^n$, τ_a is the transition probability kernel for each possible action a, for each fixed s, $\tau_a(\cdot|s)$ is a probability distribution on Σ while R is the reward function, and γ is the discount factor. Furthermore, for all $s \in \mathcal{S}$ and $B \in \Sigma$ the map $a \mapsto \tau_a(B|s)$ is smooth. The last assumption is required for differentiability with respect to actions a, which is needed in Section 5 for deriving the HPG theorem.

Given the continuous MDPs described above, we define continuous MDP homomorphisms. The equivariance condition on the transition dynamics, Equation (2), can no longer be expressed in terms of a discrete sum over partitions, and instead we use the σ-algebra structure on the different state spaces.

Definition 3 (Continuous MDP Homomorphism). A *continuous MDP homomorphism* is a map $h = (f, g_s) : \mathcal{M} \to \overline{\mathcal{M}}$ where $f : \mathcal{S} \to \overline{\mathcal{S}}$ and for every s in $\mathcal{S}$, $g_s : \mathcal{A} \to \overline{\mathcal{A}}$ are measurable, surjective maps such that the following hold:

$$\text{Invariance of reward: } \overline{R}(f(s), g_s(a)) = R(s, a) \qquad \forall s \in \mathcal{S}, a \in \mathcal{A} \qquad (6)$$

$$\text{Equivariance of transitions: } \overline{\tau}_{g_s(a)}(\overline{B}|f(s)) = \tau_a(f^{-1}(\overline{B})|s) \qquad \forall s \in \mathcal{S}, a \in \mathcal{A}, \overline{B} \in \overline{\Sigma} \qquad (7)$$

Note that if g_s is the identity map, the second condition reduces to $\overline{\tau}_a(\overline{B}|f(s)) = \tau_a(f^{-1}(\overline{B})|s)$ which is simply the condition for preservation of transition probabilities as used in bisimulation [20].

4.1 Optimal Value Equivalence

Assuming the conditions given in Definition 3, we prove that optimal value functions are preserved by the continuous MDP homomorphism as in the finite case.

Theorem 2 (Optimal Value Equivalence). *Let $\overline{\mathcal{M}} = (\overline{\mathcal{S}}, \overline{\Sigma}, \overline{\mathcal{A}}, \overline{\tau_a}, \overline{R})$ be the image of a continuous MDP homomorphism $h = (f, g_s)$ from $\mathcal{M} = (\mathcal{S}, \Sigma, \mathcal{A}, \tau_a, R)$. Then:*

$$V^*(s) = \overline{V}^*(f(s)) \quad \forall s \in \mathcal{S}, \qquad Q^*(s, a) = \overline{Q}^*(f(s), g_s(a)) \quad \forall (s, a) \in \mathcal{S} \times \mathcal{A} \qquad (8)$$

The proof, given in Appendix C.2, uses the change of variable formula of the pushforward measure of $\tau_a(\cdot|s)$ with respect to f to change the integration space from $\mathcal{S}$ to $\overline{\mathcal{S}}$.

4.2 Value Equivalence for Lifting Deterministic Policies

As in the finite case, we also require a lifting process to define $\pi^{\uparrow} = lift(\overline{\pi})$ given a policy $\overline{\pi}$ on the abstract MDP. In general, the lifted policy needs to satisfy the relation $\pi^{\uparrow}(g_s^{-1}(\beta)|s) = \overline{\pi}(\beta|f(s))$ for every Borel set $\beta \subseteq \overline{\mathcal{A}}$ and $s \in \mathcal{S}$. While our initial progress shows that lifted stochastic policies exist based on the disintegration theorem, the full proof and design of a computationally tractable algorithm for this process is left for future work. Therefore, here and in the subsequent sections we assume the policy is deterministic in which case the lifted policy can be simply obtained by choosing one representative for the preimage $g_s^{-1}(\overline{\pi}(f(s)))$. If we select g_s to be a bijection, the lifted policy can be uniquely defined as $\pi^{\uparrow}(s) = g_s^{-1}(\overline{\pi}(f(s)))$. The assumption on deterministic policies is not limiting, as in general the optimal policy of a given MDP is deterministic [9]. With this lifting definition, we state and prove the following value equivalence result:

Theorem 3 (Value Equivalence for Deterministic Policies). *Let $\overline{\mathcal{M}}$ be the image of a continuous MDP homomorphism $h = (f, g_s)$ from $\mathcal{M}$, then any two deterministic policies $\pi^{\uparrow} : \mathcal{S} \to \mathcal{A}$ and $\overline{\pi} : \overline{\mathcal{S}} \to \overline{\mathcal{A}}$ where $\pi^{\uparrow} = lift(\overline{\pi})$ have equivalent value functions on their domain:*

$$V^{\pi^{\uparrow}}(s) = V^{\overline{\pi}}(f(s)) \quad \forall s \in \mathcal{S}, \qquad Q^{\pi^{\uparrow}}(s, a) = Q^{\overline{\pi}}(f(s), g_s(a)) \quad \forall (s, a) \in \mathcal{S} \times \mathcal{A}$$

The proof, given in Appendix C.3, uses the change of variable formula of the pushforward measure of $\tau_a(\cdot|s)$ with respect to f to change the integration space from $\mathcal{S}$ to $\overline{\mathcal{S}}$ and assumes g_s to be bijective.

5 Homomorphic Policy Gradient

The next goal of this work is to derive a policy gradient estimator using samples obtained from the abstract MDP. Intuitively, this allows for direct incorporation of state-action abstraction as an

---

[1]Usually the Borel algebra.

inductive bias for policy optimization, thereby reducing the variance of actor updates and improving sample efficiency. Equipped with continuous MDP homomorphisms from Definition 3 and their value equivalence property, we now derive the *homomorphic policy gradient* (HPG) theorem.

In this section, we assume having access to an MDP homomorphism map $h = (f, g_s)$, parameterized by differentiable functions. The problem of learning such mapping from samples is addressed in Section 6. Additionally, we assume the MDP and the homomorphism map adhere to the conditions of Definition 2 and Appendix B. Similarly to prior works on policy gradients [76, 70], we define the performance measure as $J(\theta) = \mathbb{E}_\pi[V^\pi(s)]$ where the expectation is over the uncertainty in transitions, rewards, and initial states. Finally, as detailed in Section 4.2, our results are derived for deterministic policies and a bijective g_s. Notably, this choice allows us to parameterize one of the policies and to uniquely derive the other policy. In practice, we parameterize the actual policy as $\pi_\theta^\uparrow$ and obtain the abstract policy as $\overline{\pi}_\theta = g_s(\pi_\theta^\uparrow(s))$. First, we show the *equivalence of policy gradients*:

Theorem 4 (Equivalence of Deterministic Policy Gradients). *Let $\overline{\mathcal{M}}$ be the image of a continuous MDP homomorphism h from $\mathcal{M}$, and let $\pi_\theta^\uparrow : \mathcal{S} \to \mathcal{A}$ be the lifted deterministic policy corresponding to the abstract deterministic policy $\overline{\pi}_\theta : \overline{\mathcal{S}} \to \overline{\mathcal{A}}$. Then for any $(s, a) \in \mathcal{S} \times \mathcal{A}$ we have:*

$$\nabla_a Q^{\pi_\theta^\uparrow}(s, a)\Big|_{a = \pi_\theta^\uparrow(s)} \nabla_\theta \pi_\theta^\uparrow(s) = \nabla_{\overline{a}} Q^{\overline{\pi}_\theta}(\overline{s}, \overline{a})\Big|_{\overline{a} = \overline{\pi}_\theta(\overline{s})} \nabla_\theta \overline{\pi}_\theta(\overline{s}).$$

The proof is given in Appendix C.4 and uses the chain rule and the inverse function theorem on manifolds, which in turn raises the need for g_s to be a bijection and local diffeomorphism. Theorem 4 highlights that the gradient of the abstract MDP is equivalent to that of the original, despite the underlying spaces being abstracted. This implies that performing HPG on the abstract MDP is equivalent to performing DPG on the actual MDP, allowing us to use them synergistically to update the same parameters θ, as shown in Figure 1.

While one can naively use Theorem 4 to substitute gradients of the standard DPG, theoretically this does not produce any useful result as the expectation remains estimated with respect to the stationary state distribution of the actual MDP $\mathcal{M}$ under $\pi_\theta^\uparrow(s)$. However, using properties of continuous MDP homomorphisms, we can change the integration space from $\mathcal{S}$ to $\overline{\mathcal{S}}$, and consequently estimate the policy gradient with respect to the stationary distribution of the abstract MDP $\overline{\mathcal{M}}$ under $\overline{\pi}_\theta(\overline{s})$:

Theorem 5 (Homomorphic Policy Gradient Theorem). *Let $\overline{\mathcal{M}}$ be the image of a continuous MDP homomorphism h from $\mathcal{M}$, and let $\overline{\pi}_\theta : \overline{\mathcal{S}} \to \overline{\mathcal{A}}$ be a deterministic abstract policy defined on $\overline{\mathcal{M}}$. Then the gradient of the performance measure $J(\theta)$, defined on the actual MDP $\mathcal{M}$, w.r.t. θ is:*

$$\nabla_\theta J(\theta) = \int_{\overline{s} \in \overline{\mathcal{S}}} \rho^{\overline{\pi}_\theta}(\overline{s}) \nabla_{\overline{a}} Q^{\overline{\pi}_\theta}(\overline{s}, \overline{a})\Big|_{\overline{a} = \overline{\pi}_\theta(\overline{s})} \nabla_\theta \overline{\pi}_\theta(\overline{s}) d\overline{s}.$$

where $\rho^{\overline{\pi}_\theta}(\overline{s})$ is the discounted state distribution of $\overline{\mathcal{M}}$ following the deterministic policy $\overline{\pi}_\theta(\overline{s})$.

The proof is given in Appendix C.5 and applies the result of Theorem 4 and the change of variables formula of the pushforward measure on the state space. The significance of Theorem 5, which forms the basis of our proposed homomorphic actor-critic algorithm, is twofold. First, we can get another estimate for the policy gradient based on the approximate MDP homomorphic image in addition to DPG. Although the two policy gradient estimates are not statistically independent from one another as they are tied through the homomorphism map, HPG will potentially have less variance at the expense of some bias due to the approximation of the MDP homomorphism.

Second, since the minimal image of an MDP is the MDP homomorphic image [65], the abstract critic $Q^{\overline{\pi}_\theta}$ is trained on a simplified problem. In other words, each abstract state-action pair $(\overline{s}, \overline{a})$ used to train $Q^{\overline{\pi}_\theta}$ represents all (s, a) pairs that are equivalent under the MDP homomorphism relation, thus improving sample efficiency. However, the amount of complexity reduction is dependent on the approximate symmetries of the environment, as also supported by our empirical results.

6 Homomorphic Actor-Critic Algorithms

We propose a deep actor-critic algorithm based on HPG by adapting DDPG [51]. We refer to our method as *Deep Homomorphic Policy Gradient* (DHPG). Although HPG is applicable to any other deterministic actor-critic, we chose DDPG as its simplicity compared to modern choices [7, 43]

allows for a better study on the impact of MDP homomorphisms. Notably, a strong advantage of DHPG is that it is readily applicable to pixel observations without the need for extra mechanisms such as image reconstruction [29, 34, 90, 36], as the notion of MDP homomorphism provides a natural inductive bias for learning representations that preserve values and optimal values.

Since DHPG is learning the MDP homomorphism map h online and concurrently with the policy, using the actual MDP for training the critic, specifically at the early stages of training, is helpful. Therefore, we utilize a separate critic for each MDP $\mathcal{M}$ and $\overline{\mathcal{M}}$. Ultimately, critics are used to update a single set of parameters, as shown in Figure 1; see Appendix D.5 for the ablation study on this.

Thus, the components of DHPG are: actual critic $Q_\psi(s, a)$, abstract critic $\overline{Q}_{\overline{\psi}}(\overline{s}, \overline{a})$, deterministic actor $a = \pi_\theta(s)$, homomorphism map $h_{\phi,\eta} = (f_\phi(s), g_\eta(s, a))$, reward predictor $\overline{R}_\rho(\overline{s})$, and probabilistic transition model $\overline{\tau}_\nu(\overline{s}'|\overline{s}, \overline{a})$ which outputs a Gaussian distribution. We use target networks and a vanilla replay buffer [57, 51]. As discussed in Section 5, an abstract actor is obtained as $\overline{a} = g_s(\pi_\theta(s))$. In case of pixel observations, a single image encoder E_μ is shared among all components.

Training the Policy and Critic. Actual and abstract critics are trained using n-step TD error for a faster reward propagation [7]. The loss function for each critic is therefore defined as the expectation of the n-step Bellman error estimated over transitions samples from the replay buffer $\mathcal{B}$:

$$\mathcal{L}_{\text{actual critic}}(\psi) = \mathbb{E}_{(s,a,s',r)\sim\mathcal{B}}\left[\left(R_t^{(n)} + \gamma^n Q_{\psi'}(s_{t+n}, a_{t+n}) - Q_\psi(s_t, a_t)\right)^2\right] \quad (9)$$

$$\mathcal{L}_{\text{abstract critic}}(\overline{\psi}, \phi, \eta) = \mathbb{E}_{(s,a,s',r)\sim\mathcal{B}}\left[\left(R_t^{(n)} + \gamma^n \overline{Q}_{\overline{\psi'}}(\overline{s}_{t+n}, \overline{a}_{t+n}) - \overline{Q}_{\overline{\psi}}(\overline{s}_t, \overline{a}_t)\right)^2\right], \quad (10)$$

where $\overline{s}_t = f_\phi(s_t)$ and $\overline{a}_t = g_\eta(s_t, a_t)$ are computed using the learned MDP homomorphism, ψ' and $\overline{\psi}'$ denote parameters of target networks, and $R_t^{(n)} = \sum_{i=0}^{n-1} \gamma^i r_{t+i}$ is the n-step return. Consequently, we train the policy using DPG [70] and HPG from Theorem 5 by backpropagating the following loss:

$$\mathcal{L}_{\text{actor}}(\theta) \approx -\mathbb{E}_{s\sim\mathcal{B}}\left[Q_\psi(s, \pi_\theta(s)) + \overline{Q}_{\overline{\psi}}(f_\phi(s), g_\eta(s, \pi_\theta(s)))\right]. \quad (11)$$

Here, the two gradients are added together and a single policy update is conducted; see Appendix D.5 for the ablation study on other combinations of HPG and DPG. Finally, we utilize target policy smoothing and delayed actor updates [28]. The pseudo-code of DHPG is presented in Appendix E.1.

Learning Continuous MDP Homomorphisms. We now address the problem of learning continuous MDP homomorphisms. While few methods have been proposed for learning finite MDP homomorphisms [81, 83], these are not readily extendable to continuous actions. In this work, we use the lax bisimulation metric [78], Equation (5), to propose a loss function that encodes lax bisimilar states closer together in the abstract space. The lax bisimulation metric is applicable to continuous actions and as a (pseudo-)metric, it can naturally represent approximate MDP homomorphisms.

Following the same intuition as prior works on bisimulations [91], we define our proposed lax bisimulation loss over pairs of transition tuples sampled from the replay buffer. We permute samples to compute their pairwise distance in the abstract space and their pairwise lax bisimilarity distance. Consequently, we minimize the distance between these two terms:

$$\mathcal{L}_{\text{lax}}(\phi, \eta) = \mathbb{E}_{\mathcal{B}}\left[\|f_\phi(s_i) - f_\phi(s_j)\|_1 - \|r_i - r_j\|_1 - \alpha W_2\left(\overline{\tau}_\nu(\cdot|f_\phi(s_i), g_\eta(s_i, a_i)), \overline{\tau}_\nu(\cdot|f_\phi(s_j), g_\eta(s_j, a_j))\right)\right] \quad (12)$$

| (a) Sample efficiency. | (b) Performance profiles. | (c) Learning curves. | (d) Learning curves. |

Figure 2: Results of DM Control tasks with **state observations** obtained on 10 seeds. RLiable metrics are aggregated over 17 tasks. **(a)** RLiable IQM scores as a function of number of steps for comparing sample efficiency, **(b)** RLiable performance profiles at 500k steps, **(c)-(d)** examples of learning curves. Full results are in Appendix D.1. Shaded regions represent 95% confidence intervals.

234 Similarly to Zhang et al. [91], we replaced the Kantorovich (W_1) metric in Equation (5) with the W_2
235 metric as there is an explicit formula for it for Gaussian distributions. Finally, we apply the conditions
236 of a continuous MDP homomorphism map from Definition 3 via the loss function of:

$$\mathcal{L}_{\text{h}}(\phi, \eta, \nu, \rho) = \mathbb{E}_{(s_i, a_i, s_i', r_i) \sim \mathcal{B}}\big[\big(f_\phi(s_i') - \overline{s}_i'\big)^2 + \big(r_i - \overline{R}_\rho(f_\phi(s_i))\big)^2\big], \tag{13}$$

237 where $\overline{s}_i' \sim \overline{\tau}_\nu(\cdot | f_\phi(s_i), g_\eta(s_i, a_i))$. The final loss function is obtained as $\mathcal{L}_{\text{lax}}(\phi, \eta) + \mathcal{L}_{\text{h}}(\phi, \eta, \rho, \nu)$.

7   Experiments

239 In our experiments, we aim to answer the following key questions:

240   1. Does the homomorphic policy gradient improve policy optimization?
241   2. What are the qualitative properties of the learned representations and the abstract MDP?
242   3. Can DHPG learn and recover the minimal MDP image from raw pixel observations?

243 We evaluate DHPG on continuous control tasks from DM Control on state and pixel observations.
244 Importantly, to reliably evaluate our algorithm against the baselines and to correctly capture the
245 distribution of results, we follow the best practices proposed by Agarwal et al. [5] and report the
246 interquartile mean (IQM) and performance profiles aggregated on all tasks over 10 random seeds.
247 While our baseline results are obtained using the official code, when possible [2], some of the results
248 may differ from the originally reported ones due to the difference in the seed numbers and our goal to
249 present a faithful representation of the true performance distribution [5].

7.1   State Observations

251 We compare DHPG on state observations
252 against three commonly-used off-policy model-
253 free algorithms: DDPG [51], TD3 [28], and
254 SAC [35]. All methods use n-step returns, and
255 share the same hyperparameters presented in Ap-
256 pendix E.2. For a fair comparison with DDPG
257 and a better study of the impact of HPG, we
258 have improved our DDPG by adding delayed
259 policy updates and target policy [28]. Thus, the
260 only difference between our DDPG and TD3 is
261 the clipped double Q-learning present in TD3,
262 which appears to be hurting the performance in
263 some tasks of DMC as also observed in [60, 50].

264 **DHPG outperforms or matches other algo-**
265 **rithms on state observations and has a better**
266 **sample efficiency.** Results are presented in Fig-
267 ure 2, and *full results are in Appendix D.1.* Expectedly, performance gains are larger on tasks with
268 symmetries, as DHPG is able to learn a compressed abstract MDP.

(a) Actual optimal policy. (b) Abstract optimal policy.

Figure 3: Contours of actual and abstract optimal actions over the state space of the pendulum-swingup task. Colors represent action values, and states are $s = (\theta, \dot{\theta})$. **(a)** Optimal actions $a^* = \pi^{\uparrow^*}(s)$. **(b)** Abstract optimal actions $\overline{a}^* = g_s(a^*) = \overline{\pi}^*(\overline{s})$. The relation $g_{s_1}(a_1) = g_{s_2}(a_2)$ holds for equivalent state-action pairs.

269 **The learned mapping** $h = (f, g_s)$ **demonstrates properties of an MDP homomorphism.** We use
270 the pendulum swingup task to visualize its learned MDP homomorphism, as its symmetries are
271 perfectly intelligible. Two state-action pairs $(s_1 = (\theta_1, \dot{\theta}_1), a_1)$ and $(s_2 = (\theta_2, \dot{\theta}_2), a_2)$ are equivalent
272 if $a_1 = -a_2$, $\theta_1 = -\theta_2$, and $\dot{\theta}_1 = -\dot{\theta}_2$. Therefore, the learned action representations are expected to
273 reflect this by setting $g_{s_1}(a_1) = g_{s_2}(a_2)$. Figure 3a shows contours of optimal actions over $\mathcal{S}$, while
274 Figure 3b shows action representations $\overline{a} = g_s(a)$ of optimal actions over $\mathcal{S}$. Clearly, abstract actions
275 adhere to the aforementioned relation for equivalent state-action pairs, indicating $g_s(a)$ is in fact
276 representing the action encoder of an MDP homomorphism mapping.

7.2   Pixel Observations

278 We compare the effectiveness of DHPG on pixel observations against DBC [91], DeepMDP [29],
279 SAC-AE [90], and state-of-the-art performing DrQ-v2 [88]. All methods use n-step returns, share the

---

[2]We use the official implementations of DrQv2, DBC, and SAC-AE, while we re-implement DeepMDP due to the unavailability of the official code. See Appendix E.3 for full details.

(a) Sample efficiency.   (b) Performance profiles.   (c) Learning curves.   (d) Learning curves.

Figure 4: Results of DM Control tasks with **pixel observations** obtained on 10 seeds. RLiable metrics are aggregated over 14 tasks. **(a)** RLiable IQM scores as a function of number of steps for comparing sample efficiency, **(b)** RLiable performance profiles at 500k steps, **(c)**-**(d)** examples of learning curves. Full results are in Appendix D.2. Shaded regions represent 95% confidence intervals.

same hyperparameters in Appendix E.2 and all hyperparameters are adapted from DrQ-v2 *without any further tuning*. Importantly, for a fair comparison with DrQ-v2 which uses image augmentation, we present two variations of DHPG and other baselines, *with and without image augmentation*.

DHPG outperforms or matches other algorithms on pixel observations, demonstrating its effectiveness in representation learning. Results are presented in Figure 4 and *full results are in Appendix D.2*. Interestingly, DHPG without image augmentation outperforms DrQ-v2 on domains with easily learnable MDP homomorphism maps, such as cartpole and pendulum, showing its power of representation learning.

DHPG can learn and recover a low-dimensional MDP image. A key strength of MDP homomorphisms is their ability to represent the minimal MDP image [65], which is particularly important when learning from pixel observations. To demonstrate this ability, we

(a) Trajectories.   (b) Curves.   (c) Curves.

Figure 5: Effectiveness of DHPG in recovering the minimal MDP from **pixels**. All methods are limited to a 4-dimensional latent space which is equal to the dimensions of the real state space of cartpole. **(a)** Trajectories of real states obtained from Mujoco and trajectories of latent states of DHPG. **(b, c)** Learning curves averaged on 10 seeds.

have limited the latent space dimensions to the dimension of the real system and compared DHPG (without image augmentation) with baselines in Figure 5. While other methods are not able to learn the tasks, DHPG can successfully learn the policy and the minimal low-dimensional latent space. Surprisingly, trajectories of the latent states resemble that of the real states as shown in Figure 5a.

The abstract MDP demonstrates properties of an MDP homomorphic image. To qualitatively demonstrate the significance of learning joint state-action representations, Figure 6 shows visualizations of latent states for quadruped-walk, a task with symmetries around movements of its four legs. Interestingly, while the latent space of DHPG (Figure 6a) shows distinct states for each leg, abstract

(a) Latent states, DHPG.   (b) Abstract states, DHPG.   (c) Latent states, DBC.   (d) Latent States, DrQ-v2.

Figure 6: PCA projection of learned representations for quadruped-walk with **pixel observations**. **(a)** Latent states $s = E_\mu(o)$, **(b)** abstract latent states $\overline{s} = f_\phi(E_\mu(o))$ for DHPG, **(c)** latent states $s = E_\mu(o)$ for DBC, and **(d)** DrQ-v2. Color of each point denotes its value learned by $Q(s, a)$ or $\overline{Q}(\overline{s}, \overline{a})$. Points are also projected onto each main plane. The homomorphism map of DHPG has mapped the latent states of corresponding legs **(a)** on to the same abstract latent states in **(b)**, indicating a structure in $\overline{S}$.

state encoder f_ϕ has mapped corresponding legs to the same abstract latent state (Figure 6b) as they are some homomorphic image of one another. Clearly, DBC and DrQ-v2 are not able to achieve this.

The learned representations and the MDP homomorphism map transfer to new tasks within the same domain. Importantly, one consideration with representation learning methods relying on rewards is the transferability of the learned representations to a new reward setting within the same domain. To ensure that our method does not hinder such transfer, we conduct experiments in which the actor, critics, and the learned MDP homomorphism map are transferred to a new task in the same domain. Results, given in Appendix D.3 show that our method has not compromised transfer abilities.

Additional Experiments. We study the value equivalence property as a measure for the quality of the learned MDP homomorphisms in Appendix D.4, and we present ablation studies on DHPG variants, and the impact of n-step return on our method in Appendices D.5 and D.6, respectively.

8   Related Work

State Abstraction. Bisimulation [56, 47] is a notion of behavioral equivalence between systems. It is extended to continuous state spaces [12, 20] and extended to MDPs [30]. Bisimulation metrics [21, 26, 25, 27] define a pseudometric to quantify the degree of behavioural similarity. Recently, Zhang et al. [91] defined a loss function for learning representations via bisimilarity of latent states, and Kemertas et al. [46] have further improved its robustness. Castro [14] has proposed a method to approximate the bisimulation metric for deterministic MDPs with discrete actions. van der Pol et al. [81] have defined a contrastive loss based on MDP homomorphisms for learning an abstract MDP for planning, however, their method is only applicable to finite MDPs. Another approach is to directly embed the MDP homomorphic relation in the network architecture [83, 82]. Other recently proposed methods seek to learn representations that preserve values [33, 32] or policies [4], or via a sampling-based similarity metric [15]. Finally, state abstractions can in principle help improve transferring of policies [1, 16, 72, 73, 63], or learning temporally extended actions [17, 87, 86, 77].

Action Abstraction. Action representations are often studied in the context of large discrete action spaces [68] as a form of a look-up embedding that is known *a-priori* [22], factored representations [69], or policy decomposition [18]. Action representations can also be learned from expert demonstrations [79]. More related to our work is dynamics-aware embeddings [85] where a combined state-action embedding for continuous control is learned. In contrast, we use the notion of homomorphisms to learn the state-dependent action representations, while preserving values. Action representations can be combined with temporal abstraction [77] for discovering extended actions [66, 3, 16, 17].

State Representation Learning. Extant methods for learning the underlying state space from raw observations often use latent models [29, 36, 37, 34, 10], auxiliary prediction tasks [44, 53, 54], physics-inspired inductive biases [45, 19, 31], unsupervised learning [42, 52], or self-supervised learning [6, 71, 38, 39, 24]. From another view, representation learning can be effectively decoupled from the RL problem [23, 74]. Symmetries of the environment can also be used for representation learning [58, 55, 61, 84, 40, 41, 62, 13]. In fact, MDP homomorphisms are specializations of such approaches for RL. A key distinguishing factor of MDP homomorphisms is their ability to take actions into account for representation learning in the same premises as Thomas et al. [80]. Recently, simple image augmentation methods have shown significant improvements in RL performance [89, 48]. Since these approaches are in general orthogonal to state abstractions, they can be combined together.

9   Conclusion

In this paper, we developed the novel theory of continuous MDP homomorphisms using measure theory, and we rigorously proved their value and optimal value equivalence properties. We derived the homomorphic PG in order to directly use a joint state-action abstraction for policy optimization. Importantly, we rigorously proved that applying our homomorphic PG on the abstract MDP is equivalent to applying the standard DPG on the actual MDP. Based on our novel theoretical results, we developed a deep actor-critic algorithm that can simultaneously learn the policy and the MDP homomorphism map using the lax bisimulation metric. Our algorithm improves upon strong baselines. The visualization of the latent space demonstrates the strong potential of MDP homomorphisms in learning structured representations that can preserve value functions. We believe that our work will open-up future possibilities for MDP homomorphisms in challenging continuous control problems.

References

[1] David Abel, Dilip Arumugam, Kavosh Asadi, Yuu Jinnai, Michael L Littman, and Lawson LS Wong. State abstraction as compression in apprenticeship learning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pages 3134–3142, 2019.

[2] David Abel, David Hershkowitz, and Michael Littman. Near optimal behavior via approximate state abstraction. In *International Conference on Machine Learning*, pages 2915–2923. PMLR, 2016.

[3] David Abel, Nate Umbanhowar, Khimya Khetarpal, Dilip Arumugam, Doina Precup, and Michael Littman. Value preserving state-action abstractions. In *International Conference on Artificial Intelligence and Statistics*, pages 1639–1650. PMLR, 2020.

[4] Rishabh Agarwal, Marlos C Machado, Pablo Samuel Castro, and Marc G Bellemare. Contrastive behavioral similarity embeddings for generalization in reinforcement learning. In *International Conference on Learning Representations*, 2020.

[5] Rishabh Agarwal, Max Schwarzer, Pablo Samuel Castro, Aaron C Courville, and Marc Bellemare. Deep reinforcement learning at the edge of the statistical precipice. *Advances in Neural Information Processing Systems*, 34, 2021.

[6] Ankesh Anand, Evan Racah, Sherjil Ozair, Yoshua Bengio, Marc-Alexandre Côté, and R Devon Hjelm. Unsupervised state representation learning in Atari. *Advances in Neural Information Processing Systems*, 32:8769–8782, 2019.

[7] Gabriel Barth-Maron, Matthew W Hoffman, David Budden, Will Dabney, Dan Horgan, Dhruva Tb, Alistair Muldal, Nicolas Heess, and Timothy Lillicrap. Distributed distributional deterministic policy gradients. *arXiv preprint arXiv:1804.08617*, 2018.

[8] Richard Bellman. *Dynamic Programming*. Princeton University Press, 1957.

[9] Dimitri Bertsekas. *Dynamic programming and optimal control: Volume I*, volume 1. Athena scientific, 2012.

[10] O Biza, R Platt, JW van de Meent, and L Wong. Learning discrete state abstractions with deep variational inference. *Advances in Approximate Bayesian Inference*, 2021.

[11] Ondrej Biza and Robert Platt. Online abstraction with mdp homomorphisms for deep learning. In *Proceedings of the 18th International Conference on Autonomous Agents and MultiAgent Systems*, 2019.

[12] Richard Blute, Josée Desharnais, Abbas Edalat, and Prakash Panangaden. Bisimulation for labelled markov processes. In *Proceedings of Twelfth Annual IEEE Symposium on Logic in Computer Science*, pages 149–158. IEEE, 1997.

[13] Hugo Caselles-Dupré, Michael Garcia Ortiz, and David Filliat. Symmetry-based disentangled representation learning requires interaction with environments. *Advances in Neural Information Processing Systems*, 32:4606–4615, 2019.

[14] Pablo Samuel Castro. Scalable methods for computing state similarity in deterministic markov decision processes. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 10069–10076, 2020.

[15] Pablo Samuel Castro, Tyler Kastner, Prakash Panangaden, and Mark Rowland. Mico: Improved representations via sampling-based state similarity for Markov decision processes. *Advances in Neural Information Processing Systems*, 34, 2021.

[16] Pablo Samuel Castro and Doina Precup. Using bisimulation for policy transfer in MDPs. In *Twenty-Fourth AAAI Conference on Artificial Intelligence*, 2010.

[17] Pablo Samuel Castro and Doina Precup. Automatic construction of temporally extended actions for MDPs using bisimulation metrics. In *European Workshop on Reinforcement Learning*, pages 140–152. Springer, 2011.

[18] Yash Chandak, Georgios Theocharous, James Kostas, Scott Jordan, and Philip Thomas. Learning action representations for reinforcement learning. In *International Conference on Machine Learning*, pages 941–950. PMLR, 2019.

[19] Miles Cranmer, Sam Greydanus, Stephan Hoyer, Peter Battaglia, David Spergel, and Shirley Ho. Lagrangian neural networks. *arXiv preprint arXiv:2003.04630*, 2020.

[20] J. Desharnais, A. Edalat, and P. Panangaden. Bisimulation for labeled Markov processes. *Information and Computation*, 179(2):163–193, Dec 2002.

[21] J. Desharnais, V. Gupta, R. Jagadeesan, and P. Panangaden. Metrics for labeled Markov systems. In *Proceedings of CONCUR99*, number 1664 in Lecture Notes in Computer Science. Springer-Verlag, 1999.

[22] Gabriel Dulac-Arnold, Richard Evans, Hado van Hasselt, Peter Sunehag, Timothy Lillicrap, Jonathan Hunt, Timothy Mann, Theophane Weber, Thomas Degris, and Ben Coppin. Deep reinforcement learning in large discrete action spaces. *arXiv preprint arXiv:1512.07679*, 2015.

[23] SM Ali Eslami, Danilo Jimenez Rezende, Frederic Besse, Fabio Viola, Ari S Morcos, Marta Garnelo, Avraham Ruderman, Andrei A Rusu, Ivo Danihelka, Karol Gregor, et al. Neural scene representation and rendering. *Science*, 360(6394):1204–1210, 2018.

[24] Linxi Fan, Guanzhi Wang, De-An Huang, Zhiding Yu, Li Fei-Fei, Yuke Zhu, and Animashree Anandkumar. Secant: Self-expert cloning for zero-shot generalization of visual policies. In *International Conference on Machine Learning*, pages 3088–3099. PMLR, 2021.

[25] Norm Ferns, Pablo Samuel Castro, Doina Precup, and Prakash Panangaden. Methods for computing state similarity in Markov decision processes. In *Proceedings of the Twenty-Second Conference on Uncertainty in Artificial Intelligence*, pages 174–181, 2006.

[26] Norm Ferns, Prakash Panangaden, and Doina Precup. Metrics for Markov decision processes with infinite state spaces. In *Proceedings of the Twenty-First Conference on Uncertainty in Artificial Intelligence*, pages 201–208, 2005.

[27] Norm Ferns, Prakash Panangaden, and Doina Precup. Bisimulation metrics for continuous Markov decision processes. *SIAM Journal on Computing*, 40(6):1662–1714, 2011.

[28] Scott Fujimoto, Herke Hoof, and David Meger. Addressing function approximation error in actor-critic methods. In *International Conference on Machine Learning*, pages 1587–1596. PMLR, 2018.

[29] Carles Gelada, Saurabh Kumar, Jacob Buckman, Ofir Nachum, and Marc G Bellemare. Deepmdp: Learning continuous latent space models for representation learning. In *International Conference on Machine Learning*, pages 2170–2179. PMLR, 2019.

[30] Robert Givan, Thomas Dean, and Matthew Greig. Equivalence notions and model minimization in Markov decision processes. *Artificial Intelligence*, 147(1-2):163–223, 2003.

[31] Samuel J Greydanus, Misko Dzumba, and Jason Yosinski. Hamiltonian neural networks. 2019.

[32] Christopher Grimm, André Barreto, Gregory Farquhar, David Silver, and Satinder Singh. Proper value equivalence. *arXiv preprint arXiv:2106.10316*, 2021.

[33] Christopher Grimm, André Barreto, Satinder Singh, and David Silver. The value equivalence principle for model-based reinforcement learning. *arXiv preprint arXiv:2011.03506*, 2020.

[34] David Ha and Jürgen Schmidhuber. World models. *arXiv e-prints*, pages arXiv–1803, 2018.

[35] Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *International conference on machine learning*, pages 1861–1870. PMLR, 2018.

[36] Danijar Hafner, Timothy Lillicrap, Jimmy Ba, and Mohammad Norouzi. Dream to control: Learning behaviors by latent imagination. In *International Conference on Learning Representations*, 2019.

[37] Danijar Hafner, Timothy Lillicrap, Ian Fischer, Ruben Villegas, David Ha, Honglak Lee, and James Davidson. Learning latent dynamics for planning from pixels. In *International Conference on Machine Learning*, pages 2555–2565. PMLR, 2019.

[38] Nicklas Hansen, Rishabh Jangir, Yu Sun, Guillem Alenyà, Pieter Abbeel, Alexei A Efros, Lerrel Pinto, and Xiaolong Wang. Self-supervised policy adaptation during deployment. In *International Conference on Learning Representations*, 2020.

[39] Nicklas Hansen and Xiaolong Wang. Generalization in reinforcement learning by soft data augmentation. In *2021 IEEE International Conference on Robotics and Automation (ICRA)*, pages 13611–13617. IEEE, 2021.

[40] Irina Higgins, David Amos, David Pfau, Sebastien Racaniere, Loic Matthey, Danilo Rezende, and Alexander Lerchner. Towards a definition of disentangled representations. *arXiv preprint arXiv:1812.02230*, 2018.

[41] Irina Higgins, Peter Wirnsberger, Andrew Jaegle, and Aleksandar Botev. Symetric: Measuring the quality of learnt hamiltonian dynamics inferred from vision. *Advances in Neural Information Processing Systems*, 34, 2021.

[42] R Devon Hjelm, Alex Fedorov, Samuel Lavoie-Marchildon, Karan Grewal, Phil Bachman, Adam Trischler, and Yoshua Bengio. Learning deep representations by mutual information estimation and maximization. In *International Conference on Learning Representations*, 2018.

[43] Dan Horgan, John Quan, David Budden, Gabriel Barth-Maron, Matteo Hessel, Hado van Hasselt, and David Silver. Distributed prioritized experience replay. In *International Conference on Learning Representations*, 2018.

[44] Max Jaderberg, Volodymyr Mnih, Wojciech Marian Czarnecki, Tom Schaul, Joel Z Leibo, David Silver, and Koray Kavukcuoglu. Reinforcement learning with unsupervised auxiliary tasks. *arXiv preprint arXiv:1611.05397*, 2016.

[45] Rico Jonschkowski and Oliver Brock. Learning state representations with robotic priors. *Autonomous Robots*, 39(3):407–428, 2015.

[46] Mete Kemertas and Tristan Aumentado-Armstrong. Towards robust bisimulation metric learning. *Advances in Neural Information Processing Systems*, 34, 2021.

[47] Kim G Larsen and Arne Skou. Bisimulation through probabilistic testing. *Information and computation*, 94(1):1–28, 1991.

[48] Kimin Lee, Kibok Lee, Jinwoo Shin, and Honglak Lee. Network randomization: A simple technique for generalization in deep reinforcement learning. *arXiv preprint arXiv:1910.05396*, 2019.

[49] Lihong Li, Thomas J Walsh, and Michael L Littman. Towards a unified theory of state abstraction for MDPs. *ISAIM*, 4:5, 2006.

[50] Qing Li. Continuous control benchmark of DeepMind control suite and MuJoCo. `https://github.com/LQNew/Continuous_Control_Benchmark`, 2021.

[51] Timothy P Lillicrap, Jonathan J Hunt, Alexander Pritzel, Nicolas Heess, Tom Erez, Yuval Tassa, David Silver, and Daan Wierstra. Continuous control with deep reinforcement learning. *arXiv preprint arXiv:1509.02971*, 2015.

[52] Hao Liu and Pieter Abbeel. Aps: Active pretraining with successor features. In *International Conference on Machine Learning*, pages 6736–6747. PMLR, 2021.

[53] Shikun Liu, Andrew Davison, and Edward Johns. Self-supervised generalisation with meta auxiliary learning. *Advances in Neural Information Processing Systems*, 32, 2019.

[54] Clare Lyle, Mark Rowland, Georg Ostrovski, and Will Dabney. On the effect of auxiliary tasks on representation dynamics. In *International Conference on Artificial Intelligence and Statistics*, pages 1–9. PMLR, 2021.

[55] Anuj Mahajan and Theja Tulabandhula. Symmetry learning for function approximation in reinforcement learning. *arXiv preprint arXiv:1706.02999*, 2017.

[56] Robin Milner. *Communication and concurrency*, volume 84. Prentice hall Englewood Cliffs, 1989.

[57] Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Alex Graves, Ioannis Antonoglou, Daan Wierstra, and Martin Riedmiller. Playing Atari with deep reinforcement learning. *arXiv preprint arXiv:1312.5602*, 2013.

[58] Arnab Kumar Mondal, Vineet Jain, Kaleem Siddiqi, and Siamak Ravanbakhsh. Eqr: Equivariant representations for data-efficient reinforcement learning. In *International Conference on Machine Learning*, pages 15908–15926. PMLR, 2022.

[59] Shravan Matthur Narayanamurthy and Balaraman Ravindran. On the hardness of finding symmetries in markov decision processes. In *Proceedings of the 25th international conference on Machine learning*, pages 688–695, 2008.

[60] Fabio Pardo. Tonic: A deep reinforcement learning library for fast prototyping and benchmarking. *arXiv preprint arXiv:2011.07537*, 2020.

[61] Jung Yeon Park, Ondrej Biza, Linfeng Zhao, Jan Willem van de Meent, and Robin Walters. Learning symmetric embeddings for equivariant world models. *arXiv preprint arXiv:2204.11371*, 2022.

[62] Robin Quessard, Thomas D Barrett, and William R Clements. Learning group structure and disentangled representations of dynamical environments. *arXiv preprint arXiv:2002.06991*, 2020.

[63] Srividhya Rajendran and Manfred Huber. Learning to generalize and reuse skills using approximate partial policy homomorphisms. In *2009 IEEE International Conference on Systems, Man and Cybernetics*, pages 2239–2244. IEEE, 2009.

[64] Balaraman Ravindran. *An algebraic approach to abstraction in reinforcement learning*. University of Massachusetts Amherst, 2004.

[65] Balaraman Ravindran and Andrew G Barto. Symmetries and model minimization in markov decision processes, 2001.

[66] Balaraman Ravindran and Andrew G Barto. Relativized options: Choosing the right transformation. In *Proceedings of the 20th International Conference on Machine Learning (ICML-03)*, pages 608–615, 2003.

[67] Balaraman Ravindran and Andrew G Barto. Approximate homomorphisms: A framework for non-exact minimization in Markov Decision Processes. 2004.

[68] Brian Sallans and Geoffrey E Hinton. Reinforcement learning with factored states and actions. *The Journal of Machine Learning Research*, 5:1063–1088, 2004.

[69] Sahil Sharma, Aravind Suresh, Rahul Ramesh, and Balaraman Ravindran. Learning to factor policies and action-value functions: Factored action space representations for deep reinforcement learning. *arXiv preprint arXiv:1705.07269*, 2017.

[70] David Silver, Guy Lever, Nicolas Heess, Thomas Degris, Daan Wierstra, and Martin Riedmiller. Deterministic policy gradient algorithms. In *International conference on machine learning*, pages 387–395. PMLR, 2014.

[71] Samarth Sinha, Ajay Mandlekar, and Animesh Garg. S4rl: Surprisingly simple self-supervision for offline reinforcement learning in robotics. In *5th Annual Conference on Robot Learning*, 2021.

[72] Vishal Soni and Satinder Singh. Using homomorphisms to transfer options across continuous reinforcement learning domains. In *AAAI*, volume 6, pages 494–499, 2006.

[73] Jonathan Sorg and Satinder Singh. Transfer via soft homomorphisms. In *Proceedings of The 8th International Conference on Autonomous Agents and Multiagent Systems-Volume 2*, pages 741–748, 2009.

[74] Adam Stooke, Kimin Lee, Pieter Abbeel, and Michael Laskin. Decoupling representation learning from reinforcement learning. In *International Conference on Machine Learning*, pages 9870–9879. PMLR, 2021.

[75] Richard S Sutton and Andrew G Barto. *Reinforcement learning: An introduction*. MIT press, 2018.

[76] Richard S Sutton, David A McAllester, Satinder P Singh, and Yishay Mansour. Policy gradient methods for reinforcement learning with function approximation. In *Advances in neural information processing systems*, pages 1057–1063, 2000.

[77] Richard S Sutton, Doina Precup, and Satinder Singh. Between MDPs and semi-MDPs: A framework for temporal abstraction in reinforcement learning. *Artificial intelligence*, 112(1-2):181–211, 1999.

[78] Jonathan Taylor, Doina Precup, and Prakash Panagaden. Bounding performance loss in approximate mdp homomorphisms. *Advances in Neural Information Processing Systems*, 21:1649–1656, 2008.

[79] Guy Tennenholtz and Shie Mannor. The natural language of actions. In *International Conference on Machine Learning*, pages 6196–6205. PMLR, 2019.

[80] Valentin Thomas, Jules Pondard, Emmanuel Bengio, Marc Sarfati, Philippe Beaudoin, Marie-Jean Meurs, Joelle Pineau, Doina Precup, and Yoshua Bengio. Independently controllable factors. *arXiv preprint arXiv:1708.01289*, 2017.

[81] Elise van der Pol, Thomas Kipf, Frans A Oliehoek, and Max Welling. Plannable approximations to mdp homomorphisms: Equivariance under actions. In *Proceedings of the 19th International Conference on Autonomous Agents and MultiAgent Systems*, pages 1431–1439, 2020.

[82] Elise van der Pol, Herke van Hoof, Frans A Oliehoek, and Max Welling. Multi-agent MDP homomorphic networks. *arXiv preprint arXiv:2110.04495*, 2021.

[83] Elise van der Pol, Daniel Worrall, Herke van Hoof, Frans Oliehoek, and Max Welling. Mdp homomorphic networks: Group symmetries in reinforcement learning. *Advances in Neural Information Processing Systems*, 33, 2020.

[84] Dian Wang, Robin Walters, and Robert Platt. So(2)-equivariant reinforcement learning. In *International Conference on Learning Representations*, 2021.

[85] William Whitney, Rajat Agarwal, Kyunghyun Cho, and Abhinav Gupta. Dynamics-aware embeddings. In *International Conference on Learning Representations*, 2019.

[86] Alicia P Wolfe and Andrew G Barto. Decision tree methods for finding reusable mdp homomorphisms. In *PROCEEDINGS OF THE NATIONAL CONFERENCE ON ARTIFICIAL INTELLIGENCE*, volume 21, page 530. Menlo Park, CA; Cambridge, MA; London; AAAI Press; MIT Press; 1999, 2006.

[87] Alicia Peregrin Wolfe and Andrew G Barto. Defining object types and options using mdp homomorphisms. In *Proceedings of the ICML-06 Workshop on Structural Knowledge Transfer for Machine Learning*. Citeseer, 2006.

[88] Denis Yarats, Rob Fergus, Alessandro Lazaric, and Lerrel Pinto. Mastering visual continuous control: Improved data-augmented reinforcement learning. *arXiv preprint arXiv:2107.09645*, 2021.

[89] Denis Yarats, Ilya Kostrikov, and Rob Fergus. Image augmentation is all you need: Regularizing deep reinforcement learning from pixels. In *International Conference on Learning Representations*, 2020.

[90] Denis Yarats, Amy Zhang, Ilya Kostrikov, Brandon Amos, Joelle Pineau, and Rob Fergus. Improving sample efficiency in model-free reinforcement learning from images. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pages 10674–10681, 2021.

[91] Amy Zhang, Rowan Thomas McAllister, Roberto Calandra, Yarin Gal, and Sergey Levine. Learning invariant representations for reinforcement learning without reconstruction. In *International Conference on Learning Representations*, 2020.