Learning Efficient Image Super-Resolution Networks via Structure-Regularized Pruning

Yulun Zhang[1,†] **Huan Wang**[1,†,*] **Can Qin**[1] **Yun Fu**[1]
[1]Northeastern University, USA

Abstract

Several image super-resolution (SR) networks have been proposed of late for efficient SR, achieving promising results. However, they are still not lightweight enough and neglect to be extended to larger networks. At the same time, model compression techniques, like neural architecture search and knowledge distillation, typically consume considerable computation resources. In contrast, network pruning is a cheap and effective model compression technique. However, it is hard to be applied to SR networks directly because filter pruning for residual blocks is well-known tricky. To address the above issues, we propose structure-regularized pruning (SRP), which imposes regularization on the pruned structure to ensure the locations of pruned filters are aligned across different layers. Specifically, for the layers connected by the same residual, we select the filters of the same indices as unimportant filters. To transfer the expressive power in the unimportant filters to the rest of the network, we employ L_2 regularization to drive the weights towards zero so that eventually, their absence will cause minimal performance degradation. We apply SRP to train efficient image SR networks, resulting in a lightweight network SRPN-Lite and a very deep one SRPN. We conduct extensive comparisons with both lightweight and larger networks. SRPN-Lite and SRPN perform favorably against other recent efficient SR approaches quantitatively and visually.

1 Introduction

Image super-resolution (SR), a classic task in computer vision, aims to recover a high-resolution (HR) image based on its low-resolution (LR) counterpart. Essentially, image SR is ill-posed as a many-to-one mapping problem. To tackle this problem, plenty of deep convolutional neural networks (CNNs) (Dong et al., 2014; 2016; Kim et al., 2016b; Zhang et al., 2018c; 2020; 2021) have been investigated to learn the accurate mapping from LR image to its HR target.

Deep CNN for image SR is pioneered by SRCNN (Dong et al., 2014) and has continuously shown promising SR performance. There are only three convolutional (Conv) layers in SRCNN, constraining its expressivity. Kim *et al.* increased the network depth in VDSR (Kim et al., 2016a) with residual learning and obtained notable improvements over SRCNN. Lim *et al.* (Lim et al., 2017) built a much deeper network EDSR by using simplified residual blocks. Zhang *et al.* (Zhang et al., 2018b) proposed RCAN, which is one of the deepest networks in SR at present. Empowered by increased network size, deep SR models like EDSR (Lim et al., 2017) and RCAN (Zhang et al., 2018b) have seen remarkable SR performance. However, as a cost, the large model size brings about problems such as excessive memory footprint, slow inference speed. It is thereby infeasible to directly deploy them on resource-constrained platforms (Lee et al., 2020).

Aiming for efficient SR, more and more works introduce lightweight network architectures (Ahn et al., 2018; Luo et al., 2020). Ahn *et al.* proposed cascading residual network (CARN) (Ahn et al., 2018). Hui *et al.* proposed information multi-distillation network (IMDN) (Hui et al., 2019). Lee *et al.* introduced knowledge distillation (Hinton et al., 2014) for image SR (Lee et al., 2020). Besides, neural architecture search (NAS) (Zoph & Le, 2017; Elsken et al., 2019) was also utilized for lightweight SR model (Chu et al., 2019a). However, there are still several downsides to these networks: **(1)** There is still an obvious performance gap between those lightweight models and the very deep models; **(2)** These methods can consume considerable computation resources for training. For example, (Chu et al., 2019a) require 8 Tesla V100 GPUs to train a single network, and the

---

[†]Equal contribution. The main work was done when Yulun Zhang was at Northeastern University.
[*]Corresponding author: Huan Wang (wang.huan@northeastern.edu)

Figure 1: Visual comparisons ($\times4$) about lightweight and large SR networks on Urban100 dataset. The first row is lightweight SR networks comparison. The second row is about larger models comparison. SRPN-Lite and SRPN are our proposed lightweight and larger image SR networks.

training takes about three days; **(3)** It is hard for most lightweight SR network designs to generalize to more large-scale networks and achieve superior performance at the same time. In short, more effective, resource-friendly, and generic lightweight SR networks are still in need.

On the other hand, neural network pruning is well-known as an effective technique to reduce model complexity (Reed, 1993; Sze et al., 2017). For acceleration, filter pruning (a.k.a. structured pruning) (Li et al., 2017) attracts more attention than weight-element pruning (a.k.a. unstructured pruning) (Han et al., 2015; 2016b). Introducing filter pruning into image SR is a promising solution to achieve a good trade-off between performance and complexity. However, it is not easy to apply filter pruning methods to image SR networks directly. This is mainly because residual connections are well-known difficult to prune in structured pruning (Li et al., 2017). On the other hand, they are *extensively* used in state-of-the-art (SOTA) image SR methods (e.g., EDSR (Lim et al., 2017) has 32 residual blocks; RCAN (Zhang et al., 2018b) even has nested residual blocks).

To tackle the above issue, we propose *Structure-Regularized Pruning* (SRP), which imposes regularization on the pruned structure to ensure the locations of pruned filters are *aligned* across different layers. Specifically, for the layers connected by the same residual, we select the filters of the same indices as unimportant filters (i.e., those we will remove finally). To transfer the expressive power in the unimportant filters to the remainder of the network, we employ L_2 regularization to drive the weights towards zero gradually so that eventually, their absence will incur negligible performance loss. To the best of our knowledge, our SRP is one of the leading works (Zhang et al., 2021) to leverage structured pruning for efficient image SR. Our main contributions are as follows:

- We propose a network structure-regularized pruning (SRP) method to learn efficient image SR networks. We try to jointly train image SR models with network pruning simultaneously to achieve high reconstruction performance as well as efficiency.

- Our SRP provides a general idea to structurally prune networks, which consists of extensive residual connections. The introduction of regularization as a pruning tool manages to maintain the expressivity of the original network while peeling off the unnecessary redundancy.

- We employ SRP to train efficient image SR networks, resulting in a lightweight network (named SRPN-Lite) and a very deep one (named SRPN). We achieve superior performance gains on both lightweight and large image SR networks.

2 RELATED WORK

Deep Image SR Models. Dong *et al.* (Dong et al., 2014) firstly proposed SRCNN for image SR and achieved superior performance with only 3 convolutional (Conv) layers. Residual learning was introduced in VDSR (Kim et al., 2016a), reaching 20 Conv layers and a significant improvement over SRCNN. Tai *et al.* later introduced memory block in MemNet (Tai et al., 2017b) for deeper network structure. Lim *et al.* (Lim et al., 2017) simplified the residual block (He et al., 2016) and constructed deeper and wider networks with a large number of parameters. Zhang *et al.* (Zhang et al., 2018b) proposed an even deeper network, residual channel attention network (RCAN), where the attention mechanism was firstly introduced in image SR. Liu *et al.* proposed FRANet (Liu et al., 2020) to make the residual features focus on critical spatial contents. Later, Zhang *et al.* (Zhang et al., 2019) proposed residual non-local attention for image restoration. Mei *et al.* proposed CSNLN (Mei et al., 2020) by combining local, in-scale/cross-scale non-local feature correlations, and external statistics. Most of those methods have achieved SOTA results. However, they suffer from huge model size (i.e., network parameter number) and/or heavy computation operations (i.e., FLOPs).

Figure 2: **(a)** Illustration of channel-wise and filter-wise pruning for single Conv layer. In this work, we adopt filter-wise pruning to learn efficient image SR networks. **(b)** Illustration of filter pruning *within* a residual block. Feature maps F are depicted as 3d cubes. Convolutional kernel W (4d tensor) is expended as a 2d matrix here for easy illustration (each row represents a filter). Both green and blue color mean the *pruned* filters (or feature map channels): green represents the pruned filters in *free Conv layers*; blue represents the pruned filters in *constrained Conv layers*. The main point of SRP is to apply L_2 regularization to the unimportant filters to make sure the pruned indices of $F^{(i)}$ are exactly the same as those of $F^{(i+2)}$. **(c)** Illustration of filter pruning across different residual blocks. All the layers that are directly followed by the add operators are constrained Conv layers (in blue). Others are free Conv layers (in green).

Lightweight Image SR Models. Recent years have been rising interest in investigating lightweight image SR models. These approaches try to design lightweight architectures, which mainly take advantage of recursive learning and channel splitting. Kim *et al.* firstly decreased parameter number by utilizing recursive learning in DRCN (Kim et al., 2016b). Ahn *et al.* proposed CARN by designing a cascading mechanism upon a residual network (Ahn et al., 2018). Hui *et al.* proposed a lightweight information multi-distillation network (IMDN) (Hui et al., 2019). Luo *et al.* designed the lattice block with butterfly structures (Luo et al., 2020). Recently, neural architecture search was applied for image SR, like FALSR (Chu et al., 2019a). Also, model compression techniques have been explored for image SR. He *et al.* proposed knowledge distillation based feature-affinity for efficient image SR (He et al., 2020). Lee *et al.* distilled knowledge from a larger teacher network to a student one (Lee et al., 2020). Those lightweight image SR models have obtained great progress, but we still need to investigate deeper for more efficient image SR models.

Neural Network Pruning. Network pruning aims to eliminate redundant parameters in a neural network without compromising its performance seriously (Reed, 1993; Sze et al., 2017). The methodology of pruning mainly falls into two groups: filter pruning (or more generally known as structured pruning)[*] and weight-element pruning (also referred to as unstructured pruning). The former aims to remove weights by filters (i.e., 4-d tensors), while the latter removes weights by single elements (i.e., scalars). Structured pruning results in regular sparsity after pruning. It does *not* demand any special hardware features to achieve considerable practical acceleration. In contrast, unstructured pruning leads to irregular sparsity. Leveraging the irregular sparsity for acceleration typically demands special software supports, while past works have shown the practical speedup is very limited (Wen et al., 2016), unless using customized hardware platforms (Han et al., 2016a). In this paper, we tackle *filter pruning* instead of weight-element pruning for effortless acceleration. The major efforts in pruning (mainly in image classification) have been focusing on proposing a more sound pruning criterion to select unimportant weights (Reed, 1993; Sze et al., 2017). Criteria based on weight magnitude (Han et al., 2015; 2016b; Li et al., 2017) are the most prevailing ones, which we will also employ to develop our method in this paper.

3 METHODOLOGY

We first present an overview of the problem setting about deep CNN for image SR. It is also observed that excessive redundancy exists in the SR deep CNNs. Then we move on to proposing our *structure-regularized pruning (SRP)* method attempting to achieve more efficient SR networks.

3.1 DEEP CNN FOR IMAGE SR

In image super-resolution (SR), a high-resolution (a.k.a. super-resolved) image I_{SR} is reconstructed from its low-resolution (LR) counterpart I_{LR}. This image SR process can be described as

$$I_{SR} = \mathcal{F}_{SR}(I_{LR}; \Theta),\qquad(1)$$

---

[*]Filter pruning is a sub-concept within structured pruning, while they are often used interchangeably in the literature. In this paper, we stick to this terminology practice.

where $\mathcal{F}_{SR}(\cdot)$ is the image SR network, parameterized by Θ. Meanwhile, the LR image I_{LR} from its HR counterpart can be formulated as a degradation process

$$I_{LR} = \mathcal{F}_{\downarrow_s}(I_{HR}), \tag{2}$$

where $\mathcal{F}_{\downarrow_s}(\cdot)$ downscales the original ground truth I_{HR} by a scale factor s. This downscaling process typically introduces additional noise, blurring, compression, and/or other unknown artifacts. Therein, the high-frequency information will be lost more or less. The job of image SR models is to recover the high-frequency information as much as possible.

We aim to present a structural sparsity inducing SR network learning method, which can deliver more efficient SR networks with fewer parameters and FLOPs.

3.2 STRUCTURE-REGULARIZED PRUNING (SRP)

Pruned Index Constraint. Pruning filters in residual networks is well-known non-trivial as the Add operators in residual blocks require the pruned filter indices across different residual blocks must be aligned. A figurative illustration of filter pruning within a residual block is shown in Fig. 2(b). A typical residual block (e.g., in EDSR (Lim et al., 2017), RCAN (Zhang et al., 2018b)) consists of two convolutional layers. According to the mutual connection relationship, the convolutional layers can be categorized into two groups. One group is made up with the layers that can be pruned *without any constraint*, dubbed *free Conv layers* in this work; the other comprises Conv layers whose filters must be pruned *at the same indices*, dubbed *constrained Conv layers*. Concretely, the layer $W^{(i)}$ in Fig. 2(b) is a free Conv layer, while the layer $W^{(i+1)}$ is a constrained one.

Owing to the pruned index constraint problem, many filter pruning methods in image classification simply do *not* prune the last Conv layer in residual blocks (Li et al., 2017; Wang et al., 2021), which can still deliver considerable speedup of practical interest. Nevertheless, this doing-nothing solution can barely translate to the image SR networks if we target a considerable speedup. The root cause is that image SR networks typically employ *many more* residual blocks, and each block usually has only two Conv layers. In some top-performing SR networks (e.g., RCAN), there are even *nested* residual blocks. Taking EDSR for a concrete example, it has 32 residual blocks and each block has two Conv layers. If the 2nd Conv layer in a residual block is spared from pruning, half of the Conv layers will not be pruned. In other words, *at best*, we can only achieve $2\times$ theoretical acceleration measured by FLOPs reduction.

Given this issue, it is imperative to prune *all* the Conv layers in residual blocks, thus calling for an approach to align the pruned indices of all constrained Conv layers. Regularization then arises as a promising solution considering it has been widely used before to impose priors on the sparsity structure in classification (Reed, 1993; Wen et al., 2016; Wang et al., 2021).

Our SRP method is based on regularization to form desired hardware-friendly sparsity structure. Primarily, there are three questions to answer in SRP: (1) which pruning criterion is used to choose unimportant filters; (2) which kind of regularization is chosen to induce sparsity; (3) how to schedule the pruning process to make the algorithm robust and easy to use.

(1) Pruning Criterion. When it comes to formulated pruning criteria, they mainly fall into three groups: magnitude based (Han et al., 2015; Li et al., 2017), 1st-order gradient based (Molchanov et al., 2017; 2019), and 2nd-order gradient based (LeCun et al., 1990; Hassibi & Stork, 1993; Wang et al., 2019a). The 1st-order and 2nd-order gradient-based criteria are based on Taylor approximation of the increased loss when a weight is removed, pioneered by (LeCun et al., 1990). They are more accurate than magnitude-based one right after pruning. However, pruning is typically followed by a finetuning process (Reed, 1993) to regain performance. After finetuning, the advantage of the 1st-order and 2nd-order gradient-based criteria usually becomes marginal. Meanwhile, they are typically more costly than the magnitude-based criteria. Taking the cost and flexibility into account, we simply employ magnitude-based pruning criteria.

Specifically, given a pretrained SR network, for all the free Conv layers, we sort the filters in ascending order by their L_1-norms and select the filers with the least norms as *unimportant filters*, by a predefined pruning ratio $r \in (0, 1)$. For the constrained Conv layers, the problem becomes a little bit more complex. Given the pruned index constraint, ideally, we can only prune the filters in the *intersection* set (denoted by $\mathcal{S}^{(net)}$) for the whole network,

$$\mathcal{S}^{(net)} = \bigcap_{l \in \mathcal{C}} S^{(l)}, \tag{3}$$

where $\mathcal{S}^{(l)}$ represents the set of unimportant filters selected by certain pruning criterion in the l-th Conv layer; $\mathcal{C}$ denotes the set of constrained Conv layers. For top-performed image SR networks, $|\mathcal{C}|$ ($|\cdot|$ denotes cardinality of a set) is at the order of magnitude of hundreds (e.g., $|\mathcal{C}| = 200$ for RCAN). Meanwhile, given a pretrained model, its pruned filter indices by L_1-norm are usually *random* across different layers. As a consequence, $|\mathcal{S}^{(net)}|$ will be rather small (in practice, on RCAN, we even observe $|\mathcal{S}^{(net)}| = 0$ when we try to prune 32 filters out of 64). This issue brings much trouble to user control when we want to prune a layer to a pre-defined number of filters. To resolve this problem, we choose to *randomly* select a set of filters as unimportant and fixed during the whole pruning process. In practice, we find this simple scheme works pretty well. The reason enabling us to do so is that regularization for pruning is a *gradual* process. It allows ample time for the network to recover from the introduced penalty term (this will be empirically verified in our experiments, see Fig. 3). Apart from aligning cross-layer sparsity structure, this is the second reason we choose regularization for pruning in our algorithm.

(2) Regularization Form. Although L_1 regularization is well-known to induce sparsity in machine learning, it is hard to tune the coefficient to realize a desired trade-off between sparsity and performance. Instead, L_2 regularization is thereby adopted in our method given its more tamable control over the sparsification process – note the gradient of L_2 regularization is proportion to the weight magnitude while the gradient of L_1 regularization is not. Specifically, given the loss function $\mathcal{L}$ of a neural network Θ, the total error function $\mathcal{E}$ with adaptive L_2 regularization term is formulated as

$$\mathcal{E}(\Theta; \mathcal{D}) = \mathcal{L}(\Theta; \mathcal{D}) + \frac{1}{2} \sum_{l,j} \alpha_j^{(l)} ||W_j^{(l)}||_2^2, \tag{4}$$

where $\mathcal{D}$ stands for the training dataset; $W_j^{(l)}$ refers to the j-th filter in l-th Conv layer; $\alpha_j^{(l)}$ stands for the L_2 regularization co-efficient for that filter. If a filter j falls into the set of unimportant filters $S^{(l)}$, $\alpha_j^{(l)} > 0$; otherwise, $\alpha_j^{(l)} = 0$ since we do not restrict the learning of important filters.

(3) Regularization Schedule. As mentioned above, for the constrained Conv layers, we select the unimportant filters randomly. To mitigate the side effect of this sub-optimal choice, the network should be provided with abundant training iterations to adapt so that it can transfer its expressive power to the remaining part of the network. To achieve this goal, we choose to gradually increase the penalty strength, drawing inspirations from (Wang et al., 2019b; 2021),

$$\alpha_j^{(l)} = \alpha_j^{(l)} + \Delta, \tag{5}$$

where Δ (a pre-defined constant) is a small amount that the penalty strength is increased each time. This design allows us to raise the penalty strength to a large amount eventually (like 0.5 in our experiments; in contrast, note the normal L_2 regularization co-efficient is at the scale of 10^{-4}). As a result, the unimportant weights are driven rather close to zero, and removing them will hardly hurt the performance. Besides, α is updated every T iterations during training for stability.

To indicate when to terminate the pruning process, a ceiling limit τ is introduced for the regularization co-efficient α. The pruning is over when all the α's for unimportant filters arise to τ.

3.3 Learning Efficient Image SR Models via SRP

SRP can be applied to top-performing SR algorithms in a *plug-and-play* manner – simply replace the loss function $\mathcal{L}$ in Eq. (4) with the loss objective function of an SR approach of interest. The proposed L_2 regularization can be implemented on any deep learning framework very easily.

Upon finishing pruning, we take away the unimportant filters (not zeroing out them only, but literally removing them from the model), which will give us a compact SR model. Finally, the compact model will be finetuned to regain performance following the common practice in pruning (Reed, 1993).

3.4 Implementation Details

We explain how to apply SRP to both lightweight and deep image SR networks to demonstrate the method can work with a wide range of SR networks under different computation budgets.

Lightweight Networks. First, we adapt the EDSR baseline (Lim et al., 2017) with 16 residual blocks by removing the final convolutional layer to save parameters. The reconstruction upscaling is realized by the pixel-shuffle layer (Shi et al., 2016) following common practice. We set the channel number in the revised EDSR baseline as 256 and then prune it to 45. For $\times 2$ scale, we reduce the number of parameters from 19.5M to 609K and name the compressed model as SRPN-Lite.

Pruning ratio	Params (K)	FLOPs (G)	Scratch	L_1-norm pruning (Li et al., 2017)	SRP (ours)
0.1	1,101.8	254.5	37.85	37.91	**37.97**
0.3	681.1	157.7	37.81	37.81	**37.89**
0.5	381.8	88.9	37.75	37.73	**37.84**
0.7	154.2	36.5	37.56	37.58	**37.71**
0.9	26.9	7.3	36.74	36.87	**37.28**

Table 1: PSNR (dB) comparison on the Set5 ($\times 2$) between SRP and other two baselines to obtain exactly *the same* compact network. "Scratch" stands for training the small network from scratch. "L_1-norm" removes filters with the smallest L_1-norms. The unpruned model is EDSR baseline (Params: 1,369.9K, FLOPs: 316.3G, PSNR: 37.99 dB). The best results are **highlighted**.

Figure 3: Plots of the mean L_1-norm of filters vs. iterations for "model.body.12.body.0" (free Conv layer) and "model.body.12.body.2" (constrained Conv layer) in EDSR baseline. As expected, the unimportant filters ("Pruned filters") are driven down (owing to strong regularization); interestingly, the important ones arise spontaneously.

Deep Networks. To apply SRP to the very deep network RCAN (Zhang et al., 2018b), a representative top-performing deep SR network with over 400 Conv layers, we revise RCAN by removing all the channel attention modules (Zhang et al., 2018b). The channel number in the revised RCAN is chosen as 96 and then pruned to 64. For $\times 2$ scale, we reduce the number of parameters from 34.5M to 15.3M and dub the compressed model as SRPN.

4 EXPERIMENTAL RESULTS

4.1 SETTINGS

Data and Evaluation. We use DIV2K dataset (Timofte et al., 2017) and Flickr2K Lim et al. (2017) as training data, following most recent works (Timofte et al., 2017; Lim et al., 2017; Zhang et al., 2018a; Haris et al., 2018). For testing, we use five standard benchmark datasets: Set5 (Bevilacqua et al., 2012), Set14 (Zeyde et al., 2010), B100 (Martin et al., 2001), Urban100 (Huang et al., 2015), and Manga109 (Matsui et al., 2017). The SR results are evaluated with PSNR and SSIM (Wang et al., 2004) on the Y channel in YCbCr space.

Training Settings. Following (Zhang et al., 2018b), data augmentation is used in training – training images are randomly rotated by $90°$, $180°$, $270°$ and flipped horizontally. Image patches (patch size 48×48) are cropped out to form each training batch. Adam optimizer (Kingma & Ba, 2014) is adopted for training with β_1=0.9, β_2=0.999, and ϵ=10^{-8}. Initial learning rate is set to 10^{-4} and then decayed by factor 0.5 every 2×10^5 iterations. We use PyTorch (Paszke et al., 2017) to implement our models with a Tesla V100 GPU[†].

4.2 ABLATION STUDY

The EDSR baseline with 16 residual blocks (Lim et al., 2017)[‡] is used as the backbone for ablation study given its broad use in the community.

Comparison with Baseline Pruning Methods. To start with, we show that our SRP is more effective than the available baseline compact image SR network learning methods. Two baseline methods

---

[†]The code is available at https://github.com/mingsun-tse/SRP.
[‡]https://github.com/sanghyun-son/EDSR-PyTorch

Method	Scale	Params	Mult-Adds	Set5		Set14		B100		Urban100	
				PSNR	SSIM	PSNR	SSIM	PSNR	SSIM	PSNR	SSIM
SRCNN	×2	57K	52.7G	36.66	0.9542	32.42	0.9063	31.36	0.8879	29.50	0.8946
FSRCNN	×2	12K	6.0G	37.00	0.9558	32.63	0.9088	31.53	0.8920	29.88	0.9020
VDSR	×2	665K	612.6G	37.53	0.9587	33.03	0.9124	31.90	0.8960	30.76	0.9140
DRCN	×2	1,774K	17,974.3G	37.63	0.9588	33.04	0.9118	31.85	0.8942	30.75	0.9133
LapSRN	×2	813K	29.9G	37.52	0.9590	33.08	0.9130	31.80	0.8950	30.41	0.9100
DRRN	×2	297K	6,796.9G	37.74	0.9591	33.23	0.9136	32.05	0.8973	31.23	0.9188
MemNet	×2	677K	2,662.4G	37.78	0.9597	33.28	0.9142	32.08	0.8978	31.31	0.9195
CARN	×2	1,592K	222.8G	37.76	0.9590	33.52	0.9166	32.09	0.8978	31.92	0.9256
IMDN	×2	694K	158.8G	38.00	0.9605	33.63	0.9177	32.19	0.8996	32.17	0.9283
SRPN-Lite (ours)	×2	609K	139.9G	**38.10**	**0.9608**	**33.70**	**0.9189**	**32.25**	**0.9005**	**32.26**	**0.9294**
SRCNN	×3	57K	52.7G	32.75	0.9090	29.28	0.8209	28.41	0.7863	26.24	0.7989
FSRCNN	×3	12K	5.0G	33.16	0.9140	29.43	0.8242	28.53	0.7910	26.43	0.8080
VDSR	×3	665K	612.6G	33.66	0.9213	29.77	0.8314	28.82	0.7976	27.14	0.8279
DRCN	×3	1,774K	17,974.3G	33.82	0.9226	29.76	0.8311	28.80	0.7963	27.15	0.8276
DRRN	×3	297K	6,796.9G	34.03	0.9244	29.96	0.8349	28.95	0.8004	27.53	0.8378
MemNet	×3	677K	2,662.4G	34.09	0.9248	30.00	0.8350	28.96	0.8001	27.56	0.8376
CARN	×3	1,592K	118.8G	34.29	0.9255	30.29	0.8407	29.06	0.8034	28.06	0.8493
IMDN	×3	703K	71.5G	34.36	0.9270	30.32	0.8417	29.09	0.8046	28.17	0.8519
SRPN-Lite (ours)	×3	615K	62.7G	**34.47**	**0.9276**	**30.38**	**0.8425**	**29.16**	**0.8061**	**28.22**	**0.8534**
SRCNN	×4	57K	52.7G	30.48	0.8628	27.49	0.7503	26.90	0.7101	24.52	0.7221
FSRCNN	×4	12K	4.6G	30.71	0.8657	27.59	0.7535	26.98	0.7150	24.62	0.7280
VDSR	×4	665K	612.6G	31.35	0.8838	28.01	0.7674	27.29	0.7251	25.18	0.7524
DRCN	×4	1,774K	17,974.3G	31.53	0.8854	28.02	0.7670	27.23	0.7233	25.14	0.7510
LapSRN	×4	813K	149.4G	31.54	0.8850	28.19	0.7720	27.32	0.7280	25.21	0.7560
DRRN	×4	297K	6,796.9G	31.68	0.8888	28.21	0.7720	27.38	0.7284	25.44	0.7638
MemNet	×4	677K	2,662.4G	31.74	0.8893	28.26	0.7723	27.40	0.7281	25.50	0.7630
CARN	×4	1,592K	90.9G	32.13	0.8937	28.60	0.7806	27.58	0.7349	26.07	0.7837
IMDN	×4	715K	40.9G	32.21	0.8948	28.58	0.7811	27.56	0.7353	26.04	0.7838
SRPN-Lite (ours)	×4	623K	35.8G	**32.24**	**0.8958**	**28.69**	**0.7836**	**27.63**	**0.7373**	**26.16**	**0.7875**

Table 2: Quantitative results of lightweight SR networks. Best results are **highlighted**.

Figure 4: Visual comparison of different *lightweight* SR approaches on the Urban100 dataset (×4).

are compared to: training from scratch and the original L_1-norm pruning (Li et al., 2017). The results are presented in Tab. 1. As we can see, our pruned network delivers the best PSNR *consistently* across different pruning ratios. Notably, under a *greater* pruning ratio, the advantage of our method over scratch training or L_1-norm pruning is *more evident* in general, suggesting that our method is more valuable in aggressive pruning cases. Of particular note is that, our method SRP also adopts the L_1-norm as the scoring criterion to select unimportant filters, same as (Li et al., 2017). Nevertheless, our method delivers significantly better results than theirs. The primary reason is that they do not impose any regularization on the pruned structure; the remaining feature maps are thus *mismatched* in residual blocks after pruning. In contrast, our method SRP is not bothered by this issue, showing the effectiveness of our proposed structure regularization.

Visualization of Pruning Process. In Fig. 3, we visualize the pruning process by plotting the mean L_1-norm of filters in two layers of EDSR baseline during SRP training. The filters are split into two groups, kept filters and pruned filters. As is shown in the figure, the mean L_1-norm of the pruned filters goes down gradually because the penalty grows stronger and stronger, driving them towards zero. Interestingly, note the L_1-norms of the kept filters arise themselves. Recall that there is no explicit regularization to promote them to grow. In other words, the network *learns to recover by itself*, akin to the compensation effect found in human brain (Duffau et al., 2003).

Method	Scale	Set5		Set14		B100		Urban100		Manga109	
		PSNR	SSIM	PSNR	SSIM	PSNR	SSIM	PSNR	SSIM	PSNR	SSIM
EDSR	×2	38.11	0.9602	33.92	0.9195	32.32	0.9013	32.93	0.9351	39.10	0.9773
DBPN	×2	38.09	0.9600	33.85	0.9190	32.27	0.9000	32.55	0.9324	38.89	0.9775
RCAN	×2	38.27	0.9614	34.12	0.9216	32.41	0.9027	33.34	0.9384	39.44	0.9786
SRFBN	×2	38.11	0.9609	33.82	0.9196	32.29	0.9010	32.62	0.9328	39.08	0.9779
SAN	×2	38.31	**0.9620**	34.07	0.9213	32.42	0.9028	33.10	0.9370	39.32	0.9792
HAN	×2	38.27	0.9614	34.16	0.9217	32.41	0.9027	33.35	0.9385	39.46	0.9785
IGNN	×2	38.24	0.9613	34.07	0.9217	32.41	0.9025	33.23	0.9383	39.35	0.9786
CSNLN	×2	38.28	0.9616	34.12	0.9223	32.40	0.9024	33.25	0.9386	39.37	0.9785
RFANet	×2	38.26	0.9615	34.16	0.9220	32.41	0.9026	33.33	0.9389	39.44	0.9783
SRPN (ours)	×2	**38.34**	0.9619	**34.29**	**0.9232**	**32.47**	**0.9032**	**33.50**	**0.9401**	**39.76**	**0.9796**
EDSR	×3	34.65	0.9280	30.52	0.8462	29.25	0.8093	28.80	0.8653	34.17	0.9476
RCAN	×3	34.74	0.9299	30.65	0.8482	29.32	0.8111	29.09	0.8702	34.44	0.9499
SRFBN	×3	34.70	0.9292	30.51	0.8461	29.24	0.8084	28.73	0.8641	34.18	0.9481
SAN	×3	34.75	0.9300	30.59	0.8476	29.33	0.8112	28.93	0.8671	34.30	0.9494
HAN	×3	34.75	0.9299	30.67	0.8483	29.32	0.8110	29.10	0.8705	34.48	0.9500
IGNN	×3	34.72	0.9298	30.66	0.8484	29.31	0.8105	29.03	0.8696	34.39	0.9496
CSNLN	×3	34.74	0.9300	30.66	0.8482	29.33	0.8105	29.13	0.8712	34.45	0.9502
RFANet	×3	34.79	0.9300	30.67	0.8487	29.34	0.8115	29.15	0.8720	34.59	0.9506
SRPN (ours)	×3	**34.84**	**0.9303**	**30.76**	**0.8497**	**29.39**	**0.8120**	**29.36**	**0.8749**	**34.88**	**0.9515**
EDSR	×4	32.46	0.8968	28.80	0.7876	27.71	0.7420	26.64	0.8033	31.02	0.9148
SRMDNF	×4	31.96	0.8925	28.35	0.7787	27.49	0.7337	25.68	0.7731	30.09	0.9024
RCAN	×4	32.63	0.9002	28.87	0.7889	27.77	0.7436	26.82	0.8087	31.22	0.9173
SRFBN	×4	32.47	0.8983	28.81	0.7868	27.72	0.7409	26.60	0.8015	31.15	0.9160
SAN	×4	32.64	0.9003	28.92	0.7888	27.78	0.7436	26.79	0.8068	31.18	0.9169
HAN	×4	32.64	0.9002	28.90	0.7890	27.80	0.7442	26.85	0.8094	31.42	0.9177
IGNN	×4	32.57	0.8998	28.85	0.7891	27.77	0.7434	26.84	0.8090	31.28	0.9182
CSNLN	×4	32.68	0.9004	28.95	0.7888	27.80	0.7439	27.22	0.8168	31.43	0.9201
RFANet	×4	32.66	0.9004	28.88	0.7894	27.79	0.7442	26.92	0.8112	31.41	0.9187
SRPN (ours)	×4	**32.72**	**0.9010**	**29.04**	**0.7917**	**27.87**	**0.7457**	**27.25**	**0.8172**	**31.82**	**0.9221**

Table 3: Quantitative results of large SR networks. Best results are **highlighted**.

Figure 5: Visual comparison of different *large* SR networks on the Urban100 dataset (×4).

4.3 COMPARISONS WITH LIGHTWEIGHT NETWORKS

We compare our SRPN-Lite with lightweight SR networks: SRCNN (Dong et al., 2014), FSR-CNN (Dong et al., 2016), VDSR (Kim et al., 2016a), DRCN (Kim et al., 2016b), LapSRN (Lai et al., 2017), DRRN (Tai et al., 2017a), MemNet (Tai et al., 2017b), CARN (Ahn et al., 2018) and IMDN (Hui et al., 2019). The compared results are produced from their released code.

Performance Comparisons. Table 2 shows PSNR/SSIM comparisons for ×2, ×3, and ×4 SR. When compared with all previous methods, our SRPN-Lite performs the best on all the datasets under all scaling factors. Unlike most comparison methods, which achieve efficiency through careful network designs, our work starts with the existing EDSR baseline (Lim et al., 2017) and prunes it to a much smaller network, showing the effectiveness of our proposed SRP.

Model Size and Mult-Adds. Our SRPN-Lite has the fewest parameter number in comparison to recent efficient SR works such as MemNet, CARN, and IMDN. The comparison in terms of Mult-Adds (measured when the output size is set to 3×1,280×720) is also presented. As seen, our SRPN-Lite costs fewer Mult-Adds than most comparison methods. These results demonstrate the merits of SRP against other counterparts in striking a better network performance-complexity trade-off.

Method	Params	Mult-Adds	Set5	Set14	B100	Urban100
MoreMNAS-A (Chu et al., 2019b)	1,039K	238.6G	37.63	33.23	31.95	31.24
FALSR-A (Chu et al., 2019a)	1,021K	234.7G	37.82	33.55	32.12	31.93
CARN+KD (Lee et al., 2020)	1,592K	222.8G	37.82	N/A	32.08	N/A
SRPN-Lite (ours)	609K	139.9G	38.10	33.70	32.25	32.26

Table 4: Model complexity comparisons ($\times 2$). Output size is $3 \times 1,280 \times 720$ to calculate Mult-Adds.

Visual Comparisons. The visual comparisons at $\times 4$ scale are shown in Fig. 4. It is easy to see that most of the comparison algorithms can barely recover the lost texture details in the correct direction; moreover, they suffer from blurring artifacts. In stark contrast, our SRPN-Lite effectively alleviates the blurring artifacts and recovers sharper structural fine textures in the right way, justifying the performance superiority of our SRP approach over other methods.

4.4 COMPARISONS WITH LARGER NETWORKS

Most previous lightweight SR networks neglect to extend their models to deeper and compare with larger networks. As stated in Sec. 3.4, we extend our SRP method to larger network training and obtain a deeper network SRPN. In Tab. 3, we compare with large SR networks: EDSR (Lim et al., 2017), DBPN (Haris et al., 2018), RCAN (Zhang et al., 2018b), SRFBN (Li et al., 2019), SAN (Dai et al., 2019), HAN (Niu et al., 2020), IGNN (Zhou et al., 2020), CSNLN (Mei et al., 2020), and RFANet (Liu et al., 2020).

Performance Comparisons. In Tab. 3, we observe that our SRPN achieves the best PSNR/SSIM values across different test sets and scales, except for SSIM value on Set5 ($\times 2$). Our SRPN utilizes slightly fewer parameters (15.3M vs. 15.4M) with the same network depth as RCAN (Zhang et al., 2018b). Notably, our SRPN removes the channel attention module in RCAN, but still achieves better results. This is mainly because our SRPN is initially trained from a wider and stronger network (with 96 channels). We train the much larger network and then prune it to the target size.

Visual Comparisons. We further show visual comparisons with larger networks (e.g., CSNLN, RFANet, and IGNN) in Fig. 5, we can also observe similar situations as in Fig. 4. For example, in img_011, other methods suffer from heavy blurring artifacts. In other cases, they may not recover clear structures in img_044 or even wrong details in img_062. Our SRPN achieves more visually pleasing results with more structural details. Those comparisons demonstrate that our SRP method can be applied to train larger networks and obtain comparable or even better performance.

4.5 MORE COMPARISON WITH MODEL COMPRESSION TECHNIQUES

We further compare our SRP to other representative efficient image SR approaches via model compression. Concretely, neural architecture search based methods (Chu et al., 2019b;a) and knowledge distillation (KD) based methods (Lee et al., 2020) are compared to. Quantitative results at $\times 2$ scale are presented in Tab. 4, where our SRPN-Lite delivers *better* PSNR results across different datasets with *fewer* parameters and Mult-Adds. With our SRP pruning method, there is no need to search massive network architectures or pretraining a teacher network, which usually consumes considerable computation resources. These comparisons show that our SRP, as a network *pruning* method, has as much potential (if not more) as other model compression techniques for efficient image SR.

5 CONCLUSION

Existing efficient image SR methods have achieved promising results with moderate model parameters and Mult-Adds. However, they neglect to extend their approaches to larger networks, which usually perform much better with more parameters and/or operations with residual learning. Meanwhile, although model compression approaches, like neural architecture search and knowledge distillation, have also been exploited for efficient SR networks, they usually demand excessive computation resources. Network pruning, as another promising model compression method, is hard to train lightweight SR networks directly. To address these issues, we present structure-regularized pruning (SRP), which imposes L_2 regularization on the pruned structure to align the locations of pruned filters across different layers. It can transfer the expressive power in the unimportant filters to the remaining part of the network. We employ SRP to train both lightweight and large image SR networks, resulting in a lightweight network SRPN-Lite and a very deep one SRPN, delivering superior performance over recent SOTA efficient SR methods.

Acknowledgments. This research is supported by the U.S. Army Research Office Award W911NF-17-1-0367.

REFERENCES

Namhyuk Ahn, Byungkon Kang, and Kyung-Ah Sohn. Fast, accurate, and lightweight super-resolution with cascading residual network. In *ECCV*, 2018. 1, 3, 8

Marco Bevilacqua, Aline Roumy, Christine Guillemot, and Marie Line Alberi-Morel. Low-complexity single-image super-resolution based on nonnegative neighbor embedding. In *BMVC*, 2012. 6

Xiangxiang Chu, Bo Zhang, Hailong Ma, Ruijun Xu, and Qingyuan Li. Fast, accurate and lightweight super-resolution with neural architecture search. *arXiv preprint arXiv:1901.07261*, 2019a. 1, 3, 9

Xiangxiang Chu, Bo Zhang, Ruijun Xu, and Hailong Ma. Multi-objective reinforced evolution in mobile neural architecture search. *arXiv preprint arXiv:1901.01074*, 2019b. 9

Tao Dai, Jianrui Cai, Yongbing Zhang, Shu-Tao Xia, and Lei Zhang. Second-order attention network for single image super-resolution. In *CVPR*, 2019. 9

Chao Dong, Chen Change Loy, Kaiming He, and Xiaoou Tang. Learning a deep convolutional network for image super-resolution. In *ECCV*, 2014. 1, 2, 8

Chao Dong, Chen Change Loy, and Xiaoou Tang. Accelerating the super-resolution convolutional neural network. In *ECCV*, 2016. 1, 8

H Duffau, L Capelle, D Denvil, N Sichez, P Gatignol, M Lopes, MC Mitchell, JP Sichez, and R Van Effenterre. Functional recovery after surgical resection of low grade gliomas in eloquent brain: hypothesis of brain compensation. *Journal of Neurology, Neurosurgery & Psychiatry*, 74(7):901–907, 2003. 7

Thomas Elsken, Jan Hendrik Metzen, and Frank Hutter. Neural architecture search: A survey. *JMLR*, 2019. 1

S. Han, X. Liu, and H. Mao. EIE: efficient inference engine on compressed deep neural network. *ACM Sigarch Computer Architecture News*, 44(3):243–254, 2016a. 3

Song Han, Jeff Pool, John Tran, and William J Dally. Learning both weights and connections for efficient neural network. In *NeurIPS*, 2015. 2, 3, 4

Song Han, Huizi Mao, and William J Dally. Deep compression: Compressing deep neural networks with pruning, trained quantization and huffman coding. In *ICLR*, 2016b. 2, 3

Muhammad Haris, Greg Shakhnarovich, and Norimichi Ukita. Deep back-projection networks for super-resolution. In *CVPR*, 2018. 6, 9

B. Hassibi and D. G. Stork. Second order derivatives for network pruning: Optimal brain surgeon. In *NeurIPS*, 1993. 4

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *CVPR*, 2016. 2

Zibin He, Tao Dai, Jian Lu, Yong Jiang, and Shu-Tao Xia. Fakd: Feature-affinity based knowledge distillation for efficient image super-resolution. In *ICIP*, 2020. 3

Geoffrey Hinton, Oriol Vinyals, and Jeff Dean. Distilling the knowledge in a neural network. In *NeurIPS Workshop*, 2014. 1

Jia-Bin Huang, Abhishek Singh, and Narendra Ahuja. Single image super-resolution from transformed self-exemplars. In *CVPR*, 2015. 6

Zheng Hui, Xinbo Gao, Yunchu Yang, and Xiumei Wang. Lightweight image super-resolution with information multi-distillation network. In *ACM MM*, 2019. 1, 3, 8

Jiwon Kim, Jung Kwon Lee, and Kyoung Mu Lee. Accurate image super-resolution using very deep convolutional networks. In *CVPR*, 2016a. 1, 2, 8

Jiwon Kim, Jung Kwon Lee, and Kyoung Mu Lee. Deeply-recursive convolutional network for image super-resolution. In *CVPR*, 2016b. 1, 3, 8

Diederik Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *ICLR*, 2014. 6

Wei-Sheng Lai, Jia-Bin Huang, Narendra Ahuja, and Ming-Hsuan Yang. Deep laplacian pyramid networks for fast and accurate super-resolution. In *CVPR*, 2017. 8

Y. LeCun, J. S. Denker, and S. A. Solla. Optimal brain damage. In *NeurIPS*, 1990. 4

Wonkyung Lee, Junghyup Lee, Dohyung Kim, and Bumsub Ham. Learning with privileged information for efficient image super-resolution. In *ECCV*, 2020. 1, 3, 9

Hao Li, Asim Kadav, Igor Durdanovic, Hanan Samet, and Hans Peter Graf. Pruning filters for efficient convnets. In *ICLR*, 2017. 2, 3, 4, 6, 7

Zhen Li, Jinglei Yang, Zheng Liu, Xiaomin Yang, Gwanggil Jeon, and Wei Wu. Feedback network for image super-resolution. In *CVPR*, 2019. 9

Bee Lim, Sanghyun Son, Heewon Kim, Seungjun Nah, and Kyoung Mu Lee. Enhanced deep residual networks for single image super-resolution. In *CVPRW*, 2017. 1, 2, 4, 5, 6, 8, 9

Jie Liu, Wenjie Zhang, Yuting Tang, Jie Tang, and Gangshan Wu. Residual feature aggregation network for image super-resolution. In *CVPR*, 2020. 2, 9

Xiaotong Luo, Yuan Xie, Yulun Zhang, Yanyun Qu, Cuihua Li, and Yun Fu. Latticenet: Towards lightweight image super-resolution with lattice block. In *ECCV*, 2020. 1, 3

David Martin, Charless Fowlkes, Doron Tal, and Jitendra Malik. A database of human segmented natural images and its application to evaluating segmentation algorithms and measuring ecological statistics. In *ICCV*, 2001. 6

Yusuke Matsui, Kota Ito, Yuji Aramaki, Azuma Fujimoto, Toru Ogawa, Toshihiko Yamasaki, and Kiyoharu Aizawa. Sketch-based manga retrieval using manga109 dataset. *Multimedia Tools and Applications*, 2017. 6

Yiqun Mei, Yuchen Fan, Yuqian Zhou, Lichao Huang, Thomas S Huang, and Humphrey Shi. Image super-resolution with cross-scale non-local attention and exhaustive self-exemplars mining. In *CVPR*, 2020. 2, 9

P. Molchanov, S. Tyree, and T. Karras. Pruning convolutional neural networks for resource efficient inference. In *ICLR*, 2017. 4

Pavlo Molchanov, Arun Mallya, Stephen Tyree, Iuri Frosio, and Jan Kautz. Importance estimation for neural network pruning. In *CVPR*, 2019. 4

Ben Niu, Weilei Wen, Wenqi Ren, Xiangde Zhang, Lianping Yang, Shuzhen Wang, Kaihao Zhang, Xiaochun Cao, and Haifeng Shen. Single image super-resolution via a holistic attention network. In *ECCV*, 2020. 9

Adam Paszke, Sam Gross, Soumith Chintala, Gregory Chanan, Edward Yang, Zachary DeVito, Zeming Lin, Alban Desmaison, Luca Antiga, and Adam Lerer. Automatic differentiation in pytorch. 2017. 6

R. Reed. Pruning algorithms – a survey. *IEEE Transactions on Neural Networks*, 4(5):740–747, 1993. 2, 3, 4, 5

Wenzhe Shi, Jose Caballero, Ferenc Huszár, Johannes Totz, Andrew P Aitken, Rob Bishop, Daniel Rueckert, and Zehan Wang. Real-time single image and video super-resolution using an efficient sub-pixel convolutional neural network. In *CVPR*, 2016. 5

Vivienne Sze, Yu-Hsin Chen, Tien-Ju Yang, and Joel S Emer. Efficient processing of deep neural networks: A tutorial and survey. *Proceedings of the IEEE*, 105(12):2295–2329, 2017. 2, 3

Ying Tai, Jian Yang, and Xiaoming Liu. Image super-resolution via deep recursive residual network. In *CVPR*, 2017a. 8

Ying Tai, Jian Yang, Xiaoming Liu, and Chunyan Xu. Memnet: A persistent memory network for image restoration. In *ICCV*, 2017b. 2, 8

Radu Timofte, Eirikur Agustsson, Luc Van Gool, Ming-Hsuan Yang, Lei Zhang, Bee Lim, Sanghyun Son, Heewon Kim, Seungjun Nah, Kyoung Mu Lee, et al. Ntire 2017 challenge on single image super-resolution: Methods and results. In *CVPRW*, 2017. 6

Chaoqi Wang, Roger Grosse, Sanja Fidler, and Guodong Zhang. Eigendamage: Structured pruning in the kronecker-factored eigenbasis. In *ICML*, 2019a. 4

Huan Wang, Xinyi Hu, Qiming Zhang, Yuehai Wang, Lu Yu, and Haoji Hu. Structured pruning for efficient convolutional neural networks via incremental regularization. *IEEE Journal of Selected Topics in Signal Processing*, 14(4):775–788, 2019b. 5

Huan Wang, Can Qin, Yulun Zhang, and Yun Fu. Neural pruning via growing regularization. In *ICLR*, 2021. 4, 5

Zhou Wang, Alan C Bovik, Hamid R Sheikh, and Eero P Simoncelli. Image quality assessment: from error visibility to structural similarity. *TIP*, 2004. 6

Wei Wen, Chunpeng Wu, Yandan Wang, Yiran Chen, and Hai Li. Learning structured sparsity in deep neural networks. In *NeurIPS*, 2016. 3, 4

Roman Zeyde, Michael Elad, and Matan Protter. On single image scale-up using sparse-representations. In *Proc. 7th Int. Conf. Curves Surf.*, 2010. 6

Kai Zhang, Wangmeng Zuo, and Lei Zhang. Learning a single convolutional super-resolution network for multiple degradations. In *CVPR*, 2018a. 6

Yulun Zhang, Kunpeng Li, Kai Li, Lichen Wang, Bineng Zhong, and Yun Fu. Image super-resolution using very deep residual channel attention networks. In *ECCV*, 2018b. 1, 2, 4, 6, 9

Yulun Zhang, Yapeng Tian, Yu Kong, Bineng Zhong, and Yun Fu. Residual dense network for image super-resolution. In *CVPR*, 2018c. 1

Yulun Zhang, Kunpeng Li, Kai Li, Bineng Zhong, and Yun Fu. Residual non-local attention networks for image restoration. In *ICLR*, 2019. 2

Yulun Zhang, Yapeng Tian, Yu Kong, Bineng Zhong, and Yun Fu. Residual dense network for image restoration. *TPAMI*, 2020. 1

Yulun Zhang, Huan Wang, Can Qin, and Yun Fu. Aligned structured sparsity learning for efficient image super-resolution. *NeurIPS*, 2021. 1, 2

Shangchen Zhou, Jiawei Zhang, Wangmeng Zuo, and Chen Change Loy. Cross-scale internal graph neural network for image super-resolution. In *NeurIPS*, 2020. 9

Barret Zoph and Quoc Le. Neural architecture search with reinforcement learning. In *ICLR*, 2017. 1