LOOKING ALIKE FROM FAR TO NEAR: ENHANCING CROSS-RESOLUTION RE-IDENTIFICATION VIA FEATURE VECTOR PANNING

ABSTRACT

In surveillance scenarios, varying camera distances cause significant differences among pedestrian image resolutions, making it hard to match low-resolution (LR) images with high-resolution (HR) counterparts, limiting the performance of Re-Identification (ReID) tasks. Most existing Cross-Resolution ReID (CR-ReID) methods rely on super-resolution (SR) or joint learning for feature compensation, which increases training and inference complexity and has reached a performance bottleneck in recent studies. Inspired by semantic directions in the word embedding space, we empirically discover that semantic directions implying resolution differences also emerge in the feature space of ReID, and we substantiate this finding from a statistical perspective using Canonical Correlation Analysis and Pearson Correlation Analysis. Based on this interesting finding, we propose a lightweight and effective Vector Panning Feature Alignment (VPFA) framework, which conducts CR-ReID from a novel perspective of modeling the resolution-specific feature discrepancy. Extensive experimental results on multiple CR-ReID benchmarks show that our method significantly outperforms previous state-of-the-art baseline models while obtaining higher efficiency, demonstrating the effectiveness and superiority of our model based on the new finding in this paper.

1 INTRODUCTION

Person re-identification (ReID) aims to match images of the same person captured by different cameras Ye et al. (2022a); Gong et al. (2014). Thanks to deep learning advances Dosovitskiy et al. (2020); Wang et al. (2022), ReID has achieved strong performance in controlled settings. However, in real-world scenarios, many factors would degrade the performance such as viewpoint, lighting, and especially resolution gaps Ren & Zhang (2024); Zheng et al. (2022); Wu et al. (2023); Ye et al. (2022b). Specifically, the image resolution usually differs due to varying quality and distances of cameras. Thus, directly applying standard ReID models in this scenario leads to notable performance drops. To tackle this, many CR-ReID methods use super-resolution (SR) to enhance LR inputs or design resolution-invariant representations Han et al. (2020); Zhang et al. (2021); Li et al. (2015); Wu et al. (2023). However, these models face some challenges: Super resolution (SR) only enhances visual details and improves apparent resolution, but is not designed specifically for person ReID tasks. Therefore, as shown in Fig.1's Challenge, the performance of SR-based models heavily depends on the results of SR while its capability of cross resolution feature alignment for ReID is limited. In contrast, resolution invariant approaches must align cross resolution features while preserving identity discrimination, where identity differences and resolution differences are entangled in the feature space, causing difficulty in training an effective model that could accurately align cross-resolution pedestrian features. To address these challenges, we rethink CR-ReID task with a more straightforward perspective. Rather than altering image resolution or enforcing cross-resolution alignment during training, we attempt to exploit a two-stage feature alignment strategy. In the first stage, we disentangle resolution-specific discrepancies from identity-discriminative features by explicitly modeling cross-resolution differences. In the second stage, we align features at comparable resolutions to ensure identity consistency.

---

* Equal contribution. † Corresponding author.

Figure 1: The motivation of our paper. Top: semantic offset in word embedding space. Mid: resolution direction in feature space. Bottom: our Vector Panning-based cross-resolution Feature Alignment (VPFA).

As implied by our title, *Looking Alike From Far to Near*, our idea stems from a simple but insightful observation. Mikolov Mikolov et al. (2013) showed that semantic relations can be represented as consistent vector offsets. As shown in Fig.1's Inspiration, for instance, Vec(King) − Vec(Man) + Vec(Woman) ≈ Vec(Queen), indicating that the gender difference between words corresponds to a vector with stable direction and magnitude, allowing similar semantic relations to be modeled

Dataset	2×	3×	4×
Market-1501	0.9933	0.9914	0.9935
CUHK03	0.9960	0.9967	0.9977

Table 1: Cosine similarity between the average HR–LR difference vectors computed from two disjoint ID subsets on the Market-1501 and CUHK03 datasets. Higher similarity indicates more consistent resolution-specific offsets across identities.

through comparable offsets. While such offsets are not strictly linear, they effectively capture meaningful semantic variations at the feature level. Furthermore, DeepMind's recent work Neel et al. shows that multilayer perceptrons (MLP) can store factual associations and perform retrieval retrieval via a direct feature transformation strategy. **Inspired by these significant observations, we attempt to explore whether the feature space of CR-ReID also contain analogous directions that encode resolution differences**.

To investigate this, as shown in Fig.1's Observation, we conduct an empirical analysis on Market-1501 with 2× downsampling. We extract features from both the original and downsampled images to form S_{ori} and S_{2x}, and further split each set into two halves to obtain S_{ori1}, S_{ori2}, S_{2x1}, and S_{2x2}. For each subset, we compute identity-wise average features and then average across identities to derive four representative vectors: V_{HR1}, V_{HR2}, V_{LR1}, and V_{LR2}. Finally, we measure the cosine similarity between the difference vectors $V_{HR1} - V_{LR1}$ and $V_{HR2} - V_{LR2}$. As shown in Table1, the consistently high similarity values suggest that resolution-induced feature shifts converge to a stable semantic direction once identity information is averaged out. **This finding provides strong empirical evidence that resolution differences in CR-ReID are not random noise but structured semantic variations in the feature space**. Moreover, Section Section 3 provides a more rigorous statistical justification, reinforcing the significance of this resolution-specific semantic direction. These results highlight the existence of a resolution-aware semantic direction, which motivates us to explicitly model and exploit this direction for more robust cross-resolution feature alignment.

Based on our finding, we identify a new approach to CR-ReID. The fundamental challenge in CR-ReID is that identity information and resolution discrepancy are coupled in the features, which interferes with identity discrimination. Since we have demonstrated the existence of a resolution semantic direction in the feature space, we directly model this resolution discrepancy and translate the original LR feature vector to mitigate the impact of resolution differences. Therefore, as illustrated in Fig.1's Approach, we propose **Vector Panning based Cross resolution Feature Alignment (VPFA)**. We design an MLP based Vector Panning (VP) module to learn the semantic offset between HR and LR features. We also introduce a Vector Panning Loss (VPL) to align both direction and magnitude. Our method operates after feature extraction and achieves feature alignment between HR and LR images at very low cost. Our contributions are summarized as follows:

- We introduce a new perspective for CR-ReID and experimentally discover and validate a semantic direction of resolution in the feature space.

- Based on this finding, we design a lightweight postprocessing module that models resolution differences in features, namely VPFA.

- Extensive experiments on four benchmarks show that VPFA outperforms existing CR-ReID methods and also provides insights for other cross modality ReID tasks.

2 RELATED WORK

Person Re-ID Person Re-Identification has seen rapid progress in both algorithm design and performance over the past decade Bai et al. (2019); Li et al. (2020; 2019); Chen et al. (2018); Shen et al. (2018); Martinel et al. (2019); Goodfellow et al. (2014); Yuan et al. (2025c). Many methods focus on handling challenges from background clutter, pose variation, and occlusion Wu et al. (2021); Yuan et al. (2025b); Pang et al. (2024); Dou et al. (2023); Wu et al. (2019); Fang et al. (2023); Liu et al. (2022); Li et al. (2018); Liu et al. (2018). To capture fine-grained local cues, part-based models are widely adopted, explicitly or implicitly modeling body structures Zhou et al. (2020); Wu et al. (2022); Wei et al. (2021; 2022). Moreover, significant efforts aim to reduce annotation reliance through unsupervised learning Chen et al. (2021); Yin et al. (2023); Pang et al. (2024), domain adaptation Hu et al. (2022); Lee et al. (2023); Pang et al. (2022), and weak supervision Zhu et al. (2019); Jin et al. (2023). Despite these advances, resolution variation remains insufficiently addressed, limiting the robustness and practicality of ReID.

Cross-Resolution Person ReID Current CR-ReID approaches fall into two categories: learning resolution-invariant representations Li et al. (2015); Wang et al. (2016); Wu et al. (2023) and super-resolution (SR) based methods Jiao et al. (2018); Wang et al. (2018); Cheng et al. (2020); Zhang et al. (2021); Chen et al. (2019); Li et al. (2019); Wu et al. (2023). For example, Li et al. Li et al. (2015) combine cross-scale alignment with multi-scale metric learning, and Wu et al. Wu et al. (2023) introduce resolution-adaptive masks to disentangle resolution-specific information. However, most such methods emphasize identity-level features, neglecting the broader HR–LR feature relationship. SR-based methods restore image details before recognition. SING Jiao et al. (2018) jointly trains SR and ReID modules, while CSR-Net Wang et al. (2018) stacks SRGANs Ledig et al. (2017) for gradual refinement. INTACT Cheng et al. (2020) adds compatibility constraints between SR and ReID branches, and PS-HRNet Zhang et al. (2021) integrates VDSR, channel attention, and HRNet in a pseudo-siamese design. Beyond visual enhancement, RAIN Chen et al. (2019) and CAD-Net Li et al. (2019) employ adversarial learning to enforce resolution invariance. LRAR Wu et al. (2023) further decomposes HR features into shared and unique components to preserve HR-specific detail. However, due to the inherent domain gap between HR and LR, SR-based methods still struggle to reach standard ReID performance. In contrast, we model the global HR–LR shift directly in embedding space and use a lightweight postprocessing module to convert LR features into pseudo-HR ones, enabling effective cross-resolution alignment without SR or retraining.

3 THEORETICAL ANALYSIS

3.1 THEORETICAL INSPIRATION

As in this example $\text{Vec}(King) - \text{Vec}(Man) + \text{Vec}(Woman) \approx \text{Vec}(Queen)$, our idea is inspired by the linear semantic structures observed in word embedding spaces. To verify the effectiveness of this idea in the feature space of CR-ReID, we aim to demonstrate that there exists a directional discrepancy between features of high resolution and low resolution images, and we regard this directional transformation as a "resolution vector" analogous to semantic shifts in word embeddings.

Scale	Cross-res (R1/R2/R3)	Random (R1/R2/R3)
2×	0.4826 / 0.4186 / 0.4725	0.2482 / 0.3358 / 0.2117
3×	0.4944 / 0.4948 / 0.4840	0.3007 / 0.3407 / 0.3366
4×	0.4907 / 0.3479 / 0.4759	0.3054 / 0.2945 / 0.2780

Metric	2×	3×	4×
r	0.5373	0.5533	0.5721
Std. of r	0.0803	0.0748	0.0699
Proportion of $r > 0.4$	94.54%	96.93%	98.53%

(a) CCA results between LR–HR feature matrices and random matrices on Market-1501

(b) Grouped Pearson Correlation Statistics for Different Resolution Gaps

Table 2: Statistical analysis results for cross-resolution feature relationships. (a) CCA results comparing LR-HR feature matrices with random matrices. (b) Pearson correlation statistics across different resolution gaps.

3.2 STATISTICAL JUSTIFICATION

To verify the existence of a shared semantic direction induced by resolution differences, we perform global and local analyses on the Market-1501 dataset.

Canonical Correlation Analysis (CCA) evaluates global linear relationships between HR and LR features. It finds canonical vectors that maximize inter-set correlation. As shown in Table2a, canonical correlations between LR and HR feature matrices are significantly higher than those from random feature pairs. Based on standard thresholds Johnson & Wichern (1988), values above 0.4–0.5 indicate moderate to strong linear association. These results provide strong global evidence of semantic alignment between LR and HR representations.

Pearson Correlation Analysis assesses local consistency across individuals. A global "resolution shift" vector is computed by averaging HR–LR feature differences. For each of 50 identities, individual difference vectors are grouped into 25 pairs, whose mean vectors are then correlated with the global shift. In the absence of semantic alignment, these correlations would cluster around zero. However, Table2b shows most groups exceed 0.5 correlation, considered moderate to strong per Cohen Cohen (1988). Furthermore, correlations increase with larger resolution gaps, indicating stronger alignment.

These CCA and Pearson correlation results jointly provide strong evidence for the existence of a consistent semantic direction induced by resolution variation, observable at both global and identity-specific levels.

4 METHOD

Based on our finding, we propose a novel postprocessing method for CR-ReID, namely Vector Panning based Feature Alignment (VPFA). The core concept is to model the discrepancy between HR and LR features in the feature space so as to minimize the impact of resolution on features. In the experiment that demonstrates the existence of a semantic direction in the feature space, the features are extracted by standard ReID models with publicly available weights, therefore our method also does not require training the ReID model. As shown in Fig.2, VPFA first uses a frozen ReID model to extract features from LR and HR images. Initially, LR and HR features are separated in the embedding space. The VP module, composed of stacked VP blocks (Linear + LayerNorm + ReLU), learns a semantic shift that aligns LR features with HR clusters. A final Tanh gate and a residual connection produce pseudo HR features. The vector diagram illustrates how VP models and compensates for resolution induced directional differences.

4.1 PROBLEM FORMULATION

Let $z_{LR}, z_{HR} \in \mathbb{R}^d$ denote the backbone extracted features from the LR and HR images of the same person, respectively. Our objective is to learn a transformation function $g : \mathbb{R}^d \to \mathbb{R}^d$, implemented via a lightweight module, such that:

$$\hat{z}_{LR} = g(z_{LR}) \approx z_{HR} \tag{1}$$

where $\hat{z}_{LR}$ represents the pseudo-HR feature vector aligned by the VP Module. The mapping g is designed to eliminate the semantic distortions introduced by resolution degradation while preserving identity discriminative information. To suppress noise caused by individual variations such as pose or occlusion, we compute the mean feature vector for each identity in both resolution domains:

$$z_{LR}^i = \frac{1}{n_i} \sum_{j=1}^{n_i} f_{LR}(x_j^i), \quad z_{HR}^i = \frac{1}{m_i} \sum_{k=1}^{m_i} f_{HR}(x_k^i) \tag{2}$$

where $f_{LR}(\cdot)$ and $f_{HR}(\cdot)$ denote the fixed pretrained ReID backbone functions, and x_j^i is the j-th LR image of the i-th identity. These identity level prototype pairs (z_{LR}^i, z_{HR}^i) are used as supervision to train VP in the subsequent learning phase.

4.2 VECTOR PANNING (VP) MODULE ARCHITECTURE

The core of our VPFA framework is the Vector Panning (VP) Module, which learns a transformation $f(\cdot)$ that maps LR features z_{LR} into pseudo HR representations $\hat{z}_{LR}$. The transformation is

Figure 2: An overview of the proposed Vector Panning based Feature Alignment (VPFA) framework.

implemented as a gated residual function:

$$\hat{z}_{LR} = z_{LR} + \text{Gate}(\text{VP}(z_{LR})) \tag{3}$$

in which **VP (Vector Panning)** refers to a three-layer nonlinear transformation, where each layer consists of a linear projection followed by Layer Normalization and ReLU activation. It is compactly expressed as:

$$\text{VP}(z_{LR}) = W_3\,\sigma_2(W_2\,\sigma_1(W_1 z_{LR})) \tag{4}$$

The output of VP is passed through a Tanh activation, denoted as **Gate**, which regulates the magnitude of the residual vector:

$$f(z_{LR}) = \tanh(W_4 \cdot \text{VP}(z_{LR})) \tag{5}$$

Residual design. Instead of predicting z_{HR} directly, the residual structure allows the model to learn an offset that selectively corrects the resolution-specific distortions in z_{LR}. This design preserves identity semantics encoded by the backbone while simplifying the learning objective. It also makes optimization easier and prevents overfitting in low data regimes.

Expressiveness of VP. The VP block serves as a high-capacity nonlinear mapping that captures the semantic transformation between LR and HR domains. The layered composition progressively adjusts the embedding along resolution-sensitive subspace directions, which is particularly effective in modeling feature variations caused by resolution degradation.

Stabilization with LayerNorm. Each transformation inside VP is followed by LayerNorm, which normalizes feature statistics per instance. This mitigates internal covariate shifts and stabilizes training. As resolution-induced variance leads to heteroscedastic feature distributions, LayerNorm is critical for learning transferable mappings across resolution domains.

Controlled correction via Gate. The final Gate layer applies a $\tanh$ activation to the residual vector. This constrains each dimension to $[-1, 1]$, acting as a soft clipping mechanism. It ensures that the correction remains within a semantically meaningful range and prevents feature explosion. Additionally, the symmetric range supports both additive and subtractive corrections, which is essential for precise vector alignment.

To ensure training stability and prevent early overfitting, we initialize all weight matrices using a zero-mean Gaussian distribution $\mathcal{N}(0, 10^{-3})$ and set all biases to zero. This leads to $f(z_{LR}) \approx 0$ at the beginning of the training, which means that the initial output satisfies $\hat{z}_{LR} \approx z_{LR}$. Such an initialization strategy is inspired by residual tuning techniques in large scale vision models, where starting from an identity mapping allows the model to retain the backbone's semantic structure and incrementally learn useful corrections. In our setting, this prevents VP from prematurely altering discriminative identity information in z_{LR} and encourages gradual, resolution aware adjustment over time.

Algorithm 1 Proposed Model Training

Input: Training image pairs $\{(I_{LR}, I_{HR})\}$; pretrained backbone $B(\cdot)$
Output: Trained Vector Panning Module $f(\cdot)$
Stage 1: Feature Extraction
(1) For each image pair (I^i_{LR}, I^i_{HR}), extract features: $z^i_{LR} = B(I^i_{LR})$, $z^i_{HR} = B(I^i_{HR})$;
(2) Group features by identity and compute mean-pooled features to obtain $\{(\bar{z}_{LR}, \bar{z}_{HR})\}$.
Stage 2: Training the VP Module
(1) Initialize the module $f(\cdot)$ with Gaussian weights;
(2) For $epoch = 1$ to T do
    (a) Sample a mini-batch of paired features $\{(\bar{z}_{LR}, \bar{z}_{HR})\}$;
    (b) Compute predictions: $\hat{z}_{LR} = f(\bar{z}_{LR})$;
    (c) Compute loss $\mathcal{L}_{\text{VPL}}$ using Eq. (2);
    (d) Update $f(\cdot)$ using gradient descent.
end for

4.3 VECTOR PANNING LOSS (VPL)

The proposed Vector Panning Loss (VPL) supervises the VP using the Mean Squared Error (MSE) between the predicted pseudo-HR feature $\hat{z}_{LR}$ and the target HR feature z_{HR}. Formally, we define:

$$\mathcal{L}_{\text{VPL}} = \|\hat{z}_{LR} - z_{HR}\|_2^2 \tag{6}$$

Although VPL is mathematically identical to MSE, it is specifically designed to guide the learning of resolution-aware residual transformations in the feature space.

Let θ denote the angle between $\hat{z}_{LR}$ and z_{HR}, and $r = \|\hat{z}_{LR}\|$, $R = \|z_{HR}\|$ as their respective norms. Expanding the squared Euclidean distance using the law of cosines:

$$\mathcal{L}_{\text{VPL}} = r^2 + R^2 - 2rR\cos\theta \tag{7}$$

This shows that minimizing $\mathcal{L}_{\text{VPL}}$ aligns both the direction via $\cos\theta$ and magnitude of the features. Since most person ReID systems adopt cosine similarity as the inference metric, this dual effect makes VPL naturally compatible with downstream matching.

In contrast to contrastive or triplet loss functions, VPL does not require explicitly mining positive or negative pairs. Since our goal is not to classify or separate identities but to correct resolution-induced distortions, we can directly align averaged LR and HR features for each identity. This enables stable, efficient, and ID-agnostic training without relying on explicit pairwise supervision.

4.4 MODEL TRAINING

Unlike existing cross-resolution ReID methods that rely on adversarial training or joint end-to-end pipelines, our approach decouples feature correction from backbone learning and requires no modification to the base ReID model. This enables our framework to serve as a lightweight plug-in that enhances cross-resolution robustness in a post-hoc manner.

We assume that a standard ReID model has been trained on HR images. After extracting features from paired LR and HR samples, we get paired features as $\{(z_{LR}, z_{HR})\}$ and directly use the paired features for training. Our training requires no ID labels and learns the resolution difference in the vector space.

Thus, we could train the VP using the proposed VPL:

$$\mathcal{L}_{\text{VPL}} = \|f(z_{LR}) - z_{HR}\|_2^2 \tag{8}$$

The VP is optimized using the Adam optimizer with a fixed learning rate schedule and weight decay, and the model typically converges within 120 epochs. The process is simple, efficient, and supervision-free. The full training pipeline is shown in Algorithm1.

5 EXPERIMENT

In this section, we first introduce the datasets, experimental settings, and implementation details. We then conduct extensive experiments, including comparisons with existing methods and ablation

method	MLR-Market-1501			MLR-CUHK03			MLR-VIPeR			CAVIAR		
	Rank1	Rank5	Rank10	Rank1	Rank5	Rank10	Rank1	Rank5	Rank10	Rank1	Rank5	Rank10
ResNet-50 He et al. (2016)	57.0	78.7	-	70.8	91.3	-	31.4	63.1	-	31.1	65.5	-
CamStyle Zhong et al. (2018)	74.5	88.6	93.0	69.1	89.6	93.9	34.4	56.8	66.6	32.1	72.3	85.9
Part Aligned(Martinel et al. 2019)	75.6	88.5	92.2	73.4	92.1	97.5	40.2	62.3	73.1	35.7	71.4	87.9
FD-GAN Ge et al. (2018)	79.6	91.6	93.5	73.4	93.8	97.9	39.1	62.1	72.5	33.5	71.4	96.5
PyrNet(Goodfellow et al. 2014)	83.8	93.3	95.6	83.9	97.1	98.5	-	-	-	43.6	79.2	90.4
SING Jiao et al. (2018)	74.4	87.8	91.6	67.7	90.7	94.7	33.5	57	66.5	33.5	72.7	89
CSR-GAN Wang et al. (2018)	76.4	88.5	91.9	71.3	92.1	97.4	37.2	62.3	71.6	34.7	72.5	87.4
RAIN Chen et al. (2019)	-	-	-	78.9	97.3	98.7	42.5	68.3	79.6	42.0	77.3	89.6
RAPSR Yuan et al. (2025a)	-	-	-	74.9	94.6	-	-	-	-	42.8	78.4	-
CAD Li et al. (2019)	83.7	92.7	95.8	82.1	97.4	98.8	43.1	68.2	77.5	42.8	76.2	91.5
PRI Han et al. (2020)	84.9	93.5	96.1	85.2	97.5	98.8	-	-	-	43.2	78.5	91.9
PyrNet+PRI Han et al. (2020)	86.9	93.8	96.4	86.5	97.7	99.1	-	-	-	45.2	84.1	94.6
INTACT Cheng et al. (2020)	88.1	95.0	96.9	86.4	97.4	98.5	46.2	73.1	81.6	44.0	81.8	93.9
JBIM Zheng et al. (2022)	88.1	95.1	96.9	88.3	97.2	98.7	49.7	72.5	81.3	52.0	83.1	94.4
LRAR Wu et al. (2023)	90.1	96.2	97.7	89.2	98.9	99.8	-	-	-	63.6	79.2	96.6
PS-HRNet Zhang et al. (2021)	91.5	96.7	97.9	92.6	98.3	99.4	48.7	73.4	81.7	48.2	84.5	96.3
IFRSW Peng et al. (2024)	92.3	96.9	97.8	93.4	98.7	99.2	50.1	75.3	83.4	52.4	87.3	97.9
ours	94.1	97.6	98.6	94.7	99.5	99.8	50.5	78.8	87.6	66.6	87.9	93.6

Table 3: Results of Cross-Resolution Re-ID (%). Bold and underlined numbers indicate top two results, respectively.

studies, to validate the effectiveness of our approach. Additionally, we evaluate the extensibility of our method by applying it to two representative models in cross-modal ReID and text-image ReID, in order to examine its potential generalization ability for cross-domain feature alignment.

5.1 DATASETS

We used four person ReID benchmarks in our CR-ReID evaluations. The **Market-1501** dataset Zheng et al. (2015) consists of 32,668 images of 1,501 identities captured in 6 camera views. We used the standard 751/750 training/test identity split. The **CUHK03** dataset Gray & Tao (2008) contains 14,097 images of 1,467 individuals captured in 10 (5 pairs) different cameras. Besides, we use the 1,367/100 training/testing identity split Li et al. (2019). The **VIPeR** dataset Li et al. (2014) contains 1,220 images of 72 person identities captured by 2 cameras. We randomly divided this dataset into two non-overlapping halves based on the identity labels. The **CAVIAR** dataset Zheng et al. (2017) is a dataset collected in the real world. The dataset contains 1,220 images of 72 individuals captured from two cameras. Following Jiao et al. (2018), we discard 22 individuals who have only HR images. The remaining data is randomly divided into two equal parts for training and testing, each containing 25 identities. Following Li et al. (2019), we evaluate our method under the multiple LR (MLR) person ReID setting. We conduct experiments on four synthetic benchmarks—Market-1501, CUHK08, VIPeR, and DukeMTMC—and one real-world dataset, CAVIAR. For the synthetic datasets, query images from one camera are downsampled by a randomly selected rate $r \in \{2, 3, 4\}$, resulting in image sizes of $H/r \times W/r$, where H and W are the original height and width. The gallery images remain at the original resolution. We refer to these modified datasets as MLR-Market, MLR-CUHK08, MLR-VIPeR, and MLR-DukeMTMC. In contrast, CAVIAR provides naturally captured images with real resolution differences, making it a more realistic MLR benchmark.

5.2 IMPLEMENTATION DETAILS

We adopt TransReID He et al. (2021) as the backbone for feature extraction, trained only on original-resolution datasets (official weights used when available). No fine-tuning is performed for cross-resolution settings. During inference, both HR and LR images are fed into the backbone to obtain features z_{HR} and z_{LR}. Our VP module is a three-layer MLP with residual connection. It first projects the 3840-dimensional(-d) input to 2048-d, followed by two hidden layers of size 2048, each with a linear projection, LayerNorm, and ReLU. The final layer maps back to 3840-d with a Tanh activation to constrain the residual. The output is added to the input to produce the aligned feature $\hat{z}_{LR}$. To build training data, we compute ID-wise mean features from HR and LR sets, retaining IDs with at least two samples from each. For each ID, we create pairs $(\bar{z}_{LR}, \bar{z}_{HR})$ and sample 5,000 such pairs with identity-level shuffling. The VP is trained for 120 epochs using Adam (lr = 2e-4, weight decay = 1e-5) with batch size 32. The loss is mean squared error (VPL) between $\hat{z}_{LR}$ and

z_{HR}. We initialize linear layers with $\mathcal{N}(0, 10^{-3})$ and set all biases to zero. At inference, the trained VP is directly applied to LR features as a postprocessing step.

5.3 Comparisons to State-of-the-Art Methods

We compare our proposed VPFA with two categories of representative methods. (1) Traditional person ReID baselines, including ResNet-50, CamStyle, and FD-GAN, which are not specifically designed for resolution variation. (2) Recent advanced CR-ReID methods that aim to address cross-resolution challenges via super-resolution, resolution-invariant learning, or hybrid strategies. Representative examples include SING Jiao et al. (2018), PS-HRNet Zhang et al. (2021), and INTACT Cheng et al. (2020), among others. The comparison results are summarized in Table3, and the following observations can be made:

(1) Our **VPFA** achieves the highest Rank-1 accuracy on all four datasets. It outperforms PS-HRNet by 2.6% and 2.1% on MLR-Market-1501 and MLR-CUHK03 respectively, setting new state-of-the-art results. It also ranks first in Rank-5 and Rank-10 on three of the four datasets.

(2) Compared to SR-based CSR-GAN and hybrid INTACT, VPFA shows clear advantages. On MLR-Market-1501, it improves Rank-1 by 17.7% over CSR-GAN and 6.0% over INTACT, demonstrating the effectiveness of feature-level alignment over pixel-level restoration or joint learning.

(3) On smaller datasets, VPFA remains competitive. It reaches 50.6% Rank-1 on MLR-VIPeR, outperforming JBIM (49.7%) and PS-HRNet (48.7%). On CAVIAR, it achieves 66.6% Rank-1 and 87.9% Rank-5, exceeding the previous bests of 63.6% and 84.5%.

(4) Against resolution-invariant methods like LRAR and PS-HRNet, VPFA achieves comparable or better results. This confirms the effectiveness of our lightweight post-processing in addressing resolution gaps without architectural changes or retraining.

5.4 Efficiency Analysis

We assess the efficiency of our VPFA module from two key perspectives: inference speed and model size. On average, our method achieves an inference efficiency of 4,424,371.31 samples/second, demonstrating its extremely low computational overhead. Additionally, VPFA contains only 24.14 million parameters, which is significantly smaller than many existing ReID modules. These results underscore the efficiency and practicality of our approach. As a lightweight, feature-level module, VPFA can be seamlessly integrated into existing ReID frameworks without retraining, making it highly suitable for rapid deployment in real world scenarios.

5.5 Ablation Study and Parameter Analysis

Category	Method / Setting	Rank-1	Rank-5	Rank-10
Baseline	TransReID	90.3	96.1	97.5
	TransReID + VPFA	**94.1**	**97.6**	**98.6**
Residual	w/o Residual	91.2	96.7	98.0
	w/ Residual	**94.1**	**97.6**	**98.6**

(a) Baseline and residual analysis

Category	Method / Setting	Rank-1	Rank-5	Rank-10
Dim	512	92.7	96.9	97.9
	1048	93.4	97.2	98.5
	2048	**94.1**	**97.6**	**98.6**
	3840	92.8	96.9	98.0
#VP Blocks	1	92.8	97.0	98.0
	2	93.2	97.6	98.1
	3	**94.1**	**97.6**	**98.6**
	4	92.6	96.9	97.8

(b) Dimension and VP blocks analysis

Table 4: Ablation analysis and parameter analysis of VPFA on MLR-Market1501. Bold values indicate the best results. "Dim" refers to the hidden dimension in the VP block.

With vs. Without VPFA Unless otherwise noted, all ablations are conducted on MLR-Market-1501. To assess the impact of VPFA, we compare the baseline TransReID model with and without it, as shown in Table4a. VPFA consistently improves all metrics, notably boosting Rank-1 by +3.8%, without altering the backbone or its training.

(a) Original Features   (b) Aligned Features (Ours)

Figure 3: t-SNE visualization of features from 12 identities. Colors indicate different person IDs, and color brightness reflects resolution level (dark: HR, light: LR). VPFA effectively narrows the gap between HR and LR representations.

Effect of Residual Connection We ablate the residual connection by replacing the output with a direct mapping $f(z_{LR})$. As shown in Table4a, its removal degrades performance, confirming its necessity. The residual design enables VP to refine features without overwriting identity semantics, aiding robustness to resolution variation.

Effect of hidden layer dimension We vary the hidden layer width of the VP structure, as shown under Dim. VP Block in Table4b. Performance improves to 2048 before saturation, with 2048-d hidden layers achieving 94.1% Rank-1 on MLR-Market1501. Smaller widths like 512 underfit the cross-resolution alignment transformation, while larger ones such as 3840 add parameters without benefits. Thus, we use 2048.

VPblock numbers To assess depth, we stack VP blocks. Table4bshows increasing the number of blocks from 1 to 3 improves steadily, while adding a fourth block slightly degrades accuracy, likely due to overfitting or redundancy. Thus, moderate stacking boosts representation capacity while keeping the design concise.

5.6 VISUALIZATION ANALYSIS

Feature Space Visualization To further verify the effectiveness of our method in aligning LR features with their HR counterparts, we visualize feature distributions with t-SNE before and after VPFA. In Fig.3, colors denote identities and brightness encodes resolution, with dark for HR and light for LR.From Fig.3(a), LR features are dispersed from their HR counterparts with weak intra-identity cohesion, revealing resolution-induced divergence. In contrast, Fig.3(b) shows that after applying VPFA, the LR features shift to HR features and form tighter identity clusters. These results show that VPFA semantically aligns cross-resolution features and reduces the domain gap.

6 CONCLUSION

We propose Vector Panning–based Feature Alignment (VPFA), a post-processing method for cross-resolution person ReID. Unlike prior approaches that require super-resolution or backbone changes, VPFA works purely at the feature level and integrates into existing ReID models without retraining. Central to VPFA is a lightweight MLP-based Vector Panning (VP) module that learns correction vectors to align low-resolution features with high-resolution ones. The Vector Panning Loss (VPL) enforces both directional and magnitude consistency. Experiments on four benchmarks demonstrate that VPFA consistently improves strong baselines and generalizes to cross-modality ReID, underscoring its versatility as a universal feature alignment module.

REFERENCES

Song Bai, Peng Tang, Philip H.S. Torr, and Longin Jan Latecki. Re-ranking via metric fusion for object retrieval and person re-identification. In *2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 740–749, 2019. doi: 10.1109/CVPR.2019.00083.

Hao Chen, Benoit Lagadec, and François Brémond. Ice: Inter-instance contrastive encoding for unsupervised person re-identification. *2021 IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 14940–14949, 2021. URL https://api.semanticscholar.org/CorpusID:232417748.

Ying-Cong Chen, Xiatian Zhu, Wei-Shi Zheng, and Jian-Huang Lai. Person re-identification by camera correlation aware feature augmentation. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 40(2):392–408, 2018. doi: 10.1109/TPAMI.2017.2666805.

Yun-Chun Chen, Yu-Jhe Li, Xiaofei Du, and Y. Wang. Learning resolution-invariant deep representations for person re-identification. In *AAAI Conference on Artificial Intelligence*, 2019. URL https://api.semanticscholar.org/CorpusID:57541847.

Zhiyi Cheng, Qi Dong, Shaogang Gong, and Xiatian Zhu. Inter-task association critic for cross-resolution person re-identification. In *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 2602–2612, 2020. doi: 10.1109/CVPR42600.2020.00268.

Jacob Cohen. *Statistical Power Analysis for the Behavioral Sciences*. Lawrence Erlbaum Associates, revised edition edition, 1988. doi: 10.4324/9780203771587. URL https://doi.org/10.4324/9780203771587.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale. *ArXiv*, abs/2010.11929, 2020. URL https://api.semanticscholar.org/CorpusID:225039882.

Shuguang Dou, Cairong Zhao, Xinyang Jiang, Shanshan Zhang, Wei-Shi Zheng, and Wangmeng Zuo. Human co-parsing guided alignment for occluded person re-identification. *IEEE Transactions on Image Processing*, 32:458–470, 2023. doi: 10.1109/TIP.2022.3229639.

Xingye Fang, Yang Yang, and Ying Fu. Visible-infrared person re-identification via semantic alignment and affinity inference. In *2023 IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 11236–11245, 2023. doi: 10.1109/ICCV51070.2023.01035.

Yixiao Ge, Zhuowan Li, Haiyu Zhao, Guojun Yin, Shuai Yi, Xiaogang Wang, and Hongsheng Li. Fd-gan: Pose-guided feature distilling gan for robust person re-identification. In *Neural Information Processing Systems*, 2018. URL https://api.semanticscholar.org/CorpusID:52941531.

Shaogang Gong, Marco Cristani, Shuicheng Yan, and Chen Change Loy. *Person Re-Identification*. Springer Publishing Company, Incorporated, 2014. ISBN 1447162951.

Ian J. Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron C. Courville, and Yoshua Bengio. Generative adversarial nets. In *Neural Information Processing Systems*, 2014. URL https://api.semanticscholar.org/CorpusID:261560300.

Douglas Gray and Hai Tao. Viewpoint invariant pedestrian recognition with an ensemble of localized features. *DBLP*, 2008.

Ke Han, Yan Huang, Zerui Chen, Liang Wang, and Tieniu Tan. Prediction and recovery for adaptive low-resolution person re-identification. In *Computer Vision – ECCV 2020: 16th European Conference, Glasgow, UK, August 23–28, 2020, Proceedings, Part XXVI*, pp. 193–209, Berlin, Heidelberg, 2020. Springer-Verlag. ISBN 978-3-030-58573-0. doi: 10.1007/978-3-030-58574-7_12. URL https://doi.org/10.1007/978-3-030-58574-7_12.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 770–778, 2016. doi: 10.1109/CVPR.2016.90.

Shuting He, Haowen Luo, Pichao Wang, F. Wang, Hao Li, and Wei Jiang. Transreid: Transformer-based object re-identification. *2021 IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 14993–15002, 2021. URL https://api.semanticscholar.org/CorpusID:231846818.

Zhengdong Hu, Yifan Sun, Yi Yang, and Jianguang Zhou. Divide-and-regroup clustering for domain adaptive person re-identification. In *Thirty-Sixth AAAI Conference on Artificial Intelligence, AAAI 2022, Thirty-Fourth Conference on Innovative Applications of Artificial Intelligence, IAAI 2022, The Twelveth Symposium on Educational Advances in Artificial Intelligence, EAAI 2022 Virtual Event, February 22 - March 1, 2022*, pp. 980–988. AAAI Press, 2022. doi: 10.1609/AAAI.V36I1. 19981. URL https://doi.org/10.1609/aaai.v36i1.19981.

Ding Jiang and Mang Ye. Cross-modal implicit relation reasoning and aligning for text-to-image person retrieval. *2023 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 2787–2797, 2023. URL https://api.semanticscholar.org/CorpusID:257663606.

Jiening Jiao, Wei-Shi Zheng, Ancong Wu, Xiatian Zhu, and Shaogang Gong. Deep low-resolution person re-identification. In *Proceedings of the Thirty-Second AAAI Conference on Artificial Intelligence and Thirtieth Innovative Applications of Artificial Intelligence Conference and Eighth AAAI Symposium on Educational Advances in Artificial Intelligence*, AAAI'18/IAAI'18/EAAI'18. AAAI Press, 2018. ISBN 978-1-57735-800-8.

Ziqi Jin, Jinheng Xie, Bizhu Wu, and Linlin Shen. Weakly supervised pedestrian segmentation for person re-identification. *IEEE Transactions on Circuits and Systems for Video Technology*, 33(3): 1349–1362, 2023. doi: 10.1109/TCSVT.2022.3210476.

R. A. Johnson and D. W. Wichern. *Applied multivariate statistical analysis*. Prentice-Hall, Inc., USA, 1988. ISBN 0130411469.

Christian Ledig, Lucas Theis, Ferenc Huszár, Jose Caballero, Andrew Cunningham, Alejandro Acosta, Andrew Aitken, Alykhan Tejani, Johannes Totz, Zehan Wang, and Wenzhe Shi. Photo-realistic single image super-resolution using a generative adversarial network. In *2017 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 105–114, 2017. doi: 10.1109/CVPR.2017.19.

Geon Lee, Sanghoon Lee, Dohyung Kim, Younghoon Shin, Yongsang Yoon, and Bumsub Ham. Camera-driven representation learning for unsupervised domain adaptive person re-identification. In *2023 IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 11419–11428, 2023. doi: 10.1109/ICCV51070.2023.01052.

Minxian Li, Xiatian Zhu, and Shaogang Gong. Unsupervised tracklet person re-identification. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 42(7):1770–1782, 2020. doi: 10. 1109/TPAMI.2019.2903058.

Wei Li, Rui Zhao, Tong Xiao, and Xiaogang Wang. Deepreid: Deep filter pairing neural network for person re-identification. In *2014 IEEE Conference on Computer Vision and Pattern Recognition*, pp. 152–159, 2014. doi: 10.1109/CVPR.2014.27.

Wei Li, Xiatian Zhu, and Shaogang Gong. Harmonious attention network for person re-identification. *2018 IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 2285–2294, 2018. URL https://api.semanticscholar.org/CorpusID:3458516.

Xiang Li, Wei-Shi Zheng, Xiaojuan Wang, Tao Xiang, and Shaogang Gong. Multi-scale learning for low-resolution person re-identification. In *2015 IEEE International Conference on Computer Vision (ICCV)*, pp. 3765–3773, 2015. doi: 10.1109/ICCV.2015.429.

Yu-Jhe Li, Yun-Chun Chen, Yen-Yu Lin, Xiaofei Du, and Yu-Chiang Frank Wang. Recover and identify: A generative dual model for cross-resolution person re-identification. In *2019 IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 8089–8098, 2019. doi: 10.1109/ICCV. 2019.00818.

Jialun Liu, Yifan Sun, Feng Zhu, Hongbin Pei, Yi Yang, and Wenhui Li. Learning memory-augmented unidirectional metrics for cross-modality person re-identification. In *2022 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 19344–19353, 2022. doi: 10.1109/CVPR52688.2022.01876.

Jinxian Liu, Bingbing Ni, Yichao Yan, Peng Zhou, Shuo Cheng, and Jianguo Hu. Pose transferrable person re-identification. In *2018 IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 4099–4108, 2018. doi: 10.1109/CVPR.2018.00431.

Niki Martinel, Gian Luca Foresti, and Christian and Micheloni. Aggregating deep pyramidal representations for person re-identification. In *2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops (CVPRW)*, pp. 1544–1554, 2019. doi: 10.1109/CVPRW.2019. 00196.

Tomas Mikolov, Wen-tau Yih, and Geoffrey Zweig. Linguistic regularities in continuous space word representations. In Lucy Vanderwende, Hal Daumé III, and Katrin Kirchhoff (eds.), *Proceedings of the 2013 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pp. 746–751, Atlanta, Georgia, June 2013. Association for Computational Linguistics. URL https://aclanthology.org/N13-1090/.

Nanda Neel, Rajamanoharan Senthooran, Kramár János, and Shah Rohin. Fact finding: Attempting to reverse-engineer factual recall on the neuron level. URL https://www.alignmentforum.org/s/hpWHhjvjn67LJ4xXX/p/iGuwZTHWb6DFY3sKB.

Dat Tien Nguyen, Hyung Gil Hong, Ki Wan Kim, and Kang Ryoung Park. Person recognition system based on a combination of body images from visible light and thermal cameras. *Sensors*, 17(3), 2017. ISSN 1424-8220. doi: 10.3390/s17030605. URL https://www.mdpi.com/1424-8220/17/3/605.

Zhiqi Pang, Jifeng Guo, Zhiqiang Ma, Wenbo Sun, and Yanbang Xiao. Median stable clustering and global distance classification for cross-domain person re-identification. *IEEE Transactions on Circuits and Systems for Video Technology*, 32(5):3164–3177, 2022. doi: 10.1109/TCSVT. 2021.3103753.

Zhiqi Pang, Lingling Zhao, and Chunyu Wang. Dual-resolution fusion modeling for unsupervised cross-resolution person re-identification. In *Proceedings of the 32nd ACM International Conference on Multimedia*, MM '24, pp. 4063–4072, New York, NY, USA, 2024. Association for Computing Machinery. ISBN 9798400706868. doi: 10.1145/3664647.3681067. URL https://doi.org/10.1145/3664647.3681067.

Houfu Peng, Xing Lu, Xia Daoxun, and Xiaoyao Xie. A novel image restoration solution for cross-resolution person re-identification. 2024. doi: 10.21203/rs.3.rs-3594420/v1.

Kaijie Ren and Lei Zhang. Implicit discriminative knowledge learning for visible-infrared person re-identification. *2024 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 393–402, 2024. URL https://api.semanticscholar.org/CorpusID: 268531822.

Yantao Shen, Hongsheng Li, Shuai Yi, Dapeng Chen, and Xiaogang Wang. Person re-identification with deep similarity-guided graph neural network. In *European Conference on Computer Vision*, 2018. URL https://api.semanticscholar.org/CorpusID:50785503.

Haochen Wang, Jiayi Shen, Yongtuo Liu, Yan Gao, and Efstratios Gavves. Nformer: Robust person re-identification with neighbor transformer. In *2022 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 7287–7297, 2022. doi: 10.1109/CVPR52688.2022.00715.

Zheng Wang, Ruimin Hu, Yi Yu, Junjun Jiang, Chao Liang, and Jinqiao Wang. Scale-adaptive low-resolution person re-identification via learning a discriminating surface. In *Proceedings of the Twenty-Fifth International Joint Conference on Artificial Intelligence*, IJCAI'16, pp. 2669–2675. AAAI Press, 2016. ISBN 9781577357704.

Zheng Wang, Mang Ye, Fan Yang, Xiang Bai, and Shin'Ichi Satoh. Cascaded sr-gan for scale-adaptive low resolution person re-identification. In *Proceedings of the 27th International Joint Conference on Artificial Intelligence*, IJCAI'18, pp. 3891–3897. AAAI Press, 2018. ISBN 9780999241127.

Ziyu Wei, Xi Yang, Nannan Wang, and Xinbo Gao. Syncretic modality collaborative learning for visible infrared person re-identification. In *2021 IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 225–234, 2021. doi: 10.1109/ICCV48922.2021.00029.

Ziyu Wei, Xi Yang, Nannan Wang, and Xinbo Gao. Flexible body partition-based adversarial learning for visible infrared person re-identification. *IEEE Transactions on Neural Networks and Learning Systems*, 33(9):4676–4687, 2022. doi: 10.1109/TNNLS.2021.3059713.

Lin Wu, Yang Wang, Hongzhi Yin, Meng Wang, and Ling Shao. Few-shot deep adversarial learning for video-based person re-identification. *IEEE Transactions on Image Processing*, 29:1233–1245, 2019. URL https://api.semanticscholar.org/CorpusID:88522997.

Lin Wu, Yang Wang, Junbin Gao, Meng Wang, Zheng-Jun Zha, and Dacheng Tao. Deep coattention-based comparator for relative representation learning in person re-identification. *IEEE Transactions on Neural Networks and Learning Systems*, 32(2):722–735, 2021. doi: 10.1109/TNNLS. 2020.2979190.

Lin Wu, Deyin Liu, Wenying Zhang, Dapeng Chen, Zongyuan Ge, Farid Boussaid, Mohammed Bennamoun, and Jialie Shen. Pseudo-pair based self-similarity learning for unsupervised person re-identification. *IEEE Transactions on Image Processing*, 31:4803–4816, 2022. doi: 10.1109/ TIP.2022.3186746.

Lin Yuanbo Wu, Lingqiao Liu, Yang Wang, Zheng Zhang, Farid Boussaid, Mohammed Bennamoun, and Xianghua Xie. Learning resolution-adaptive representations for cross-resolution person re-identification. *IEEE Transactions on Image Processing*, 32:4800–4811, 2023. doi: 10.1109/TIP. 2023.3305817.

Mang Ye, Jianbing Shen, Gaojie Lin, Tao Xiang, Ling Shao, and Steven C. H. Hoi. Deep learning for person re-identification: A survey and outlook. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 44(6):2872–2893, 2022a. doi: 10.1109/TPAMI.2021.3054775.

Yuteng Ye, Hang Zhou, Junqing Yu, Qiang Hu, and Wei Yang. Dynamic feature pruning and consolidation for occluded person re-identification. In *AAAI Conference on Artificial Intelligence*, 2022b. URL https://api.semanticscholar.org/CorpusID:254044700.

Junhui Yin, Xinyu Zhang, Zhanyu Ma, Jun Guo, and Yifan Liu. A real-time memory updating strategy for unsupervised person re-identification. *IEEE Transactions on Image Processing*, 32: 2309–2321, 2023. doi: 10.1109/TIP.2023.3266166.

Caihong Yuan, Zhijie Guan, Yuanchen Xu, Xiaopan Chen, Xiaoke Zhu, and Wenjuan Liang. Jointly adaptive cross-resolution person re-identification on super-resolution. *Complex & Intelligent Systems*, 11, 04 2025a. doi: 10.1007/s40747-025-01881-1.

Chao Yuan, Guiwei Zhang, Changxiao Ma, Tianyi Zhang, and Guanglin Niu. From poses to identity: Training-free person re-identification via feature centralization. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pp. 24409–24418, 2025b.

Chao Yuan, Tianyi Zhang, and Guanglin Niu. Neighbor-based feature and index enhancement for person re-identification. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pp. 5762–5769, 2025c.

Guoqing Zhang, Yu Ge, Zhicheng Dong, Hao Wang, Yuhui Zheng, and Shengyong Chen. Deep high-resolution representation learning for cross-resolution person re-identification. *IEEE Transactions on Image Processing*, 30:8913–8925, 2021. doi: 10.1109/TIP.2021.3120054.

Liang Zheng, Liyue Shen, Lu Tian, Shengjin Wang, Jingdong Wang, and Qi Tian. Scalable person re-identification: A benchmark. In *2015 IEEE International Conference on Computer Vision (ICCV)*, pp. 1116–1124, 2015. doi: 10.1109/ICCV.2015.133.

Wei Shi Zheng, Jincheng Hong, Jiening Jiao, Ancong Wu, and Jianhuang Lai. Joint bilateral-resolution identity modeling for cross-resolution person re-identification. *International Journal of Computer Vision*, 130(8), 2022.

Zhedong Zheng, Liang Zheng, and Yi Yang. Unlabeled samples generated by gan improve the person re-identification baseline in vitro. In *2017 IEEE International Conference on Computer Vision (ICCV)*, pp. 3774–3782, 2017. doi: 10.1109/ICCV.2017.405.

Zhun Zhong, Liang Zheng, Zhedong Zheng, Shaozi Li, and Yi Yang. Camera style adaptation for person re-identification. In *2018 IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 5157–5166, 2018. doi: 10.1109/CVPR.2018.00541.

Runwu Zhou, Xiaojun Chang, Lei Shi, Yi-Dong Shen, Yi Yang, and Feiping Nie. Person reiden-tification via multi-feature fusion with adaptive graph learning. *IEEE Transactions on Neural Networks and Learning Systems*, 31(5):1592–1601, 2020. doi: 10.1109/TNNLS.2019.2920905.

Aichun Zhu, Zijie Wang, Yifeng Li, Xili Wan, Jing Jin, Tian Wang, Fangqiang Hu, and Gang Hua. Dssl: Deep surroundings-person separation learning for text-based person retrieval. *Proceedings of the 29th ACM International Conference on Multimedia*, 2021. URL https://api.semanticscholar.org/CorpusID:237490866.

Xiangping Zhu, Xiatian Zhu, Minxian Li, Vittorio Murino, and Shaogang Gong. Intra-camera supervised person re-identification: A new benchmark. *2019 IEEE/CVF International Conference on Computer Vision Workshop (ICCVW)*, pp. 1079–1087, 2019. URL https://api.semanticscholar.org/CorpusID:201646405.

A APPENDIX

A.1 EXPERIMENTAL ENVIRONMENT

All experiments were conducted on a server equipped with an Intel(R) Xeon(R) Platinum 8336C CPU (base frequency 2.30 GHz) as the central processing unit. For parallel computing and acceleration of deep learning tasks, the system utilized NVIDIA A800 GPUs with 40GB of memory. The operating system running on the server was Debian GNU/Linux 11(bullseye), providing a stable environment for software execution and dependency management.

A.2 TESTING IN MORE CHALLENGING CROSS-RESOLUTION SETTINGS

To further validate the generalizability and robustness of our approach, we conduct experiments under more complex cross-resolution scenarios. Specifically, we follow the traditional cross-resolution ReID construction strategy for consistency, and extend the original MLR datasets to include six downsampling ratios (2×, 3×, 4×, 5×, 6×, and 7×), forming a new benchmark we refer to as **ML-Rpro**. In addition, we evaluate on MSMT17, which is the largest fully supervised ReID dataset, comprising 126,441 images with greater domain and resolution diversity.

As shown in Table5, our proposed VPFA consistently improves the performance over both the standard MLR and the more challenging MLRpro settings. The improvements are especially significant on MSMT17, demonstrating that VP maintains strong effectiveness even under large-scale, high-variance conditions.

A.3 GENERALIZATION ACROSS MODALITIES

To assess VPFA's generalization beyond cross-resolution tasks, we apply it to two cross-modality settings: visible-infrared (VI) and text-image (TI) ReID. We use SAAI Fang et al. (2023) as the baseline on RegDB for VI ReID, and IRRA Jiang & Ye (2023) on RSTPReid for TI ReID. VPFA is directly integrated into each backbone without architectural or training changes.

Method	Market1501 (R1/5/10)	MSMT17 (R1/5/10)
MLR	90.3 / 96.1 / 97.5	80.4 / 88.7 / 91.4
MLR + VP	**94.1 / 97.6 / 98.6**	**83.1 / 90.5 / 91.9**
MLRpro	84.3 / 90.4 / 92.2	75.1 / 83.9 / 87.1
MLRpro + VP	**88.2 / 93.7 / 95.6**	**79.6 / 86.2 / 90.0**

Table 5: Performance under more challenging cross-resolution settings.

Task	Method	Dataset	mAP	Rank-1	Rank-5
VI	SAAI (v2i)	RegDB	91.45	91.07	-
	+VPFA (v2i)		**92.13**	**91.36**	-
	SAAI (i2v)		92.01	92.09	-
	+VPFA (i2v)		**93.02**	**92.71**	-
TI	IRRA	RSTPReid	47.17	60.20	81.30
	+VPFA		**47.85**	**61.20**	**82.05**

Table 6: Generalization of VPFA to cross-modality and text-image ReID tasks. VI: visible-infrared; TI: text-image.

RegDB Nguyen et al. (2017) contains 8,240 visible/infrared image pairs from 412 identities, split into train/test sets. It includes two settings: Visible2Infrared (v2i) and Infrared2Visible (i2v), referring to cross-modal retrieval directions. **RSTPReid** Zhu et al. (2021) includes 20,505 images of 4,101 identities, each annotated with two text descriptions. Following the official split, the training/validation/test sets include 3,701, 200, and 200 identities, respectively.

As shown in Table6, VPFA consistently improves performance across both tasks. On RegDB, it enhances SAAI by +0.68% and +1.01% mAP in the v2i and i2v settings, respectively, with corresponding Rank-1 gains of +0.29% and +0.62%. These improvements verify VPFA's effectiveness in mitigating modality-induced shifts between visible and infrared features.

On the more challenging TI task, VPFA boosts IRRA on RSTPReid by +0.68% mAP, +1.00% Rank-1, and +0.75% Rank-5. This suggests its capability in aligning representations even across vision and language domains.

Overall, these results highlight VPFA's strong cross-modal generalization. Its feature-level semantic correction mechanism enables flexible deployment across modalities without retraining, making it a broadly applicable postprocessing solution for heterogeneous ReID tasks.

A.4 FEATURE ALIGNMENT EFFECTIVENESS

To further validate the effectiveness of VPFA in aligning cross-resolution features, we conduct a quantitative analysis on the MLR-Market1501 dataset. Specifically, we compute the Euclidean distances between the HR (HR) and LR (LR) feature centers for a subset of representative identities, both before and after applying VPFA.

As shown in Table7, the distances between HR and LR feature centers are consistently reduced after applying our module. On average, the distances are reduced by approximately 25%, clearly demonstrating VPFA's capability in narrowing the semantic gap induced by resolution differences. These results provide strong evidence that our method effectively aligns cross-resolution features at the representation level.

ID	1401	865	877	1355	507
Before VPFA	17.87	22.53	15.32	15.26	15.15
After VPFA	13.78	16.34	11.28	11.10	10.87
Reduction	22.92%	27.46%	26.35%	27.24%	28.18%

Table 7: Euclidean distances between HR and LR feature centers for six sample identities on MLR-Market1501.

Figure 4: Visualization of Retrieval Results Before and After Applying Vector Panning based Feature Alignmen(VPFA).(The left side of the figure shows the original experimental results, while the right side shows the results after applying VPFA.)

A.5 EXPERIMENTAL DETAILS

For experiments on the MLR-CUHK03, MLR-VIPeR, and CAVIAR datasets, we perform 10 random splits and report the average results. The corresponding results are presented in Table8, Table9, and Table10, respectively.

Split	0	1	2	3	4	5	6	7	8	9	AVG
R1	95.0	95.1	97.3	94.1	95.6	91.3	93.5	96.0	95.7	93.1	94.7
R5	99.8	99.6	100.0	99.2	98.3	99.2	99.8	100.0	99.6	99.2	99.5
R10	99.8	100.0	100.0	100.0	99.2	99.8	99.8	100.0	100.0	99.6	99.8

Table 8: Performance on CUHK03 over 10 splits and the average result.

Split	0	1	2	3	4	5	6	7	8	9	AVG
R1	57.9	56.0	43.4	49.4	34.8	50.9	50.3	57.3	54.4	50.3	50.5
R5	79.7	80.7	79.1	82.0	65.5	79.7	81.6	78.2	78.2	83.2	78.8
R10	89.2	89.2	87.3	89.2	77.2	87.3	88.9	88.6	88.3	91.1	87.6

Table 9: Performance on VIPER over 10 splits and the average result.

A.6 VISUALIZATION ANALYSIS

Fig.4 presents a qualitative comparison of retrieval results before and after applying VPFA. The left side shows the original results, where many top-ranked retrievals (highlighted with red bounding boxes) are incorrect matches, indicating that the baseline model struggles to distinguish fine-grained appearance cues under cross-resolution settings. In contrast, the right side displays the results after integrating VPFA. Most top-ranked candidates are now correct matches (green bounding boxes), and the ranking of true matches has been significantly improved. This improvement demonstrates that VPFA effectively aligns LR features with their HR counterparts, reducing semantic discrepancies and enhancing retrieval precision.

A.7 CROSS-DOMAIN ANALYSIS

To evaluate whether our proposed VPFA module truly captures resolution-related semantics rather than dataset-specific distribution priors, we conduct cross-domain experiments where the VP is trained on one dataset and directly applied to others without any fine-tuning. The results are shown in Table11. We observe that the VP trained on MLR-Market1501 performs remarkably well on MLR-CUHK03 (Rank-1: 94.0), and vice versa (Rank-1: 90.5), even though the two datasets differ

Split	0	1	2	3	4	5	6	7	8	9	AVG
R1	66.8	74.4	68.0	71.6	44.8	76.4	78.8	72.8	61.2	52.0	66.6
R5	91.2	90.0	85.2	90.8	77.6	89.6	92.0	92.0	80.0	81.2	87.9
R10	95.2	96.4	92.0	96.0	87.2	96.0	96.8	97.2	86.4	92.8	93.6

Table 10: Performance on CAVIAR over 10 splits and the average result.

in appearance distributions and camera styles. Furthermore, both VP modules achieve considerable improvements on the CAVIAR dataset, despite no exposure to its domain during training. These results contrast with the non-cross-domain setting in Table.11, where VP is trained and tested on the same dataset. The relatively strong cross-dataset generalization suggests that VPFA does not simply overfit to dataset-specific features, but learns an intrinsic semantic direction in the embedding space that consistently reflects resolution-induced feature shifts. This demonstrates the transferable nature of the resolution alignment learned by our model.

A.8 THE USE OF LARGE LANGUAGE MODELS(LLMs)

During the preparation of this manuscript, we used LLMs to assist in language polishing and grammar checking.

Training Dataset	Test Dataset	Rank-1	Rank-5
MLR-Market1501	MLR-CUHK03	94.0	97.3
MLR-CUHK03	MLR-Market1501	90.5	96.2
MLR-Market1501	MLR-Market1501	94.1	97.8
MLR-CUHK03	MLR-CUHK03	94.7	99.5

Table 11: Cross-domain evaluation results of VPFA. Each row indicates the dataset used for training the VP module, while the columns show results on different test datasets.