CauFR-TS: Causal Time-Series Identifiability via Factorized Representations

Abstract

Causal discovery from multivariate time series is a fundamental problem for interpretable modelling, causality-aware downstream analysis, and intervention-driven simulation. Recent neural approaches commonly rely on shared latent embeddings to capture temporal dynamics and utilize them for causal structure estimation and downstream prediction. We formally establish that such shared encoders entangle distinct causal mechanisms into a unified latent manifold, which exhibits fundamental theoretical limitations of structural non-identifiability and conditional independence assumptions required for Granger causality. To address these issues, we propose CauFR-TS, a recurrent variational framework that enforces mechanism modularity through dimension-wise encoders and ensures mediation of all cross-variable dependencies through structured latent aggregation. Furthermore, we address the instability of heuristic thresholding in continuous relaxation methods by proposing an adaptive, data-driven unsupervised link selection strategy based on decoder weight distribution. Empirical evaluation on synthetic and in silico biological benchmarks demonstrates that CauFR-TS outperforms recent baselines in graph recovery metrics while preserving competitive probabilistic forecasting performance. Code for review: https://anonymous.4open.science/r/caufr-ts-148D

1 Introduction

Understanding causal relationships in multivariate time series is a fundamental problem with implications for forecasting, decision-making, and intervention-aware simulation in domains such as climate science (Fizaine & Le Borgne, 2025), healthcare (Feuerriegel et al., 2024), and industrial monitoring (Ma et al., 2025). Unlike static causal discovery, temporal causal inference must simultaneously account for temporal dependencies, delayed effects, and feedback loops (Mokhtarian et al., 2025; Ferdous et al., 2025) while remaining robust to noise, nonlinearity, and high dimensionality (Aslan & Ombao, 2025; Zhou et al., 2024). As a result, Granger causality and its nonlinear extensions have emerged as a dominant operational the operational bedrock for causal discovery in time series (Mameche et al., 2025; Gong et al., 2024), positing that a variable X^j causes X^i if the unique history of X^j reduces the predictive error of X^i.

While classical Vector Autoregressive models (Moneta et al., 2011; Haufe et al., 2010) provide interpretability, they fail to capture the nonlinear dynamics inherent in real-world systems. This limitation has spurred a paradigm shift towards neural Granger causality methods, where deep neural networks parameterize autoregressive functions (Lin et al., 2024; Bussmann et al., 2021). Such methods leverage expressive function approximators to model nonlinear temporal dynamics while inducing sparsity in lagged dependencies, enabling scalable causal graph estimation. Subsequent works have extended this paradigm to high-dimensional settings (Mokhtarian et al., 2025), irregularly sampled time series (Cheng et al., 2024), and scenarios incorporating interventional or heterogeneous data (Varı cıet al., 2024). More recent transformer-based approaches (Kong et al., 2025; Huang et al., 2025) further aim to unify temporal representation learning and causal graph estimation within a single end-to-end framework, offering improved performance and interpretability.

Despite their empirical success, we identify a critical theoretical oversight in the design of modern causal time-series models. The prevailing architectural paradigm employs a shared encoder processing the full

multivariate input vector X_t to map history into a unified latent representation Z_t. This latent code is subsequently reused for forecasting, simulation, and causal structure estimation (Lin et al., 2024; Li et al., 2023). While this design is computationally appealing, we argue that this design fundamentally violates the Principle of Independent Causal Mechanisms (ICM) (Parascandolo et al., 2018). By compressing the history of all variables into a shared vector, the encoder inevitably entangles the information of distinct mechanisms. From a causal inference perspective, this shared representation acts as an unobserved architectural confounder that violates the conditional independence assumptions (Seth & Príncipe, 2012) required for Granger causality. Even if variable X^j has no true causal effect on X^i, a shared encoder may leak information about X^j into the latent representation used to predict X^i. Consequently, downstream detectors, including attention heads or sparse decoders, operate on confounded representations, rendering the resulting causal graphs structurally non-identifiable (Bodik & Chavez-Demoulin, 2025; Brogueira & Figueiredo, 2025).

Several recent works attempt to mitigate related challenges through architectural regularization, graph priors, or adaptive lag selection (Zoroddu et al., 2024; Zhang et al., 2024). Methods incorporating prior structural knowledge constrain the search space of causal graphs, while flexible time-windowed and dynamic causal discovery approaches address temporal heterogeneity and evolving dependencies. However, these methods typically assume that the learned latent representations are causally valid and do not explicitly prevent cross-variable information sharing at the representation level (Chen et al., 2025; Zhang et al., 2025). Similarly, thresholding strategies for causal link selection are often heuristic or manually tuned, leading to instability across datasets and limiting reproducibility (Lee & Honavar, 2020). Therefore, reliable causal identification in deep time-series models requires explicit enforcement of mechanism modularity at the representation level.

To bridge the gap between deep generative expressivity and rigorous causal identifiability, we propose CauFR-TS. Unlike prior approaches that rely on post-hoc interpretation of entangled representations or solely impose sparsity at the decoder level, CauFR-TS enforces causal modularity directly at the representation level. Specifically, we introduce a factorized encoder architecture in which each time series variable is processed by an independent neural module, thereby strictly preventing information leakage in the latent space. In addition, to address the sensitivity of existing methods to manually tuned thresholding hyperparameters, we propose an adaptive, parameter-free causal thresholding strategy based on a Gaussian Mixture Model of learned decoder weights, which robustly separates causal signals from noise and yields stable causal graphs. We further provide a theoretical analysis showing that CauFR-TS restores causal identifiability under the Principle of Independent Causal Mechanisms. Extensive empirical evaluation on synthetic benchmarks and biologically grounded datasets demonstrate that CauFR-TS consistently outperforms the state-of-the-art baselines in causal graph recovery. Furthermore, we empirically verify that enforcing causal modularity does not degrade predictive performance, thereby decoupling causal identifiability from forecasting accuracy.

2 Preliminaries

We briefly introduce the notation, causal notions, and identifiability principles underlying our analysis. These concepts form the theoretical basis for Granger causal discovery in multivariate time series and motivate the architectural considerations examined in the subsequent section.

Definition 1 (Granger Causality) *A time series component $x^{(j)}$ is said to Granger-cause $x^{(i)}$ if the prediction of $x_t^{(i)}$ based on the full history X_{t-} is strictly better, in terms of reduced prediction error variance, than the prediction based on the history excluding $x^{(j)}$, denoted as X_{t-}^{-j}. Formally, if $P(x_t^{(i)}|X_{t-}) \neq P(x_t^{(i)}|X_{t-}^{-j})$, then a directed Granger-causal link $x^{(i)} \to x^{(i)}$ exists.*

Granger causality (Granger, 1969) operationalizes causality through conditional predictive dependence and is widely adopted in temporal causal discovery.

Definition 2 (Structural Identifiability) *Let $\mathcal{M} = \{P_\theta : \theta \in \Omega\}$ be a parametric model class over observable data X, where θ parameterizes both the data-generating mechanisms and an associated causal graph $G(\theta)$. The model class $\mathcal{M}$ is said to be structurally identifiable if, for any two parameter sets $\theta, \theta' \in \Omega$, $P_\theta(X) = P_{\theta'}(X) \Rightarrow \theta = \theta'$, up to trivial symmetries such as permutation or reparameterization that do not alter the causal structure.*

In non-linear settings, structural identifiability is generally not guaranteed without additional assumptions. Results from non-linear Independent Component Analysis show that latent representations learned from observational data are typically identifiable only up to complex non-linear transformations, unless constraints, such as sparsity, interventions, or non-stationarity are imposed.

Definition 3 (Graph Identifiability) *A causal model class $\mathcal{M}$ is said to be graph identifiable if, for any two parameter sets $\theta, \theta' \in \Omega$, $P_\theta(X) = P_{\theta'}(X) \Rightarrow G(\theta) = G(\theta')$, where $G(\theta)$ denotes the causal graph induced by the parameters θ.*

In causal discovery from observational time series, graph identifiability is a necessary condition for reliable inference. If multiple causal graphs induce the same observational distribution, no algorithm can distinguish them without additional assumptions.

Definition 4 (Independent Causal Mechanisms (ICM)) *Let $X_t = (x_t^{(1)}, \ldots, x_t^{(D)})$ denote a multivariate time series generated by a causal process with directed temporal graph G. The Principle of Independent Causal Mechanisms posits that each variable $x_t^{(p)}$ is generated by a distinct causal mechanism $x_t^{(p)} = f_p\big(PA(x^{(p)})_{t-}, \varepsilon_t^{(p)}\big)$, where $PA(x^{(p)})_{t-}$ denotes the historical causal parents of $x^{(p)}$, $\varepsilon_t^{(p)}$ is an exogenous noise term, and the mechanisms $\{f_p\}_{p=1}^{D}$ are statistically independent in the sense that knowledge of one mechanism provides no information about the others.*

Under ICM (Gresele et al., 2021), the conditional transition distribution of the multivariate time series factorizes according to the causal graph as:

$$P(X_t|X_{t-}) = \prod_{p=1}^{D} P(x_t^{(p)}|PA(x^{(p)})_{t-})$$

This factorization expresses mechanism modularity, namely that each variable evolves according to its own autonomous mechanism conditioned solely on its direct causes. In neural time-series models, ICM can be respected when each $P(x_t^{(p)}|\cdot)$ is parameterized independently. However, a shared encoder that maps the multivariate history into a single latent representation z_t, induces a common conditioning context across variables. If z_t is not explicitly factorized, information from different channels becomes entangled, rendering the conditional distributions $P(x_t^{(p)}|z_t)$ statistically dependent. This violates ICM and motivates encoder-level modularity as a necessary structural prior for causal identifiability.

3 Fundamental Limitations of Shared-Latent Causal TS Models

In recent years, a large class of neural time-series models has emerged that jointly perform generative modelling, forecasting, and causal discovery (Kong et al., 2025; Li et al., 2023; Tank et al., 2021). Most of these approaches adopt a shared-latent architectural paradigm, wherein a single encoder maps the multivariate history into a global latent representation, which is subsequently reused by task-specific decoders to generate predictions and infer causal structure. This design underlines recurrent VAE-based causal models, shared-backbone neural Granger causality methods, and several recent transformer-based formulations.

Despite their empirical success, the theoretical implications of shared latent representations for causal identifiability remain poorly understood. In this section, we analyze this architectural paradigm and show that shared latent encoders fundamentally violate the conditional independence assumptions required for Granger causality. As a result, the induced causal graphs are generally non-identifiable, regardless of the model capacity or decoder-level sparsity constraints.

3.1 Model Class and Problem Setup

Let $X_t = (x_t^{(1)}, \cdots, x_t^{(D)}) \in \mathbb{R}^D$ denote a multivariate time series generated by an unknown causal process. We consider a broad class of neural causal time-series models that employ a shared encoder $z_t = f_\theta(X_{t-})$, where $z_t \in \mathbb{R}^H$ is the latent representation computed from the full multivariate history and reused by one

or more decoders for prediction, generation, and causal structure estimation. The encoder parameters are shared across variables, and no explicit constraint enforces variable-wise separation in the latent space. This formulation subsumes recurrent VAE-based architectures, shared-backbone neural Granger causality models, and transformer-based approaches relying on a global latent state.

3.2 Entanglement in Shared Latent Encoders

We first show that shared encoders inevitably induce information redundancy and non-identifiability of channel-specific contributions.

Proposition 1 (Entanglement and Information Mixing) *Let $\mathbf{z}_t = f_\theta(\mathbf{X}_{t-}) \in \mathbb{R}^H$ be a latent representation produced by a shared encoder with parameters θ, where f_θ jointly processes the full multivariate history $\mathbf{X}_{t-} = (x_{t-}^{(1)}, \ldots, x_{t-}^{(D)})$. Then, in general, $\mathbf{z}_t$ constitutes a non-separable representation in which information from multiple input channels is entangled across its dimensions. Consequently, there exists no unique decomposition $\mathbf{z}_t = (\mathbf{z}_t^{(1)}, \ldots, \mathbf{z}_t^{(D)})$ such that each component $\mathbf{z}_t^{(p)}$ depends exclusively on the history of variable $x^{(p)}$, $\forall p \in \{1, \cdots, D\}$.*

Proof sketch. The shared encoder f_θ maps the full multivariate history $\mathbf{X}_{t-}$ to a latent representation $\mathbf{z}_t$ using a single parameterization. As a result, each latent dimension $h \in \{1, \cdots, H\}$ is, in general, a function of multiple input channels, implying that information from different variables is mixed across the latent space. Although f_θ is expressive enough to represent arbitrary nonlinear transformations, this expressiveness leads to non-identifiability in the absence of additional structural constraints. In particular, without architectural modularity or independence-enforcing assumptions, multiple latent representations exist that induce identical predictive distributions while assigning different subsets of latent dimensions to different variables.

Consequently, no unique decomposition of $\mathbf{z}_t$ into variable-specific components is identifiable, establishing that shared latent encoders yield the entangled representations that preclude variable-wise separation.

3.3 Violation of Conditional Independence

Having established in Proposition 1 that shared latent encoders produce inherently entangled representations, we next show that such entanglement has direct consequences for causal identification. Specifically, entangled latent variables function as unobserved confounders at the representation level, thereby violating the conditional independence conditions required for valid Granger causal inference.

Proposition 2 (Latent-Induced Confounding) *Let $\mathbf{z}_t = f_\theta(\mathbf{X}_{t-})$ be a latent representation produced by a shared encoder with a single parameterization over all the input channels. When causal influence on a target variable $\hat{x}_t^{(q)}$ is estimated through $\mathbf{z}_t$, the representation induces confounding between source variables, thereby violating the conditional independence assumptions required for valid Granger causal inference.*

Proof sketch. Granger causality relies on conditional independence: if a variable $x^{(p)}$ does not Granger-cause $x^{(q)}$, then conditioning on the histories of all other variables renders $x^{(p)}$ irrelevant for predicting $x_t^{(q)}$. In shared-latent architectures, however, the encoder f_θ compresses the entire multivariate history into a single latent representation, causing information from multiple source variables to be jointly encoded.

As a result, $\mathbf{z}_t$ generally contains predictive information about $x_t^{(q)}$ originating from variables other than $x^{(p)}$, even after conditioning. This latent aggregation effectively introduces an unobserved confounder between the source variables at the representation level. Consequently, conditioning on $\mathbf{z}_t$ does not recover the required conditional independence, and estimated causal effects from $x_{t-}^{(p)}$ to $x_t^{(q)}$ are biased by spurious dependencies induced by the shared representation.

We provide the detailed theoretical proofs and discussion of the limitations in Appendix D.

Figure 1: Overview of CauFR-TS. Each variable is encoded independently via a channel-wise encoder, yielding a factorized latent representation **z**. Decoders parameterized by group-sparse weights model cross-channel temporal dependencies. A data-driven thresholding procedure applied to decoder weights recovers the causal adjacency matrix A.

4 Proposed CauFR-TS Framework

Motivated by the theoretical limitations of shared-latent architectures, we propose CauFR-TS, a neural Granger causal discovery framework based on factorized latent representations. The method trains a recurrent variational forecaster to model the conditional distribution $\hat{p}(\mathbf{x}_T|\mathbf{x}_{1:T-1})$, while enforcing structured sparsity in the decoding stage to recover the underlying causal adjacency matrix.

4.1 Model Architecture

Our model comprises a multi-head recurrent encoder and a multi-head fully connected decoder. Given a past observation window of length τ, the model can be expressed as,

$$\hat{x}_T^{(d)} = D_\Theta^{(d)}\left(E_\Phi^{(d)}\left(x_{T-\tau:T-1}\right)\right), \quad \forall d \in \{1,\ldots,D\} \tag{1}$$

where $E_\Phi^{(d)}(\cdot)$ and $D_\Theta^d(\cdot)$ denote the encoder and decoder associated with the d^{th} variable, respectively. We do not restrict the architecture of the encoder to a specific recurrent formulation. Instead, any recurrent encoder that processes the lagged observations $x_{T-\tau:T-1}^{(d)}$ and produces a latent embedding $h^{(d)} \in \mathbb{R}^H$ may be employed. Channel-specific embeddings are subsequently reparameterized (Chung et al., 2015; Fabius et al., 2014) and concatenated to form a joint latent representation $\mathbf{z} \in \mathbb{R}^{D \times H}$, which is then provided as input to the decoder. The multi-head decoder is composed of single-layer fully-connected networks, where each decoding head maps the joint latent representation $\mathbf{z}$ to the parameters of the conditional distribution of $x_T^{(d)}$. Taken together, the decoder parameterizes the joint conditional distribution $p(x_T|x_{1:T-1})$. Subsequently, the prediction for the multivariate observation x_T is constructed by concatenating the outputs of the D decoder heads. A formal description of the encoder and decoder has been provided in Appendix C.

4.2 Objective Function

To estimate the causal matrix A during training, we employ the group-wise sparsification method widely adopted in many recent causal discovery works (Rahmani & Frossard, 2025; Dhir et al., 2025; Li et al., 2023). The learning objective of CauFR-TS is to jointly maximize the forecasting accuracy of the multivariate time series while enforcing sparsity in the causal structure, under the assumption that the actual causal matrix A is sparse. We formulate this objective by maximizing the Evidence Lower Bound (ELBO), augmented with a structural sparsity penalty. For optimization, this is implemented as the minimization of a composite loss function comprising the Negative Log-Likelihood and the KL-Divergence. Formally, given a time series instance $x_{1:T-1}$ of D variables, the encoder parameters Φ, and the decoder parameters Θ, the composite

---

Algorithm 1 CauFR-TS Training Pipeline and Optimization

Require: Initialized encoder parameters $\Phi = \{\phi_d\}_{d=1}^D$ and decoder parameters $\Theta = \{\theta_d\}_{d=1}^D$; KL and Group
    lasso coefficients β & λ; learning rate η; Time lag τ;
Input: Multivariate time series instance $\{x\}_{t=1}^T$ with D dimensions;
Output: Estimated Granger causal matrix $\hat{A}$ and trained model parameters $\{\Phi, \Theta\}$;
  1: **while** not converged or stopping criteria not met **do**
  2:      Extract $x_{t-\tau:t-1}$ from $\{x_t\}_{t=1}^T$
  3:      **for** $d = 1$ to D **do**
  4:          Extract $x_{t-\tau:t-1}^{(d)}$ from $x_{t-\tau:t-1}$
  5:          Compute posteriors (μ_d, σ_d) using ϕ_d
  6:          Sample latent $z^{(d)} \sim \mathcal{N}(\mu_d, \text{diag}(\sigma_d^2))$ $\triangleright \mathcal{L}_{KL}$
  7:      **end for**
  8:      Construct latent representation $z = \{z^{(d)}\}_{d=1}^D$
  9:      **for** $d = 1$ to D **do**
10:          Predict $\hat{x}_t^{(d)}$ from z using θ_d $\triangleright \mathcal{L}_{MSE}$
11:          Extract decoder weights $\mathbf{W}_{(j)}^{(d)}$ connecting z_j to target d $\triangleright \mathcal{L}_{GL}$
12:      **end for**
13:      Compute total loss $\mathcal{L}$ from Equation 2
14:      Update $\{\Phi, \Theta\}$ using AdamW optimizer
15: **end while**
16: Invoke Algorithm 2 to retrieve $\hat{A}$
17: **return** $\hat{A}$ and trained $\{\Phi, \Theta\}$.

---

objective function can be defined as,

$$\mathcal{L}(\Phi, \Theta) = -\mathbb{E}_{q_\Phi(\mathbf{z}|x)}[\log p_\Theta(x|\mathbf{z})] + \beta\,\mathcal{D}_{KL}(q_\Phi(\mathbf{z}|x)||p(\mathbf{z})) + \lambda \sum_{i=1}^D \sum_{j=1}^D ||\mathbf{W}_{(j)}^i||_2 \tag{2}$$

where β and λ are hyperparameters controlling the strength of the variational regularization and the group lasso penalty, respectively. The core mechanism of our causal discovery mechanism is the Group Lasso penalty applied to the decoder weights. Let $\mathbf{W}^i \in \mathbb{R}^{D \cdot K}$ be the weight vector of the decoder head predicting $\hat{x}_t^{(i)}$. We partition $\mathbf{W}^i$ into D groups, where the j^{th} group, denoted as $\mathbf{W}_{(j)}^i \in \mathbb{R}^K$, contains the weights connecting $\mathbf{z}_j$, the latent vector of variable j, to the predictor of i^{th} variable. The third term in Equation 2, weighted by λ, applies an ℓ_1/ℓ_2 regularization in order to introduce the Granger-causal sparsity. If the predictor for the target variable i does not rely on the history of the source variable j, the optimization process drives the ℓ_2 norm of the entire block $\mathbf{W}_{(j)}^i$ to zero. Consequently, the absence of a causal link $j \rightarrow i$ is learned end-to-end, as the decoder effectively blocks the input from z_j. In our experiments, we tune λ alongside the variational weight β to balance identifiability and forecasting performance.

4.3 Probabilistic Thresholding of Group-Lasso Weights

We implement a data-driven adaptive thresholding mechanism to eliminate spurious connections and retrieve the causal structure during training. Prior approaches commonly rely on manually specified thresholds on weight norms to identify Granger-causal parents. In this work, we instead model the distribution of learned interaction strengths, measured via the ℓ_2-norms of decoder weight groups, using a Gaussian Mixture Model (GMM).We fit a two-component GMM to the empirical distribution $p(s)$ of weight norms, modelling interaction strengths as a bimodal distribution with one component capturing weak, non-causal interactions and the other capturing strong, potentially causal interactions. Formally, we can define it as,

$$p(s) = \pi_{\text{noise}}\mathcal{N}(s; \mu_{\text{noise}}, \sigma_{\text{noise}}^2) + \pi_{\text{signal}}\mathcal{N}(s; \mu_{\text{signal}}, \sigma_{\text{signal}}^2) \tag{3}$$

where π_k, μ_k, σ_k^2 represent the mixing coefficient, mean, and variance for component $k \in \{\text{noise}, \text{signal}\}$. We enforce the structural constraint $\mu_{\text{noise}} < \mu_{\text{signal}}$ to identify the components. The parameters $\psi =$

Algorithm 2 Probabilistic Thresholding of Group-Lasso Weights using Gaussian Mixture Model

---

Require: Decoder weight groups $\mathbf{W}_{(j)}^i$, $\forall i, j \in \{1, \ldots, D\}$

Ensure: Binary causal adjacency matrix $\hat{A}$

1: Initialize set of interaction strengths $\mathcal{S} = \phi$
2: **for** each variable $i = 1$ to D and each group $j = 1$ to D **do**
3:     Compute interaction strengths $s_{(j)}^i \leftarrow \|\mathbf{W}_{(j)}^i\|_2$
4:     $\mathcal{S} \leftarrow \mathcal{S} \cup \{s_{(j)}^i\}$
5: **end for**
6: Construct empirical distribution $p(s)$ from $\mathcal{S}$
7: Fit a two-component GMM to $p(s)$ ▷ Equation 3
8: Compute posteriors $\gamma_k(s) = P(C = k \mid s)$ for $k \in \{\text{noise, signal}\}$
9: Identify Noise cluster and Signal cluster where $\mu_{\text{noise}} < \mu_{\text{signal}}$.
10: Determine adaptive threshold τ^* ▷ Equation 4
11: Obtain $\hat{A}_{ij} = \mathbb{I}(\|\mathbf{W}_{(j)}^i\|_2 > \tau^*)$
12: **return** $\hat{A}$

$\{\pi_k, \mu_k, \sigma_k\}_k$ are estimated via the Expectation-Maximization (EM) algorithm. Given the estimated mixture parameters, the optimal threshold τ^* is defined as the point that minimizes the Bayes classification error, equivalently given by the intersection of the posterior probabilities of the two Gaussian components.

Let $\gamma_k(s) = P(C = k|s)$ be the posterior probability that an observed strength s belongs to component k. The decision boundary τ^* is the value in the interval $[\mu_{\text{noise}}, \mu_{\text{signal}}]$ satisfying:

$$\tau^* = \{s \in \mathbb{R}^+ \mid \gamma_{\text{signal}}(s) = \gamma_{\text{noise}}(s)\} \tag{4}$$

Practically, τ^* is where the probability density of the causal signal begins to dominate the noise tail. The final binary causal matrix $\hat{A}$ is then obtained as follows,

$$\hat{A}_{ij} = \begin{cases} 1 & \text{if } s_{ij} > \tau^* \\ 0 & \text{otherwise} \end{cases}$$

By adapting τ^* to the empirical distribution of learned weights, the method reduces reliance on manually specified hyperparameters and exhibits robustness across different scales of causal effects.

5 Experimental Setup

In this section, we first outline the datasets, baselines, and evaluation metrics, followed by reporting results on causal discovery, predictive accuracy, and ablation analyses in the next section.

5.1 Datasets

We systematically evaluate the proposed approach on both causal discovery and time-series forecasting tasks using two widely adopted synthetic causal time-series benchmarks and two in silico simulated biological datasets, all of which provide access to ground-truth causal graphs.

Hénon maps. We consider a system of 10 coupled Hénon chaotic maps (Kugiumtzis, 2013), in which the ground-truth causal structure follows a unidirectional chain $x^{i-1} \rightarrow x^i$. A total of 5,000 samples are generated and used for training and evaluation.

Lorenz-96 model. The Lorenz system (Lorenz, 1996)is a nonlinear dynamical model commonly used to simulate atmospheric and climate processes. We simulate a 10-dimensional system ($p = 10$) with the forcing constant set to 10 and generate 5,000 samples for training and evaluation.

***E.coli* dataset.** The *E. coli* dataset (Krieger & Gilpin, 2025) consists of in silico gene expression time series generated from transcriptional regulatory subnetworks derived from RegulonDB v6.7, where biologically grounded network topologies are coupled with simulated nonlinear regulatory dynamics to provide known

(a) Ground Truth (b) CausalFormer   (c) CR-VAE   (d) NGC   (e) GVAR   (f) TCDF   (g) **Ours**

Figure 2: Visual representation of ground truth causal graph of Hénon (2a), retrieved adjacency matrices by the chosen baselines (2b-2f), and our proposed CauFR-TS (2g).

causal ground-truth structures for evaluation.

Yeast dataset. The yeast dataset (Krieger & Gilpin, 2025) comprises simulated gene expression time series constructed from curated *Saccharomyces cerevisiae* transcriptional regulatory networks, combining experimentally derived regulatory interactions with mechanistic nonlinear dynamical models to yield benchmark causal graphs with known ground truth.

More details of the datasets, including data generation process, the governing equations, and simulation dynamics, are provided in Appendix A and B.

5.2 Baselines

We compare our proposed CauFR-TS approach with five representative state-of-the-art methods for Granger Causal Discovery in multivariate time series. We specifically emphasize neural network-based approaches that infer causality via sparsification or interpretation of learned model parameters.

NGC (Tank et al., 2021) is the first neural network-based temporal causal discovery method which uses autoregressive neural networks with group sparsity on input connections. GVAR (Marcinkevičs & Vogt, 2021) uses self-explaining neural networks to augment neural Granger causality with explicit attribution mechanisms in order to improve interpretability of causal contributions. However, the underlying architecture still relies on shared latent representations and post-hoc explanation, failing to meet the ICM principles. CR-VAE (Li et al., 2023) integrates Granger causality into a recurrent variational autoencoder using a multi-head decoder and sparsity-inducing regularization. Causal structure is extracted from decoder weights, while the latent encoder is shared across variables, producing entangled representations. TCDF (Nauta et al., 2019) employs attention-based dilated temporal convolutions and infers causality from learned convolutional and attention weights. It represents convolutional neural approaches to Granger causal discovery based on parameter inspection under shared representations. Recently introduced CausalFormer (Kong et al., 2025) is a transformer-based temporal causal discovery model that learns predictive representations and recovers causal graphs through decomposition-based interpretation of attention and convolutional components.

All the aforementioned baselines apply sparsity or interpretability mechanisms, and infer causal links from globally shared representations. They implicitly assume that entangled latent embeddings preserve the conditional independence structure required for Granger causality. Our work formally examines and addresses the failure of this assumption by enforcing representation-level modularity through a factorized encoder-decoder design.

6 Results and Evaluation

The experimental evaluation assesses the proposed framework along two complementary dimensions. We first evaluate causal structure recovery from multivariate time series, which constitutes the primary objective of this work. We then assess predictive and generative performance to verify that enforcing representation-level modularity does not compromise forecasting accuracy. Causal discovery results are reported on synthetic and biologically grounded benchmarks with known ground truth, followed by forecasting results presented as a sanity check.

Table 1: Quantitative comparison of causal discovery using AUROC, F1-score, and SHD on the chosen datasets. The best performance has been highlighted in **bold**.

Metrics	Datasets	CausalFormer (Kong et al., 2025)	CR-VAE (Li et al., 2023)	NGC (Tank et al., 2021)	GVAR (Marcinkevičs & Vogt, 2021)	TCDF (Nauta et al., 2019)	**CauFR-TS** **(Proposed)**
AUROC↑	Hénon	0.971	0.960	0.960	0.925	0.911	**1.0**
	Lorenz-96	0.975	0.954	0.980	0.862	0.871	**1.0**
	E.coli	0.785	0.766	0.760	0.654	0.596	**0.994**
	Yeast	0.710	0.702	0.722	0.695	0.611	**0.925**
F1-Score↑	Hénon	0.926	0.879	0.946	0.866	0.820	**1.0**
	Lorenz-96	0.885	0.812	0.815	0.754	0.713	**1.0**
	E.coli	0.762	0.754	0.712	0.623	0.551	**0.855**
	Yeast	0.689	0.675	0.701	0.678	0.584	**0.819**
SHD↓	Hénon	3	6	3	6	9	**0**
	Lorenz-96	5	4	4	6	8	**0**
	E.coli	10	12	11	10	17	**6**
	Yeast	11	13	12	10	20	**7**

6.1 Causal Discovery Performance

Table 1 presents a quantitative comparison of causal discovery performance across the selected baseline methods and the proposed approach. Evaluation is conducted using three widely adopted metrics in the recent literature: Area under the receiver operating characteristic curve (AUROC) to assess ranking quality of inferred causal strengths; F1-score to measure binary edge detection accuracy after adaptive thresholding; Structural Hamming Distance (SHD) to quantify the absolute structural discrepancy between estimated and ground-truth graphs. For each method, the causal matrix corresponding to the minimum convex loss is selected. The proposed model achieves superior performance relative to the selected baselines across all three metrics on the synthetic Hénon, highlighting its effectiveness in recovering causal structures defined by known dynamical systems. On the in silico biological benchmarks, although the performance margins are smaller, the results still suggest that the model benefits from enforcing mechanism modularity to enhance temporal causal discovery. The visual comparison of causal discovery from Hénon dataset has been given in Figure 2.

Remark 1 (Latent Deconfounding via Factorization) *Let $X_t = \{x_{t-}^1, \ldots, x_{t-}^D\}$ be the multivariate history. In a shared-encoder framework, the latent state $z_t = E_\Phi(X_t)$ creates a path $x_{t-}^j \to z_t \to \hat{x}_t^i$ regardless of the causal graph structure A_{ji}. In contrast, CauFR-TS enforces a factorized mapping $z_t^i = E_\Phi^{(i)}(x_{t-}^i)$. Consequently, the conditional predictive distribution $P(x_t^i|X_t)$ satisfies:*

$$\frac{\partial \hat{x}_t^i}{\partial x_{t-}^j} \neq 0 \iff A_{ji} \neq 0$$

This condition ensures that the adjacency matrix A is the exclusive gateway for inter-variable information flow, structurally guaranteeing that non-zero edges in A are necessary to minimize prediction error, thereby improving identifiability.

To summarize, the observed performance gains of CauFR-TS can be attributed to its explicit enforcement of mechanism modularity at the representation level and the adaptive thresholding strategy applied on the decoder weight distribution. Unlike NGC, CausalFormer, and CR-VAE, which rely on shared latent encoders or post-hoc interpretation of entangled representations, CauFR-TS employs factorized, variable-specific encoders that prevent cross-channel information leakage during representation learning. This architectural constraint directly mitigates latent-induced confounding and restores the conditional independence assumptions underlying Granger causality. Furthermore, the proposed data-driven thresholding strategy based on the empirical distribution of decoder weights avoids the sensitivity and instability associated with manually tuned cutoffs, yielding consistent improvements.

Table 2: Quantitative comparison of one-step-ahead forecasting in terms of RMSE on the synthetic and in silico biological benchmarks. Lower values indicate better predictive accuracy.

Methods	Hénon	Lorenz-96	*E. coli*	Yeast
NGC (Tank et al., 2021)	0.233	0.384	0.668	0.689
CR-VAE (Li et al., 2023)	0.236	0.375	0.657	0.612
CauFR-TS (Proposed)	0.144	0.254	0.454	0.330

6.2 Probabilistic Forecasting Performance

While the primary objective of this work is causal structure identification, CauFR-TS is trained as a generative forecaster and should therefore preserve predictive performance. We evaluate whether enforcing representation-level modularity and causal sparsity adversely affects forecasting accuracy. To this end, we compare one-step-ahead prediction performance against representative baselines using RMSE, a standard forecasting metric. The quantitative performance has been given in Table 2.

Across all datasets, CauFR-TS achieves predictive performance comparable to or better than shared-latent baselines. This indicates that enforcing factorized representations and causal gating does not compromise forecasting accuracy, despite significantly improving causal identifiability. These results support the view that factorized latent representation yields accurate temporal prediction, and therefore, shared encoder can be safely eliminated in favour of causal modularity.

Additional Information. We provide additional visualization results and analyses on the convergence of the model and adaptive selection of threshold value in Appendix **??**, followed by the implementation setup in Appendix G.

6.3 Ablation Study

We conduct an ablation study to assess the contribution of the key architectural and algorithmic components of CauFR-TS. In particular, we examine the roles of encoder factorization and adaptive thresholding in achieving stable and identifiable causal discovery. Following the work by Li et al. (2023), we have chosen the fixed threshold value of 0 of the ℓ_2-norm of decoder weights. Both the ablated variants are evaluated under the same experimental protocol and datasets as the full model.

The ablation results in Table 3 highlight the necessity of each component in the proposed framework. Replacing the factorized encoder with a shared encoder degrades causal graph recovery. This behaviour is consistent with the theoretical analysis, which shows that shared representations induce latent confounding and non-identifiability. Substituting the adaptive thresholding mechanism with a fixed cutoff leads to a significant drop in performance. Depending on the chosen threshold, the method either fails to remove noisy connections, resulting in a high false positive rate, or suppresses weak but genuine causal links, leading to false negatives. This instability highlights the limitation of manually specified thresholds and motivates data-driven causal link selection. The shared-encoder variant benefits from adaptive GMM-based thresholding. Although the latent representation remains entangled, the mixture model separates signal and noise in the decoder weight distribution with sufficient reliability. This allows partial recovery of the causal structure and yields performance comparable to strong baselines. Overall, the results show that causal identifiability in CauFR-TS emerges from the combined effect of representation-level modularity and adaptive thresholding.

7 Conclusion

In this work, we investigated a fundamental limitation of the neural Granger causal discovery models for multivariate time series. Specifically, we showed that shared latent representations entangle distinct causal mechanisms and violate the conditional independence assumptions required for Granger causality, thereby leading to structurally non-identifiable causal graphs. To address these issues, we proposed CauFR-TS,

Table 3: Quantitative evaluation of the impacts of encoder factorization and adaptive thresholding with their respective ablations on causal discovery performance on Hénon maps.

Variant	Factorized Encoder	Adaptive Threshold	F1-score ↑	SHD ↓
Shared Encoder	×	√	0.870	6
Fixed Threshold	√	×	0.418	31
Full CauFR-TS	√	√	**1.0**	**0**

a recurrent variational framework that enforces mechanism modularity through channel-wise encoders and mediates cross-variable dependencies exclusively via structured latent aggregation. In addition, we introduced an adaptive, data-driven thresholding strategy for causal link selection that avoids heuristic tuning and yields stable causal graphs. Empirical results on synthetic dynamical systems and in silico biological benchmarks demonstrated the consistent superiority of CauFR-TS over recent baselines in causal graph recovery. In addition, we demonstrate that the proposed factorized architecture preserves forecasting performance, confirming that causal identifiability can be achieved without sacrificing generative accuracy. Future work will extend this framework to time-varying and irregularly sampled settings and incorporate interventional or weakly supervised signals to further strengthen causal identifiability.

Limitations. The proposed framework is developed under the Granger causality paradigm and is therefore limited to predictive causal relationships inferred from temporal dependence. It does not model instantaneous effects or interventional causal semantics. The theoretical analysis assumes observational time series generated by stationary mechanisms. In addition, the use of dimension-wise encoders may introduce computational overhead in very high-dimensional settings.

References

Sipan Aslan and Hernando Ombao. Granger causality in high-dimensional networks of time series, 2025.

Juraj Bodik and Valérie Chavez-Demoulin. Identifiability of causal graphs under non-additive conditionally parametric causal models. *Journal of Machine Learning Research*, 26(264):1–55, 2025.

Tiago Brogueira and Mário Figueiredo. Rethinking causal discovery through the lens of exchangeability, 2025.

Bart Bussmann, Jannes Nys, and Steven Latré. Neural additive vector autoregression models for causal discovery in time series. In Carlos Soares and Luis Torgo (eds.), *Discovery Science*, pp. 446–460, Cham, 2021. Springer International Publishing.

Guangyi Chen, Yunlong Deng, Peiyuan Zhu, Yan Li, Yifan Shen, Zijian Li, and Kun Zhang. Causalverse: Benchmarking causal representation learning with configurable high-fidelity simulations. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems Datasets and Benchmarks Track*, 2025.

Yuxiao Cheng, Lianglong Li, Tingxiong Xiao, Zongren Li, Jinli Suo, Kunlun He, and Qionghai Dai. Cuts+: high-dimensional causal discovery from irregular time-series. In *Proceedings of the Thirty-Eighth AAAI Conference on Artificial Intelligence and Thirty-Sixth Conference on Innovative Applications of Artificial Intelligence and Fourteenth Symposium on Educational Advances in Artificial Intelligence*, AAAI'24/IAAI'24/EAAI'24. AAAI Press, 2024. ISBN 978-1-57735-887-9. doi: 10.1609/aaai.v38i10.29034.

Junyoung Chung, Kyle Kastner, Laurent Dinh, Kratarth Goel, Aaron Courville, and Yoshua Bengio. A recurrent latent variable model for sequential data. In *Proceedings of the 29th International Conference on Neural Information Processing Systems - Volume 2*, NIPS'15, pp. 2980–2988, Cambridge, MA, USA, 2015. MIT Press.

Anish Dhir, Ruby Sedgwick, Avinash Kori, Ben Glocker, and Mark Van Der Wilk. Continuous Bayesian model selection for multivariate causal discovery. In Aarti Singh, Maryam Fazel, Daniel Hsu, Simon Lacoste-Julien, Felix Berkenkamp, Tegan Maharaj, Kiri Wagstaff, and Jerry Zhu (eds.), *Proceedings of the 42nd International Conference on Machine Learning*, volume 267 of *Proceedings of Machine Learning Research*, pp. 13486–13512. PMLR, 13–19 Jul 2025.

Otto Fabius, Joost R. van Amersfoort, and Diederik P. Kingma. Variational recurrent auto-encoders. *CoRR*, abs/1412.6581, 2014.

Muhammad Hasan Ferdous, Emam Hossain, and Md Osman Gani. Timegraph: Synthetic benchmark datasets for robust time-series causal discovery. In *Proceedings of the 31st ACM SIGKDD Conference on Knowledge Discovery and Data Mining V.2*, KDD '25, pp. 5425–5435, New York, NY, USA, 2025. Association for Computing Machinery. ISBN 9798400714542. doi: 10.1145/3711896.3737439.

Stefan Feuerriegel, Dennis Frauen, Valentyn Melnychuk, Jonas Schweisthal, Konstantin Hess, Alicia Curth, Stefan Bauer, Niki Kilbertus, Isaac S Kohane, and Mihaela van der Schaar. Causal machine learning for predicting treatment outcomes. *Nature Medicine*, 30(4):958–968, 2024.

Florian Fizaine and Guillaume Le Borgne. Climate knowledge matters: A causal analysis of knowledge and individual carbon emissions. *Journal of Environmental Management*, 385:125604, 2025. ISSN 0301-4797. doi: https://doi.org/10.1016/j.jenvman.2025.125604.

Chang Gong, Chuzhe Zhang, Di Yao, Jingping Bi, Wenbin Li, and YongJun Xu. Causal discovery from temporal data: An overview and new perspectives. *ACM Comput. Surv.*, 57(4), December 2024. ISSN 0360-0300. doi: 10.1145/3705297. URL https://doi.org/10.1145/3705297.

Clive WJ Granger. Investigating causal relations by econometric models and cross-spectral methods. *Econometrica: journal of the Econometric Society*, pp. 424–438, 1969.

Luigi Gresele, Julius von Kügelgen, Vincent Stimper, Bernhard Schölkopf, and Michel Besserve. Independent mechanism analysis, a new concept? In *Proceedings of the 35th International Conference on Neural Information Processing Systems*, NIPS '21, Red Hook, NY, USA, 2021. Curran Associates Inc. ISBN 9781713845393.

Stefan Haufe, Klaus-Robert Müller, Guido Nolte, and Nicole Krämer. Sparse causal discovery in multivariate time series. In Isabelle Guyon, Dominik Janzing, and Bernhard Schölkopf (eds.), *Proceedings of Workshop on Causality: Objectives and Assessment at NIPS 2008*, volume 6 of *Proceedings of Machine Learning Research*, pp. 97–106, Whistler, Canada, 12 Dec 2010. PMLR.

Jihua Huang, Yi Yao, and Ajay Divakaran. Transforming causality: Transformer-based temporal causal discovery with prior knowledge integration, 2025.

Lingbai Kong, Wengen Li, Hanchen Yang, Yichao Zhang, Jihong Guan, and Shuigeng Zhou. Causalformer: An interpretable transformer for temporal causal discovery. *IEEE Transactions on Knowledge and Data Engineering*, 37(1):102–115, 2025. doi: 10.1109/TKDE.2024.3484461.

Madison S. Krieger and William Gilpin. Interpretable gene network inference with nonlinear causality. *bioRxiv*, 2025. doi: 10.1101/2025.09.28.678927.

Dimitris Kugiumtzis. Direct-coupling information measure from nonuniform embedding. *Physical Review E—Statistical, Nonlinear, and Soft Matter Physics*, 87(6):062918, 2013.

Sanghack Lee and Vasant Honavar. Towards robust relational causal discovery. In Ryan P. Adams and Vibhav Gogate (eds.), *Proceedings of The 35th Uncertainty in Artificial Intelligence Conference*, volume 115 of *Proceedings of Machine Learning Research*, pp. 345–355. PMLR, 22–25 Jul 2020.

Hongming Li, Shujian Yu, and Jose Principe. Causal recurrent variational autoencoder for medical time series generation. In *Proceedings of the Thirty-Seventh AAAI Conference on Artificial Intelligence and Thirty-Fifth Conference on Innovative Applications of Artificial Intelligence and Thirteenth Symposium*

on Educational Advances in Artificial Intelligence, AAAI'23/IAAI'23/EAAI'23. AAAI Press, 2023. ISBN 978-1-57735-880-0. doi: 10.1609/aaai.v37i7.26031.

Hongyu Lin, Mohan Ren, Paolo Barucca, and Tomaso Aste. Granger causality detection with kolmogorov-arnold networks, 2024.

Edward N Lorenz. Predictability: A problem partly solved. In *Proc. Seminar on predictability*, volume 1. Reading, 1996.

Liang Ma, Yifei Peng, and Kaixiang Peng. An attention minimal gated unit-based causality analysis framework for root cause diagnosis of faults in nonstationary industrial processes. *IEEE Sensors Journal*, 25 (4):6952–6966, 2025. doi: 10.1109/JSEN.2024.3524388.

Sarah Mameche, Lénaïg Cornanguer, Urmi Ninad, and Jilles Vreeken. Spacetime: causal discovery from non-stationary time series. In *Proceedings of the Thirty-Ninth AAAI Conference on Artificial Intelligence and Thirty-Seventh Conference on Innovative Applications of Artificial Intelligence and Fifteenth Symposium on Educational Advances in Artificial Intelligence*, AAAI'25/IAAI'25/EAAI'25. AAAI Press, 2025. ISBN 978-1-57735-897-8. doi: 10.1609/aaai.v39i18.34136.

Ričards Marcinkevičs and Julia E Vogt. Interpretable models for granger causality using self-explaining neural networks. In *International Conference on Learning Representations*, 2021.

Ehsan Mokhtarian, Sepehr Elahi, Sina Akbari, and Negar Kiyavash. Recursive causal discovery. *Journal of Machine Learning Research*, 26(61):1–65, 2025.

Alessio Moneta, Nadine Chlass, Doris Entner, and Patrik Hoyer. Causal search in structural vector autoregressive models. In Florin Popescu and Isabelle Guyon (eds.), *Proceedings of the Neural Information Processing Systems Mini-Symposium on Causality in Time Series*, volume 12 of *Proceedings of Machine Learning Research*, pp. 95–114, Vancouver, Canada, 10 Dec 2011. PMLR.

Meike Nauta, Doina Bucur, and Christin Seifert. Causal discovery with attention-based convolutional neural networks. *Machine Learning and Knowledge Extraction*, 1(1):19, 2019.

Giambattista Parascandolo, Niki Kilbertus, Mateo Rojas-Carulla, and Bernhard Schölkopf. Learning independent causal mechanisms. In Jennifer Dy and Andreas Krause (eds.), *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pp. 4036–4044. PMLR, 10–15 Jul 2018.

Abdellah Rahmani and Pascal Frossard. Flow based approach for dynamic temporal causal models with non-gaussian or heteroscedastic noises. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems*, 2025.

Sohan Seth and José Carlos Príncipe. Assessing granger non-causality using nonparametric measure of conditional independence. *IEEE Transactions on Neural Networks and Learning Systems*, 23:47–59, 2012.

Alex Tank, Ian Covert, Nicholas Foti, Ali Shojaie, and Emily B Fox. Neural granger causality. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 44(8):4267–4279, 2021.

Burak Varıcı, Dmitriy A. Katz, Dennis Wei, Prasanna Sattigeri, and Ali Tajer. Interventional causal discovery in a mixture of dags. In A. Globerson, L. Mackey, D. Belgrave, A. Fan, U. Paquet, J. Tomczak, and C. Zhang (eds.), *Advances in Neural Information Processing Systems*, volume 37, pp. 86574–86601. Curran Associates, Inc., 2024. doi: 10.52202/079017-2749.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Ł ukasz Kaiser, and Illia Polosukhin. Attention is all you need. In I. Guyon, U. Von Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017.

Xingyu Zhang, Wenwen Qiang, Siyu Zhao, Huijie Guo, Jiangmeng Li, Chuxiong Sun, and Changwen Zheng. Caiformer: A causal informed transformer for multivariate time series forecasting, 2025.

Ziyi Zhang, Shaogang Ren, Xiaoning Qian, and Nick Duffield. Learning flexible time-windowed granger causality integrating heterogeneous interventional time series data. In *Proceedings of the 30th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, KDD '24, pp. 4408–4418, New York, NY, USA, 2024. Association for Computing Machinery. ISBN 9798400704901. doi: 10.1145/3637528.3672023.

Wanqi Zhou, Shuanghao Bai, Shujian Yu, Qibin Zhao, and Badong Chen. Jacobian regularizer-based neural granger causality. In *Proceedings of the 41st International Conference on Machine Learning*, ICML'24. JMLR.org, 2024.

Lucas Zoroddu, Pierre Humbert, and Laurent Oudre. Learning network granger causality using graph prior knowledge. *Transactions on Machine Learning Research*, 2024. ISSN 2835-8856.

CauFR-TS: Causal Time-Series Identifiability via Factorized Representations
(Appendix)

We have arranged the additional information and analysis in the appendix, organized under different sections and subsections. The arrangement of sections and their contents are as follows:

- Section A details the governing equations and data generation processes for the synthetic dynamical systems Hénon chaotic maps and Lorenz-96 data.

- Section B describes the in silico biological benchmark datasets, including the underlying transcriptional regulatory networks and kinetic models.

- Section C provides the rigorous mathematical formulation of the proposed CauFR-TS architecture, emphasizing the factorized Transformer encoder and the group-sparse decoder under Sections C.1 and C.2 respectively.

- Section E defines the quantitative evaluation metrics used to assess causal graph recovery in this work.

- Section F presents extended empirical results, focusing on the convergence dynamics of the learned decoder weights during training, the stability and efficiency of the adaptive thresholding mechanism.

- Section G outlines the implementation details, including hardware specifications, hyperparameter settings, and optimization procedures.

A   Synthetic Data Generation

Here we discuss all necessary equations used for synthesizing the Hénon chaotic maps Kugiumtzis (2013) and Lorenz-96 Lorenz (1996) data. Following these equations, we have generated the Hénon chaotic maps,

$$x_{t+1}^1 = 1.4 - (x_t^1)^2 + 0.3x_{t-1}^1, \tag{5}$$

$$x_{t+1}^d = 1.4 - (ex_t^{d-1} + (1-e)x_t^d)^2 + 0.3x_{t-1}^d, \tag{6}$$

where $d \in [2, M]$, M is the dimensionality, $e = 0.3$ and $d = 10$. The true causal relations $x^d \to x^{d+1}$ and self-causal relations $x^d \to x^d$ in the corresponding adjacency matrix should be 1. The lag length has been taken as 2.

Similarly, we have used the following equations for simulating the M-dimensional Lorenz-96 chaotic maps,

$$\frac{dx_t^p}{dt} = (x_t^{p+1} - x_t^{p-2})x_t^{p-1} - x_t^p + F \tag{7}$$

where $x_t^{-1} = x_t^{M-1}, x_t^0 = x_t^M, x_t^{M+1} = x_t^1$, p is the index variable and F is the forcing constant that dictates the degree of nonlinearity and chaos in the series.

We generated around 5000 samples for each dataset. For the Hénon and Lorenz-96 systems, we sample initial values from a typical Gaussian distribution and then infer the trajectories via transition functions.

The generated data is then divided into several chunks of consecutive timesteps. Each of the chunks is considered as a single instance. We divide the set of instances into training and validation sets in a ratio of 85:15. For all the experiments, we have taken the chunk size $X_{1:T} = 50$.

B   Details about in silico Biological Benchmark Datasets

***E. coli* Dataset.** To evaluate causal discovery in a biologically grounded setting, we utilize the *E. coli* benchmark dataset introduced by Krieger & Gilpin (2025). This dataset consists of gene expression time series generated from transcriptional regulatory subnetworks subsampled from the E. coli interactome

(a) First 100 timesteps of Hénon

(b) First 200 timesteps of Lorenz-96

Figure 3: Visualization of the first 4 dimensions of the generated Hénon and Lorenz-96 datasets

(RegulonDB v6.7). The underlying dynamics are simulated using a stochastic kinetic model that explicitly captures thermodynamic noise and regulatory kinetics. By retaining the topology of real biological subnetworks, such as specific degree distributions and motif frequencies, this dataset provides a realistic testbed for identifying causal links from sparse, noisy, and non-linear biological signals. For our experiments, we utilize the 10-node subsystem variant to evaluate the recovery of ground-truth transcriptional interactions.

Yeast Dataset. We further evaluate our method on the Yeast dataset (Krieger & Gilpin, 2025), which comprises simulated gene expression trajectories derived from *Saccharomyces cerevisiae*. Similar to the E. coli benchmark, the ground-truth causal graphs are constructed by integrating genome-wide transcription factor binding evidence with curated interactions. The dynamics are governed by a mechanistic model of coupled mRNA-protein interactions that incorporates key non-linear regulatory features, such as dimerization, phosphorylation-dependent activation, and autoregulatory feedback loops. These mechanisms induce complex dynamical behaviours, such as multistability and oscillations, making it an ideal dataset for validating our experiments on establishing causal identifiability.

C Details about the Encoder and Decoder

In this section, we provide the formal mathematical formulation of the channel-wise encoders and decoders introduced in Section 4.1. We employ a Transformer-based architecture for the encoder to capture long-range temporal dependencies within each univariate series and a structured Multi-Layer Perceptron (MLP) for the decoder to model cross-variable causal interactions.

C.1 Factorized Transformer Encoder

For a D-dimensional input, our proposed CauFR-TS utilizes D independent encoders. The input the d-th encoder head is the lagged history window $\mathbf{x}_{t-\tau:t-1}^{(d)} \in \mathbb{R}^{\tau \times 1}$.

Input Embedding and Positional Encoding. The scalar input at each time step $t \in \{1, \ldots, \tau\}$ is first projected into a higher-dimensional feature space d_{model} using a linear layer, followed by the addition of sinusoidal positional encodings PE to retain temporal order information:

$$\mathbf{h}_t^{(d)} = \text{Linear}(x_{T-\tau:t-1}^{(d)}) + PE(t)$$

Self-Attention Mechanism. The embedding is processed through L layers of Transformer blocks. Each block k computes the self-attention mechanism on the channel-specific history. Let $H^{(d,k-1)} \in \mathbb{R}^{\tau \times d_{model}}$ be the input to layer k. The query (Q), key (K), and value (V) matrices are computed as:

$$Q = H^{(d,k-1)} W_Q^{(d)}, \quad K = H^{(d,k-1)} W_K^{(d)}, \quad V = H^{(d,k-1)} W_V^{(d)}$$

The attention output is, therefore, derived via the scaled dot-product attention:

$$\text{Attention}(Q, K, V) = \text{softmax}\left(\frac{QK^T}{\sqrt{d_k}}\right) V$$

This mechanism allows the encoder $E_\Phi^{(d)}$ to dynamically weigh the historical time steps that are most relevant for the current state of variable d, without accessing information from other variables.

Variational Reparameterization. To enable the generative capability and robust latent representation required by the ELBO objective (Equation 2), the final hidden state of the Transformer is mapped to the parameters of the variational posterior $q_\phi(z^{(d)}|x^{(d)})$. Let $\mathbf{h}_{final}^{(d)}$ be the last time step output or a pooled representation, then we can represent the steps as:

$$\boldsymbol{\mu}^{(d)} = \text{Linear}_\mu(\mathbf{h}_{final}^{(d)}), \quad \log \boldsymbol{\sigma}^{2(d)} = \text{Linear}_\sigma(\mathbf{h}_{final}^{(d)})$$

The latent code $z^{(d)} \in \mathbb{R}^H$ is then obtained via the reparameterization trick:

$$z^{(d)} = \boldsymbol{\mu}^{(d)} + \boldsymbol{\epsilon} \odot \boldsymbol{\sigma}^{(d)}, \quad \boldsymbol{\epsilon} \sim \mathcal{N}(0, I)$$

This ensures that the latent subspace for dimension d contains stochastic information derived exclusively from the historical observations $x_{t-\tau:t-1}^{(d)}$. The global latent representation $\mathbf{z} \in \mathbb{R}^{D \times H}$ is formed by concatenating the independent latent vectors $\mathbf{z} = [z^{(1)}, z^{(2)}, \ldots, z^{(D)}]$.

C.2 Group-Sparse Decoder

The prediction for the target variable $x_t^{(d)}$ is generated by a dedicated decoder $D_\Theta^{(d)}$. To strictly enforce the Granger causal definition, the decoder models the mapping from the joint history $\mathbf{z}$ to the target distribution.

Linear Projection and Sparsification. The core of the causal discovery mechanism lies in the decoder heads. The input $\mathbf{z}$ is formed as a vector of size $D \times H$. The decoder applies a weight matrix $\mathbf{W}^{(d)} \in \mathbb{R}^{H_{out} \times (D \times H)}$:

$$\mathbf{u}^{(d)} = \mathbf{W}^{(d)}.\mathbf{z} + \mathbf{b}^{(d)}$$

The weight matrix $\mathbf{W}^{(d)}$ is structurally partitioned into D groups, where the j-th group $\mathbf{W}_{(j)}^{(i)} \in \mathbb{R}^{H_{out} \times H}$ corresponds to the weights multiplying the latent sub-vector $z^{(j)}$. The Group Lasso penalty (third component in Equation 2) operates on these blocks:

$$\mathcal{L}_{GL} = \lambda \sum_{i=1}^{D} \sum_{j=1}^{D} \|W_{(j)}^i\|_2$$

If $\|W_{(j)}^{(i)}\|_2 \to 0$, the decoder $D^{(i)}$ effectively ignores the information from variable j, implying $x^{(j)}$ does not Granger-cause $x^{(i)}$.

Probabilistic Output. The output of the linear projection maps to the parameters of the predictive distribution for the target variable:

$$\hat{x}_t^{(d)} \sim \mathcal{N}(\mu_{dec}^{(d)}, \sigma_{dec}^{2(d)}) = D_\Theta^{(d)}(\mathbf{z})$$

This formulation of multi-head decoder ensures that the only path for information to flow from variable j to variable i is through the specific weight group $W_{(j)}^i$. It makes the causal structure explicitly identifiable via the adaptive thresholding mechanism described in Algorithm 2.

D   Theoretical Proofs

In this section, we provide formal derivations for the propositions stated in Section 3 and Section 6. We rigorously show that shared latent encoders introduce irreducible confounding that violates the structural conditions required for Granger causal discovery and that our proposed CauFR-TS restores the necessary conditional independence.

D.1   Proof of Proposition 1

Consider the shared encoder mapping $f_\theta : \mathbb{R}^{\tau \times D} \to \mathbb{R}^H$. Let $\mathbf{X}_{t-}$ be the input history window. The latent vector is given by $z_t = f_\theta(\mathbf{X}_{t-})$. For the representation to be disentangled or factorized with respect to the input variables, each dimension of $\mathbf{z}_t$ must be sensitive to variations in only one specific input variable $x^{(p)}$. Formally, a specific latent dimension z_k is sensitive to an input variable $x^{(p)}$ if $\frac{\partial z_k}{\partial x^{(p)}} \neq 0$. For the representation to be disentangled, we require that the latent vector $\mathbf{z}_t$ can be sliced into disjoint groups $[z^{(1)}, z^{(2)}, \ldots, z^{(D)}]$ where slice $z^{(p)}$ is sensitive only to input $x^{(p)}$. Mathematically, this requires the Jacobian matrix $J = \frac{\partial \mathbf{z}_t}{\partial \mathbf{X}_{t-}}$ to have a block-diagonal or permutation-equivalent structure:

$$\frac{\partial z^{(p)}}{\partial x^{(q)}} = 0 \quad \text{for all } p \neq q$$

General Jacobian Structure. In standard neural architectures for sequential data, the operation at layer l typically takes the form:

$$h^{(l)} = \sigma(\mathbf{W}h^{(l-1)} + b)$$

where $\mathbf{W}$ is a dense weight matrix. For a shared encoder processing multivariate input $\mathbf{X}_{t-}$, the information flow mixes immediately. Let $x^{(j)}_{t-k}$ be the value of variable j at lag k. The sensitivity of the m-th latent dimension $z_{t,m}$ to this input is:

$$\frac{\partial z_{t,m}}{\partial x^{(j)}_{t-k}} \neq 0$$

Because f_θ is trained to minimize a global reconstruction loss, the optimizer utilizes any correlation in the data to compress the input. Thus, for a change in $x^{(p)}, \forall p, z_k$ changes. This effectively creates a confounding path between variables.

Entanglement Condition. Unless explicitly constrained, the mixing weights are non-zero almost everywhere. Thus, for any arbitrary latent coordinate $z_{t,m}$, we have:

$$z_{t,m} = g_m(x^{(1)}_{t-}, x^{(2)}_{t-}, \ldots, x^{(D)}_{t-})$$

where g_m depends non-trivially on multiple inputs.

Non-Decomposability. A valid causal decomposition requires finding sub-vectors $z^{(p)}$ such that $I(z^{(p)}; x^{(q)}_{t-}) = 0$ for all $q \neq p$. Since every coordinate $z_{t,m}$ is a function of the joint history, $H(z_{t,m}|x^{(p)}_{t-}) > 0$ if dependencies on other variables exist. Therefore, the mutual information $I(\mathbf{z}_t; x^{(q)}_{t-}) > 0$ for all q, and no subset of $\mathbf{z}_t$ isolates $x^{(p)}$ exclusively.

D.2   Proof of Proposition 2

Formulation of Causal Estimator. Consider the shared encoder mapping $f_\theta : \mathbb{R}^{\tau \times D} \to \mathbb{R}^H$. Let $\mathbf{X}_{t-}$ be the input history window. The latent vector is given by $z_t = f_\theta(\mathbf{X}_{t-})$. The prediction for the i-th target variable, $\hat{x}^{(i)}_t$, is generated by a decoder function $D^{(i)}_\Theta$ acting on this latent state:

$$\hat{x}^{(i)}_t = D^{(i)}_\Theta(z_t) = \mathbb{E}[x^{(i)}_t|z_t]$$

For a causal link $j \to i$ to be identified as non-existent or sparse, the model must exhibit invariance to the history of j when predicting i. Mathematically, this requires the gradient of the prediction with respect to the input $x_{t-}^{(j)}$ to be zero:

$$\frac{\partial \hat{x}_t^{(i)}}{\partial x_{t-}^{(j)}} = 0 \quad \text{if } j \notin PA(x^{(i)})$$

Decomposition of the Causal Gradient. We decompose the total sensitivity of the prediction into the product of the decoder's sensitivity to the latent space and the encoder's sensitivity to the input:

$$\frac{\partial \hat{x}_t^{(i)}}{\partial x_{t-}^{(j)}} = \underbrace{\left(\frac{\partial \hat{x}_t^{(i)}}{\partial z_t} \right)}_{\text{Decoder Term}} \cdot \underbrace{\left(\frac{\partial z_t}{\partial x_{t-}^{(j)}} \right)}_{\text{Encoder Term}} \tag{8}$$

Analysis of Encoder term. From Proposition 1, we established that a shared encoder minimizes the global reconstruction loss by compressing all available correlations into the latent capacity. For any arbitrary latent dimension $h \in \{1, \ldots, H\}$, he partial derivative with respect to any input channel j is non-zero almost everywhere:

$$\frac{\partial z_{t,h}}{\partial x_{t-}^{(j)}} \neq 0$$

This implies that a perturbation in the input $x_{t-}^{(j)}$ propagates to the entire latent vector z_t, shifting the manifold location for all dimensions.

Analysis of Decoder term. We assume that for any three dimensions or channels i, j, k, $j \nrightarrow i$ and $k \to i$. To minimize the prediction error for $x_t^{(i)}$, the decoder $D_\Theta^{(i)}$ must extract information about the true parent $x_{t-}^{(k)}$ from z_t. However, due to the entanglement in the shared encoder, the information regarding the true parent $x_{t-}^{(k)}$ and the non-parent $x_{t-}^{(j)}$ is mixed into the same latent dimensions. Let us assume a specific latent neuron $z_{t,h}$ encodes inputs as,

$$z_{t,h} \approx \sigma(w_j x_{t-}^{(j)} + w_k x_{t-}^{(k)})$$

To access the necessary signal from $x^{(k)}$, the decoder must assign a non-zero weight to $z_{t,h}$. Consequently, the gradient of the prediction with respect to that latent neuron is non-zero:

$$\frac{\partial \hat{x}_t^{(i)}}{\partial z_{t,h}} \neq 0$$

Finally, substituting the non-zero terms back into Equation 8, we get:

$$\frac{\partial \hat{x}_t^{(i)}}{\partial x_{t-}^{(j)}} \approx \sum_{h=1}^{H} \left(\frac{\partial \hat{x}_t^{(i)}}{\partial z_{t,h}} \right) \cdot \left(\frac{\partial z_{t,h}}{\partial x_{t-}^{(j)}} \right) \neq 0$$

Even though j has no physical causal influence on i, the shared representation creates an architectural confounder through the latent space that structurally couples the variables. Because the total gradient $\frac{\partial \hat{x}_t^{(i)}}{\partial x_{t-}^{(j)}}$ is non-zero, the model learns a functional dependence of $x^{(i)}$ on $x^{(j)}$. This violates the core condition of Granger Non-Causality, which requires that $P(x_t^{(i)} \mid X_{t-}) = P(x_t^{(i)} \mid X_{t-}^{j \notin PA(x^{(i)})})$. Thus, the causal graph derived from such a model is structurally non-identifiable.

D.3 Justification on Remark 1

Formulation of Factorized Estimator. Unlike the shared formulation in Proposition 2, CauFR-TS processes each input dimension $k \in \{1, \ldots, D\}$ via an independent encoder $E_\phi^{(k)}$. The latent representation for variable k is conditioned exclusively on its own history:

$$z_t^{(k)} = E_\Phi^{(k)}(x_{t-}^{(k)})$$

The global latent state z_t is constructed via concatenating all the embeddings from the Encoder heads as $z_t = [z_t^{(1)}, z_t^{(2)}, \ldots, z_t^{(D)}]$. The prediction for a target variable i is generated by a channel-specific decoder $D_\theta^{(i)}$, which takes the global state z_t as input:

$$\hat{x}_t^{(i)} = D_\Theta^{(i)}(z_t) = D_\theta^{(i)}([z_t^{(1)}, \ldots, z_t^{(D)}])$$

Analysis of the Jacobian Structure. The global Jacobian $\frac{\partial z_t}{\partial X_{t-}}$ describes how every latent component changes with every input. Because the encoder $E_\Phi^{(k)}$ does not receive inputs from any variable $j \neq k$, the below expression holds true:

$$\frac{\partial z_t^{(k)}}{\partial x_{t-}^{(j)}} = \begin{cases} J_k & \text{if } k = j \\ \mathbf{0} & \text{if } k \neq j \end{cases} \tag{9}$$

This makes the Jacobian for the encoder strictly block-diagonal, fundamentally distinct from the dense Jacobian of the shared encoder derived in Proposition 1.

Collapsing Spurious Paths. To determine if source j Granger-causes target i, we evaluate the total sensitivity of the prediction $\hat{x}_t^{(i)}$ to the input history $x_{t-}^{(j)}$:

$$\frac{\partial \hat{x}_t^{(i)}}{\partial x_{t-}^{(j)}} = \sum_{k=1}^{D} \underbrace{\left(\frac{\partial \hat{x}_t^{(i)}}{\partial z_t^{(k)}} \right)}_{\text{Path via } z^{(k)}} \cdot \underbrace{\left(\frac{\partial z_t^{(k)}}{\partial x_{t-}^{(j)}} \right)}_{\text{Sensitivity of } z^{(k)}} \tag{10}$$

For any path where $k \neq j$, the term $\frac{\partial z_t^{(k)}}{\partial x_{t-}^{(j)}}$ is zero. This means the history of variable j cannot mix into the latent code of variable k. Therefore, the only non-zero term is the term where $k = j$. Substituting the block-diagonal property (Equation 9) into Equation 10, it collapses into a single causal path:

$$\frac{\partial \hat{x}_t^{(i)}}{\partial x_{t-}^{(j)}} = \frac{\partial \hat{x}_t^{(i)}}{\partial z_t^{(j)}} \cdot \frac{\partial z_t^{(j)}}{\partial x_{t-}^{(j)}} \tag{11}$$

This shows that the influence of $x^{(j)}$ on $x^{(i)}$ is mediated exclusively by the specific latent vector $z^{(j)}$. It effectively blocks all backdoor paths through other latent dimensions that existed in the shared architecture.

Role of the Group-Sparse Decoder. The term $\frac{\partial \hat{x}_t^{(i)}}{\partial z_t^{(j)}}$ represents the sensitivity of the i-th decoder to the j-th latent code. In our proposed CauFR-TS, this sensitivity is parameterized linearly by the weight group $\mathbf{W}_{(j)}^i$:

$$\frac{\partial \hat{x}_t^{(i)}}{\partial z_t^{(j)}} \propto \mathbf{W}_{(j)}^i$$

The objective function (Equation 2) applies a Group Lasso penalty to drive $||\mathbf{W}_{(j)}^i||_2 \to 0$ for non-causal pairs. During the optimization, if $\mathbf{W}_{(j)}^i$ becomes 0, then $\frac{\partial \hat{x}_t^{(i)}}{\partial z_t^{(j)}} = 0$. Therefore, this forces the total gradient $\frac{\partial \hat{x}_t^{(i)}}{\partial x_{t-}^{(j)}} = 0$ in Equation 11. If $\mathbf{W}_{(j)}^i \neq 0$, the gradient remains non-zero.

To summarize, the factorization ensures that the condition $\frac{\partial \hat{x}_t^{(i)}}{\partial x_{t-}^{(j)}} \neq 0$ is mathematically equivalent to $\mathbf{W}_{(j)}^i \neq 0$. This guarantees that the inferred adjacency matrix $\hat{A}$ accurately reflects the true conditional dependence structure of the data, thereby fulfilling the requirements of structural identifiability.

E   Evaluation Metrics

Here we provide a brief description and equations of the quantitative evaluation metrics we have used in our work.

Area under Receiver Operating Characteristic curve (AUROC). The Receiver Operating Characteristic (ROC) curve is a graphical representation that plots the True Positive Rate (TPR) against the False Positive Rate (FPR) at different threshold values. The AUROC represents the area under this curve, providing a single scalar value that summarizes the model's performance. The AUC ranges from 0 to 1, where, an AUC of 0.5 indicates no discriminative ability and an AUC of 1.0 indicates perfect discrimination between classes. It can be mathematically represented as shown in Equation 12.

$$\text{AUROC} = \sum_{i=1}^{N} (\text{FPR}_i - \text{FPR}_{i-1}).\text{TPR} \tag{12}$$

where TPR and FPR stand for True Positive Rate and False Positive Rate, respectively, and they can be given as follows:

$$\text{TPR} = \frac{\#\text{True Positives}}{\#\text{True Positives} + \#\text{False Negatives}}$$

$$\text{FPR} = \frac{\#\text{False Positives}}{\#\text{False Positives} + \#\text{True Negatives}}$$

We use the AUROC score as a quantitative indicator while assessing the calculated causal adjacency matrices by comparing them to the ground truth. The numerical results have been given in the main manuscript.

F1-score. While AUROC assesses the global ranking quality of the learned interaction strengths, it does not evaluate the final recovered causal structure requiring a discrete decision boundary. We employ the F1-score in order to evaluate the quality of the binary causal graph $\hat{A}$. This metric is particularly critical in our setting to validate the effectiveness of the proposed adaptive thresholding strategy described in Section 4.3. Given the ground truth binary adjacency matrix $A \in \{0,1\}^{D \times D}$ and the estimated binary matrix $\hat{A} \in \{0,1\}^{D \times D}$ obtained after thresholding the decoder weights, the F1-score is calculated as:

$$\text{F1} = 2 \cdot \frac{\text{Precision} \cdot \text{Recall}}{\text{Precision} + \text{Recall}} \tag{13}$$

where $\text{Precision} = \frac{\text{TP}}{\text{TP+FP}}$ and $\text{Recall} = \frac{\text{TP}}{\text{TP+FN}}$. We define the constituent counts as:

- True Positives (TP): The number of correctly identified causal links (i,j) such that $\hat{A}_{ij} = 1$ and $A_{ij} = 1$.

- False Positives (FP): The number of identified spurious links (i,j) such that $\hat{A}_{ij} = 1$ and $A_{ij} = 0$.

- False Negatives (FN): The number of missed causal links (i,j) such that $\hat{A}_{ij} = 0$ and $A_{ij} = 1$.

An F1-score of 1.0 indicates perfect reconstruction of the causal skeleton, whereas lower scores reflect a trade-off between missing true edges and hallucinating spurious ones.

Structural Hamming Distance (SHD). To quantify the absolute topological discrepancy between the estimated graph and the ground truth, we utilize the Structural Hamming Distance (SHD). Unlike the F1-score, SHD provides a direct count of the structural errors, specifically the number of edge insertions, deletions, or reversals required to transform the estimated graph $\hat{A}$ into the true graph A. SHD is formally defined as the ℓ_0 norm of the difference between the adjacency matrices of the ground truth and the retrieved causal graph:

$$\text{SHD}(A, \hat{A}) = \sum_{i=1}^{D} \sum_{j=1}^{D} \mathbb{I}(\hat{A}_{ij} \neq A_{ij}) \tag{14}$$

where $\mathbb{I}(\cdot)$ is the indicator function. A value of $\text{SHD} = 0$ implies that the recovered graph is isomorphic to the ground truth. This metric is particularly sensitive to the density of the graph. Therefore, we consider it alongside AUROC and F1-score to provide a comprehensive view of identifiability.

Figure 4: Evolution of learned interaction strengths during training on the Hénon (4a-4j) and Lorenz-96 (4k-4t) dynamical systems. The blue trajectories representing ground-truth causal parents exhibit varying degrees of magnitude but consistently separate from the yellow ones presenting non-causal variables. Black curve represents the evolution of the adaptive threshold at every iteration, which can also be seen getting stabilized. The vertical dashed green line marks the epoch with the minimum validation loss, which is selected as the optimal checkpoint for final graph inference.

F   Additional Results and Discussions

F.1   Convergence Analysis and Plots

To empirically validate the optimization dynamics of CauFR-TS, we analyze the evolution of the learned decoder weights and the stability of the proposed adaptive thresholding mechanism throughout the training process. Figures 4 and 5 illustrate the trajectory of the raw Granger Causal (GC) values, specifically , the ℓ_2-norms of the decoder weight groups $||W_{(j)}^i||_2$, across 10 dimensions of the four chosen datasets over all the training epochs.

Separation of Causal and Non-Causal Mechanisms.   The plots in Figures 4 and 5 demonstrate the creation of a distinct separation between the weights associated with true causal parents and those associated with non-causal variables towards the end. The weights corresponding to ground-truth causal links showed a rapid ascent at the beginning, subsequently stabilizing at significant magnitudes. This confirms that the factorized encoder-decoder architecture successfully captures the underlying dependency structure and is capable of assigning high predictive importance to the true drivers of the target variable. Conversely, the weights corresponding to non-causal inputs are progressively suppressed towards zero. This behavior empirically verifies the effectiveness of the Group Lasso penalty term $\lambda \sum ||W_{(j)}^i||_2$ in Equation 2

Figure 5: Convergence dynamics of causal discovery on the in silico *E. coli* (5a-5j) and Yeast (5k-5t) gene regulatory benchmarks. Similar to the synthetic experiments, the model successfully disentangles true regulatory interactions (blue) from spurious correlations (yellow). Except for some of the dimensions, the adaptive threshold (black) effectively delineates the causal mechanism despite the higher complexity and noise inherent in biological simulations. The vertical dashed green line marks the epoch with the minimum validation loss, which is selected as the optimal checkpoint for final graph inference.

objective function. Therefore, it enforces the necessary sparsity required for Granger causal identification.

Dynamics of Adaptive Thresholding. A critical contribution of our framework is the unsupervised selection of the decision boundary τ^*. Instead of a predefined static threshold, τ^* dynamically adjusts to the changing empirical distribution of the learned weights. As the training progresses and the bimodal distributions diverge, τ^* settles into a stable region that effectively separates the two modes. These visualizations confirm that our thresholding strategy provides a robust, data-driven alternative to heuristic cutoffs, ensuring that the final adjacency matrix $\hat{A}$ accurately reflects the structural independence assumptions of the ICM principle.

F.2 Qualitative Analysis of Causal Graph Estimation

we provide a qualitative visualization of causal graph recovery for all four datasets. For each dataset, we present three matrices: the ground-truth causal adjacency matrix, the estimated raw causal matrix obtained from the learned group-lasso decoder weights prior to thresholding, and the final binary causal graph after applying the proposed adaptive thresholding procedure. The raw causal matrices show that the learned interaction strengths concentrate around the true causal structure. The low-magnitude spurious connections are removed via adaptive thresholding. For the synthetic datasets, the proposed method successfully

(a) Hénon GC True (b) Hénon GC Raw (c) Hénon GC Estimated (d) Lorenz-96 GC True (e) Lorenz-96 GC Raw (f) Lorenz GC Estimated

(g) *E. coli* GC True (h) *E. coli* GC Raw (i) *E. coli* GC Estimated (j) Yeast GC True (k) Yeast GC Raw (l) Yeast GC Estimated

Figure 6: Qualitative visualization of causal graph recovery across all four datasets. For each dataset, we show the ground-truth causal adjacency matrix (left), the estimated raw causal matrix derived from decoder weight norms before thresholding (middle), and the final binary causal graph obtained after applying the proposed adaptive thresholding strategy (right).

recovers the underlying causal graphs with minimal structural error. In contrast, for the in silico biological benchmarks, the recovered graphs exhibit a small number of false positives and false negatives. This behaviour is expected due to measurement noise and the complex, partially overlapping regulatory mechanisms that characterize biological systems. For the Yeast dataset, several causal links are expressed through weak interaction strengths. The adaptive thresholding mechanism successfully recovers these links by separating weak but consistent causal signals from noise. Overall, these visualizations highlight the role of adaptive thresholding and representation-level modularity in producing stable and interpretable causal graphs across diverse dynamical regimes.

G Implementation setup

The whole system has been implemented in PyTorch v2.4.0 with support for CUDA v12.5 and trained on a single NVIDIA RTX 3050 Pro GPU with 35GB VRAM. We have chosen Transformer Vaswani et al. (2017) for implementing the encoder heads of the main causal recurrent model. We have set the values of β and λ as 0.05 and 0.1, respectively. For AdamW optimizer, we keep the default values of hyperparameters as implemented in PyTorch v2.4.0. The maximum number of epochs is 2000, and the learning rate γ has been set at 0.001. Additionally, we have incorporated early stopping regularization based on the validation loss, which stops the training if the validation loss does not decrease for 200 consecutive epochs.