MIRA: Mental Imagery for Robotic Affordances

Abstract: Humans form mental images of 3D scenes to support counterfactual imagination, planning, and motor control. Our abilities to predict the appearance and affordance of the scene from previously unobserved viewpoints aid us in performing manipulation tasks (e.g., 6-DoF kitting) with a level of ease that is currently out of reach for existing robot learning frameworks. In this work, we aim to build artificial systems that can analogously plan actions on top of imagined images. To this end, we introduce Mental Imagery for Robotic Affordances (MIRA), an action reasoning framework that optimizes actions with novel-view synthesis and affordance prediction in the loop. Given a set of 2D RGB images, MIRA builds a consistent 3D scene representation, through which we synthesize novel orthographic views amenable to pixel-wise affordances prediction for action optimization. We illustrate how this optimization process enables us to generalize to unseen out-of-plane rotations for 6-DoF robotic manipulation tasks given a limited number of demonstrations, paving the way toward machines that autonomously learn to understand the world around them for planning actions.

Keywords: Neural Radiance Fields, Rearrangement, Robotic Manipulation

1 Introduction

Suppose you are shown a small, unfamiliar object and asked if it could fit through an M-shaped slot. How might you solve this task? One approach would be to "rotate" the object in your mind's eye and see if, from some particular angle, the object's profile fits into an M. To put the object through the slot would then just require orienting it to that particular imagined angle. In their famous experiments on "mental rotation", Shepard & Metzler argued that this is the approach humans use when reasoning about the relative poses of novel shapes [1]. Decades of work in psychology have documented numerous other ways that "mental images", i.e. pictures in our heads, can aid human cognition [2]. In this paper, we ask: can we give robots a similar ability, where they use mental imagery to aid their spatial reasoning?

Fortunately, the generic ability to perform imagined translations and rotations of a scene, also known as *novel view synthesis*, has seen a recent explosion of research in the computer vision and graphics community [3, 4, 5]. Our work builds in particular upon Neural Radiance Fields (NeRFs) [6], which can render what a scene would look like from any camera pose. We treat a NeRF as a robot's "mind's eye", a virtual camera it may use to imagine how the scene would look were the robot to reposition itself. We couple this ability with an affordance model [7], which predicts, from any given view of the scene, what actions are currently afforded. Then the robot must just search, in its imagination, for the mental image that best affords the action it wishes to execute, then execute the action corresponding to that mental image.

We test this framework on 6-DoF rearrangement tasks [8], where the affordance model simply predicts, for each pixel in a given camera view, what is the action value of picking (or placing) at that pixel's coordinates. Using NeRF as a virtual camera for this task has several advantages over prior works which used physical cameras:

- **Out-of-plane rotation.** Prior works have applied affordance maps to 2-dimensional top-down camera views, allowing only the selection of top-down picking and placing actions [7, 9, 10]. We instead

Figure 1: Overview of MIRA. (a) Given a set of multi-view RGB images as input, we optimize a neural radiance field representation of the scene via volume rendering with perspective ray casting. (b) After the NeRF is optimized, we perform volume rendering with orthographic ray casting to render the scene from V viewpoints. (c) The rendered orthographic images are fed into the policy for predicting pixel-wise action-values that correlate with picking and placing success. (d) The pixel with the highest action-value is selected, and its estimated depth and associated view orientation are used to parameterize the robot's motion primitive.

formulate the pick and place problem as an action optimization process that searches across different novel synthesized views and their affordances of the scene. We demonstrate that this optimization process can handle the multi-modality of picking and placing while naturally supporting actions that involve out-of-plane rotations.

- **Orthographic ray casting.** A NeRF trained with images from consumer cameras can be used to synthesize novel views from *novel kinds of cameras* that are more suitable to action reasoning. Most physical cameras use perspective projection, in which the apparent size of an object in the image plane is inversely proportional to that object's distance from the camera — a relationship that any vision algorithm must comprehend and disentangle. NeRF can instead create images under other rendering procedures; we show that orthographic ray casting is particularly useful, which corresponds to a non-physical "camera" that is infinitely large and infinitely distant from the scene. This yields images in which an object's size in the image plane is invariant to its distance from the camera, and its appearance is equivariant with respect to translation parallel to the image plane. In essence, this novel usage of NeRF allows us to generate "blueprints" for the scene that complement the inductive biases of algorithms that encode translational equivariance (such as ConvNets).

- **RGB-only.** Prior rearrangement methods [11, 12, 13] commonly require 3D sensors (e.g. via structured light, stereo, or time-of-flight), and these are error-prone when objects contain thin structures or are composed of specular or semi-transparent materials—a common occurrence. These limitations drastically restrict the set of tasks, objects, and surfaces these prior works can reason over.

We term our method Mental Imagery for Robotic Affordances, or MIRA. To test MIRA, we perform experiments in both simulation and the real world. For simulation, we extend the Ravens [9] benchmark to include tasks that require 6-DoF actions. Our model demonstrates superior performance to existing state-of-the-art methods for object rearrangement [14, 9], despite not requiring depth sensors. Importantly, the optimization process with novel view synthesis and affordance prediction in the loop enables our framework to generalize to out-of-distribution object configurations, where the baselines struggle. In summary, we contribute (i) a framework that uses NeRFs as the scene representation to perform novel view synthesis for precise object rearrangement, (ii) an orthographic ray casting procedure for NeRFs rendering that facilitates the policy's translation equivariance, (iii) an extended benchmark of 6-DoF manipulation tasks in Ravens [9], and (iv) empirical results on a broad range of manipulation tasks, validated with real-robot experiments.

2   Related Works

2.1   Vision-based Manipulation.

Object-centric.   Classical methods in visual perception for robotic manipulation mainly focus on representing instances with 6-DoF poses [15, 16, 17, 18, 19, 20, 21]. However, 6-DoF poses cannot represent the states of deformable objects or granular media, and cannot capture large intra-category variations of unseen instances [11]. Alternative methods that represent objects with dense descriptors [22, 23, 24] or keypoints [11, 25, 26, 27] improve generalization, but they require a dedicated data collection procedure (e.g., configuring scenes with single objects).

Action-centric.   Recent methods based on end-to-end learning directly predict actions given visual observations [28, 29, 30, 31, 32, 33]. These methods can potentially work with deformable objects or granular media, and do not require any object-specific data collection procedures. However, these methods are known to be sample inefficient and challenging to debug. Recently, several works [9, 13, 34, 35, 36, 37, 38] have proposed to incorporate spatial structure into action reasoning for improved performance and better sample efficiency. Among them, the closest work to ours is Song et al. [13] which relies on view synthesis to plan 6-DoF picking. Our work differs in that it 1) uses NeRF whereas [13] uses TSDF [39], 2) does not require depth sensors, 3) uses orthographic image representation, 4) does not directly use the camera pose as actions, and 5) shows results on rearrangement tasks that require both picking and placing.

2.2   Neural Fields for Robotics

Neural fields have emerged as a promising tool to represent 2D images [40], 3D geometry [41, 42], appearance [6, 43, 44], touch [45], and audio [46, 47]. They offer several advantages over classic representations (e.g., voxels, point clouds, and meshes) including reconstruction quality, and memory efficiency. Several works have explored the usage of neural fields for robotic applications including localization [48, 49], SLAM [50, 51, 52], navigation [53], dynamics modeling [54, 55, 56, 57], and reinforcement learning [58]. For robotic manipulation, GIGA [59] jointly trains a grasping network and an occupancy network for synergy. Dex-NeRF [60] infers the geometry of transparent objects with NeRF and determines the grasp poses with Dex-Net [30]. NDF [12] uses the features of occupancy networks [42] as object descriptors for few-shot imitation learning. NeRF-Supervision [61] uses NeRF as a dataset generator to learn dense object descriptors for picking.

3   Method

Our goal is to predict actions a_t, given RGB-only visual observations o_t, and trained from only a limited number of demonstrations. We parameterize our action space with two-pose primitives $a_t = (\mathcal{T}_{\text{pick}}, \mathcal{T}_{\text{place}})$, which are able to flexibly parameterize rearrangement tasks [9]. This problem is challenging due to the high degrees of freedom of a_t (12 degrees of freedom for two full SE(3) poses), a lack of information about the underlying object state (such as object poses), and limited data. Our method (illustrated in Fig. 1) factorizes action reasoning into two modules: 1) a continuous neural radiance field that can synthesize virtual views of the scene at novel viewpoints, and 2) an optimization procedure which optimizes actions by predicting per-pixel affordances across different synthesized virtual pixels. We discuss these two modules in Sec. 3.1 and Sec. 3.2 respectively, followed by training details in Sec. 3.3.

3.1   Scene Representation with Neural Radiance Field

To provide high-fidelity novel-view synthesis of virtual cameras, we represent the scene with a neural radiance field (NeRF) [6]. For our purposes, a key feature of NeRF is that it *renders individual rays (pixels) rather than whole images*, which enables flexible parameterization of rendering at inference time, including camera models that are non-physical (e.g., orthographic cameras) and not provided in the training set.

To render a pixel, NeRF casts a ray $\mathbf{r}(t) = \mathbf{o} + t\mathbf{d}$ from some origin $\mathbf{o}$ along the direction $\mathbf{d}$ passing through that pixel on an image plane. In particular, these rays are casted into a field F_Θ whose input is a 3D location

| (a) 3D scene | (b) Perspective ray casting | (c) Orthographic ray casting |

Figure 2: Perspective vs. Orthographic Ray Casting. (a) A 3D world showing two objects, with the camera located at the top. (b) The procedure of perspective ray casting and a perspective rendering of the scene. The nearby object is large, the distant object is small, and both objects appear "tilted" according to their position. (c) The procedure of orthographic ray casting and an orthographic rendering of the scene, which does not correspond to any real consumer camera, wherein the size and appearance of both objects are invariant to their distances and equivariant to their locations. By using NeRF to synthesize these orthographic images, which correspond to non-physical cameras, we are able to construct RGB inputs that are equivariant with translation.

$\mathbf{x} = (x, y, z)$ and unit-norm viewing direction $\mathbf{d}$, and whose output is an emitted color $c = (r, g, b)$ and volume density σ. Along each ray, K discrete points $\{\mathbf{x}_k = \mathbf{r}(t_k)\}_{k=1}^{K}$ are sampled for use as input to F_Θ, which outputs a set of densities and colors $\{\sigma_k, \mathbf{c}_k\}_{k=1}^{K} = \{F_\Theta(\mathbf{x}_k, \mathbf{d})\}_{k=1}^{K}$. Volume rendering [62] with a numerical quadrature approximation [63] is performed using these values to produce the color $\hat{\mathbf{C}}(\mathbf{r})$ of that pixel:

$$\hat{\mathbf{C}}(\mathbf{r}) = \sum_{k=1}^{K} T_k \left(1 - \exp\left(-\sigma_k (t_{k+1} - t_k) \right) \right) \mathbf{c}_k, \quad T_k = \exp\left(-\sum_{k' < k} \sigma_{k'} (t_{k'+1} - t_{k'}) \right). \tag{1}$$

where T_k represents the probability that the ray successfully transmits to point $\mathbf{r}(t_k)$. At the beginning of each pick-and-place, our system takes multi-view posed RGB images as input and optimizes Θ by minimizing a photometric loss $\mathcal{L}_{\text{photo}} = \sum_{\mathbf{r} \in \mathcal{R}} \|\hat{\mathbf{C}}(\mathbf{r}) - \mathbf{C}(\mathbf{r})\|_2^2$, using some sampled set of rays $\mathbf{r} \in \mathcal{R}$, where $\mathbf{C}(\mathbf{r})$ is the observed RGB value of the pixel corresponding to ray $\mathbf{r}$ in an input image. In practice, we use instant-NGP [64] to accelerate NeRF training and inference.

Orthographic Ray Casting. In Fig. 2 we illustrate the difference between perspective and orthographic cameras. Though renderings from a NeRF F_Θ are highly realistic, the perspective ray casting procedure used by default in NeRF's volume rendering, which we visualize in Fig. 2(b), may cause scene content to appear distorted or scaled depending on the viewing angle and the camera's field of view — more distant objects will appear smaller in the image plane. Specifically, given a pixel coordinate (u, v) and camera pose $(\mathbf{R}, \mathbf{t})$, NeRF forms a ray $\mathbf{r} = (\mathbf{o}, \mathbf{d})$ using the perspective camera model:

$$\mathbf{o} = \mathbf{t}, \qquad \mathbf{d} = \mathbf{R} \begin{bmatrix} (u - c_x)/f_x \\ (v - c_y)/f_y \\ 1 \end{bmatrix}. \tag{2}$$

This model is a reasonable proxy for the geometry of most consumer RGB cameras, hence its use by NeRF during training and evaluation. However, the distortion and scaling effects caused by perspective ray casting degrades the performance of the downstream optimization procedure that takes as input the synthesized images rendered by NeRF, as we will demonstrate in our results (Sec. 4.1). To address this issue, we modify the rendering procedure of NeRF after it is optimized by replacing perspective ray casting with orthographic ray casting:

$$\mathbf{o} = \mathbf{t} + \mathbf{R} \begin{bmatrix} (u - c_x)/f_x \\ (v - c_y)/f_y \\ 0 \end{bmatrix}, \qquad \mathbf{d} = \mathbf{R} \begin{bmatrix} 0 \\ 0 \\ 1 \end{bmatrix}. \tag{3}$$

We visualize this procedure in Fig. 2(c). Orthographic ray casting marches parallel rays into the scene, so that each rendered pixel represents a parallel window of 3D space. This property removes the dependence between an object's appearance and its distance to the camera: an object looks the same if it is either far

137 or nearby. Further, as all rays for a given camera rotation $\mathbf{R}$ are parallel, this provides equivariance to the
138 in-plane camera center c_x, c_y. These attributes facilitate downstream learning to be equivariant to objects'
139 3D locations and thereby encourages generalization. As open-source instant-NGP [64] did not support
140 orthographic projection, we implement this ourselves as a CUDA kernel (see Supp.).

141 Our decision of choosing an orthographic view of the scene draws inspiration from previous works that
142 have used single-view orthographic scene representations [16, 9], but critically differs in the following
143 two aspects: (a) we create orthographic scene representations by casting rays into a radiance field rather
144 than by point-cloud reprojection, thereby significantly reducing image artifacts (see Supp.); (b) we rely
145 on multi-view RGB images to recover scene geometry, instead of depth sensors.

3.2 Policy Representation: Affordance Raycasts in a Radiance Field

147 To address $SE(3)$-parameterized actions, we formulate action selection as an optimization problem over
148 synthesized novel-view pixels and their affordances. Using our NeRF-based scene representation, we
149 densely sample V camera poses around the workspace and render images $\hat{I}_{v_t} = F_\Theta(\mathcal{T}_{v_t})$ for each pose,
150 $\forall v_t = 0, 1, \cdots, V$. One valid approach is to search for actions directly in the space of camera poses for
151 the best $\mathcal{T}_{v_t}$, but orders of magnitude computation may be saved by instead considering actions that
152 correspond to *each pixel* within each image, and sharing computation between all pixels in the image
153 (e.g., by processing each image with just a single pass through a ConvNet). This (i) extends the paradigm
154 of pixel-wise affordances [7] into full 6-DOF, novel-view-enabled action spaces, and (ii) alleviates the
155 search over poses due to translational equivariance provided by orthographic rendering (Sec. 3.1).

156 Accordingly, we formulate each pixel in each synthesized view as parameterizing a robot action, and
157 we learn a dense action-value function E which outputs per-pixel action values of shape $\mathbb{R}^{H \times W}$ given
158 a novel-view image of shape $\mathbb{R}^{H \times W \times 3}$. Actions are selected by simultaneously searching across all pixels
159 $\mathbf{u}$ in all synthesized views v_t:

$$\mathbf{u}_t^*, v_t^* = \underset{\mathbf{u}_t, v_t}{\arg\min}\, E(\hat{I}_{v_t}, \mathbf{u}_t), \quad \forall v_t = 0, 1, \cdots, V \tag{4}$$

160 where the pixel $\mathbf{u}_t^*$ and the associated estimated depth $d(\mathbf{u}_t^*)$ from NeRF are used to determine the 3D
161 translation, and the orientation of $\mathcal{T}_{v_t^*}$ is used to determine the 3D rotation of the predicted action. Our
162 approach employs multiple strategies for equivariance: 3D translational equivariance is in part enabled
163 by orthographic raycasting and synergizes well with translationally-equivariant dense model architectures
164 for E such as ConvNets [65, 66], meanwhile 3D rotational equivariance is also encouraged, as synthesized
165 rotated views can densely cover novel orientations of objects.

166 While the formulation above may be used to predict the picking pose $\mathcal{T}_{\text{pick}}$ and the placing pose $\mathcal{T}_{\text{place}}$
167 independently, intuitively the prediction of $\mathcal{T}_{\text{pick}}$ affects the prediction of $\mathcal{T}_{\text{place}}$ due to the latter's geometric
168 dependence on the former. We therefore decompose the action-value function into (i) picking and (ii)
169 pick-conditioned placing, similar to prior work [9]:

$$\mathbf{u}_{\text{pick}}^*, v_{\text{pick}}^* = \underset{\mathbf{u}_{\text{pick}}, v_{\text{pick}}}{\arg\min}\, E_{\text{pick}}(\hat{I}_{v_{\text{pick}}}, \mathbf{u}_{\text{pick}}), \qquad \forall v_{\text{pick}} = 0, 1, \cdots, V \tag{5}$$

$$\mathbf{u}_{\text{place}}^*, v_{\text{place}}^* = \underset{\mathbf{u}_{\text{place}}, v_{\text{place}}}{\arg\min}\, E_{\text{place}}(\hat{I}_{v_{\text{place}}}, \mathbf{u}_{\text{place}} | \mathbf{u}_{\text{pick}}^*, v_{\text{pick}}^*), \qquad \forall v_{\text{place}} = 0, 1, \cdots, V \tag{6}$$

170 where E_{place} uses the Transport operation from Zeng et al. [9] to convolve the feature map of $\hat{I}_{v_{\text{pick}}^*}$ around
171 $\mathbf{u}_{\text{pick}}^*$ with the feature maps of $\{\hat{I}_{v_{\text{place}}}\}_{v_{\text{place}}=1}^V$ for action-value prediction. We refer readers to [9] for details
172 on this coupling.

3.3 Training

174 We train the action-value function as an energy-based model (EBM) [67, 68, 69]. For each expert
175 demonstration, we construct a tuple $\mathcal{D} = \{\hat{I}_{v_{\text{pick}}^*}, \mathbf{u}_{\text{pick}}^*, \hat{I}_{v_{\text{place}}^*}, \mathbf{u}_{\text{place}}^*\}$, where $\hat{I}_{v_{\text{pick}}^*}$ and $\hat{I}_{v_{\text{place}}^*}$ are the synthesized
176 images whose viewing directions are aligned with the end-effector's rotations; $\mathbf{u}_{\text{pick}}^*$ and $\mathbf{u}_{\text{place}}^*$ are the
177 best pixels in those views annotated by experts. We use a Monte-Carlo log-likelihood training objective

Figure 3: Simulation qualitative results. MIRA only requires RGB inputs and can solve different 6-DoF tasks: (a) hanging-disks, (b) place-red-in-green, (c) stacking-objects, and (d) block-insertion.

Task	precise placing	multi-modal placing	distractors	unseen colors	unseen objects
block-insertion	✓	✗	✗	✗	✗
place-red-in-green	✗	✓	✓	✗	✗
hanging-disks	✓	✗	✗	✓	✗
stacking-objects	✓	✗	✗	✗	✓

Table 1: Simulation tasks. We extend Ravens [9] with four new 6-DoF tasks and summarize their associated challenges.

[70], where we draw pixels $\{\hat{\mathbf{u}}_j | \hat{\mathbf{u}}_j \neq \mathbf{u}^*_{\text{pick}}, \hat{\mathbf{u}}_j \neq \mathbf{u}^*_{\text{place}}\}_{j=1}^{N_{\text{neg}}}$ from randomly synthesized images $\hat{I}_{\text{neg}}$ as negative samples. For brevity, we omit the subscript for pick and place and present the loss function that is used to train both action-value functions:

$$\mathcal{L}(\mathcal{D}) = -\log p\Big(\mathbf{u}^* | \hat{I}, \hat{I}_{\text{neg}}, \{\hat{\mathbf{u}}_j\}_{j=1}^{N_{\text{neg}}}\Big), \quad p\Big(\mathbf{u}^* | \hat{I}, \hat{I}_{\text{neg}}, \{\hat{\mathbf{u}}_j\}_{j=1}^{N_{\text{neg}}}\Big) = \frac{e^{-E_\theta(\hat{I}, \mathbf{u})}}{e^{-E_\theta(\hat{I}, \mathbf{u})} + \sum_{j=1}^{N_{\text{neg}}} e^{-E_\theta(\hat{I}_{\text{neg}}, \hat{\mathbf{u}}_j)}} \quad (7)$$

A key innovation of our objective function compared to previous works [9, 10, 36, 71] is the inclusion of negative samples $\{\hat{\mathbf{u}}_j\}_{j=1}^{N_{\text{neg}}}$ from imagined views $\hat{I}_{\text{neg}}$. We study the effects of ablating negative samples in Sec. 4.1 and show that they are essential for successfully training action-value functions.

4 Results

We execute experiments in both simulation and real-world settings to evaluate the proposed method across various tasks.

4.1 Simulation Experiments

Environment. We propose four new 6-DoF tasks based on Ravens [9] and use them as the benchmark. We show qualitative examples of these tasks in Fig. 3 and summarize their associated challenges in Table 1. All simulated experiments are conducted in PyBullet [72] using a Universal Robot UR5e with a suction gripper. The input observations for MIRA are 30 RGB images from different cameras pointing toward the center. For all the baselines, we additionally supply the corresponding noiseless depth images. Each image has a resolution of 640×480. The camera has focal length $f = 450$ and camera center $(c_x, c_y) = (320, 240)$.

Evaluation. For each task, we perform evaluations under two settings: *in-distribution* configures objects with random rotations ($\theta_x, \theta_y \in [-\frac{\pi}{6}, \frac{\pi}{6}], \theta_z \in [-\pi, \pi]$). This is also the distribution we used to construct the training set. *out-of-distribution* instead configures objects with random rotations ($\theta_x, \theta_y \in [-\frac{\pi}{4}, -\frac{\pi}{6}] \cup [\frac{\pi}{6}, \frac{\pi}{4}], \theta_z \in [-\pi, \pi]$). We note that these rotations are outside the training distribution and also correspond to larger out-of-plane rotations. Thus, this setting requires stronger generalization. We use a binary score (0 for failure and 1 for success) and report results on 100 evaluation runs for agents trained with $n = 1, 10, 100$ demonstrations.

Baseline Methods. Although our method only requires RGB images, we benchmark against published baselines that additionally require depth images as inputs. Form2Fit [14] predicts the placing action by estimating dense descriptors of the scene for geometric matching. Transporter-*SE*(2) and Transporter-*SE*(3) are both introduced in Zeng et al. [9]. Although Transporter-*SE*(2) is not designed to solve manipulation tasks that require 6-DoF actions, its inclusion helps indicate what level of task success can be achieved on the shown tasks by simply ignoring out-of-plane rotations. Transporter-*SE*(3) predicts 6-DoF actions

by first using Transporter-$SE(2)$ to estimate $SE(2)$ actions, and then feeding them into a regression model to predict the remaining rotational (r_x, r_y) and translational (z-height) degrees of freedom. Additionally, we benchmark against a baseline, GT-State MLP, that assumes perfect object poses. It takes ground truth state (object poses) as inputs and trains an MLP to regress two $SE(3)$ poses for $\mathcal{T}_{\text{pick}}$ and $\mathcal{T}_{\text{place}}$.

Method	block-insertion in-distribution-poses			block-insertion out-of-distribution-poses			place-red-in-greens in-distribution-poses			place-red-in-greens out-of-distribution-poses		
	1	10	100	1	10	100	1	10	100	1	10	100
GT-State MLP	0	1	1	0	0	1	0	1	3	0	1	1
Form2Fit [14]	0	1	10	0	0	0	**35**	79	**96**	21	30	61
Transporter-$SE(2)$ [9]	25	69	73	**1**	21	20	30	74	83	**25**	18	36
Transporter-$SE(3)$ [9]	**26**	70	77	0	20	22	29	77	85	23	20	38
Ours	0	**84**	**89**	0	**74**	**78**	27	**89**	**96**	22	**56**	**77**

Method	hanging-disks in-distribution-poses			hanging-disks out-of-distribution-poses			stacking-objects in-distribution-poses			stacking-objects out-of-distribution-poses		
	1	10	100	1	10	100	1	10	100	1	10	100
GT-State MLP	0	0	3	0	0	1	0	1	1	0	0	0
Form2Fit [14]	0	11	5	**4**	1	3	1	7	12	0	4	5
Transporter-$SE(2)$ [9]	6	65	72	3	32	17	0	**46**	40	**1**	**18**	35
Transporter-$SE(3)$ [9]	6	66	75	0	32	20	0	42	40	0	16	34
Ours	**13**	**68**	**100**	0	**43**	**71**	**13**	21	**76**	0	3	**74**

Table 2: Quantitative results. Task success rate (mean %) vs. # of demonstration episodes (1, 10, 100) used in training. Tasks labeled with in-distribution configure objects with random rotations ($\theta_x, \theta_y \in [-\frac{\pi}{6}, \frac{\pi}{6}], \theta_z \in [-\pi, \pi]$). This is also the rotation distribution used for creating the training set. Tasks labeled with out-of-distribution configure objects with rotations ($\theta_x, \theta_y \in [-\frac{\pi}{4}, -\frac{\pi}{6}] \cup [\frac{\pi}{6}, \frac{\pi}{4}], \theta_z \in [-\pi, \pi]$) that are (i) outside the training pose distribution and (ii) larger out-of-plane rotations.

Results. Fig. 4 shows the average scores of all methods trained on different numbers of demonstrations. GT-State MLP fails completely; Form2Fit cannot achieve 40% success rate under any setting; Both Transporter-$SE(2)$ and Transporter-$SE(3)$ are able to achieve ~70% success rate when the object poses are sampled from the training distribution, but the success rate drops to ~30% when the object poses are outside the training distribution. MIRA outperforms all baselines by a large margin when there are enough demonstrations of the task. Its success rate is ~90% under the setting of *in-distribution* and ~80% under the setting of *out-of-distribution*. The performance improvement over baselines demonstrates its generalization ability thanks to the action optimization process with novel view synthesis and

Figure 4: Average scores of all methods under both in-distribution and out-of-distribution settings.

affordance prediction in the loop. Interestingly, we found that MIRA sometimes performs worse than baselines when only 1 demonstration is supported. We hypothesize that this is because our action-value function needs more data to understand the subtle differences between images rendered from different views in order to select the best view. We show the full quantitative results in Table 2.

Ablation studies. To understand the importance of different components within our framework, we benchmark against two variants: (i) ours w/ perspective ray casting, and (ii) ours w/o multi-view negative samples in Eq. (7). We show the quantitative results in Table 3. We find that ours w/ perspective ray casting fail to learn the action-value functions because the perspective images (a) contain distorted appearances of the objects that are challenging for CNNs to comprehend and (b) the groudtruth picking or placing locations may be occluded by the robot arms. We visualize these challenges in the supplementary materials. Our method with orthographic ray casting circumvents both challenges by controlling the near/far planes to ignore occlusions without worrying about the distortion and scaling. Ours w/o multi-view negative samples

Figure 5: Real-world qualitative results. We validate MIRA in the real world with a kitting task that includes objects with reflective or transparent materials. We show that our framework can successfully pick up a stainless steel ice sphere and place it into 10+ different cups configured with random translations and out-of-plane rotations.

also fails to learn reliable action-value functions, and this may be due to a distribution shift between training and test: during training, it has only been supervised to choose the best pixel given an image. However, it is tasked to both select the best pixel and best view during the test time.

	block-insertion in-distribution-poses			block-insertion out-of-distribution-poses		
Method	1	10	100	1	10	100
Ours w/ perspective	0	0	0	0	0	0
Ours w/o multi-view negatives	0	11	13	0	2	4
Ours	0	84	89	0	74	78

Table 3: Ablation studies. We study the effects of ablating orthographic ray casting or multi-view negative samples from our system.

4.2 Real-world Experiments

We validate our framework with a kitting task in the real world and show qualitative results in Fig. 5. Our system consists of a UR5 arm, a customized suction gripper, and a wrist-mounted camera. We show that our method can successfully pick up a stainless steel ice sphere and place it into 10+ different cups configured with random translations and out-of-plane rotations. This task is challenging because (i) it includes objects with reflective or transparent materials, which makes this task not amenable to existing works that require depth sensors [9, 12, 14], and (ii) it requires out-of-plane action reasoning. The action-value functions are trained with 20 demonstrations using these cups. At the beginning of each pick-and-place, our system gathers 30 1280×720 RGB images of the scene with the wrist-mounted camera. Each image's camera pose is derived from the robotic manipulator's end-effector pose and a calibrated transformation between the end-effector and the camera. This data collection procedure is advantageous as industrial robotic manipulators feature sub-millimeter repeatability, which provides accurate camera poses for building NeRF. In practice, we search through $V = 121$ virtual views that uniformly cover the workspace and predict their affordances for optimizing actions. The optimization process currently takes around 2 seconds using a single NVIDIA RTX 2080 Ti GPU. This step can be straightforwardly accelerated by parallelizing the computations with multiple GPUs.

5 Limitations And Conclusion

In terms of limitations, our system currently requires training a NeRF of the scene for each step of the manipulation. An instant-NGP [64] requires approximately 10 seconds to converge using a single NVIDIA RTX 2080 Ti GPU, and moving the robot arms around to collect 30 multi-view RGB images of the scene takes nearly 1 minute. We believe observing the scene with multiple mounted cameras or learning a prior over instant-NGP could drastically reduce the runtime. In the future, we plan to explore the usage of mental imagery for other robotics applications such as navigation and mobile manipulation.

References

[1] R. N. Shepard and J. Metzler. Mental rotation of three-dimensional objects. *Science*, 171(3972): 701–703, 1971.

[2] A. Richardson. *Mental imagery*. Springer, 2013.

[3] F. Dellaert and L. Yen-Chen. Neural volume rendering: Nerf and beyond. *arXiv preprint arXiv:2101.05204*, 2020.

[4] Y. Xie, T. Takikawa, S. Saito, O. Litany, S. Yan, N. Khan, F. Tombari, J. Tompkin, V. Sitzmann, and S. Sridhar. Neural fields in visual computing and beyond. In *Computer Graphics Forum*, 2022.

[5] A. Tewari, J. Thies, B. Mildenhall, P. Srinivasan, E. Tretschk, W. Yifan, C. Lassner, V. Sitzmann, R. Martin-Brualla, S. Lombardi, et al. Advances in neural rendering. In *Computer Graphics Forum*, 2022.

[6] B. Mildenhall, P. P. Srinivasan, M. Tancik, J. T. Barron, R. Ramamoorthi, and R. Ng. Nerf: Representing scenes as neural radiance fields for view synthesis. In *ECCV*, 2020.

[7] A. Zeng. *Learning visual affordances for robotic manipulation*. PhD thesis, Princeton University, 2019.

[8] D. Batra, A. X. Chang, S. Chernova, A. J. Davison, J. Deng, V. Koltun, S. Levine, J. Malik, I. Mordatch, R. Mottaghi, et al. Rearrangement: A challenge for embodied ai. *arXiv preprint arXiv:2011.01975*, 2020.

[9] A. Zeng, P. Florence, J. Tompson, S. Welker, J. Chien, M. Attarian, T. Armstrong, I. Krasin, D. Duong, V. Sindhwani, and J. Lee. Transporter networks: Rearranging the visual world for robotic manipulation. *CoRL*, 2020.

[10] M. Shridhar, L. Manuelli, and D. Fox. Cliport: What and where pathways for robotic manipulation. In *CoRL*, 2021.

[11] L. Manuelli, W. Gao, P. Florence, and R. Tedrake. kpam: Keypoint affordances for category-level robotic manipulation. In *ISRR*, 2019.

[12] A. Simeonov, Y. Du, A. Tagliasacchi, J. B. Tenenbaum, A. Rodriguez, P. Agrawal, and V. Sitzmann. Neural descriptor fields: Se (3)-equivariant object representations for manipulation. In *ICRA*, 2022.

[13] S. Song, A. Zeng, J. Lee, and T. Funkhouser. Grasping in the wild: Learning 6dof closed-loop grasping from low-cost demonstrations. In *IROS*, 2020.

[14] K. Zakka, A. Zeng, J. Lee, and S. Song. Form2fit: Learning shape priors for generalizable assembly from disassembly. In *ICRA*, 2020.

[15] M. Zhu, K. G. Derpanis, Y. Yang, S. Brahmbhatt, M. Zhang, C. Phillips, M. Lecce, and K. Daniilidis. Single image 3d object detection and pose estimation for grasping. In *ICRA*, 2014.

[16] A. Zeng, K.-T. Yu, S. Song, D. Suo, E. Walker, A. Rodriguez, and J. Xiao. Multi-view self-supervised deep learning for 6d pose estimation in the amazon picking challenge. In *ICRA*, 2017.

[17] Y. Xiang, T. Schmidt, V. Narayanan, and D. Fox. PoseCNN: A convolutional neural network for 6d object pose estimation in cluttered scenes. In *RSS*, 2018.

[18] X. Deng, Y. Xiang, A. Mousavian, C. Eppner, T. Bretl, and D. Fox. Self-supervised 6d object pose estimation for robot manipulation. In *ICRA*, 2020.

[19] H. Wang, S. Sridhar, J. Huang, J. Valentin, S. Song, and L. J. Guibas. Normalized object coordinate space for category-level 6d object pose and size estimation. In *CVPR*, 2019.

[20] X. Chen, Z. Dong, J. Song, A. Geiger, and O. Hilliges. Category level object pose estimation via neural analysis-by-synthesis. In *ECCV*, 2020.

[21] X. Li, H. Wang, L. Yi, L. J. Guibas, A. L. Abbott, and S. Song. Category-level articulated object pose estimation. In *CVPR*, 2020.

[22] P. R. Florence, L. Manuelli, and R. Tedrake. Dense object nets: Learning dense visual object descriptors by and for robotic manipulation. In *CoRL*, 2018.

[23] P. Florence, L. Manuelli, and R. Tedrake. Self-supervised correspondence in visuomotor policy learning. *RA-L*, 2019.

[24] P. Sundaresan, J. Grannen, B. Thananjeyan, A. Balakrishna, M. Laskey, K. Stone, J. E. Gonzalez, and K. Goldberg. Learning rope manipulation policies using dense object descriptors trained on synthetic depth data. In *ICRA*, 2020.

[25] T. D. Kulkarni, A. Gupta, C. Ionescu, S. Borgeaud, M. Reynolds, A. Zisserman, and V. Mnih. Unsupervised learning of object keypoints for perception and control. *NeurIPS*, 32, 2019.

[26] X. Liu, R. Jonschkowski, A. Angelova, and K. Konolige. Keypose: Multi-view 3d labeling and keypoint estimation for transparent objects. In *CVPR*, 2020.

[27] Y. You, L. Shao, T. Migimatsu, and J. Bohg. Omnihang: Learning to hang arbitrary objects using contact point correspondences and neural collision estimation. In *2021 IEEE International Conference on Robotics and Automation (ICRA)*, pages 5921–5927. IEEE, 2021.

[28] S. Levine, C. Finn, T. Darrell, and P. Abbeel. End-to-end training of deep visuomotor policies. *JMLR*, 2016.

[29] D. Kalashnikov, A. Irpan, P. Pastor, J. Ibarz, A. Herzog, E. Jang, D. Quillen, E. Holly, M. Kalakrishnan, V. Vanhoucke, and S. Levine. Scalable deep reinforcement learning for vision-based robotic manipulation. In *CoRL*, 2018.

[30] J. Mahler, J. Liang, S. Niyaz, M. Laskey, R. Doan, X. Liu, J. A. Ojea, and K. Goldberg. Dex-net 2.0: Deep learning to plan robust grasps with synthetic point clouds and analytic grasp metrics. *arXiv preprint arXiv:1703.09312*, 2017.

[31] A. Zeng, S. Song, K.-T. Yu, E. Donlon, F. R. Hogan, M. Bauza, D. Ma, O. Taylor, M. Liu, E. Romo, et al. Robotic pick-and-place of novel objects in clutter with multi-affordance grasping and cross-domain image matching. In *ICRA*, 2018.

[32] A. ten Pas, M. Gualtieri, K. Saenko, and R. Platt. Grasp pose detection in point clouds. *IJRR*, 2017.

[33] A. Mousavian, C. Eppner, and D. Fox. 6-dof graspnet: Variational grasp generation for object manipulation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, 2019.

[34] J. Wu, X. Sun, A. Zeng, S. Song, J. Lee, S. Rusinkiewicz, and T. Funkhouser. Spatial action maps for mobile manipulation. *arXiv preprint arXiv:2004.09141*, 2020.

[35] S. James, K. Wada, T. Laidlow, and A. J. Davison. Coarse-to-fine q-attention: Efficient learning for visual robotic manipulation via discretisation. In *CVPR*, 2022.

[36] H. Huang, D. Wang, R. Walter, and R. Platt. Equivariant transporter network. In *RSS*, 2022.

[37] D. Wang, R. Walters, and R. Platt. So (2) equivariant reinforcement learning. In *ICLR*, 2022.

[38] X. Zhu, D. Wang, O. Biza, G. Su, R. Walters, and R. Platt. Sample efficient grasp learning using equivariant models. In *RSS*, 2022.

[39] B. Curless and M. Levoy. A volumetric method for building complex models from range images. In *Proceedings of the 23rd annual conference on Computer graphics and interactive techniques*, 1996.

[40] T. Karras, M. Aittala, S. Laine, E. Härkönen, J. Hellsten, J. Lehtinen, and T. Aila. Alias-free generative adversarial networks. *NeurIPS*, 34, 2021.

[41] J. J. Park, P. Florence, J. Straub, R. Newcombe, and S. Lovegrove. Deepsdf: Learning continuous signed distance functions for shape representation. In *CVPR*, 2019.

[42] L. Mescheder, M. Oechsle, M. Niemeyer, S. Nowozin, and A. Geiger. Occupancy networks: Learning 3d reconstruction in function space. In *CVPR*, 2019.

[43] V. Sitzmann, M. Zollhöfer, and G. Wetzstein. Scene representation networks: Continuous 3d-structure-aware neural scene representations. In *NeurIPS*, 2019.

[44] V. Sitzmann, S. Rezchikov, B. Freeman, J. Tenenbaum, and F. Durand. Light field networks: Neural scene representations with single-evaluation rendering. *NeurIPS*, 34, 2021.

[45] R. Gao, Y.-Y. Chang, S. Mall, L. Fei-Fei, and J. Wu. Objectfolder: A dataset of objects with implicit visual, auditory, and tactile representations. In *CoRL*, 2021.

[46] V. Sitzmann, J. Martel, A. Bergman, D. Lindell, and G. Wetzstein. Implicit neural representations with periodic activation functions. In *NeurIPS*, 2020.

[47] A. Luo, Y. Du, M. J. Tarr, J. B. Tenenbaum, A. Torralba, and C. Gan. Learning neural acoustic fields. *arXiv preprint arXiv:2204.00628*, 2022.

[48] L. Yen-Chen, P. Florence, J. T. Barron, A. Rodriguez, P. Isola, and T.-Y. Lin. iNeRF: Inverting neural radiance fields for pose estimation. In *IROS*, 2021.

[49] A. Moreau, N. Piasco, D. Tsishkou, B. Stanciulescu, and A. de La Fortelle. Lens: Localization enhanced by nerf synthesis. In *Conference on Robot Learning*, 2022.

[50] E. Sucar, S. Liu, J. Ortiz, and A. Davison. iMAP: Implicit mapping and positioning in real-time. In *ICCV*, 2021.

[51] Z. Zhu, S. Peng, V. Larsson, W. Xu, H. Bao, Z. Cui, M. R. Oswald, and M. Pollefeys. Nice-slam: Neural implicit scalable encoding for slam. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 12786–12796, 2022.

[52] J. Ortiz, A. Clegg, J. Dong, E. Sucar, D. Novotny, M. Zollhoefer, and M. Mukadam. isdf: Real-time neural signed distance fields for robot perception. In *RSS*, 2022.

[53] M. Adamkiewicz, T. Chen, A. Caccavale, R. Gardner, P. Culbertson, J. Bohg, and M. Schwager. Vision-only robot navigation in a neural radiance world. In *RA-L*, 2022.

[54] Y. Li, S. Li, V. Sitzmann, P. Agrawal, and A. Torralba. 3d neural scene representations for visuomotor control. In *CoRL*, 2021.

[55] D. Driess, Z. Huang, Y. Li, R. Tedrake, and M. Toussaint. Learning multi-object dynamics with compositional neural radiance fields. *arXiv preprint arXiv:2202.11855*, 2022.

[56] Y. Wi, P. Florence, A. Zeng, and N. Fazeli. Virdo: Visio-tactile implicit representations of deformable objects. In *ICRA*, 2022.

[57] B. Shen, Z. Jiang, C. Choy, L. J. Guibas, S. Savarese, A. Anandkumar, and Y. Zhu. Acid: Action-conditional implicit visual dynamics for deformable object manipulation. In *RSS*, 2022.

[58] D. Driess, I. Schubert, P. Florence, Y. Li, and M. Toussaint. Reinforcement learning with neural radiance fields. *arXiv preprint arXiv:2206.01634*, 2022.

[59] Z. Jiang, Y. Zhu, M. Svetlik, K. Fang, and Y. Zhu. Synergies between affordance and geometry: 6-dof grasp detection via implicit representations. In *RSS*, 2021.

[60] J. Ichnowski*, Y. Avigal*, J. Kerr, and K. Goldberg. Dex-NeRF: Using a neural radiance field to grasp transparent objects. In *CoRL*, 2020.

[61] L. Yen-Chen, P. Florence, J. T. Barron, T.-Y. Lin, A. Rodriguez, and P. Isola. NeRF-Supervision: Learning dense object descriptors from neural radiance fields. In *ICRA*, 2022.

[62] J. T. Kajiya and B. P. V. Herzen. Ray tracing volume densities. *SIGGRAPH*, 1984.

[63] N. Max. Optical models for direct volume rendering. *IEEE TVCG*, 1995.

[64] T. Müller, A. Evans, C. Schied, and A. Keller. Instant neural graphics primitives with a multiresolution hash encoding. In *SIGGRAPH*, 2022.

[65] Y. LeCun, Y. Bengio, et al. Convolutional networks for images, speech, and time series. *The handbook of brain theory and neural networks*, 3361(10):1995, 1995.

[66] J. Long, E. Shelhamer, and T. Darrell. Fully convolutional networks for semantic segmentation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 3431–3440, 2015.

[67] Y. LeCun, S. Chopra, R. Hadsell, M. Ranzato, and F. Huang. A tutorial on energy-based learning. *Predicting structured data*, 1(0), 2006.

[68] Y. Du and I. Mordatch. Implicit generation and generalization in energy-based models. *arXiv preprint arXiv:1903.08689*, 2019.

[69] P. Florence, C. Lynch, A. Zeng, O. A. Ramirez, A. Wahid, L. Downs, A. Wong, J. Lee, I. Mordatch, and J. Tompson. Implicit behavioral cloning. In *Conference on Robot Learning*, pages 158–168. PMLR, 2022.

[70] S. Li, Y. Du, G. M. van de Ven, and I. Mordatch. Energy-based models for continual learning. *arXiv preprint arXiv:2011.12216*, 2020.

[71] D. Seita, P. Florence, J. Tompson, E. Coumans, V. Sindhwani, K. Goldberg, and A. Zeng. Learning to rearrange deformable cables, fabrics, and bags with goal-conditioned transporter networks. In *2021 IEEE International Conference on Robotics and Automation (ICRA)*. IEEE, 2021.

[72] E. Coumans and Y. Bai. Pybullet, a python module for physics simulation for games, robotics and machine learning. 2016.