Finite-Time Regret of Thompson Sampling Algorithms for Exponential Family Multi-Armed Bandits

Abstract

We study the regret of Thompson sampling (TS) algorithms for exponential family bandits, where the reward distribution is from a one-dimensional exponential family, which covers many common reward distributions including Bernoulli, Gaussian, Gamma, Exponential, etc. We propose a Thompson sampling algorithm, termed ExpTS, which uses a novel sampling distribution to avoid the under-estimation of the optimal arm. We provide a tight regret analysis for ExpTS, which simultaneously yields both the finite-time regret bound as well as the asymptotic regret bound. In particular, for a K-armed bandit with exponential family rewards, ExpTS over a horizon T is sub-UCB (a strong criterion for the finite-time regret that is problem-dependent), minimax optimal up to a factor $\sqrt{\log K}$, and asymptotically optimal, for exponential family rewards. Moreover, we propose ExpTS$^+$, by adding a greedy exploitation step in addition to the sampling distribution used in ExpTS, to avoid the over-estimation of sub-optimal arms. ExpTS$^+$ is an anytime bandit algorithm and achieves the minimax optimality and asymptotic optimality simultaneously for exponential family reward distributions. Our proof techniques are general and conceptually simple and can be easily applied to analyze standard Thompson sampling with specific reward distributions.

1 Introduction

The Multi-Armed Bandit (MAB) problem is centered around a fundamental model for balancing the exploration versus exploitation trade-off in many online decision problems. In this problem, the agent is given an environment with a set of K arms $[K] = \{1, 2, \cdots, K\}$. At each time step t, the agent pulls an arm $A_t \in [K]$ based on observations of previous $t - 1$ time steps, and then a reward r_t is revealed at the end of the step. In real-world applications, reward distributions often have different forms such as Bernoulli, Gaussian, etc. As suggested by Auer et al. [7, 8], Agrawal and Goyal [5], Lattimore [27], Garivier et al. [14], a good bandit strategy should be general enough to cover a sufficiently rich family of reward distributions. In this paper, we assume the reward r_t is independently generated from some canonical one-parameter exponential family of distributions with a mean value μ_{A_t}. It is a rich family that covers many common distributions including Bernoulli, Gaussian, Gamma, Exponential, and others.

The goal of a bandit strategy is usually to maximize the cumulative reward over T time steps, which is equivalent to minimizing the regret, defined as the expected cumulative difference between playing the best arm and playing the arm according to the strategy: $R_\mu(T) = T \cdot \max_{i \in [K]} \mu_i - \mathbb{E}[\sum_{t=1}^{T} r_t]$. We assume, without loss of generality, $\mu_1 = \max_{i \in [K]} \mu_i$ is the best arm throughout this paper. For a fixed bandit instance (i.e., mean rewards $\mu_1, \cdots, \mu_K$ are fixed), Lai and Robbins [24] shows that for

distributions that are continuously parameterized by their means,

$$\lim_{T \to \infty} \frac{R_\mu(T)}{\log T} \geq \sum_{i>1} \frac{\mu_1 - \mu_i}{\mathrm{kl}(\mu_i, \mu_1)}, \tag{1.1}$$

where $\mathrm{kl}(\mu_i, \mu_1)$ is the Kullback-Leibler divergence between two distributions with mean μ_i and μ_1. A bandit strategy satisfying $\lim_{T \to \infty} R_\mu(T)/\log T = \sum_{i>1} \frac{\mu_1 - \mu_i}{\mathrm{kl}(\mu_i, \mu_1)}$ is said to be *asymptotically optimal* or achieve the asymptotic optimality in regret. The asymptotic optimality is one of the most important statistical properties in regret minimization, which shows that an algorithm is consistently good when it is played for infinite steps and thus should be a basic theoretical requirement of any good bandit strategy [7].

In practice, we can only run the bandit algorithm for a finite number T steps, which is the time horizon of interest in real-world applications. Therefore, the finite-time regret is the ultimate property of a practical bandit strategy in regret minimization problems. A strong notion of finite-time regret bounds is called *the sub-UCB criteria* [27], where the regret satisfies

$$R_\mu(T) = O\left(\sum_{i \in [K]: \Delta_i > 0} \left(\Delta_i + \frac{\log T}{\Delta_i} \right) \right), \tag{1.2}$$

where $\Delta_i = \mu_1 - \mu_i$ is the sub-optimal gap between arm 1 and arm i. Note that the regret bound in (1.2) is a problem-dependent bound since it depends on the bandit instance and the sub-optimal gaps. Sub-UCB is an important metric for finite-time regret bound and has been adopted by recent work of Lattimore [27], Bian and Jun [9]. Another special type of finite-time bounds is called the worst-case regret, which is defined as the finite-time regret of an algorithm on any possible bandit instance within a bandit class. Specifically, for a finite time horizon T, Auer et al. [7] proves that any strategy has at least worst-case regret $\Omega(\sqrt{KT})$ for a K-armed bandit. We say the strategy that achieves a worst-case regret $O(\sqrt{KT})$ is *minimax optimal* or achieves the minimax optimality. Different from the asymptotic optimality, the minimax optimality characterizes the worst-case performance of the bandit strategy in finite steps.

A vast body of literature in multi-armed bandits [6, 5, 20, 30, 14, 27] have been pursing the afore-mentioned theoretical properties of bandit algorithms: generality, asymptotic optimality, problem-dependent finite-time regret, and minimax optimality. However, most of them focus on one or two properties and sacrifice the others. Moreover, many of existing theoretical analyses of bandit strategies are for optimism-based algorithm. The theoretical analysis of Thompson sampling (TS) is much less understood until recently, which has been shown to exhibit superior practical performances compared to the state-of-the-art methods [11, 32]. Specifically, its finite-time regret, asymptotic optimality, and near minimax optimality have been studied by Agrawal and Goyal [3, 4, 5] for Bernoulli rewards. Jin et al. [18] proved the minimax optimality of TS for sub-Gaussian rewards. For exponential family reward distributions, the asymptotic optimality is shown by Korda et al. [23], but no finite-time regret of TS is provided. See Table 1 for a comprehensive comparison of these results.

In this paper, we study the regret of Thompson sampling for exponential family reward distributions and address all the theoretical properties of TS. We propose a variant of TS algorithm with a general sampling distribution and a tight analysis for frequentist regret bounds. Our analysis simultaneously yields both the finite-time regret bound and the asymptotic regret bound.

Specifically, the **main contributions** of this paper are summarized as follows:

- We propose ExpTS, a general variant of Thompson Sampling, that uses a novel sampling distribution with a tight anti-concentration bound to avoid the under-estimation of the optimal arm and a tight concentration bound to avoid the over-estimation of sub-optimal arms. For exponential family of reward distributions, we prove that ExpTS is the first Thompson sampling algorithm achieving the sub-UCB criteria, which is a strong notion of problem-dependent finite-time regret bounds. We further show that ExpTS is also simultaneously minimax optimal up to a factor of $\sqrt{\log K}$, as well as asymptotically optimal, where K is the number of arms.
- We also propose ExpTS$^+$, which explores between the sample generated in ExpTS and the empirical mean reward for each arm, to get rid of the extra $\sqrt{\log K}$ factor in the minimax regret. Thus ExpTS$^+$ is the first Thompson sampling algorithm that is simultaneously minimax and asymptotically optimal for exponential family of reward distributions.
- Our regret analysis of ExpTS can be easily extended to analyze Thompson sampling with common reward distributions in the exponential family. For Gaussian reward with known variance, we prove

Table 1: Comparisons of different Thompson sampling algorithms on K-armed bandits over a horizon T. For any algorithm, *Asym. Opt* is the indicator whether it is asymptotically optimal, *minimax ratio* is the scaling of its worst-case regret w.r.t. the minimax optimal regret $O(\sqrt{VKT})$, where V is the variance of reward distributions, and sub-UCB is the indicator if it satisfies the sub-UCB criteria.

Algorithm	Reward Type	Asym. Opt	Finite-Time Regret		Anytime	Reference
			Minimax Ratio	Sub-UCB		
TS	Bernoulli	yes	$\sqrt{\log T}$	yes	yes	[4]
TS	Bernoulli	–	$\sqrt{\log K}$	yes	yes	[5]
TS	Exponential Family	yes	–	–	yes	[23]
MOTS	sub-Gaussian	no	1	no	no	[18]
MOTS-$\mathcal{J}$	Gaussian	yes	1	no	no	[18]
ExpTS	Exponential Family	yes	$\sqrt{\log K}$	yes	yes	This paper
ExpTS$^+$	Exponential Family	yes	1	no	yes	This paper

that TS with Gaussian posteriors (Gaussian-TS) is asymptotically optimal and minimax optimal up to a factor of $\sqrt{\log K}$. For Bernoulli reward, we prove that TS with Beta posteriors (Bernoulli-TS) is asymptotically optimal and minimax optimal up to a factor of $\sqrt{\log K}$. Similar to the idea of ExpTS$^+$, we can add a greedy exploration step to the posterior distributions used in these variants of TS, and then the algorithms are simultaneously minimax and asymptotically optimal.

Our techniques are novel and conceptually simple. First, we introduce a lower confidence bound in the regret decomposition to avoid the under-estimation of the optimal arm, which is important in obtaining the finite-time regret bound. Specifically, Jin et al. [18] (Lemma 5 in their paper) shows that for Gaussian reward distributions, Gaussian-TS has a regret bound at least in the order of $\Omega(\sqrt{KT \log T})$ if the standard regret decomposition in existing analysis of Thompson sampling [5, 28, 18] is adopted. With our new regret decomposition that is conditioned on the lower confidence bound introduced in this paper, we improve the worst-case regret of Gaussian-TS for Gaussian reward distributions to $O(\sqrt{KT \log K})$.

Second, we do not require the closed form of the reward distribution, but only make use of the corresponding concentration bounds. This means our results can be readily extended to other reward distributions. For example, we can extend ExpTS$^+$ to sub-Gaussian reward distributions and the algorithm is simultaneously minimax and asymptotically optimal[1], which improve the results of MOTS proposed by Jin et al. [18] (see Table 1).

Third, the idea of ExpTS$^+$ is simple and can be used to remove the extra $\sqrt{\log K}$ factor in the minimax regret. We note that MOTS [18] can also achieve the minimax optimal via the clipped Gaussian. However, it is not clear how to generalize the clipping idea to the exponential family of reward distribution. Moreover, it uses the MOSS [6] index for clipping, which needs to know the horizon T in advance and thus cannot be extended to the anytime setting, while ExpTS$^+$ is an anytime bandit algorithm which does not need to know the horizon length in advance.

Notations. We let T be the total number of time steps, K be the total number of arms, and $[K] = \{1, 2, \cdots, K\}$. For simplicity, we assume arm 1 is the optimal throughout this paper, i.e., $\mu_1 = \max_{i \in [K]} \mu_i$. We denote $\log^+(x) = \max\{0, \log x\}$ and $\Delta_i := \mu_1 - \mu_i, i \in [K] \setminus \{1\}$ for the gap between arm 1 and arm i. We let $T_i(t) := \sum_{j=1}^{t} \mathbb{1}\{A_t = i\}$ be the number of pulls of arm i at the time step t, $\widehat{\mu}_i(t) := 1/T_i(t) \sum_{j=1}^{t} [r_j \cdot \mathbb{1}\{A_t = i\}]$ be the average reward of arm i at the time step t, and $\widehat{\mu}_{is}$ be the average reward of arm i after its s-th pull.

2 Related Work

There are series of works pursuing the asymptotic optimal regret bound and minimax regret bound for MAB. For asymptotic optimality, UCB algorithms [13, 29, 5, 27], Thompson sampling [21, 23, 5, 18],

---

[1]Note that sub-Gaussian is a non-parametric family and thus the lower bound (1.1) by Lai and Robbins [24] does not directly apply to a general sub-Gaussian distribution. Following similar work in the literature [18], in this paper, when we say an algorithm achieves the asymptotic optimality for sub-Gaussian rewards, we mean its regret matches the asymptotic lower bound for Gaussian rewards, which is a stronger notion.

Bayes-UCB [20], and other methods [19, 9] are all shown to be asymptotically optimal. Among them, only a few [13, 5, 23] can be extended to exponential families of distributions. For minimax regret, MOSS [6] is first proved to be minimax optimal. Later, KL-UCB^{++} [5], AdaUCB [27], MOTS [18] also join the family. The anytime version of MOSS is studied by Degenne and Perchet [12]. There are also some works that focus on the near optimal problem-dependent regret bound [25, 26]. As far as we know, no algorithm has been proved to achieve the sub-UCB criteria, asymptotic optimality, and minimax optimality simultaneously for exponential family reward distributions.

For Thompson sampling, Russo and Van Roy [31] studied the Bayesian regret. They show that the Bayesian regret of Thompson sampling is never worse than the regret of UCB. Bubeck and Liu [10] further showed the Bayesian regret of Thompson sampling is optimal using the regret analysis of MOSS. There are also a line of works focused on the frequentist regret of TS. Agrawal and Goyal [3] proposed the first finite time regret analysis for TS. Kaufmann et al. [21], Agrawal and Goyal [4] proved that TS with beta posteriors is asymptotically optimal for Bernoulli reward distributions. Korda et al. [23] extended the asymptotic optimality to the exponential family of reward distributions. Subsequently, for Bernoulli rewards, Agrawal and Goyal [5] proved that TS with Beta prior is asymptotically optimal and has worst-case regret $O(\sqrt{KT \log T})$. Besides, they showed that TS with Gaussian posteriors can achieve a better worst-case regret bound $O(\sqrt{KT \log K})$. They also proved that for Bernoulli rewards, TS with Gaussian posteriors has a worst-case regret at least $\Omega(\sqrt{KT \log K})$. Very recently, Jin et al. [18] proposed the MOTS algorithm that can achieve the minimax optimal regret $O(\sqrt{KT})$ for multi-armed bandits with sub-Gaussian rewards but at the cost of losing the asymptotic optimality by a multiplicative factor of $1/\rho$, where $0 < \rho < 1$ is an arbitrarily fixed constant. For bandits with Gaussian rewards, Jin et al. [18] proved that MOTS combined with a Rayleigh distribution can achieve the minimax optimality and the asymptotic optimality simultaneously. We refer readers to Tables 1 and 2 for more details.

3 Preliminary on Exponential Family Distributions

A one-dimensional canonical exponential family (the same definition also can be found in [13, 15, 30]) is a parametric set of probability distributions with respect to some reference measure, with the density function given by

$$p_\theta(x) = \exp(x\theta - b(\theta) + c(x)),$$

where θ is the model parameter, and c is a real function. Denote the measure $p_\theta(x)$ as ν_θ. Then, the above definition can be rewritten as

$$\frac{d\nu_\theta}{d\rho}(x) = \exp(x\theta - b(\theta)),$$

for some measure ρ and $b(\theta) = \log(\int e^{x\theta} d\rho(x))$. We make the classic assumption used by Garivier and Cappé [13], Ménard and Garivier [30] that $b(\theta)$ is twice differentiable with a continuous second derivative. Then, we can verify that exponential families have the following properties:

$$b'(\theta) = \mathbb{E}[\nu_\theta] \qquad \text{and} \qquad b''(\theta) = \text{Var}[\nu_\theta] > 0.$$

Let $\mu = \mathbb{E}[\nu_\theta]$. The above equality means that the mapping between the mean value μ of $\nu(\theta)$ and the parameter θ is one-to-one. Hence, exponential family of distributions can also be parametrized by the mean value $\mu = b'(\theta)$. Note that $b''(\theta) > 0$ for all θ, which implies $b'(\cdot)$ is invertible and its inverse function b'^{-1} satisfies $\theta = b'^{-1}(\mu)$. In this paper, we will use the notion of Kullback-Leibler (KL) divergence. The KL divergence between two exponential family distributions with parameter θ and θ' respectively is defined as follows:

$$\text{KL}(\nu_\theta, \nu_{\theta'}) = b(\theta') - b(\theta) - b'(\theta)(\theta' - \theta). \tag{3.1}$$

Recall that the mapping $\theta \mapsto \mu$ is one-to-one. We can define an equivalent notion of the KL divergence between random variables ν_θ and $\nu_{\theta'}$ as a function of the mean values μ and μ' respectively:

$$\text{kl}(\mu, \mu') = \text{KL}(\nu_\theta, \nu_{\theta'}),$$

where $\mathbb{E}[\nu_\theta] = \mu$ and $\mathbb{E}[\nu_{\theta'}] = \mu'$. Similarly, we define $V(\mu) = \text{Var}(\nu_{b'^{-1}(\mu)})$ as the variance of an exponential family random variable ν_θ with mean μ. We assume the variances of exponential family distributions used in this paper are bounded by a constant $V > 0$:

$$0 < V(\mu) \le V < +\infty.$$

We have the following property of the KL divergence between exponential family distributions.

Algorithm 1 Exponential Family Thompson Sampling (ExpTS)

1: **Input:** Arm set $[K]$
2: **Initialization:** Play each arm once and set $T_i(K) = 1$; let $\widehat{\mu}_i(K)$ be the observed reward of playing arm i
3: **for** $t = K + 1, K + 2, \cdots$ **do**
4:     For all $i \in [K]$, sample $\theta_i(t)$ independently from $\mathcal{P}(\widehat{\mu}_i(t), T_i(t))$
5:     Play arm $A_t = \arg\max_{i \in [K]} \theta_i(t)$ and observe the reward r_t
6:     For all $i \in [K]$, update the mean reward estimator and the number of pulls:

$$\hat{\mu}_i(t) = \frac{T_i(t-1) \cdot \widehat{\mu}_i(t-1) + r_t \, \mathbb{1}\{i = A_t\}}{T_i(t-1) + \mathbb{1}\{i = A_t\}}, \quad T_i(t) = T_i(t-1) + \mathbb{1}\{i = A_t\}$$

7: **end for**

Proposition 3.1 (Harremoës [15]). *Let μ and μ' be the mean values of two exponential family distributions. The Kullback-Leibler divergence between them can be calculated as follows:*

$$kl(\mu, \mu') = \int_{\mu}^{\mu'} \frac{x - \mu}{V(x)} dx. \tag{3.2}$$

It is worth noting that exponential families cover many of the most common distributions used in practice such as Bernoulli, exponential, Gamma, and Gaussian distributions. In particular, for two Gaussian distributions with the same known variance σ^2 and different means μ and μ', we can choose $V(\cdot) = \sigma^2$, and recover the results in Proposition 3.1 as $kl(\mu, \mu') = (\mu - \mu')/(2\sigma^2)$. For two Bernoulli distributions with mean values μ and μ' respectively, we can choose $V(\cdot) = 1/4$, and recover the result in Proposition 3.1 as $kl(\mu, \mu') = \mu \log(\mu/\mu') + (1 - \mu) \log((1 - \mu)/(1 - \mu'))$.

Based on Proposition 3.1, we can also verify the following properties.

Proposition 3.2 (Jin et al. [17]). *For all μ and μ', we have*

$$kl(\mu, \mu') \geq (\mu - \mu')^2/(2V). \tag{3.3}$$

In addition, for $\epsilon > 0$ and $\mu \leq \mu' - \epsilon$, we can obtain that

$$kl(\mu, \mu') \geq kl(\mu, \mu' - \epsilon) \quad and \quad kl(\mu, \mu') \leq kl(\mu - \epsilon, \mu'). \tag{3.4}$$

4 Thompson Sampling for Exponential Family Reward Distributions

We present a general variant of Thompson sampling for exponential family rewards in Algorithm 1, which is termed ExpTS. At round t, ExpTS maintains an estimate of a sampling distribution for each arm, denoted as $\mathcal{P}$. The algorithm generates a sample parameter $\theta_i(t)$ for each arm i independently from their sampling distribution and chooses the arm that attains the largest sample parameter. For each arm $i \in [K]$, the sampling distribution $\mathcal{P}$ is usually defined as a function of the total number of pulls $T_i(t)$ and the empirical average reward $\widehat{\mu}_i(t)$. After pulling the chosen arm, the algorithm updates $T_i(t)$ and $\widehat{\mu}_i(t)$ for each arm based on the reward r_t it receives and proceeds to the next round.

It is worth noting that we study the frequentist regret bound of Algorithm 1 and thus ExpTS is not restricted as a Bayesian method. As pointed out by Abeille and Lazaric [1], Jin et al. [18], Kim et al. [22], Zhang [33], the sampling distribution does not have to be a posterior distribution derived from a pre-defined prior distribution. Therefore, we call $\mathcal{P}$ the sampling distribution instead of the posterior distribution as in Bayesian regret analysis of Thompson sampling [31, 10]. To obtain the finite-time regret bound of ExpTS for exponential family rewards, we will discuss the choice of a general sampling distribution and a new proof technique.

4.1 Challenges in Regret Analysis for Exponential Family Bandits

Before we choose a specific sampling distribution $\mathcal{P}$ for ExpTS, we first discuss the main challenges in the finite-time regret analysis of Thompson sampling, which is the main motivation for our design of $\mathcal{P}$ in the next subsection.

Under-Estimation of the Optimal Arm. Denote $\widehat{\mu}_{is}$ as the average reward of arm i after its s-th pull, $T_i(t)$ as the number of pulls of arm i at time t, and $\mathcal{P}(\widehat{\mu}_{is}, s)$ as the sampling distribution of arm i after its s-th pull. The regret of the algorithm contributed by pulling arm i is $\Delta_i \mathbb{E}[T_i(T)]$, where $T_i(T)$ is the total number of pulls of arm i. All existing analysis of finite-time regret bounds for TS [3–5, 18] decomposes this regret term as $\Delta_i \mathbb{E}[T_i(T)] \leq D_i + h_i(\Delta_i, T, \theta_i(1), \ldots, \theta_i(T))$, where $h_i()$ is a quantity characterizing the over-estimation of arm i which can be easily dealt with by some concentration properties of the sampling distribution (see Lemma B.5 for more details). The term D_i characterizes the under-estimation of the optimal arm 1, which is usually bounded as follows in existing work:

$$D_i = \Delta_i \sum_{s=1}^{T} \mathbb{E}_{\widehat{\mu}_{1s}} \left[\frac{1}{G_{1s}(\epsilon)} - 1 \right], \tag{4.1}$$

where $G_{1s}(\epsilon) = 1 - F_{1s}(\mu_1 - \epsilon)$, F_{1s} is the CDF of the sampling distribution $\mathcal{P}(\widehat{\mu}_{1s}, s)$, and $\epsilon = \Theta(\Delta_i)$. In other words, $G_{1s}(\epsilon) = \mathbb{P}(\theta_1(t) > \mu_1 - \epsilon)$ is the probability that the best arm will *not be under-estimated* from the mean reward by a margin ϵ. Furthermore, we can interpret the quantity in (4.1) as the result of a union bound indicating how many samples TS requires to ensure that at least one sample of the best arm $\{\theta_1(t)\}_{t=1}^{T}$ is larger than $\mu_1 - \epsilon$. If $G_{1s}(\epsilon)$ is too small, arm 1 could be significantly under-estimated, and thus D_i will be unbounded. In fact, as shown in Lemma 5 by Jin et al. [18], for MAB with Gaussian rewards, TS using Gaussian posteriors will unavoidably suffer from a regret $D_i = \Omega(\sqrt{KT \log T})$.

To address the above issue, we introduce a lower confidence bound for measuring the under-estimation problem. We use a new decomposition of the regret that bounds D_i with the following term

$$\Delta_i \sum_{s=1}^{T} \mathbb{E}_{\widehat{\mu}_{1s}} \left[\left(\frac{1}{G_{1s}(\epsilon)} - 1 \right) \cdot \mathbb{1}\{\widehat{\mu}_{1s} \geq Low_s\} \right], \tag{4.2}$$

where Low_s is a lower confidence bound of $\widehat{\mu}_{1s}$. Intuitively, due to the concentration of arm 1, the probability of $\widehat{\mu}_{1s} \leq Low_s$ is very small. Thus, even when $G_{1s}(\epsilon)$ is small, the overall regret can be well controlled.

In the regret analysis of TS, we can bound (4.2) from two facets: (1) the lower confidence bound can be proved using the concentration property of the reward distributions; and (2) the term $G_{1s}(\epsilon) = \mathbb{P}(\theta_1(t) > \mu_1 - \epsilon)$ can be upper bounded by the anti-concentration property for the sampling distribution $\mathcal{P}$. To achieve an optimal regret, one needs to carefully balance the interplay between these two bounds. For a specific reward distribution (e.g., Gaussian, Bernoulli) as is studied by Agrawal and Goyal [5], Jin et al. [18], there is already a tight anti-concentration for the reward distribution, and thus the first lower confidence bound is tight. Therefore, by choosing Gaussian or Bernoulli as the prior (which leads to a Gaussian or Beta sampling distribution $\mathcal{P}$), we can use existing anti-concentration bounds for Gaussian (Formula 7.1.13 in [2]) or Beta (Prop. A.4 in [16]) distributions to obtain a tight bound of $G_{1s}(\epsilon)$.

In this paper, we study the general exponential family of reward distribution, which has no closed form. Thus we cannot obtain a tight concentration bound for $\hat{\mu}_{1s}$ as in special cases such as Gaussian or Bernoulli rewards. This increases the hardness of tightly bounding term (4.2) and it is imperative for us to design a sampling distribution $\mathcal{P}$ with a tight anti-concentration bound that can carefully control $G_{1s}(\epsilon)$ while without knowledge of the closed form distribution of the average reward $\hat{\mu}_{1s}$. Due to the generality of exponential family distributions, it is challenging and nontrivial to find such a sampling distribution to obtain a tight finite-time regret bound.

4.2 Sampling Distribution Design in Exponential Family Bandits

As discussed in the previous subsection, we need a sampling distribution $\mathcal{P}$ that has a tight anti-concentration bound to overcome the under-estimation of the optimal arm and a concentration bound to overcome the over-estimation of the suboptimal arms.

For the simplicity of notation, we denote $\mathcal{P}(\mu, n)$ as the sampling distribution, where μ and n are some input parameters. In particular, for ExpTS, we will choose $\mu = \widehat{\mu}_i(t)$ and $n = T_i(t)$ for arm $i \in [K]$ at round t. We define $\mathcal{P}(\mu, n)$ as a distribution with PDF

$$f(x; \mu, n) = 1/2|(n \cdot \mathrm{kl}(\mu, x))'|e^{-nb_n \cdot \mathrm{kl}(\mu,x)} = \frac{n \cdot |x - \mu|}{2V(x)} e^{-nb_n \cdot \mathrm{kl}(\mu,x)}, \tag{4.3}$$

Table 2: Comparisons of different algorithms on K-armed bandits over a horizon T. For any algorithm, *Asym. Opt* is the indicator whether it is asymptotically optimal, *minimax ratio* is the scaling of its worst-case regret w.r.t. the minimax optimal regret $O(\sqrt{VKT})$, *sub-UCB* indicates whether it satisfies the sub-UCB criteria, and *Anytime* indicates whether it needs the knowledge of the horizon length T in advance.

Algorithm	Reward Type	Asym. Opt	Finite-Time Regret		Anytime	References
			Minimax Ratio	Sub-UCB		
MOSS	$[0,1]$	no	1	no	no	[6]
Anytime MOSS	$[0,1]$	no	1	no	yes	[12]
KL-UCB^{++}	Exponential Family	yes	1	no	no	[30]
OCUCB	sub-Gaussian	no	$\sqrt{\log\log T}$	yes	yes	[26]
AdaUCB	Gaussian	yes	1	yes	no	[27]
MS	sub-Gaussian	yes	$\sqrt{\log K}$	yes	yes	[9]
ExpTS	Exponential Family	yes	$\sqrt{\log K}$	yes	yes	This paper
ExpTS^{+}	Exponential Family	yes	1	no	yes	This paper

where $(\mathrm{kl}(\mu,x))'$ denotes the derivative of $\mathrm{kl}(\mu,x)$ with respect to x and b_n is a function of n and will be chosen later.

We assume the reward is supported in $[R_{\min}, R_{\max}]$. Note that $R_{\min} = 0$, and $R_{\max} = 1$ for Bernoulli rewards, and $R_{\min} = -\infty$, and $R_{\max} = \infty$ for Gaussian rewards. Let $p(x)$ and $q(x)$ be the density functions of two exponential family distributions with mean values μ_p and μ_q respectively. By the definition in Section 3, we have $\mathrm{kl}(\mu_p, \mu_q) = \mathrm{KL}(p(x), q(x)) = \int_{R_{\min}}^{R_{\max}} p(x) \log \frac{p(x)}{q(x)} \mathrm{d}x$. If the mean value of $q(x)$ is $\mu_q = R_{\max}$, we must have $q(x) = 0$ for all $x < R_{\max}$, which implies $\mathrm{kl}(\mu, R_{\max}) = \infty$ for any $\mu < R_{\max}$. Similarly, we have $\mathrm{kl}(\mu, R_{\min}) = \infty$. Therefore, we can easily verify that the sampling distribution has the following tail bounds: for $z \in [\mu, R_{\max})$, it holds

$$\mathbb{P}(\theta \geq z) = \int_z^{R_{\max}} f(x; \mu, n)\mathrm{d}x = -1/2 e^{-nb_n \cdot \mathrm{kl}(\mu,x)}\Big|_z^{R_{\max}} = 1/2 e^{-nb_n \cdot \mathrm{kl}(\mu,z)}, \tag{4.4}$$

and for $z \in (R_{\min}, \mu]$, it holds that

$$\mathbb{P}(\theta \leq z) = \int_{R_{\min}}^z f(x; \mu, n)\mathrm{d}x = 1/2 e^{-nb_n \cdot \mathrm{kl}(\mu,x)}\Big|_{R_{\min}}^z = 1/2 e^{-nb_n \cdot \mathrm{kl}(\mu,z)}, \tag{4.5}$$

which also implies the PDF of $\mathcal{P}$ is well-defined due to $\int_{R_{\min}}^{R_{\max}} f(x; \mu, n)\mathrm{d}x = \int_{R_{\min}}^{\mu} f(x; \mu, n)\mathrm{d}x + \int_{\mu}^{R_{\max}} f(x; \mu, n)\mathrm{d}x = 1$.

Intuition for the Design of the Sampling Distribution. The tail bounds in (4.4) and (4.5) provide proper anti-concentration and concentration bounds for the sampling distribution $\mathcal{P}$ as long as we have corresponding lower and upper bounds of $e^{-nb_n \cdot \mathrm{kl}(\mu,z)}$. When n is large, we will choose b_n to be close to 0, and thus (4.4) and (4.5) ensure that the sample of the corresponding arm concentrates in the interval $(\mu - \epsilon, \mu + \epsilon)$ with an exponentially small probability $e^{-\mathrm{kl}(\mu-\epsilon,\mu+\epsilon)}$, which is crucial for achieving a tight finite-time regret.

How to Sample from $\mathcal{P}$. We show that sampling from $\mathcal{P}$ is tractable since the CDF of $\mathcal{P}$ is invertible. And thus we even do not need to use approximate sampling methods such as Monte Carlo Markov Chain and Hastings-Metropolis [23]. In particular, according to (4.4) and (4.5), the CDF of $\mathcal{P}(\mu, n)$ is $F(x) = 1 - 1/2 e^{-nb_n \cdot \mathrm{kl}(\mu,x)}$ for $x \geq \mu$ and $F(x) = 1/2 e^{-nb_n \cdot \mathrm{kl}(\mu,x)}$ for $x \leq \mu$. To sample from $\mathcal{P}(\mu, n)$, we can first pick y uniformly random from $[0, 1]$. Then, for $y \geq 1/2$, we solve the equation $y = 1 - 1/2 e^{-nb_n \cdot \mathrm{kl}(\mu,x)}$ for x ($x \geq \mu$), which is equivalent to solving $\log(1/(2(1 - y)))/(nb_n) = \mathrm{kl}(\mu,x)$. For $y \leq 1/2$, we solve the equation $y = 1/2 e^{-nb_n \cdot \mathrm{kl}(\mu,x)}$ for x ($x \leq \mu$), which is equivalent to solving $\log(1/(2y))/(nb_n) = \mathrm{kl}(\mu,x)$. Thus x would be an exact sample from distribution $\mathcal{P}$.

4.3 Regret Analysis of ExpTS for Exponential Family Rewards

Now we present the regret bound of ExpTS for general exponential family bandits. The sampling distribution used in Algorithm 1 is defined in (4.3).

Theorem 4.1. *Let $b_n = (n-1)/n$. Let $\mathcal{P}$ be the sampling distribution defined in Section 4.2. The regret of Algorithm 1 simultaneously satisfies the following finite-time bounds:*

$$R_\mu(T) = \sum_{i \in [K]:\Delta_i > \lambda} O\left(\Delta_i + \frac{V \log(T\Delta_i^2/V)}{\Delta_i}\right) + \max_{i \in [K], \Delta_i \leq \lambda} \Delta_i \cdot T, \qquad (4.6)$$

$$R_\mu(T) = O\left(\sum_{i=2}^{K} \Delta_i + \sqrt{VKT \log K}\right), \qquad (4.7)$$

where $\lambda \geq 16\sqrt{V/T}$, and also satisfies the following asymptotic bound:

$$\lim_{T \to \infty} \frac{R_\mu(T)}{\log T} = \sum_{i=2}^{K} \frac{\Delta_i}{kl(\mu_i, \mu_1)}. \qquad (4.8)$$

Note that ExpTS is an anytime algorithm and simultaneously satisfies the sub-UCB criteria in (1.2), the minimax optimal regret up to a factor $\sqrt{\log K}$, and the asymptotically optimal regret. ExpTS is the first Thompson sampling algorithm that provides finite-time regret bounds for exponential family of rewards. Compared with state-of-the-art MAB algorithms listed in Table 2, ExpTS is comparable to the best known UCB algorithms and no algorithms can dominate ExpTS. In particular, compared with MS [9] and OCUCB [26], ExpTS is asymptotically optimal for exponential family of rewards, while MS is only asymptotically optimal for sub-Gaussian rewards and OCUCB is not asymptotically optimal. We note that Exponential Family does not cover the sub-Gaussian rewards. However, since we only use the tail bound to approximate the reward distribution, ExpTS can also be extended to solve sub-Gaussian reward bandits.

4.4 Gaussian and Bernoulli Reward Distributions

The choice of $\mathcal{P}$ in (4.3) seems complicated for a general exponential family reward distribution, even though we only need the sampling distribution to satisfy a nice tail bound derived from this reward distribution. Nevertheless, when the reward distribution has a closed form such as Gaussian and Bernoulli distributions, we can directly use the posterior in standard Thompson sampling and obtain the asymptotic and finite-time regrets in the previous section.

Theorem 4.2. *If the reward follows a Gaussian distribution with a known variance V, we can set the sampling distribution in Algorithm 1 as $\mathcal{N}(\widehat{\mu}_i(t), V/T_i(t))$. The resulting algorithm (denoted as Gaussian-TS) enjoys the same regret bounds presented in Theorem 4.1.*

Remark 4.3. *Jin et al. [18] shows in Lemma 5 of their paper that for Gaussian rewards, Gaussian-TS has a regret bound at least $\Omega(\sqrt{VKT \log T})$ if the standard regret decomposition [5, 28, 18] is adopted in the proof. With our new regret decomposition and the lower confidence bound introduced in (4.2), we improve the worst-case regret of Gaussian-TS for Gaussian rewards to $O(\sqrt{VKT \log K})$.*

Although Jin et al. [18] can also overcome the under-estimation issue (see (4.1) for details) by one of the following methods, they are either at the cost of sacrificing the asymptotic optimality or not generalizable to exponential family bandits. (1) For Gaussian rewards, MOTS [18] enlarge the variance of Gaussian posterior by a factor of $1/\rho$, where $\rho \in (0, 1)$. However, this will loss the asymptotic optimality. (2) For Gaussian rewards, MOTS-$\mathcal{J}$ [18] introduces the Rayleigh posterior to overcome the under-estimation. Although it does not sacrifice the asymptotic optimality, it is not clear how to generalize the idea to exponential family reward distributions and their experimental results show that compared with Rayleigh posterior, Gaussian posterior actually has a smaller regret empirically. Therefore, the new regret decomposition and the novel lower confidence bound in our paper is a better way to overcome the under-estimation issue of Gaussian-TS.

Theorem 4.4. *If the reward distribution is Bernoulli, we can set the sampling distribution $\mathcal{P}$ in Algorithm 1 as Beta posterior $\mathcal{B}(S_i(t) + 1, T_i(t) + 1)$, where $S_i(t)$ is the number of successes among the $T_i(t)$ plays of arm i. We denote the resulting algorithm as Bernoulli-TS, which enjoys the same regret bounds as in Theorem 4.1*

Remark 4.5. *[5] showed that for Bernoulli rewards, Thompson sampling with Beta posterior is asymptotically optimal and has a minimax regret in order $O(\sqrt{KT \log T})$. Our regret analysis improve the minimax regret to $O(\sqrt{KT \log K})$. Besides, Agrawal and Goyal [5] proves Gaussian-TS applied to the Bernoulli reward setting has a regret $O(\sqrt{KT \log K})$. However, no asymptotic regret was guaranteed in this setting.*

5 Minimax Optimal Thompson Sampling for Exponential Family Rewards

In this section, in order to remove the extra logarithm term in the worst-case regret of ExpTS, we introduce a new sampling distribution that adds a greedy exploration step to the sampling distribution used in ExpTS. Specifically, the new algorithm ExpTS$^+$ is the same as ExpTS but uses a new sampling distribution $\mathcal{P}^+(\mu, n)$. A parameter θ is sampled from $\mathcal{P}^+(\mu, n)$ in the following way: $\theta = \mu$ with probability $1 - 1/K$ and $\theta \sim \mathcal{P}(\mu, n)$ with probability $1/K$.

Over-Estimation of Sub-Optimal Arms. Thompson sampling also faces the over-estimation of sub-optimal arms. To explain, suppose that the sample of each arm i has a probability $p = \mathbb{P}(\theta_i(t) \geq \theta_1(t))$ to become larger than the sample of arm 1. Note that when this event happens, the algorithm chooses the wrong arm and thus incurs a regret. Intuitively, the probability of making a mistake will be $K - 1$ times larger due to the union bound over $K - 1$ sub-optimal arms, which leads to an additional $\sqrt{\log K}$ factor in the minimax regret. To reduce the probability $\mathbb{P}(\theta_i(t) \geq \theta_1(t))$, ExpTS$^+$ adds a greedy step that chooses the ExpTS sample with probability $1/K$ and chooses the arm with the largest empirical average reward with probability $1 - 1/K$. Then we can prove that for sufficiently large s, with high probability $\hat{\mu}_{is} < \theta_1$ and in this case $\mathbb{P}(\theta_i(t) \geq \theta_1(t)) = p/K$. Thus the extra factor $\sqrt{\log K}$ in regret is removed.

We have the following theorem showing that ExpTS$^+$ is asymptotically optimal and minimax optimal simultaneously.

Theorem 5.1. *Let $b_n = (n - 1)/n$. The regret of ExpTS$^+$ satisfies*

$$R_\mu(T) = O\left(\sum_{i=2}^K \Delta_i + \sqrt{VKT}\right), \quad \text{and} \quad \lim_{T \to \infty} \frac{R_\mu(T)}{\log T} = \sum_{i=2}^K \frac{\Delta_i}{kl(\mu_i, \mu_1)}.$$

This is the first time that the Thompson sampling algorithm achieves the minimax and asymptotically optimal regret for exponential family of reward distributions. Moreover, ExpTS$^+$ is also an anytime algorithm since it does not need to know the horizon T in advance.

Remark 5.2 (Sub-Gaussian Rewards). *In the proof of Theorem 5.1, we do not need the strict form of the PDF of the empirical mean reward $\hat{\mu}_{is}$, but only the maximal inequality (Lemma I.1). This means that the proof can be straightforwardly extended to sub-Gaussian reward distributions, where similar maximal inequality holds [19].*

It is worth noting that MOTS proposed by Jin et al. [18] (Thompson sampling with a clipped Gaussian) also achieves the minimax optimal regret for sub-Gaussian rewards, but it can not keep the asymptotic optimality simultaneously with the same algorithm parameters. In particular, to achieve the minimax optimality, MOTS will have an additional $1/\rho$ factor in the asymptotic regret with $0 < \rho < 1$. Moreover, different from ExpTS$^+$, MOTS is only designed for fixed T setting and thus is not an anytime algorithm.

Remark 5.3 (Gaussian and Bernoulli Rewards). *Follow the idea of ExpTS$^+$, we can easily obtain new algorithms Gaussian-TS$^+$ and Bernoulli-TS$^+$ for Gaussian and Bernoulli rewards. Using a similar proof, we can show that they are simultaneously minimax and asymptotically optimal.*

6 Conclusions

We studied Thompson sampling for exponential family of reward distributions. We proposed the ExpTS algorithm and proved it satisfies the sub-UCB criteria for problem-dependent finite-time regret, as well as achieves the asymptotic optimality and the minimax optimality up to a factor of $\sqrt{\log K}$ for exponential family rewards. Furthermore, we proposed ExpTS$^+$ that adds a greedy exploration step to balance between the sample generated in ExpTS and the empirical mean reward for each arm. We proved that ExpTS$^+$ is simultaneously minimax and asymptotically optimal. We also extended our proof techniques to standard Thompson sampling with common posterior distributions and improved existing results. For Gaussian/Bernoulli rewards, we proved Gaussian-TS/Bernoulli-TS satisfies the sub-UCB criteria and enjoys the asymptotically optimal regret and minimax optimal regret $O(\sqrt{KT \log K})$. Although ExpTS$^+$ is simultaneously minimax and asymptotically optimal, it does not satisfies the sub-UCB criteria anymore. It would be an interesting future direction to design a sampling distribution such that TS is asymptotically optimal, minimax optimal, and matches the sub-UCB criteria at the same time.

References

[1] Marc Abeille and Alessandro Lazaric. Linear thompson sampling revisited. In *Artificial Intelligence and Statistics*, pages 176–184. PMLR, 2017. (p. 5.)

[2] Milton Abramowitz and Irene A Stegun. Handbook of mathematical functions with formulas, graphs, and mathematical table. In *US Department of Commerce*. National Bureau of Standards Applied Mathematics series 55, 1965. (pp. 6 and 36.)

[3] Shipra Agrawal and Navin Goyal. Analysis of thompson sampling for the multi-armed bandit problem. In *Conference on learning theory*, pages 39–1, 2012. (pp. 2, 4, and 6.)

[4] Shipra Agrawal and Navin Goyal. Further optimal regret bounds for thompson sampling. In *Artificial intelligence and statistics*, pages 99–107, 2013. (pp. 2, 3, and 4.)

[5] Shipra Agrawal and Navin Goyal. Near-optimal regret bounds for thompson sampling. *Journal of the ACM (JACM)*, 64(5):30, 2017. (pp. 1, 2, 3, 4, 6, 8, 25, and 27.)

[6] Jean-Yves Audibert and Sébastien Bubeck. Minimax policies for adversarial and stochastic bandits. In *COLT*, pages 217–226, 2009. (pp. 2, 3, 4, and 7.)

[7] Peter Auer, Nicolo Cesa-Bianchi, and Paul Fischer. Finite-time analysis of the multiarmed bandit problem. *Machine learning*, 47(2-3):235–256, 2002. (pp. 1 and 2.)

[8] Peter Auer, Nicolo Cesa-Bianchi, Yoav Freund, and Robert E Schapire. The nonstochastic multiarmed bandit problem. *SIAM journal on computing*, 32(1):48–77, 2002. (p. 1.)

[9] Jie Bian and Kwang-Sung Jun. Maillard sampling: Boltzmann exploration done optimally. *arXiv preprint arXiv:2111.03290*, 2021. (pp. 2, 4, 7, and 8.)

[10] Sébastien Bubeck and Che-Yu Liu. Prior-free and prior-dependent regret bounds for thompson sampling. In *Advances in Neural Information Processing Systems*, pages 638–646, 2013. (pp. 4 and 5.)

[11] Olivier Chapelle and Lihong Li. An empirical evaluation of thompson sampling. In *Advances in neural information processing systems*, pages 2249–2257, 2011. (p. 2.)

[12] Rémy Degenne and Vianney Perchet. Anytime optimal algorithms in stochastic multi-armed bandits. In *International Conference on Machine Learning*, pages 1587–1595. PMLR, 2016. (pp. 4 and 7.)

[13] Aurélien Garivier and Olivier Cappé. The kl-ucb algorithm for bounded stochastic bandits and beyond. In *Proceedings of the 24th annual conference on learning theory*, pages 359–376, 2011. (pp. 3 and 4.)

[14] Aurélien Garivier, Hédi Hadiji, Pierre Menard, and Gilles Stoltz. Kl-ucb-switch: optimal regret bounds for stochastic bandits from both a distribution-dependent and a distribution-free viewpoints. *arXiv preprint arXiv:1805.05071*, 2018. (pp. 1 and 2.)

[15] Peter Harremoës. Bounds on tail probabilities in exponential families. *arXiv preprint arXiv:1601.05179*, 2016. (pp. 4 and 5.)

[16] Emil Jeřábek. Dual weak pigeonhole principle, boolean complexity, and derandomization. *Annals of Pure and Applied Logic*, 129(1-3):1–37, 2004. (pp. 6 and 25.)

[17] Tianyuan Jin, Jing Tang, Pan Xu, Keke Huang, Xiaokui Xiao, and Quanquan Gu. Almost optimal anytime algorithm for batched multi-armed bandits. In *International Conference on Machine Learning*, pages 5065–5073. PMLR, 2021. (p. 5.)

[18] Tianyuan Jin, Pan Xu, Jieming Shi, Xiaokui Xiao, and Quanquan Gu. MOTS: Minimax Optimal Thompson Sampling. In *International Conference on Machine Learning*, pages 5074–5083. PMLR, 2021. (pp. 2, 3, 4, 5, 6, 8, and 9.)

[19] Tianyuan Jin, Pan Xu, Xiaokui Xiao, and Quanquan Gu. Double explore-then-commit: Asymptotic optimality and beyond. In *Conference on Learning Theory*, pages 2584–2633. PMLR, 2021. (pp. 4 and 9.)

[20] Emilie Kaufmann. On bayesian index policies for sequential resource allocation. *arXiv preprint arXiv:1601.01190*, 2016. (pp. 2 and 4.)

[21] Emilie Kaufmann, Nathaniel Korda, and Rémi Munos. Thompson sampling: An asymptotically optimal finite-time analysis. In *International conference on algorithmic learning theory*, pages 199–213. Springer, 2012. (pp. 3 and 4.)

[22] Wonyoung Kim, Gi-soo Kim, and Myunghee Cho Paik. Doubly robust thompson sampling with linear payoffs. *Advances in Neural Information Processing Systems*, 34, 2021. (p. 5.)

[23] Nathaniel Korda, Emilie Kaufmann, and Remi Munos. Thompson sampling for 1-dimensional exponential family bandits. In *Advances in neural information processing systems*, pages 1448–1456, 2013. (pp. 2, 3, 4, and 7.)

[24] Tze Leung Lai and Herbert Robbins. Asymptotically efficient adaptive allocation rules. *Advances in applied mathematics*, 6(1):4–22, 1985. (pp. 1 and 3.)

[25] Tor Lattimore. Optimally confident ucb: Improved regret for finite-armed bandits. *arXiv preprint arXiv:1507.07880*, 2015. (p. 4.)

[26] Tor Lattimore. Regret analysis of the finite-horizon gittins index strategy for multi-armed bandits. In *Conference on Learning Theory*, pages 1214–1245, 2016. (pp. 4, 7, and 8.)

[27] Tor Lattimore. Refining the confidence level for optimistic bandit strategies. *The Journal of Machine Learning Research*, 19(1):765–796, 2018. (pp. 1, 2, 3, 4, and 7.)

[28] Tor Lattimore and Csaba Szepesvári. *Bandit algorithms*. Cambridge University Press, 2020. (pp. 3, 8, and 14.)

[29] Odalric-Ambrym Maillard, Rémi Munos, and Gilles Stoltz. A finite-time analysis of multi-armed bandits problems with kullback-leibler divergences. In *Proceedings of the 24th annual Conference On Learning Theory*, pages 497–514, 2011. (p. 3.)

[30] Pierre Ménard and Aurélien Garivier. A minimax and asymptotically optimal algorithm for stochastic bandits. In *International Conference on Algorithmic Learning Theory*, pages 223–237, 2017. (pp. 2, 4, 7, and 36.)

[31] Daniel Russo and Benjamin Van Roy. Learning to optimize via posterior sampling. *Mathematics of Operations Research*, 39(4):1221–1243, 2014. (pp. 4 and 5.)

[32] Siwei Wang and Wei Chen. Thompson sampling for combinatorial semi-bandits. In *International Conference on Machine Learning*, pages 5114–5122, 2018. (p. 2.)

[33] Tong Zhang. Feel-good thompson sampling for contextual bandits and reinforcement learning. *arXiv preprint arXiv:2110.00871*, 2021. (p. 5.)