A Geometric Deep Learning Framework for Generation of Virtual Left Ventricles as Graphs

Soodeh Kalaie[1]   s.kalaie1@leeds.ac.uk
Andy Bulpitt[2]   a.j.bulpitt@leeds.ac.uk
Alejandro F. Frangi [1]   a.frangi@leeds.ac.uk
Ali Gooya [3]   Ali.Gooya@glasgow.ac.uk

[1] *Centre for Computational Imaging and Simulation Technologies in Biomedicine (CISTIB), School of Computing, University of Leeds, UK*

[2] *School of Computing, University of Leeds, UK*

[3] *School of Computing Science, University of Glasgow, UK*

Abstract

Generative statistical models have a wide range of applications in the modelling of anatomies. In-silico clinical trials of medical devices, for instance, require the development of virtual populations of anatomy that capture enough variability while remaining plausible. Model construction and use are heavily influenced by the correspondence problem and establishing shape matching over a large number of training data. This study focuses on generating virtual cohorts of left ventricle geometries resembling different-sized shape populations, suitable for in-silico experiments. We present an unsupervised data-driven probabilistic generative model for shapes. This framework incorporates an attention-based shape matching procedure using graph neural networks, coupled with a $\beta-$VAE generation model, eliminating the need for initial shape correspondence. Left ventricle shapes derived from cardiac magnetic resonance images available in the UK Biobank are utilized for training and validating the framework. We investigate our method's generative capabilities in terms of generalisation and specificity and show that it is able to synthesise virtual populations of realistic shapes with volumetric measurements in line with actual clinical indices. Moreover, results show our method outperforms joint registration-PCA-based models.

Keywords: Attention, Generative modelling, Geometric Deep Learning, Graph Neural Networks, Shape matching, Virtual populations.

1. Introduction

Modelling cardiac anatomy using generative statistical models can have many applications, including identifying diseases, predicting them, and generating population cohorts for electrophysiological and mechanical computer simulations. Machine learning methods combined with computational modelling and simulation bring the possibility of gaining valuable information about new therapies and medical devices through In-Silico Clinical Trials (ISCTs) (Viceconti et al., 2016; Pappalardo et al., 2019). Therefore, virtual populations of anatomical shapes (typically represented as computational meshes) are a key enabler for conducting ISCTs of clinical devices.

However, building rich or descriptive generative shape models from inconsistent anatomical structures is challenging for several reasons. First, due to the fact that real-world anatomical shapes derived from different subjects do not generally share any topological correspondence, this is a challenging task for existing techniques to generate coherent,

anatomically plausible shape populations. In addition, most techniques demand access to large volumes of training data, thus the process would require expensive and laborious annotation of medical imaging data. Also, it can still be computationally challenging to create synthetic samples that are clinically meaningful and that fully represent the characteristics of each individual patient. Therefore, this study aims to address the problem of generating virtual patient cohorts of left ventricle (LV) geometries resembling different-sized shape populations. These models allow to perform in-silico clinical trials on the so-called digital twins (Corral-Acero et al., 2020).

While PCA-based statistical shape models have been extensively used for shape generation (Piazzese et al., 2017; Gooya et al., 2017; Cosentino et al., 2020), deep learning approaches for generative modelling have gained increasing attention in recent years (Harsh-vardhan et al., 2020). A few studies have adopted these approaches for generating virtual populations of anatomy. Presenting cardiac biventricular anatomy as a point cloud, a geometric deep learning method is proposed for generating populations of realistic biventricular anatomies in (Beetz et al., 2021). The generation of personalized anatomies is further enhanced by adding subpopulation-specific characteristics as conditional inputs. Using binary masks of aortas as inputs, Romero *et al.* (Romero et al., 2021) explored the generation efficiency of the generative adversarial network (GAN) (Goodfellow et al., 2014). This method specifically addressed the generation of a cohort of patients meeting a specific clinical criterion. Danu *et al.* (Danu et al., 2019) employed deep generative models (VAE (Kingma and Welling, 2013) and GAN) for generating voxelised vessel surfaces, where they represented the unstructured surface mesh as a three-dimensional (3D) image. Although the results show potential for employing deep generative models on 3D surfaces, these models can not deal with complex data structures like bifurcations. In conclusion, firstly, these methods are limited by requiring a tedious pre-processing step to obtain dense point correspondence between training shapes. Secondly, they can only be applied to data with the same shape structure. Hence, presenting a meaningful shape matching (i.e. shape correspondence) across training data is often a prerequisite for these methods.

A number of problems can be categorized under the scope of shape correspondence. However, a unified approach can be achieved by considering the problem statement: given input shapes $\{g_k\}_{k=1}^K$, establish a meaningful relation $\mathcal{F}$ between their elements (such as points, feature points, etc). The correspondence can be obtained directly based on the similarity of the elements, or it can be derived from the proximity of the aligned elements by aligning the shapes first. Additionally, we can iterate between the two procedures.

In the first scenario, the relation $\mathcal{F}$ is derived from aligning the shapes in a rigid or non-rigid manner. Some statistical approaches align two point sets via their Gaussian mixture representations (Myronenko and Song, 2010; Ma et al., 2020). Other approaches are taken in (Rusinkiewicz and Levoy, 2001; Zhang et al., 2021) for aligning point sets using optimising local quadratic distances. Moreover, due to the complexity of deformations in the optimisation process, the optimisation can easily get stuck in local optima. In another group, similarity-based methods estimate a pairwise assignment between shapes or their collected features to derive correspondences. More recent works on graph matching are based on deep learning methods to find the optimal point-to-pint correspondences (Wang et al., 2019; Zanfir and Sminchisescu, 2018). These approaches develop supervised graph matching networks based on displacement rather than a registration task. However, the

proposed graph matching methods are performed offline and remain unaltered during shape generation. Further, a pair-wised graph matching framework proposed in (Bai et al., 2018, 2019) is a learning-based framework rather than a pairwise graph distance computation. These methods employed multi-scale graph convolutional network (GCN) layers and then calculated multiple similarity matrices, increasing time complexity for large-scale graphs.

Compared with existing approaches, this study proposes an unsupervised geometric deep learning framework to generate virtual cohorts of left ventricle structures from different-sized training shapes. We consider the structures of the shapes within the context of the graphs. To the best of our knowledge, this is the first end-to-end deep learning framework capable of finding shape matching and generating anatomical shapes from different-sized shapes population without correspondence. The key contributions of this study are: (i) The framework presents a novel unsupervised learning-based shape matching procedure in the absence of any optimisation, which derives a learnable set of correspondences using graph neural networks (GNNs) and attention mechanisms. (ii) Using the soft attention mechanism, we present a domain transformation across the training data to address the problem of shape generation from different-sized shapes. (iii) We establish high-quality shape matching across the training data, and our non-linear generative framework is able to synthesise plausible LV shapes. Although the proposed generative framework is demonstrated here on left ventricle structures, it is generic in design and can be applied similarly to other anatomical shape ensembles.

2. Method

Our proposed framework consists of an unsupervised geometric deep learning network embedded in (i) an Attention-based Shape Matching (ASM) mechanism for deriving a learnable set of correspondences (ii) followed by a soft attention mechanism for domain transformation and β-VAE (Higgins et al., 2016) generation framework for synthesising 3D surface models of the shapes. Given a set of observed 3D surface meshes, we seek to develop a shape generative model using graph representation.

2.1. Attention-based Shape Matching

Presenting the 3D surface mesh as a graph, we propose a matching procedure to determine correspondence based on the similarity measure of local node embeddings, without the need to solve an optimisation problem during inference. To compute nodal embeddings, GNNs enable us to efficiently and flexibly aggregate information through graph nodes and edges, which generate a powerful representation of shapes. Once the graph embedding is learned, an attention mechanism is applied to those embedded features to learn correspondence across the population.

Given a training set of different-sized graphs $G = \{g_k\}_{k=1}^{K}$, where $g_k = (V_k, E_k)$ is the k-th graph, with $|V_k|$ nodes, vertex Euclidean geometry feature matrix $\mathbf{X}_k \in \mathbb{R}^{|V_k| \times 3}$ and E_k denotes the set of edges, connecting the vertices. The sparse adjacency matrix $\mathbf{A}_k \in \{0,1\}^{|V_k| \times |V_k|}$ represents the edge connections. In order to determine where and what shape matching should focus on, an attention mechanism is utilized. We model our attention-based matching procedure by computing similarities between nodes in the k-th observed graph g_k and the template graph g_t based on nodal embeddings. Therefore,

given the latent embeddings of nodes $\mathbf{Z}_k = \Psi(\mathbf{X}_k, \mathbf{A}_k)$ and $\mathbf{Z}_t = \Psi(\mathbf{X}_t, \mathbf{A}_t)$, computed by a shared graph neural network Ψ for the template graph and the observed graph, respectively, we obtain the soft correspondence (i.e. attention maps), as the mapping function in the embedded-space paradigm

$$\mathbf{C}_k = Softmax(\lambda \mathbf{Z}_t \mathbf{Z}_k^T). \tag{1}$$

Where $\mathbf{Z}_k \in \mathbb{R}^{|V_k| \times d_z}$, $\mathbf{Z}_t \in \mathbb{R}^{|V_t| \times d_z}$, $\mathbf{C}_k \in [0,1]^{|V_t| \times |V_k|}$ and hyper-parameter λ sets empirically. d_z denotes the dimension of the latent vector $\mathbf{z}$. In this study, we exploit the ability of spatial-based geometric deep learning methods to handle inconsistent graph populations, where the convolution is performed in local Euclidean neighbourhoods. While the spectral-based approaches are limited to fixed graph structures due to filtering in the spectral domain. We consider a variational graph auto-encoder network Ψ as a Spatial-based GNN (SpaGNN) to perform graph convolution locally on each node. That is, the convolution operator learns features from the preceding network layer to dynamically determine the association between filter weights and graph neighbourhood, rather than relying on static predefined local pseudo-coordinate systems. Subsequently, to normalise shapes structurally, an attention mechanism is employed for domain transformation.

2.2. Shape Generation

The soft correspondence matrix $\mathbf{C}_k$ is a map from the node function space $\mathcal{F}(\mathbb{R}^{|V_k|})$ to node function space $\mathcal{F}(\mathbb{R}^{|V_t|})$ thus allows for domain transformations. To focus more on the relevant features of the shape, soft attention is implemented. In soft attention, irrelevant areas are discredited by multiplying the corresponding shape features with a low weight. Hence, to obtain shapes in the template domain, the soft attention mechanism directly passes node features vector $\mathbf{x} \in \mathcal{F}(g)$ along with the soft correspondences

$$\mathbf{x}'_j = \sum_{n=1}^{|V_k|} C_{jn} \mathbf{x}_n \; ; j = \{1, ..., |V_t|\} \tag{2}$$

where $\mathbf{x}' \in \mathcal{F}(g')$ represents the node features vector in the other domain. Each structurally normalised shape g'_k is presented by matrix feature representation $\mathbf{X}'_k \in \mathbb{R}^{|V_t| \times 3}$. Finally, a generation network, designed in β-VAE framework, learns a probability density function from a set of $\{g'_k\}_{k=1}^K$ graphs, which allows us to generate cohorts of artificial shapes.

2.3. Loss Function

A hierarchical unsupervised framework Attention-based Shape Matching (ASM) and Generation (G) is trained by minimizing the cost function $\mathcal{L} = \mathcal{L}_{ASM} + \mathcal{L}_G$, where $\mathcal{L}_{ASM}$ and $\mathcal{L}_G$ in the right hand side are defined subsequently.

Shape matching cost: In the shape matching procedure, a refinement strategy is also considered in order to avoid finding false correspondences. To achieve this, loss $\mathcal{L}_{SM}$ is computed as

$$\mathcal{L}_{ASM} = \mathcal{L}_\Psi + \mathcal{L}_{Ref} = \frac{1}{2} \sum_{k=1}^K \sum_{n=1}^{|V_k|} \|\mathbf{x}_{kn}^{rec} - \mathbf{x}_{kn}\|^2 + w D_{KL} + CD(g'_k, g_k) + Lap(g'_k). \tag{3}$$

Where $\mathcal{L}_{Ref}$ refers to the refinement strategy consisting of Chamfer and Laplacian losses. Chamfer loss measures the distance of vertices between two graphs: $CD(g, g') = \sum_{\mathbf{x} \in g} \min_{g'} \|\mathbf{x} - \mathbf{x}'\|^2 + \sum_{\mathbf{x}' \in g'} \min_g \|\mathbf{x} - \mathbf{x}'\|^2$ and $Lap(g'_k)$ is a laplacian smoothness loss to result in smoother surface reconstructions (Taubin, 1995).

Generation cost: Loss function $\mathcal{L}_G$ follows the original loss of the β-VAE, where hyperparameter β makes a balance between low reconstruction error and high latent space quality, which emphasizes discovering disentangled latent factors. Assuming VAE is made of an encoder-decoder pair, we define our architecture as a pair E, G neural networks, respectively. Following this, we define:

$$\mathcal{L}_G = \frac{1}{2} \sum_{k=1}^{K} \sum_{j=1}^{|V_t|} \left\| G(\mathbf{x}'_{kj}) - \mathbf{x}'_{kj} \right\|^2 + \beta D_{KL} \tag{4}$$

where D_{KL} denotes the Kullback-Leibler, which computes the divergence between the Gaussian prior $\mathcal{N}(0, I)$ and posterior distributions of the latent space.

3. Experiments and Results

In this section, we describe the experimental settings and the evaluation of our method on the clinical dataset.

Dataset: We utilized 1000 LV 3D surface mesh dataset obtained from cardiac magnetic resonance (CMR) images of the UK Biobank (UKB) (Petersen et al., 2015), using the pipeline described in (Zakeri et al., 2022). All the LV meshes are related to the end-diastolic phase of the cardiac cycle. Mesh cardinalities vary from 1000 to 2000 points.

Exprimental Setup: The network Ψ uses the spatial graph convolution layers (Verma et al., 2018), with $64, 64, 128, 128$-dim hidden layers for the encoder (which are mirrored for the decoder) with convolutional filter weight matrices of size 8. To build the shape generation network fully-connected layers are used in the structure of the β-VAE network with hidden layers of size $512, 256, 768, 128, 64$ for the encoder. The decoder is a mirrored version of the encoder. All the internal layers use batch normalisation and Leaky ReLU as activation layers. We empirically set β value as $2e^{-6}$, w and learning rate to $1e^{-3}$ and use the ADAM optimiser (Kingma and Ba, 2014) to train the model.

3.1. Results and Discussion

A number of experiments were conducted to evaluate the performance of the generative shape framework proposed in this study. Since existing works on shape generative modelling can only be applied to data with the same shape structure, we compared our model with a baseline model, where the pipeline includes registration and PCA models. We evaluate our method in terms of both its matching (i.e. correspondence establishment) and generation performances.

3.1.1. Matching quality

We investigated the proposed Attention-based Shape Matching (ASM) framework in two settings, With/WithOut Refinement, and compared them with the rigid Registration-based

Figure 1: Examples show the comparison between different shape matching approaches for deriving correspondence. Cyan-coloured meshes present input g_k with cardinality $|V_k| = 1039, 1216, 1353, 1497$ and 1503 respectively from left to right. Grey-coloured shapes are the normalised meshes g'_k with cardinality $|V_t| = 1093$ obtained from different methods. Notice endocardial, epicardial, LV base, and apex landmarks.

Table 1: Shape Matching Quality: comparison between different methods using two distance metrics HD and CD (mean $\pm$ std) in $[mm]$. **Bold** values show a significant difference between the methods with a p-value < 0.001 using the statistical paired t-test.

	RSM	ASM(WoR)	ASM(WR)
HD	8.11 ± 2.13	8.32 ± 1.77	$\mathbf{6.54 \pm 1.57}$
CD	12.04 ± 2.63	9.91 ± 1.54	$\mathbf{4.06 \pm 0.57}$

Shape Matching (RSM) proposed in (Myronenko and Song, 2010). The correspondence maps obtained from different methods RSM and ASM(WoR/WR) are utilized to transform actual shapes g_k from the domain $\mathbb{R}^{|V_k|}$ to $\mathbb{R}^{|V_t|}$. For a qualitative evaluation, Figure 1 visualises some examples of the network input (g_k) and normalised surface mesh (g'_k) for five sample cases, obtained from the different methods. Visual inspection of results shows that normalised shapes obtained from our framework (especially with the refinement strategy introduced in section 2.3) are more realistic and present meaningful correspondences for anatomical landmarks on LV shapes (e.g. endocardial, epicardial, LV base, and apex), whereas the results obtained from RSM show some disorders and lacking details. We further evaluated the quality of obtained shapes in the template domain using two distance metrics: Hausdorff distance (HD) and Chamfer distance (CD). Table 1 summarises the accuracy of shapes in the template domain obtained by different methods. Obtained results show that our similarity-based method maintains high accuracy when compared with the registration-based method. These results suggest that the refinement strategy produces more accurate features derived from the SpaGNN network, thus providing high-quality correspondences. By achieving lower mean Hausdorff and Chamfer distances, our method demonstrates good

Table 2: Correspondence Quality: comparison between generative models in terms of generalisation ability and specificity using three distance metrics HD, ED and ED^* (mean $\pm$ std) in $[mm]$.

		RSMP	ASMG(WoR)	ASMG(WR)
	HD	8.02 ± 2.14	7.99 ± 1.83	7.08 ± 1.58
Generalisation	ED	2.15 ± 0.20	2.11 ± 0.14	2.05 ± 0.13
	ED^*	2.38 ± 0.24	2.36 ± 0.17	2.23 ± 0.11
	HD	5.96 ± 0.59	5.82 ± 0.70	5.80 ± 0.99
Specificity	ED	2.28 ± 0.22	2.18 ± 0.13	2.25 ± 0.20
	ED^*	2.23 ± 0.28	2.47 ± 0.18	2.55 ± 0.20

normalisation quality in arbitrary target domains, while the low standard deviation values demonstrate its robustness. This is because our method followed an efficient spatial-based geometric deep learning strategy and considered a learning-based fully-differentiable shape matching procedure that aimed to reach a data-driven neighbourhood between matched node pairs without the need to solve any optimisation.

3.1.2. Generation quality

In order to evaluate the generative performance of our framework (ASMG), we provide a quantitative assessment in terms of generalisation, specificity (Styner et al., 2003) and clinical relevance.

The generalisation ability of a generative model indicates the capability of the model to represent unseen samples and thus capture the variability in LV shapes based on its error when reconstructing unseen actual test data. Model specificity determines the anatomical plausibility of the virtual LV cohorts by comparing them to the actual samples in the training set. In order to report generalisation and specificity, three distance measures are considered: Hausdorff distance (HD), the average of minimum Euclidean (ED) distance and its symmetric distance (ED^*), where $ED^*(g, g') = ED(g', g)$. High-performance generative models refer to models that generate synthetic shapes with simultaneously low specificity and generalisation errors. Table 2 summarises the generalisation and specificity errors of all methods investigated in this study (ASMG(WoR) and ASMG(WR)) and the baseline model RSMP, where the generative model RSMP is built from synergy of Registration-based Shape Matching and PCA generator. We observe that the ASMG model achieves the highest generalisability and specificity (i.e. lower concurrent specificity and generalisation errors for the majority of distances) for both investigated scenarios. As expected, due to lower specificity errors, our similarity-based generative model presents more realistic synthesised LV shapes when compared with the model based on registration. The lower specificity error can be explained as follows: considering shapes as graphs supports our unsupervised shape matching framework to learn better disentangled latent representations and thus derive a more effective form of soft correspondences between shapes, which in turn preserves more details during the normalisation process. As a result, shapes generated from structurally normalised populations have a greater degree of plausibility. Compared to PCA, which is a linear projection of shapes onto lower-dimensional subspaces, our generative model is based on graph convolution networks and $\beta-$VAE, which can capture non-linear variations

Table 3: Clinical acceptance rates $\mathcal{A}$ [in %] achieved by each generative model for LV volumes.

	RSMP	ASMG(WoR)	ASMG(WR)
$\mathcal{A}_{[\min,\max]}$	93.95	100	**100**
$\mathcal{A}_{M\pm2B}$	47.73	88.88	**91.62**
$\mathcal{A}_{\mu\pm2\sigma}$	24.38	56.50	**62.82**

in shapes. A proper balance between latent space and reconstruction quality is achieved by using the $\beta-$VAE generator, resulting in realistic randomly generated samples.

Inspired by (Romero et al., 2021), we present the clinical relevance assessment for the synthesised LV shapes in this study. Given the actual cohort UKB, the acceptance rate $\mathcal{A}$ determines the percentage of synthetic samples in virtual cohorts with cardiac indices (e.g. volume), within a 90% confidence interval of the distribution of the cardiac indices observed in the actual population. To compute the acceptance rate $\mathcal{A}$, three different confidence intervals are considered. First, $[\min, \max]$ interval presents the range of the observed actual biomarkers (e.g. LV volume). Relying on Chebyshev's inequality, we define two confidence intervals $\mu \pm 2\sigma$ and $M \pm 2B$, based on the corresponding mean (μ), standard deviation (σ) and the mode (M) observed in the actual population (see Figure S1). Where $B = \sqrt{\sigma^2 + (M - \mu)^2}$ measures the variability across the data. Table 3 shows the efficiency of each method measured using the different acceptance criteria. The clinical acceptance rates of LV virtual cohorts synthesised by our generative model are higher than RSMP method. Although the specificity errors in Table 2 indicate that there is no huge difference between the plausibility of LV shapes synthesised by the model with and without refinement strategy, the clinical acceptance rates estimated for ASMG with refinement are consistently higher than those without refinement across the LV volume indices (refer to Table 3). This indicates that the generative model proposed in this study, when considering the refinement strategy, provides better fidelity in preserving the distributions of clinically relevant cardiac indices in the synthesised virtual cohorts relative to the UKB population. It is therefore more suitable for ISCTs that require higher statistical fidelity based on anatomical characteristics.

4. Conclusion

This study proposed a novel unsupervised probabilistic deep generative model, capable of generating virtual LV shape cohorts, resembling the different-sized actual data. The framework is a synergy of attention-based graph convolutional networks and generator modules which do not require any prior landmarking, making it significantly efficient. Furthermore, this method is capable of working on 3D image-derived surface meshes due to its use of graphs instead of highly sparse and memory-intensive voxel grids. Additionally, using spatial-based graph convolutional networks in the matching procedure made the proposed method well suited for handling inconsistent shape structures. The study demonstrated the suitability and applicability of the proposed generative model in conducting ISCTs, with virtual cohorts, through a comparative analysis. Further extensions to our work would include richer descriptions of vertex geometry, such as normal vertex along the vertex geometry, and different strategies for sampling generation.

Acknowledgments

The UKB CMR dataset has been provided under UK Biobank access application number 11350.

References

Yunsheng Bai, Hao Ding, Yizhou Sun, and Wei Wang. Convolutional set matching for graph similarity. *arXiv preprint arXiv:1810.10866*, 2018.

Yunsheng Bai, Hao Ding, Song Bian, Ting Chen, Yizhou Sun, and Wei Wang. Simgnn: A neural network approach to fast graph similarity computation. In *Proceedings of the Twelfth ACM International Conference on Web Search and Data Mining*, pages 384–392, 2019.

Marcel Beetz, Abhirup Banerjee, and Vicente Grau. Generating subpopulation-specific biventricular anatomy models using conditional point cloud variational autoencoders. In *International Workshop on Statistical Atlases and Computational Models of the Heart*, pages 75–83. Springer, 2021.

Jorge Corral-Acero, Francesca Margara, Maciej Marciniak, Cristobal Rodero, Filip Loncaric, Yingjing Feng, Andrew Gilbert, Joao F Fernandes, Hassaan A Bukhari, Ali Wajdan, et al. The 'digital twin' to enable the vision of precision cardiology. *European heart journal*, 41(48):4556–4564, 2020.

Federica Cosentino, Giuseppe M Raffa, Giovanni Gentile, Valentina Agnese, Diego Bellavia, Michele Pilato, and Salvatore Pasta. Statistical shape analysis of ascending thoracic aortic aneurysm: correlation between shape and biomechanical descriptors. *Journal of Personalized Medicine*, 10(2):28, 2020.

Manuela Danu, Cosmin-Ioan Nita, Anamaria Vizitiu, Constantin Suciu, and Lucian Mihai Itu. Deep learning based generation of synthetic blood vessel surfaces. In *2019 23rd International Conference on System Theory, Control and Computing (ICSTCC)*, pages 662–667. IEEE, 2019.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. *Advances in neural information processing systems*, 27, 2014.

Ali Gooya, Karim Lekadir, Isaac Castro-Mateos, Jose Maria Pozo, and Alejandro F Frangi. Mixture of probabilistic principal component analyzers for shapes from point sets. *IEEE transactions on pattern analysis and machine intelligence*, 40(4):891–904, 2017.

GM Harshvardhan, Mahendra Kumar Gourisaria, Manjusha Pandey, and Siddharth Swarup Rautaray. A comprehensive survey and analysis of generative models in machine learning. *Computer Science Review*, 38:100285, 2020.

Irina Higgins, Loic Matthey, Arka Pal, Christopher Burgess, Xavier Glorot, Matthew Botvinick, Shakir Mohamed, and Alexander Lerchner. beta-vae: Learning basic visual concepts with a constrained variational framework. 2016.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Xinke Ma, Shijin Xu, Jie Zhou, Qinglu Yang, Yang Yang, Kun Yang, and Sim Heng Ong. Point set registration with mixture framework and variational inference. *Pattern Recognition*, 104:107345, 2020.

Andriy Myronenko and Xubo Song. Point set registration: Coherent point drift. *IEEE transactions on pattern analysis and machine intelligence*, 32(12):2262–2275, 2010.

Francesco Pappalardo, Giulia Russo, Flora Musuamba Tshinanu, and Marco Viceconti. In silico clinical trials: concepts and early adoptions. *Briefings in bioinformatics*, 20(5): 1699–1708, 2019.

Steffen E Petersen, Paul M Matthews, Jane M Francis, Matthew D Robson, Filip Zemrak, Redha Boubertakh, Alistair A Young, Sarah Hudson, Peter Weale, Steve Garratt, et al. Uk biobank's cardiovascular magnetic resonance protocol. *Journal of cardiovascular magnetic resonance*, 18(1):1–7, 2015.

Concetta Piazzese, M Chiara Carminati, Mauro Pepi, and Enrico G Caiani. Statistical shape models of the heart: applications to cardiac imaging. In *Statistical Shape and Deformation Analysis*, pages 445–480. Elsevier, 2017.

Pau Romero, Miguel Lozano, Francisco Martínez-Gil, Dolors Serra, Rafael Sebastián, Pablo Lamata, and Ignacio García-Fernández. Clinically-driven virtual patient cohorts generation: An application to aorta. *Frontiers in Physiology*, page 1375, 2021.

Szymon Rusinkiewicz and Marc Levoy. Efficient variants of the icp algorithm. In *Proceedings third international conference on 3-D digital imaging and modeling*, pages 145–152. IEEE, 2001.

Martin A Styner, Kumar T Rajamani, Lutz-Peter Nolte, Gabriel Zsemlye, Gábor Székely, Christopher J Taylor, and Rhodri H Davies. Evaluation of 3d correspondence methods for model building. In *Biennial International Conference on Information Processing in Medical Imaging*, pages 63–75. Springer, 2003.

Gabriel Taubin. A signal processing approach to fair surface design. In *Proceedings of the 22nd annual conference on Computer graphics and interactive techniques*, pages 351–358, 1995.

Nitika Verma, Edmond Boyer, and Jakob Verbeek. Feastnet: Feature-steered graph convolutions for 3d shape analysis. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 2598–2606, 2018.

Marco Viceconti, Adriano Henney, and Edwin Morley-Fletcher. In silico clinical trials: how computer simulation will transform the biomedical industry. *International Journal of Clinical Trials*, 3(2):37–46, 2016.

Runzhong Wang, Junchi Yan, and Xiaokang Yang. Learning combinatorial embedding networks for deep graph matching. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 3056–3065, 2019.

Arezoo Zakeri, Alireza Hokmabadi, Nishant Ravikumar, Alejandro F Frangi, and Ali Gooya. A probabilistic deep motion model for unsupervised cardiac shape anomaly assessment. *Medical Image Analysis*, 75:102276, 2022.

Andrei Zanfir and Cristian Sminchisescu. Deep learning of graph matching. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 2684–2693, 2018.

Juyong Zhang, Yuxin Yao, and Bailin Deng. Fast and robust iterative closest point. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2021.

5. Supplementary Material

The resulting volume indices distributions are presented in Figure S1 by means of violin charts. As shown in this figure, horizontal lines indicate the boundaries of the different acceptance criteria. Comparing actual to synthetic distributions for volume variables shows that our model generates more realistic samples from the population of LV while capturing sufficient variability. PCA-based generative model RSMP, with higher generalisation and specificity errors, is reflected in the wider range (unrealistic) of values observed for volume indices in the synthesised virtual population. In addition, a visualization of the generated (synthetic) samples by the trained ASMG(WR) model are shown in Figure S2.

Figure S1: Violin plots for the distribution of LV volume indices on the actual UKB samples, alongside with those generated using methods: RSMP, ASMG(WoR) and ASMG(WR).

Figure S2: Examples of virtual samples generated by the ASMG(WR) generator model.