# TangramPuzzle: Evaluating Multimodal Large Language Models with Compositional Spatial Reasoning

## Abstract

Multimodal Large Language Models (MLLMs) have achieved remarkable progress in visual recognition and semantic understanding. Nevertheless, their ability to perform precise compositional spatial reasoning remains largely unexplored. Existing benchmarks often involve relatively simple tasks and rely on semantic approximations or coarse relative positioning, while their evaluation metrics are typically limited and lack rigorous mathematical formulations. To bridge this gap, we introduce **TangramPuzzle** [1], a geometry-grounded benchmark designed to evaluate compositional spatial reasoning through the lens of the classic Tangram game. We propose the Tangram Construction Expression (TCE), a symbolic geometric framework that grounds tangram assemblies in exact, machine-verifiable coordinate specifications, to mitigate the ambiguity of visual approximation. We design two complementary tasks: Outline Prediction, which demands inferring global shapes from local components, and End-to-End Code Generation, which requires solving inverse geometric assembly problems. We conduct extensive evaluation experiments on advanced open-source and proprietary models, revealing an interesting insight: MLLMs tend to prioritize matching the target silhouette while neglecting geometric constraints, leading to distortions or deformations of the pieces.

## 1 Introduction

Multimodal Large Language Models (MLLMs) have achieved strong performance on a broad range of vision–language tasks, including visual understanding (Wang et al., 2025b; Fang et al., 2025; Ding et al., 2025), document question answering (Wu et al., 2025b; Huang et al., 2025a), OCR (Chen et al., 2025a; Huang et al., 2025b; Greif et al., 2025), and chart interpretation (Chen et al.,

Figure 1: Illustration of the two spatial reasoning tasks. (a) Task 1 global shape inference; (b) Task 2 constrained shape decomposition.

2025b; Zhao et al., 2025). Recently, both training and evaluation have been increasingly shifting from semantic recognition toward more demanding tasks that require precise spatial understanding and reasoning, such as visual grounding (Tang et al., 2025b; Xu et al., 2025c; Ma et al., 2025b), GUI agent (Cheng et al., 2025a; Xiao et al., 2025), and visual reasoning in complex scenes (Kuang et al., 2025; Li et al., 2024). Spatial reasoning is not merely about recognizing objects, but about constructing and validating structured geometric relationships that support reliable decision making.

Despite rapid progress, existing spatial reasoning tasks for MLLMs still exhibit several limitations. First, many tasks focus on coarse relational concepts (e.g., left/right, front/behind, adjacency) (Liu et al., 2025; Deng et al., 2025; Wu et al., 2025a),

---

[1]We will open-source the data after the paper is published.

which do not fully capture reasoning under strict geometric and physical constraints. Second, spatial problems are often specified using natural language descriptions or multiple-choice formats without a formal geometric representation (Rodionov et al., 2025; Ma et al., 2025a), relying more on linguistic reasoning ability than visual reasoning. In addition, evaluation commonly relies on text answer matching or human/LLM judgment, which is particularly problematic for constructive tasks where multiple valid solutions may exist. ***These issues make it difficult to precisely measure whether a model truly "compositionally reasons" in space or merely exploits superficial cues.***

In this work, we study a classic yet still underexplored problem of compositional spatial reasoning, for which tangram puzzles (Zhao et al., 2022; Bofferding and Aqazade, 2023; Bofferding and Zhu, 2023) provide a particularly suitable instantiation. The tangram serves as a minimalist yet highly expressive abstraction of real-world spatial assembly. This task requires the precise arrangement of seven fixed rigid polygonal pieces into a target silhouette through Euclidean transformations (translation, rotation, and optionally reflection), while satisfying strict constraints such as non-overlap, full coverage, and topological validity. These fundamental capabilities form the functional basis for solving critical real-world problems such as CAD-like mechanical assembly, robotic manipulation planning, and structural chart reconstruction. By mastering these atomic spatial operations and constraint-satisfaction principles within a controlled environment, we can effectively probe a model's underlying potential for more complex, embodied spatial planning in the physical world.

However, prior tangram-related resources and studies only focus on overall interpretation of shapes or perceptual approximations (Zhang et al., 2024; Ji et al., 2022), and typically lack (i) a standardized, machine-verifiable geometric representation, and (ii) a strict evaluation protocol that validates rigidity, physical feasibility, and solution correctness. Moreover, natural-language descriptions of complex spatial layouts are often ambiguous, reducing evaluation precision and reliability.

To address these gaps, we introduce TangramPuzzle, a benchmark designed to evaluate compositional spatial reasoning in MLLMs under rigorous geometric constraints. Central to our framework is the Tangram Construction Expression (TCE), a symbolic geometry schema that formalizes the as-sembly process. By transitioning from descriptive prose to an algebraic symbolic system, TCE represents each instance with exact coordinates and structural relations, effectively eliminating floating-point errors and linguistic vagueness. Built upon TCE, the benchmark includes two complementary tasks, as shown in Figure 1: (1) Outline Prediction, where models infer the global silhouette from a given final arrangement of pieces; and (2) End-to-End Tangram Solution Generation, where models construct a complete assembly that exactly fills a given target outline. We evaluate outputs with a constraint-based verifier that checks syntactic validity, rigid-shape preservation, and physical feasibility (e.g., non-overlap and connectivity), and then measures silhouette fidelity using IoU and Hausdorff distance, avoiding ill-posed comparisons under multi-solution ambiguity. TangramPuzzle is constructed through a multi-stage pipeline involving source filtering, an interactive annotation tool with snapping, symbolic normalization into exact expressions, and human-in-the-loop validation. Extensive experiments across a wide range of MLLMs show that TangramPuzzle remains highly challenging, revealing systematic failure modes in both compositional outline reasoning and constraint-satisfying solution generation. Our main contributions are as follows:

- We introduce TangramPuzzle, a tangram-inspired benchmark for compositional spatial reasoning in MLLMs, with a rigorous and machine-verifiable math representation.

- We design the data construction pipeline for two tasks that jointly evaluate discriminative global-shape inference and constructive inverse assembly generation.

- We conduct comprehensive evaluation of advanced MLLMs, highlighting persistent limitations in complex spatial reasoning.

## 2 Method

### 2.1 Task Definition

Tangram is a classic dissection puzzle in which seven rigid polygons must be assembled to form a target shape. Although simple in form, tangram assembly mirrors practical tasks such as assembling parts into a target structure, where each component must be placed with the correct orientation and position for the overall configuration to be valid, mak-

ing it an ideal testbed for compositional spatial reasoning. TangramPuzzle consists of two challenging tasks designed to evaluate the spatial reasoning capabilities of MLLMs, ranging from passive spatial perception to active solution generation.

**Geometry Description by TCE Formula**   While natural language is expressive, verbal descriptions alone are often too ambiguous for geometric assembly. For example, "place the triangle above the square" may refer either to a triangle directly touching the square from above or to one located some distance above it, making reliable evaluation difficult because multiple geometrically distinct configurations may satisfy the same description. Moreover, TangramPuzzle is governed by strict Euclidean and topological constraints, motivating a formal, coordinate-based representation that grounds visual inputs in precise mathematical formulations and supports unambiguous task definition, automatic verification, and fine-grained evaluation of spatial reasoning abilities. To represent tangram configurations in a precise and machine-verifiable manner, we introduce the Tangram Construction Expression (TCE), a symbolic geometry description language for 2D tangram assembly. Each TCE instance consists of five core components: instance_id, target_outline, initial_state, final_state, and adjacency_graph.

The field **instance_id** uniquely identifies each puzzle instance and serves as a stable key for indexing, retrieval, and evaluation. Both **initial_state** and **final_state** describe the geometric states of the seven tangram pieces before and after assembly. In TCE, each piece is specified by its piece type, a set of vertex coordinates, explicit edge relations, and a center point. In addition, final_state includes a transform_matrix that parameterizes the rigid motion applied to each piece to reach the assembled configuration, including translation, rotation angle, and optional reflection. Because tangram geometries frequently involve irrational numbers, finite decimal representations induce precision loss. To ensure geometric rigor, TCE encodes all quantities as exact algebraic expressions in LaTeX. The **target_outline** specifies the global silhouette produced by the assembled tangram. It is represented by the outline's vertex coordinates together with its edge relations. The **adjacency_graph** captures local interactions between pieces in the final configuration, indicating which pieces are adjacent. The representation of TCE is shown in Figure 2.

$$\mathbf{TCE} = \langle \text{id}, \Omega_{target}, \Sigma_{init}, \Sigma_{final}, G_{adj} \rangle$$
$$\text{id} = \text{"swan\_cfg\_01"}$$
$$\Omega_{target} = \{V : [(0,0), (4, 2\sqrt{2}), ...], E : [(v_0, v_1), ...]\}$$
$$\Sigma_{final} = \{p_{T1} : \langle \mathbf{M} = \begin{bmatrix} \frac{\sqrt{2}}{2} & -\frac{\sqrt{2}}{2} & 2 \\ \frac{\sqrt{2}}{2} & \frac{\sqrt{2}}{2} & 0 \\ 0 & 0 & 1 \end{bmatrix}, V_{world} : [...] \rangle, ..\}$$
$$G_{adj} = \{(T1, S1), (S1, T3), ...\}$$

Figure 2: Compact representation of a TCE instance.

**Task 1: Outline Prediction**   This setting tests whether MLLMs can synthesize a global visual shape from local component arrangements. Rather than performing conventional visual recognition, the model is required to mentally compose the union of seven discrete tangram pieces and reason about their resulting overall shape. The input consists of the textual TCE specification of the seven tangram pieces (including piece types and exact vertex coordinates) and a candidate image displaying four distinct silhouette options (A–D). The model is required to select the correct matching silhouette from the candidate set. Accuracy and Invalid Rate are used as the evaluation metrics.

**Task 2: End-to-End Tangram Solution Generation**   This task assesses the model's ability to solve the tangram puzzle under strict geometric constraints and generate a precise executable solution. It represents a complex inverse spatial reasoning problem where the model must decompose a given target silhouette into the seven fixed rigid shapes. The input consists of a visual image of the target outline with vertex coordinates explicitly annotated within the figure. To precisely define the boundary conditions, the model is also provided with textual geometric data, including the vertex coordinates of the target outline and its edge relationships, specifying which vertices connect to form edges and their respective lengths. Furthermore, the input includes the initial state specifications for the seven tangram pieces, detailing their types, initial vertex coordinates, and constituent edges. The model is required to output the complete Tangram Configuration Expression (TCE) in JSON format. This code must explicitly define the final state of all seven pieces, including their types, vertex coordinates, and edge relationships, ensuring they perfectly fill the target outline. The evaluation checks both the geometric validity (satisfaction of rigid body and non-overlap constraints) and the shape fidelity of the generated solution, measured

Figure 3: Overview of the TangramPuzzle data construction pipeline.

by Intersection over Union (IoU) and Hausdorff Distance ($d_H$) against the ground truth.

## 2.2 Data Construction

To ensure high-quality geometric data, we implemented a multi-stage construction pipeline, as illustrated in Figure 3, comprising source filtering, interactive annotation, and symbolic refinement.

### 2.2.1 Raw Data Collection

We utilize the visual patterns from the KiloGram (Ji et al., 2022) dataset as our foundational source. Although KiloGram provides a diverse collection of tangram compositions, TangramPuzzle differs fundamentally from it in task design. KiloGram primarily focuses on linguistic descriptions and semantic part labels (e.g., "a person wearing a robe"), whereas TangramPuzzle introduces TCE, which grounds each shape in exact LaTeX-based algebraic coordinates and requires models to reason over precise spatial configurations rather than rely on approximate semantic categories. In addition, not all KiloGram instances satisfy the strict topological constraints required for mathematical verification. Consequently, we perform a manual filtering process to exclude invalid configurations, including patterns with holes, disconnected pieces, or incomplete assemblies. Only configurations that form a single connected shape without internal voids are retained for further comprehensive re-annotation and canonicalization.

### 2.2.2 Annotation Tool Development

Commonly used geometric software has proven insufficient for efficient and precise tangram annotation. Tools like GeoGebra[2] require users to compute coordinates before drawing and offer limited support for interactive manipulation, while manipulation-friendly platforms like Polypad[3] lack the functionality to export precise vertex coordinates. To address these limitations, we developed a bespoke web-based tangram annotation interface. To reduce human-induced alignment errors, we further incorporate vertex snapping and edge snapping mechanisms that automatically align coincident geometric features during assembly. The tool records the coordinates of all vertices in real time and exports complete annotations directly in a structured jsonl format, substantially accelerating the labeling process. Detailed human annotation procedures and the tool are provided in Appendix C.

### 2.2.3 Geometric Normalization

The raw annotations produced by the tool are stored in floating-point form, which is insufficient for exact geometric reasoning. To avoid ambiguity from finite-precision decimals, we post-process to normalize and convert all geometric values into exact symbolic forms. Specifically, each assembled configuration is translated such that its lower boundary lies on the $x$-axis and its left boundary lies on the $y$-axis, yielding a canonical placement. We then apply fixed rules to map all vertex coordinates to exact algebraic expressions in LaTeX. Based on these coordinates, we further extract the global outer contour, edge relations, and piece adjacency, and serialize the result into the unified TCE representation. Detailed TCE construction is provided in Appendix D.

To generate samples for the task 1, we leverage the geometric properties of the TCE. For each tan-

[2]https://www.geogebra.org/classic

[3]https://polypad.amplify.com/p#tangram

gram instance, we first reconstruct the ground-truth silhouette accurately based on the corresponding information encoded in the TCE. To construct the multiple-choice options, we randomly sample three distinct silhouettes from the rest of the dataset as distractors. These distractors are combined with the ground-truth silhouette, randomly shuffled, and rendered into a single candidate image labeled A through D. This automated pipeline ensures that the ground-truth silhouette is geometrically consistent with the coordinate-based input while maintaining visual diversity among the options.

### 2.2.4 Human Filtering

To ensure data correctness, we perform careful manual verification through visualization. Each annotated instance is rendered to display the assembled configuration, highlighting individual pieces and their boundaries. Instances exhibiting misaligned vertices, unintended gaps between adjacent edges, or overlaps between pieces are promptly flagged as invalid. Such cases are re-annotated using the tool, followed by repeated verification and conversion. This iterative process continues until all retained instances satisfy the geometric validity constraints required by TCE.

### 2.2.5 Data Statistics

TangramPuzzle exhibits both rich structural diversity and strict geometric rigor. The target silhouettes cover a wide range of semantic categories, including abstract shapes, everyday objects, and animals, spanning a broad and challenging spectrum of difficulty from simple, compact forms to complex, articulated silhouettes with intricate boundaries. In total, the dataset contains 668 unique tangram configurations. Each configuration is used to instantiate both Task 1 and Task 2, resulting in 1,336 problem instances overall.

### 2.3 Evaluation Metrics

**Task 1: Outline Prediction**  To evaluate vision-grounded spatial perception, we measure the standard classification **Accuracy (Acc)**, which calculates the percentage of instances where the model selects the correct target outline. Additionally, to assess the model's instruction-following capability and robustness, we report the **Invalid Rate**, defined as the proportion of responses that fail to map to any valid candidate option. Invalid outputs may arise from formatting errors or from generating content unrelated to the candidate options, reflect-ing common failure modes in instruction execution, in which case no interpretable decision can be extracted. Detailed metric computations for Task 1 are provided in Appendix E.1.

**Task 2: End-to-End Solution Generation**  Evaluating assembly generation is non-trivial because a single target silhouette may admit multiple valid internal arrangements, making direct comparison with a single reference solution unreasonable. Moreover, relying solely on a binary success metric is insufficient to understand model behavior: a prediction may fail to produce a fully valid assembly for many different reasons. To better diagnose these failure modes, we introduce a two-stage hierarchical constraint-based evaluation framework that not only measures whether the final objective is achieved, but also reveals where and how failures occur, while providing a smoother view of progress toward valid assembly generation. Detailed metric definitions and computation procedures for Task 2 are provided in Appendix E.2. Concretely, the framework comprises:

- **Stage 1: Constraint Validation.** We first check whether the generated assembly satisfies the required physical and geometric constraints by identifying three types of errors: **Syntax Error (TSE)** checks whether the output conforms to the TCE format and piece count; **Rigid Geometry Error (RGE)** verifies that the area and perimeter of each piece remain unchanged to prevent shape distortion; and **Physical Error (PE)** detects if any two pieces exhibit impermissible overlap or if the global union of all pieces fails to form a single connected component. The metric **Validation Pass Rate (VPR)** reports the percentage of samples that satisfy all these constraints.

- **Stage 2: Shape Similarity.** We further quantify how well the constructed shape matches the target silhouette using two metrics: **Intersection over Union (IoU)** measures the global area overlap between the predicted assembly and the target, while **Hausdorff Distance** ($d_H$) captures fine-grained boundary deviations to penalize shape outliers. Finally, **Success** reports the percentage of samples with a fully valid assembly that solve the puzzle.

# 3 Experiment

## 3.1 Experimental Setting

**Baselines** We evaluate TangramPuzzle across a diverse set of models. For open-source models, we evaluate Qwen3-VL-8B-Instruct, Qwen3-VL-32B-Instruct (Bai et al., 2025), InternVL3-78B (Zhu et al., 2025), DeepSeek-OCR (Wei et al., 2025), DeepSeek-VL2 (Wu et al., 2024), and GLM-4.6V (Z.ai, 2025). For commercial models, we include GPT-5.2 (OpenAI, 2025), Gemini3-Pro (Google DeepMind, 2025), and Claude-Sonnet-4.5 (Anthropic, 2025). We utilize the official chat templates and default generation parameters for all models to ensure a fair comparison.

**Details** All experiments are conducted by calling the corresponding model APIs. We run the evaluation pipeline on a workstation equipped with an NVIDIA RTX 2080 Ti GPU, and use a unified implementation to send requests, parse outputs, and compute all metrics across models.

## 3.2 Results

The results for Task 1 are summarized in Table 1, revealing substantial performance differences across models. The task requires models to mentally compose a silhouette from disjointed parts and identify the correct visual match, making it difficult to solve through simple memorization or superficial cues alone. Among open-source baselines, Qwen3-VL-32B-Instruct performs best, while Gemini3-Pro reaches near-ceiling accuracy. Most models also maintain low invalid-output rates, although a few remain less stable. Detailed analysis for Task 1 is provided in Appendix F.1.

Table 2 presents the results for Task 2. Their generally low **TSE** scores indicate that models can usually produce outputs in the required TCE-style format, and a lightweight recovery mechanism is applied to avoid over-penalizing minor formatting errors. This suggests that the main bottleneck is not formatting, but compositional spatial reasoning under geometric constraints. In particular, high RGE and PE across most models indicate a failure to maintain rigid geometry and physical validity, despite achieving high IoU in silhouette similarity. Further inspection reveals that this apparent visual fidelity is often achieved through "cheating," namely by impermissibly distorting rigid pieces or allowing overlaps to force a visual match. Detailed analysis for Task 2 is provided in Appendix F.2.

Table 1: Performance comparison on Task 1.

| Model | Invalid ($\downarrow$) | Acc ($\uparrow$) |
|---|---|---|
| Qwen3-VL-8B (Bai et al., 2025) | **00.00** | 37.57 |
| Qwen3-VL-32B (Bai et al., 2025) | 00.15 | 73.05 |
| InternVL3-78B (Zhu et al., 2025) | 00.75 | 29.19 |
| DeepSeek-OCR (Wei et al., 2025) | 12.87 | 22.46 |
| DeepSeek-VL2 (Wu et al., 2024) | 10.18 | 25.45 |
| GLM-4.6V (Z.ai, 2025) | **00.00** | 30.84 |
| GPT-5.2 (OpenAI, 2025) | **00.00** | 77.54 |
| Gemini3-Pro (Google DeepMind, 2025) | **00.00** | **98.65** |
| Claude-Sonnet-4.5 (Anthropic, 2025) | 00.45 | 51.20 |

## 3.3 Analysis

**Effect of In-context Learning (ICL)** To examine whether the bottleneck in Task 2 stems from the TCE schema or deeper spatial reasoning limitations, we evaluate models by prepending three solved examples to the prompt (In-Context Learning), as shown in Table 2. Rather than uniformly helping, ICL introduces a trade-off: the additional symbolic context tends to increase syntactic errors, while successfully parsed outputs often show better silhouette quality. This suggests that examples improve shape approximation but do not induce robust understanding of rigid geometric constraints. Detailed analysis is provided in Appendix G.1.

**Effect of Textual Geometry** We further investigated the models' dependency on textual metadata through an ablation study in a Visual-Centric setting, as shown in Table 2. In this setup, we removed the textual description of the target outline (i.e., vertex and edge lists), providing only the outline image with annotated coordinates alongside the initial piece descriptions. Most MLLMs show a clear performance drop, accompanied by more hallucinations and syntax errors, indicating a strong dependence on textual "crutches" rather than precise geometric extraction from vision alone. Textual geometry analysis is detailed in Appendix G.2.

**Effect of Chain-of-Thought (CoT)** As shown in Table 2, CoT provides only limited and uneven benefits. While it slightly improves formatting or some intermediate metrics for certain models, it does not resolve the core difficulty of Task 2. In some cases, better silhouette matching even comes with increased geometric violations, suggesting continued reliance on "visual cheating." For smaller models, performance remains largely unchanged, indicating that simply adding step-by-step reasoning is insufficient without stronger spatial grounding. Detailed analysis is provided in Appendix G.3.

Table 2: Performance comparison on Task 2 under different settings.

| Model | Constraint error (↓) | | | VPR (↑) | Silhouette Quality | | Success (↑) |
|---|---|---|---|---|---|---|---|
| | TSE (↓) | RGE (↓) | PE (↓) | | IoU (↑) | Hausdorff (↓) | |
| Qwen3-VL-8B-Instruct (Bai et al., 2025) | 23.35 | 40.42 | 80.69 | 00.00 | 20.25 | 07.81 | 00.00 |
| Qwen3-VL-32B-Instruct (Bai et al., 2025) | 07.93 | 83.08 | 94.46 | 00.00 | 50.55 | 01.39 | 00.00 |
| InternVL3-78B (Zhu et al., 2025) | 06.59 | 91.77 | 92.96 | 00.00 | 36.15 | 03.18 | 00.00 |
| GLM-4.6V (Z.ai, 2025) | 06.29 | 91.02 | 93.56 | 00.15 | 43.79 | 01.37 | 00.15 |
| GPT-5.2 (OpenAI, 2025) | 07.19 | 90.12 | 92.81 | 00.00 | 58.49 | 00.84 | 00.00 |
| Gemini3-Pro (Google DeepMind, 2025) | 08.83 | **37.57** | **65.57** | **22.60** | **85.93** | **00.37** | **21.56** |
| Claude-Sonnet-4.5 (Anthropic, 2025) | **00.60** | 98.20 | 97.90 | 00.15 | 61.61 | 00.57 | 00.00 |
| *In-Context Learning (ICL)* | | | | | | | |
| Qwen3-VL-8B-Instruct (Bai et al., 2025) | 33.98 | 57.04 | 66.17 | 00.15 | 28.48 | 03.51 | 00.00 |
| Qwen3-VL-32B-Instruct (Bai et al., 2025) | **06.74** | 87.28 | 93.71 | 00.00 | 48.65 | 01.49 | 00.00 |
| GPT-5.2 (OpenAI, 2025) | 09.43 | 86.98 | 90.72 | 00.00 | 60.30 | 00.74 | 00.00 |
| Gemini3-Pro (Google DeepMind, 2025) | 10.78 | **34.28** | **61.53** | **26.20** | **87.36** | **00.35** | **24.85** |
| *Visual-Centric Setting* | | | | | | | |
| Qwen3-VL-8B-Instruct (Bai et al., 2025) | 15.42 | 17.07 | 86.23 | 00.00 | 11.39 | 12.28 | 00.00 |
| Qwen3-VL-32B-Instruct (Bai et al., 2025) | **09.58** | 74.70 | 93.26 | 00.15 | 43.69 | 02.78 | 00.15 |
| DeepSeek-OCR (Wei et al., 2025) | 100.0 | **00.00** | **01.35** | 00.00 | 11.72 | 07.81 | 00.00 |
| DeepSeek-VL2 (Wu et al., 2024) | 99.85 | 00.15 | 13.32 | 00.00 | 12.08 | 05.49 | 00.00 |
| GPT-5.2 (OpenAI, 2025) | 39.67 | 58.23 | 58.08 | 00.00 | 53.67 | 01.21 | 00.00 |
| Gemini3-Pro (Google DeepMind, 2025) | 16.77 | 32.34 | 56.89 | **25.00** | **82.75** | **00.42** | **22.75** |
| *Chain-of-Thought (CoT)* | | | | | | | |
| Qwen3-VL-8B-Instruct (Bai et al., 2025) | 23.35 | 40.12 | 78.74 | 00.00 | 18.64 | 07.93 | 00.00 |
| Qwen3-VL-32B-Instruct (Bai et al., 2025) | 06.29 | 83.83 | 95.51 | 00.15 | 51.51 | 01.38 | 00.15 |
| GPT-5.2 (OpenAI, 2025) | **04.04** | 91.32 | 95.96 | 00.00 | 58.80 | 00.68 | 00.00 |
| Gemini3-Pro (Google DeepMind, 2025) | 24.40 | **33.38** | **51.35** | **20.66** | **83.12** | **00.50** | **19.76** |
| *Decomposition-Based Strategy* | | | | | | | |
| Qwen3-VL-8B-Instruct (Bai et al., 2025) | 26.35 | 41.47 | 78.14 | 00.00 | 24.22 | 07.11 | 00.00 |
| Qwen3-VL-32B-Instruct (Bai et al., 2025) | **06.89** | 86.23 | 94.61 | 00.15 | 51.25 | 01.23 | 00.00 |
| GPT-5.2 (OpenAI, 2025) | 35.33 | 60.78 | 64.22 | 00.00 | 60.25 | 00.88 | 00.00 |
| Gemini3-Pro (Google DeepMind, 2025) | 25.45 | **30.84** | **52.69** | **20.21** | **86.26** | **00.36** | **18.86** |
| *Text-Only Setting* | | | | | | | |
| Qwen3-VL-8B-Instruct (Bai et al., 2025) | 50.15 | **26.35** | 51.95 | 00.00 | 21.56 | 07.45 | 00.00 |
| Qwen3-VL-32B-Instruct (Bai et al., 2025) | **13.92** | 72.16 | 87.72 | 00.00 | 47.66 | 02.20 | 00.00 |
| GPT-5.2 (OpenAI, 2025) | 54.04 | 40.42 | **43.86** | 00.00 | 54.40 | 02.23 | 00.00 |
| Gemini3-Pro (Google DeepMind, 2025) | 28.14 | 33.68 | 56.74 | **13.32** | **81.15** | **00.59** | **12.28** |

**Effect of Systematic Decomposition** Motivated by the human expert analysis in Appendix H, we evaluate a decomposition-based prompting strategy for Task 2 that encourages models to represent both the target silhouette and tangram pieces using a shared unit—the small isosceles right triangle. As shown in Table 2, this approach yields modest improvements in silhouette quality and slightly reduces geometric constraint violations for some models. However, these gains rarely translate into higher final Success, and smaller models show little change. Overall, while decomposition provides a more structured reasoning prior, limited compositional spatial reasoning remains the primary obstacle. Detailed analysis is provided in Appendix G.4.

**Effect of Removing Visual Input** To examine whether Task 2 degenerates into a purely symbolic encoding–decoding problem once converted into TCE, we conduct a text-only ablation in which models receive only the textual description of the target outline vertices, without the target image. As shown in Table 2, removing visual input leads to a clear performance drop, most notably for Gemini3-Pro, while the other models still fail to produce valid final assemblies. This suggests that the visual silhouette provides a crucial spatial anchor that cannot be fully replaced by symbolic coordinates alone. Overall, the degradation indicates that solving TangramPuzzle requires genuine visual–spatial grounding and compositional reasoning rather than simple symbolic mapping. Detailed analysis is presented in Appendix G.5.

**Human Performance** We evaluate human performance on both tasks using domain experts, with results shown in Table 3. For Task 1, all three participants achieved 100% accuracy on a random

Table 3: Human Performance on Tasks 1 and 2.

| Human | Success (↑) | Complexity (↓) | Time usage (↓) |
|---|---|---|---|
| *Human performance on Task 1* | | | |
| Human 1 | **100.0** | 02.10 | 03.10 |
| Human 2 | **100.0** | **01.50** | 02.80 |
| Human 3 | **100.0** | 01.70 | **02.50** |
| Average | 100.0 | 01.77 | 02.80 |
| *Human performance on Task 2* | | | |
| Human 1 | 72.00 | 04.10 | **06.30** |
| Human 2 | **100.0** | **03.80** | 06.60 |
| Human 3 | 46.00 | 04.30 | 07.10 |
| Average | 72.67 | 04.07 | 06.67 |

Table 4: Human evaluation of MLLM on Task 2.

| Model | Expert | PSM (↑) | PPC (↑) | NMS (↑) |
|---|---|---|---|---|
| Gemini3-Pro | Expert 1 | 04.20 | 04.30 | 04.60 |
| | Expert 2 | 04.50 | 04.60 | 04.10 |
| | Expert 3 | 04.20 | 04.50 | 04.00 |
| | Average | **04.30** | **04.47** | **04.23** |
| GPT-5.2 | Expert 1 | 01.60 | 01.50 | 01.80 |
| | Expert 2 | 01.20 | 01.10 | 01.10 |
| | Expert 3 | 01.50 | 01.20 | 01.60 |
| | Average | 01.43 | 01.27 | 01.50 |

subset of 50 questions, indicating that the task is straightforward for humans once the seven pieces are mentally composed into the correct silhouette, while the performance gap across models shows that it remains discriminative for MLLMs. For Task 2, human solvers rarely violate geometric constraints, such as piece shape preservation or piece count correctness, and their outcomes exhibit a near-binary pattern: solutions are either correct or left unsolved. A detailed analysis of human results and solving strategies (ranging from systematic triangle decomposition to iterative trial-and-error) is provided in Appendix H.

### 3.4 Human Evaluation on MLLMs

Automatic metrics mainly assess strict geometric validity and may miss perceptual plausibility. To complement them, we conduct a human evaluation on Task 2 using three 5-point criteria: Perceptual Silhouette Match (PSM), Piece Plausibility & Canonicality (PPC), and Near-Miss Severity (NMS). As shown in Table 4, Gemini3-Pro receives consistently high scores, indicating strong perceptual alignment and many near-correct solutions even when automatic success is not achieved. Detailed analysis is provided in Appendix J.

Figure 4: Visualization of a case from Task 2.

### 3.5 Case Study

Figure 4 presents a case study on a U-shaped target in Task 2. Gemini3-Pro is the only model that produces a fully valid assembly, showing strong geometric grounding and compositional reasoning. Other models tend to favor silhouette matching over geometric validity: Claude-Sonnet-4.5 deforms pieces, InternVL3-78B produces severe overlaps, and GPT-5.2 generates a plausible outline but with an incorrect piece inventory. Detailed analysis is presented in Appendix I.

## 4 Conclusion

We presented TangramPuzzle, a geometry-grounded benchmark specifically designed for evaluating MLLMs on compositional spatial reasoning. Addressing the limitations of existing semantic-focused evaluations, we introduced the Tangram Construction Expression (TCE), a symbolic geometric framework that enables the precise, machine-verifiable assessment of rigid body constraints and physical feasibility. The benchmark encompasses the Outline Prediction and End-to-End TCE Code Generation tasks, which jointly probe the spectrum of spatial intelligence. We conducted a comprehensive evaluation of open-source and closed-source MLLMs covering different scales, accompanied by in-depth exploratory analyses on in-context learning and modality dependency. By shifting the evaluation paradigm from approximate visual matching to exact constraint satisfaction, TangramPuzzle provides a standardized and challenging testbed for future research.

## Limitations

While TangramPuzzle establishes a rigorous framework for evaluating compositional spatial reasoning through exact geometric constraints, several limitations remain. The benchmark is currently confined to 2D planar geometry with a fixed number of components, which may not fully capture the scalability and complexity of real-world 3D spatial manipulation tasks involving occlusion or variable object counts. Future work will seek to extend this evaluation paradigm to three-dimensional settings, thereby bringing the evaluation closer to real-world embodied scenarios.

## Ethical Considerations

**Potential Risks**   The TangramPuzzle benchmark focuses on abstract geometric reasoning and is constructed entirely from publicly available sources. Due to the inherently abstract nature of these geometric shapes, the dataset is devoid of personally identifiable information (PII), sensitive biometric data, or offensive content. Consequently, there are no foreseeable risks related to safety, discrimination, or surveillance.

**Ethical Statement**   Our data construction process strictly adhered to ethical research guidelines. All source images were derived from public domains, ensuring no copyright infringement. During the human-in-the-loop annotation and validation stages, all participants were informed of the nature of the task and compensated fairly in accordance with local labor standards. Furthermore, as the dataset comprises solely rigid geometric shapes, it is inherently free from biometric data, social biases, or other privacy concerns. Thus, the proposed research direction and tasks are ethically benign and socially harmless. All data and annotations will be released under a permissive open-source license upon acceptance to facilitate transparency and reproducibility.

**LLMs Usage Statement**   We use large language models and multimodal models as baselines to generate predictions for evaluation and analysis. During the writing of this paper, we also use large language models to assist with grammar checking and improving text fluency. The authors have carefully reviewed and verified all suggested revisions provided by the large language models to ensure their correctness, and take full responsibility for the content of this paper.

## References

Anthropic. 2025. Introducing claude sonnet 4.5. https://www.anthropic.com/news/claude-sonnet-4-5. Accessed: 2026-01-04.

Shuai Bai, Yuxuan Cai, Ruizhe Chen, Keqin Chen, Xionghui Chen, Zesen Cheng, Lianghao Deng, Wei Ding, Chang Gao, Chunjiang Ge, Wenbin Ge, Zhifang Guo, Qidong Huang, Jie Huang, Fei Huang, Binyuan Hui, Shutong Jiang, Zhaohai Li, Mingsheng Li, and 45 others. 2025. Qwen3-vl technical report. *Preprint*, arXiv:2511.21631.

Laura Bofferding and Mahtob Aqazade. 2023. "where does the square go?": reinterpreting shapes when solving a tangram puzzle. *Educational Studies in Mathematics*, 112(1):25–47.

Laura Bofferding and Yi Zhu. 2023. Composing tangram puzzles to support shape transformation. *Mathematics Teacher: Learning and Teaching PK-12*, 116(7):503–510.

Garrick Brazil, Abhinav Kumar, Julian Straub, Nikhila Ravi, Justin Johnson, and Georgia Gkioxari. 2023. Omni3d: A large benchmark and model for 3d object detection in the wild. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 13154–13164.

Lin Chen, Jinsong Li, Xiaoyi Dong, Pan Zhang, Yuhang Zang, Zehui Chen, Haodong Duan, Jiaqi Wang, Yu Qiao, Dahua Lin, and 1 others. 2024a. Are we on the right way for evaluating large vision-language models? *Advances in Neural Information Processing Systems*, 37:27056–27087.

Song Chen, Xinyu Guo, Yadong Li, Tao Zhang, Mingan Lin, Dongdong Kuang, Youwei Zhang, Lingfeng Ming, Fengyu Zhang, Yuran Wang, and 1 others. 2025a. Ocean-ocr: Towards general ocr application via a vision-language model. *arXiv preprint arXiv:2501.15558*.

Xiang Chen, Chenxi Wang, Yida Xue, Ningyu Zhang, Xiaoyan Yang, Qiang Li, Yue Shen, Lei Liang, Jinjie Gu, and Huajun Chen. 2024b. Unified hallucination detection for multimodal large language models. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 3235–3252, Bangkok, Thailand. Association for Computational Linguistics.

Zixin Chen, Sicheng Song, Kashun Shum, Yanna Lin, Rui Sheng, Weiqi Wang, and Huamin Qu. 2025b. Unmasking deceptive visuals: Benchmarking multimodal large language models on misleading chart question answering. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 13767–13800.

Pengzhou Cheng, Zheng Wu, Zongru Wu, Tianjie Ju, Aston Zhang, Zhuosheng Zhang, and Gongshen Liu. 2025a. Os-kairos: Adaptive interaction for mllm-powered gui agents. In *Findings of the Association*

*for Computational Linguistics: ACL 2025*, pages 6701–6725.

Xianfu Cheng, Wei Zhang, Shiwei Zhang, Jian Yang, Xiangyuan Guan, Xianjie Wu, Xiang Li, Ge Zhang, Jiaheng Liu, Yuying Mai, and 1 others. 2025b. Simplevqa: Multimodal factuality evaluation for multimodal large language models. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 4637–4646.

Ziming Cheng, Binrui Xu, Lisheng Gong, Zuhe Song, Tianshuo Zhou, Shiqi Zhong, Siyu Ren, Mingxiang Chen, Xiangchao Meng, Yuxin Zhang, and 1 others. 2025c. Evaluating mllms with multimodal multi-image reasoning benchmark. *arXiv preprint arXiv:2506.04280*.

Nianchen Deng, Lixin Gu, Shenglong Ye, Yinan He, Zhe Chen, Songze Li, Haomin Wang, Xingguang Wei, Tianshuo Yang, Min Dou, and 1 others. 2025. Internspatial: A comprehensive dataset for spatial reasoning in vision-language models. *arXiv preprint arXiv:2506.18385*.

Yihao Ding, Siwen Luo, Yue Dai, Yanbei Jiang, Zechuan Li, Geoffrey Martin, and Yifan Peng. 2025. A survey on mllm-based visually rich document understanding: Methods, challenges, and emerging trends. *arXiv preprint arXiv:2507.09861*.

Hongyuan Dong, Jiawen Li, Bohong Wu, Jiacong Wang, Yuan Zhang, and Haoyuan Guo. 2024. Benchmarking and improving detail image caption. *arXiv preprint arXiv:2405.19092*.

Wenlong Fang, Qiaofeng Wu, Jing Chen, and Yun Xue. 2025. guided mllm reasoning: Enhancing mllm with knowledge and visual notes for visual question answering. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pages 19597–19607.

Ling Fu, Zhebin Kuang, Jiajun Song, Mingxin Huang, Biao Yang, Yuzhe Li, Linghao Zhu, Qidi Luo, Xinyu Wang, Hao Lu, and 1 others. 2024a. Ocrbench v2: An improved benchmark for evaluating large multimodal models on visual text localization and reasoning. *arXiv preprint arXiv:2501.00321*.

Xingyu Fu, Yushi Hu, Bangzheng Li, Yu Feng, Haoyu Wang, Xudong Lin, Dan Roth, Noah A Smith, Wei-Chiu Ma, and Ranjay Krishna. 2024b. Blink: Multimodal large language models can see but not perceive. In *European Conference on Computer Vision*, pages 148–166. Springer.

Google DeepMind. 2025. Gemini 3 pro. https://deepmind.google/models/gemini/pro/. Accessed: 2026-01-04.

Gavin Greif, Niclas Griesshaber, and Robin Greif. 2025. Multimodal llms for ocr, ocr post-correction, and named entity recognition in historical documents. *arXiv preprint arXiv:2504.00414*.

Tianrui Guan, Fuxiao Liu, Xiyang Wu, Ruiqi Xian, Zongxia Li, Xiaoyu Liu, Xijun Wang, Lichang Chen, Furong Huang, Yaser Yacoob, and 1 others. 2024. Hallusionbench: an advanced diagnostic suite for entangled language hallucination and visual illusion in large vision-language models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 14375–14385.

Meng-Hao Guo, Jiajun Xu, Yi Zhang, Jiaxi Song, Haoyang Peng, Yi-Xuan Deng, Xinzhi Dong, Kiyohiro Nakayama, Zhengyang Geng, Chen Wang, and 1 others. 2025. Rbench: Graduate-level multidisciplinary benchmarks for llm & mllm complex reasoning evaluation. In *Forty-second International Conference on Machine Learning*.

Jiaxi Huang, Dongxu Wu, Hanwei Zhu, Lingyu Zhu, Jun Xing, Xu Wang, and Baoliang Chen. 2025a. Q-doc: Benchmarking document image quality assessment capabilities in multi-modal large language models. *arXiv preprint arXiv:2511.11410*.

Mingxin Huang, Yongxin Shi, Dezhi Peng, Songxuan Lai, Zecheng Xie, and Lianwen Jin. 2025b. Ocr-reasoning benchmark: Unveiling the true capabilities of mllms in complex text-rich image reasoning. *arXiv preprint arXiv:2505.17163*.

Anya Ji, Noriyuki Kojima, Noah Rush, Alane Suhr, Wai Keen Vong, Robert Hawkins, and Yoav Artzi. 2022. Abstract visual reasoning with tangram shapes. In *Proceedings of the 2022 conference on empirical methods in natural language processing*, pages 582–601.

Mengdi Jia, Zekun Qi, Shaochen Zhang, Wenyao Zhang, Xinqiang Yu, Jiawei He, He Wang, and Li Yi. 2025. Omnispatial: Towards comprehensive spatial reasoning benchmark for vision language models. *arXiv preprint arXiv:2506.03135*.

Dongfu Jiang, Xuan He, Huaye Zeng, Cong Wei, Max W.F. Ku, Qian Liu, and Wenhu Chen. 2024. Mantis: Interleaved multi-image instruction tuning. *Transactions on Machine Learning Research*, 2024.

Jiayi Kuang, Yinghui Li, Chen Wang, Haohao Luo, Ying Shen, and Wenhao Jiang. 2025. Express what you see: Can multimodal llms decode visual ciphers with intuitive semiosis comprehension? In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 12743–12774.

Sicong Leng, Yun Xing, Zesen Cheng, Yang Zhou, Hang Zhang, Xin Li, Deli Zhao, Shijian Lu, Chunyan Miao, and Lidong Bing. 2024. The curse of multi-modalities: Evaluating hallucinations of large multimodal models across language, visual, and audio. *arXiv preprint arXiv:2410.12787*.

Kaixin Li, Ziyang Meng, Hongzhan Lin, Ziyang Luo, Yuchen Tian, Jing Ma, Zhiyong Huang, and Tat-Seng Chua. 2025. Screenspot-pro: Gui grounding for professional high-resolution computer use. In *Proceedings of the 33rd ACM International Conference on Multimedia*, pages 8778–8786.

Yifan Li, Yifan Du, Kun Zhou, Jinpeng Wang, Wayne Xin Zhao, and Ji-Rong Wen. 2023. Evaluating object hallucination in large vision-language models. In *The 2023 Conference on Empirical Methods in Natural Language Processing*.

Yinghui Li, Zishan Xu, Shaoshen Chen, Haojing Huang, Yangning Li, Shirong Ma, Yong Jiang, Zhongli Li, Qingyu Zhou, Hai-Tao Zheng, and 1 others. 2024. Towards real-world writing assistance: A chinese character checking benchmark with faked and misspelled characters. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 8656–8668.

Jingping Liu, Ziyan Liu, Zhedong Cen, Yan Zhou, Yinan Zou, Weiyan Zhang, Haiyun Jiang, and Tong Ruan. 2025. Can multimodal large language models understand spatial relations? *arXiv preprint arXiv:2505.19015*.

Ruiyang Liu, Yinghui Li, Linmi Tao, Dun Liang, and Hai-Tao Zheng. 2022. Are we ready for a new paradigm shift? a survey on visual deep mlp. *Patterns*, 3(7).

Yuan Liu, Haodong Duan, Yuanhan Zhang, Bo Li, Songyang Zhang, Wangbo Zhao, Yike Yuan, Jiaqi Wang, Conghui He, Ziwei Liu, and 1 others. 2024. Mmbench: Is your multi-modal model an all-around player? In *European conference on computer vision*, pages 216–233. Springer.

Fan Lu, Wei Wu, Kecheng Zheng, Shuailei Ma, Biao Gong, Jiawei Liu, Wei Zhai, Yang Cao, Yujun Shen, and Zheng-Jun Zha. 2025. Benchmarking large vision-language models via directed scene graph for comprehensive image captioning. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pages 19618–19627.

Wufei Ma, Haoyu Chen, Guofeng Zhang, Yu-Cheng Chou, Jieneng Chen, Celso de Melo, and Alan Yuille. 2025a. 3dsrbench: A comprehensive 3d spatial reasoning benchmark. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 6924–6934.

Xinyu Ma, Ziyang Ding, Zhicong Luo, Chi Chen, Zonghao Guo, Derek F Wong, Xiaoyi Feng, and Maosong Sun. 2025b. Deepperception: Advancing r1-like cognitive visual perception in mllms for knowledge-intensive visual grounding. *arXiv preprint arXiv:2503.12797*.

Ahmed Masry, Mohammed Saidul Islam, Mahir Ahmed, Aayush Bajaj, Firoz Kabir, Aaryaman Kartha, Md Tahmid Rahman Laskar, Mizanur Rahman, Shadikur Rahman, Mehrad Shahmohammadi, Megh Thakkar, Md Rizwan Parvez, Enamul Hoque, and Shafiq Joty. 2025. ChartQAPro: A more diverse and challenging benchmark for chart question answering. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 19123–19151, Vienna, Austria. Association for Computational Linguistics.

OpenAI. 2025. Introducing gpt-5.2. https://openai.com/index/introducing-gpt-5-2/. Accessed: 2026-01-04.

Linke Ouyang, Yuan Qu, Hongbin Zhou, Jiawei Zhu, Rui Zhang, Qunshu Lin, Bin Wang, Zhiyuan Zhao, Man Jiang, Xiaomeng Zhao, and 1 others. 2025. Omnidocbench: Benchmarking diverse pdf document parsing with comprehensive annotations. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pages 24838–24848.

Roni Paiss, Ariel Ephrat, Omer Tov, Shiran Zada, Inbar Mosseri, Michal Irani, and Tali Dekel. 2023. Teaching clip to count to ten. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 3170–3180.

Long Phan, Alice Gatti, Ziwen Han, Nathaniel Li, Josephina Hu, Hugh Zhang, Chen Bo Calvin Zhang, Mohamed Shaaban, John Ling, Sean Shi, and 1 others. 2025. Humanity's last exam. *arXiv preprint arXiv:2501.14249*.

Christopher Rawles, Sarah Clinckemaillie, Yifan Chang, Jonathan Waltz, Gabrielle Lau, Marybeth Fair, Alice Li, William E Bishop, Wei Li, Folawiyo Campbell-Ajala, and 1 others. 2025. Androidworld: A dynamic benchmarking environment for autonomous agents. In *The Thirteenth International Conference on Learning Representations*.

Jonathan Roberts, Mohammad Reza Taesiri, Ansh Sharma, Akash Gupta, Samuel Roberts, Ioana Croitoru, Simion-Vlad Bogolin, Jialu Tang, Florian Langer, Vyas Raina, and 1 others. 2025. Zerobench: An impossible visual benchmark for contemporary large multimodal models. *arXiv preprint arXiv:2502.09696*.

Fedor Rodionov, Abdelrahman Eldesokey, Michael Birsak, John Femiani, Bernard Ghanem, and Peter Wonka. 2025. Floorplanqa: A benchmark for spatial reasoning in llms using structured representations. *arXiv preprint arXiv:2507.07644*.

Kexian Tang, Junyao Gao, Yanhong Zeng, Haodong Duan, Yanan Sun, Zhening Xing, Wenran Liu, Kaifeng Lyu, and Kai Chen. 2025a. Lego-puzzles: How good are mllms at multi-step spatial reasoning? *arXiv preprint arXiv:2503.19990*.

Wei Tang, Yanpeng Sun, Qinying Gu, and Zechao Li. 2025b. Visual position prompt for mllm based visual grounding. *arXiv preprint arXiv:2503.15426*.

Fei Wang, Xingyu Fu, James Y Huang, Zekun Li, Qin Liu, Xiaogeng Liu, Mingyu Derek Ma, Nan Xu, Wenxuan Zhou, Kai Zhang, and 1 others. 2025a. Muirbench: A comprehensive benchmark for robust multi-image understanding. In *The Thirteenth International Conference on Learning Representations*.

Wei Wang, Zhaowei Li, Qi Xu, Linfeng Li, YiQing Cai, Botian Jiang, Hang Song, Xingcan Hu, Pengyu Wang, and Li Xiao. 2025b. Advancing fine-grained

visual understanding with multi-scale alignment in multi-modal models. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 14282–14301.

Zirui Wang, Mengzhou Xia, Luxi He, Howard Chen, Yitao Liu, Richard Zhu, Kaiqu Liang, Xindi Wu, Haotian Liu, Sadhika Malladi, and 1 others. 2024. Charxiv: Charting gaps in realistic chart understanding in multimodal llms. *Advances in Neural Information Processing Systems*, 37:113569–113697.

Haoran Wei, Yaofeng Sun, and Yukun Li. 2025. Deepseek-ocr: Contexts optical compression. *arXiv preprint arXiv:2510.18234*.

Haoning Wu, Xiao Huang, Yaohui Chen, Ya Zhang, Yanfeng Wang, and Weidi Xie. 2025a. Spatialscore: Towards unified evaluation for multimodal spatial understanding. *arXiv preprint arXiv:2505.17012*.

Junda Wu, Yu Xia, Tong Yu, Xiang Chen, Sai Sree Harsha, Akash V Maharaj, Ruiyi Zhang, Victor Bursztyn, Sungchul Kim, Ryan A Rossi, and 1 others. 2025b. Doc-react: Multi-page heterogeneous document question-answering. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pages 67–78.

Zhiyu Wu, Xiaokang Chen, Zizheng Pan, Xingchao Liu, Wen Liu, Damai Dai, Huazuo Gao, Yiyang Ma, Chengyue Wu, Bingxuan Wang, and 1 others. 2024. Deepseek-vl2: Mixture-of-experts vision-language models for advanced multimodal understanding. *arXiv preprint arXiv:2412.10302*.

xAI. 2024. Realworldqa. https://huggingface.co/datasets/xai-org/RealworldQA. Accessed: 2025-12-30.

Renqiu Xia, Hancheng Ye, Xiangchao Yan, Qi Liu, Hongbin Zhou, Zijun Chen, Botian Shi, Junchi Yan, and Bo Zhang. 2025. Chartx & chartvlm: A versatile benchmark and foundation model for complicated chart reasoning. *IEEE Transactions on Image Processing*.

Han Xiao, Guozhi Wang, Yuxiang Chai, Zimu Lu, Weifeng Lin, Hao He, Lue Fan, Liuyang Bian, Rui Hu, Liang Liu, and 1 others. 2025. Ui-genie: A self-improving approach for iteratively boosting mllm-based mobile gui agents. *arXiv preprint arXiv:2505.21496*.

Yijia Xiao, Edward Sun, Tianyu Liu, and Wei Wang. 2024. Logicvista: Multimodal llm logical reasoning benchmark in visual contexts. *arXiv preprint arXiv:2407.04973*.

Tianbao Xie, Jiaqi Deng, Xiaochuan Li, Junlin Yang, Haoyuan Wu, Jixuan Chen, Wenjing Hu, Xinyuan Wang, Yuhui Xu, Zekun Wang, and 1 others. 2025. Scaling computer-use grounding via user interface decomposition and synthesis. *arXiv preprint arXiv:2505.13227*.

Peiran Xu, Sudong Wang, Yao Zhu, Jianing Li, and Yunjian Zhang. 2025a. Spatialbench: Benchmarking multimodal large language models for spatial cognition. *arXiv preprint arXiv:2511.21471*.

Rui Xu, Dakuan Lu, Zicheng Zhao, Xiaoyu Tan, Xintao Wang, Siyu Yuan, Jiangjie Chen, and Xu Yinghui. 2025b. Origamispace: Benchmarking multimodal llms in multi-step spatial reasoning with mathematical constraints. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems*.

Yunqiu Xu, Linchao Zhu, and Yi Yang. 2025c. Mc-bench: A benchmark for multi-context visual grounding in the era of mllms. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 17675–17687.

Fernanda Miyuki Yamada, Harlen Costa Batagelo, João Paulo Gois, and Hiroki Takahashi. 2025. Tangan: solving tangram puzzles using generative adversarial network. *Applied Intelligence*, 55(6):1–27.

Sihan Yang, Runsen Xu, Yiman Xie, Sizhe Yang, Mo Li, Jingli Lin, Chenming Zhu, Xiaochen Chen, Haodong Duan, Xiangyu Yue, and 1 others. 2025a. Mmsi-bench: A benchmark for multi-image spatial intelligence. *arXiv preprint arXiv:2505.23764*.

Songyuan Yang, Weijiang Yu, Wenjing Yang, Xinwang Liu, Huibin Tan, Long Lan, and Nong Xiao. 2025b. Wildvideo: Benchmarking lmms for understanding video-language interaction. *IEEE Transactions on Pattern Analysis and Machine Intelligence*.

Jiakang Yuan, Tianshuo Peng, Yilei Jiang, Yiting Lu, Renrui Zhang, Kaituo Feng, Chaoyou Fu, Tao Chen, Lei Bai, Bo Zhang, and 1 others. 2025. Mme-reasoning: A comprehensive benchmark for logical reasoning in mllms. *arXiv preprint arXiv:2505.21327*.

Xiang Yue, Tianyu Zheng, Yuansheng Ni, Yubo Wang, Kai Zhang, Shengbang Tong, Yuxuan Sun, Botao Yu, Ge Zhang, Huan Sun, and 1 others. 2025. Mmmu-pro: A more robust multi-discipline multimodal understanding benchmark. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 15134–15186.

Z.ai. 2025. Glm-4.6v: Open source multimodal models with native tool use. https://z.ai/blog/glm-4.6v. Accessed: 2025-01-04.

Chao Zhang, Jiamin Tang, and Jing Xiao. 2024. Tangram: Benchmark for evaluating geometric element recognition in large multimodal models. *arXiv preprint arXiv:2408.13854*.

Xuanle Zhao, Xuexin Liu, Haoyue Yang, Xianzhen Luo, Fanhu Zeng, Jianling Li, Qi Shi, and Chi Chen. 2025. Chartedit: How far are mllms from automating chart analysis? evaluating mllms' capability via chart editing. *arXiv preprint arXiv:2505.11935*.

Yizhou Zhao, Liang Qiu, Pan Lu, Feng Shi, Tian Han, and Song-Chun Zhu. 2022. Learning from the tangram to solve mini visual tasks. In *Proceedings of the AAAI conference on artificial intelligence*, volume 36, pages 3490–3498.

Longtao Zheng, Zhiyuan Huang, Zhenghai Xue, Xinrun Wang, Bo An, and Shuicheng YAN. 2025a. Agentstudio: A toolkit for building general virtual agents. In *The Thirteenth International Conference on Learning Representations*.

Xu Zheng, Zihao Dongfang, Lutao Jiang, Boyuan Zheng, Yulong Guo, Zhenquan Zhang, Giuliano Albanese, Runyi Yang, Mengjiao Ma, Zixin Zhang, and 1 others. 2025b. Multimodal spatial reasoning in the large model era: A survey and benchmarks. *arXiv preprint arXiv:2510.25760*.

Liangyu Zhong, Fabio Rosenthal, Joachim Sicking, Fabian Hüger, Thorsten Bagdonat, Hanno Gottschalk, and Leo Schwinn. 2025. Focus: Internal mllm representations for efficient fine-grained visual question answering. *arXiv preprint arXiv:2506.21710*.

Jinguo Zhu, Weiyun Wang, Zhe Chen, Zhaoyang Liu, Shenglong Ye, Lixin Gu, Hao Tian, Yuchen Duan, Weijie Su, Jie Shao, and 1 others. 2025. Internvl3: Exploring advanced training and test-time recipes for open-source multimodal models. *arXiv preprint arXiv:2504.10479*.

# A  Related Work

## A.1  General Multimodal Benchmarks

Standard benchmarks for Multimodal Large Language Models (MLLMs) have transitioned from foundational tasks like visual question answering (VQA) (Cheng et al., 2025b; Zhong et al., 2025; Liu et al., 2024; Chen et al., 2024a) and image captioning (Dong et al., 2024; Liu et al., 2022; Lu et al., 2025) to comprehensive assessments of emergent capabilities. Recent benchmarks target diverse competencies, including reasoning ability (Guo et al., 2025; Yuan et al., 2025; Yue et al., 2025; Xiao et al., 2024), where challenging datasets like Humanity's Last Exam (Phan et al., 2025) and ZeroBench (Roberts et al., 2025) test the upper bounds of expert-level cognition; document and chart understanding (Wang et al., 2024; Fu et al., 2024a; Xia et al., 2025; Ouyang et al., 2025; Masry et al., 2025); as well as visual grounding (Paiss et al., 2023; Brazil et al., 2023), hallucination evaluation (Li et al., 2023; Guan et al., 2024; Leng et al., 2024; Chen et al., 2024b; Yang et al., 2025b), and multi-image comprehension (Cheng et al., 2025c; Fu et al., 2024b; Jiang et al., 2024; Wang et al., 2025a). Furthermore, the assessment of agentic capabilities (Li et al., 2025; Xie et al., 2025; Rawles et al., 2025; Zheng et al., 2025a) centers on GUI interpretation and precise element interaction.

## A.2  Spatial Reasoning Benchmarks

Spatial reasoning is essential for MLLMs to perceive and interact with the physical world (Zheng et al., 2025b). Early research emphasized spatial understanding, as SpatialBench (Xu et al., 2025a) and RealWorldQA (xAI, 2024) evaluate relative positioning and depth in natural images. As the field progressed, benchmarks like OmniSpatial (Jia et al., 2025), MMSI-Bench (Yang et al., 2025a), and LEGO-Puzzles (Tang et al., 2025a) expanded this scope to dynamic scenarios, multi-view interactions, or the following of assembly instructions. However, most of these are formulated as visual question answering tasks, which may unintentionally encourage "shortcut" behaviors, such as exploiting language priors or superficial visual cues, rather than performing faithful geometric reasoning. Similarly, while ORIGAMISPACE (Xu et al., 2025b) emphasizes procedural reasoning through sequential folding steps, our benchmark focuses on a different aspect of spatial reasoning by requiring models to mentally assemble a complete structure from scratch under strict constraints, directly testing compositional spatial reasoning in an inverse assembly setting. In the tangram domain, Tangram (Zhang et al., 2024) targets basic element recognition and counting, while TANGAN (Yamada et al., 2025) treats assembly as an optimization problem rather than evaluating MLLMs.

Unlike prior approaches that rely mainly on perceptual approximations, our benchmark is built around explicit mathematical representations and constraint-based evaluation, enabling precise assessment of solution validity. Its expressive 2D formulation also avoids the viewpoint and depth ambiguities common in 3D tasks, such as self-occlusion and projection effects, which often make errors difficult to attribute clearly to reasoning failures. In contrast, the 2D formulation makes reasoning failures clearer and supports automatic verification.

# B  Discussion

## B.1  Generalizability to Real-World Spatial Scenarios

Although TangramPuzzle is instantiated in a highly controlled puzzle domain, the benchmark targets a set of core capabilities that are not specific to tangrams themselves, but are broadly relevant to

real-world spatial reasoning. At its core, solving a tangram requires preserving the identity of rigid parts under Euclidean transformations, composing multiple local pieces into a globally valid configuration, and satisfying hard geometric constraints such as non-overlap, connectivity, and exact boundary alignment. These requirements closely mirror the structural demands of practical spatial tasks, where success depends not only on recognizing a plausible overall shape, but also on maintaining the validity of each constituent part throughout the construction process.

This is particularly relevant to applications such as CAD-style assembly and robotic manipulation. In CAD assembly, parts have fixed geometry and must be placed under rigid transformations while satisfying contact, fit, and compatibility constraints; a visually plausible arrangement is insufficient if dimensions, orientations, or interfaces are inconsistent. Similarly, in robotic manipulation and assembly planning, an agent must reason about how individual objects can be rotated, translated, and composed into a target structure without violating physical feasibility. In both cases, the essential challenge lies in coordinating local geometric decisions with global structural validity. TangramPuzzle captures this challenge in a minimal setting, making it possible to evaluate whether a model truly preserves rigid-body structure and composes parts coherently, rather than relying on coarse silhouette matching.

The controlled nature of the benchmark is therefore a deliberate design choice. Real-world spatial tasks typically involve additional sources of difficulty, including perception noise, occlusion, uncertain correspondences, and underspecified goals. While these factors are important, they can also obscure the underlying reasoning problem and make evaluation ambiguous. By abstracting away such confounds, TangramPuzzle isolates the compositional geometric core of the problem and enables exact, machine-verifiable assessment. This is aligned with the motivation of our symbolic TCE representation and constraint-based verifier, which were introduced precisely to move evaluation beyond approximate perceptual similarity toward rigorous geometric correctness. In this sense, the benchmark should be viewed as a diagnostic testbed for compositional spatial reasoning abilities that real-world systems also rely upon.

## B.2 Unique Challenges of TangramPuzzle

TangramPuzzle poses a form of spatial reasoning that is structurally different from many existing benchmarks. Rather than asking the model to recognize a local spatial relation, answer a geometry-related question, or reason over an already observed scene, it requires the model to construct a globally valid configuration from multiple rigid parts under strict constraints.

**Diagnostic interpretability.** One advantage of TangramPuzzle is that it does not collapse evaluation into a single accuracy or success score. Because the benchmark separates failures into syntax errors, rigid-geometry violations, physical-validity violations, and silhouette mismatch, it reveals not only whether a model fails, but also *how* it fails. This makes the benchmark more informative for diagnosing weaknesses and tracking progress.

**Rigid-body preservation.** A distinctive challenge of TangramPuzzle is that every piece is a rigid geometric object whose shape must remain unchanged. Our experiments reveal a systematic failure mode in which MLLMs appear to "cheat" by implicitly deforming pieces to better match the target silhouette. This type of error is easy to miss when evaluation relies mainly on answer correctness or approximate outline similarity, but TangramPuzzle makes it explicit by checking whether each piece preserves its exact geometry.

**Inverse assembly.** TangramPuzzle is fundamentally an inverse assembly problem. The model must search over a large transformation space—including translations, rotations, and reflections—to find a configuration that satisfies both the outer boundary and the internal non-overlap constraints. This is more demanding than simply interpreting a given spatial scene, because the model must reason from the desired global shape back to the placement of individual parts.

**Mathematically grounded validity.** Rather than evaluating spatial reasoning through natural-language answers or coarse perceptual judgments, TangramPuzzle grounds the task in an explicit geometric representation via TCE, where each solution is specified by exact coordinates and structural relations. This makes the reasoning process mathematically explicit and the final output exactly verifiable. As a result, the benchmark can sharply distinguish between outputs that merely *look* correct and those that are truly geometrically valid: a predicted assembly may closely match the target sil-

houette while still violating rigidity or non-overlap constraints, and is therefore marked invalid.

### B.3 Future Work

Although TangramPuzzle is instantiated in a clean 2D tangram setting, the underlying framework is not limited to the classical seven-piece puzzle. Because the benchmark is built on an explicit geometric representation together with an automatic verifier, it can be naturally extended to a broader family of polygonal assembly problems, including settings with richer part libraries, non-convex components, distractor pieces, partial observations, and noisy target contours.

An important direction for future work is to bridge the current controlled setting with more realistic spatial reasoning scenarios. This includes introducing perceptual uncertainty, increasing the diversity and complexity of component geometries, and moving beyond planar assembly toward 3D object construction. We believe such extensions would preserve the core evaluation philosophy of TangramPuzzle while bringing the benchmark closer to practical applications in structured design and embodied manipulation.

### C Human Annotation Details

**Recruitment and Payment.** To ensure the high quality and rigorous geometric precision of the TangramPuzzle benchmark, we invited researchers with backgrounds in geometry and computer science to conduct the data annotation and verification. We strictly adhered to local labor standards regarding compensation. The payment rate was determined based on the estimated time required to complete the annotation for each puzzle, ensuring that the hourly rate met or exceeded the local minimum wage requirements.

**Annotation Process.** Annotators used our interactive tangram tool to assemble each target configuration by dragging, rotating, and flipping pieces. The annotation interface is shown in Figure 5. To avoid pixel-level misalignment, the tool incorporates a magnetic snapping mechanism that automatically aligns piece vertices to the global coordinate grid or to vertices of adjacent pieces, ensuring that spatial relationships are mathematically exact rather than visually approximate. After completing an instance, annotators exported the generated data, and we conducted additional visual inspection and re-annotation when necessary (e.g., minor mis-alignment, unintended overlaps, or disconnected components) to ensure geometric correctness.

**Instructions and Consent.** Prior to the data collection process, all annotators were provided with comprehensive instructions detailing the usage of the annotation interface, the definition of the Tangram Construction Expression (TCE), and the strict physical constraints (e.g., non-overlap, boundary adherence). We obtained informed consent from all participants, who were explicitly informed that the annotated data would be used for academic research and released to the public.

### D Detailed Geometric Normalization

To ensure the resulting dataset is machine-verifiable and free from floating-point ambiguity, we implemented a rigorous post-processing pipeline to convert raw manual annotations into the symbolic TCE format. This process consists of three key steps:

**1. Reference Alignment and Raw Capture.** First, annotators utilize our custom web-based tool to manually reconstruct the tangram patterns from the source KiloGram dataset (Ji et al., 2022). By dragging, rotating, and snapping the seven virtual pieces, annotators align the pieces to visually match the reference image. Upon saving, the tool records the raw floating-point coordinates of all vertices for the seven constituent pieces in their current assembled state.

**2. Canonical Placement.** To standardize the coordinate system across all instances and eliminate arbitrary canvas positioning, we apply a translation operation to the raw assembly. Let $\mathcal{V} = \{(x_i, y_i)\}_{i=1}^{N}$ denote the set of all vertex coordinates in the raw annotation. We compute the global minima of the assembly:

$$x_{min} = \min_{(x,y) \in \mathcal{V}} x, \quad y_{min} = \min_{(x,y) \in \mathcal{V}} y \quad (1)$$

We then translate every vertex $(x, y)$ to a new coordinate $(x', y')$:

$$x' = x - x_{min}, \quad y' = y - y_{min} \quad (2)$$

This operation ensures that the assembly's lower boundary lies strictly on the $x$-axis and its left boundary lies on the $y$-axis, resulting in a standardized, positive-quadrant layout.

Figure 5: Annotation interface for TangramPuzzle.

## 3. Symbolic Conversion and TCE Generation.
To support exact geometric reasoning and eliminate floating-point ambiguity, we convert the normalized coordinates into precise algebraic expressions represented in LaTeX format.

We employ a deterministic mapping algorithm to convert decimal approximations into exact rational or irrational numbers. For instance, a coordinate 0.5 is converted to \frac{1}{2}, and irrational numbers resulting from $45°$ rotations (e.g., $1.414\dots$) are resolved to their symbolic forms (e.g., \sqrt{2}). This ensures exact geometric relations (e.g., edge equality).

With the exact coordinates of the seven pieces established (forming the `final_state`), we computationally extract the global geometry. This includes calculating the geometric union of the pieces to extract the `target_outline` (effectively dissolving internal edges) and generating an adjacency graph by identifying shared vertex pairs and overlapping edge segments. Finally, these components are serialized into the unified TCE JSON format, providing a mathematically perfect ground truth for model evaluation.

## E  Detailed Evaluation Protocols

This section provides the formal definitions and precise calculation details for the metrics used in our evaluation.

### E.1  Task 1 Metrics

**Accuracy (Acc)**  Performance is measured using classification accuracy:

$$\text{Acc} = \frac{1}{N}\sum_{i=1}^{N}\mathbb{I}(\hat{a}_i = a_i), \tag{3}$$

where $a_i \in \mathcal{A}$ denotes the ground-truth option for the $i$-th instance, $\hat{a}_i \in \mathcal{A}$ is the model's predicted option, $\mathcal{A}$ is the option set (e.g., $\{A, B, C, D\}$), and $\mathbb{I}(\cdot)$ is the indicator function.

**Invalid Rate**  We further define the Invalid rate as the proportion of instances in which the model output does not yield any valid option that can be mapped to the candidate set. Invalid outputs may arise from formatting errors or from generating content unrelated to the candidate options. Formally:

$$\text{Invalid} = \frac{1}{N}\sum_{i=1}^{N}\mathbb{I}(\hat{a}_i \notin \mathcal{A}). \tag{4}$$

### E.2  Task 2 Metrics

Let $\mathcal{P} = \{P_1, \dots, P_7\}$ denote the set of predicted piece polygons after assembly, and let $\mathcal{T}$ denote the ground-truth target silhouette. The evaluation pipeline consists of two stages: constraint validation and silhouette quality assessment.

**Constraint Validation**  We consider three types of constraint errors:

- **TSE (Syntax Error)** checks whether the predicted output conforms to the required TCE

format. A prediction is flagged as TSE if the JSON cannot be parsed, the number of pieces is incorrect, or piece types are invalid:

$$\text{TSE} = \neg\text{Valid}_{\text{syn}}(\mathcal{P}), \qquad (5)$$

where $\text{Valid}_{\text{syn}}(\mathcal{P})$ denotes syntactic validity under the TCE schema.

- **RGE (Rigid Geometry Error)** verifies that each predicted piece preserves its original shape. For each piece, we compare its area and perimeter against the corresponding ground-truth specification. Let $P_i$ be a simple polygon with ordered vertices $\{\mathbf{v}_1, \ldots, \mathbf{v}_n\}$. Its area is computed as:

$$\text{Area}(P_i) = \frac{1}{2}\left|\sum_{k=1}^{n}(x_k y_{k+1} - x_{k+1}y_k)\right|, \qquad (6)$$

and its perimeter is given by

$$\text{Perimeter}(P_i) = \sum_{k=1}^{n}\|\mathbf{v}_{k+1} - \mathbf{v}_k\|_2, \quad (7)$$

where $\mathbf{v}_{n+1} = \mathbf{v}_1$. A rigid geometry error is triggered if either quantity deviates from that of the corresponding canonical tangram piece.

- **PE (Physical Error)** evaluates physical feasibility. A prediction is considered invalid if any two pieces overlap or if the union of all pieces is not a single connected shape.

**Shape Similarity** We adopt two complementary shape similarity metrics:

- **IoU (Intersection over Union)** measures the overlap between the predicted assembly $U$ and the target silhouette $\mathcal{T}$:

$$\text{IoU}(U, \mathcal{T}) = \frac{\mu(U \cap \mathcal{T})}{\mu(U \cup \mathcal{T})}, \qquad (8)$$

where $\mu(\cdot)$ denotes planar area.

- **Hausdorff Distance** ($d_H$) To capture boundary-level deviations, we compute the Hausdorff distance between the boundaries of $U$ and $\mathcal{T}$:

$$d_H(\partial U, \partial \mathcal{T}) =$$
$$\max\left\{\begin{array}{l} \sup_{x\in\partial U}\inf_{y\in\partial\mathcal{T}}\|x - y\|_2, \\ \sup_{y\in\partial\mathcal{T}}\inf_{x\in\partial U}\|x - y\|_2 \end{array}\right\}. \quad (9)$$

Here $\partial U$ and $\partial \mathcal{T}$ denote the boundaries of the predicted assembly and the target silhouette, respectively, and $\|\cdot\|_2$ represents the standard Euclidean distance.

# F Detailed Experimental Results

## F.1 Experimental Results for Task 1

The results for Task 1 are summarized in Table 1, revealing substantial performance differences across models. This task assesses the model's ability to mentally compose a silhouette from disjointed parts and identify the correct visual match accurately. Notably, many models perform poorly on this task, suggesting that Task 1 cannot be reliably solved through simple memorization or superficial pattern matching; instead, it requires genuine compositional spatial reasoning based on part–whole structure. Among open-source baselines, Qwen3-VL-32B-Instruct stands out with an accuracy of 73.05%, approaching the performance of the closed-source model GPT-5.2, while smaller or earlier architectures struggle to exceed 40% accuracy. For commercial models, Gemini3-Pro achieves near-ceiling performance with an accuracy of 98.65%, underscoring its superior capacity for fine-grained visual perception and holistic mental shape composition regarding global silhouettes. For most models, the rate of invalid outputs remains low, suggesting a strong ability to follow instructions and produce interpretable decisions. However, DeepSeek-OCR and DeepSeek-VL2 exhibit noticeably higher invalid rates, suggesting that under the stress of this complex spatial reasoning task, these models often fail to form a decisive conclusion or collapse into generating irrelevant content.

## F.2 Experimental Results for Task 2

Table 2 presents the quantitative results for Task 2. Although **Success** is zero for most models, the intermediate metrics reveal why they fail. Most models achieve relatively low **TSE** scores, typically at the single-digit level, indicating that they can generally produce outputs in the required TCE-style JSON format. This suggests that the main bottleneck is not TCE formatting itself, but compositional spatial reasoning. To avoid over-penalizing minor formatting issues, our evaluation pipeline incorporates a lightweight recovery mechanism: we use `json_repair` to fix malformed JSON and regex-based heuristics to resolve common formatting defects in LaTeX-style mathematical expres-

sions. This ensures that we extract and evaluate the model's true geometric intent.

By contrast, constraint-related errors remain widespread. In particular, **Rigid Geometry Errors (RGE)** and **Physical Errors (PE)** are highly prevalent, indicating that models struggle to comply with the fundamental geometric rules of the puzzle. One notable observation is the pronounced discrepancy between silhouette quality and the Success rate. Top-tier models like Claude-Sonnet-4.5 and GPT-5.2 achieve high IoU scores yet fail to produce a single valid solution (0% Success). Further inspection reveals that the accompanying high RGE and PE scores indicate that this apparent visual fidelity is achieved through "cheating," namely by impermissibly distorting rigid pieces or overlapping them to force a visual match. Meanwhile, Gemini3-Pro stands out as the only model demonstrating robust geometric reasoning, achieving the highest validation pass rate and success score while also maintaining superior silhouette quality.

These intermediate metrics are also useful for tracking incremental progress. Models show substantial variation in **IoU** and **Hausdorff Distance**, which remain informative even when **Success** is zero. Higher IoU corresponds to better global alignment with the target silhouette, while lower Hausdorff Distance captures more accurate boundary matching, providing graded signals below the strict validity threshold. More broadly, these metrics reveal a smoother progression toward successful assembly: improvements typically appear first in **IoU** (better outline alignment), then in reduced **RGE** and **PE** (better adherence to rigid and physical constraints), and finally in non-zero **Success**. This makes the benchmark suitable for tracking incremental advances, even when achieving full validity remains challenging.

## G   Detailed Analytical Experiments

### G.1   In-context Learning Details

We examine the effect of In-context Learning (ICL) by prepending three solved examples to the prompt for a subset of models (Qwen3-VL, GPT-5.2, Gemini3-Pro).

Contrary to the expectation that examples stabilize output, several models exhibited increased Syntax Error (TSE) rates compared to the zero-shot setting. For instance, Qwen3-VL-8B-Instruct and Gemini3-Pro showed higher failure rates in generating valid JSONs. This suggests that the extensive symbolic context imposes a cognitive load that interferes with the model's ability to strictly adhere to structural constraints.

Despite the syntactic instability, ICL yields clear benefits for silhouette-level quality in valid responses. Models demonstrated improved IoU and reduced Hausdorff distances, effectively learning to better approximate the global target shape. This suggests that while ICL serves as a potent mechanism for refining visual matching strategies and "teaching" the task format, it ultimately falls short of spontaneously instilling a fundamental understanding of strict physical validity in models that inherently lack it.

### G.2   Textual Geometry Ablation

To quantify the models' dependency on textual metadata, we evaluated a Visual-Centric setting where explicit textual descriptions of the target outline (vertices and edges) were removed, leaving only the image with annotated coordinates.

The elimination of explicit textual outline specifications significantly destabilized structured generation. Notably, GPT-5.2 experienced a dramatic surge in syntax errors, with TSE rising from $7.19\%$ to $39.67\%$. Similarly, the Deepseek series frequently hallucinated irrelevant content, indicating a heavy reliance on text prompts to guide the generation process.

For the majority of models, the absence of textual data precipitated a marked deterioration in Silhouette Quality, exposing a critical dependency on semantic prompts. This confirms a widespread inability to precisely "read" geometric coordinates directly from raw visual inputs. However, Gemini3-Pro's robust performance in this setting serves as a notable exception, highlighting its advanced capability to perform rigorous reasoning solely based on visual grounding, independent of textual crutches.

### G.3   Effect of Chain-of-Thought (CoT)

To investigate whether explicit step-by-step reasoning can alleviate the spatial logic bottleneck, we evaluate models using Chain-of-Thought (CoT) prompting. As shown in the "Chain-of-Thought (CoT)" results in Table 2, CoT provides only limited and highly uneven benefits. While it improves some intermediate metrics for certain models, it does not fundamentally resolve the core difficulty of the task: producing geometrically valid assemblies under rigid and physical constraints.

We observe that CoT can improve syntax compliance for certain models such as Qwen3-VL-32B and GPT-5.2, suggesting that explicit reasoning prompts may help organize outputs into a more structured form. However, this effect is inconsistent across the board. For example, Gemini3-pro becomes noticeably less stable in its output formatting under CoT, with its TSE rising significantly, indicating that longer reasoning traces can introduce additional formatting noise. This further supports our earlier conclusion that syntax is not the primary bottleneck in Task 2.

More importantly, CoT does not effectively enhance constraint satisfaction. Qwen3-VL-32B managed to achieve a non-zero Success rate ($0.15\%$) under CoT, suggesting that explicit reasoning can occasionally help models stumble upon a valid configuration. Conversely, while silhouette matching slightly improved for GPT-5.2, we observed an exacerbation of geometric deformations, with both PE and RGE increasing. This reinforces our finding that models tend to prioritize "visual cheating" over rigorous physical rules.

For smaller-scale models such as Qwen3-VL-8B, performance remains largely stagnant despite CoT, with Success and VPR rates remaining at zero. This suggests that without basic spatial grounding, adding a thinking step is insufficient to solve complex inverse geometric problems.

### G.4 Effect of Systematic Decomposition

Motivated by the human expert analysis in Appendix H, we explore whether a decomposition-based strategy can improve performance on Task 2. A key human strategy is to treat both the target silhouette and the seven tangram pieces as compositions of the same basic unit: the small isosceles right triangle. The solver can then reason about how groups of these basic units within the target outline correspond to individual tangram pieces, making the puzzle easier to solve. We therefore introduce prompts that encourage models to perform this kind of decomposition before generating the final assembly.

As shown in the "Decomposition-Based Strategy" results in Table 2, this strategy leads to modest but consistent improvements in silhouette quality for several models. Qwen3-VL-8B, Qwen3-VL-32B, GPT-5.2, and Gemini3-Pro all achieve higher IoU scores under this setting, suggesting that explicit decomposition helps models align the overall assembly more closely with the target outline. In some cases, boundary precision also improves, suggesting that decomposition provides a more structured basis for global shape planning.

Proprietary models, particularly GPT-5.2 and Gemini3-Pro, show marked improvements in adhering to rigid-body and non-overlap constraints, as reflected by a decrease in RGE and PE scores. Such results underscore the role of a shared geometric basis in guiding models to reconcile how composite shapes populate the available interior space of the target outline. However, Gemini3-Pro's final Success rate experienced a slight decline compared to the original setting. For the Qwen3-VL series, the benefits of decomposition are more subtle; Qwen3-VL-32B showed a marginal improvement in VPR and silhouette quality, while the 8B model's performance remained largely stagnant, with Success and VPR staying at zero. Overall, while encouraging models to reason in terms of a shared geometric basis improves global shape planning and reduces constraint violations for some models, the lack of compositional spatial reasoning remains the primary cause of failure.

### G.5 Effect of Removing Visual Input

To address the potential concern that the task might degenerate into a purely symbolic encoding-decoding problem once converted into TCE, we conducted a text-only ablation study. In this configuration, models receive only the textual descriptions of the target outline's vertices, completely removing the visual image. This setup allows us to evaluate whether models can effectively solve the puzzle through symbolic coordinates alone or if visual grounding remains indispensable for compositional reasoning.

As illustrated in the "Text-Only Setting" results in Table 2, removing the visual modality leads to a definitive decline in overall performance. The strongest model, Gemini3-Pro, suffers a substantial drop in both VPR and Success, with both metrics falling by nearly half, while the other models remain unable to produce valid final assemblies. These findings demonstrate that the visual silhouette serves as a critical spatial anchor that symbolic coordinates alone cannot adequately replace.

The text-only setting does not produce a uniform pattern across intermediate metrics. For some models, certain constraint errors decrease, but these changes do not translate into better final outcomes. In other words, access to coordinates alone may help with parts of the formal representation, yet it

remains insufficient for carrying out the full part-to-whole assembly process. The persistent gap in Success indicates that solving the task requires more than simply decoding symbolic input into TCE format.

A particularly important observation is that models do not become stronger when the problem is reduced to text only. If Task 2 were primarily a symbolic encoding–decoding problem, one would expect performance to remain stable, or even improve, after removing the image. Instead, performance generally deteriorates, especially for the strongest model. This suggests that the benchmark genuinely depends on visual-spatial grounding: models must interpret the global shape, mentally organize its structure, and coordinate this understanding with the geometry of the seven pieces. Moreover, the task presents a vast search space, as each tangram piece permits an infinite range of continuous translations, alongside discrete rotations and reflections. This type of compositional spatial reasoning goes beyond simple end-to-end symbolic mapping.

## H   Detailed Human Performance Analysis

### H.1   Human Performance on Task 1

We evaluate human performance on Task 1 using three domain experts, each of whom completed a random subset of 50 questions. As shown in Table 3, all three participants achieved 100% accuracy. This indicates that Task 1 is straightforward for humans: once the seven tangram pieces are composed, the correct outer silhouette is typically easy to recognize. Participants also reported low complexity and short time usage, suggesting that the task can be solved efficiently and with little difficulty by human experts.

The human results also help contextualize the model performance in Table 1. Although Gemini3-Pro achieves near-ceiling accuracy and GPT-5.2 also performs strongly, most other models remain substantially below the human level, with many open-source models still far from reliable recognition. In particular, model accuracies span a wide range, from below 30% to nearly 99%, revealing a clear gap between proprietary and many open-source models. This spread indicates that Task 1 is far from saturated: despite being easy for humans, it remains discriminative for models and provides a meaningful test of visual perception and mental shape composition.

### H.2   Human Performance on Task 2

We evaluate human performance on Task 2 by involving three domain experts who independently solved the task sets under the same conditions as the models.

**Performance Patterns.** As shown in our results, human solvers rarely violate fundamental geometric constraints such as piece shape preservation or piece count correctness. Consequently, human performance manifests as a binary outcome: a solution is either strictly valid or the participant fails to find a solution within a reasonable time. This stands in sharp contrast to model predictions, which often achieve partial visual similarity through impermissible physical violations (e.g., overlapping pieces or shape distortion).

**Solving Strategies.** We observe substantial variance in success rates across the strategies employed. One expert achieved perfect performance by adopting a *systematic decomposition strategy*. Specifically, all seven tangram pieces were interpreted as compositions of a common geometric primitive: the small isosceles right triangle. Under this view, each piece corresponds to a fixed number and arrangement of these primitive units, and the target silhouette can likewise be mentally decomposed into the same unit-triangle basis. Once the silhouette is represented in this way, the puzzle becomes a structured assignment problem: the solver searches for regions within the decomposed outline whose unit counts and geometric patterns match those of the seven tangram pieces, and then assembles the solution by mapping pieces to these regions. In contrast, the other two experts primarily relied on *iterative trial-and-error*, repeatedly adjusting piece positions until a feasible configuration emerged. This heuristic approach resulted in lower success rates and significantly longer solving times.

**Complexity Assessment.** Participants were asked to rate task difficulty on a scale from 1 to 5. The high average complexity score of 4.1 confirms that TangramPuzzle is non-trivial even for humans. On average, each instance required approximately 6.7 minutes to solve, reflecting the substantial cognitive effort required for precise geometric reasoning and assembly planning.

## I   Detailed Case Study

Figure 4 visualizes the generation results for a U-shaped target (Task 2). Gemini3-Pro achieves a

perfect assembly, demonstrating its ability to effectively ground coordinate constraints to solve complex compositional problems. A critical failure mode observed across other models is the tendency to prioritize visual silhouette matching at the expense of geometric constraints. For instance, Claude-Sonnet-4.5 attempts to force an alignment with the target contour by non-rigidly elongating the edges of the left and right triangles, whereas InternVL3-78B generates severe overlaps to maximize area coverage. Meanwhile, GPT-5.2 produces a visually plausible silhouette but fails to preserve component fidelity, utilizing an incorrect piece inventory (e.g., hallucinating an extra square while omitting the parallelogram). We further observe that smaller models such as Qwen3-VL-8B-Instruct often arrange pieces in a simple linear sequence, indicating an inability to map symbolic coordinate specifications onto a 2D planar workspace.

## J  Human Evaluation on MLLMs

Automatic metrics primarily capture strict geometric validity, often overlooking perceptual plausibility. To address this, we conduct a human evaluation on Task 2 using three criteria rated on a 5-point scale: Perceptual Silhouette Match (PSM), which assesses the visual similarity of the assembly to the target; Piece Plausibility & Canonicality (PPC), which evaluates whether piece placements appear natural rather than visually strained; and Near-Miss Severity (NMS), which measures the proximity of an incorrect prediction to a successful solution. Table 4 summarizes the human evaluation results. Gemini3-Pro consistently receives high scores, indicating strong perceptual alignment with the target silhouette; even when automatic success is not achieved, many solutions are judged to be close to correct. In contrast, GPT-5.2 receives substantially lower scores, with frequent perceptual mismatches, implausible constructions, and failures that are judged to be far from correct.